

## [MS-ADDM]:

# Active Directory Web Services: Data Model and Common Elements

---

### Intellectual Property Rights Notice for Open Specifications Documentation

- **Technical Documentation.** Microsoft publishes Open Specifications documentation (“this documentation”) for protocols, file formats, data portability, computer languages, and standards support. Additionally, overview documents cover inter-protocol relationships and interactions.
- **Copyrights.** This documentation is covered by Microsoft copyrights. Regardless of any other terms that are contained in the terms of use for the Microsoft website that hosts this documentation, you can make copies of it in order to develop implementations of the technologies that are described in this documentation and can distribute portions of it in your implementations that use these technologies or in your documentation as necessary to properly document the implementation. You can also distribute in your implementation, with or without modification, any schemas, IDLs, or code samples that are included in the documentation. This permission also applies to any documents that are referenced in the Open Specifications documentation.
- **No Trade Secrets.** Microsoft does not claim any trade secret rights in this documentation.
- **Patents.** Microsoft has patents that might cover your implementations of the technologies described in the Open Specifications documentation. Neither this notice nor Microsoft's delivery of this documentation grants any licenses under those patents or any other Microsoft patents. However, a given Open Specifications document might be covered by the Microsoft [Open Specifications Promise](#) or the [Microsoft Community Promise](#). If you would prefer a written license, or if the technologies described in this documentation are not covered by the Open Specifications Promise or Community Promise, as applicable, patent licenses are available by contacting [iplg@microsoft.com](mailto:iplg@microsoft.com).
- **Trademarks.** The names of companies and products contained in this documentation might be covered by trademarks or similar intellectual property rights. This notice does not grant any licenses under those rights. For a list of Microsoft trademarks, visit [www.microsoft.com/trademarks](http://www.microsoft.com/trademarks).
- **Fictitious Names.** The example companies, organizations, products, domain names, email addresses, logos, people, places, and events that are depicted in this documentation are fictitious. No association with any real company, organization, product, domain name, email address, logo, person, place, or event is intended or should be inferred.

**Reservation of Rights.** All other rights are reserved, and this notice does not grant any rights other than as specifically described above, whether by implication, estoppel, or otherwise.

**Tools.** The Open Specifications documentation does not require the use of Microsoft programming tools or programming environments in order for you to develop an implementation. If you have access to Microsoft programming tools and environments, you are free to take advantage of them. Certain Open Specifications documents are intended for use in conjunction with publicly available standards specifications and network programming art and, as such, assume that the reader either is familiar with the aforementioned material or has immediate access to it.

## Revision Summary

| Date       | Revision History | Revision Class | Comments   |
|------------|------------------|----------------|--|
| 12/5/2008  | 0.1              | Major          | Initial Availability   |
| 1/16/2009  | 1.0              | Major          | Updated and revised the technical content.                                   |
| 2/27/2009  | 2.0              | Major          | Updated and revised the technical content.                                   |
| 4/10/2009  | 3.0              | Major          | Updated and revised the technical content.                                   |
| 5/22/2009  | 4.0              | Major          | Updated and revised the technical content.                                   |
| 7/2/2009   | 5.0              | Major          | Updated and revised the technical content.                                   |
| 8/14/2009  | 5.1              | Minor          | Clarified the meaning of the technical content.                              |
| 9/25/2009  | 6.0              | Major          | Updated and revised the technical content.                                   |
| 11/6/2009  | 7.0              | Major          | Updated and revised the technical content.                                   |
| 12/18/2009 | 8.0              | Major          | Updated and revised the technical content.                                   |
| 1/29/2010  | 8.0.1            | Editorial      | Changed language and formatting in the technical content.                    |
| 3/12/2010  | 8.0.2            | Editorial      | Changed language and formatting in the technical content.                    |
| 4/23/2010  | 8.1              | Minor          | Clarified the meaning of the technical content.                              |
| 6/4/2010   | 8.1.1            | Editorial      | Changed language and formatting in the technical content.                    |
| 7/16/2010  | 9.0              | Major          | Updated and revised the technical content.                                   |
| 8/27/2010  | 9.0              | None           | No changes to the meaning, language, or formatting of the technical content. |
| 10/8/2010  | 9.0              | None           | No changes to the meaning, language, or formatting of the technical content. |
| 11/19/2010 | 9.0              | None           | No changes to the meaning, language, or formatting of the technical content. |
| 1/7/2011   | 9.0              | None           | No changes to the meaning, language, or formatting of the technical content. |
| 2/11/2011  | 9.0              | None           | No changes to the meaning, language, or formatting of the technical content. |
| 3/25/2011  | 9.0              | None           | No changes to the meaning, language, or formatting of the technical content. |
| 5/6/2011   | 9.0              | None           | No changes to the meaning, language, or formatting of the technical content. |
| 6/17/2011  | 9.1              | Minor          | Clarified the meaning of the technical content.                              |
| 9/23/2011  | 9.1              | None           | No changes to the meaning, language, or formatting of the technical content. |
| 12/16/2011 | 10.0             | Major          | Updated and revised the technical content.                                   |
| 3/30/2012  | 10.0             | None           | No changes to the meaning, language, or formatting of the technical content. |

| <b>Date</b> | <b>Revision History</b> | <b>Revision Class</b> | <b>Comments</b>  |
|-------------|-------------------------|-----------------------|--|
| 7/12/2012   | 10.0                    | None                  | No changes to the meaning, language, or formatting of the technical content. |
| 10/25/2012  | 10.0                    | None                  | No changes to the meaning, language, or formatting of the technical content. |
| 1/31/2013   | 10.0                    | None                  | No changes to the meaning, language, or formatting of the technical content. |
| 8/8/2013    | 11.0                    | Major                 | Updated and revised the technical content.                                   |
| 11/14/2013  | 11.0                    | None                  | No changes to the meaning, language, or formatting of the technical content. |
| 2/13/2014   | 11.0                    | None                  | No changes to the meaning, language, or formatting of the technical content. |
| 5/15/2014   | 11.0                    | None                  | No changes to the meaning, language, or formatting of the technical content. |
| 6/30/2015   | 12.0                    | Major                 | Significantly changed the technical content.                                 |
| 10/16/2015  | 12.0                    | None                  | No changes to the meaning, language, or formatting of the technical content. |
| 7/14/2016   | 13.0                    | Major                 | Significantly changed the technical content.                                 |

# Table of Contents

|          |  |           |
|----------|--|-----------|
| <b>1</b> | <b>Introduction .....</b>  | <b>5</b>  |
| 1.1      | Glossary .....   | 5         |
| 1.2      | References .....   | 7         |
| 1.2.1    | Normative References .....   | 7         |
| 1.2.2    | Informative References .....   | 8         |
| 1.3      | Overview .....   | 9         |
| 1.4      | Relationship to Protocols and Other Structures .....                   | 9         |
| 1.5      | Applicability Statement .....  | 9         |
| 1.6      | Versioning and Localization .....                                      | 9         |
| 1.7      | Vendor-Extensible Fields .....   | 9         |
| <b>2</b> | <b>Data Model and Common Elements.....</b>                             | <b>10</b> |
| 2.1      | Endpoints.....   | 10        |
| 2.2      | XML Namespaces and URIs .....  | 11        |
| 2.3      | XML Data Model .....   | 12        |
| 2.3.1    | Object Naming .....  | 12        |
| 2.3.2    | XML View of Directory Objects.....                                     | 13        |
| 2.3.3    | Synthetic Attributes .....   | 14        |
| 2.3.3.1  | ad:objectReferenceProperty .....                                       | 15        |
| 2.3.3.2  | ad:container-hierarchy-parent .....                                    | 15        |
| 2.3.3.3  | ad:distinguishedName .....   | 15        |
| 2.3.3.4  | ad:relativeDistinguishedName .....                                     | 16        |
| 2.3.4    | Syntax Mapping.....  | 16        |
| 2.4      | XPath 1.0-Derived Selection Language.....                              | 17        |
| 2.5      | Common SOAP Headers .....  | 19        |
| 2.5.1    | ad:instance Header .....   | 19        |
| 2.5.2    | ad:objectReferenceProperty Header .....                                | 20        |
| 2.6      | Common SOAP Fault Detail .....   | 21        |
| 2.7      | Range Retrieval .....  | 24        |
| 2.7.1    | XML View of Multivalued Attribute with Range Option .....              | 24        |
| 2.7.2    | Range Specifiers for Requests .....                                    | 26        |
| 2.7.2.1  | WS-Transfer Range Retrieval Extensions.....                            | 27        |
| 2.7.2.2  | WS-Enumeration Range Retrieval Extensions.....                         | 27        |
| <b>3</b> | <b>Structure Examples .....</b>  | <b>29</b> |
| 3.1      | WS-Transfer 'Get' Example.....   | 29        |
| 3.2      | WS-Transfer Identity Management Extension 'ModifyRequest' Example..... | 31        |
| 3.3      | WS-Enumeration 'Pull' Example .....                                    | 33        |
| <b>4</b> | <b>Security.....</b>   | <b>35</b> |
| 4.1      | Security Considerations for Implementers .....                         | 35        |
| 4.2      | Index of Security Fields .....   | 35        |
| <b>5</b> | <b>Appendix A: Product Behavior .....</b>                              | <b>36</b> |
| <b>6</b> | <b>Change Tracking.....</b>  | <b>46</b> |
| <b>7</b> | <b>Index.....</b>  | <b>48</b> |

# 1 Introduction

Active Directory Web Services: Data Model and Common Elements contains an XML data model and other protocol components (such as the definition of an XPath 1.0-derived selection language) that are used in various protocols that belong to the set of Active Directory Web Services protocols. The documentation for individual protocols contains references to this document, as needed.

Sections 1.7 and 2 of this specification are normative. All other sections and examples in this specification are informative.

## 1.1 Glossary

This document uses the following terms:

**Active Directory:** A general-purpose network **directory service**. **Active Directory** also refers to the Windows implementation of a **directory service**. **Active Directory** stores information about a variety of objects in the network. Importantly, user accounts, computer accounts, groups, and all related credential information used by the Windows implementation of Kerberos are stored in **Active Directory**. **Active Directory** is either deployed as **Active Directory Domain Services (AD DS)** or **Active Directory Lightweight Directory Services (AD LDS)**. [\[MS-ADTS\]](#) describes both forms. For more information, see [\[MS-AUTHSOD\]](#) section 1.1.1.5.2, **Lightweight Directory Access Protocol (LDAP)** versions 2 and 3, Kerberos, and DNS.

**Active Directory Domain Services (AD DS):** A **directory service (DS)** implemented by a domain controller (DC). The **DS** provides a data store for objects that is distributed across multiple DCs. The DCs interoperate as peers to ensure that a local change to an object replicates correctly across DCs. For more information, see [\[MS-AUTHSOD\]](#) section 1.1.1.5.2 and [\[MS-ADTS\]](#). For information about product versions, see [\[MS-ADTS\]](#) section 1. See also **Active Directory**.

**Active Directory Lightweight Directory Services (AD LDS):** A **directory service (DS)** implemented by a domain controller (DC). The most significant difference between **AD LDS** and **Active Directory Domain Services (AD DS)** is that **AD LDS** does not host domain naming contexts (domain NCs). A server can host multiple **AD LDS** DCs. Each DC is an independent **AD LDS** instance, with its own independent state. **AD LDS** can be run as an operating system **DS** or as a directory service provided by a standalone application (Active Directory Application Mode (ADAM)). For more information, see [\[MS-ADTS\]](#). See also **Active Directory**.

**attribute syntax:** Specifies the format and range of permissible values of an attribute. The syntax of an attribute is defined by several attributes on the attributeSchema object, as specified in [\[MS-ADTS\]](#) section 3.1.1.2. Attribute syntaxes supported by **Active Directory** include Boolean, Enumeration, Integer, LargeInteger, String(UTC-Time), Object(DS-DN), and String(Unicode).

**directory object:** A **Lightweight Directory Access Protocol (LDAP)** object, as specified in [\[RFC2251\]](#), that is a specialization of an object.

**directory service (DS):** A service that stores and organizes information about a computer network's users and network shares, and that allows network administrators to manage users' access to the shares. See also **Active Directory**.

**directory tree:** An **LDAP directory service** is organized into a hierarchical tree structure in which each **directory object** has exactly one parent **directory object** (except for one object that serves as the root of the tree) and zero or more child **directory objects**.

**distinguished name (DN):** A name that uniquely identifies an object by using the **relative distinguished name (RDN)** for the object, and the names of container objects and domains that contain the object. The distinguished name (DN) identifies the object and its location in a tree.

**endpoint:** In the context of a web service, a network target to which a **SOAP** message can be addressed. See [\[WSADDR\]](#).

**global catalog (GC):** A unified partial view of multiple **naming contexts (NCs)** in a distributed partitioned directory. The **Active Directory** directory service **GC** is implemented by GC servers. The definition of **global catalog** is specified in [MS-ADTS] section 3.1.1.1.8.

**globally unique identifier (GUID):** A term used interchangeably with **universally unique identifier (UUID)** in Microsoft protocol technical documents (TDs). Interchanging the usage of these terms does not imply or require a specific algorithm or mechanism to generate the value. Specifically, the use of this term does not imply or require that the algorithms described in [\[RFC4122\]](#) or [\[C706\]](#) must be used for generating the **GUID**. See also **universally unique identifier (UUID)**.

**Lightweight Directory Access Protocol (LDAP):** The primary access protocol for **Active Directory**. Lightweight Directory Access Protocol (LDAP) is an industry-standard protocol, established by the Internet Engineering Task Force (IETF), which allows users to query and update information in a **directory service (DS)**, as described in [MS-ADTS]. The Lightweight Directory Access Protocol can be either version 2 [\[RFC1777\]](#) or version 3 [\[RFC3377\]](#).

**naming context (NC):** An **NC** is a set of objects organized as a tree. It is referenced by a DSName. The **DN** of the DSName is the distinguishedName attribute of the tree root. The **GUID** of the DSName is the objectGUID attribute of the tree root. The security identifier (SID) of the DSName, if present, is the objectSid attribute of the tree root; for **Active Directory Domain Services (AD DS)**, the SID is present if and only if the **NC** is a domain naming context (domain NC). **Active Directory** supports organizing several **NCs** into a tree structure.

**object reference property:** In Active Directory Web Services, this is the property that uniquely identifies a **directory object**. It can be expressed as either a **GUID** or as a **distinguished name**.

**object reference syntax:** An **attribute syntax** that supports object references. The five object reference syntaxes are specified in [MS-ADTS] section 3.1.1.1.6, and the referential integrity constraints around attributes with these syntaxes are specified in [MS-ADTS] section 3.1.1.2.2.3.

**relative distinguished name (RDN):** In the **Active Directory** directory service, the unique name of a child element relative to its parent in Active Directory. The RDN of a child element combined with the fully qualified domain name (FQDN) (2) of the parent forms the FQDN of the child.

**SOAP:** A lightweight protocol for exchanging structured information in a decentralized, distributed environment. **SOAP** uses XML technologies to define an extensible messaging framework, which provides a message construct that can be exchanged over a variety of underlying protocols. The framework has been designed to be independent of any particular programming model and other implementation-specific semantics. SOAP 1.2 supersedes SOAP 1.1. See [\[SOAP1.2-1/2003\]](#).

**SOAP fault:** A container for error and status information within a **SOAP message**. See [\[SOAP1.2-1/2007\]](#) section 5.4 for more information.

**SOAP header:** A mechanism for implementing extensions to a **SOAP message** in a decentralized manner without prior agreement between the communicating parties. See [SOAP1.2-1/2007] section 5.2 for more information.

**SOAP message:** An XML document consisting of a mandatory SOAP envelope, an optional **SOAP header**, and a mandatory SOAP body. See [SOAP1.2-1/2007] section 5 for more information.

**synthetic attribute:** In Active Directory Web Services, an attribute that is part of the XML view of a **directory object** but which is not part of the **directory object** as stored in the **directory service**.

**Transport Layer Security (TLS):** A security protocol that supports confidentiality and integrity of messages in client and server applications communicating over open networks. **TLS** supports server and, optionally, client authentication by using X.509 certificates (as specified in [\[X509\]](#)). **TLS** is standardized in the IETF TLS working group. See [\[RFC4346\]](#).

**Uniform Resource Identifier (URI):** A string that identifies a resource. The URI is an addressing mechanism defined in Internet Engineering Task Force (IETF) Uniform Resource Identifier (URI): Generic Syntax [\[RFC3986\]](#).

**universally unique identifier (UUID):** A 128-bit value. UUIDs can be used for multiple purposes, from tagging objects with an extremely short lifetime, to reliably identifying very persistent objects in cross-process communication such as client and server interfaces, manager entry-point vectors, and RPC objects. UUIDs are highly likely to be unique. UUIDs are also known as **globally unique identifiers (GUIDs)** and these terms are used interchangeably in the Microsoft protocol technical documents (TDs). Interchanging the usage of these terms does not imply or require a specific algorithm or mechanism to generate the UUID. Specifically, the use of this term does not imply or require that the algorithms described in [\[RFC4122\]](#) or [\[C706\]](#) must be used for generating the UUID.

**MAY, SHOULD, MUST, SHOULD NOT, MUST NOT:** These terms (in all caps) are used as defined in [\[RFC2119\]](#). All statements of optional behavior use either MAY, SHOULD, or SHOULD NOT.

## 1.2 References

Links to a document in the Microsoft Open Specifications library point to the correct section in the most recently published version of the referenced document. However, because individual documents in the library are not updated at the same time, the section numbers in the documents may not match. You can confirm the correct section numbering by checking the [Errata](#).

### 1.2.1 Normative References

We conduct frequent surveys of the normative references to assure their continued availability. If you have any issue with finding a normative reference, please contact [dochelp@microsoft.com](mailto:dochelp@microsoft.com). We will assist you in finding the relevant information.

[MS-ADCAP] Microsoft Corporation, "[Active Directory Web Services: Custom Action Protocol](#)".

[MS-ADTS] Microsoft Corporation, "[Active Directory Technical Specification](#)".

[MS-DTYP] Microsoft Corporation, "[Windows Data Types](#)".

[MS-ERREF] Microsoft Corporation, "[Windows Error Codes](#)".

[MS-NMFTB] Microsoft Corporation, "[.NET Message Framing TCP Binding Protocol](#)".

[MS-NNS] Microsoft Corporation, "[.NET NegotiateStream Protocol](#)".

[MS-WSDS] Microsoft Corporation, "[WS-Enumeration: Directory Services Protocol Extensions](#)".

[MS-WSPELD] Microsoft Corporation, "[WS-Transfer and WS-Enumeration Protocol Extension for Lightweight Directory Access Protocol v3 Controls](#)".

[MS-WSTIM] Microsoft Corporation, "[WS-Transfer: Identity Management Operations for Directory Access Extensions](#)".

- [RFC2119] Bradner, S., "Key words for use in RFCs to Indicate Requirement Levels", BCP 14, RFC 2119, March 1997, <http://www.rfc-editor.org/rfc/rfc2119.txt>
- [RFC2251] Wahl, M., Howes, T., and Kille, S., "Lightweight Directory Access Protocol (v3)", RFC 2251, December 1997, <http://www.ietf.org/rfc/rfc2251.txt>
- [RFC2252] Wahl, M., Coulbeck, A., Howes, T., and Kille, S., "Lightweight Directory Access Protocol (v3): Attribute Syntax Definitions", RFC 2252, December 1997, <http://www.ietf.org/rfc/rfc2252.txt>
- [RFC4122] Leach, P., Mealling, M., and Salz, R., "A Universally Unique Identifier (UUID) URN Namespace", RFC 4122, July 2005, <http://www.ietf.org/rfc/rfc4122.txt>
- [SOAP1.2-1/2003] Gudgin, M., Hadley, M., Mendelsohn, N., et al., "SOAP Version 1.2 Part 1: Messaging Framework", W3C Recommendation, June 2003, <http://www.w3.org/TR/2003/REC-soap12-part1-20030624>
- [WSADDR] Gudgin, M., Hadley, M., and Rogers, T., "Web Services Addressing (WS-Addressing) 1.0", W3C Recommendation, May 2006, <http://www.w3.org/2005/08/addressing>
- [WSASB] Gudgin, M., Hadley, M., and Rogers, T., Eds., "Web Services Addressing 1.0 - SOAP Binding", W3C Recommendation, May 2006, <http://www.w3.org/TR/2006/REC-ws-addr-soap-20060509/>
- [WSENUM] Alexander, J., Box, D., Cabrera, L.F., et al., "Web Services Enumeration (WS-Enumeration)", March 2006, <http://www.w3.org/Submission/2006/SUBM-WS-Enumeration-20060315/>
- [WSMETA] Ballinger, K., Bissett, B., Box, D., et al., "Web Services Metadata Exchange (WS-MetadataExchange)", Version 1.1, August 2006, <http://specs.xmlsoap.org/ws/2004/09/mex/WS-MetadataExchange.pdf>
- [WSSUTP1.1] OASIS Standard, "Web Services Security UsernameToken Profile 1.1", February 2006, <http://www.oasis-open.org/committees/download.php/16782/wss-v1.1-spec-os-UsernameTokenProfile.pdf>
- [WSS] OASIS, "Web Services Security: SOAP Message Security 1.1 (WS-Security 2004)", February 2006, <http://www.oasis-open.org/committees/download.php/16790/wss-v1.1-spec-os-SOAPMessageSecurity.pdf>
- [WXFR] Alexander, J., Box, D., Cabrera, L.F., et al., "Web Services Transfer (WS-Transfer)", September 2006, <http://www.w3.org/Submission/2006/SUBM-WS-Transfer-20060927/>
- [XML10] World Wide Web Consortium, "Extensible Markup Language (XML) 1.0 (Third Edition)", February 2004, <http://www.w3.org/TR/2004/REC-xml-20040204/>
- [XMLNS-2ED] World Wide Web Consortium, "Namespaces in XML 1.0 (Second Edition)", August 2006, <http://www.w3.org/TR/2006/REC-xml-names-20060816/>
- [XMLSCHEMA1] Thompson, H., Beech, D., Maloney, M., and Mendelsohn, N., Eds., "XML Schema Part 1: Structures", W3C Recommendation, May 2001, <http://www.w3.org/TR/2001/REC-xmlschema-1-20010502/>
- [XPATH] Clark, J., and DeRose, S., "XML Path Language (XPath), Version 1.0", W3C Recommendation, November 1999, <http://www.w3.org/TR/xpath/>

## 1.2.2 Informative References

None.



### 1.3 Overview

Active Directory Web Services (ADWS) permits access to **Active Directory** [\[MS-ADTS\]](#) via the use of common **SOAP**-based Web Service protocols such as WS-Transfer [\[WXFR\]](#) and WS-Enumeration [\[WSENUM\]](#). These protocols operate on an XML [\[XML10\]](#) view of the data stored in the Active Directory **directory service**. The same XML view is shared by all the protocols in the ADWS protocol set. This document specifies that shared XML view.

Additionally, the protocols share a selection language, derived from XPath 1.0 [\[XPath\]](#), that is used to specify which aspect of the XML view is operated on. That shared selection language is also specified in this document.

This document also specifies other shared cross-protocol aspects of ADWS, such as the **endpoints** used and shared **SOAP headers** and **SOAP fault** details [\[SOAP1.2-1/2003\]](#).

Finally, this document provides a mechanism for performing a range retrieval operation through some Web Service protocols in the ADWS protocol set. Range retrieval, as specified in section [2.7](#), allows for returning only a portion of the complete set of values of a multivalued attribute, or specifying that only a certain portion of the set of values of a multivalued attribute be retrieved. For the same purpose, it defines an extension to the shared XML view of data that incorporates this range retrieval extension.

Note that this document does not define a protocol. Rather, it serves as a common repository for information used across the entire ADWS protocol set. For operations such as range retrieval, it provides common extensions to [\[WXFR\]](#) and [\[WSENUM\]](#), which are used by certain protocols within the ADWS protocol set. [<1>](#)

### 1.4 Relationship to Protocols and Other Structures

The information in this document is used by protocols in the set of Active Directory Web Services protocols. The ADWS protocol documentation set comprises this document and the following documents: [\[MS-WSDS\]](#), [\[MS-WPELD\]](#), [\[MS-WSTIM\]](#), and [\[MS-ADCAP\]](#).

### 1.5 Applicability Statement

The XML data model and XPath 1.0-derived selection language is suitable for use when the implementer desires to retrieve and manipulate data stored in a directory service via an XML-based model. It can be particularly useful with protocols, such as many SOAP-based Web Service protocols, that are intended to operate over data that is represented as an XML document.

There is an implicit assumption in the design of the data model that the directory service exposes semantics similar to that of a **Lightweight Directory Access Protocol (LDAP)** version 3 directory service [\[RFC2251\]](#). For example, it assumes that objects in the directory consist of attribute-value pairs in which each attribute can have one or more values. It also assumes that the **directory objects** can be arranged in a single hierarchical tree structure. The XML data model described in this document might not be suitable for use with directories that do not expose such semantics.

### 1.6 Versioning and Localization

None.

### 1.7 Vendor-Extensible Fields

None.

## 2 Data Model and Common Elements

This section discusses the shared protocol elements that are used by various protocols in the set of Active Directory Web Service protocols. In this document, the convention from [\[MS-ADTS\]](#) section 3.1.1.1.2 is adopted such that, if variable *O* refers to a directory object and *a* is the LDAP display name of an attribute, then *O!a* denotes the value or values of attribute *a* on object *O*.

### 2.1 Endpoints

This section specifies the Web Service endpoints that are used by protocols in the ADWS protocol set. ADWS exposes protocols that can be accessed via an endpoint. Each endpoint can be uniquely identified by a **Uniform Resource Identifier (URI)**. The URIs for the ADWS protocols are shown in the following table. All endpoints use the "net.tcp" URI binding type. For semantics of this binding type, see [\[MS-NMFTB\]](#).

| Endpoint URI  | Protocol exposed by endpoint                         | Authentication mechanism (see below) |
|---|--|--------------------------------------|
| net.tcp://localhost:9389/ActiveDirectoryWebServices/Windows/Resource            | <a href="#">[WXFR]</a> , <a href="#">[MS-WSTIM]</a>  | Windows Integrated                   |
| net.tcp://localhost:9389/ActiveDirectoryWebServices/Windows/ResourceFactory     | [MS-WSTIM]   | Windows Integrated                   |
| net.tcp://localhost:9389/ActiveDirectoryWebServices/Windows/Enumeration         | <a href="#">[WSENUM]</a> , <a href="#">[MS-WSDS]</a> | Windows Integrated                   |
| net.tcp://localhost:9389/ActiveDirectoryWebServices/Windows/AccountManagement   | <a href="#">[MS-ADCAP]</a>                           | Windows Integrated                   |
| net.tcp://localhost:9389/ActiveDirectoryWebServices/Windows/TopologyManagement  | [MS-ADCAP]   | Windows Integrated                   |
| net.tcp://localhost:9389/ActiveDirectoryWebServices/UserName/Resource           | [WXFR], [MS-WSTIM]                                   | Username/password                    |
| net.tcp://localhost:9389/ActiveDirectoryWebServices/UserName/ResourceFactory    | [MS-WSTIM]   | Username/password                    |
| net.tcp://localhost:9389/ActiveDirectoryWebServices/UserName/Enumeration        | [WSENUM], [MS-WSDS]                                  | Username/password                    |
| net.tcp://localhost:9389/ActiveDirectoryWebServices/UserName/AccountManagement  | [MS-ADCAP]   | Username/password                    |
| net.tcp://localhost:9389/ActiveDirectoryWebServices/UserName/TopologyManagement | [MS-ADCAP]   | Username/password                    |
| net.tcp://localhost:9389/ActiveDirectoryWebServices/mex                         | <a href="#">[WSMETA]</a>                             | None                                 |

In the preceding table, "localhost" represents the DNS hostname of the server hosting the endpoint. All endpoints listen on TCP port 9389.

The ADWS protocol set uses two types of authentication. Each endpoint (except for the "mex" endpoint) supports one or the other. The forms of authentication are:

- Windows Integrated: These endpoints use **Transport Layer Security (TLS)** to protect the TCP transport. Integrated Windows authentication using the .Net Negotiate Stream protocol [\[MS-NNS\]](#) is used to authenticate the client to the server at the transport layer and to negotiate the session key used for TLS.
- Username/password: These endpoints use TLS to protect the TCP transport. TLS is used to negotiate a session key to protect the TCP transport. The client authenticates (at the message layer) to the server by providing a plaintext username and password, as documented in WS-Security [\[WSS\]](#) and the WS-Security UserNameToken profile [\[WSSUTP1.1\]](#).

The "mex" endpoint neither requires nor supports authentication.

## 2.2 XML Namespaces and URIs

The following XML namespaces are defined and referenced by the ADWS protocol set, using the XML namespace mechanisms defined in [\[XMLNS-2ED\]](#). A brief informative summary of each namespace is included in the table below. The detailed usage and semantics of each namespace are explained in the portion of the document that makes use of it. Some namespaces are used by multiple ADWS protocols or protocol components. Although this specification associates a specific XML namespace prefix for each XML namespace that is used, the choice of any particular XML namespace prefix is implementation-specific and is not significant for interoperability.

| Prefix  | Namespace URI   | Informative summary  |
|---------|---|--|
| ad:     | <a href="http://schemas.microsoft.com/2008/1/ActiveDirectory">http://schemas.microsoft.com/2008/1/ActiveDirectory</a>   | The core ADWS namespace. Most ADWS protocol elements are located in this namespace.  |
| addata: | <a href="http://schemas.microsoft.com/2008/1/ActiveDirectory/Data">http://schemas.microsoft.com/2008/1/ActiveDirectory/Data</a>                               | The namespace for ADWS protocol elements that correspond to the LDAP display names of Active Directory classes and attributes. |
| adlq:   | <a href="http://schemas.microsoft.com/2008/1/ActiveDirectory/Dialect/LdapQuery">http://schemas.microsoft.com/2008/1/ActiveDirectory/Dialect/LdapQuery</a>     | The LdapQuery language, defined in <a href="#">[MS-WSDS]</a> .   |
| da:     | <a href="http://schemas.microsoft.com/2006/11/IdentityManagement/DirectoryAccess">http://schemas.microsoft.com/2006/11/IdentityManagement/DirectoryAccess</a> | The namespace for the <a href="#">[MS-WSTIM]</a> protocol.   |
| ca:     | <a href="http://schemas.microsoft.com/2008/1/ActiveDirectory/CustomActions">http://schemas.microsoft.com/2008/1/ActiveDirectory/CustomActions</a>             | The namespace for the <a href="#">[MS-ADCAP]</a> protocol.   |

Additionally, ADWS defines the following three URIs which do not correspond to XML namespaces.

| URI   | Informative summary   |
|---|---|
| <a href="http://schemas.microsoft.com/2008/1/ActiveDirectory/Data/fault">http://schemas.microsoft.com/2008/1/ActiveDirectory/Data/fault</a> | The fault action URI <a href="#">[SOAP1.2-1/2003]</a> for ADWS-defined SOAP faults, excluding those defined by <a href="#">[MS-WSTIM]</a> (used for the "[Action]" property of <a href="#">[WSASB]</a> ). |

| URI   | Informative summary   |
|---|---|
| http://schemas.microsoft.com/2006/11/IdentityManagement/DirectoryAccess/fault | The fault action URI [SOAP1.2-1/2003] for SOAP faults defined by [MS-WSTIM] protocol (used for the "[Action]" property of [WSASB]). |
| http://schemas.microsoft.com/2008/1/ActiveDirectory/Dialect/XPath-Level-1     | The name of the XPath 1.0-derived selection language defined in section <a href="#">2.4</a> .                                       |

Although not defined by ADWS, the following XML namespaces are referenced elsewhere in this document.

| Prefix   | Namespace URI                                     | Reference                    |
|----------|---|------------------------------|
| soapenv: | http://www.w3.org/2003/05/soap-envelope           | [SOAP1.2-1/2003]             |
| wsa:     | http://www.w3.org/2005/08/addressing              | <a href="#">[WSADDR]</a>     |
| wsen:    | http://schemas.xmlsoap.org/ws/2004/09/enumeration | <a href="#">[WSENUM]</a>     |
| wxf:     | http://schemas.xmlsoap.org/ws/2004/09/transfer    | <a href="#">[WXFR]</a>       |
| xsd:     | http://www.w3.org/2001/XMLSchema                  | <a href="#">[XMLSCHEMA1]</a> |
| xsi:     | http://www.w3.org/2001/XMLSchema-instance         | [XMLSCHEMA1]                 |

## 2.3 XML Data Model

This section documents how directory objects, each of which is a collection of LDAP attributes (with one or more values stored in each attribute) [\[MS-ADTS\]](#), are represented in XML. This XML view of directory objects is shared by the protocols in the ADWS protocol set.

### 2.3.1 Object Naming

In the ADWS data model, directory objects are identified by their **object reference property**. The object reference property can be either a **GUID** or the object's LDAP **distinguished name**.

**Note** Unless otherwise specified, GUID values are represented using the following forms in this document:

- In the descriptive text, GUID values are represented by Curly Braced String form defined in [\[MS-DTYP\]](#) section 2.3.4.3.
- In the XML examples and definitions, GUID values are represented by the string form of a **universally unique identifier (UUID)**, as specified in [\[RFC4122\]](#) section 3.

For a directory object *O*, to specify the object reference property of *O* as a GUID, the value of the GUID MUST equal the value of *O*!objectGUID. Alternatively, the object reference property of *O* can be specified as *O*'s LDAP distinguished name (*O*!distinguishedName) instead.

The object reference property (in either GUID or distinguished name form) in a **SOAP message** request identifies the directory object that should be operated on by the operation specified in that message (see section [2.5.2](#)). The object reference property in a SOAP response message indicates the identity of a directory object that is returned in that response message.

The object reference property value in the GUID form of {11111111-1111-1111-1111-111111111111} exclusively refers to the LDAP rootDSE [\[RFC2251\]](#).

The following SOAP message requests use the object reference property as either the GUID or the distinguished name:

- In adlq:BaseObject in LdapQuery [\[MS-WSDS\]](#)
- In the ad:objectReferenceProperty SOAP header for a WS-Transfer [\[WXFR\]](#) Get, Put, or Delete operation (section 2.5.2)
- In the ad:objectReferenceProperty SOAP header for a [\[MS-WSTIM\]](#) BaseObjectSearchRequest or ModifyRequest operation (section 2.5.2)
- As the value of a directory attribute which has an **object reference syntax** (see [\[MS-ADTS\]](#), section 3.1.1.1.6)
- In the ad:container-hierarchy-parent (see section [2.3.3.2](#)) **synthetic attribute** for a WS-Transfer Put or Create operation
- In the ad:container-hierarchy-parent (see section [2.3.3.2](#)) **synthetic attribute** for a [\[MS-WSTIM\]](#) ModifyRequest or AddRequest operation

The object reference property in a protocol response can be in either GUID or distinguished name form.

## 2.3.2 XML View of Directory Objects

In the XML view of the directory objects presented by ADWS, the XML elements are named for the LDAP classes and attributes used in the directory object. Additionally, XML elements are used to represent the ADWS synthetic attributes, described in the next section.

Begin by defining how a single LDAP attribute and its value(s) are represented in the XML view. Let  $A$  be the LDAP display name of an attribute that has values  $V1(A) \dots Vn(A)$ . Let  $S1(A) \dots Sn(A)$  be the XML representation of values  $V1 \dots Vn$  as described in section [2.3.4](#). Let  $LDAPSYN(A)$  be the LDAP **attribute syntax** of attribute  $A$ , and let  $XMLSYN(A)$  be the corresponding XML syntax, as described in section [2.3.4](#). The XML representation for this attribute is the following.

```
<addata:A LdapSyntax="LDAPSYN(A)">
  <ad:value xsi:type="XMLSYN(A)">
    S1(A)
  </ad:value>
  ...
  ...
  <ad:value xsi:type="XMLSYN(A)">
    Sn(A)
  </ad:value>
</addata:A>
```

Now extend this view to an entire directory object. Let  $O$  be an object in the directory. Let  $C$  be the LDAP display name of the most specific structural object class ([\[MS-ADTS\]](#) section 3.1.1.1.4) of  $O$ . Let  $A1 \dots An$  be the LDAP display names of all the LDAP attributes of  $O$ . Then, the representation of  $O$  as the XML view in the data model is the following.

```
<addata:C>
  <addata:A1 LdapSyntax="LDAPSYN(A1)">
    <ad:value xsi:type="XMLSYN(A1)">
      S1(A1)
    </ad:value>
```

```

...
...
<ad:value xsi:type="XMLSYN(A1) ">
    Sn(A1)
</ad:value>
</addata:A1>
...
...
<addata:An LdapSyntax="LDAPSYN(An) ">
    <ad:value xsi:type="XMLSYN(An) ">
        S1(An)
    </ad:value>
    ...
    ...
    <ad:value xsi:type="XMLSYN(An) ">
        Sn(An)
    </ad:value>
</addata:An>
</addata:C>

```

Not shown in the above example are the ADWS synthetic attributes. These are shown in the next section.

The root element is named for the LDAP display name of the most specific structural object class of *O*, and is in the `http://schemas.microsoft.com/2008/1/ActiveDirectory/Data` XML namespace. When representing an LDAP display name where the most specific structural object class of *O* is not available, "top" is used for the name of the root element. Additionally, when representing the LDAP rootDse, "top" is used for the name of the root element.

Each child element represents a single LDAP attribute stored on that object and is named for that attribute's LDAP display name (and is also located in the `http://schemas.microsoft.com/2008/1/ActiveDirectory/Data` XML namespace). This element can have an XML attribute named `LdapSyntax` that represents the LDAP attribute syntax of that LDAP attribute. Each child element under an attribute represents a single value stored in that attribute. The actual value is represented as a text node under this `ad:value` element.

The `LdapSyntax` XML attribute is present for each LDAP attribute specified in a SOAP response, including the above XML representation of a directory object.

The `LdapSyntax` XML attribute is optional in a SOAP request.

Multiple directory objects are represented as sibling XML elements, regardless of the hierarchical relationship between the objects in the LDAP **directory tree**.

### 2.3.3 Synthetic Attributes

In addition to containing the LDAP attributes of a directory object, the XML view of that object contains up to four additional attributes that are not part of that object's representation stored in the directory service (that is, the four attributes are constructed by the server implementing the ADWS protocol set). These are referred to as the synthetic attributes of ADWS. They can be distinguished from LDAP attributes because the elements that represent the synthetic attributes have names that are in the `http://schemas.microsoft.com/2008/1/ActiveDirectory` XML namespace rather than in the `http://schemas.microsoft.com/2008/1/ActiveDirectory/Data` XML namespace that is used for LDAP attributes and classes. Additionally, the `LdapSyntax` XML attribute is never included in the XML representation of a synthetic attribute.

The four synthetic attributes are specified in the following subsections.

### 2.3.3.1 ad:objectReferenceProperty

The synthetic attribute `ad:objectReferenceProperty` contains the object reference property of the directory object, as described in section [2.3.1](#). Values of this attribute have `xsi:type` equal to `"xsd:string"`.

This attribute is read only.

This attribute is optional. [<2>](#)

The following is an example of the `ad:objectReferenceProperty` synthetic attribute as it would be found in the XML view of a directory object. In this example, the object reference property is in the GUID form.

```
<ad:objectReferenceProperty>
  <ad:value xsi:type="xsd:string">
    e4f8a504-d7df-4b63-a636-5642d3bf1cf6
  </ad:value>
</ad:objectReferenceProperty>
```

### 2.3.3.2 ad:container-hierarchy-parent

The synthetic attribute `ad:container-hierarchy-parent` contains the object reference property (as described in section [2.3.1](#)) of the directory object that is the object's parent in the directory tree. If the directory object has no parent (that is, if it is the root of its **naming context**), this attribute is omitted from the object's XML view. [<3>](#) Values of this attribute have `xsi:type` equal to `"xsd:string"`.

This attribute can be modified. When this attribute is modified, the object's location in the directory is made consistent with the value of this attribute.

The following is an example of the `ad:container-hierarchy-parent` synthetic attribute as it would be found in the XML view of a directory object. In this example, the object reference property is in the GUID form.

```
<ad:container-hierarchy-parent>
  <ad:value xsi:type="xsd:string">
    d8f7a25a-26f5-4463-bbe3-aa01e4002afd
  </ad:value>
</ad:container-hierarchy-parent>
```

### 2.3.3.3 ad:distinguishedName

The synthetic attribute `ad:distinguishedName` contains the LDAP distinguished name of the directory object; that is, the value of `O!distinguishedName` where `O` is the directory object being represented as a XML view. Values of this attribute have `xsi:type` equal to `"xsd:string"`.

This attribute is read only.

The following is an example of the `ad:distinguishedName` synthetic attribute as it would be found in the XML view of a directory object.

```
<ad:distinguishedName>
  <ad:value xsi:type="xsd:string">CN=Test,DC=fabrikam,DC=com</ad:value>
</ad:distinguishedName>
```

### 2.3.3.4 ad:relativeDistinguishedName

The synthetic attribute `ad:relativeDistinguishedName` contains the **relative distinguished name** of the directory object. Values of this attribute have `xsi:type` equal to `"xsd:string"`.

This attribute can be modified. When this attribute is modified, the object's relative distinguished name is made consistent with the value of this attribute.

The following is an example of the `ad:relativeDistinguishedName` synthetic attribute as it would be found in the XML view of a directory object.

```
<ad:relativeDistinguishedName>
  <ad:value xsi:type="xsd:string">CN=Test</ad:value>
</ad:relativeDistinguishedName>
```

### 2.3.4 Syntax Mapping

As mentioned in section [2.3.2](#), the content of the `<ad:value>` element is the value of the directory attribute (or synthetic attribute) represented as an XML value. For LDAP directory attributes, the choice of the XML syntax for this value (and thus, the corresponding textual representation of that XML value) is dependent on the attribute syntax of the LDAP directory attribute. This mapping is specified in the following table. *LDAPSYN* and *XMLSYN* refer to the variables of the same names used in section 2.3.2. The attribute syntaxes are as specified in [\[MS-ADTS\]](#) section 3.1.1.2.2.2.

| LDAP attribute syntax        | LDAPSYN              | XML syntax (XMLSYN) |
|------------------------------|----------------------|---------------------|
| Boolean                      | Boolean              | xsd:string          |
| Enumeration                  | Enumeration          | xsd:string          |
| Integer                      | Integer              | xsd:string          |
| LargeInteger                 | LargeInteger         | xsd:string          |
| Object(Access-Point)         | AccessPoint          | xsd:string          |
| Object(DN-String)            | DNString             | xsd:string          |
| Object(OR-Name)              | ORName               | xsd:string          |
| Object(DN-Binary)            | DNBinary             | xsd:string          |
| Object(DS-DN)                | DSDNString           | xsd:string          |
| Object(Presentation-Address) | PresentationAddress  | xsd:string          |
| Object(Replica-Link)         | ReplicaLink          | xsd:base64Binary    |
| String(Case)                 | CaseString           | xsd:string          |
| String(IA5)                  | IA5String            | xsd:string          |
| String(NT-Sec-Desc)          | NTSecurityDescriptor | xsd:base64Binary    |
| String(Numeric)              | NumericString        | xsd:string          |
| String(Object-Identifier)    | ObjectIdentifier     | xsd:string          |
| String(Octet)                | OctetString          | xsd:base64Binary    |
| String(Printable)            | PrintableString      | xsd:string          |



| LDAP attribute syntax    | LDAPSYN               | XML syntax (XMSYN) |
|--------------------------|-----------------------|--------------------|
| String(Sid)              | SidString             | xsd:base64Binary   |
| String(Teletex)          | TeletexString         | xsd:string         |
| String(Unicode)          | UnicodeString         | xsd:string         |
| String(UTC-Time)         | UTCTimeString         | xsd:string         |
| String(Generalized-Time) | GeneralizedTimeString | xsd:string         |

The LDAP directory attributes located on the LDAP rootDse do not have attribute syntaxes defined for them. Mappings between an implementation's **rootDse** attributes and XML syntaxes is implementation specific. [<4>](#)

For the synthetic attributes, the choice of XML syntax is as specified in the following table.

| Synthetic attribute                           | XML syntax (XMSYN) |
|---|--------------------|
| <a href="#">ad:objectReferenceProperty</a>    | xsd:string         |
| <a href="#">ad:container-hierarchy-parent</a> | xsd:string         |
| <a href="#">ad:distinguishedName</a>          | xsd:string         |
| <a href="#">ad:relativeDistinguishedName</a>  | xsd:string         |

## 2.4 XPath 1.0-Derived Selection Language

Some Web Service protocols in the ADWS protocol set require the use of a selection language to specify which portion of the directory object to operate on. In other words, the selection language permits the requestor to specify that only certain attributes are to be retrieved from the directory object (rather than every attribute) or to specify that a particular attribute or attribute value is to be added, replaced, or removed from a directory object.

The ADWS protocol set uses a selection language that is derived from XPath 1.0 [\[XPATH\]](#) for this purpose. This selection language is applied to the XML view (described in section [2.3.2](#)) of the directory object. A compliant implementation need only implement the subset of the language described in this section. This derived language is identified by the following URI:

<http://schemas.microsoft.com/2008/1/ActiveDirectory/Dialect/XPath-Level-1>

For simplicity, this language will be referred to as "XPathSelection" in the remainder of this section.

The grammar for XPathSelection is shown below in ABNF notation.

XpathSelection = (root elements)

root = "/"

elements = (element [additional-element] [selection\_predicate])

additional-element = ("/" element)

element = *QName* (*qualified name*) as defined in grammar rule [7] of [\[XMLNS-2ED\]](#).

selection\_predicate = ("[" value\_element "=" value "]")

value\_element = see below

value = *dstring* as defined in [RFC2252](#) surrounded by quotation marks

The value\_element is the string literal "value" qualified with an XML namespace prefix that corresponds to the XML namespace URI "http://schemas.microsoft.com/2008/1/ActiveDirectory" in the scope of the XML node in which the XpathSelection expression appears. This is illustrated in the following example.

```
<node1 xmlns:ad="http://schemas.microsoft.com/2008/1/ActiveDirectory">
  /element1/element2[ad:value="abc"]
</node1>
```

Without the selection-predicate, an XpathSelection expression is analogous to an XPath 1.0 absolute location path with one or two location steps along the child axis. The expression "/X" selects the XML element named "X" whose parent is the root node of the XML document. The expression "/X/Y" selects the XML element named "Y" whose parent is the XML element named "X" whose parent, in turn, is the root node of the document. For example, given the following XML document:

```
<addata:user>
  <addata:description LdapType="UnicodeString">
    <ad:value xsi:type="xsd:string">
      First sample description
    </ad:value>
    <ad:value xsi:type="xsd:string">
      Second sample description
    </ad:value>
  </addata:description>
</addata:user>
```

The XpathSelection expression "/addata:user" selects the entire <addata:user> element (including child elements), while the XpathSelection expression "/addata:user/addata:description" selects the following portion.

```
<addata:description LdapType="UnicodeString">
  <ad:value xsi:type="xsd:string">
    First sample description
  </ad:value>
  <ad:value xsi:type="xsd:string">
    Second sample description
  </ad:value>
</addata:description>
```

However, unlike an XPath 1.0 expression, the comparison of the LocalPart of the QName is done in a case-insensitive manner. For example, the following XpathSelection expressions are equivalent:

/addata:user/addata:description

/addata:USER/addata:DESCRIPTION

/addata:User/addata:Description

The inclusion of a selection\_predicate allows an individual <ad:value> element to be specified. The predicate "[ad:value="X"]" matches the <ad:value> element whose child text node is equal to "X". The equality comparison is done using a comparison operation appropriate to the attribute syntax of the directory attribute, as specified in [MS-ADTS](#) section 3.1.1.2.2.4 (for example, values for attributes that are of type String(case) in the directory are compared using a case-insensitive string comparison, while values of type Integer are compared as integers).

Using the previous XML document, the XpathSelection expression `"/addata:user/addata:description[ad:value="First sample description"]"` selects the following portion.

```
<ad:value xsi:type="xsd:string">
  First sample description
</ad:value>
```

## 2.5 Common SOAP Headers

The following sections describe SOAP headers that are defined by the ADWS protocol set. These headers, and the ADWS protocols that use them, are summarized in the following table.

| SOAP 1.2 header (with namespace prefix) | Informative summary   | Protocols in which header is used  |
|---|---|--|
| ad:instance                             | Specifies the directory service against which the operation is to be performed.                                 | <a href="#">[WXFR]</a><br><a href="#">[MS-WSTIM]</a><br><a href="#">[WSENUM]/[MS-WSDS]</a> |
| ad:objectReferenceProperty              | Specifies the object reference property of the directory object against which the operation is to be performed. | [WXFR]<br>[MS-WSTIM]   |

### 2.5.1 ad:instance Header

An implementation can allow multiple directory services to be accessed via a single endpoint. [<5>](#) The ad:instance SOAP header, which is located in the <http://schemas.microsoft.com/2008/1/ActiveDirectory> XML namespace, is included in a SOAP request message to specify which directory service the request is intended for.

The content of the ad:instance header is the string literal "ldap:" followed by an integer (expressed as a string in base 10) that specifies the TCP port number of the desired directory service's LDAP interface.

In the following example, the requestor is asking that the operation (a WS-Transfer Get [\[WXFR\]](#)) that is specified in the SOAP message be performed against the directory service that listens on port 3268.

```
<soapenv:Envelope>
  <soapenv:Header>
    <wsa:Action soapenv:mustUnderstand="1">
      http://schemas.xmlsoap.org/ws/2004/09/transfer/Get
    </wsa:Action>
    <ad:objectReferenceProperty>
      a492d5f2-18c3-4f93-87d8-09a8c66bb5e4
    </ad:objectReferenceProperty>
    <ad:instance>ldap:3268</ad:instance>
    <wsa:MessageID>
      urn:uuid:d3cf5d97-3e9d-4c1c-b7b7-f2893685ddea
    </wsa:MessageID>
    <wsa:ReplyTo>
      <wsa:Address>
        http://www.w3.org/2005/08/addressing/anonymous
      </wsa:Address>
    </wsa:ReplyTo>
    <wsa:To soapenv:mustUnderstand="1">
      net.tcp://server01.fabrikam.com:9389/ActiveDirectoryWebServices/Windows/Resource
    </wsa:To>
```

```

</soapenv:Header>
<soapenv:Body />
</soapenv:Envelope>

```

## 2.5.2 ad:objectReferenceProperty Header

The ad:objectReferenceProperty SOAP header, which is located in the <http://schemas.microsoft.com/2008/1/ActiveDirectory> XML namespace, is attached to a SOAP request message to specify the object reference property of the directory object against which the operation specified in the SOAP message is to be performed. For example, if the SOAP message specifies a WS-Transfer Get operation [[WXFR](#)], the ad:objectReferenceProperty header specifies the directory object that is to be returned.

The content of the ad:objectReferenceProperty header is the directory object's object reference property in either GUID or distinguished name form, as specified in section [2.3.1](#). For example, in the following request, the requestor is asking that the operation (a WS-Transfer Get) specified in the SOAP message be performed against the object whose object reference property (specified as a GUID) is {a492d5f2-18c3-4f93-87d8-09a8c66bb5e4}. In conjunction with the ad:instance SOAP header, this uniquely identifies a single directory object located in a single directory service.

```

<soapenv:Envelope>
  <soapenv:Header>
    <wsa:Action s:mustUnderstand="1">
      http://schemas.xmlsoap.org/ws/2004/09/transfer/Get
    </wsa:Action>
    <ad:objectReferenceProperty>
      a492d5f2-18c3-4f93-87d8-09a8c66bb5e4
    </ad:objectReferenceProperty>
    <ad:instance>ldap:3268</ad:instance>
    <wsa:MessageID>
      urn:uuid:d3cf5d97-3e9d-4c1c-b7b7-f2893685ddea
    </wsa:MessageID>
    <wsa:ReplyTo>
      <wsa:Address>
        http://www.w3.org/2005/08/addressing/anonymous
      </wsa:Address>
    </wsa:ReplyTo>
    <wsa:To soapenv:mustUnderstand="1">
      net.tcp://server01.fabrikam.com:9389/ActiveDirectoryWebServices/Windows/Resource
    </wsa:To>
  </soapenv:Header>
  <soapenv:Body />
</soapenv:Envelope>

```

The ad:objectReferenceProperty is relative to the [ad:instance header](#) specified in the request. If the ad:instance header is not specified, the directory object cannot be uniquely identified, because directory objects on different directory services could share the same GUID or distinguished name.

The ad:instance and ad:objectReferenceProperty header elements are included in the wxf:resourceCreated/wsa:ReferenceParameters element of the response to a WS-Transfer Create operation, as shown in the following example.

```

<soapenv:Envelope>
  <soapenv:Header>
    ...
  </soapenv:Header>
  <soapenv:Body>
    <wxf:ResourceCreated>
      <wsa:Address>...</wsa:Address>

```

```

    <wsa:ReferenceParameters>
      <ad:objectReferenceProperty>...</ad:objectReferenceProperty>
      <ad:instance>...</ad:Instance>
    </wsa:ReferenceParameters>
  </wxf:ResourceCreated>
</soapenv:Body>
</soapenv:Envelope>

```

## 2.6 Common SOAP Fault Detail

This section defines a SOAP fault Detail element [\[SOAP1.2-1/2003\]](#) that is used by the ADWS protocol set. This element is used for the "[Detail]" property of [\[WSASB\]](#). The SOAP fault detail is specified via the following XML schema [\[XMLSCHEMA1\]](#) definition.

```

<xsd:schema
  targetNamespace="http://schemas.microsoft.com/2008/1/ActiveDirectory"
  xmlns:xsd="http://www.w3.org/2001/XMLSchema"
  xmlns:ad="http://schemas.microsoft.com/2008/1/ActiveDirectory"
  xmlns:da="http://schemas.microsoft.com/2006/11/IdentityManagement/DirectoryAccess"
  elementFormDefault="qualified">
  <xsd:complexType name="ArgumentErrorType">
    <xsd:sequence>
      <xsd:element name="Message" type="xsd:string" minOccurs="0"/>
      <xsd:element name="ParameterName" type="xsd:string"
        minOccurs="0"/>
      <xsd:element name="ShortMessage" type="xsd:string"
        minOccurs="0"/>
    </xsd:sequence>
  </xsd:complexType>

  <xsd:complexType name="DirectoryErrorType">
    <xsd:sequence>
      <xsd:element name="Message" type="xsd:string" minOccurs="0"/>
      <xsd:element name="ErrorCode" type="xsd:string" minOccurs="0"/>
      <xsd:element name="ExtendedErrorMessage" type="xsd:string"
        minOccurs="0"/>
      <xsd:element name="MatchedDN" type="xsd:string" minOccurs="0"/>
      <xsd:element name="Referral" type="xsd:string" minOccurs="0"
        maxOccurs="unbounded"/>
      <xsd:element name="Win32ErrorCode" type="xsd:string" minOccurs="0"/>
      <xsd:element name="ShortMessage" type="xsd:string" minOccurs="0"/>
    </xsd:sequence>
  </xsd:complexType>

  <xsd:complexType name="ChangeType">
    <xsd:sequence>
      <xsd:element name="AttributeType" type="da:AttributeType"/>
      <xsd:element name="AttributeValue" type="da:AttributeValue"/>
    </xsd:sequence>
    <xsd:attribute name="Operation" type="xsd:string"/>
  </xsd:complexType>

  <xsd:complexType name="InvalidAttributeTypeOrValueType">
    <xsd:sequence>
      <xsd:element name="AttributeType" type="da:AttributeType"/>
      <xsd:element name="AttributeValue" type="da:AttributeValue"/>
    </xsd:sequence>
  </xsd:complexType>

  <xsd:complexType name="FaultDetailType">
    <xsd:sequence>
      <xsd:element name="Error" type="xsd:string" minOccurs="0"/>
      <xsd:choice>
        <xsd:element name="ArgumentError" type="ad:ArgumentErrorType"/>
        <xsd:element name="DirectoryError" type="ad:DirectoryErrorType"/>
        <xsd:element name="InvalidAttributeType" type="xsd:string"/>
      </xsd:choice>
    </xsd:sequence>
  </xsd:complexType>

```

```

        <xsd:element name="InvalidOperation" type="xsd:string"/>
        <xsd:element name="InvalidChange" type="ad:ChangeType"/>
        <xsd:element name="InvalidAttributeTypeOrValue"
            type="ad:InvalidAttributeTypeOrValueType"/>
    </xsd:choice>
    <xsd:element name="ShortError" type="xsd:string" minOccurs="0"/>
</xsd:sequence>
</xsd:complexType>

<xsd:element name="FaultDetail" type="ad:FaultDetailType"/>

</xsd:schema>

```

In the following descriptions, XPath 1.0 [\[XPATH\]](#) notation is used to indicate the XML element or attribute that is being referred to.

A single SOAP fault can specify ad:FaultDetail/ad:Error, ad:FaultDetail/ad:ShortError, or both in addition to exactly one of the following: [<6>](#)

- ad:FaultDetail/ad:ArgumentError
- ad:FaultDetail/ad:DirectoryError
- ad:FaultDetail/ad:InvalidAttributeType
- ad:FaultDetail/ad:InvalidOperation
- ad:FaultDetail/ad:InvalidChange
- ad:FaultDetail/ad:InvalidAttributeTypeOrValue

The use of ad:FaultDetail/ad:ArgumentError is implementation-defined. [<7>](#)

The presence of ad:FaultDetail/ad:DirectoryError in a SOAP fault indicates that an error was returned by the directory service.

| Element  | Contents   |
|--|--|
| ad:FaultDetail/ad:DirectoryError/ad:Message              | A human-readable error message string explaining the nature of the directory error that occurred.                    |
| ad:FaultDetail/ad:DirectoryError/ad:ErrorCode            | An LDAP resultCode as specified in <a href="#">[RFC2251]</a> .   |
| ad:FaultDetail/ad:DirectoryError/ad:ExtendedErrorMessage | An LDAP errorMessage as specified in <a href="#">[RFC2251]</a> .   |
| ad:FaultDetail/ad:DirectoryError/ad:MatchedDN            | An LDAP matchedDN as specified in <a href="#">[RFC2251]</a> .  |
| ad:FaultDetail/ad:DirectoryError/ad:Referral             | An LDAP referral URL as specified in <a href="#">[RFC2251]</a> .   |
| ad:FaultDetail/ad:DirectoryError/ad:Win32ErrorCode       | An error code generated from ad:ErrorCode(*).  |
| ad:FaultDetail/ad:DirectoryError/ad:ShortMessage         | A non-localized error message string representing the nature of the directory error that occurred in ad:Message(**). |

(\*) The information in the following product behavior note applies to this element. [<8>](#)

(\*\*) The information in the following product behavior note applies to this element. [<9>](#)

The ad:FaultDetail/ad:InvalidAttributeType element indicates that a [\[MS-WSTIM\]](#) ModifyRequest operation specified a da:ModifyRequest/da:Change/da:AttributeValue when a value was not permitted

to be specified by the setting of the da:ModifyRequest/da:Change/@Operation attribute, or did not specify a value when one was required by the setting of that attribute.

| Element                                | Contents  |
|--|---|
| ad:FaultDetail/ad:InvalidAttributeType | The value of the da:ModifyRequest/da:Change/da:AttributeType for the da:ModifyRequest/da:Change with the incorrectly specified value. |

The ad:FaultDetail/ad:InvalidOperation element indicates that a [MS-WSTIM] ModifyRequest operation specified an invalid value for the da:ModifyRequest/da:Change/@Operation attribute.

| Element                            | Contents   |
|------------------------------------|--|
| ad:FaultDetail/ad:InvalidOperation | The invalid value specified for the da:ModifyRequest/da:Change/@Operation attribute. |

The ad:FaultDetail/ad:InvalidChange element indicates that a [MS-WSTIM] ModifyRequest specified an invalid value for the contents of a da:ModifyRequest/da:Change/da:AttributeValue.

| Element   | Contents  |
|---|---|
| ad:FaultDetail/ad:InvalidChange/@Operation        | The value of the da:ModifyRequest/da:Change/@Operation attribute for the da:ModifyRequest/da:Change with the invalid value. |
| ad:FaultDetail/ad:InvalidChange/da:AttributeType  | The value of the da:ModifyRequest/da:Change/da:AttributeType for the da:ModifyRequest/da:Change with the invalid value.     |
| ad:FaultDetail/ad:InvalidChange/da:AttributeValue | The value of the da:ModifyRequest/da:Change/da:AttributeValue for the da:ModifyRequest/da:Change with the invalid value.    |

The ad:FaultDetail/ad:InvalidAttributeTypeOrValue element indicates that a [MS-WSTIM] AddRequest specified an invalid da:AddRequest/da:AttributeTypeAndValue.

| Element   | Contents  |
|---|---|
| ad:FaultDetail/ad:InvalidAttributeTypeOrValue/da:AttributeType  | The value of the da:AddRequest/da:AttributeTypeAndValue/da:AttributeType for the invalid da:AddRequest/da:AttributeTypeAndValue.  |
| ad:FaultDetail/ad:InvalidAttributeTypeOrValue/da:AttributeValue | The value of the da:AddRequest/da:AttributeTypeAndValue/da:AttributeValue for the invalid da:AddRequest/da:AttributeTypeAndValue. |

The ad:FaultDetail/ad:Error element provides a human-readable error explaining the error. This option is used when none of the other options apply and can be used in addition to the other options. Unlike ad:FaultDetail/ad:DirectoryError/ad:Message, the contents of ad:FaultDetail/ad:Error/ad:Message need not be an error related to the directory service.

| Element                 | Contents  |
|-------------------------|---|
| ad:FaultDetail/ad:Error | A human-readable error message string explaining the nature of the error that occurred. |

For example, the following demonstrates the SOAP fault detail that could be returned when the directory service returns an LDAP referral error code.

```
<soapenv:Envelope>
  <soapenv:Header>
    ....
  </soapenv:Header>
  <soapenv:Body>
    <soapenv:Fault>
      ....
      <soapenv:Detail>
        <FaultDetail
          xmlns="http://schemas.microsoft.com/2008/1/ActiveDirectory">
            <DirectoryError>
              <Message>An operation error occurred.</Message>
              <ErrorCode>10</ErrorCode>
              <ExtendedErrorMessage>
                0000202B: RefErr: DSID-03100768, data 0, 1 access points ref 1:
                'server01.fabrikam.com'
              </ExtendedErrorMessage>
              <MatchedDN>
              </MatchedDN>
              <Referral>
                ldap://server01.fabrikam.com/CN=Test,DC=fabrikam,DC=com
              </Referral>
              <ShortMessage>ELdap</ShortMessage>
              <Win32ErrorCode>8235</Win32ErrorCode>
            </DirectoryError>
          </FaultDetail>
        </soapenv:Detail>
      </soapenv:Fault>
    </soapenv:Body>
  </soapenv:Envelope>
```

## 2.7 Range Retrieval

Retrieving the contents of a multivalued attribute from a group such as a distribution list can often result in a large number of returned values. A directory service can place limits on the maximum number of attribute values that can be retrieved in a single query. [<10>](#) If an attribute has more values than can be returned by the server in a single call, the only way to enumerate all of the attribute values is through the use of the range option.

Range retrieval involves requesting a limited number of attribute values in a single query. The number of values requested must be less than or equal to the maximum number of values supported by the server. To reduce the number of times the query must contact the server, the number of values requested should be as close to this maximum as possible.

To support range retrieval, the WS-Transfer and WS-Enumeration Web Service protocols in the ADWS protocol set require defining an XML representation to return portions of a multivalued attribute or to specify which portion of the attribute to retrieve. The following sections provide an extension to the XML serialization of the data model defined in section [2.3.2](#) that specifies an XML representation of an attribute with only a portion of its values. They also define extensions to the WS-Transfer [\[WXFR\]](#) and WS-Enumeration [\[WSENUM\]](#) protocols that indicate how a requester is to specify the portion of the attribute values to be returned.

### 2.7.1 XML View of Multivalued Attribute with Range Option

Section [2.3.2](#) describes the XML view of a directory object and its attributes as presented by ADWS. This section defines extensions to such an XML view for a multivalued attribute in which only a subset of the values are represented in the XML. This subset is referred to as a range of values. This range of



values is represented by XML attributes RangeLow and RangeHigh. For example, suppose that an attribute contains 5,000 values. The XML view might contain only the first 1,000 values, in which case RangeLow and RangeHigh would be 0 and 999, respectively.

The following description defines how a multivalued LDAP attribute and a portion of its value(s) limited by a range are represented in the XML view. Let  $B$  be the LDAP display name of the multivalued attribute that contains the complete set of values  $V_1(B) \dots V_n(B)$ . Let  $RANGELOW(B)$  and  $RANGEHIGH(B)$  be the respective lower and higher range of values returned by the server for the multivalued attribute. Let  $V_{RANGELOW(B)}$  and  $V_{RANGEHIGH(B)}$  be the returned values lying between  $RANGELOW(B)$  and  $RANGEHIGH(B)$  of values  $V_1(B)$  and  $V_n(B)$ . Let  $S_{RANGELOW(B)}(B) \dots S_{RANGEHIGH(B)}(B)$  be the XML representation of values  $V_{RANGELOW(B)} \dots V_{RANGEHIGH(B)}$  as described in section 2.3.4. Let  $LDAPSYN(B)$  be the LDAP attribute syntax of attribute  $B$  and let  $XMLSYN(B)$  be the corresponding XML syntax, as described in section 2.3.4. The XML representation for this multivalued attribute with range option is the following.

```
<addata:B RangeLow="RANGELOW(B)" RangeHigh="RANGEHIGH(B)" LdapSyntax="LDAPSYN(B)">
  <ad:value xsi:type="XMLSYN(B)">
    S (RANGELOW(B)) (B)
  </ad:value>
  ...
  ...
  <ad:value xsi:type="XMLSYN(B)">
    S (RANGEHIGH(B)) (B)
  </ad:value>
</addata:B>
```

If  $O$  is the directory object,  $C$  being the LDAP display name of the most specific structural object class ([MS-ADTS] section 3.1.1.1.4) and  $B$  being one its multivalued attributes, then the following representation of  $O$  as the XML view in the data model described in section 2.3.2 remains unchanged except for the multivalued attribute XML representation comprised of range attributes.

```
<addata:C>
  ...
  ...
  <addata:B RangeLow="RANGELOW(B)" RangeHigh="RANGEHIGH(B)" LdapSyntax="LDAPSYN(B)">
    <ad:value xsi:type="XMLSYN(B)">
      S (RANGELOW(B)) (B)
    </ad:value>
    ...
    ...
    <ad:value xsi:type="XMLSYN(B)">
      S (RANGEHIGH(B)) (B)
    </ad:value>
  </addata:B>
  ...
  ...
</addata:C>
```

For each multivalued LDAP attribute for which the server is including only a portion of the values contained in that attribute, both the RangeLow and RangeHigh XML attributes are returned.

ADWS specification of the possible values of these XML attributes, which are returned in the response as part of the XML view of the object for a request with range specification, is illustrated in section 2.7.2.

## 2.7.2 Range Specifiers for Requests

The range option for an attribute query is represented using the following XML attributes in the request:

```
RangeLow="RANGELOW" RangeHigh="RANGEHIGH"
```

where *RANGELOW* is the zero-based index of the first attribute value to retrieve, and *RANGEHIGH* is the zero-based index of the last attribute value to retrieve.

When querying for an attribute, a request can specify a RangeLow XML attribute in addition to a RangeHigh XML attribute to retrieve values between the lower and higher range, inclusively. A SOAP request to retrieve multivalued attributes containing a RangeHigh XML attribute must also contain a RangeLow XML attribute. A SOAP request to retrieve multivalued attributes not containing a RangeHigh attribute specifies a request to retrieve all the values beyond *RANGELOW* (this is subject to the limit imposed by the server on the maximum number of values that can be returned).

In search queries and results, zero is used for *RANGELOW* to specify the first entry and the wildcard character (\*) is used for *RANGEHIGH* to specify all remaining entries. If specified, *RANGELOW* MUST be of type positive integer. If specified, *RANGEHIGH* MUST be either a positive integer or the wildcard character (\*).

Both RangeLow and RangeHigh can be absent if the range retrieval extensions as illustrated in [2.7.2.1](#) and [2.7.2.2](#) are not used. Both RangeLow and RangeHigh attributes being absent from a request specifies a request for all values to be returned in that single call. For example, if a distribution list contains 1,000 member values, and if this number is less than the directory service-imposed limit on the maximum values that can be retrieved in a single query (1,500 for instance), all 1,000 values must be returned.

If the list of values is larger than the maximum limit of values the server can return, for example 2,000 member values, the first response contains the member attribute with RangeLow and RangeHigh XML attributes specifying the lower and higher range, respectively, and containing all the member values in this range.

To retrieve the next group of member values in the previous example, the search query can be repeated with a range specification that begins at the attribute number that is one past the RANGEHIGH value that was returned in the previous call. This process can be repeated until the last group of values is retrieved. In the above example, the first call would return member values in the range RangeLow as "0" and RangeHigh as "1,499". To retrieve the remaining values, the search query would request member values with RangeLow = 1,500 and RangeHigh = \*, and would be given member values in the range RangeLow as "1,500" and RangeHigh as "2000".

The ADWS protocol set shares these range specifiers as common XML attributes that are used to extend WS-Transfer [\[WXFR\]](#) Get and WS-Enumeration [\[WSENUM\]](#) Enumerate requests, which are described in subsequent sections.

The following table lists examples of how to implement range specifiers.

| Example                      | Meaning                                       |
|------------------------------|---|
| RangeLow="0" RangeHigh="*"   | Retrieve all attribute values.*               |
| RangeLow="0" RangeHigh="500" | Retrieve the 1st to 501st values, inclusive.  |
| RangeLow="2" RangeHigh="3"   | Retrieve the 3rd and 4th values.              |
| RangeLow="501" RangeHigh="*" | Retrieve the 502nd and all remaining values.* |

(\*) This is subject to the limits imposed by the server. [<11>](#)

The following sections illustrate extensions to the WS-Transfer [WXFR] and WS-Enumeration [WSENUM] protocols by specifying how requestors could retrieve only a portion of the attribute values through an Enumerate or Get request using the range specifiers defined previously.

### 2.7.2.1 WS-Transfer Range Retrieval Extensions

This section illustrates a range retrieval extension to the Get operation of the WS-Transfer [WXFR] protocol, which, when used with [MS-WSTIM] extensions, provides a way to retrieve portions of a multivalued attribute of a specific directory object.

In this example, the following is the XML representation of the da:AttributeType XML element defined in [MS-WSTIM] section 2.2.3.1, with range specifiers for retrieving only portions of the multivalued attribute.

```
<da:AttributeType RangeLow="0" RangeHigh="*">
  addata:member
</da:AttributeType>
```

The updated XML schema definition for the da:AttributeType element relative to the schema definition defined in [MS-WSTIM] would be similar to the following.

```
<xsd:element name="AttributeType">
  <xsd:complexType>
    <xsd:complexContent>
      <xsd:extension base="ExtensibleType">
        <xsd:attribute name="RangeLow" use="required" type="xsd:nonNegativeInteger"/>
        <xsd:attribute name="RangeHigh" use="optional" type="xsd:string"/>
      </xsd:extension>
    </xsd:complexContent>
  </xsd:complexType>
</xsd:element>
<xsd:complexType name="ExtensibleType">
  <xsd:complexContent mixed="true">
    <xsd:restriction base="xsd:anyType">
      <xsd:sequence>
        <xsd:any processContents="lax"
          minOccurs="0" maxOccurs="unbounded" />
      </xsd:sequence>
    </xsd:restriction>
  </xsd:complexContent>
</xsd:complexType>
```

### 2.7.2.2 WS-Enumeration Range Retrieval Extensions

This section illustrates a range retrieval extension to the Enumerate operation of the WS-Enumerate [WSENUM] protocol, which, when used with [MS-WSDS] extensions, provides a way to retrieve portions of a multivalued attribute of selected directory objects during a pull operation.

In this example, the following is the XML representation of the ad:SelectionProperty XML element defined in [MS-WSDS] section 3.1.4.1.1.2.1, with range specifiers for retrieving only portions of the multivalued attribute.

```
<ad:SelectionProperty RangeLow="0" RangeHigh="*">
  addata:member
</ad:SelectionProperty>
```

The updated XML schema definition for the ad:SelectionProperty element relative to the schema defined in [MS-WSDS] would be similar to the following.

```
<xsd:element name="SelectionProperty">
  <xsd:complexType>
    <xsd:complexContent>
      <xsd:extension base="xsd:string">
        <xsd:attribute name="RangeLow" use="required" type="xsd:nonNegativeInteger"/>
        <xsd:attribute name="RangeHigh" use="optional" type="xsd:string"/>
      </xsd:extension>
    </xsd:complexContent>
  </xsd:complexType>
</xsd:element>
```

## 3 Structure Examples

This section contains examples of the XML view of sample directory objects, including the ADWS synthetic attributes. For illustrative purposes, these examples are shown in the context of protocols in the ADWS protocol set.

### 3.1 WS-Transfer 'Get' Example

The following example shows a WS-Transfer Get [\[WXFR\]](#) operation. Both the SOAP request message and the SOAP response message are shown. This example retrieves the complete XML view of a directory object. In this example, the most specific structural object class of the directory object is user. The object has an LDAP distinguished name of "CN=TestUser1,DC=fabrikam,DC=com". The GUID for its object reference property is {1e0f3427-bbcb-474d-a532-a2ba6168c4dc}, and its parent object has a object reference property whose GUID is {e4f8a504-d7df-4b63-a636-5642d3bf1cf6}.

SOAP request message:

```
<soapenv:Envelope
  xmlns:wsa="http://www.w3.org/2005/08/addressing"
  xmlns:soapenv="http://www.w3.org/2003/05/soap-envelope">
  <soapenv:Header>
    <wsa:Action soapenv:mustUnderstand="1">
      http://schemas.xmlsoap.org/ws/2004/09/transfer/Get
    </wsa:Action>
    <objectReferenceProperty
      xmlns="http://schemas.microsoft.com/2008/1/ActiveDirectory">
      1e0f3427-bbcb-474d-a532-a2ba6168c4dc
    </objectReferenceProperty>
    <instance xmlns="http://schemas.microsoft.com/2008/1/ActiveDirectory">
      ldap:389
    </instance>
    <wsa:MessageID>
      urn:uuid:720f1d9c-5181-42c8-91ab-3deef105d0ff
    </wsa:MessageID>
    <wsa:ReplyTo>
      <wsa:Address>
        http://www.w3.org/2005/08/addressing/anonymous
      </wsa:Address>
    </wsa:ReplyTo>
    <wsa:To soapenv:mustUnderstand="1">
      net.tcp://server01.fabrikam.com:9389/ActiveDirectoryWebServices/Windows/Resource
    </wsa:To>
  </soapenv:Header>
  <soapenv:Body/>
</soapenv:Envelope>
```

SOAP response message:

```
<soapenv:Envelope
  xmlns:soapenv="http://www.w3.org/2003/05/soap-envelope"
  xmlns:wsa="http://www.w3.org/2005/08/addressing">
  <soapenv:Header>
    <wsa:Action soapenv:mustUnderstand="1">
      http://schemas.xmlsoap.org/ws/2004/09/transfer/GetResponse
    </wsa:Action>
    <wsa:RelatesTo>
      urn:uuid:720f1d9c-5181-42c8-91ab-3deef105d0ff
    </wsa:RelatesTo>
    <wsa:To soapenv:mustUnderstand="1">
      http://www.w3.org/2005/08/addressing/anonymous
    </wsa:To>
  </soapenv:Header>
```

```

<soapenv:Body>
  <addata:user
    xmlns:addata="http://schemas.microsoft.com/2008/1/ActiveDirectory/Data"
    xmlns:ad="http://schemas.microsoft.com/2008/1/ActiveDirectory"
    xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
    xmlns:xsd="http://www.w3.org/2001/XMLSchema">
    <ad:objectReferenceProperty>
      <ad:value xsi:type="xsd:string">
        1e0f3427-bbcb-474d-a532-a2ba6168c4dc
      </ad:value>
    </ad:objectReferenceProperty>
    <addata:lastLogon LdapSyntax="LargeInteger">
      <ad:value xsi:type="xsd:string">0</ad:value>
    </addata:lastLogon>
    <addata:dSCorePropagationData LdapSyntax="GeneralizedTimeString">
      <ad:value xsi:type="xsd:string">16010101000000.0Z</ad:value>
    </addata:dSCorePropagationData>
    <addata:objectSid LdapSyntax="SidString">
      <ad:value xsi:type="xsd:base64Binary">
        AQUAAAAAAAAUVAAbTii8R3L2V3ypAE4plMAAA==
      </ad:value>
    </addata:objectSid>
    <addata:whenCreated LdapSyntax="GeneralizedTimeString">
      <ad:value xsi:type="xsd:string">20080722202149.0Z</ad:value>
    </addata:whenCreated>
    <addata:badPasswordTime LdapSyntax="LargeInteger">
      <ad:value xsi:type="xsd:string">0</ad:value>
    </addata:badPasswordTime>
    <addata:accountExpires LdapSyntax="LargeInteger">
      <ad:value xsi:type="xsd:string">9223372036854775807</ad:value>
    </addata:accountExpires>
    <addata:name LdapSyntax="UnicodeString">
      <ad:value xsi:type="xsd:string">TestUser1</ad:value>
    </addata:name>
    <addata:uSNChanged LdapSyntax="LargeInteger">
      <ad:value xsi:type="xsd:string">166235</ad:value>
    </addata:uSNChanged>
    <addata:objectCategory LdapSyntax="DSDNString">
      <ad:value xsi:type="xsd:string">
        CN=Person,CN=Schema,CN=Configuration,DC=Fabrikam,DC=com
      </ad:value>
    </addata:objectCategory>
    <addata:sAMAccountType LdapSyntax="Integer">
      <ad:value xsi:type="xsd:string">805306368</ad:value>
    </addata:sAMAccountType>
    <addata:codePage LdapSyntax="Integer">
      <ad:value xsi:type="xsd:string">0</ad:value>
    </addata:codePage>
    <addata:instanceType LdapSyntax="Integer">
      <ad:value xsi:type="xsd:string">4</ad:value>
    </addata:instanceType>
    <addata:countryCode LdapSyntax="Integer">
      <ad:value xsi:type="xsd:string">0</ad:value>
    </addata:countryCode>
    <addata:distinguishedName LdapSyntax="DSDNString">
      <ad:value xsi:type="xsd:string">
        CN=TestUser1,DC=Fabrikam,DC=com
      </ad:value>
    </addata:distinguishedName>
    <addata:cn LdapSyntax="UnicodeString">
      <ad:value xsi:type="xsd:string">TestUser1</ad:value>
    </addata:cn>
    <addata:objectClass LdapSyntax="ObjectIdentifier">
      <ad:value xsi:type="xsd:string">top</ad:value>
      <ad:value xsi:type="xsd:string">person</ad:value>
      <ad:value xsi:type="xsd:string">organizationalPerson</ad:value>
      <ad:value xsi:type="xsd:string">user</ad:value>
    </addata:objectClass>
    <addata:logonCount LdapSyntax="Integer">

```

```

    <ad:value xsi:type="xsd:string">0</ad:value>
  </addata:logonCount>
  <addata:uSNCreated LdapSyntax="LargeInteger">
    <ad:value xsi:type="xsd:string">166234</ad:value>
  </addata:uSNCreated>
  <addata:userAccountControl LdapSyntax="Integer">
    <ad:value xsi:type="xsd:string">546</ad:value>
  </addata:userAccountControl>
  <addata:objectGUID LdapSyntax="OctetString">
    <ad:value xsi:type="xsd:base64Binary">
      JzQPHsu7TUelMqK6YWjE3A==
    </ad:value>
  </addata:objectGUID>
  <addata:primaryGroupID LdapSyntax="Integer">
    <ad:value xsi:type="xsd:string">513</ad:value>
  </addata:primaryGroupID>
  <addata:lastLogoff LdapSyntax="LargeInteger">
    <ad:value xsi:type="xsd:string">0</ad:value>
  </addata:lastLogoff>
  <addata:sAMAccountName LdapSyntax="UnicodeString">
    <ad:value xsi:type="xsd:string">testusr1</ad:value>
  </addata:sAMAccountName>
  <addata:badPwdCount LdapSyntax="Integer">
    <ad:value xsi:type="xsd:string">0</ad:value>
  </addata:badPwdCount>
  <addata:whenChanged LdapSyntax="GeneralizedTimeString">
    <ad:value xsi:type="xsd:string">20080722202149.0Z</ad:value>
  </addata:whenChanged>
  <addata:pwdLastSet LdapSyntax="LargeInteger">
    <ad:value xsi:type="xsd:string">0</ad:value>
  </addata:pwdLastSet>
  <ad:container-hierarchy-parent>
    <ad:value xsi:type="xsd:string">
      e4f8a504-d7df-4b63-a636-5642d3bf1cf6
    </ad:value>
  </ad:container-hierarchy-parent>
  <ad:relativeDistinguishedName>
    <ad:value xsi:type="xsd:string">CN=TestUser1</ad:value>
  </ad:relativeDistinguishedName>
  <ad:distinguishedName>
    <ad:value xsi:type="xsd:string">
      CN=TestUser1,DC=Fabrikam,DC=com
    </ad:value>
  </ad:distinguishedName>
</addata:user>
</soapenv:Body>
</soapenv:Envelope>

```

### 3.2 WS-Transfer Identity Management Extension 'ModifyRequest' Example

This example demonstrates a [\[MS-WSTIM\]](#) ModifyRequest operation. Both the SOAP request message and the SOAP response message are shown. In the SOAP request message, the requestor is specifying that the LDAP directory attribute whose LDAP display name is "description" is to have its value replaced with the new value "Modified description attribute". The requestor is also asking that the values "(212) 555-0100" and "(516) 555-0100" be appended to the set of existing values (if any) in the LDAP directory attribute whose LDAP display name is "otherTelephone". The directory object on which this operation is being performed is identified by its GUID-valued object reference property {cf041608-84b9-4fd0-a83c-46d40a964b88}.

SOAP request message:

```

<soapenv:Envelope
  xmlns:soapenv="http://www.w3.org/2003/05/soap-envelope"
  xmlns:wsa="http://www.w3.org/2005/08/addressing">

```

```

<soapenv:Header>
  <wsa:Action soapenv:mustUnderstand="1">
    http://schemas.xmlsoap.org/ws/2004/09/transfer/Put
  </wsa:Action>
  <IdentityManagementOperation
    xmlns="http://schemas.microsoft.com/2006/11/IdentityManagement/DirectoryAccess"/>
  <objectReferenceProperty
    xmlns="http://schemas.microsoft.com/2008/1/ActiveDirectory">
    cf041608-84b9-4fd0-a83c-46d40a964b88
  </objectReferenceProperty>
  <instance xmlns="http://schemas.microsoft.com/2008/1/ActiveDirectory">
    ldap:389
  </instance>
  <wsa:MessageID>
    urn:uuid:e36457ff-d0f1-4c85-abe6-6cdf4bd511e9
  </wsa:MessageID>
  <wsa:ReplyTo>
    <wsa:Address>
      http://www.w3.org/2005/08/addressing/anonymous
    </wsa:Address>
  </wsa:ReplyTo>
  <wsa:To soapenv:mustUnderstand="1">
    net.tcp://server01.fabrikam.com:9389/ActiveDirectoryWebServices/Windows/Resource
  </wsa:To>
</soapenv:Header>
<soapenv:Body>
  <da:ModifyRequest
    Dialect="http://schemas.microsoft.com/2008/1/ActiveDirectory/Dialect/XPath-Level-1"
    xmlns:da="http://schemas.microsoft.com/2006/11/IdentityManagement/DirectoryAccess"
    xmlns:addata="http://schemas.microsoft.com/2008/1/ActiveDirectory/Data"
    xmlns:ad="http://schemas.microsoft.com/2008/1/ActiveDirectory"
    xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
    xmlns:xsd="http://www.w3.org/2001/XMLSchema">
    <da:Change Operation="replace">
      <da:AttributeType>addata:description</da:AttributeType>
      <da:AttributeValue>
        <ad:value xsi:type="xsd:string">
          Modified description attribute
        </ad:value>
      </da:AttributeValue>
    </da:Change>
    <da:Change Operation="add">
      <da:AttributeType>addata:otherTelephone</da:AttributeType>
      <da:AttributeValue>
        <ad:value xsi:type="xsd:string">(212) 555-0100</ad:value>
        <ad:value xsi:type="xsd:string">(516) 555-0100</ad:value>
      </da:AttributeValue>
    </da:Change>
  </da:ModifyRequest>
</soapenv:Body>
</soapenv:Envelope>

```

#### SOAP response message:

```

<soapenv:Envelope
  xmlns:soapenv="http://www.w3.org/2003/05/soap-envelope"
  xmlns:wsa="http://www.w3.org/2005/08/addressing">
  <soapenv:Header>
    <wsa:Action soapenv:mustUnderstand="1">
      http://schemas.xmlsoap.org/ws/2004/09/transfer/PutResponse
    </wsa:Action>
    <wsa:RelatesTo>
      urn:uuid:e36457ff-d0f1-4c85-abe6-6cdf4bd511e9
    </wsa:RelatesTo>
    <wsa:To soapenv:mustUnderstand="1">
      http://www.w3.org/2005/08/addressing/anonymous
    </wsa:To>

```



```
</soapenv:Header>
<soapenv:Body/>
</soapenv:Envelope>
```

### 3.3 WS-Enumeration 'Pull' Example

This example demonstrates a WS-Enumeration Pull operation [WSENUM] using a previously obtained enumeration context. Both the SOAP request message and the SOAP response message are shown. In the response message, two directory objects are returned. Both objects have the same parent directory object, as evidenced by the fact that both have the same value for their [ad:container-hierarchy-parent](#) synthetic attribute. In this example, the WS-Enumeration Enumerate operation that began the search requested three attributes to be returned: the LDAP directory attribute `addata:givenName` and the synthetic attributes `ad:container-hierarchy-parent` and `ad:relativeDistinguishedName`. The [ad:objectReferenceProperty](#) synthetic attribute is automatically included in the response by the server [MS-WSDS].

SOAP request message:

```
<soapenv:Envelope
  xmlns:soapenv="http://www.w3.org/2003/05/soap-envelope"
  xmlns:wsa="http://www.w3.org/2005/08/addressing">
  <soapenv:Header>
    <wsa:Action soapenv:mustUnderstand="1">
      http://schemas.xmlsoap.org/ws/2004/09/enumeration/Pull
    </wsa:Action>
    <wsa:MessageID>
      urn:uuid:b22747a9-ca15-41de-8c91-5a51bd88669c
    </wsa:MessageID>
    <wsa:ReplyTo>
      <wsa:Address>
        http://www.w3.org/2005/08/addressing/anonymous
      </wsa:Address>
    </wsa:ReplyTo>
    <wsa:To soapenv:mustUnderstand="1">
      net.tcp://server01.fabrikam.com:9389/ActiveDirectoryWebServices/Windows/Enumeration
    </wsa:To>
  </soapenv:Header>
  <soapenv:Body>
    <wsen:Pull
      xmlns:wsen="http://schemas.xmlsoap.org/ws/2004/09/enumeration"
      xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
      xmlns:xsd="http://www.w3.org/2001/XMLSchema"
      xmlns:ad="http://schemas.microsoft.com/2008/1/ActiveDirectory">
      <wsen:EnumerationContext>
        f52c7e9d-80c2-40cd-b8c9-55bc94fc3e47
      </wsen:EnumerationContext>
      <wsen:MaxTime>PT10S</wsen:MaxTime>
      <wsen:MaxElements>2</wsen:MaxElements>
    </wsen:Pull>
  </soapenv:Body>
</soapenv:Envelope>
```

SOAP response message:

```
<soapenv:Envelope
  xmlns:soapenv="http://www.w3.org/2003/05/soap-envelope"
  xmlns:wsa="http://www.w3.org/2005/08/addressing">
  <soapenv:Header>
    <wsa:Action soapenv:mustUnderstand="1">
      http://schemas.xmlsoap.org/ws/2004/09/enumeration/PullResponse
    </wsa:Action>
    <wsa:RelatesTo>
```

```

    urn:uuid:b22747a9-ca15-41de-8c91-5a51bd88669c
  </wsa:RelatesTo>
  <wsa:To soapenv:mustUnderstand="1">
    http://www.w3.org/2005/08/addressing/anonymous
  </wsa:To>
</soapenv:Header>
<soapenv:Body>
  <wsen:PullResponse
    xmlns:wsen="http://schemas.xmlsoap.org/ws/2004/09/enumeration"
    xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
    xmlns:xsd="http://www.w3.org/2001/XMLSchema"
    xmlns:ad="http://schemas.microsoft.com/2008/1/ActiveDirectory"
    xmlns:addata="http://schemas.microsoft.com/2008/1/ActiveDirectory/Data">
    <wsen:EnumerationContext>
      d22e957c-8278-4eb9-a57f-41574c55305d
    </wsen:EnumerationContext>
    <wsen:Items>
      <addata:user>
        <ad:objectReferenceProperty>
          <ad:value xsi:type="xsd:string">
            373e1409-cf88-41dc-b8ea-bdd27d54e073
          </ad:value>
        </ad:objectReferenceProperty>
        <ad:container-hierarchy-parent>
          <ad:value xsi:type="xsd:string">
            41816238-95ca-48d9-9a99-3bd9ae9e0e42
          </ad:value>
        </ad:container-hierarchy-parent>
        <ad:relativeDistinguishedName>
          <ad:value xsi:type="xsd:string">CN=TestUser1</ad:value>
        </ad:relativeDistinguishedName>
        <addata:givenName LdapSyntax="UnicodeString">
          <ad:value xsi:type="xsd:string">John</ad:value>
        </addata:givenName>
      </addata:user>
      <addata:user>
        <ad:objectReferenceProperty>
          <ad:value xsi:type="xsd:string">
            51d67624-d52d-421d-a0d6-1dc350abd009
          </ad:value>
        </ad:objectReferenceProperty>
        <ad:container-hierarchy-parent>
          <ad:value xsi:type="xsd:string">
            41816238-95ca-48d9-9a99-3bd9ae9e0e42
          </ad:value>
        </ad:container-hierarchy-parent>
        <ad:relativeDistinguishedName>
          <ad:value xsi:type="xsd:string">CN=TestUser2</ad:value>
        </ad:relativeDistinguishedName>
        <addata:givenName LdapSyntax="UnicodeString">
          <ad:value xsi:type="xsd:string">Robert</ad:value>
        </addata:givenName>
      </addata:user>
    </wsen:Items>
  </wsen:PullResponse>
</soapenv:Body>
</soapenv:Envelope>

```

## **4 Security**

### **4.1 Security Considerations for Implementers**

None.

### **4.2 Index of Security Fields**

None.

## 5 Appendix A: Product Behavior

The information in this specification is applicable to the following Microsoft products or supplemental software. References to product versions include released service packs.

- Active Directory Management Gateway Service
- Remote Server Administration Tools for Windows 7
- Windows Server 2008 R2 operating system
- Remote Server Administration Tools for Windows 8 operating system
- Windows Server 2012 operating system
- Remote Server Administration Tools for Windows 8.1 operating system
- Windows Server 2012 R2 operating system
- Remote Server Administration Tools for Windows 10 operating system
- Windows Server 2016 operating system

Exceptions, if any, are noted below. If a service pack or Quick Fix Engineering (QFE) number appears with the product version, behavior changed in that service pack or QFE. The new behavior also applies to subsequent service packs of the product unless otherwise specified. If a product edition appears with the product version, behavior is different in that product edition.

Unless otherwise specified, any statement of optional behavior in this specification that is prescribed using the terms SHOULD or SHOULD NOT implies product behavior in accordance with the SHOULD or SHOULD NOT prescription. Unless otherwise specified, the term MAY implies that the product does not follow the prescription.

[<1> Section 1.3](#): Of the products listed in the applicability list at the beginning of this section, Active Directory Management Gateway Service contains the server implementation of the ADWS set of protocols that use Active Directory Web Services: Data Model and Common Elements, all the versions of the Remote Server Administration Tools contain the client implementation, and all the versions of Windows Server operating system contain both the server and the client implementations.

Active Directory Management Gateway Service is available for Windows Server 2003 operating system with Service Pack 2 (SP2), Windows Server 2003 R2 operating system with Service Pack 2 (SP2), and Windows Server 2008 operating system.

[<2> Section 2.3.3.1](#): Microsoft implementations of Active Directory Web Services: Data Model and Common Elements do not return the [ad:objectReferenceProperty](#) synthetic attribute if the requestor does not have permission to read *O!objectGUID*, where *O* is the directory object being represented as an XML view.

[<3> Section 2.3.3.2](#): Microsoft implementations of Active Directory Web Services: Data Model and Common Elements in Active Directory Management Gateway Service for Windows Server 2003 operating system omits this attribute from the XML view of all directory objects, regardless of whether the directory object has a parent.

[<4> Section 2.3.4](#): Microsoft implementations of Active Directory Web Services: Data Model and Common Elements use the following mapping between **rootDse** attributes (specified by their LDAP display names) and XML syntaxes.

| <b>rootDse attribute name</b> | <b>LDAPSYN</b>        | <b>XML syntax (XMSYN)</b> |
|-------------------------------|-----------------------|---------------------------|
| configurationnamingcontext    | DSDNString            | xsd:string                |
| Currenttime                   | GeneralizedTimeString | xsd:string                |
| defaultnamingcontext          | DSDNString            | xsd:string                |
| Dnshostname                   | UnicodeString         | xsd:string                |
| Dsschemaattrcount             | Integer               | xsd:string                |
| Dsschemaclasscount            | Integer               | xsd:string                |
| dsschemaprefixcount           | Integer               | xsd:string                |
| Dsservicename                 | DSDNString            | xsd:string                |
| highestcommittedusn           | LargeInteger          | xsd:string                |
| Isglobalcatalogready          | Boolean               | xsd:string                |
| Issynchronized                | Boolean               | xsd:string                |
| Ldap servicename              | UnicodeString         | xsd:string                |
| Namingcontexts                | DSDNString            | xsd:string                |
| pendingpropagations           | DSDNString            | xsd:string                |
| rootdomainnamingcontext       | DSDNString            | xsd:string                |
| schemanamingcontext           | DSDNString            | xsd:string                |
| Servername                    | DSDNString            | xsd:string                |
| Subschemasubentry             | DSDNString            | xsd:string                |
| supportedcapabilities         | ObjectIdentifier      | xsd:string                |
| Supportedcontrol              | ObjectIdentifier      | xsd:string                |
| supportedldappolicies         | UnicodeString         | xsd:string                |
| supportedldapversion          | Integer               | xsd:string                |
| supporteddsaslmechanisms      | UnicodeString         | xsd:string                |
| domaincontrollerfunctionality | Integer               | xsd:string                |
| Domainfunctionality           | Integer               | xsd:string                |
| Forestfunctionality           | Integer               | xsd:string                |
| msds-replallinboundneighbors  | UnicodeString         | xsd:string                |
| msds-replalloutboundneighbors | UnicodeString         | xsd:string                |
| msds-replconnectionfailures   | UnicodeString         | xsd:string                |
| msds-repllinkfailures         | UnicodeString         | xsd:string                |
| msds-replpendingops           | UnicodeString         | xsd:string                |
| msds-replqueuestatistics      | UnicodeString         | xsd:string                |

| <b>rootDse attribute name</b>  | <b>LDAPSYN</b>   | <b>XML syntax (XMSYN)</b> |
|--------------------------------|------------------|---------------------------|
| msds-topquotausage             | UnicodeString    | xsd:string                |
| supportedconfigurablesettings  | UnicodeString    | xsd:string                |
| Supportedextension             | ObjectIdentifier | xsd:string                |
| Validfsmos                     | DSDNString       | xsd:string                |
| Dsaversionstring               | UnicodeString    | xsd:string                |
| msds-portldap                  | Integer          | xsd:string                |
| msds-portssl                   | Integer          | xsd:string                |
| msds-principalname             | UnicodeString    | xsd:string                |
| Serviceaccountinfo             | UnicodeString    | xsd:string                |
| Spnregistrationresult          | Integer          | xsd:string                |
| Tokengroups                    | SidString        | xsd:base64Binary          |
| Usnatrifm                      | LargeInteger     | xsd:string                |
| becomePdcWithCheckPoint        | SidString        | xsd:base64Binary          |
| checkPhantoms                  | UnicodeString    | xsd:string                |
| doGarbageCollection            | Integer          | xsd:string                |
| dumpDatabase                   | UnicodeString    | xsd:string                |
| fixupInheritance               | UnicodeString    | xsd:string                |
| invalidateRidPool              | SidString        | xsd:base64Binary          |
| recalcHierarchy                | UnicodeString    | xsd:string                |
| schemaUpdateNow                | UnicodeString    | xsd:string                |
| removeLingeringObject          | UnicodeString    | xsd:string                |
| doLinkCleanup                  | UnicodeString    | xsd:string                |
| doOnlineDefrag                 | Integer          | xsd:string                |
| replicateSingleObject          | UnicodeString    | xsd:string                |
| updateCachedMemberships        | UnicodeString    | xsd:string                |
| doGarbageCollectionPhantomsNow | Integer          | xsd:string                |
| invalidateGCConnection         | UnicodeString    | xsd:string                |
| renewServerCertificate         | UnicodeString    | xsd:string                |
| rODCPurgeAccount               | UnicodeString    | xsd:string                |
| sqmRunOnce                     | UnicodeString    | xsd:string                |
| runProtectAdminGroupsTask      | UnicodeString    | xsd:string                |

<5> [Section 2.5.1](#): Microsoft implementations of Active Directory Web Services: Data Model and Common Elements provide access to any **Active Directory Domain Services (AD DS)** or **Active Directory Lightweight Directory Services (AD LDS)** directory service that is running on the same computer as ADWS. AD DS can be accessed via "ldap:389". If the machine is also an AD DS **global catalog**, then the global catalog can be accessed as "ldap:3268". An AD LDS instance can be accessed as "ldap:N", where N is the LDAP port number that the AD LDS instance has been configured to use.

<6> [Section 2.6](#): Microsoft implementations of Active Directory Web Services: Data Model and Common Elements include both ad:FaultDetail/ad:Error and ad:FaultDetail/ad:ShortError elements.

<7> [Section 2.6](#): Microsoft implementations of Active Directory Web Services: Data Model and Common Elements use ad:FaultDetail/ad:ArgumentError to indicate that an invalid argument was passed from one internal function to another.

| Element  | Contents   |
|--|--|
| ad:FaultDetail/ad:ArgumentError/ad:Message       | A human-readable error message string explaining the nature of the argument error that occurred. |
| ad:FaultDetail/ad:ArgumentError/ad:ParameterName | The name of the function parameter whose argument was invalid.                                   |

<8> [Section 2.6](#): Microsoft implementations of Active Directory Web Services: Data Model and Common Elements translate LDAP error codes to Win32 error codes ([\[MS-ERREF\]](#) section 2.2) using the following table.

| LDAP Error |                                 | Win32 Error |                                     |
|------------|---------------------------------|-------------|-------------------------------------|
| Code (Hex) | Name                            | Code (Dec)  | Name                                |
| 0x00       | LDAP_SUCCESS                    | 0           | NO_ERROR                            |
| 0x01       | LDAP_OPERATIONS_ERROR           | 8224        | ERROR_DS_OPERATIONS_ERROR           |
| 0x02       | LDAP_PROTOCOL_ERROR             | 8225        | ERROR_DS_PROTOCOL_ERROR             |
| 0x03       | LDAP_TIMELIMIT_EXCEEDED         | 8226        | ERROR_DS_TIMELIMIT_EXCEEDED         |
| 0x04       | LDAP_SIZELIMIT_EXCEEDED         | 8227        | ERROR_DS_SIZELIMIT_EXCEEDED         |
| 0x05       | LDAP_COMPARE_FALSE              | 8229        | ERROR_DS_COMPARE_FALSE              |
| 0x06       | LDAP_COMPARE_TRUE               | 8230        | ERROR_DS_COMPARE_TRUE               |
| 0x07       | LDAP_AUTH_METHOD_NOT_SUPPORTED  | 8231        | ERROR_DS_AUTH_METHOD_NOT_SUPPORTED  |
| 0x08       | LDAP_STRONG_AUTH_REQUIRED       | 8232        | ERROR_DS_STRONG_AUTH_REQUIRED       |
| 0x09       | LDAP_PARTIAL_RESULTS            | 299         | ERROR_PARTIAL_COPY                  |
| 0x0a       | LDAP_REFERRAL                   | 8235        | ERROR_DS_REFERRAL                   |
| 0x0b       | LDAP_ADMIN_LIMIT_EXCEEDED       | 8228        | ERROR_DS_ADMIN_LIMIT_EXCEEDED       |
| 0x0c       | LDAP_UNAVAILABLE_CRIT_EXTENSION | 8236        | ERROR_DS_UNAVAILABLE_CRIT_EXTENSION |
| 0x0d       | LDAP_CONFIDENTIALITY_REQUIRED   | 8237        | ERROR_DS_CONFIDENTIALITY_REQUIRED   |

| LDAP Error |                                | Win32 Error |                                    |
|------------|--------------------------------|-------------|------------------------------------|
| 0x0e       | LDAP_SASL_BIND_IN_PROGRESS     | 590610      | SEC_I_CONTINUE_NEEDED              |
| 0x10       | LDAP_NO_SUCH_ATTRIBUTE         | 8202        | ERROR_DS_NO_ATTRIBUTE_OR_VALUE     |
| 0x11       | LDAP_UNDEFINED_TYPE            | 8204        | ERROR_DS_ATTRIBUTE_TYPE_UNDEFINED  |
| 0x12       | LDAP_INAPPROPRIATE_MATCHING    | 8238        | ERROR_DS_INAPPROPRIATE_MATCHING    |
| 0x13       | LDAP_CONSTRAINT_VIOLATION      | 8239        | ERROR_DS_CONSTRAINT_VIOLATION      |
| 0x14       | LDAP_ATTRIBUTE_OR_VALUE_EXISTS | 8205        | ERROR_DS_ATTRIBUTE_OR_VALUE_EXISTS |
| 0x15       | LDAP_INVALID_SYNTAX            | 8203        | ERROR_DS_INVALID_ATTRIBUTE_SYNTAX  |
| 0x20       | LDAP_NO_SUCH_OBJECT            | 8240        | ERROR_DS_NO_SUCH_OBJECT            |
| 0x21       | LDAP_ALIAS_PROBLEM             | 8241        | ERROR_DS_ALIAS_PROBLEM             |
| 0x22       | LDAP_INVALID_DN_SYNTAX         | 8242        | ERROR_DS_INVALID_DN_SYNTAX         |
| 0x23       | LDAP_IS_LEAF                   | 8243        | ERROR_DS_IS_LEAF                   |
| 0x24       | LDAP_ALIAS_DEREF_PROBLEM       | 8244        | ERROR_DS_ALIAS_DEREF_PROBLEM       |
| 0x30       | LDAP_INAPPROPRIATE_AUTH        | 8233        | ERROR_DS_INAPPROPRIATE_AUTH        |
| 0x31       | LDAP_INVALID_CREDENTIALS       | 1326        | ERROR_LOGON_FAILURE                |
| 0x32       | LDAP_INSUFFICIENT_RIGHTS       | 5           | ERROR_ACCESS_DENIED                |
| 0x33       | LDAP_BUSY                      | 8206        | ERROR_DS_BUSY                      |
| 0x34       | LDAP_UNAVAILABLE               | 8207        | ERROR_DS_UNAVAILABLE               |
| 0x35       | LDAP_UNWILLING_TO_PERFORM      | 8245        | ERROR_DS_UNWILLING_TO_PERFORM      |
| 0x36       | LDAP_LOOP_DETECT               | 8246        | ERROR_DS_LOOP_DETECT               |
| 0x3C       | LDAP_SORT_CONTROL_MISSING      | 8261        | ERROR_DS_SORT_CONTROL_MISSING      |
| 0x3D       | LDAP_OFFSET_RANGE_ERROR        | 8262        | ERROR_DS_OFFSET_RANGE_ERROR        |
| 0x40       | LDAP_NAMING_VIOLATION          | 8247        | ERROR_DS_NAMING_VIOLATION          |
| 0x41       | LDAP_OBJECT_CLASS_VIOLATION    | 8212        | ERROR_DS_OBJ_CLASS_VIOLATION       |
| 0x42       | LDAP_NOT_ALLOWED_ON_NONLEAF    | 8213        | ERROR_DS_CANT_ON_NON_LEAF          |
| 0x43       | LDAP_NOT_ALLOWED_ON_RDN        | 8214        | ERROR_DS_CANT_ON_RDN               |
| 0x44       | LDAP_ALREADY_EXISTS            | 5010        | ERROR_OBJECT_ALREADY_EXISTS        |
| 0x45       | LDAP_NO_OBJECT_CLASS_MODS      | 8215        | ERROR_DS_CANT_MOD_OBJ_CLASS        |
| 0x46       | LDAP_RESULTS_TOO_LARGE         | 8248        | ERROR_DS_OBJECT_RESULTS_TOO_LARGE  |
| 0x47       | LDAP_AFFECTS_MULTIPLE_DSAS     | 8249        | ERROR_DS_AFFECTS_MULTIPLE_DSAS     |
| 0x4c       | LDAP_VIRTUAL_LIST_VIEW_ERROR   | 8341        | ERROR_DS_GENERIC_ERROR             |
| 0x50       | LDAP_OTHER                     | 31          | ERROR_GEN_FAILURE                  |
| 0x51       | LDAP_SERVER_DOWN               | 8250        | ERROR_DS_SERVER_DOWN               |



| LDAP Error |                              | Win32 Error |                                  |
|------------|------------------------------|-------------|----------------------------------|
| 0x52       | LDAP_LOCAL_ERROR             | 8251        | ERROR_DS_LOCAL_ERROR             |
| 0x53       | LDAP_ENCODING_ERROR          | 8252        | ERROR_DS_ENCODING_ERROR          |
| 0x54       | LDAP_DECODING_ERROR          | 8253        | ERROR_DS_DECODING_ERROR          |
| 0x55       | LDAP_TIMEOUT                 | 1460        | ERROR_TIMEOUT                    |
| 0x56       | LDAP_AUTH_UNKNOWN            | 8234        | ERROR_DS_AUTH_UNKNOWN            |
| 0x57       | LDAP_FILTER_ERROR            | 8254        | ERROR_DS_FILTER_UNKNOWN          |
| 0x58       | LDAP_USER_CANCELLED          | 1223        | ERROR_CANCELLED                  |
| 0x59       | LDAP_PARAM_ERROR             | 8255        | ERROR_DS_PARAM_ERROR             |
| 0x5a       | LDAP_NO_MEMORY               | 8           | ERROR_NOT_ENOUGH_MEMORY          |
| 0x5b       | LDAP_CONNECT_ERROR           | 1225        | ERROR_CONNECTION_REFUSED         |
| 0x5c       | LDAP_NOT_SUPPORTED           | 8256        | ERROR_DS_NOT_SUPPORTED           |
| 0x5e       | LDAP_NO_RESULTS_RETURNED     | 8257        | ERROR_DS_NO_RESULTS_RETURNED     |
| 0x5d       | LDAP_CONTROL_NOT_FOUND       | 8258        | ERROR_DS_CONTROL_NOT_FOUND       |
| 0x5f       | LDAP_MORE_RESULTS_TO_RETURN  | 234         | ERROR_MORE_DATA                  |
| 0x60       | LDAP_CLIENT_LOOP             | 8259        | ERROR_DS_CLIENT_LOOP             |
| 0x61       | LDAP_REFERRAL_LIMIT_EXCEEDED | 8260        | ERROR_DS_REFERRAL_LIMIT_EXCEEDED |

<9> [Section 2.6](#): Microsoft implementations of Active Directory Web Services: Data Model and Common Elements attempt to find the ad:Message value in column B of the first table shown below.

- If the value is found in column B of the first table, the ad:ShortMessage is populated with text from column A.
- If no match is found in column B of the first table, ad:ShortMessage is populated from column A of the second table based on the error encountered, as described in column B.

First table:

| A                                   | B   |
|-------------------------------------|---|
| AnonymousNotAllowed                 | Anonymous access to the directory is not permitted.                                   |
| AttributeValueNotaObjRef            | The attribute found is not a valid object reference (neither a GUID nor a string DN). |
| AttributeValueNotaString            | The attribute found is not a String.  |
| AttributeValueNotByteOrStringOrGuid | The attribute found is not a String, byte[] or GUID.                                  |
| BadPutOrCreateValue                 | A Create or Put operation is being attempted with a bad value or values.              |
| BadValue                            | An update is being attempted with an bad value.                                       |

| <b>A</b>                                  | <b>B</b>   |
|---|--|
| BadValueForRangeHigh                      | Bad value has been specified for RangeHigh attribute.  |
| BadValueForRangeLow                       | Bad value has been specified for RangeLow attribute.   |
| CanOnlyReplaceParentObjectRefForUpdate    | The parent object identity can only be replaced, not removed or added.   |
| CanOnlyReplaceRdnForUpdate                | The relative distinguished name (RDN) can only be replaced, not removed or added.  |
| CantSetDistinguishedNameForCreate         | The distinguished name attribute cannot be set during object creation. It is automatically set based on the relative distinguished name (RDN) and the parent object. |
| CantSetDistinguishedNameForUpdate         | The distinguished name attribute cannot be updated. It is generated from the object's relative distinguished name (RDN) and the parent object.                       |
| CantSetObjectRefPropertyForCreate         | The object reference property attribute cannot be set during object creation. It is automatically assigned by the directory.   |
| CantSetObjectRefPropertyForUpdate         | The object reference property attribute cannot be changed. It is automatically assigned by the directory at object creation.   |
| CouldntFindObjectForMove                  | The object could not be found in the directory.  |
| CouldntFindParentObjectForCreation        | The parent object under which the new object is to be created could not be found in the directory.   |
| CouldntRetrieveRootDSEForFilter           | The RootDSE could not be retrieved from the directory. Please specify filter for the enumerate request under such circumstances.                                     |
| CreateMissingValues                       | An AttributeTypeAndValue element in the Create operation did not contain any AttributeValue elements.  |
| DuplicateAttributeWithValues              | The attribute was found more than once, and has values.  |
| DuplicateEnumerationCacheEntry            | The EnumerationCacheEntry is a duplicate entry.  |
| EmptyAttribute                            | The attribute has no value.  |
| EmptyCreate                               | The Create operation did not contain any AttributeTypeAndValue elements.   |
| EmptyPut                                  | The Put operation did not contain any Change elements.   |
| EnumContextAbsentInTheRequest             | Request must specify the enumeration context.  |
| ErrorWhileFetchingAttributeValues         | Error while retrieving values for attribute {0} from the directory.  |
| ImpersonationLevelNotSetToImpersonate     | Impersonation level not set to Impersonate or higher by caller   |
| InvalidBase64Binary                       | The base64Binary value len is not 4, or a multiple of 4.   |
| InvalidDnWithStringBinaryAccessPointValue | The DN-with-binary, DN-with-string, or access-point value is in an invalid format.   |
| InvalidEnumerationCacheEntry              | The EnumerationCacheEntry is invalid.  |
| InvalidObjectReferenceProperty            | The supplied object reference property is not valid.   |
| InvalidParentObjectRefForCreateAndUpdate  | A single value must be specified for container-hierarchy-parent attribute.   |

| <b>A</b>                             | <b>B</b>  |
|--------------------------------------|---|
| InvalidPredicate                     | An update was specified with an invalid predicate.  |
| InvalidPutSyntax                     | There is a mismatch between Put 'Operation' and the presence of an AttributeValue element       |
| MaxEnumCtxsTotalReached              | The maximum allowed number of enumeration contexts has been reached.                            |
| MissingDialect                       | Dialect not specified in the request.   |
| MissingExpression                    | A create or update is missing an attribute.   |
| MissingLowerRange                    | RangeLow attribute must be specified on the element with range qualifier.                       |
| MissingOrMultipleBaseObjectNodes     | LdapQuery filter has a missing or multiple baseobject nodes                                     |
| MissingOrMultipleFilterNodes         | LdapQuery filter has a missing or multiple filter nodes   |
| MissingOrMultipleScopeNodes          | LdapQuery filter has a missing or multiple scope nodes  |
| MissingScopeOrBaseObjectOrFilterNode | LdapQuery is missing the Scope, BaseObject or Filter node                                       |
| MissingSelectionDialect              | Selection dialect not specified in the request.   |
| MissingSortingDialect                | Sorting dialect not specified in the request.   |
| MissingTypeAttribute                 | The attribute type is missing.  |
| MissingValue                         | A create is missing the value for an attribute.   |
| MustSpecifyBaseDnForQuery            | Distinguished name search base must be supplied in the LdapQuery element.                       |
| MustSpecifyContainerForMove          | Must specify the destination container to which the object is to be moved.                      |
| MustSpecifyDnForIdentifierLookup     | Must specify the distinguished name to retrieve the object reference property.                  |
| MustSpecifyInstanceInfoInTheHeader   | Instance Information is not provided in the Request Header.                                     |
| MustSpecifyNamespace                 | An object has been found with no qualifying namespace.  |
| MustSpecifyNonNullAttrValue          | An attribute value cannot be null.  |
| MustSpecifyObjectClassForCreation    | Must specify the object class of the new object that is to be created.                          |
| MustSpecifyObjectRefPropInTheHeader  | No object reference property element is present in the request header.                          |
| MustSpecifyParentForCreation         | Must specify the parent object under which the new object is to be created.                     |
| MustSpecifyRdnForCreation            | Must specify a relative distinguished name (RDN) for the new object during object creation.     |
| MustSpecifyRdnForRename              | Must specify the relative distinguished name (RDN) to which the object is to be renamed.        |
| NewExpirationTimeNotSpecified        | New expiration time/duration for the enumeration context is not specified in the renew request. |

| A                                      | B  |
|--|--|
| NoAttrTypeAndValsPresentInTheBody      | There are no AttributeTypeAndValues present in the body to operate on.   |
| NoChangesPresentInTheBody              | There are no Changes present in the body to operate on.  |
| NoConnectionAvailable                  | No connection is currently available to process the requested operation. This is typically a transient condition.                                    |
| NoDCInstanceForGCSchemaLookup          | No Domain Controller instance was found running on the system to look up schema for the Global Catalog instance.                                     |
| NoDefaultNamingContextFoundForFilter   | Default Naming Context could not be retrieved from the directory. Please specify filter for the enumerate request under such circumstances.          |
| NoSuchEnumCtxGuidExists                | Unknown or expired enumeration context.  |
| NotCorrectFilterType                   | The supplied filter is of the wrong type.  |
| NotificationSearchControlNotAllowed    | Unsupported LDAP control. The Notification Search (1.2.840.113556.1.4.528) and Shutdown Notify (1.2.840.113556.1.4.1907) controls are not supported. |
| ObjectCreatedButIdentityUnknown        | The object was created but its object reference property could not be retrieved from the directory.  |
| ObjectInWrongNamespace                 | The object is in the wrong namespace.  |
| OperationTimeout                       | The operation timed-out.   |
| PageSizeMustBeGreaterThanOrEqualToZero | The number of items to retrieve must be greater than zero.   |
| PutOperationUnsupported                | The Put 'Operation' is invalid for this operation, or is unrecognized.   |
| ReservedConnectionInvalidated          | The connection for processing this request is unavailable. It may have been closed for being open or idle too long.                                  |
| ScopeNodeNotOneLevelNorSubtreeNorBase  | LdapQuery filter scope is not onelevel nor subtree nor base  |
| ServerTimeMustBeNonNegative            | The maximum duration for the Pull operation cannot be negative.  |
| SessionsMismatch                       | Enumeration context belongs to a different principal.  |
| SortKeyIsSpecialAttribute              | Sort key on the specified directory attribute is not supported.  |
| TooManySortKeysSpecified               | Too many sort keys were specified. Only one sort key is supported.   |
| UnknownAttribute                       | The specified attribute {0} is unknown.  |
| UnknownAttributeType                   | Unrecognized attribute found.  |
| UnknownXmlNode                         | An unknown XML node was encountered and cannot be processed.   |
| UnrecognizedDateAndTime                | Expiration time does not correspond to any of the recognized datetime or duration format patterns.   |
| UnrecognizedMaxElements                | MaxElements does not correspond to valid xs:positiveInteger data type.   |

Second table:

| A                           | B   |
|-----------------------------|---|
| EArgument                   | An ArgumentException was returned.                        |
| ECreate                     | A CreateException was returned.                           |
| EDirectoryOperation         | A DirectoryOperationException was returned.               |
| EEnumContextLimitExceeded   | An EnumerationContextLimitExceededException was returned. |
| EInvalidExpression          | An InvalidExpressionException was returned.               |
| EInvalidModifyRequestSyntax | An InvalidModifyRequestSyntaxException was returned.      |
| EInvalidOperation           | An InvalidOperationException was returned.                |
| EInvalidXml                 | An XmlException was returned.                             |
| ELdap                       | An LdapException was returned.                            |
| EModifyOperationUnsupported | An InvalidOperationException was returned.                |
| ENoConnection               | A NoConnectionAvailableException was returned.            |
| EPut                        | A PutException was returned.                              |
| ESerialization              | A SerializationException was returned.                    |
| EUnknownAttribute           | An UnknownAttributeException was returned.                |

[<10> Section 2.7](#): Microsoft implementations of Active Directory Web Services: Data Model and Common Elements accessing any AD DS or AD LDS directory service impose the same limit on the maximum number of attribute values returned as the server version to which it is connected. Active Directory behavior for range retrieval and its imposed limits on values returned are defined in [\[MS-ADTS\]](#) section 3.1.1.3.1.3.3.

[<11> Section 2.7.2](#): Microsoft implementations of Active Directory Web Services: Data Model and Common Elements, when accessing any AD DS or AD LDS directory service, impose the same limit on the maximum number of attribute values returned as the server version to which it is connected. Active Directory behavior for range retrieval and its imposed limits on values returned are defined in [\[MS-ADTS\]](#) section 3.1.1.3.1.3.3.

## 6 Change Tracking

This section identifies changes that were made to this document since the last release. Changes are classified as New, Major, Minor, Editorial, or No change.

The revision class **New** means that a new document is being released.

The revision class **Major** means that the technical content in the document was significantly revised. Major changes affect protocol interoperability or implementation. Examples of major changes are:

- A document revision that incorporates changes to interoperability requirements or functionality.
- The removal of a document from the documentation set.

The revision class **Minor** means that the meaning of the technical content was clarified. Minor changes do not affect protocol interoperability or implementation. Examples of minor changes are updates to clarify ambiguity at the sentence, paragraph, or table level.

The revision class **Editorial** means that the formatting in the technical content was changed. Editorial changes apply to grammatical, formatting, and style issues.

The revision class **No change** means that no new technical changes were introduced. Minor editorial and formatting changes may have been made, but the technical content of the document is identical to the last released version.

Major and minor changes can be described further using the following change types:

- New content added.
- Content updated.
- Content removed.
- New product behavior note added.
- Product behavior note updated.
- Product behavior note removed.
- New protocol syntax added.
- Protocol syntax updated.
- Protocol syntax removed.
- New content added due to protocol revision.
- Content updated due to protocol revision.
- Content removed due to protocol revision.
- New protocol syntax added due to protocol revision.
- Protocol syntax updated due to protocol revision.
- Protocol syntax removed due to protocol revision.
- Obsolete document removed.

Editorial changes are always classified with the change type **Editorially updated**.

Some important terms used in the change type descriptions are defined as follows:

- **Protocol syntax** refers to data elements (such as packets, structures, enumerations, and methods) as well as interfaces.
- **Protocol revision** refers to changes made to a protocol that affect the bits that are sent over the wire.

The changes made to this document are listed in the following table. For more information, please contact [dochelp@microsoft.com](mailto:dochelp@microsoft.com).

| Section                          | Tracking number (if applicable) and description  | Major change (Y or N) | Change type     |
|----------------------------------|--|-----------------------|-----------------|
| <a href="#">2.1</a><br>Endpoints | Replaced general reference "SPNEGO [RFC4178]" with ".Net Negotiate Stream protocol [MS-NNS]" and the informative reference for net.tcp binding [MSDN-BINDING] with the normative reference [MS-NMFTB]. | Y                     | Content update. |

## 7 Index

### A

[Applicability](#) 9

### C

[Change tracking](#) 46

Common elements

[endpoints](#) 10

[overview](#) 10

range retrieval

[overview](#) 24

range specifiers for requests

[overview](#) 26

[WS-Enumeration range retrieval extensions](#) 27

[WS-Transfer range retrieval extensions](#) 27

[XML view of multivalued attribute with range](#)

[option](#) 24

SOAP

[fault detail](#) 21

headers

[ad:instance](#) 19

[ad:objectReferenceProperty](#) 20

[overview](#) 19

XML

[data model](#) 12

[namespaces and URIs](#) 11

[XPath 1.0-derived selection language](#) 17

### D

Data model

common SOAP

[fault detail](#) 21

headers

[ad:instance](#) 19

[ad:objectReferenceProperty](#) 20

[overview](#) 19

[endpoints](#) 10

[overview](#) 10

range retrieval

[overview](#) 24

range specifiers for requests

[overview](#) 26

[WS-Enumeration range retrieval extensions](#) 27

[WS-Transfer range retrieval extensions](#) 27

[XML view of multivalued attribute with range](#)

[option](#) 24

[XML namespaces and URIs](#) 11

[XPath 1.0-derived selection language](#) 17

[Directory objects - XML view](#) 13

### E

[Endpoints](#) 10

[Examples](#) 29

[overview](#) 29

[WS-Enumeration Pull](#) 33

[WS-Enumeration 'Pull' Example](#) 33

[WS-Transfer Get](#) 29

[WS-Transfer 'Get' Example](#) 29

[WS-Transfer Identity Management Extension  
ModifyRequest](#) 31

[WS-Transfer Identity Management Extension  
'ModifyRequest' Example](#) 31

### F

Fields

[security index](#) 35

[vendor-extensible](#) 9

[Fields - security index](#) 35

[Fields - vendor-extensible](#) 9

### G

[Glossary](#) 5

### I

[Implementer - security considerations](#) 35

[Index of security fields](#) 35

[Informative references](#) 8

[Introduction](#) 5

### L

[Localization](#) 9

### N

[Normative references](#) 7

### O

[Object naming](#) 12

[Overview \(synopsis\)](#) 9

### P

[Product behavior](#) 36

### R

Range retrieval

[overview](#) 24

range specifiers for requests

[overview](#) 26

[WS-Enumeration range retrieval extensions](#) 27

[WS-Transfer range retrieval extensions](#) 27

[XML view of multivalued attribute with range](#)

[option](#) 24

[References](#) 7

[informative](#) 8

[normative](#) 7

[Relationship to protocols and other structures](#) 9

### S

Security

[field index](#) 35



- [fields index](#) 35
- [implementer considerations](#) 35
- SOAP
  - [fault detail](#) 21
  - headers
    - [ad:instance](#) 19
    - [ad:objectReferenceProperty](#) 20
    - [overview](#) 19
  - [Syntax mapping](#) 16
- Synthetic attributes
  - [ad:container-hierarchy-parent](#) 15
  - [ad:distinguishedName](#) 15
  - [ad:objectReferenceProperty](#) 15
  - [ad:relativeDistinguishedName](#) 16
  - [overview](#) 14

## T

- [Tracking changes](#) 46

## U

- [URIs](#) 11

## V

- [Vendor-extensible fields](#) 9
- [Versioning](#) 9

## W

- [WS-Enumeration Pull example](#) 33
- [WS-Enumeration 'Pull' Example example](#) 33
- [WS-Transfer Get example](#) 29
- [WS-Transfer 'Get' Example example](#) 29
- [WS-Transfer Identity Management Extension](#)
  - [ModifyRequest example](#) 31
- [WS-Transfer Identity Management Extension](#)
  - ['ModifyRequest' Example example](#) 31

## X

### XML

- data model
  - [object naming](#) 12
  - [overview](#) 12
  - [syntax mapping](#) 16
- synthetic attributes
  - [ad:container-hierarchy-parent](#) 15
  - [ad:distinguishedName](#) 15
  - [ad:objectReferenceProperty](#) 15
  - [ad:relativeDistinguishedName](#) 16
  - [overview](#) 14
  - [XML view of directory objects](#) 13
- [namespaces](#) 11