

[MS-ADLS-Diff]:

Active Directory Lightweight Directory Services Schema

Intellectual Property Rights Notice for Open Specifications Documentation

- **Technical Documentation.** Microsoft publishes Open Specifications documentation (“this documentation”) for protocols, file formats, data portability, computer languages, and standards as well as overviews of the interaction among each of these technologies support. Additionally, overview documents cover inter-protocol relationships and interactions.
- **Copyrights.** This documentation is covered by Microsoft copyrights. Regardless of any other terms that are contained in the terms of use for the Microsoft website that hosts this documentation, you may can make copies of it in order to develop implementations of the technologies that are described in the Open Specifications- this documentation and may can distribute portions of it in your implementations using that use these technologies or in your documentation as necessary to properly document the implementation. You may can also distribute in your implementation, with or without modification, any schema, IDL's schemas, IDLs, or code samples that are included in the documentation. This permission also applies to any documents that are referenced in the Open Specifications- documentation.
- **No Trade Secrets.** Microsoft does not claim any trade secret rights in this documentation.
- **Patents.** Microsoft has patents that may might cover your implementations of the technologies described in the Open Specifications- documentation. Neither this notice nor Microsoft's delivery of the this documentation grants any licenses under those patents or any other Microsoft patents. However, a given Open Specification may Specifications document might be covered by the Microsoft Open Specifications Promise or the Microsoft Community Promise. If you would prefer a written license, or if the technologies described in the Open Specifications this documentation are not covered by the Open Specifications Promise or Community Promise, as applicable, patent licenses are available by contacting iplg@microsoft.com.
- **Trademarks.** The names of companies and products contained in this documentation may might be covered by trademarks or similar intellectual property rights. This notice does not grant any licenses under those rights. For a list of Microsoft trademarks, visit www.microsoft.com/trademarks.
- **Fictitious Names.** The example companies, organizations, products, domain names, e-mail email addresses, logos, people, places, and events that are depicted in this documentation are fictitious. No association with any real company, organization, product, domain name, email address, logo, person, place, or event is intended or should be inferred.

Reservation of Rights. All other rights are reserved, and this notice does not grant any rights other than as specifically described above, whether by implication, estoppel, or otherwise.

Tools. The Open Specifications documentation does not require the use of Microsoft programming tools or programming environments in order for you to develop an implementation. If you have access to Microsoft programming tools and environments, you are free to take advantage of them. Certain Open Specifications documents are intended for use in conjunction with publicly available standard standards specifications and network programming art, and assumes, as such, assume that the reader either is familiar with the aforementioned material or has immediate access to it.

Revision Summary

Date	Revision History	Revision Class	Comments
2/22/2007	0.01	<u>New</u>	Version 0.01 release
6/1/2007	1.0	Major	Updated and revised the technical content.
7/3/2007	1.0.1	Editorial	Added missing description.
7/20/2007	1.0.2	Editorial	Changed language and formatting in the technical content.
8/10/2007	1.0.3	Editorial	Changed language and formatting in the technical content.
9/28/2007	1.0.4	Editorial	Changed language and formatting in the technical content.
10/23/2007	1.0.5	Editorial	Changed language and formatting in the technical content.
11/30/2007	1.0.6	Editorial	Changed language and formatting in the technical content.
1/25/2008	1.0.7	Editorial	Changed language and formatting in the technical content.
3/14/2008	1.0.8	Editorial	Changed language and formatting in the technical content.
5/16/2008	1.0.9	Editorial	Changed language and formatting in the technical content.
6/20/2008	1.0.10	Editorial	Changed language and formatting in the technical content.
7/25/2008	1.1	Minor	Clarified the meaning of the technical content.
8/29/2008	2.0	Major	Updated and revised the technical content.
10/24/2008	3.0	Major	Updated and revised the technical content.
12/5/2008	4.0	Major	Updated and revised the technical content.
1/16/2009	4.0.1	Editorial	Changed language and formatting in the technical content.
2/27/2009	4.0.2	Editorial	Changed language and formatting in the technical content.
4/10/2009	4.0.3	Editorial	Changed language and formatting in the technical content.
5/22/2009	5.0	Major	Updated and revised the technical content.
7/2/2009	6.0	Major	Updated and revised the technical content.
8/14/2009	6.0.1	Editorial	Changed language and formatting in the technical content.
9/25/2009	7.0	Major	Updated and revised the technical content.
11/6/2009	7.0.1	Editorial	Changed language and formatting in the technical content.
12/18/2009	8.0	Major	Updated and revised the technical content.
1/29/2010	9.0	Major	Updated and revised the technical content.
3/12/2010	10.0	Major	Updated and revised the technical content.
4/23/2010	11.0	Major	Updated and revised the technical content.
6/4/2010	12.0	Major	Updated and revised the technical content.
7/16/2010	12.0	None	No changes to the meaning, language, or formatting of the

Date	Revision History	Revision Class	Comments
			technical content.
8/27/2010	13.0	Major	Updated and revised the technical content.
10/8/2010	14.0	Major	Updated and revised the technical content.
11/19/2010	14.1	Minor	Clarified the meaning of the technical content.
1/7/2011	15.0	Major	Updated and revised the technical content.
2/11/2011	15.0	None	No changes to the meaning, language, or formatting of the technical content.
3/25/2011	15.0	None	No changes to the meaning, language, or formatting of the technical content.
5/6/2011	15.1	Minor	Clarified the meaning of the technical content.
6/17/2011	15.2	Minor	Clarified the meaning of the technical content.
9/23/2011	15.3	Minor	Clarified the meaning of the technical content.
12/16/2011	16.0	Major	Updated and revised the technical content.
3/30/2012	16.0	None	No changes to the meaning, language, or formatting of the technical content.
7/12/2012	16.0	None	No changes to the meaning, language, or formatting of the technical content.
10/25/2012	16.1	Minor	Clarified the meaning of the technical content.
1/31/2013	16.1	None	No changes to the meaning, language, or formatting of the technical content.
8/8/2013	17.0	Major	Updated and revised the technical content.
11/14/2013	18.0	Major	Updated and revised the technical content.
2/13/2014	18.0	None	No changes to the meaning, language, or formatting of the technical content.
5/15/2014	19.0	Major	Updated and revised the technical content.
6/30/2015	19.1	Minor	Clarified the meaning of the technical content.
10/16/2015	19.1	No Change None	No changes to the meaning, language, or formatting of the technical content.

Table of Contents

1	Introduction	13
1.1	References	13
2	Attributes	15
2.1	Attribute accountExpires	15
2.2	Attribute adminContextMenu	15
2.3	Attribute adminDescription	16
2.4	Attribute adminDisplayName	16
2.5	Attribute adminMultiselectPropertyPages.....	16
2.6	Attribute adminPropertyPages.....	17
2.7	Attribute allowedAttributes	17
2.8	Attribute allowedAttributesEffective	18
2.9	Attribute allowedChildClasses	18
2.10	Attribute allowedChildClassesEffective	18
2.11	Attribute aNR	19
2.12	Attribute appliesTo	19
2.13	Attribute assistant.....	19
2.14	Attribute attributeCertificateAttribute.....	20
2.15	Attribute attributeDisplayNames	20
2.16	Attribute attributeID	20
2.17	Attribute attributeSecurityGUID	21
2.18	Attribute attributeSyntax	21
2.19	Attribute attributeTypes	22
2.20	Attribute audio.....	22
2.21	Attribute auxiliaryClass	22
2.22	Attribute badPasswordTime	23
2.23	Attribute badPwdCount	23
2.24	Attribute bridgeheadServerListBL	23
2.25	Attribute bridgeheadTransportList	24
2.26	Attribute businessCategory.....	24
2.27	Attribute c.....	25
2.28	Attribute canonicalName	25
2.29	Attribute carLicense.....	25
2.30	Attribute classDisplayName	26
2.31	Attribute cn	26
2.32	Attribute co	27
2.33	Attribute comment	27
2.34	Attribute company.....	27
2.35	Attribute configurationFile	28
2.36	Attribute configurationFileGuid.....	28
2.37	Attribute contextMenu	28
2.38	Attribute cost	29
2.39	Attribute countryCode.....	29
2.40	Attribute createDialog.....	29
2.41	Attribute createTimeStamp.....	30
2.42	Attribute createWizardExt	30
2.43	Attribute creationWizard	30
2.44	Attribute dc.....	31
2.45	Attribute defaultClassStore.....	31
2.46	Attribute defaultGroup	31
2.47	Attribute defaultHidingValue	32
2.48	Attribute defaultObjectCategory	32
2.49	Attribute defaultSecurityDescriptor	32
2.50	Attribute department.....	33
2.51	Attribute departmentNumber.....	33

2.52	Attribute description	34
2.53	Attribute desktopProfile	34
2.54	Attribute destinationIndicator	34
2.55	Attribute directReports	35
2.56	Attribute displayName	35
2.57	Attribute displayNamePrintable	36
2.58	Attribute distinguishedName	36
2.59	Attribute dITContentRules	36
2.60	Attribute division	37
2.61	Attribute dMDLocation	37
2.62	Attribute dmdName	38
2.63	Attribute dNSHostName	38
2.64	Attribute dnsRoot	38
2.65	Attribute dSASignature	39
2.66	Attribute dSCorePropagationData	39
2.67	Attribute dSHeuristics	39
2.68	Attribute dSUIAdminMaximum	40
2.69	Attribute dSUIAdminNotification	40
2.70	Attribute dSUIShellMaximum	41
2.71	Attribute dynamicLDAPServer	41
2.72	Attribute employeeID	41
2.73	Attribute employeeNumber	42
2.74	Attribute employeeType	42
2.75	Attribute Enabled	42
2.76	Attribute enabledConnection	43
2.77	Attribute entryTTL	43
2.78	Attribute extendedAttributeInfo	44
2.79	Attribute extendedCharsAllowed	44
2.80	Attribute extendedClassInfo	44
2.81	Attribute extensionName	45
2.82	Attribute extraColumns	45
2.83	Attribute facsimileTelephoneNumber	45
2.84	Attribute fromEntry	46
2.85	Attribute fromServer	46
2.86	Attribute fSMORoleOwner	46
2.87	Attribute garbageCollPeriod	47
2.88	Attribute generatedConnection	47
2.89	Attribute generationQualifier	48
2.90	Attribute givenName	48
2.91	Attribute governsID	48
2.92	Attribute groupType	49
2.93	Attribute hasMasterNCs	49
2.94	Attribute hasPartialReplicaNCs	49
2.95	Attribute homePhone	50
2.96	Attribute homePostalAddress	50
2.97	Attribute houseIdentifier	51
2.98	Attribute iconPath	51
2.99	Attribute initials	51
2.100	Attribute instanceType	52
2.101	Attribute internationalISDNNumber	52
2.102	Attribute interSiteTopologyFailover	53
2.103	Attribute interSiteTopologyGenerator	53
2.104	Attribute interSiteTopologyRenew	53
2.105	Attribute invocationId	54
2.106	Attribute ipPhone	54
2.107	Attribute isCriticalSystemObject	54
2.108	Attribute isDefunct	55
2.109	Attribute isDeleted	55

2.110	Attribute isEphemeral	55
2.111	Attribute isMemberOfPartialAttributeSet	56
2.112	Attribute isRecycled	56
2.113	Attribute isSingleValued	57
2.114	Attribute jpegPhoto	57
2.115	Attribute keywords	57
2.116	Attribute l	58
2.117	Attribute labeledURI	58
2.118	Attribute lastAgedChange	58
2.119	Attribute lastBackupRestorationTime	59
2.120	Attribute lastKnownParent	59
2.121	Attribute lastLogonTimestamp	59
2.122	Attribute LDAPAdminLimits	60
2.123	Attribute LDAPDisplayName	60
2.124	Attribute LDAPIPDenyList	61
2.125	Attribute linkID	61
2.126	Attribute localizationDisplayId	61
2.127	Attribute location	62
2.128	Attribute lockoutTime	62
2.129	Attribute mail	62
2.130	Attribute mailAddress	63
2.131	Attribute managedBy	63
2.132	Attribute managedObjects	64
2.133	Attribute manager	64
2.134	Attribute masteredBy	64
2.135	Attribute mayContain	65
2.136	Attribute member	65
2.137	Attribute memberOf	66
2.138	Attribute middleName	66
2.139	Attribute mobile	66
2.140	Attribute modifyTimeStamp	67
2.141	Attribute moveTreeState	67
2.142	Attribute mS-DS-ConsistencyChildCount	67
2.143	Attribute mS-DS-ConsistencyGuid	68
2.144	Attribute mS-DS-ReplicatesNCREason	68
2.145	Attribute ms-DS-UserAccountAutoLocked	69
2.146	Attribute ms-DS-UserEncryptedTextPasswordAllowed	69
2.147	Attribute ms-DS-UserPasswordNotRequired	69
2.148	Attribute msDS-AllowedDNSSuffixes	70
2.149	Attribute msDS-Approx-Immed-Subordinates	70
2.150	Attribute msDS-Auxiliary-Classes	70
2.151	Attribute msDS-AzApplicationData	71
2.152	Attribute msDS-AzApplicationName	71
2.153	Attribute msDS-AzApplicationVersion	72
2.154	Attribute msDS-AzBizRule	72
2.155	Attribute msDS-AzBizRuleLanguage	72
2.156	Attribute msDS-AzClassId	73
2.157	Attribute msDS-AzDomainTimeout	73
2.158	Attribute msDS-AzGenerateAudits	73
2.159	Attribute msDS-AzGenericData	74
2.160	Attribute msDS-AzLastImportedBizRulePath	74
2.161	Attribute msDS-AzLDAPQuery	74
2.162	Attribute msDS-AzMajorVersion	75
2.163	Attribute msDS-AzMinorVersion	75
2.164	Attribute msDS-AzObjectGuid	75
2.165	Attribute msDS-AzOperationID	76
2.166	Attribute msDS-AzScopeName	76
2.167	Attribute msDS-AzScriptEngineCacheMax	77

2.168	Attribute msDS-AzScriptTimeout	77
2.169	Attribute msDS-AzTaskIsRoleDefinition	77
2.170	Attribute msDS-Behavior-Version	78
2.171	Attribute msDS-BridgeHeadServersUsed	78
2.172	Attribute msDS-DefaultNamingContext	78
2.173	Attribute msDS-DefaultNamingContextBL	79
2.174	Attribute msDS-DefaultQuota	79
2.175	Attribute msDS-DeletedObjectLifetime	79
2.176	Attribute msDS-DisableForInstances	80
2.177	Attribute msDS-DisableForInstancesBL	80
2.178	Attribute msDS-DnsRootAlias	81
2.179	Attribute msDS-EnabledFeature	81
2.180	Attribute msDS-EnabledFeatureBL	81
2.181	Attribute msDS-Entry-Time-To-Die	82
2.182	Attribute msDS-ExecuteScriptPassword	82
2.183	Attribute msDS-FilterContainers	83
2.184	Attribute msDS-HasDomainNCs	83
2.185	Attribute msDS-HasInstantiatedNCs	83
2.186	Attribute msDS-hasMasterNCs	84
2.187	Attribute msDS-IntId	84
2.188	Attribute msds-memberOfTransitive	85
2.189	Attribute msds-memberTransitive	85
2.190	Attribute msDS-LastKnownRDN	85
2.191	Attribute msDS-LocalEffectiveDeletionTime	86
2.192	Attribute msDS-LocalEffectiveRecycleTime	86
2.193	Attribute msDs-masteredBy	86
2.194	Attribute msDS-MembersForAzRole	87
2.195	Attribute msDS-MembersForAzRoleBL	87
2.196	Attribute msDS-NC-Replica-Locations	87
2.197	Attribute msDS-NCReplCursors	88
2.198	Attribute msDS-NCReplInboundNeighbors	88
2.199	Attribute msDS-NCReplOutboundNeighbors	89
2.200	Attribute msDS-Non-Security-Group-Extra-Classes	89
2.201	Attribute msDS-NonMembers	89
2.202	Attribute msDS-NonMembersBL	90
2.203	Attribute msDS-OperationsForAzRole	90
2.204	Attribute msDS-OperationsForAzRoleBL	90
2.205	Attribute msDS-OperationsForAzTask	91
2.206	Attribute msDS-OperationsForAzTaskBL	91
2.207	Attribute msDS-OptionalFeatureFlags	92
2.208	Attribute msDS-OptionalFeatureGUID	92
2.209	Attribute msDS-Other-Settings	92
2.210	Attribute msDS-parentdistingname	93
2.211	Attribute msDS-PortLDAP	93
2.212	Attribute msDS-PortSSL	93
2.213	Attribute msDS-Preferred-GC-Site	94
2.214	Attribute msDS-PrincipalName	94
2.215	Attribute msDS-QuotaAmount	94
2.216	Attribute msDS-QuotaEffective	95
2.217	Attribute msDS-QuotaTrustee	95
2.218	Attribute msDS-QuotaUsed	96
2.219	Attribute msDS-ReplAttributeMetaData	96
2.220	Attribute msDS-ReplAuthenticationMode	96
2.221	Attribute msDS-Replication-Notify-First-DSA-Delay	97
2.222	Attribute msDS-Replication-Notify-Subsequent-DSA-Delay	97
2.223	Attribute msDS-ReplicationEpoch	97
2.224	Attribute msDS-ReplValueMetaData	98
2.225	Attribute msDS-ReplValueMetaDataExt	98

2.226	Attribute msDS-RequiredDomainBehaviorVersion	99
2.227	Attribute msDS-RequiredForestBehaviorVersion	99
2.228	Attribute msDS-RetiredRepINCSignatures	99
2.229	Attribute msDs-Schema-Extensions	100
2.230	Attribute msDS-SCPContainer	100
2.231	Attribute msDS-SDReferenceDomain	100
2.232	Attribute msDS-Security-Group-Extra-Classes	101
2.233	Attribute msDS-ServiceAccount	101
2.234	Attribute msDS-ServiceAccountBL	101
2.235	Attribute msDS-ServiceAccountDNSDomain	102
2.236	Attribute msDS-Settings	102
2.237	Attribute msDS-TasksForAzRole	103
2.238	Attribute msDS-TasksForAzRoleBL	103
2.239	Attribute msDS-TasksForAzTask	103
2.240	Attribute msDS-TasksForAzTaskBL	104
2.241	Attribute msDS-TombstoneQuotaFactor	104
2.242	Attribute msDS-TopQuotaUsage	104
2.243	Attribute msDS-UpdateScript	105
2.244	Attribute msDS-User-Account-Control-Computed	105
2.245	Attribute msDS-UserAccountDisabled	105
2.246	Attribute msDS-UserDontExpirePassword	106
2.247	Attribute msDS-UserPasswordExpired	106
2.248	Attribute msDS-USNLastSyncSuccess	107
2.249	Attribute mustContain	107
2.250	Attribute name	107
2.251	Attribute nCName	108
2.252	Attribute nETBIOSName	108
2.253	Attribute networkAddress	108
2.254	Attribute nonIndexedMetadata	109
2.255	Attribute notificationList	109
2.256	Attribute ntPwdHistory	109
2.257	Attribute nTSecurityDescriptor	110
2.258	Attribute o	110
2.259	Attribute objectCategory	111
2.260	Attribute objectClass	111
2.261	Attribute objectClassCategory	111
2.262	Attribute objectClasses	112
2.263	Attribute objectGUID	112
2.264	Attribute objectSid	113
2.265	Attribute objectVersion	113
2.266	Attribute oMObjectClass	113
2.267	Attribute oMSyntax	114
2.268	Attribute options	114
2.269	Attribute otherFacsimileTelephoneNumber	114
2.270	Attribute otherHomePhone	115
2.271	Attribute otherIpPhone	115
2.272	Attribute otherMobile	116
2.273	Attribute otherPager	116
2.274	Attribute otherTelephone	116
2.275	Attribute otherWellKnownObjects	117
2.276	Attribute ou	117
2.277	Attribute owner	118
2.278	Attribute ownerBL	118
2.279	Attribute pager	118
2.280	Attribute parentGUID	119
2.281	Attribute partialAttributeDeletionList	119
2.282	Attribute partialAttributeSet	119
2.283	Attribute pekList	120

2.284	Attribute personalTitle	120
2.285	Attribute photo	121
2.286	Attribute physicalDeliveryOfficeName	121
2.287	Attribute possibleInferiors	121
2.288	Attribute possSuperiors.....	122
2.289	Attribute postalAddress.....	122
2.290	Attribute postalCode.....	122
2.291	Attribute postOfficeBox	123
2.292	Attribute preferredDeliveryMethod	123
2.293	Attribute preferredLanguage.....	124
2.294	Attribute preferredOU	124
2.295	Attribute prefixMap	124
2.296	Attribute primaryGroupToken	125
2.297	Attribute primaryInternationalISDNNumber.....	125
2.298	Attribute primaryTelexNumber.....	125
2.299	Attribute proxiedObjectName.....	126
2.300	Attribute proxyAddresses	126
2.301	Attribute pwdLastSet	127
2.302	Attribute queryFilter	127
2.303	Attribute queryPolicyBL.....	127
2.304	Attribute queryPolicyObject	128
2.305	Attribute rangeLower.....	128
2.306	Attribute rangeUpper.....	128
2.307	Attribute rDNAttID	129
2.308	Attribute registeredAddress	129
2.309	Attribute replInterval.....	130
2.310	Attribute replPropertyMetaData.....	130
2.311	Attribute replTopologyStayOfExecution	130
2.312	Attribute replUpToDateVector	131
2.313	Attribute repsFrom	131
2.314	Attribute repsTo.....	132
2.315	Attribute retiredReplDSASignatures	132
2.316	Attribute revision	132
2.317	Attribute rightsGuid.....	133
2.318	Attribute roomNumber.....	133
2.319	Attribute rootTrust	133
2.320	Attribute schedule.....	134
2.321	Attribute schemaFlagsEx.....	134
2.322	Attribute schemaIDGUID.....	135
2.323	Attribute schemaInfo	135
2.324	Attribute schemaUpdate.....	135
2.325	Attribute schemaVersion	136
2.326	Attribute scopeFlags	136
2.327	Attribute sDRightsEffective	136
2.328	Attribute searchFlags.....	137
2.329	Attribute searchGuide	137
2.330	Attribute secretary	137
2.331	Attribute seeAlso.....	138
2.332	Attribute serialNumber.....	138
2.333	Attribute serverReference	139
2.334	Attribute serverReferenceBL	139
2.335	Attribute shellContextMenu	139
2.336	Attribute shellPropertyPages.....	140
2.337	Attribute showInAdvancedViewOnly.....	140
2.338	Attribute siteLinkList.....	140
2.339	Attribute siteList	141
2.340	Attribute siteObject	141
2.341	Attribute siteObjectBL.....	142

2.342	Attribute siteServer	142
2.343	Attribute sn	142
2.344	Attribute sourceObjectGuid	143
2.345	Attribute st	143
2.346	Attribute street	143
2.347	Attribute streetAddress	144
2.348	Attribute structuralObjectClass	144
2.349	Attribute subClassOf	145
2.350	Attribute subRefs	145
2.351	Attribute subSchemaSubEntry	145
2.352	Attribute superiorDNSRoot	146
2.353	Attribute supplementalCredentials	146
2.354	Attribute systemAuxiliaryClass	146
2.355	Attribute systemFlags	147
2.356	Attribute systemMayContain	147
2.357	Attribute systemMustContain	148
2.358	Attribute systemOnly	148
2.359	Attribute systemPossSuperiors	148
2.360	Attribute telephoneNumber	149
2.361	Attribute teletexTerminalIdentifier	149
2.362	Attribute telexNumber	149
2.363	Attribute thumbnailLogo	150
2.364	Attribute thumbnailPhoto	150
2.365	Attribute title	151
2.366	Attribute tokenGroups	151
2.367	Attribute tombstoneLifetime	151
2.368	Attribute transportAddressAttribute	152
2.369	Attribute transportDLLName	152
2.370	Attribute transportType	153
2.371	Attribute treatAsLeaf	153
2.372	Attribute trustParent	153
2.373	Attribute uid	154
2.374	Attribute unicodePwd	154
2.375	Attribute uPNSuffixes	154
2.376	Attribute url	155
2.377	Attribute userCertificate	155
2.378	Attribute userParameters	156
2.379	Attribute userPassword	156
2.380	Attribute userPKCS12	156
2.381	Attribute userPrincipalName	157
2.382	Attribute userSMIMECertificate	157
2.383	Attribute uSNChanged	158
2.384	Attribute uSNCreated	158
2.385	Attribute uSNSALastObjRemoved	158
2.386	Attribute USNIntersite	159
2.387	Attribute uSNLastObjRem	159
2.388	Attribute uSNSource	159
2.389	Attribute validAccesses	160
2.390	Attribute wbemPath	160
2.391	Attribute wellKnownObjects	160
2.392	Attribute whenChanged	161
2.393	Attribute whenCreated	161
2.394	Attribute wWWHomePage	162
2.395	Attribute x121Address	162
2.396	Attribute x500uniqueIdentifier	163
3	Classes	164
3.1	Class applicationSettings	164

3.2	Class applicationSiteSettings	164
3.3	Class attributeSchema	165
3.4	Class classSchema	165
3.5	Class configuration	166
3.6	Class container	166
3.7	Class controlAccessRight	167
3.8	Class country	167
3.9	Class crossRef	167
3.10	Class crossRefContainer	168
3.11	Class displaySpecifier	168
3.12	Class dMD	169
3.13	Class domain	169
3.14	Class domainDNS	170
3.15	Class dSUISettings	170
3.16	Class dynamicObject	170
3.17	Class foreignSecurityPrincipal	171
3.18	Class group	171
3.19	Class groupOfNames	172
3.20	Class inetOrgPerson	172
3.21	Class interSiteTransport	173
3.22	Class interSiteTransportContainer	173
3.23	Class leaf	173
3.24	Class locality	174
3.25	Class lostAndFound	174
3.26	Class msDS-AzAdminManager	175
3.27	Class msDS-AzApplication	175
3.28	Class msDS-AzOperation	176
3.29	Class msDS-AzRole	176
3.30	Class msDS-AzScope	176
3.31	Class msDS-AzTask	177
3.32	Class msDS-BindableObject	177
3.33	Class msDS-BindProxy	178
3.34	Class msDS-OptionalFeature	178
3.35	Class msDS-QuotaContainer	179
3.36	Class msDS-QuotaControl	179
3.37	Class msDS-ServiceConnectionPointPublicationService	180
3.38	Class nTDSConnection	180
3.39	Class nTDSDSA	180
3.40	Class nTDSservice	181
3.41	Class nTDSsiteSettings	181
3.42	Class organizationalPerson	182
3.43	Class organization	182
3.44	Class organizationalUnit	183
3.45	Class person	183
3.46	Class queryPolicy	184
3.47	Class securityPrincipal	184
3.48	Class server	185
3.49	Class serversContainer	185
3.50	Class site	185
3.51	Class siteLink	186
3.52	Class siteLinkBridge	186
3.53	Class sitesContainer	187
3.54	Class subnet	187
3.55	Class subnetContainer	188
3.56	Class subSchema	188
3.57	Class syncEngineAuxConfiguration	188
3.58	Class syncEngineAuxObject	189
3.59	Class top	189

3.60	Class userProxy	190
3.61	Class userProxyFull	190
3.62	Class user	191
4	Change Tracking.....	192
5	Index.....	193

1 Introduction

Active Directory Lightweight Directory Services Schema contains a list of the objects that exist in the Active Directory Lightweight Directory Services (AD LDS) schema. Active Directory and all associated terms and concepts are described in the document titled "Active Directory Technical Specification", which has the following normative reference:

[MS-ADTS] Microsoft Corporation, "Active Directory Technical Specification".

Note This document is not intended to stand on its own; it is intended to act as an appendix to the Active Directory Technical Specification, as specified in the normative reference shown above. For details about the Active Directory schema, see [MS-ADTS] section 3.1.1.2 (Active Directory Schema).

Note The object definitions in this document are also available for download in LDAP Data Interchange Format (LDIF) at the following location: [MSFT-ADSCHEMA].

1.1 References

[JFIF] Hamilton, E., "JPEG File Interchange Format, Version 1.02", September 1992, <http://www.w3.org/Graphics/JPEG/jfif.txt>

[MS-ADOD] Microsoft Corporation, "Active Directory Protocols Overview".

[MS-ADTS] Microsoft Corporation, "Active Directory Technical Specification".

[MS-DTYP] Microsoft Corporation, "Windows Data Types".

[MSDN-ExtUserIntDirObj] Microsoft Corporation, "Extending the User Interface for Directory Objects", <http://msdn.microsoft.com/en-us/library/ms676902.aspx>

[MSDN-GroupType] Microsoft Corporation, "Group-Type", <http://msdn.microsoft.com/en-us/library/ms675935.aspx>

[MSFT-ADSCHEMA] Microsoft Corporation, "Combined Active Directory Schema Classes and Attributes for Windows Server", February 2011, <http://www.microsoft.com/downloads/en/details.aspx?displaylang=en&FamilyID=da2fc73a-3d35-484c-9bea-f023dcb7275>

[RFC2251] Wahl, M., Howes, T., and Kille, S., "Lightweight Directory Access Protocol (v3)", RFC 2251, December 1997, <http://www.ietf.org/rfc/rfc2251.txt>

[RFC2849] Good, G., "The LDAP Data Interchange Format (LDIF) - Technical Specification", RFC 2849, June 2000, <http://www.ietf.org/rfc/rfc2849.txt>

[RFC3280] Housley, R., Polk, W., Ford, W., and Solo, D., "Internet X.509 Public Key Infrastructure Certificate and Certificate Revocation List (CRL) Profile", RFC 3280, April 2002, <http://www.ietf.org/rfc/rfc3280.txt>

[RFC822] Crocker, D.H., "Standard for ARPA Internet Text Messages", STD 11, RFC 822, August 1982, <http://www.ietf.org/rfc/rfc0822.txt>

[X121] ITU-T, "Public data networks - Network aspects - International numbering plan for public data networks", Recommendation X.121, October 2000, <http://www.itu.int/rec/T-REC-X.121/en>

[X500] ITU-T, "Information Technology - Open Systems Interconnection - The Directory: Overview of Concepts, Models and Services", Recommendation X.500, August 2005, <http://www.itu.int/rec/T-REC-X.500-200508-S/en>

Note There is a charge to download the specification.

2 Attributes

~~Note: Some of the information in this section is subject to change because it applies to a preliminary product version, and thus may differ from the final version of the software when released. All behavior notes that pertain to the preliminary product version contain specific references to it as an aid to the reader.~~

The following sections specify the attributes in the Active Directory Lightweight Directory Services schema.

These sections normatively specify the schema definition of each attribute and version-specific behavior of those schema definitions (such as when the attribute was added to the schema). Additionally, as an aid to the reader some of the sections include informative notes about how the attribute can be used.

Note Lines of text in the attribute definitions that are excessively long have been "folded" in accordance with [RFC2849] Note 2.

2.1 Attribute accountExpires

This attribute specifies the date when an account expires. This value represents the number of 100-nanosecond intervals since January 1, 1601, Coordinated Universal Time (Greenwich Mean Time). A value of 0 or 0x7FFFFFFFFFFFFFFF (9223372036854775807) indicates that the account never expires.

```
cn: Account-Expires
ldapDisplayName: accountExpires
attributeId: 1.2.840.113556.1.4.159
attributeSyntax: 2.5.5.16
omSyntax: 65
isSingleValued: TRUE
schemaIdGuid: bf967915-0de6-11d0-a285-00aa003049e2
systemOnly: FALSE
searchFlags: fCOPY
attributeSecurityGuid: 4c164200-20c0-11d0-a768-00aa006e0529
systemFlags: FLAG_SCHEMA_BASE_OBJECT
```

Version-Specific Behavior: Implemented on Active Directory Application Mode (ADAM), Windows Server 2008 operating system, Active Directory Lightweight Directory Services (AD LDS) for Windows Vista, Windows Server 2008 R2 operating system, Active Directory Lightweight Directory Services (AD LDS) for Windows 7, Windows Server 2012 operating system, Active Directory Lightweight Directory Services (AD LDS) for Windows 8 operating system, Windows Server 2012 R2 operating system, Active Directory Lightweight Directory Services (AD LDS) for Windows 8.1 operating system, Windows Server 2016 ~~Technical Preview~~ operating system, and Active Directory Lightweight Directory Services (AD LDS) for Windows 10 operating system.

2.2 Attribute adminContextMenu

This attribute specifies the order number and globally unique identifier (GUID) of the context menu to be used on administration screens. GUID is defined in [MS-DTYP] section 2.3.4.

```
cn: Admin-Context-Menu
ldapDisplayName: adminContextMenu
attributeId: 1.2.840.113556.1.4.614
attributeSyntax: 2.5.5.12
omSyntax: 64
isSingleValued: FALSE
schemaIdGuid: 553fd038-f32e-11d0-b0bc-00c04fd8dca6
```

```
systemOnly: FALSE
```

Version-Specific Behavior: Implemented on Windows Server 2008, AD LDS for Windows Vista, Windows Server 2008 R2, AD LDS for Windows 7, Windows Server 2012, AD LDS for Windows 8, Windows Server 2012 R2, AD LDS for Windows 8.1, Windows Server 2016 ~~Technical Preview~~, and AD LDS for Windows 10.

2.3 Attribute adminDescription

This attribute specifies the description displayed on administration screens.

```
cn: Admin-Description
ldapDisplayName: adminDescription
attributeId: 1.2.840.113556.1.2.226
attributeSyntax: 2.5.5.12
omSyntax: 64
isSingleValued: TRUE
schemaIdGuid: bf967919-0de6-11d0-a285-00aa003049e2
systemOnly: FALSE
searchFlags: 0
rangeLower: 0
rangeUpper: 1024
attributeSecurityGuid: 59ba2f42-79a2-11d0-9020-00c04fc2d3cf
systemFlags: FLAG_SCHEMA_BASE_OBJECT
```

Version-Specific Behavior: Implemented on ADAM, Windows Server 2008, AD LDS for Windows Vista, Windows Server 2008 R2, AD LDS for Windows 7, Windows Server 2012, AD LDS for Windows 8, Windows Server 2012 R2, AD LDS for Windows 8.1, Windows Server 2016 ~~Technical Preview~~, and AD LDS for Windows 10.

2.4 Attribute adminDisplayName

This attribute specifies the name displayed on administration screens.

```
cn: Admin-Display-Name
ldapDisplayName: adminDisplayName
attributeId: 1.2.840.113556.1.2.194
attributeSyntax: 2.5.5.12
omSyntax: 64
isSingleValued: TRUE
schemaIdGuid: bf96791a-0de6-11d0-a285-00aa003049e2
systemOnly: FALSE
searchFlags: 0
rangeLower: 1
rangeUpper: 256
systemFlags: FLAG_SCHEMA_BASE_OBJECT
```

Version-Specific Behavior: Implemented on ADAM, Windows Server 2008, AD LDS for Windows Vista, Windows Server 2008 R2, AD LDS for Windows 7, Windows Server 2012, AD LDS for Windows 8, Windows Server 2012 R2, AD LDS for Windows 8.1, Windows Server 2016 ~~Technical Preview~~, and AD LDS for Windows 10.

2.5 Attribute adminMultiselectPropertyPages

A multivalued attribute whose values are a number representing the order in which the pages are added and a GUID of a component object model (COM) object that implements multiselect property pages for the Active Directory Users and Computers snap-in.


```
cn: Admin-Multiselect-Property-Pages
ldapDisplayName: adminMultiselectPropertyPages
attributeId: 1.2.840.113556.1.4.1690
attributeSyntax: 2.5.5.12
omSyntax: 64
isSingleValued: FALSE
schemaIdGuid: 18f9b67d-5ac6-4b3b-97db-d0a406afb7ba
systemOnly: FALSE
```

Version-Specific Behavior: Implemented on Windows Server 2008, AD LDS for Windows Vista, Windows Server 2008 R2, AD LDS for Windows 7, Windows Server 2012, AD LDS for Windows 8, Windows Server 2012 R2, AD LDS for Windows 8.1, Windows Server 2016 ~~Technical Preview~~, and AD LDS for Windows 10.

2.6 Attribute adminPropertyPages

This attribute specifies the order number and GUID of the property pages for an object to be displayed on Active Directory administration screens. For more information, see the document "Extending the User Interface for Directory Objects" [MSDN-ExtUserIntDirObj].

```
cn: Admin-Property-Pages
ldapDisplayName: adminPropertyPages
attributeId: 1.2.840.113556.1.4.562
attributeSyntax: 2.5.5.12
omSyntax: 64
isSingleValued: FALSE
schemaIdGuid: 52458038-ca6a-11d0-afff-0000f80367c1
systemOnly: FALSE
```

Version-Specific Behavior: Implemented on Windows Server 2008, AD LDS for Windows Vista, Windows Server 2008 R2, AD LDS for Windows 7, Windows Server 2012, AD LDS for Windows 8, Windows Server 2012 R2, AD LDS for Windows 8.1, Windows Server 2016 ~~Technical Preview~~, and AD LDS for Windows 10.

2.7 Attribute allowedAttributes

This attribute specifies attributes that are permitted to be assigned to a class.

```
cn: Allowed-Attributes
ldapDisplayName: allowedAttributes
attributeId: 1.2.840.113556.1.4.913
attributeSyntax: 2.5.5.2
omSyntax: 6
isSingleValued: FALSE
schemaIdGuid: 9a7ad940-ca53-11d1-bbd0-0080c76670c0
systemOnly: TRUE
searchFlags: 0
attributeSecurityGuid: e48d0154-bcf8-11d1-8702-00c04fb96050
systemFlags: FLAG_SCHEMA_BASE_OBJECT | FLAG_ATTR_IS_CONSTRUCTED |
FLAG_DOMAIN_DISALLOW_RENAME
```

Version-Specific Behavior: Implemented on ADAM, Windows Server 2008, AD LDS for Windows Vista, Windows Server 2008 R2, AD LDS for Windows 7, Windows Server 2012, AD LDS for Windows 8, Windows Server 2012 R2, AD LDS for Windows 8.1, Windows Server 2016 ~~Technical Preview~~, and AD LDS for Windows 10.

2.8 Attribute allowedAttributesEffective

This attribute specifies a list of attributes that can be modified on the object.

```
cn: Allowed-Attributes-Effective
ldapDisplayName: allowedAttributesEffective
attributeId: 1.2.840.113556.1.4.914
attributeSyntax: 2.5.5.2
omSyntax: 6
isSingleValued: FALSE
schemaIdGuid: 9a7ad941-ca53-11d1-bbd0-0080c76670c0
systemOnly: TRUE
searchFlags: 0
attributeSecurityGuid: e48d0154-bcf8-11d1-8702-00c04fb96050
systemFlags: FLAG_SCHEMA_BASE_OBJECT | FLAG_ATTR_IS_CONSTRUCTED |
FLAG_DOMAIN_DISALLOW_RENAME
```

Version-Specific Behavior: Implemented on ADAM, Windows Server 2008, AD LDS for Windows Vista, Windows Server 2008 R2, AD LDS for Windows 7, Windows Server 2012, AD LDS for Windows 8, Windows Server 2012 R2, AD LDS for Windows 8.1, Windows Server 2016 ~~Technical Preview~~, and AD LDS for Windows 10.

2.9 Attribute allowedChildClasses

This attribute specifies classes that may be contained by a class.

```
cn: Allowed-Child-Classes
ldapDisplayName: allowedChildClasses
attributeId: 1.2.840.113556.1.4.911
attributeSyntax: 2.5.5.2
omSyntax: 6
isSingleValued: FALSE
schemaIdGuid: 9a7ad942-ca53-11d1-bbd0-0080c76670c0
systemOnly: TRUE
searchFlags: 0
attributeSecurityGuid: e48d0154-bcf8-11d1-8702-00c04fb96050
systemFlags: FLAG_SCHEMA_BASE_OBJECT | FLAG_ATTR_IS_CONSTRUCTED |
FLAG_DOMAIN_DISALLOW_RENAME
```

Version-Specific Behavior: Implemented on ADAM, Windows Server 2008, AD LDS for Windows Vista, Windows Server 2008 R2, AD LDS for Windows 7, Windows Server 2012, AD LDS for Windows 8, Windows Server 2012 R2, AD LDS for Windows 8.1, Windows Server 2016 ~~Technical Preview~~, and AD LDS for Windows 10.

2.10 Attribute allowedChildClassesEffective

This attribute specifies a list of classes that can be modified.

```
cn: Allowed-Child-Classes-Effective
ldapDisplayName: allowedChildClassesEffective
attributeId: 1.2.840.113556.1.4.912
attributeSyntax: 2.5.5.2
omSyntax: 6
isSingleValued: FALSE
schemaIdGuid: 9a7ad943-ca53-11d1-bbd0-0080c76670c0
systemOnly: TRUE
searchFlags: 0
attributeSecurityGuid: e48d0154-bcf8-11d1-8702-00c04fb96050
systemFlags: FLAG_SCHEMA_BASE_OBJECT | FLAG_ATTR_IS_CONSTRUCTED |
```

FLAG_DOMAIN_DISALLOW_RENAME

Version-Specific Behavior: Implemented on ADAM, Windows Server 2008, AD LDS for Windows Vista, Windows Server 2008 R2, AD LDS for Windows 7, Windows Server 2012, AD LDS for Windows 8, Windows Server 2012 R2, AD LDS for Windows 8.1, Windows Server 2016 ~~Technical Preview~~, and AD LDS for Windows 10.

2.11 Attribute aNR

This attribute specifies whether ambiguous name resolution is to be used when choosing between objects.

```
cn: ANR
ldapDisplayName: aNR
attributeId: 1.2.840.113556.1.4.1208
attributeSyntax: 2.5.5.12
omSyntax: 64
isSingleValued: TRUE
schemaIdGuid: 45b01500-c419-11d1-bbc9-0080c76670c0
systemOnly: FALSE
searchFlags: 0
systemFlags: FLAG_SCHEMA_BASE_OBJECT | FLAG_ATTR_IS_CONSTRUCTED |
FLAG_DOMAIN_DISALLOW_RENAME
```

Version-Specific Behavior: Implemented on ADAM, Windows Server 2008, AD LDS for Windows Vista, Windows Server 2008 R2, AD LDS for Windows 7, Windows Server 2012, AD LDS for Windows 8, Windows Server 2012 R2, AD LDS for Windows 8.1, Windows Server 2016 ~~Technical Preview~~, and AD LDS for Windows 10.

2.12 Attribute appliesTo

This attribute contains the list of object classes that the extended right applies to. In the list, an object class is represented by the schemaIDGUID property for its schemaClass object.

```
cn: Applies-To
ldapDisplayName: appliesTo
attributeId: 1.2.840.113556.1.4.341
attributeSyntax: 2.5.5.12
omSyntax: 64
isSingleValued: FALSE
schemaIdGuid: 8297931d-86d3-11d0-afda-00c04fd930c9
systemOnly: FALSE
searchFlags: 0
rangeLower: 36
rangeUpper: 36
systemFlags: FLAG_SCHEMA_BASE_OBJECT
```

Version-Specific Behavior: Implemented on ADAM, Windows Server 2008, AD LDS for Windows Vista, Windows Server 2008 R2, AD LDS for Windows 7, Windows Server 2012, AD LDS for Windows 8, Windows Server 2012 R2, AD LDS for Windows 8.1, Windows Server 2016 ~~Technical Preview~~, and AD LDS for Windows 10.

2.13 Attribute assistant

This attribute specifies the distinguished name (DN) of a user's administrative assistant.

```
cn: Assistant
```

```
ldapDisplayName: assistant
attributeId: 1.2.840.113556.1.4.652
attributeSyntax: 2.5.5.1
omSyntax: 127
omObjectClass: 1.3.12.2.1011.28.0.714
isSingleValued: TRUE
schemaIdGuid: 0296c11c-40da-11d1-a9c0-0000f80367c1
systemOnly: FALSE
searchFlags: fCOPY
attributeSecurityGuid: 77b5b886-944a-11d1-aebd-0000f80367c1
```

Version-Specific Behavior: Implemented on ADAM, Windows Server 2008, AD LDS for Windows Vista, Windows Server 2008 R2, AD LDS for Windows 7, Windows Server 2012, AD LDS for Windows 8, Windows Server 2012 R2, AD LDS for Windows 8.1, Windows Server 2016 ~~Technical Preview~~, and AD LDS for Windows 10.

2.14 Attribute attributeCertificateAttribute

This attribute specifies a digitally signed or certified identity and set of attributes. It is used to bind authorization information to an identity.

```
cn: attributeCertificateAttribute
ldapDisplayName: attributeCertificateAttribute
attributeId: 2.5.4.58
attributeSyntax: 2.5.5.10
omSyntax: 4
isSingleValued: FALSE
schemaIdGuid: fa4693bb-7bc2-4cb9-81a8-c99c43b7905e
systemOnly: FALSE
searchFlags: 0
```

Version-Specific Behavior: Implemented on ADAM, Windows Server 2008, AD LDS for Windows Vista, Windows Server 2008 R2, AD LDS for Windows 7, Windows Server 2012, AD LDS for Windows 8, Windows Server 2012 R2, AD LDS for Windows 8.1, Windows Server 2016 ~~Technical Preview~~, and AD LDS for Windows 10.

2.15 Attribute attributeDisplayNames

This attribute specifies the name to be displayed for this object.

```
cn: Attribute-Display-Names
ldapDisplayName: attributeDisplayNames
attributeId: 1.2.840.113556.1.4.748
attributeSyntax: 2.5.5.12
omSyntax: 64
isSingleValued: FALSE
schemaIdGuid: cb843f80-48d9-11d1-a9c3-0000f80367c1
systemOnly: FALSE
```

Version-Specific Behavior: Implemented on Windows Server 2008, AD LDS for Windows Vista, Windows Server 2008 R2, AD LDS for Windows 7, Windows Server 2012, AD LDS for Windows 8, Windows Server 2012 R2, AD LDS for Windows 8.1, Windows Server 2016 ~~Technical Preview~~, and AD LDS for Windows 10.

2.16 Attribute attributeID

This attribute specifies the unique X.500 object identifier (OID) that identifies an attribute. For more information, see [X500].

```
cn: Attribute-ID
ldapDisplayName: attributeID
attributeId: 1.2.840.113556.1.2.30
attributeSyntax: 2.5.5.2
omSyntax: 6
isSingleValued: TRUE
schemaIdGuid: bf967922-0de6-11d0-a285-00aa003049e2
systemOnly: TRUE
searchFlags: fPRESERVEONDELETE
systemFlags: FLAG_SCHEMA_BASE_OBJECT
```

Version-Specific Behavior: Implemented on ADAM, Windows Server 2008, AD LDS for Windows Vista, Windows Server 2008 R2, AD LDS for Windows 7, Windows Server 2012, AD LDS for Windows 8, Windows Server 2012 R2, AD LDS for Windows 8.1, Windows Server 2016 ~~Technical Preview~~, and AD LDS for Windows 10.

2.17 Attribute attributeSecurityGUID

This attribute specifies the GUID to be used to apply security credentials to a set of objects.

```
cn: Attribute-Security-GUID
ldapDisplayName: attributeSecurityGUID
attributeId: 1.2.840.113556.1.4.149
attributeSyntax: 2.5.5.10
omSyntax: 4
isSingleValued: TRUE
schemaIdGuid: bf967924-0de6-11d0-a285-00aa003049e2
systemOnly: FALSE
searchFlags: 0
rangeLower: 16
rangeUpper: 16
systemFlags: FLAG_SCHEMA_BASE_OBJECT
```

Version-Specific Behavior: Implemented on ADAM, Windows Server 2008, AD LDS for Windows Vista, Windows Server 2008 R2, AD LDS for Windows 7, Windows Server 2012, AD LDS for Windows 8, Windows Server 2012 R2, AD LDS for Windows 8.1, Windows Server 2016 ~~Technical Preview~~, and AD LDS for Windows 10.

2.18 Attribute attributeSyntax

This attribute specifies the OID for the syntax for this attribute.

```
cn: Attribute-Syntax
ldapDisplayName: attributeSyntax
attributeId: 1.2.840.113556.1.2.32
attributeSyntax: 2.5.5.2
omSyntax: 6
isSingleValued: TRUE
schemaIdGuid: bf967925-0de6-11d0-a285-00aa003049e2
systemOnly: TRUE
searchFlags: fPRESERVEONDELETE
systemFlags: FLAG_SCHEMA_BASE_OBJECT
```

Version-Specific Behavior: Implemented on ADAM, Windows Server 2008, AD LDS for Windows Vista, Windows Server 2008 R2, AD LDS for Windows 7, Windows Server 2012, AD LDS for Windows 8, Windows Server 2012 R2, AD LDS for Windows 8.1, Windows Server 2016 ~~Technical Preview~~, and AD LDS for Windows 10.

2.19 Attribute attributeTypes

This attribute specifies a multivalued property containing strings that represent each attribute in the schema.

```
cn: Attribute-Types
ldapDisplayName: attributeTypes
attributeId: 2.5.21.5
attributeSyntax: 2.5.5.12
omSyntax: 64
isSingleValued: FALSE
schemaIdGuid: 9a7ad944-ca53-11d1-bbd0-0080c76670c0
systemOnly: TRUE
searchFlags: 0
systemFlags: FLAG_SCHEMA_BASE_OBJECT | FLAG_ATTR_IS_CONSTRUCTED |
FLAG_DOMAIN_DISALLOW_RENAME
```

Version-Specific Behavior: Implemented on ADAM, Windows Server 2008, AD LDS for Windows Vista, Windows Server 2008 R2, AD LDS for Windows 7, Windows Server 2012, AD LDS for Windows 8, Windows Server 2012 R2, AD LDS for Windows 8.1, Windows Server 2016 ~~Technical Preview~~, and AD LDS for Windows 10.

2.20 Attribute audio

This attribute allows the storing of sounds in Active Directory.

```
cn: audio
ldapDisplayName: audio
attributeId: 0.9.2342.19200300.100.1.55
attributeSyntax: 2.5.5.10
omSyntax: 4
isSingleValued: FALSE
schemaIdGuid: d0e1d224-e1a0-42ce-a2da-793ba5244f35
systemOnly: FALSE
searchFlags: 0
rangeUpper: 250000
showInAdvancedViewOnly: FALSE
```

Version-Specific Behavior: Implemented on ADAM, Windows Server 2008, AD LDS for Windows Vista, Windows Server 2008 R2, AD LDS for Windows 7, Windows Server 2012, AD LDS for Windows 8, Windows Server 2012 R2, AD LDS for Windows 8.1, Windows Server 2016 ~~Technical Preview~~, and AD LDS for Windows 10.

2.21 Attribute auxiliaryClass

This attribute specifies the list of auxiliary classes to be associated with this class.

```
cn: Auxiliary-Class
ldapDisplayName: auxiliaryClass
attributeId: 1.2.840.113556.1.2.351
attributeSyntax: 2.5.5.2
omSyntax: 6
isSingleValued: FALSE
schemaIdGuid: bf96792c-0de6-11d0-a285-00aa003049e2
systemOnly: FALSE
searchFlags: 0
systemFlags: FLAG_SCHEMA_BASE_OBJECT
```

Version-Specific Behavior: Implemented on ADAM, Windows Server 2008, AD LDS for Windows Vista, Windows Server 2008 R2, AD LDS for Windows 7, Windows Server 2012, AD LDS for Windows 8, Windows Server 2012 R2, AD LDS for Windows 8.1, Windows Server 2016 ~~Technical Preview~~, and AD LDS for Windows 10.

2.22 Attribute badPasswordTime

This attribute specifies the last time and date that an attempt to log on to this account was made using an invalid password. This value is stored as a large integer that represents the number of 100-nanosecond intervals since January 1, 1601 (UTC). A value of zero means that the last "bad password time" is unknown.

```
cn: Bad-Password-Time
ldapDisplayName: badPasswordTime
attributeId: 1.2.840.113556.1.4.49
attributeSyntax: 2.5.5.16
omSyntax: 65
isSingleValued: TRUE
schemaIdGuid: bf96792d-0de6-11d0-a285-00aa003049e2
systemOnly: TRUE
searchFlags: 0
systemFlags: FLAG_SCHEMA_BASE_OBJECT | FLAG_ATTR_NOT_REPLICATED
```

Version-Specific Behavior: Implemented on ADAM, Windows Server 2008, AD LDS for Windows Vista, Windows Server 2008 R2, AD LDS for Windows 7, Windows Server 2012, AD LDS for Windows 8, Windows Server 2012 R2, AD LDS for Windows 8.1, Windows Server 2016 ~~Technical Preview~~, and AD LDS for Windows 10.

2.23 Attribute badPwdCount

This attribute specifies the number of times the user tried to log on to the account by using an incorrect password. A value of 0 indicates that the value is unknown.

```
cn: Bad-Pwd-Count
ldapDisplayName: badPwdCount
attributeId: 1.2.840.113556.1.4.12
attributeSyntax: 2.5.5.9
omSyntax: 2
isSingleValued: TRUE
schemaIdGuid: bf96792e-0de6-11d0-a285-00aa003049e2
systemOnly: TRUE
searchFlags: 0
attributeSecurityGuid: 5f202010-79a5-11d0-9020-00c04fc2d4cf
systemFlags: FLAG_SCHEMA_BASE_OBJECT | FLAG_ATTR_NOT_REPLICATED
```

Version-Specific Behavior: Implemented on ADAM, Windows Server 2008, AD LDS for Windows Vista, Windows Server 2008 R2, AD LDS for Windows 7, Windows Server 2012, AD LDS for Windows 8, Windows Server 2012 R2, AD LDS for Windows 8.1, Windows Server 2016 ~~Technical Preview~~, and AD LDS for Windows 10.

2.24 Attribute bridgeheadServerListBL

This attribute is the back link attribute of bridgeheadServerList and contains the list of servers that are bridgeheads for replication.

```
cn: Bridgehead-Server-List-BL
ldapDisplayName: bridgeheadServerListBL
attributeId: 1.2.840.113556.1.4.820
```

```
attributeSyntax: 2.5.5.1
omSyntax: 127
omObjectClass: 1.3.12.2.1011.28.0.714
isSingleValued: FALSE
schemaIdGuid: d50c2cdb-8951-11d1-aebc-0000f80367c1
systemOnly: TRUE
searchFlags: 0
linkID: 99
systemFlags: FLAG_SCHEMA_BASE_OBJECT | FLAG_ATTR_NOT_REPLICATED
```

Version-Specific Behavior: Implemented on ADAM, Windows Server 2008, AD LDS for Windows Vista, Windows Server 2008 R2, AD LDS for Windows 7, Windows Server 2012, AD LDS for Windows 8, Windows Server 2012 R2, AD LDS for Windows 8.1, Windows Server 2016 ~~Technical Preview~~, and AD LDS for Windows 10.

2.25 Attribute bridgeheadTransportList

This attribute specifies transports for which this server is a bridgehead.

```
cn: Bridgehead-Transport-List
ldapDisplayName: bridgeheadTransportList
attributeId: 1.2.840.113556.1.4.819
attributeSyntax: 2.5.5.1
omSyntax: 127
omObjectClass: 1.3.12.2.1011.28.0.714
isSingleValued: FALSE
schemaIdGuid: d50c2cda-8951-11d1-aebc-0000f80367c1
systemOnly: FALSE
searchFlags: 0
linkID: 98
systemFlags: FLAG_SCHEMA_BASE_OBJECT
```

Version-Specific Behavior: Implemented on ADAM, Windows Server 2008, AD LDS for Windows Vista, Windows Server 2008 R2, AD LDS for Windows 7, Windows Server 2012, AD LDS for Windows 8, Windows Server 2012 R2, AD LDS for Windows 8.1, Windows Server 2016 ~~Technical Preview~~, and AD LDS for Windows 10.

2.26 Attribute businessCategory

This attribute specifies descriptive text on an organizational unit.

```
cn: Business-Category
ldapDisplayName: businessCategory
attributeId: 2.5.4.15
attributeSyntax: 2.5.5.12
omSyntax: 64
isSingleValued: FALSE
schemaIdGuid: bf967931-0de6-11d0-a285-00aa003049e2
systemOnly: FALSE
searchFlags: 0
rangeLower: 1
rangeUpper: 128
systemFlags: FLAG_SCHEMA_BASE_OBJECT
```

Version-Specific Behavior: Implemented on ADAM, Windows Server 2008, AD LDS for Windows Vista, Windows Server 2008 R2, AD LDS for Windows 7, Windows Server 2012, AD LDS for Windows 8, Windows Server 2012 R2, AD LDS for Windows 8.1, Windows Server 2016 ~~Technical Preview~~, and AD LDS for Windows 10.

2.27 Attribute c

This attribute specifies the country/region in the address of the user. The country/region is represented as the two-character country code based on ISO-3166.

```
cn: Country-Name
ldapDisplayName: c
attributeId: 2.5.4.6
attributeSyntax: 2.5.5.12
omSyntax: 64
isSingleValued: TRUE
schemaIdGuid: bf967945-0de6-11d0-a285-00aa003049e2
systemOnly: FALSE
searchFlags: fCOPY
rangeLower: 1
rangeUpper: 3
attributeSecurityGuid: 77b5b886-944a-11d1-aebd-0000f80367c1
isMemberOfPartialAttributeSet: TRUE
systemFlags: FLAG_SCHEMA_BASE_OBJECT |
FLAG_ATTR_REQ_PARTIAL_SET_MEMBER
```

Version-Specific Behavior: Implemented on ADAM, Windows Server 2008, AD LDS for Windows Vista, Windows Server 2008 R2, AD LDS for Windows 7, Windows Server 2012, AD LDS for Windows 8, Windows Server 2012 R2, AD LDS for Windows 8.1, Windows Server 2016 ~~Technical Preview~~, and AD LDS for Windows 10.

2.28 Attribute canonicalName

This attribute specifies the name of the object in canonical format. "myserver2.fabrikam.com/users/jeffsmith" is an example of a DN in canonical format.

This is a constructed attribute. The results returned are identical to those returned by the following Active Directory function: DsCrackNames(NULL, DS_NAME_FLAG_SYNTACTICAL_ONLY, DS_FQDN_1779_NAME, DS_CANONICAL_NAME, ...).

```
cn: Canonical-Name
ldapDisplayName: canonicalName
attributeId: 1.2.840.113556.1.4.916
attributeSyntax: 2.5.5.12
omSyntax: 64
isSingleValued: FALSE
schemaIdGuid: 9a7ad945-ca53-11d1-bbd0-0080c76670c0
systemOnly: TRUE
searchFlags: 0
systemFlags: FLAG_SCHEMA_BASE_OBJECT | FLAG_ATTR_IS_CONSTRUCTED |
FLAG_DOMAIN_DISALLOW_RENAME
```

Version-Specific Behavior: Implemented on ADAM, Windows Server 2008, AD LDS for Windows Vista, Windows Server 2008 R2, AD LDS for Windows 7, Windows Server 2012, AD LDS for Windows 8, Windows Server 2012 R2, AD LDS for Windows 8.1, Windows Server 2016 ~~Technical Preview~~, and AD LDS for Windows 10.

2.29 Attribute carLicense

This attribute specifies the vehicle license or registration plate.

```
cn: carLicense
ldapDisplayName: carLicense
attributeId: 2.16.840.1.113730.3.1.1
```

```
attributeSyntax: 2.5.5.12
omSyntax: 64
isSingleValued: FALSE
schemaIdGuid: d4159c92-957d-4a87-8a67-8d2934e01649
systemOnly: FALSE
searchFlags: 0
showInAdvancedViewOnly: FALSE
```

Version-Specific Behavior: Implemented on ADAM, Windows Server 2008, AD LDS for Windows Vista, Windows Server 2008 R2, AD LDS for Windows 7, Windows Server 2012, AD LDS for Windows 8, Windows Server 2012 R2, AD LDS for Windows 8.1, Windows Server 2016 ~~Technical Preview~~, and AD LDS for Windows 10.

2.30 Attribute classDisplayName

This attribute specifies the object name to be displayed on dialogs.

```
cn: Class-Display-Name
ldapDisplayName: classDisplayName
attributeId: 1.2.840.113556.1.4.610
attributeSyntax: 2.5.5.12
omSyntax: 64
isSingleValued: FALSE
schemaIdGuid: 548e1c22-dea6-11d0-b010-0000f80367c1
systemOnly: FALSE
searchFlags: 0
systemFlags: FLAG_SCHEMA_BASE_OBJECT
```

Version-Specific Behavior: Implemented on ADAM, Windows Server 2008, AD LDS for Windows Vista, Windows Server 2008 R2, AD LDS for Windows 7, Windows Server 2012, AD LDS for Windows 8, Windows Server 2012 R2, AD LDS for Windows 8.1, Windows Server 2016 ~~Technical Preview~~, and AD LDS for Windows 10.

2.31 Attribute cn

This attribute specifies the name that represents an object. This attribute is used to perform searches.

```
cn: Common-Name
ldapDisplayName: cn
attributeId: 2.5.4.3
attributeSyntax: 2.5.5.12
omSyntax: 64
isSingleValued: TRUE
schemaIdGuid: bf96793f-0de6-11d0-a285-00aa003049e2
systemOnly: FALSE
searchFlags: fATTINDEX
rangeLower: 1
rangeUpper: 64
attributeSecurityGuid: e48d0154-bcf8-11d1-8702-00c04fb96050
isMemberOfPartialAttributeSet: TRUE
systemFlags: FLAG_SCHEMA_BASE_OBJECT |
FLAG_ATTR_REQ_PARTIAL_SET_MEMBER
```

Version-Specific Behavior: Implemented on ADAM, Windows Server 2008, AD LDS for Windows Vista, Windows Server 2008 R2, AD LDS for Windows 7, Windows Server 2012, AD LDS for Windows 8, Windows Server 2012 R2, AD LDS for Windows 8.1, Windows Server 2016 ~~Technical Preview~~, and AD LDS for Windows 10.

2.32 Attribute co

This attribute specifies the country/region in which the user is located.

```
cn: Text-Country
ldapDisplayName: co
attributeId: 1.2.840.113556.1.2.131
attributeSyntax: 2.5.5.12
omSyntax: 64
isSingleValued: TRUE
schemaIdGuid: f0f8ffa7-1191-11d0-a060-00aa006c33ed
systemOnly: FALSE
searchFlags: fCOPY
rangeLower: 1
rangeUpper: 128
attributeSecurityGuid: e48d0154-bcf8-11d1-8702-00c04fb96050
systemFlags: FLAG_SCHEMA_BASE_OBJECT
```

Version-Specific Behavior: Implemented on ADAM, Windows Server 2008, AD LDS for Windows Vista, Windows Server 2008 R2, AD LDS for Windows 7, Windows Server 2012, AD LDS for Windows 8, Windows Server 2012 R2, AD LDS for Windows 8.1, Windows Server 2016 ~~Technical Preview~~, and AD LDS for Windows 10.

2.33 Attribute comment

This attribute specifies the user's comments.

```
cn: User-Comment
ldapDisplayName: comment
attributeId: 1.2.840.113556.1.4.156
attributeSyntax: 2.5.5.12
omSyntax: 64
isSingleValued: TRUE
schemaIdGuid: bf967a6a-0de6-11d0-a285-00aa003049e2
systemOnly: FALSE
searchFlags: 0
attributeSecurityGuid: 59ba2f42-79a2-11d0-9020-00c04fc2d3cf
```

Version-Specific Behavior: Implemented on ADAM, Windows Server 2008, AD LDS for Windows Vista, Windows Server 2008 R2, AD LDS for Windows 7, Windows Server 2012, AD LDS for Windows 8, Windows Server 2012 R2, AD LDS for Windows 8.1, Windows Server 2016 ~~Technical Preview~~, and AD LDS for Windows 10.

2.34 Attribute company

This attribute specifies the user's company name.

```
cn: Company
ldapDisplayName: company
attributeId: 1.2.840.113556.1.2.146
attributeSyntax: 2.5.5.12
omSyntax: 64
isSingleValued: TRUE
schemaIdGuid: f0f8ff88-1191-11d0-a060-00aa006c33ed
systemOnly: FALSE
searchFlags: fCOPY
rangeLower: 1
rangeUpper: 64
attributeSecurityGuid: e48d0154-bcf8-11d1-8702-00c04fb96050
```

Version-Specific Behavior: Implemented on ADAM, Windows Server 2008, AD LDS for Windows Vista, Windows Server 2008 R2, AD LDS for Windows 7, Windows Server 2012, AD LDS for Windows 8, Windows Server 2012 R2, AD LDS for Windows 8.1, Windows Server 2016 ~~Technical Preview~~, and AD LDS for Windows 10.

2.35 Attribute configurationFile

ms-DS-Configuration-File

```
cn: ms-DS-Configuration-File
ldapDisplayName: configurationFile
attributeId: 1.2.840.113556.1.4.1889
attributeSyntax: 2.5.5.12
omSyntax: 64
isSingleValued: FALSE
searchFlags: fATTINDEX
```

Version-Specific Behavior: Implemented on ADAM, Windows Server 2008, AD LDS for Windows Vista, Windows Server 2008 R2, AD LDS for Windows 7, Windows Server 2012, AD LDS for Windows 8, Windows Server 2012 R2, AD LDS for Windows 8.1, Windows Server 2016 ~~Technical Preview~~, and AD LDS for Windows 10.

2.36 Attribute configurationFileGuid

ms-DS-Configuration-File-Guid

```
cn: ms-DS-Configuration-File-Guid
ldapDisplayName: configurationFileGuid
attributeId: 1.2.840.113556.1.4.1886
attributeSyntax: 2.5.5.10
omSyntax: 4
isSingleValued: FALSE
searchFlags: fATTINDEX
```

Version-Specific Behavior: Implemented on ADAM, Windows Server 2008, AD LDS for Windows Vista, Windows Server 2008 R2, AD LDS for Windows 7, Windows Server 2012, AD LDS for Windows 8, Windows Server 2012 R2, AD LDS for Windows 8.1, Windows Server 2016 ~~Technical Preview~~, and AD LDS for Windows 10.

2.37 Attribute contextMenu

This attribute specifies the order number and GUID of the context menu to be used for an object.

```
cn: Context-Menu
ldapDisplayName: contextMenu
attributeId: 1.2.840.113556.1.4.499
attributeSyntax: 2.5.5.12
omSyntax: 64
isSingleValued: FALSE
schemaIdGuid: 4d8601ee-ac85-11d0-afe3-00c04fd930c9
systemOnly: FALSE
```

Version-Specific Behavior: Implemented on Windows Server 2008, AD LDS for Windows Vista, Windows Server 2008 R2, AD LDS for Windows 7, Windows Server 2012, AD LDS for Windows 8, Windows Server 2012 R2, AD LDS for Windows 8.1, Windows Server 2016 ~~Technical Preview~~, and AD LDS for Windows 10.

2.38 Attribute cost

This attribute contains the relative cost for routing messages through a particular site connector.

```
cn: Cost
ldapDisplayName: cost
attributeId: 1.2.840.113556.1.2.135
attributeSyntax: 2.5.5.9
omSyntax: 2
isSingleValued: TRUE
schemaIdGuid: bf967944-0de6-11d0-a285-00aa003049e2
systemOnly: FALSE
searchFlags: 0
```

Version-Specific Behavior: Implemented on ADAM, Windows Server 2008, AD LDS for Windows Vista, Windows Server 2008 R2, AD LDS for Windows 7, Windows Server 2012, AD LDS for Windows 8, Windows Server 2012 R2, AD LDS for Windows 8.1, Windows Server 2016 **Technical Preview**, and AD LDS for Windows 10.

2.39 Attribute countryCode

This attribute specifies the country code for the user's language of choice.

```
cn: Country-Code
ldapDisplayName: countryCode
attributeId: 1.2.840.113556.1.4.25
attributeSyntax: 2.5.5.9
omSyntax: 2
isSingleValued: TRUE
schemaIdGuid: 5fd42471-1262-11d0-a060-00aa006c33ed
systemOnly: FALSE
searchFlags: fCOPY
rangeLower: 0
rangeUpper: 65535
attributeSecurityGuid: 59ba2f42-79a2-11d0-9020-00c04fc2d3cf
systemFlags: FLAG_SCHEMA_BASE_OBJECT
```

Version-Specific Behavior: Implemented on ADAM, Windows Server 2008, AD LDS for Windows Vista, Windows Server 2008 R2, AD LDS for Windows 7, Windows Server 2012, AD LDS for Windows 8, Windows Server 2012 R2, AD LDS for Windows 8.1, Windows Server 2016 **Technical Preview**, and AD LDS for Windows 10.

2.40 Attribute createDialog

This attribute specifies the GUID of a dialog that is used for creating an associated object.

```
cn: Create-Dialog
ldapDisplayName: createDialog
attributeId: 1.2.840.113556.1.4.810
attributeSyntax: 2.5.5.12
omSyntax: 64
isSingleValued: TRUE
schemaIdGuid: 2b09958a-8931-11d1-aebc-0000f80367c1
systemOnly: FALSE
```

Version-Specific Behavior: Implemented on Windows Server 2008, AD LDS for Windows Vista, Windows Server 2008 R2, AD LDS for Windows 7, Windows Server 2012, AD LDS for Windows 8,

Windows Server 2012 R2, AD LDS for Windows 8.1, Windows Server 2016 ~~Technical Preview~~, and AD LDS for Windows 10.

2.41 Attribute createTimeStamp

This attribute specifies the date when this object was created. This value is replicated.

```
cn: Create-Time-Stamp
ldapDisplayName: createTimeStamp
attributeId: 2.5.18.1
attributeSyntax: 2.5.5.11
omSyntax: 24
isSingleValued: TRUE
schemaIdGuid: 2df90d73-009f-11d2-aa4c-00c04fd7d83a
systemOnly: TRUE
searchFlags: 0
systemFlags: FLAG_SCHEMA_BASE_OBJECT | FLAG_ATTR_IS_CONSTRUCTED |
FLAG_DOMAIN_DISALLOW_RENAME
```

Version-Specific Behavior: Implemented on ADAM, Windows Server 2008, AD LDS for Windows Vista, Windows Server 2008 R2, AD LDS for Windows 7, Windows Server 2012, AD LDS for Windows 8, Windows Server 2012 R2, AD LDS for Windows 8.1, Windows Server 2016 ~~Technical Preview~~, and AD LDS for Windows 10.

2.42 Attribute createWizardExt

This attribute specifies the GUID of the wizard extensions for creating an associated object.

```
cn: Create-Wizard-Ext
ldapDisplayName: createWizardExt
attributeId: 1.2.840.113556.1.4.812
attributeSyntax: 2.5.5.12
omSyntax: 64
isSingleValued: FALSE
schemaIdGuid: 2b09958b-8931-11d1-aebc-0000f80367c1
systemOnly: FALSE
```

Version-Specific Behavior: Implemented on Windows Server 2008, AD LDS for Windows Vista, Windows Server 2008 R2, AD LDS for Windows 7, Windows Server 2012, AD LDS for Windows 8, Windows Server 2012 R2, AD LDS for Windows 8.1, Windows Server 2016 ~~Technical Preview~~, and AD LDS for Windows 10.

2.43 Attribute creationWizard

This attribute specifies the wizard to activate when creating objects of this class.

```
cn: Creation-Wizard
ldapDisplayName: creationWizard
attributeId: 1.2.840.113556.1.4.498
attributeSyntax: 2.5.5.12
omSyntax: 64
isSingleValued: TRUE
schemaIdGuid: 4d8601ed-ac85-11d0-afe3-00c04fd930c9
systemOnly: FALSE
```

Version-Specific Behavior: Implemented on Windows Server 2008, AD LDS for Windows Vista, Windows Server 2008 R2, AD LDS for Windows 7, Windows Server 2012, AD LDS for Windows 8,

Windows Server 2012 R2, AD LDS for Windows 8.1, Windows Server 2016 ~~Technical Preview~~, and AD LDS for Windows 10.

2.44 Attribute dc

This attribute specifies the naming attribute for domain and DNS objects. This attribute is usually displayed as dc=DomainName.

```
cn: Domain-Component
ldapDisplayName: dc
attributeId: 0.9.2342.19200300.100.1.25
attributeSyntax: 2.5.5.12
omSyntax: 64
isSingleValued: TRUE
schemaIdGuid: 19195a55-6da0-11d0-afd3-00c04fd930c9
systemOnly: FALSE
searchFlags: 0
rangeLower: 1
rangeUpper: 255
isMemberOfPartialAttributeSet: TRUE
systemFlags: FLAG_SCHEMA_BASE_OBJECT |
FLAG_ATTR_REQ_PARTIAL_SET_MEMBER
```

Version-Specific Behavior: Implemented on ADAM, Windows Server 2008, AD LDS for Windows Vista, Windows Server 2008 R2, AD LDS for Windows 7, Windows Server 2012, AD LDS for Windows 8, Windows Server 2012 R2, AD LDS for Windows 8.1, Windows Server 2016 ~~Technical Preview~~, and AD LDS for Windows 10.

2.45 Attribute defaultClassStore

This attribute specifies the default class store for a given user.

```
cn: Default-Class-Store
ldapDisplayName: defaultClassStore
attributeId: 1.2.840.113556.1.4.213
attributeSyntax: 2.5.5.1
omSyntax: 127
omObjectClass: 1.3.12.2.1011.28.0.714
isSingleValued: FALSE
schemaIdGuid: bf967948-0de6-11d0-a285-00aa003049e2
systemOnly: FALSE
searchFlags: 0
```

Version-Specific Behavior: Implemented on ADAM, Windows Server 2008, AD LDS for Windows Vista, Windows Server 2008 R2, AD LDS for Windows 7, Windows Server 2012, AD LDS for Windows 8, Windows Server 2012 R2, AD LDS for Windows 8.1, Windows Server 2016 ~~Technical Preview~~, and AD LDS for Windows 10.

2.46 Attribute defaultGroup

This attribute specifies the group to which this object is assigned when it is created.

```
cn: Default-Group
ldapDisplayName: defaultGroup
attributeId: 1.2.840.113556.1.4.480
attributeSyntax: 2.5.5.1
omSyntax: 127
omObjectClass: 1.3.12.2.1011.28.0.714
isSingleValued: TRUE
```

```
schemaIdGuid: 720bc4e2-a54a-11d0-afdf-00c04fd930c9
systemOnly: FALSE
searchFlags: 0
systemFlags: FLAG_SCHEMA_BASE_OBJECT
```

Version-Specific Behavior: Implemented on ADAM, Windows Server 2008, AD LDS for Windows Vista, Windows Server 2008 R2, AD LDS for Windows 7, Windows Server 2012, AD LDS for Windows 8, Windows Server 2012 R2, AD LDS for Windows 8.1, Windows Server 2016 ~~Technical Preview~~, and AD LDS for Windows 10.

2.47 Attribute defaultHidingValue

This attribute specifies a Boolean value that specifies the default setting of the showInAdvancedViewOnly property of new instances of this class.

```
cn: Default-Hiding-Value
ldapDisplayName: defaultHidingValue
attributeId: 1.2.840.113556.1.4.518
attributeSyntax: 2.5.5.8
omSyntax: 1
isSingleValued: TRUE
schemaIdGuid: b7b13116-b82e-11d0-afee-0000f80367c1
systemOnly: FALSE
searchFlags: 0
systemFlags: FLAG_SCHEMA_BASE_OBJECT
```

Version-Specific Behavior: Implemented on ADAM, Windows Server 2008, AD LDS for Windows Vista, Windows Server 2008 R2, AD LDS for Windows 7, Windows Server 2012, AD LDS for Windows 8, Windows Server 2012 R2, AD LDS for Windows 8.1, Windows Server 2016 ~~Technical Preview~~, and AD LDS for Windows 10.

2.48 Attribute defaultObjectCategory

This attribute specifies the object category to use for an object if one is not specified.

```
cn: Default-Object-Category
ldapDisplayName: defaultObjectCategory
attributeId: 1.2.840.113556.1.4.783
attributeSyntax: 2.5.5.1
omSyntax: 127
omObjectClass: 1.3.12.2.1011.28.0.714
isSingleValued: TRUE
schemaIdGuid: 26d97367-6070-11d1-a9c6-0000f80367c1
systemOnly: FALSE
searchFlags: 0
systemFlags: FLAG_SCHEMA_BASE_OBJECT
```

Version-Specific Behavior: Implemented on ADAM, Windows Server 2008, AD LDS for Windows Vista, Windows Server 2008 R2, AD LDS for Windows 7, Windows Server 2012, AD LDS for Windows 8, Windows Server 2012 R2, AD LDS for Windows 8.1, Windows Server 2016 ~~Technical Preview~~, and AD LDS for Windows 10.

2.49 Attribute defaultSecurityDescriptor

This attribute specifies the security descriptor to be assigned to the object when it is first created.

```
cn: Default-Security-Descriptor
```



```
ldapDisplayName: defaultSecurityDescriptor
attributeId: 1.2.840.113556.1.4.224
attributeSyntax: 2.5.5.12
omSyntax: 64
isSingleValued: TRUE
schemaIdGuid: 807a6d30-1669-11d0-a064-00aa006c33ed
systemOnly: FALSE
searchFlags: 0
rangeLower: 0
rangeUpper: 32767
systemFlags: FLAG_SCHEMA_BASE_OBJECT
```

Version-Specific Behavior: Implemented on ADAM, Windows Server 2008, AD LDS for Windows Vista, Windows Server 2008 R2, AD LDS for Windows 7, Windows Server 2012, AD LDS for Windows 8, Windows Server 2012 R2, AD LDS for Windows 8.1, Windows Server 2016 ~~Technical Preview~~, and AD LDS for Windows 10.

2.50 Attribute department

This attribute contains the name for the department in which the user works.

```
cn: Department
ldapDisplayName: department
attributeId: 1.2.840.113556.1.2.141
attributeSyntax: 2.5.5.12
omSyntax: 64
isSingleValued: TRUE
schemaIdGuid: bf96794f-0de6-11d0-a285-00aa003049e2
systemOnly: FALSE
searchFlags: fCOPY
rangeLower: 1
rangeUpper: 64
attributeSecurityGuid: e48d0154-bcf8-11d1-8702-00c04fb96050
```

Version-Specific Behavior: Implemented on ADAM, Windows Server 2008, AD LDS for Windows Vista, Windows Server 2008 R2, AD LDS for Windows 7, Windows Server 2012, AD LDS for Windows 8, Windows Server 2012 R2, AD LDS for Windows 8.1, Windows Server 2016 ~~Technical Preview~~, and AD LDS for Windows 10.

2.51 Attribute departmentNumber

This attribute identifies a department within an organization.

```
cn: departmentNumber
ldapDisplayName: departmentNumber
attributeId: 2.16.840.1.113730.3.1.2
attributeSyntax: 2.5.5.12
omSyntax: 64
isSingleValued: FALSE
schemaIdGuid: be9ef6ee-cbc7-4f22-b27b-96967e7ee585
systemOnly: FALSE
searchFlags: 0
showInAdvancedViewOnly: FALSE
```

Version-Specific Behavior: Implemented on ADAM, Windows Server 2008, AD LDS for Windows Vista, Windows Server 2008 R2, AD LDS for Windows 7, Windows Server 2012, AD LDS for Windows 8, Windows Server 2012 R2, AD LDS for Windows 8.1, Windows Server 2016 ~~Technical Preview~~, and AD LDS for Windows 10.

2.52 Attribute description

This attribute contains the description to display for an object. This value is treated as single-valued by the Active Directory system.

```
cn: Description
ldapDisplayName: description
attributeId: 2.5.4.13
attributeSyntax: 2.5.5.12
omSyntax: 64
isSingleValued: FALSE
schemaIdGuid: bf967950-0de6-11d0-a285-00aa003049e2
systemOnly: FALSE
searchFlags: 0
rangeLower: 0
rangeUpper: 1024
attributeSecurityGuid: e48d0154-bcf8-11d1-8702-00c04fb96050
isMemberOfPartialAttributeSet: TRUE
systemFlags: FLAG_SCHEMA_BASE_OBJECT
```

Version-Specific Behavior: Implemented on ADAM, Windows Server 2008, AD LDS for Windows Vista, Windows Server 2008 R2, AD LDS for Windows 7, Windows Server 2012, AD LDS for Windows 8, Windows Server 2012 R2, AD LDS for Windows 8.1, Windows Server 2016 ~~Technical Preview~~, and AD LDS for Windows 10.

2.53 Attribute desktopProfile

This attribute specifies the location of the desktop profile for a user or group of users.

```
cn: Desktop-Profile
ldapDisplayName: desktopProfile
attributeId: 1.2.840.113556.1.4.346
attributeSyntax: 2.5.5.12
omSyntax: 64
isSingleValued: TRUE
schemaIdGuid: eea65906-8ac6-11d0-afda-00c04fd930c9
systemOnly: FALSE
searchFlags: 0
systemFlags: FLAG_SCHEMA_BASE_OBJECT
```

Version-Specific Behavior: Implemented on ADAM, Windows Server 2008, AD LDS for Windows Vista, Windows Server 2008 R2, AD LDS for Windows 7, Windows Server 2012, AD LDS for Windows 8, Windows Server 2012 R2, AD LDS for Windows 8.1, Windows Server 2016 ~~Technical Preview~~, and AD LDS for Windows 10.

2.54 Attribute destinationIndicator

This attribute is part of the X.500 specification [X500].

```
cn: Destination-Indicator
ldapDisplayName: destinationIndicator
attributeId: 2.5.4.27
attributeSyntax: 2.5.5.5
omSyntax: 19
isSingleValued: FALSE
schemaIdGuid: bf967951-0de6-11d0-a285-00aa003049e2
systemOnly: FALSE
searchFlags: 0
rangeLower: 1
rangeUpper: 128
```

```
systemFlags: FLAG_SCHEMA_BASE_OBJECT
```

Version-Specific Behavior: Implemented on ADAM, Windows Server 2008, AD LDS for Windows Vista, Windows Server 2008 R2, AD LDS for Windows 7, Windows Server 2012, AD LDS for Windows 8, Windows Server 2012 R2, AD LDS for Windows 8.1, Windows Server 2016 ~~Technical Preview~~, and AD LDS for Windows 10.

2.55 Attribute directReports

This attribute contains the list of users that directly report to the user. The users that are listed as reports are those that have the property manager property set to this user. Each item in the list is a linked reference to the object that represents the user.

```
cn: Reports
ldapDisplayName: directReports
attributeId: 1.2.840.113556.1.2.436
attributeSyntax: 2.5.5.1
omSyntax: 127
omObjectClass: 1.3.12.2.1011.28.0.714
isSingleValued: FALSE
schemaIdGuid: bf967a1c-0de6-11d0-a285-00aa003049e2
systemOnly: TRUE
searchFlags: 0
attributeSecurityGuid: e48d0154-bcf8-11d1-8702-00c04fb96050
linkID: 43
systemFlags: FLAG_ATTR_NOT_REPLICATED
```

Version-Specific Behavior: Implemented on ADAM, Windows Server 2008, AD LDS for Windows Vista, Windows Server 2008 R2, AD LDS for Windows 7, Windows Server 2012, AD LDS for Windows 8, Windows Server 2012 R2, AD LDS for Windows 8.1, Windows Server 2016 ~~Technical Preview~~, and AD LDS for Windows 10.

2.56 Attribute displayName

This attribute specifies the display name for an object. This attribute is usually the combination of the user's first name, middle initial, and last name.

```
cn: Display-Name
ldapDisplayName: displayName
attributeId: 1.2.840.113556.1.2.13
attributeSyntax: 2.5.5.12
omSyntax: 64
isSingleValued: TRUE
schemaIdGuid: bf967953-0de6-11d0-a285-00aa003049e2
systemOnly: FALSE
searchFlags: fANR | fATTINDEX
rangeLower: 0
rangeUpper: 256
attributeSecurityGuid: 59ba2f42-79a2-11d0-9020-00c04fc2d3cf
isMemberOfPartialAttributeSet: TRUE
systemFlags: FLAG_SCHEMA_BASE_OBJECT
```

Version-Specific Behavior: Implemented on ADAM, Windows Server 2008, AD LDS for Windows Vista, Windows Server 2008 R2, AD LDS for Windows 7, Windows Server 2012, AD LDS for Windows 8, Windows Server 2012 R2, AD LDS for Windows 8.1, Windows Server 2016 ~~Technical Preview~~, and AD LDS for Windows 10.

2.57 Attribute displayNamePrintable

This attribute specifies the printable display name for an object. The printable display name is usually the combination of the user's first name, middle initial, and last name.

```
cn: Display-Name-Printable
ldapDisplayName: displayNamePrintable
attributeId: 1.2.840.113556.1.2.353
attributeSyntax: 2.5.5.5
omSyntax: 19
isSingleValued: TRUE
schemaIdGuid: bf967954-0de6-11d0-a285-00aa003049e2
systemOnly: FALSE
rangeLower: 1
rangeUpper: 256
attributeSecurityGuid: e48d0154-bcf8-11d1-8702-00c04fb96050
isMemberOfPartialAttributeSet: TRUE
```

Version-Specific Behavior: Implemented on ADAM, Windows Server 2008, Active Directory Lightweight Directory Services for Windows Vista operating system, Windows Server 2008 R2, AD LDS for Windows 7, Windows Server 2012, AD LDS for Windows 8, Windows Server 2012 R2, AD LDS for Windows 8.1, Windows Server 2016 ~~Technical Preview~~, and AD LDS for Windows 10.

2.58 Attribute distinguishedName

This attribute is the same as the DN for an object.

```
cn: Obj-Dist-Name
ldapDisplayName: distinguishedName
attributeId: 2.5.4.49
attributeSyntax: 2.5.5.1
omSyntax: 127
omObjectClass: 1.3.12.2.1011.28.0.714
isSingleValued: TRUE
schemaIdGuid: bf9679e4-0de6-11d0-a285-00aa003049e2
systemOnly: TRUE
searchFlags: fPRESERVEONDELETE
attributeSecurityGuid: e48d0154-bcf8-11d1-8702-00c04fb96050
isMemberOfPartialAttributeSet: TRUE
systemFlags: FLAG_SCHEMA_BASE_OBJECT |
FLAG_ATTR_REQ_PARTIAL_SET_MEMBER | FLAG_ATTR_NOT_REPLICATED
```

Version-Specific Behavior: Implemented on ADAM, Windows Server 2008, AD LDS for Windows Vista, Windows Server 2008 R2, AD LDS for Windows 7, Windows Server 2012, AD LDS for Windows 8, Windows Server 2012 R2, AD LDS for Windows 8.1, Windows Server 2016 ~~Technical Preview~~, and AD LDS for Windows 10.

2.59 Attribute dITContentRules

This attribute specifies the permissible content of entries of a particular structural object class via the identification of an optional set of auxiliary object classes, mandatory, optional, and precluded attributes. Collective attributes are included in DIT-Content-Rules, as specified in [RFC2251] section 3.2.1.

```
cn: DIT-Content-Rules
ldapDisplayName: dITContentRules
attributeId: 2.5.21.2
attributeSyntax: 2.5.5.12
```

```
omSyntax: 64
isSingleValued: FALSE
schemaIdGuid: 9a7ad946-ca53-11d1-bbd0-0080c76670c0
systemOnly: TRUE
searchFlags: 0
systemFlags: FLAG_SCHEMA_BASE_OBJECT | FLAG_ATTR_IS_CONSTRUCTED |
FLAG_DOMAIN_DISALLOW_RENAME
```

Version-Specific Behavior: Implemented on ADAM, Windows Server 2008, AD LDS for Windows Vista, Windows Server 2008 R2, AD LDS for Windows 7, Windows Server 2012, AD LDS for Windows 8, Windows Server 2012 R2, AD LDS for Windows 8.1, Windows Server 2016 ~~Technical Preview~~, and AD LDS for Windows 10.

2.60 Attribute division

This attribute specifies the user's division.

```
cn: Division
ldapDisplayName: division
attributeId: 1.2.840.113556.1.4.261
attributeSyntax: 2.5.5.12
omSyntax: 64
isSingleValued: TRUE
schemaIdGuid: fe6136a0-2073-11d0-a9c2-00aa006c33ed
systemOnly: FALSE
searchFlags: fCOPY
rangeLower: 0
rangeUpper: 256
attributeSecurityGuid: e48d0154-bcf8-11d1-8702-00c04fb96050
```

Version-Specific Behavior: Implemented on ADAM, Windows Server 2008, AD LDS for Windows Vista, Windows Server 2008 R2, AD LDS for Windows 7, Windows Server 2012, AD LDS for Windows 8, Windows Server 2012 R2, AD LDS for Windows 8.1, Windows Server 2016 ~~Technical Preview~~, and AD LDS for Windows 10.

2.61 Attribute dMDLocation

This attribute specifies the DN that identifies the schema partition.

```
cn: DMD-Location
ldapDisplayName: dMDLocation
attributeId: 1.2.840.113556.1.2.36
attributeSyntax: 2.5.5.1
omSyntax: 127
omObjectClass: 1.3.12.2.1011.28.0.714
isSingleValued: TRUE
schemaIdGuid: f0f8ff8b-1191-11d0-a060-00aa006c33ed
systemOnly: TRUE
searchFlags: 0
systemFlags: FLAG_SCHEMA_BASE_OBJECT
```

Version-Specific Behavior: Implemented on ADAM, Windows Server 2008, AD LDS for Windows Vista, Windows Server 2008 R2, AD LDS for Windows 7, Windows Server 2012, AD LDS for Windows 8, Windows Server 2012 R2, AD LDS for Windows 8.1, Windows Server 2016 ~~Technical Preview~~, and AD LDS for Windows 10.

2.62 Attribute dmdName

This attribute specifies a name that is used to identify the schema partition.

```
cn: DMD-Name
ldapDisplayName: dmdName
attributeId: 1.2.840.113556.1.2.598
attributeSyntax: 2.5.5.12
omSyntax: 64
isSingleValued: TRUE
schemaIdGuid: 167757b9-47f3-11d1-a9c3-0000f80367c1
systemOnly: FALSE
searchFlags: 0
rangeLower: 1
rangeUpper: 1024
systemFlags: FLAG_SCHEMA_BASE_OBJECT
```

Version-Specific Behavior: Implemented on ADAM, Windows Server 2008, AD LDS for Windows Vista, Windows Server 2008 R2, AD LDS for Windows 7, Windows Server 2012, AD LDS for Windows 8, Windows Server 2012 R2, AD LDS for Windows 8.1, Windows Server 2016 ~~Technical Preview~~, and AD LDS for Windows 10.

2.63 Attribute dNSHostName

This attribute specifies the name of the computer as it is registered in DNS.

```
cn: DNS-Host-Name
ldapDisplayName: dNSHostName
attributeId: 1.2.840.113556.1.4.619
attributeSyntax: 2.5.5.12
omSyntax: 64
isSingleValued: TRUE
schemaIdGuid: 72e39547-7b18-11d1-edef-00c04fd8d5cd
systemOnly: FALSE
searchFlags: 0
rangeLower: 0
rangeUpper: 2048
attributeSecurityGuid: 72e39547-7b18-11d1-edef-00c04fd8d5cd
isMemberOfPartialAttributeSet: TRUE
systemFlags: FLAG_SCHEMA_BASE_OBJECT
```

Version-Specific Behavior: Implemented on ADAM, Windows Server 2008, AD LDS for Windows Vista, Windows Server 2008 R2, AD LDS for Windows 7, Windows Server 2012, AD LDS for Windows 8, Windows Server 2012 R2, AD LDS for Windows 8.1, Windows Server 2016 ~~Technical Preview~~, and AD LDS for Windows 10.

2.64 Attribute dnsRoot

This attribute specifies the FQDN (1) ([MS-ADTS] section 1.1) that is associated with a naming context. This attribute is set on a crossRef object and is used for referral generation.

When a search is made through an entire domain tree, the search musthas to be initiated at the Dns-Root object. This attribute can be multivalued, in which case multiple referrals are generated.

```
cn: Dns-Root
ldapDisplayName: dnsRoot
attributeId: 1.2.840.113556.1.4.28
attributeSyntax: 2.5.5.12
omSyntax: 64
isSingleValued: FALSE
```

```
schemaIdGuid: bf967959-0de6-11d0-a285-00aa003049e2
systemOnly: FALSE
searchFlags: fATTINDEX
rangeLower: 1
rangeUpper: 255
systemFlags: FLAG_SCHEMA_BASE_OBJECT
```

Version-Specific Behavior: Implemented on ADAM, Windows Server 2008, AD LDS for Windows Vista, Windows Server 2008 R2, AD LDS for Windows 7, Windows Server 2012, AD LDS for Windows 8, Windows Server 2012 R2, AD LDS for Windows 8.1, Windows Server 2016 ~~Technical Preview~~, and AD LDS for Windows 10.

2.65 Attribute dSASignature

This attribute specifies the DSA-Signature of an object, which is the Invocation-ID of the last directory to modify the object.

```
cn: DSA-Signature
ldapDisplayName: dSASignature
attributeId: 1.2.840.113556.1.2.74
attributeSyntax: 2.5.5.10
omSyntax: 4
isSingleValued: TRUE
schemaIdGuid: 167757bc-47f3-11d1-a9c3-0000f80367c1
systemOnly: FALSE
searchFlags: 0
systemFlags: FLAG_SCHEMA_BASE_OBJECT
```

Version-Specific Behavior: Implemented on ADAM, Windows Server 2008, AD LDS for Windows Vista, Windows Server 2008 R2, AD LDS for Windows 7, Windows Server 2012, AD LDS for Windows 8, Windows Server 2012 R2, AD LDS for Windows 8.1, Windows Server 2016 ~~Technical Preview~~, and AD LDS for Windows 10.

2.66 Attribute dSCorePropagationData

This attribute is for internal use only.

```
cn: DS-Core-Propagation-Data
ldapDisplayName: dSCorePropagationData
attributeId: 1.2.840.113556.1.4.1357
attributeSyntax: 2.5.5.11
omSyntax: 24
isSingleValued: FALSE
schemaIdGuid: d167aa4b-8b08-11d2-9939-0000f87a57d4
systemOnly: TRUE
searchFlags: 0
isMemberOfPartialAttributeSet: TRUE
systemFlags: FLAG_SCHEMA_BASE_OBJECT |
  FLAG_ATTR_REQ_PARTIAL_SET_MEMBER | FLAG_ATTR_NOT_REPLICATED
```

Version-Specific Behavior: Implemented on ADAM, Windows Server 2008, AD LDS for Windows Vista, Windows Server 2008 R2, AD LDS for Windows 7, Windows Server 2012, AD LDS for Windows 8, Windows Server 2012 R2, AD LDS for Windows 8.1, Windows Server 2016 ~~Technical Preview~~, and AD LDS for Windows 10.

2.67 Attribute dSHeuristics

This attribute contains global settings for the entire forest.

```
cn: DS-Heuristics
ldapDisplayName: dsHeuristics
attributeId: 1.2.840.113556.1.2.212
attributeSyntax: 2.5.5.12
omSyntax: 64
isSingleValued: TRUE
schemaIdGuid: f0f8ff86-1191-11d0-a060-00aa006c33ed
systemOnly: FALSE
searchFlags: 0
systemFlags: FLAG_SCHEMA_BASE_OBJECT
```

Version-Specific Behavior: Implemented on ADAM, Windows Server 2008, AD LDS for Windows Vista, Windows Server 2008 R2, AD LDS for Windows 7, Windows Server 2012, AD LDS for Windows 8, Windows Server 2012 R2, AD LDS for Windows 8.1, Windows Server 2016 ~~Technical Preview~~, and AD LDS for Windows 10.

2.68 Attribute dSUIAdminMaximum

This attribute specifies the default maximum number of objects that are shown in a container by the admin UI.

```
cn: DS-UI-Admin-Maximum
ldapDisplayName: dSUIAdminMaximum
attributeId: 1.2.840.113556.1.4.1344
attributeSyntax: 2.5.5.9
omSyntax: 2
isSingleValued: TRUE
schemaIdGuid: ee8d0ae0-6f91-11d2-9905-0000f87a57d4
systemOnly: FALSE
```

Version-Specific Behavior: Implemented on Windows Server 2008, AD LDS for Windows Vista, Windows Server 2008 R2, AD LDS for Windows 7, Windows Server 2012, AD LDS for Windows 8, Windows Server 2012 R2, AD LDS for Windows 8.1, Windows Server 2016 ~~Technical Preview~~, and AD LDS for Windows 10.

2.69 Attribute dSUIAdminNotification

This attribute specifies a list of the GUIDs of COM objects that support a callback interface that DSAdmin calls when an action has occurred on an object through the UI.

```
cn: DS-UI-Admin-Notification
ldapDisplayName: dSUIAdminNotification
attributeId: 1.2.840.113556.1.4.1343
attributeSyntax: 2.5.5.12
omSyntax: 64
isSingleValued: FALSE
schemaIdGuid: f6ea0a94-6f91-11d2-9905-0000f87a57d4
systemOnly: FALSE
```

Version-Specific Behavior: Implemented on Windows Server 2008, AD LDS for Windows Vista, Windows Server 2008 R2, AD LDS for Windows 7, Windows Server 2012, AD LDS for Windows 8, Windows Server 2012 R2, AD LDS for Windows 8.1, Windows Server 2016 ~~Technical Preview~~, and AD LDS for Windows 10.

2.70 Attribute dSUIShellMaximum

This attribute specifies the default maximum number of objects that are shown in a container by the shell UI.

```
cn: DS-UI-Shell-Maximum
ldapDisplayName: dSUIShellMaximum
attributeId: 1.2.840.113556.1.4.1345
attributeSyntax: 2.5.5.9
omSyntax: 2
isSingleValued: TRUE
schemaIdGuid: fcca766a-6f91-11d2-9905-0000f87a57d4
systemOnly: FALSE
```

Version-Specific Behavior: Implemented on Windows Server 2008, AD LDS for Windows Vista, Windows Server 2008 R2, AD LDS for Windows 7, Windows Server 2012, AD LDS for Windows 8, Windows Server 2012 R2, AD LDS for Windows 8.1, Windows Server 2016 ~~Technical Preview~~, and AD LDS for Windows 10.

2.71 Attribute dynamicLDAPServer

This attribute specifies the fully qualified domain name (FQDN) (1) ([MS-ADTS] section 1.1) of the server handling dynamic properties for this account.

```
cn: Dynamic-LDAP-Server
ldapDisplayName: dynamicLDAPServer
attributeId: 1.2.840.113556.1.4.537
attributeSyntax: 2.5.5.1
omSyntax: 127
omObjectClass: 1.3.12.2.1011.28.0.714
isSingleValued: TRUE
schemaIdGuid: 52458021-ca6a-11d0-afff-0000f80367c1
systemOnly: FALSE
searchFlags: 0
```

Version-Specific Behavior: Implemented on ADAM, Windows Server 2008, AD LDS for Windows Vista, Windows Server 2008 R2, AD LDS for Windows 7, Windows Server 2012, AD LDS for Windows 8, Windows Server 2012 R2, AD LDS for Windows 8.1, Windows Server 2016 ~~Technical Preview~~, and AD LDS for Windows 10.

2.72 Attribute employeeID

This attribute specifies the ID of an employee.

```
cn: Employee-ID
ldapDisplayName: employeeID
attributeId: 1.2.840.113556.1.4.35
attributeSyntax: 2.5.5.12
omSyntax: 64
isSingleValued: TRUE
schemaIdGuid: bf967962-0de6-11d0-a285-00aa003049e2
systemOnly: FALSE
searchFlags: 0
rangeLower: 0
rangeUpper: 16
```

Version-Specific Behavior: Implemented on ADAM, Windows Server 2008, AD LDS for Windows Vista, Windows Server 2008 R2, AD LDS for Windows 7, Windows Server 2012, AD LDS for Windows 8,

Windows Server 2012 R2, AD LDS for Windows 8.1, Windows Server 2016 ~~Technical Preview~~, and AD LDS for Windows 10.

2.73 Attribute `employeeNumber`

This attribute specifies the number assigned to an employee other than the employee ID.

```
cn: Employee-Number
ldapDisplayName: employeeNumber
attributeId: 1.2.840.113556.1.2.610
attributeSyntax: 2.5.5.12
omSyntax: 64
isSingleValued: TRUE
schemaIdGuid: a8df73ef-c5ea-11d1-bbcb-0080c76670c0
systemOnly: FALSE
searchFlags: 0
rangeLower: 1
rangeUpper: 512
```

Version-Specific Behavior: Implemented on ADAM, Windows Server 2008, AD LDS for Windows Vista, Windows Server 2008 R2, AD LDS for Windows 7, Windows Server 2012, AD LDS for Windows 8, Windows Server 2012 R2, AD LDS for Windows 8.1, Windows Server 2016 ~~Technical Preview~~, and AD LDS for Windows 10.

2.74 Attribute `employeeType`

This attribute specifies the job category for an employee.

```
cn: Employee-Type
ldapDisplayName: employeeType
attributeId: 1.2.840.113556.1.2.613
attributeSyntax: 2.5.5.12
omSyntax: 64
isSingleValued: TRUE
schemaIdGuid: a8df73f0-c5ea-11d1-bbcb-0080c76670c0
systemOnly: FALSE
searchFlags: fCOPY
rangeLower: 1
rangeUpper: 256
```

Version-Specific Behavior: Implemented on ADAM, Windows Server 2008, AD LDS for Windows Vista, Windows Server 2008 R2, AD LDS for Windows 7, Windows Server 2012, AD LDS for Windows 8, Windows Server 2012 R2, AD LDS for Windows 8.1, Windows Server 2016 ~~Technical Preview~~, and AD LDS for Windows 10.

2.75 Attribute `Enabled`

This attribute is used to signify whether or not a given crossRef is enabled.

```
cn: Enabled
ldapDisplayName: Enabled
attributeId: 1.2.840.113556.1.2.557
attributeSyntax: 2.5.5.8
omSyntax: 1
isSingleValued: TRUE
schemaIdGuid: a8df73f2-c5ea-11d1-bbcb-0080c76670c0
systemOnly: FALSE
searchFlags: 0
```

```
systemFlags: FLAG_SCHEMA_BASE_OBJECT
```

Version-Specific Behavior: Implemented on ADAM, Windows Server 2008, AD LDS for Windows Vista, Windows Server 2008 R2, AD LDS for Windows 7, Windows Server 2012, AD LDS for Windows 8, Windows Server 2012 R2, AD LDS for Windows 8.1, Windows Server 2016 ~~Technical Preview~~, and AD LDS for Windows 10.

2.76 Attribute enabledConnection

This attribute indicates whether a connection is available for use.

```
cn: Enabled-Connection
ldapDisplayName: enabledConnection
attributeId: 1.2.840.113556.1.4.36
attributeSyntax: 2.5.5.8
omSyntax: 1
isSingleValued: TRUE
schemaIdGuid: bf967963-0de6-11d0-a285-00aa003049e2
systemOnly: FALSE
searchFlags: 0
systemFlags: FLAG_SCHEMA_BASE_OBJECT
```

Version-Specific Behavior: Implemented on ADAM, Windows Server 2008, AD LDS for Windows Vista, Windows Server 2008 R2, AD LDS for Windows 7, Windows Server 2012, AD LDS for Windows 8, Windows Server 2012 R2, AD LDS for Windows 8.1, Windows Server 2016 ~~Technical Preview~~, and AD LDS for Windows 10.

2.77 Attribute entryTTL

This operational attribute is maintained by the server and appears to be present in every dynamic entry. The attribute is not present when the entry does not contain the dynamicObject object class.

The value of this attribute is the time, in seconds, that the entry continues to exist before disappearing from the directory. In the absence of intervening "refresh" operations, the values returned by reading the attribute in two successive searches are guaranteed to be nonincreasing. The smallest permissible value is 0, indicating that the entry ~~may~~ disappear without warning. The attribute is marked NO-USER-MODIFICATION because it ~~may~~ only be changed by using the refresh operation.

```
cn: Entry-TTL
ldapDisplayName: entryTTL
attributeId: 1.3.6.1.4.1.1466.101.119.3
attributeSyntax: 2.5.5.9
omSyntax: 2
isSingleValued: TRUE
schemaIdGuid: d213decc-d81a-4384-aac2-dcfcfd631cf8
systemOnly: FALSE
searchFlags: 0
rangeLower: 0
rangeUpper: 31557600
systemFlags: FLAG_SCHEMA_BASE_OBJECT | FLAG_ATTR_IS_CONSTRUCTED
```

Version-Specific Behavior: Implemented on ADAM, Windows Server 2008, AD LDS for Windows Vista, Windows Server 2008 R2, AD LDS for Windows 7, Windows Server 2012, AD LDS for Windows 8, Windows Server 2012 R2, AD LDS for Windows 8.1, Windows Server 2016 ~~Technical Preview~~, and AD LDS for Windows 10.

2.78 Attribute extendedAttributeInfo

This attribute specifies a multivalued property containing strings that represent additional information for each attribute.

```
cn: Extended-Attribute-Info
ldapDisplayName: extendedAttributeInfo
attributeId: 1.2.840.113556.1.4.909
attributeSyntax: 2.5.5.12
omSyntax: 64
isSingleValued: FALSE
schemaIdGuid: 9a7ad947-ca53-11d1-bbd0-0080c76670c0
systemOnly: TRUE
searchFlags: 0
systemFlags: FLAG_SCHEMA_BASE_OBJECT | FLAG_ATTR_IS_CONSTRUCTED |
FLAG_DOMAIN_DISALLOW_RENAME
```

Version-Specific Behavior: Implemented on ADAM, Windows Server 2008, AD LDS for Windows Vista, Windows Server 2008 R2, AD LDS for Windows 7, Windows Server 2012, AD LDS for Windows 8, Windows Server 2012 R2, AD LDS for Windows 8.1, Windows Server 2016 ~~Technical Preview~~, and AD LDS for Windows 10.

2.79 Attribute extendedCharsAllowed

This attribute indicates whether extended characters are allowed in the value of this attribute. Applies only to IA5, Numeric, Printable, and Teletex string attributes.

```
cn: Extended-Chars-Allowed
ldapDisplayName: extendedCharsAllowed
attributeId: 1.2.840.113556.1.2.380
attributeSyntax: 2.5.5.8
omSyntax: 1
isSingleValued: TRUE
schemaIdGuid: bf967966-0de6-11d0-a285-00aa003049e2
systemOnly: FALSE
searchFlags: 0
systemFlags: FLAG_SCHEMA_BASE_OBJECT
```

Version-Specific Behavior: Implemented on ADAM, Windows Server 2008, AD LDS for Windows Vista, Windows Server 2008 R2, AD LDS for Windows 7, Windows Server 2012, AD LDS for Windows 8, Windows Server 2012 R2, AD LDS for Windows 8.1, Windows Server 2016 ~~Technical Preview~~, and AD LDS for Windows 10.

2.80 Attribute extendedClassInfo

This attribute specifies a multivalued property containing strings that represent additional information for each class. Each value contains the governsID, LDAPDisplayName, and schemaIDGUID of the class.

```
cn: Extended-Class-Info
ldapDisplayName: extendedClassInfo
attributeId: 1.2.840.113556.1.4.908
attributeSyntax: 2.5.5.12
omSyntax: 64
isSingleValued: FALSE
schemaIdGuid: 9a7ad948-ca53-11d1-bbd0-0080c76670c0
systemOnly: TRUE
searchFlags: 0
systemFlags: FLAG_SCHEMA_BASE_OBJECT | FLAG_ATTR_IS_CONSTRUCTED |
FLAG_DOMAIN_DISALLOW_RENAME
```

Version-Specific Behavior: Implemented on ADAM, Windows Server 2008, AD LDS for Windows Vista, Windows Server 2008 R2, AD LDS for Windows 7, Windows Server 2012, AD LDS for Windows 8, Windows Server 2012 R2, AD LDS for Windows 8.1, Windows Server 2016 ~~Technical Preview~~, and AD LDS for Windows 10.

2.81 Attribute extensionName

This attribute specifies the name of a property page that is used to extend the UI of a directory object.

```
cn: Extension-Name
ldapDisplayName: extensionName
attributeId: 1.2.840.113556.1.2.227
attributeSyntax: 2.5.5.12
omSyntax: 64
isSingleValued: FALSE
schemaIdGuid: bf967972-0de6-11d0-a285-00aa003049e2
systemOnly: FALSE
rangeLower: 1
rangeUpper: 255
```

Version-Specific Behavior: Implemented on ADAM, Windows Server 2008, Active Directory Lightweight Directory Services for Windows Vista, Windows Server 2008 R2, AD LDS for Windows 7, Windows Server 2012, AD LDS for Windows 8, Windows Server 2012 R2, AD LDS for Windows 8.1, Windows Server 2016 ~~Technical Preview~~, and AD LDS for Windows 10.

2.82 Attribute extraColumns

This is a multivalued attribute whose values consist of a 5 tuple: (attribute name), (column title), (default visibility (0,1)), (column width (-1 for auto width)), 0 (reserved for future use; must has to be zero). This value is used by the Active Directory Users and Computers console.

```
cn: Extra-Columns
ldapDisplayName: extraColumns
attributeId: 1.2.840.113556.1.4.1687
attributeSyntax: 2.5.5.12
omSyntax: 64
isSingleValued: FALSE
schemaIdGuid: d24e2846-1dd9-4bcf-99d7-a6227cc86da7
systemOnly: FALSE
```

Version-Specific Behavior: Implemented on Windows Server 2008, AD LDS for Windows Vista, Windows Server 2008 R2, AD LDS for Windows 7, Windows Server 2012, AD LDS for Windows 8, Windows Server 2012 R2, AD LDS for Windows 8.1, Windows Server 2016 ~~Technical Preview~~, and AD LDS for Windows 10.

2.83 Attribute facsimileTelephoneNumber

This attribute contains the telephone number of the user's business fax machine.

```
cn: Facsimile-Telephone-Number
ldapDisplayName: facsimileTelephoneNumber
attributeId: 2.5.4.23
attributeSyntax: 2.5.5.12
omSyntax: 64
isSingleValued: TRUE
schemaIdGuid: bf967974-0de6-11d0-a285-00aa003049e2
systemOnly: FALSE
```

```
searchFlags: 0
rangeLower: 1
rangeUpper: 64
attributeSecurityGuid: 77b5b886-944a-11d1-aebd-0000f80367c1
systemFlags: FLAG_SCHEMA_BASE_OBJECT
```

Version-Specific Behavior: Implemented on ADAM, Windows Server 2008, AD LDS for Windows Vista, Windows Server 2008 R2, AD LDS for Windows 7, Windows Server 2012, AD LDS for Windows 8, Windows Server 2012 R2, AD LDS for Windows 8.1, Windows Server 2016 ~~Technical Preview~~, and AD LDS for Windows 10.

2.84 Attribute fromEntry

This is a constructed attribute that is TRUE if the object is writable and FALSE if it is read-only; for example, a global catalog (GC) replica instance.

```
cn: From-Entry
ldapDisplayName: fromEntry
attributeId: 1.2.840.113556.1.4.910
attributeSyntax: 2.5.5.8
omSyntax: 1
isSingleValued: FALSE
schemaIdGuid: 9a7ad949-ca53-11d1-bbd0-0080c76670c0
systemOnly: TRUE
searchFlags: 0
systemFlags: FLAG_SCHEMA_BASE_OBJECT | FLAG_ATTR_IS_CONSTRUCTED |
FLAG_DOMAIN_DISALLOW_RENAME
```

Version-Specific Behavior: Implemented on ADAM, Windows Server 2008, AD LDS for Windows Vista, Windows Server 2008 R2, AD LDS for Windows 7, Windows Server 2012, AD LDS for Windows 8, Windows Server 2012 R2, AD LDS for Windows 8.1, Windows Server 2016 ~~Technical Preview~~, and AD LDS for Windows 10.

2.85 Attribute fromServer

This attribute specifies the distinguished name of the replication source server.

```
cn: From-Server
ldapDisplayName: fromServer
attributeId: 1.2.840.113556.1.4.40
attributeSyntax: 2.5.5.1
omSyntax: 127
omObjectClass: 1.3.12.2.1011.28.0.714
isSingleValued: TRUE
schemaIdGuid: bf967979-0de6-11d0-a285-00aa003049e2
systemOnly: FALSE
searchFlags: 0
systemFlags: FLAG_SCHEMA_BASE_OBJECT
```

Version-Specific Behavior: Implemented on ADAM, Windows Server 2008, AD LDS for Windows Vista, Windows Server 2008 R2, AD LDS for Windows 7, Windows Server 2012, AD LDS for Windows 8, Windows Server 2012 R2, AD LDS for Windows 8.1, Windows Server 2016 ~~Technical Preview~~, and AD LDS for Windows 10.

2.86 Attribute fsmoRoleOwner

The fsmoRoleOwner attribute stores the distinguished name of a DSA object as described in [MS-ADTS] section 3.1.1.1.11 (FSMO Roles).

```
cn: FSMO-Role-Owner
ldapDisplayName: fSMORoleOwner
attributeId: 1.2.840.113556.1.4.369
attributeSyntax: 2.5.5.1
omSyntax: 127
omObjectClass: 1.3.12.2.1011.28.0.714
isSingleValued: TRUE
schemaIdGuid: 66171887-8f3c-11d0-afda-00c04fd930c9
systemOnly: FALSE
searchFlags: fATTINDEX
systemFlags: FLAG_SCHEMA_BASE_OBJECT
```

Version-Specific Behavior: Implemented on ADAM, Windows Server 2008, AD LDS for Windows Vista, Windows Server 2008 R2, AD LDS for Windows 7, Windows Server 2012, AD LDS for Windows 8, Windows Server 2012 R2, AD LDS for Windows 8.1, Windows Server 2016 ~~Technical Preview~~, and AD LDS for Windows 10.

2.87 Attribute garbageCollPeriod

This attribute is located on the CN=Directory Service,CN=Windows NT,CN=Services,CN=Configuration,... object. It represents the period of time, in hours, between directory service (DS) garbage collection runs.

```
cn: Garbage-Coll-Period
ldapDisplayName: garbageCollPeriod
attributeId: 1.2.840.113556.1.2.301
attributeSyntax: 2.5.5.9
omSyntax: 2
isSingleValued: TRUE
schemaIdGuid: 5fd424a1-1262-11d0-a060-00aa006c33ed
systemOnly: FALSE
searchFlags: 0
systemFlags: FLAG_SCHEMA_BASE_OBJECT
```

Version-Specific Behavior: Implemented on ADAM, Windows Server 2008, AD LDS for Windows Vista, Windows Server 2008 R2, AD LDS for Windows 7, Windows Server 2012, AD LDS for Windows 8, Windows Server 2012 R2, AD LDS for Windows 8.1, Windows Server 2016 ~~Technical Preview~~, and AD LDS for Windows 10.

2.88 Attribute generatedConnection

This attribute is TRUE if this connection was created by auto-topology generation.

```
cn: Generated-Connection
ldapDisplayName: generatedConnection
attributeId: 1.2.840.113556.1.4.41
attributeSyntax: 2.5.5.8
omSyntax: 1
isSingleValued: TRUE
schemaIdGuid: bf96797a-0de6-11d0-a285-00aa003049e2
systemOnly: FALSE
searchFlags: 0
systemFlags: FLAG_SCHEMA_BASE_OBJECT
```

Version-Specific Behavior: Implemented on ADAM, Windows Server 2008, AD LDS for Windows Vista, Windows Server 2008 R2, AD LDS for Windows 7, Windows Server 2012, AD LDS for Windows 8, Windows Server 2012 R2, AD LDS for Windows 8.1, Windows Server 2016 ~~Technical Preview~~, and AD LDS for Windows 10.

2.89 Attribute generationQualifier

This attribute indicates a person's generation; for example, "Jr." or "II".

```
cn: Generation-Qualifier
ldapDisplayName: generationQualifier
attributeId: 2.5.4.44
attributeSyntax: 2.5.5.12
omSyntax: 64
isSingleValued: TRUE
schemaIdGuid: 16775804-47f3-11d1-a9c3-0000f80367c1
systemOnly: FALSE
searchFlags: 0
rangeLower: 1
rangeUpper: 64
```

Version-Specific Behavior: Implemented on ADAM, Windows Server 2008, AD LDS for Windows Vista, Windows Server 2008 R2, AD LDS for Windows 7, Windows Server 2012, AD LDS for Windows 8, Windows Server 2012 R2, AD LDS for Windows 8.1, Windows Server 2016 ~~Technical Preview~~, and AD LDS for Windows 10.

2.90 Attribute givenName

This attribute contains the given name (first name) of the user.

```
cn: Given-Name
ldapDisplayName: givenName
attributeId: 2.5.4.42
attributeSyntax: 2.5.5.12
omSyntax: 64
isSingleValued: TRUE
schemaIdGuid: f0f8ff8e-1191-11d0-a060-00aa006c33ed
systemOnly: FALSE
searchFlags: fANR | fATTINDEX
rangeLower: 1
rangeUpper: 64
attributeSecurityGuid: e48d0154-bcf8-11d1-8702-00c04fb96050
isMemberOfPartialAttributeSet: TRUE
```

Version-Specific Behavior: Implemented on ADAM, Windows Server 2008, AD LDS for Windows Vista, Windows Server 2008 R2, AD LDS for Windows 7, Windows Server 2012, AD LDS for Windows 8, Windows Server 2012 R2, AD LDS for Windows 8.1, Windows Server 2016 ~~Technical Preview~~, and AD LDS for Windows 10.

2.91 Attribute governsID

This attribute specifies the unique object ID of the class defined by this Class-Schema object.

```
cn: Governs-ID
ldapDisplayName: governsID
attributeId: 1.2.840.113556.1.2.22
attributeSyntax: 2.5.5.2
omSyntax: 6
isSingleValued: TRUE
schemaIdGuid: bf96797d-0de6-11d0-a285-00aa003049e2
systemOnly: TRUE
searchFlags: fPRESERVEONDELETE
systemFlags: FLAG_SCHEMA_BASE_OBJECT
```


Version-Specific Behavior: Implemented on ADAM, Windows Server 2008, AD LDS for Windows Vista, Windows Server 2008 R2, AD LDS for Windows 7, Windows Server 2012, AD LDS for Windows 8, Windows Server 2012 R2, AD LDS for Windows 8.1, Windows Server 2016 ~~Technical Preview~~, and AD LDS for Windows 10.

2.92 Attribute groupType

This attribute contains a set of flags that define the type and scope of a group object. For more information about the possible values for this attribute, see the Remarks section of [MSDN-GroupType].

```
cn: Group-Type
ldapDisplayName: groupType
attributeId: 1.2.840.113556.1.4.750
attributeSyntax: 2.5.5.9
omSyntax: 2
isSingleValued: TRUE
schemaIdGuid: 9a9a021e-4a5b-11d1-a9c3-0000f80367c1
systemOnly: FALSE
searchFlags: fPRESERVEONDELETE | fATTINDEX
isMemberOfPartialAttributeSet: TRUE
systemFlags: FLAG_SCHEMA_BASE_OBJECT |
  FLAG_ATTR_REQ_PARTIAL_SET_MEMBER
```

Version-Specific Behavior: Implemented on ADAM, Windows Server 2008, AD LDS for Windows Vista, Windows Server 2008 R2, AD LDS for Windows 7, Windows Server 2012, AD LDS for Windows 8, Windows Server 2012 R2, AD LDS for Windows 8.1, Windows Server 2016 ~~Technical Preview~~, and AD LDS for Windows 10.

2.93 Attribute hasMasterNCs

This attribute specifies the DN for the naming contexts for the DC. It is a forward link for the Mastered-By attribute. This attribute is maintained for backward compatibility; msDS-hasMasterNCs ~~should be~~ used instead.

```
cn: Has-Master-NCs
ldapDisplayName: hasMasterNCs
attributeId: 1.2.840.113556.1.2.14
attributeSyntax: 2.5.5.1
omSyntax: 127
omObjectClass: 1.3.12.2.1011.28.0.714
isSingleValued: FALSE
schemaIdGuid: bf967982-0de6-11d0-a285-00aa003049e2
systemOnly: TRUE
searchFlags: 0
linkID: 76
systemFlags: FLAG_SCHEMA_BASE_OBJECT
```

Version-Specific Behavior: Implemented on ADAM, Windows Server 2008, AD LDS for Windows Vista, Windows Server 2008 R2, AD LDS for Windows 7, Windows Server 2012, AD LDS for Windows 8, Windows Server 2012 R2, AD LDS for Windows 8.1, Windows Server 2016 ~~Technical Preview~~, and AD LDS for Windows 10.

2.94 Attribute hasPartialReplicaNCs

This attribute specifies the sibling to Has-Master-NCs. Reflects the DN for all other-domain NCs that have been replicated into a global catalog.

```
cn: Has-Partial-Replica-NCs
ldapDisplayName: hasPartialReplicaNCs
attributeId: 1.2.840.113556.1.2.15
attributeSyntax: 2.5.5.1
omSyntax: 127
omObjectClass: 1.3.12.2.1011.28.0.714
isSingleValued: FALSE
schemaIdGuid: bf967981-0de6-11d0-a285-00aa003049e2
systemOnly: TRUE
searchFlags: 0
linkID: 74
systemFlags: FLAG_SCHEMA_BASE_OBJECT
```

Version-Specific Behavior: Implemented on ADAM, Windows Server 2008, AD LDS for Windows Vista, Windows Server 2008 R2, AD LDS for Windows 7, Windows Server 2012, AD LDS for Windows 8, Windows Server 2012 R2, AD LDS for Windows 8.1, Windows Server 2016 ~~Technical Preview~~, and AD LDS for Windows 10.

2.95 Attribute homePhone

This attribute specifies the user's main home phone number.

```
cn: Phone-Home-Primary
ldapDisplayName: homePhone
attributeId: 0.9.2342.19200300.100.1.20
attributeSyntax: 2.5.5.12
omSyntax: 64
isSingleValued: TRUE
schemaIdGuid: f0f8ffa1-1191-11d0-a060-00aa006c33ed
systemOnly: FALSE
searchFlags: 0
rangeLower: 1
rangeUpper: 64
attributeSecurityGuid: 77b5b886-944a-11d1-aebd-0000f80367c1
isMemberOfPartialAttributeSet: TRUE
```

Version-Specific Behavior: Implemented on ADAM, Windows Server 2008, AD LDS for Windows Vista, Windows Server 2008 R2, AD LDS for Windows 7, Windows Server 2012, AD LDS for Windows 8, Windows Server 2012 R2, AD LDS for Windows 8.1, Windows Server 2016 ~~Technical Preview~~, and AD LDS for Windows 10.

2.96 Attribute homePostalAddress

This attribute specifies the user's home address.

```
cn: Address-Home
ldapDisplayName: homePostalAddress
attributeId: 1.2.840.113556.1.2.617
attributeSyntax: 2.5.5.12
omSyntax: 64
isSingleValued: TRUE
schemaIdGuid: 16775781-47f3-11d1-a9c3-0000f80367c1
systemOnly: FALSE
searchFlags: 0
rangeLower: 1
rangeUpper: 4096
attributeSecurityGuid: 77b5b886-944a-11d1-aebd-0000f80367c1
```

Version-Specific Behavior: Implemented on ADAM, Windows Server 2008, AD LDS for Windows Vista, Windows Server 2008 R2, AD LDS for Windows 7, Windows Server 2012, AD LDS for Windows 8, Windows Server 2012 R2, AD LDS for Windows 8.1, Windows Server 2016 ~~Technical Preview~~, and AD LDS for Windows 10.

2.97 Attribute houseIdentifier

This attribute specifies a linguistic construct used to identify a particular building; for example, a house number or house name relative to a street, avenue, town, or city.

```
cn: houseIdentifier
ldapDisplayName: houseIdentifier
attributeId: 2.5.4.51
attributeSyntax: 2.5.5.12
omSyntax: 64
isSingleValued: FALSE
schemaIdGuid: a45398b7-c44a-4eb6-82d3-13c10946dbfe
systemOnly: FALSE
searchFlags: 0
rangeLower: 1
rangeUpper: 32768
```

Version-Specific Behavior: Implemented on ADAM, Windows Server 2008, AD LDS for Windows Vista, Windows Server 2008 R2, AD LDS for Windows 7, Windows Server 2012, AD LDS for Windows 8, Windows Server 2012 R2, AD LDS for Windows 8.1, Windows Server 2016 ~~Technical Preview~~, and AD LDS for Windows 10.

2.98 Attribute iconPath

This attribute specifies the source for loading an icon.

```
cn: Icon-Path
ldapDisplayName: iconPath
attributeId: 1.2.840.113556.1.4.219
attributeSyntax: 2.5.5.12
omSyntax: 64
isSingleValued: FALSE
schemaIdGuid: f0f8ff83-1191-11d0-a060-00aa006c33ed
systemOnly: FALSE
rangeLower: 0
rangeUpper: 2048
```

Version-Specific Behavior: Implemented on Windows Server 2008, AD LDS for Windows Vista, Windows Server 2008 R2, AD LDS for Windows 7, Windows Server 2012, AD LDS for Windows 8, Windows Server 2012 R2, AD LDS for Windows 8.1, Windows Server 2016 ~~Technical Preview~~, and AD LDS for Windows 10.

2.99 Attribute initials

This attribute contains the initials for parts of the user's full name. ~~MayIt can~~ be used as the middle initial in the Windows Address Book.

```
cn: Initials
ldapDisplayName: initials
attributeId: 2.5.4.43
attributeSyntax: 2.5.5.12
omSyntax: 64
isSingleValued: TRUE
```

```
schemaIdGuid: f0f8ff90-1191-11d0-a060-00aa006c33ed
systemOnly: FALSE
searchFlags: 0
rangeLower: 1
rangeUpper: 6
attributeSecurityGuid: e48d0154-bcf8-11d1-8702-00c04fb96050
```

Version-Specific Behavior: Implemented on ADAM, Windows Server 2008, AD LDS for Windows Vista, Windows Server 2008 R2, AD LDS for Windows 7, Windows Server 2012, AD LDS for Windows 8, Windows Server 2012 R2, AD LDS for Windows 8.1, Windows Server 2016 ~~Technical Preview~~, and AD LDS for Windows 10.

2.100 Attribute instanceType

This attribute specifies a bit field that dictates how the object is instantiated on a particular server. The value of this attribute can differ on different replicas, even if the replicas are in sync.

```
cn: Instance-Type
ldapDisplayName: instanceType
attributeId: 1.2.840.113556.1.2.1
attributeSyntax: 2.5.5.9
omSyntax: 2
isSingleValued: TRUE
schemaIdGuid: bf96798c-0de6-11d0-a285-00aa003049e2
systemOnly: TRUE
searchFlags: fPRESERVEONDELETE
isMemberOfPartialAttributeSet: TRUE
systemFlags: FLAG_SCHEMA_BASE_OBJECT |
FLAG_ATTR_REQ_PARTIAL_SET_MEMBER
```

Version-Specific Behavior: Implemented on ADAM, Windows Server 2008, AD LDS for Windows Vista, Windows Server 2008 R2, AD LDS for Windows 7, Windows Server 2012, AD LDS for Windows 8, Windows Server 2012 R2, AD LDS for Windows 8.1, Windows Server 2016 ~~Technical Preview~~, and AD LDS for Windows 10.

2.101 Attribute internationalISDNNumber

This attribute specifies an international ISDN number associated with an object.

```
cn: International-ISDN-Number
ldapDisplayName: internationalISDNNumber
attributeId: 2.5.4.25
attributeSyntax: 2.5.5.6
omSyntax: 18
isSingleValued: FALSE
schemaIdGuid: bf96798d-0de6-11d0-a285-00aa003049e2
systemOnly: FALSE
searchFlags: 0
rangeLower: 1
rangeUpper: 16
attributeSecurityGuid: 77b5b886-944a-11d1-aebd-0000f80367c1
systemFlags: FLAG_SCHEMA_BASE_OBJECT
```

Version-Specific Behavior: Implemented on ADAM, Windows Server 2008, AD LDS for Windows Vista, Windows Server 2008 R2, AD LDS for Windows 7, Windows Server 2012, AD LDS for Windows 8, Windows Server 2012 R2, AD LDS for Windows 8.1, Windows Server 2016 ~~Technical Preview~~, and AD LDS for Windows 10.

2.102 Attribute interSiteTopologyFailover

This attribute indicates how much time **musthas to** transpire since the last keep-alive in order for the intersite topology generator to be considered dead.

```
cn: Inter-Site-Topology-Failover
ldapDisplayName: interSiteTopologyFailover
attributeId: 1.2.840.113556.1.4.1248
attributeSyntax: 2.5.5.9
omSyntax: 2
isSingleValued: TRUE
schemaIdGuid: b7c69e60-2cc7-11d2-854e-00a0c983f608
systemOnly: FALSE
searchFlags: 0
systemFlags: FLAG_SCHEMA_BASE_OBJECT
```

Version-Specific Behavior: Implemented on ADAM, Windows Server 2008, AD LDS for Windows Vista, Windows Server 2008 R2, AD LDS for Windows 7, Windows Server 2012, AD LDS for Windows 8, Windows Server 2012 R2, AD LDS for Windows 8.1, Windows Server 2016 **Technical Preview**, and AD LDS for Windows 10.

2.103 Attribute interSiteTopologyGenerator

This attribute is used to support failover for the machine designated as the one that runs Knowledge Consistency Checker intersite topology generation in a given site.

```
cn: Inter-Site-Topology-Generator
ldapDisplayName: interSiteTopologyGenerator
attributeId: 1.2.840.113556.1.4.1246
attributeSyntax: 2.5.5.1
omSyntax: 127
omObjectClass: 1.3.12.2.1011.28.0.714
isSingleValued: TRUE
schemaIdGuid: b7c69e5e-2cc7-11d2-854e-00a0c983f608
systemOnly: FALSE
searchFlags: 0
systemFlags: FLAG_SCHEMA_BASE_OBJECT
```

Version-Specific Behavior: Implemented on ADAM, Windows Server 2008, AD LDS for Windows Vista, Windows Server 2008 R2, AD LDS for Windows 7, Windows Server 2012, AD LDS for Windows 8, Windows Server 2012 R2, AD LDS for Windows 8.1, Windows Server 2016 **Technical Preview**, and AD LDS for Windows 10.

2.104 Attribute interSiteTopologyRenew

This attribute indicates how often the intersite topology generator updates the keep-alive message that is sent to DCs contained in the same site.

```
cn: Inter-Site-Topology-Renew
ldapDisplayName: interSiteTopologyRenew
attributeId: 1.2.840.113556.1.4.1247
attributeSyntax: 2.5.5.9
omSyntax: 2
isSingleValued: TRUE
schemaIdGuid: b7c69e5f-2cc7-11d2-854e-00a0c983f608
systemOnly: FALSE
searchFlags: 0
systemFlags: FLAG_SCHEMA_BASE_OBJECT
```

Version-Specific Behavior: Implemented on ADAM, Windows Server 2008, AD LDS for Windows Vista, Windows Server 2008 R2, AD LDS for Windows 7, Windows Server 2012, AD LDS for Windows 8, Windows Server 2012 R2, AD LDS for Windows 8.1, Windows Server 2016 ~~Technical Preview~~, and AD LDS for Windows 10.

2.105 Attribute invocationId

This attribute is used to uniquely identify the specific version of the directory database associated with an AD-LDS instance.

```
cn: Invocation-Id
ldapDisplayName: invocationId
attributeId: 1.2.840.113556.1.2.115
attributeSyntax: 2.5.5.10
omSyntax: 4
isSingleValued: TRUE
schemaIdGuid: bf96798e-0de6-11d0-a285-00aa003049e2
systemOnly: TRUE
searchFlags: fATTINDEX
systemFlags: FLAG_SCHEMA_BASE_OBJECT
```

Version-Specific Behavior: Implemented on ADAM, Windows Server 2008, AD LDS for Windows Vista, Windows Server 2008 R2, AD LDS for Windows 7, Windows Server 2012, AD LDS for Windows 8, Windows Server 2012 R2, AD LDS for Windows 8.1, Windows Server 2016 ~~Technical Preview~~, and AD LDS for Windows 10.

2.106 Attribute ipPhone

This attribute specifies the TCP/IP address for the phone. Used by telephony.

```
cn: Phone-Ip-Primary
ldapDisplayName: ipPhone
attributeId: 1.2.840.113556.1.4.721
attributeSyntax: 2.5.5.12
omSyntax: 64
isSingleValued: TRUE
schemaIdGuid: 4d146e4a-48d4-11d1-a9c3-0000f80367c1
systemOnly: FALSE
searchFlags: 0
rangeUpper: 64
attributeSecurityGuid: 77b5b886-944a-11d1-aebd-0000f80367c1
isMemberOfPartialAttributeSet: TRUE
```

Version-Specific Behavior: Implemented on ADAM, Windows Server 2008, AD LDS for Windows Vista, Windows Server 2008 R2, AD LDS for Windows 7, Windows Server 2012, AD LDS for Windows 8, Windows Server 2012 R2, AD LDS for Windows 8.1, Windows Server 2016 ~~Technical Preview~~, and AD LDS for Windows 10.

2.107 Attribute isCriticalSystemObject

If TRUE, the object hosting this attribute must have to be replicated during installation of a new replica.

```
cn: Is-Critical-System-Object
ldapDisplayName: isCriticalSystemObject
attributeId: 1.2.840.113556.1.4.868
attributeSyntax: 2.5.5.8
omSyntax: 1
isSingleValued: TRUE
```

```
schemaIdGuid: 00fbf30d-91fe-11d1-aebc-0000f80367c1
systemOnly: FALSE
searchFlags: 0
systemFlags: FLAG_SCHEMA_BASE_OBJECT
```

Version-Specific Behavior: Implemented on ADAM, Windows Server 2008, AD LDS for Windows Vista, Windows Server 2008 R2, AD LDS for Windows 7, Windows Server 2012, AD LDS for Windows 8, Windows Server 2012 R2, AD LDS for Windows 8.1, Windows Server 2016 ~~Technical Preview~~, and AD LDS for Windows 10.

2.108 Attribute isDefunct

If TRUE, the class or attribute is no longer usable. Old versions of this object may exist, but new ones cannot be created.

```
cn: Is-Defunct
ldapDisplayName: isDefunct
attributeId: 1.2.840.113556.1.4.661
attributeSyntax: 2.5.5.8
omSyntax: 1
isSingleValued: TRUE
schemaIdGuid: 28630ebe-41d5-11d1-a9c1-0000f80367c1
systemOnly: FALSE
searchFlags: 0
systemFlags: FLAG_SCHEMA_BASE_OBJECT
```

Version-Specific Behavior: Implemented on ADAM, Windows Server 2008, AD LDS for Windows Vista, Windows Server 2008 R2, AD LDS for Windows 7, Windows Server 2012, AD LDS for Windows 8, Windows Server 2012 R2, AD LDS for Windows 8.1, Windows Server 2016 ~~Technical Preview~~, and AD LDS for Windows 10.

2.109 Attribute isDeleted

If TRUE, this object has been marked for deletion and will be removed from the Active Directory system.

```
cn: Is-Deleted
ldapDisplayName: isDeleted
attributeId: 1.2.840.113556.1.2.48
attributeSyntax: 2.5.5.8
omSyntax: 1
isSingleValued: TRUE
schemaIdGuid: bf96798f-0de6-11d0-a285-00aa003049e2
systemOnly: TRUE
searchFlags: 0
isMemberOfPartialAttributeSet: TRUE
systemFlags: FLAG_SCHEMA_BASE_OBJECT |
FLAG_ATTR_REQ_PARTIAL_SET_MEMBER
```

Version-Specific Behavior: Implemented on ADAM, Windows Server 2008, AD LDS for Windows Vista, Windows Server 2008 R2, AD LDS for Windows 7, Windows Server 2012, AD LDS for Windows 8, Windows Server 2012 R2, AD LDS for Windows 8.1, Windows Server 2016 ~~Technical Preview~~, and AD LDS for Windows 10.

2.110 Attribute isEphemeral

```
cn: Is-Ephemeral
ldapDisplayName: isEphemeral
```

```
attributeId: 1.2.840.113556.1.4.1212
attributeSyntax: 2.5.5.8
omSyntax: 1
isSingleValued: TRUE
schemaIdGuid: f4c453f0-c5f1-11d1-bbcb-0080c76670c0
systemOnly: TRUE
searchFlags: 0
systemFlags: FLAG_SCHEMA_BASE_OBJECT
```

Version-Specific Behavior: Implemented on ADAM, Windows Server 2008, AD LDS for Windows Vista, Windows Server 2008 R2, AD LDS for Windows 7, Windows Server 2012, AD LDS for Windows 8, Windows Server 2012 R2, AD LDS for Windows 8.1, Windows Server 2016 ~~Technical Preview~~, and AD LDS for Windows 10.

2.111 Attribute isMemberOfPartialAttributeSet

If TRUE, this attribute is replicated to the global catalog.

```
cn: Is-Member-Of-Partial-Attribute-Set
ldapDisplayName: isMemberOfPartialAttributeSet
attributeId: 1.2.840.113556.1.4.639
attributeSyntax: 2.5.5.8
omSyntax: 1
isSingleValued: TRUE
schemaIdGuid: 19405b9d-3cfa-11d1-a9c0-0000f80367c1
systemOnly: FALSE
searchFlags: 0
systemFlags: FLAG_SCHEMA_BASE_OBJECT
```

Version-Specific Behavior: Implemented on ADAM, Windows Server 2008, AD LDS for Windows Vista, Windows Server 2008 R2, AD LDS for Windows 7, Windows Server 2012, AD LDS for Windows 8, Windows Server 2012 R2, AD LDS for Windows 8.1, Windows Server 2016 ~~Technical Preview~~, and AD LDS for Windows 10.

2.112 Attribute isRecycled

If TRUE, this object has been marked for permanent deletion. Additionally, if the Recycle Bin optional feature is enabled, the value TRUE marks an object that cannot be undeleted. It will be removed from the Active Directory system.

```
cn: Is-Recycled
ldapDisplayName: isRecycled
attributeId: 1.2.840.113556.1.4.2058
attributeSyntax: 2.5.5.8
omSyntax: 1
isSingleValued: TRUE
schemaIdGuid: 8fb59256-55f1-444b-aacb-f5b482fe3459
systemOnly: TRUE
searchFlags: fPRESERVEONDELETE
systemFlags: FLAG_SCHEMA_BASE_OBJECT | FLAG_ATTR_REQ_PARTIAL_SET_MEMBER
```

Version-Specific Behavior: Implemented on Windows Server 2008 R2, AD LDS for Windows 7, Windows Server 2012, AD LDS for Windows 8, Windows Server 2012 R2, AD LDS for Windows 8.1, Windows Server 2016 ~~Technical Preview~~, and AD LDS for Windows 10.

2.113 Attribute isSingleValued

If TRUE, this attribute can only store one value.

```
cn: Is-Single-Valued
ldapDisplayName: isSingleValued
attributeId: 1.2.840.113556.1.2.33
attributeSyntax: 2.5.5.8
omSyntax: 1
isSingleValued: TRUE
schemaIdGuid: bf967992-0de6-11d0-a285-00aa003049e2
systemOnly: TRUE
searchFlags: 0
systemFlags: FLAG_SCHEMA_BASE_OBJECT
```

Version-Specific Behavior: Implemented on ADAM, Windows Server 2008, AD LDS for Windows Vista, Windows Server 2008 R2, AD LDS for Windows 7, Windows Server 2012, AD LDS for Windows 8, Windows Server 2012 R2, AD LDS for Windows 8.1, Windows Server 2016 ~~Technical Preview~~, and AD LDS for Windows 10.

2.114 Attribute jpegPhoto

This attribute is used to store one or more images of a person using the JPEG File Interchange Format [JFIF].

```
cn: jpegPhoto
ldapDisplayName: jpegPhoto
attributeId: 0.9.2342.19200300.100.1.60
attributeSyntax: 2.5.5.10
omSyntax: 4
isSingleValued: FALSE
schemaIdGuid: bac80572-09c4-4fa9-9ae6-7628d7adbe0e
systemOnly: FALSE
searchFlags: 0
showInAdvancedViewOnly: FALSE
```

Version-Specific Behavior: Implemented on ADAM, Windows Server 2008, AD LDS for Windows Vista, Windows Server 2008 R2, AD LDS for Windows 7, Windows Server 2012, AD LDS for Windows 8, Windows Server 2012 R2, AD LDS for Windows 8.1, Windows Server 2016 ~~Technical Preview~~, and AD LDS for Windows 10.

2.115 Attribute keywords

This attribute specifies a list of keywords that can be used to locate a given connection point.

```
cn: Keywords
ldapDisplayName: keywords
attributeId: 1.2.840.113556.1.4.48
attributeSyntax: 2.5.5.12
omSyntax: 64
isSingleValued: FALSE
schemaIdGuid: bf967993-0de6-11d0-a285-00aa003049e2
systemOnly: FALSE
searchFlags: fATTINDEX
rangeLower: 1
rangeUpper: 256
isMemberOfPartialAttributeSet: TRUE
systemFlags: FLAG_SCHEMA_BASE_OBJECT
```

Version-Specific Behavior: Implemented on ADAM, Windows Server 2008, AD LDS for Windows Vista, Windows Server 2008 R2, AD LDS for Windows 7, Windows Server 2012, AD LDS for Windows 8, Windows Server 2012 R2, AD LDS for Windows 8.1, Windows Server 2016 ~~Technical Preview~~, and AD LDS for Windows 10.

2.116 Attribute l

This attribute represents the name of a locality, such as a town or city.

```
cn: Locality-Name
ldapDisplayName: l
attributeId: 2.5.4.7
attributeSyntax: 2.5.5.12
omSyntax: 64
isSingleValued: TRUE
schemaIdGuid: bf9679a2-0de6-11d0-a285-00aa003049e2
systemOnly: FALSE
searchFlags: fCOPY | fATTINDEX
rangeLower: 1
rangeUpper: 128
attributeSecurityGuid: 77b5b886-944a-11d1-aebd-0000f80367c1
isMemberOfPartialAttributeSet: TRUE
systemFlags: FLAG_SCHEMA_BASE_OBJECT |
FLAG_ATTR_REQ_PARTIAL_SET_MEMBER
```

Version-Specific Behavior: Implemented on ADAM, Windows Server 2008, AD LDS for Windows Vista, Windows Server 2008 R2, AD LDS for Windows 7, Windows Server 2012, AD LDS for Windows 8, Windows Server 2012 R2, AD LDS for Windows 8.1, Windows Server 2016 ~~Technical Preview~~, and AD LDS for Windows 10.

2.117 Attribute labeledURI

This attribute specifies a Uniform Resource Identifier (URI) followed by a label. The label is used to describe the resource to which the URI points and is intended as a friendly name fit for human readers.

```
cn: labeledURI
ldapDisplayName: labeledURI
attributeId: 1.3.6.1.4.1.250.1.57
attributeSyntax: 2.5.5.12
omSyntax: 64
isSingleValued: FALSE
schemaIdGuid: c569bb46-c680-44bc-a273-e6c227d71b45
systemOnly: FALSE
searchFlags: 0
showInAdvancedViewOnly: FALSE
```

Version-Specific Behavior: Implemented on ADAM, Windows Server 2008, AD LDS for Windows Vista, Windows Server 2008 R2, AD LDS for Windows 7, Windows Server 2012, AD LDS for Windows 8, Windows Server 2012 R2, AD LDS for Windows 8.1, Windows Server 2016 ~~Technical Preview~~, and AD LDS for Windows 10.

2.118 Attribute lastAgedChange

ms-DS-Last-Aged-Change

```
cn: ms-DS-Last-Aged-Change
ldapDisplayName: lastAgedChange
```

```
attributeId: 1.2.840.113556.1.4.1888
attributeSyntax: 2.5.5.11
omSyntax: 24
isSingleValued: FALSE

searchFlags: fATTINDEX
```

Version-Specific Behavior: Implemented on ADAM, Windows Server 2008, AD LDS for Windows Vista, Windows Server 2008 R2, AD LDS for Windows 7, Windows Server 2012, AD LDS for Windows 8, Windows Server 2012 R2, AD LDS for Windows 8.1, Windows Server 2016 ~~Technical Preview~~, and AD LDS for Windows 10.

2.119 Attribute lastBackupRestorationTime

This attribute specifies the time when the last system restore operation occurred.

```
cn: Last-Backup-Restoration-Time
ldapDisplayName: lastBackupRestorationTime
attributeId: 1.2.840.113556.1.4.519
attributeSyntax: 2.5.5.16
omSyntax: 65
isSingleValued: TRUE
schemaIdGuid: 1fbb0be8-ba63-11d0-afef-0000f80367c1
systemOnly: FALSE
searchFlags: 0
systemFlags: FLAG_SCHEMA_BASE_OBJECT
```

Version-Specific Behavior: Implemented on ADAM, Windows Server 2008, AD LDS for Windows Vista, Windows Server 2008 R2, AD LDS for Windows 7, Windows Server 2012, AD LDS for Windows 8, Windows Server 2012 R2, AD LDS for Windows 8.1, Windows Server 2016 ~~Technical Preview~~, and AD LDS for Windows 10.

2.120 Attribute lastKnownParent

This attribute specifies the DN of the last known parent of an orphaned or deleted object.

```
cn: Last-Known-Parent
ldapDisplayName: lastKnownParent
attributeId: 1.2.840.113556.1.4.781
attributeSyntax: 2.5.5.1
omSyntax: 127
omObjectClass: 1.3.12.2.1011.28.0.714
isSingleValued: TRUE
schemaIdGuid: 52ab8670-5709-11d1-a9c6-0000f80367c1
systemOnly: FALSE
searchFlags: 0
systemFlags: FLAG_SCHEMA_BASE_OBJECT
```

Version-Specific Behavior: Implemented on ADAM, Windows Server 2008, AD LDS for Windows Vista, Windows Server 2008 R2, AD LDS for Windows 7, Windows Server 2012, AD LDS for Windows 8, Windows Server 2012 R2, AD LDS for Windows 8.1, Windows Server 2016 ~~Technical Preview~~, and AD LDS for Windows 10.

2.121 Attribute lastLogonTimestamp

This attribute specifies the time at which the user last logged on to the domain. This value is only updated if the user logs on after a week has passed since the last update. This value is replicated.

```
cn: Last-Logon-Timestamp
ldapDisplayName: lastLogonTimestamp
attributeId: 1.2.840.113556.1.4.1696
attributeSyntax: 2.5.5.16
omSyntax: 65
isSingleValued: TRUE
schemaIdGuid: c0e20a04-0e5a-4ff3-9482-5efeaeed7060
systemOnly: TRUE
searchFlags: 0
attributeSecurityGuid: 5f202010-79a5-11d0-9020-00c04fc2d4cf
systemFlags: FLAG_SCHEMA_BASE_OBJECT
```

Version-Specific Behavior: Implemented on ADAM, Windows Server 2008, AD LDS for Windows Vista, Windows Server 2008 R2, AD LDS for Windows 7, Windows Server 2012, AD LDS for Windows 8, Windows Server 2012 R2, AD LDS for Windows 8.1, Windows Server 2016 ~~Technical Preview~~, and AD LDS for Windows 10.

2.122 Attribute LDAPAdminLimits

This attribute contains a set of attribute/value pairs that define Lightweight Directory Access Protocol (LDAP) server administrative limits.

```
cn: LDAP-Admin-Limits
ldapDisplayName: LDAPAdminLimits
attributeId: 1.2.840.113556.1.4.843
attributeSyntax: 2.5.5.12
omSyntax: 64
isSingleValued: FALSE
schemaIdGuid: 7359a352-90f7-11d1-aebc-0000f80367c1
systemOnly: FALSE
searchFlags: 0
systemFlags: FLAG_SCHEMA_BASE_OBJECT
```

Version-Specific Behavior: Implemented on ADAM, Windows Server 2008, AD LDS for Windows Vista, Windows Server 2008 R2, AD LDS for Windows 7, Windows Server 2012, AD LDS for Windows 8, Windows Server 2012 R2, AD LDS for Windows 8.1, Windows Server 2016 ~~Technical Preview~~, and AD LDS for Windows 10.

2.123 Attribute LDAPDisplayName

This attribute specifies the name used by LDAP clients, such as the ADSI LDAP provider, to read and write the attribute by using the LDAP protocol.

```
cn: LDAP-Display-Name
ldapDisplayName: LDAPDisplayName
attributeId: 1.2.840.113556.1.2.460
attributeSyntax: 2.5.5.12
omSyntax: 64
isSingleValued: TRUE
schemaIdGuid: bf96799a-0de6-11d0-a285-00aa003049e2
systemOnly: FALSE
searchFlags: fPRESERVEONDELETE | fATTINDEX
rangeLower: 1
rangeUpper: 256
isMemberOfPartialAttributeSet: TRUE
systemFlags: FLAG_SCHEMA_BASE_OBJECT
```

Version-Specific Behavior: Implemented on ADAM, Windows Server 2008, AD LDS for Windows Vista, Windows Server 2008 R2, AD LDS for Windows 7, Windows Server 2012, AD LDS for Windows 8,

Windows Server 2012 R2, AD LDS for Windows 8.1, Windows Server 2016 ~~Technical Preview~~, and AD LDS for Windows 10.

2.124 Attribute IDAPIDenyList

This attribute holds a list of binary IP addresses that are denied access to an LDAP server.

```
cn: LDAP-IPDeny-List
ldapDisplayName: LDAPIPDenyList
attributeId: 1.2.840.113556.1.4.844
attributeSyntax: 2.5.5.10
omSyntax: 4
isSingleValued: FALSE
schemaIdGuid: 7359a353-90f7-11d1-aebc-0000f80367c1
systemOnly: FALSE
searchFlags: 0
systemFlags: FLAG_SCHEMA_BASE_OBJECT
```

Version-Specific Behavior: Implemented on ADAM, Windows Server 2008, AD LDS for Windows Vista, Windows Server 2008 R2, AD LDS for Windows 7, Windows Server 2012, AD LDS for Windows 8, Windows Server 2012 R2, AD LDS for Windows 8.1, Windows Server 2016 ~~Technical Preview~~, and AD LDS for Windows 10.

2.125 Attribute linkID

This attribute specifies an integer that indicates that the attribute is a linked attribute. An even integer is a forward link, and an odd integer is a back link.

```
cn: Link-ID
ldapDisplayName: linkID
attributeId: 1.2.840.113556.1.2.50
attributeSyntax: 2.5.5.9
omSyntax: 2
isSingleValued: TRUE
schemaIdGuid: bf96799b-0de6-11d0-a285-00aa003049e2
systemOnly: TRUE
searchFlags: 0
systemFlags: FLAG_SCHEMA_BASE_OBJECT
```

Version-Specific Behavior: Implemented on ADAM, Windows Server 2008, AD LDS for Windows Vista, Windows Server 2008 R2, AD LDS for Windows 7, Windows Server 2012, AD LDS for Windows 8, Windows Server 2012 R2, AD LDS for Windows 8.1, Windows Server 2016 ~~Technical Preview~~, and AD LDS for Windows 10.

2.126 Attribute localizationDisplayId

This attribute is used to index into the Extrts.mc file to get the localized displayName of the objects for UI purposes.

```
cn: Localization-Display-Id
ldapDisplayName: localizationDisplayId
attributeId: 1.2.840.113556.1.4.1353
attributeSyntax: 2.5.5.9
omSyntax: 2
isSingleValued: TRUE
schemaIdGuid: a746f0d1-78d0-11d2-9916-0000f87a57d4
systemOnly: FALSE
searchFlags: 0
```

```
systemFlags: FLAG_SCHEMA_BASE_OBJECT
```

Version-Specific Behavior: Implemented on ADAM, Windows Server 2008, AD LDS for Windows Vista, Windows Server 2008 R2, AD LDS for Windows 7, Windows Server 2012, AD LDS for Windows 8, Windows Server 2012 R2, AD LDS for Windows 8.1, Windows Server 2016 ~~Technical Preview~~, and AD LDS for Windows 10.

2.127 Attribute location

This attribute specifies the user's location, such as an office number.

```
cn: Location
ldapDisplayName: location
attributeId: 1.2.840.113556.1.4.222
attributeSyntax: 2.5.5.12
omSyntax: 64
isSingleValued: TRUE
schemaIdGuid: 09dcb79f-165f-11d0-a064-00aa006c33ed
systemOnly: FALSE
searchFlags: fATTINDEX
rangeLower: 0
rangeUpper: 1024
isMemberOfPartialAttributeSet: TRUE
systemFlags: FLAG_SCHEMA_BASE_OBJECT
```

Version-Specific Behavior: Implemented on ADAM, Windows Server 2008, AD LDS for Windows Vista, Windows Server 2008 R2, AD LDS for Windows 7, Windows Server 2012, AD LDS for Windows 8, Windows Server 2012 R2, AD LDS for Windows 8.1, Windows Server 2016 ~~Technical Preview~~, and AD LDS for Windows 10.

2.128 Attribute lockoutTime

This attribute specifies the date and time (in UTC) that this account was locked out. This value is stored as a large integer that represents the number of 100-nanosecond intervals since January 1, 1601 (UTC). A value of zero means that the account is not currently locked out.

```
cn: Lockout-Time
ldapDisplayName: lockoutTime
attributeId: 1.2.840.113556.1.4.662
attributeSyntax: 2.5.5.16
omSyntax: 65
isSingleValued: TRUE
schemaIdGuid: 28630ebf-41d5-11d1-a9c1-0000f80367c1
systemOnly: FALSE
searchFlags: 0
systemFlags: FLAG_SCHEMA_BASE_OBJECT
```

Version-Specific Behavior: Implemented on ADAM, Windows Server 2008, AD LDS for Windows Vista, Windows Server 2008 R2, AD LDS for Windows 7, Windows Server 2012, AD LDS for Windows 8, Windows Server 2012 R2, AD LDS for Windows 8.1, Windows Server 2016 ~~Technical Preview~~, and AD LDS for Windows 10.

2.129 Attribute mail

This attribute specifies the list of email addresses for a contact.

```
cn: E-mail-Addresses
```

```
ldapDisplayName: mail
attributeId: 0.9.2342.19200300.100.1.3
attributeSyntax: 2.5.5.12
omSyntax: 64
isSingleValued: TRUE
schemaIdGuid: bf967961-0de6-11d0-a285-00aa003049e2
systemOnly: FALSE
searchFlags: fATTINDEX
rangeLower: 0
rangeUpper: 256
attributeSecurityGuid: e48d0154-bcf8-11d1-8702-00c04fb96050
isMemberOfPartialAttributeSet: TRUE
```

Version-Specific Behavior: Implemented on ADAM, Windows Server 2008, AD LDS for Windows Vista, Windows Server 2008 R2, AD LDS for Windows 7, Windows Server 2012, AD LDS for Windows 8, Windows Server 2012 R2, AD LDS for Windows 8.1, Windows Server 2016 ~~Technical Preview~~, and AD LDS for Windows 10.

2.130 Attribute mailAddress

This attribute specifies the generic mail address attribute. It is used "in the box" as an optional attribute of server objects, where it is consumed by mail-based DS replication (if the machines are so configured).

```
cn: SMTP-Mail-Address
ldapDisplayName: mailAddress
attributeId: 1.2.840.113556.1.4.786
attributeSyntax: 2.5.5.12
omSyntax: 64
isSingleValued: TRUE
schemaIdGuid: 26d9736f-6070-11d1-a9c6-0000f80367c1
systemOnly: FALSE
searchFlags: 0
systemFlags: FLAG_SCHEMA_BASE_OBJECT
```

Version-Specific Behavior: Implemented on ADAM, Windows Server 2008, AD LDS for Windows Vista, Windows Server 2008 R2, AD LDS for Windows 7, Windows Server 2012, AD LDS for Windows 8, Windows Server 2012 R2, AD LDS for Windows 8.1, Windows Server 2016 ~~Technical Preview~~, and AD LDS for Windows 10.

2.131 Attribute managedBy

This attribute specifies the DN of the object that is assigned to manage this object.

```
cn: Managed-By
ldapDisplayName: managedBy
attributeId: 1.2.840.113556.1.4.653
attributeSyntax: 2.5.5.1
omSyntax: 127
omObjectClass: 1.3.12.2.1011.28.0.714
isSingleValued: TRUE
schemaIdGuid: 0296c120-40da-11d1-a9c0-0000f80367c1
systemOnly: FALSE
searchFlags: 0
linkID: 72
systemFlags: FLAG_SCHEMA_BASE_OBJECT
```

Version-Specific Behavior: Implemented on ADAM, Windows Server 2008, AD LDS for Windows Vista, Windows Server 2008 R2, AD LDS for Windows 7, Windows Server 2012, AD LDS for Windows 8,

Windows Server 2012 R2, AD LDS for Windows 8.1, Windows Server 2016 ~~Technical Preview~~, and AD LDS for Windows 10.

2.132 Attribute managedObjects

This attribute contains the list of objects that are managed by the user. The objects listed are those that have the managedBy property set to this user. Each item in the list is a linked reference to the managed object.

```
cn: Managed-Objects
ldapDisplayName: managedObjects
attributeId: 1.2.840.113556.1.4.654
attributeSyntax: 2.5.5.1
omSyntax: 127
omObjectClass: 1.3.12.2.1011.28.0.714
isSingleValued: FALSE
schemaIdGuid: 0296c124-40da-11d1-a9c0-0000f80367c1
systemOnly: TRUE
searchFlags: 0
linkID: 73
systemFlags: FLAG_SCHEMA_BASE_OBJECT | FLAG_ATTR_NOT_REPLICATED
```

Version-Specific Behavior: Implemented on ADAM, Windows Server 2008, AD LDS for Windows Vista, Windows Server 2008 R2, AD LDS for Windows 7, Windows Server 2012, AD LDS for Windows 8, Windows Server 2012 R2, AD LDS for Windows 8.1, Windows Server 2016 ~~Technical Preview~~, and AD LDS for Windows 10.

2.133 Attribute manager

This attribute contains the DN of the user who is the user's manager. The manager's user object contains a directReports property that contains references to all user objects that have their manager properties set to this DN.

```
cn: Manager
ldapDisplayName: manager
attributeId: 0.9.2342.19200300.100.1.10
attributeSyntax: 2.5.5.1
omSyntax: 127
omObjectClass: 1.3.12.2.1011.28.0.714
isSingleValued: TRUE
schemaIdGuid: bf9679b5-0de6-11d0-a285-00aa003049e2
systemOnly: FALSE
searchFlags: fCOPY
attributeSecurityGuid: e48d0154-bcf8-11d1-8702-00c04fb96050
linkID: 42
isMemberOfPartialAttributeSet: TRUE
```

Version-Specific Behavior: Implemented on ADAM, Windows Server 2008, AD LDS for Windows Vista, Windows Server 2008 R2, AD LDS for Windows 7, Windows Server 2012, AD LDS for Windows 8, Windows Server 2012 R2, AD LDS for Windows 8.1, Windows Server 2016 ~~Technical Preview~~, and AD LDS for Windows 10.

2.134 Attribute masteredBy

This attribute specifies the back link for the Has-Master-NCs attribute. The DN for its NTDS Settings objects.

```
cn: Mastered-By
```



```
ldapDisplayName: masteredBy
attributeId: 1.2.840.113556.1.4.1409
attributeSyntax: 2.5.5.1
omSyntax: 127
omObjectClass: 1.3.12.2.1011.28.0.714
isSingleValued: FALSE
schemaIdGuid: e48e64e0-12c9-11d3-9102-00c04fd91ab1
systemOnly: TRUE
searchFlags: 0
linkID: 77
systemFlags: FLAG_SCHEMA_BASE_OBJECT | FLAG_ATTR_NOT_REPLICATED
```

Version-Specific Behavior: Implemented on ADAM, Windows Server 2008, AD LDS for Windows Vista, Windows Server 2008 R2, AD LDS for Windows 7, Windows Server 2012, AD LDS for Windows 8, Windows Server 2012 R2, AD LDS for Windows 8.1, Windows Server 2016 **Technical Preview**, and AD LDS for Windows 10.

2.135 Attribute mayContain

This attribute specifies the list of optional attributes for a class.

```
cn: May-Contain
ldapDisplayName: mayContain
attributeId: 1.2.840.113556.1.2.25
attributeSyntax: 2.5.5.2
omSyntax: 6
isSingleValued: FALSE
schemaIdGuid: bf9679bf-0de6-11d0-a285-00aa003049e2
systemOnly: FALSE
searchFlags: 0
systemFlags: FLAG_SCHEMA_BASE_OBJECT
```

Version-Specific Behavior: Implemented on ADAM, Windows Server 2008, AD LDS for Windows Vista, Windows Server 2008 R2, AD LDS for Windows 7, Windows Server 2012, AD LDS for Windows 8, Windows Server 2012 R2, AD LDS for Windows 8.1, Windows Server 2016 **Technical Preview**, and AD LDS for Windows 10.

2.136 Attribute member

This attribute specifies the list of users that belong to the group.

```
cn: Member
ldapDisplayName: member
attributeId: 2.5.4.31
attributeSyntax: 2.5.5.1
omSyntax: 127
omObjectClass: 1.3.12.2.1011.28.0.714
isSingleValued: FALSE
schemaIdGuid: bf9679c0-0de6-11d0-a285-00aa003049e2
systemOnly: FALSE
searchFlags: 0
attributeSecurityGuid: bc0ac240-79a9-11d0-9020-00c04fc2d4cf
linkID: 2
isMemberOfPartialAttributeSet: TRUE
systemFlags: FLAG_SCHEMA_BASE_OBJECT |
FLAG_ATTR_REQ_PARTIAL_SET_MEMBER
```

Version-Specific Behavior: Implemented on ADAM, Windows Server 2008, AD LDS for Windows Vista, Windows Server 2008 R2, AD LDS for Windows 7, Windows Server 2012, AD LDS for Windows 8,

Windows Server 2012 R2, AD LDS for Windows 8.1, Windows Server 2016 ~~Technical Preview~~, and AD LDS for Windows 10.

2.137 Attribute memberOf

This attribute specifies the DN of the groups to which this object belongs.

```
cn: Is-Member-Of-DL
ldapDisplayName: memberOf
attributeId: 1.2.840.113556.1.2.102
attributeSyntax: 2.5.5.1
omSyntax: 127
omObjectClass: 1.3.12.2.1011.28.0.714
isSingleValued: FALSE
schemaIdGuid: bf967991-0de6-11d0-a285-00aa003049e2
systemOnly: TRUE
searchFlags: fCOPY
attributeSecurityGuid: bc0ac240-79a9-11d0-9020-00c04fc2d4cf
linkID: 3
systemFlags: FLAG_SCHEMA_BASE_OBJECT | FLAG_ATTR_NOT_REPLICATED
```

Version-Specific Behavior: Implemented on ADAM, Windows Server 2008, AD LDS for Windows Vista, Windows Server 2008 R2, AD LDS for Windows 7, Windows Server 2012, AD LDS for Windows 8, Windows Server 2012 R2, AD LDS for Windows 8.1, Windows Server 2016 ~~Technical Preview~~, and AD LDS for Windows 10.

2.138 Attribute middleName

This attribute specifies additional names for a user; for example, middle name, patronymic, matronymic, or others.

```
cn: Other-Name
ldapDisplayName: middleName
attributeId: 2.16.840.1.113730.3.1.34
attributeSyntax: 2.5.5.12
omSyntax: 64
isSingleValued: TRUE
schemaIdGuid: bf9679f2-0de6-11d0-a285-00aa003049e2
systemOnly: FALSE
searchFlags: 0
rangeLower: 0
rangeUpper: 64
```

Version-Specific Behavior: Implemented on ADAM, Windows Server 2008, AD LDS for Windows Vista, Windows Server 2008 R2, AD LDS for Windows 7, Windows Server 2012, AD LDS for Windows 8, Windows Server 2012 R2, AD LDS for Windows 8.1, Windows Server 2016 ~~Technical Preview~~, and AD LDS for Windows 10.

2.139 Attribute mobile

This attribute specifies the primary cellular phone number for a user.

```
cn: Phone-Mobile-Primary
ldapDisplayName: mobile
attributeId: 0.9.2342.19200300.100.1.41
attributeSyntax: 2.5.5.12
omSyntax: 64
isSingleValued: TRUE
schemaIdGuid: f0f8ffa3-1191-11d0-a060-00aa006c33ed
```

```
systemOnly: FALSE
searchFlags: 0
rangeLower: 1
rangeUpper: 64
attributeSecurityGuid: 77b5b886-944a-11d1-aebd-0000f80367c1
```

Version-Specific Behavior: Implemented on ADAM, Windows Server 2008, AD LDS for Windows Vista, Windows Server 2008 R2, AD LDS for Windows 7, Windows Server 2012, AD LDS for Windows 8, Windows Server 2012 R2, AD LDS for Windows 8.1, Windows Server 2016 ~~Technical Preview~~, and AD LDS for Windows 10.

2.140 Attribute modifyTimeStamp

This attribute specifies the date when this object was last changed. This value is replicated.

```
cn: Modify-Time-Stamp
ldapDisplayName: modifyTimeStamp
attributeId: 2.5.18.2
attributeSyntax: 2.5.5.11
omSyntax: 24
isSingleValued: TRUE
schemaIdGuid: 9a7ad94a-ca53-11d1-bbd0-0080c76670c0
systemOnly: TRUE
searchFlags: 0
systemFlags: FLAG_SCHEMA_BASE_OBJECT | FLAG_ATTR_IS_CONSTRUCTED |
FLAG_DOMAIN_DISALLOW_RENAME
```

Version-Specific Behavior: Implemented on ADAM, Windows Server 2008, AD LDS for Windows Vista, Windows Server 2008 R2, AD LDS for Windows 7, Windows Server 2012, AD LDS for Windows 8, Windows Server 2012 R2, AD LDS for Windows 8.1, Windows Server 2016 ~~Technical Preview~~, and AD LDS for Windows 10.

2.141 Attribute moveTreeState

This attribute is not necessary for Active Directory Lightweight Directory Services (AD LDS) to function. The protocol does not define a format beyond that required by the schema.

```
cn: Move-Tree-State
ldapDisplayName: moveTreeState
attributeId: 1.2.840.113556.1.4.1305
attributeSyntax: 2.5.5.10
omSyntax: 4
isSingleValued: FALSE
schemaIdGuid: 1f2ac2c8-3b71-11d2-90cc-00c04fd91ab1
systemOnly: FALSE
searchFlags: 0
systemFlags: FLAG_SCHEMA_BASE_OBJECT
```

Version-Specific Behavior: Implemented on ADAM, Windows Server 2008, AD LDS for Windows Vista, Windows Server 2008 R2, AD LDS for Windows 7, Windows Server 2012, AD LDS for Windows 8, Windows Server 2012 R2, AD LDS for Windows 8.1, Windows Server 2016 ~~Technical Preview~~, and AD LDS for Windows 10.

2.142 Attribute mS-DS-ConsistencyChildCount

This attribute is not necessary for Active Directory to function. The protocol does not define a format beyond that required by the schema.

```
cn: MS-DS-Consistency-Child-Count
ldapDisplayName: mS-DS-ConsistencyChildCount
attributeId: 1.2.840.113556.1.4.1361
attributeSyntax: 2.5.5.9
omSyntax: 2
isSingleValued: TRUE
schemaIdGuid: 178b7bc2-b63a-11d2-90e1-00c04fd91ab1
systemOnly: FALSE
searchFlags: 0
systemFlags: FLAG_SCHEMA_BASE_OBJECT
```

Version-Specific Behavior: Implemented on ADAM, Windows Server 2008, AD LDS for Windows Vista, Windows Server 2008 R2, AD LDS for Windows 7, Windows Server 2012, AD LDS for Windows 8, Windows Server 2012 R2, AD LDS for Windows 8.1, Windows Server 2016 ~~Technical Preview~~, and AD LDS for Windows 10.

2.143 Attribute mS-DS-ConsistencyGuid

This attribute is not necessary for Active Directory to function. The protocol does not define a format beyond that required by the schema.

```
cn: MS-DS-Consistency-Guid
ldapDisplayName: mS-DS-ConsistencyGuid
attributeId: 1.2.840.113556.1.4.1360
attributeSyntax: 2.5.5.10
omSyntax: 4
isSingleValued: TRUE
schemaIdGuid: 23773dc2-b63a-11d2-90e1-00c04fd91ab1
systemOnly: FALSE
searchFlags: 0
systemFlags: FLAG_SCHEMA_BASE_OBJECT
```

Version-Specific Behavior: Implemented on ADAM, Windows Server 2008, AD LDS for Windows Vista, Windows Server 2008 R2, AD LDS for Windows 7, Windows Server 2012, AD LDS for Windows 8, Windows Server 2012 R2, AD LDS for Windows 8.1, Windows Server 2016 ~~Technical Preview~~, and AD LDS for Windows 10.

2.144 Attribute mS-DS-ReplicatesNCREason

This is an attribute of an nTDSConnection object that indicates why (or whether) the Knowledge Consistency Checker (KCC) concludes that the connection is useful in the replication topology. This attribute is multivalued and has DistName+Binary syntax, where the binary part is an int-size bit field.

```
cn: MS-DS-Replicates-NC-Reason
ldapDisplayName: mS-DS-ReplicatesNCREason
attributeId: 1.2.840.113556.1.4.1408
attributeSyntax: 2.5.5.7
omSyntax: 127
omObjectClass: 1.2.840.113556.1.1.1.11
isSingleValued: FALSE
schemaIdGuid: 0ea12b84-08b3-11d3-91bc-0000f87a57d4
systemOnly: FALSE
searchFlags: 0
systemFlags: FLAG_SCHEMA_BASE_OBJECT
```

Version-Specific Behavior: Implemented on ADAM, Windows Server 2008, AD LDS for Windows Vista, Windows Server 2008 R2, AD LDS for Windows 7, Windows Server 2012, AD LDS for Windows 8,

Windows Server 2012 R2, AD LDS for Windows 8.1, Windows Server 2016 ~~Technical Preview~~, and AD LDS for Windows 10.

2.145 Attribute ms-DS-UserAccountAutoLocked

This attribute specifies a Boolean flag that indicates whether the account that this attribute references has been locked out. (TRUE means locked out.)

```
cn: ms-DS-User-Account-Auto-Locked
ldapDisplayName: ms-DS-UserAccountAutoLocked
attributeId: 1.2.840.113556.1.4.1857
attributeSyntax: 2.5.5.8
omSyntax: 1
isSingleValued: TRUE
schemaIdGuid: f2dd7bab-1f3b-47cf-89fa-143b56ad0a3d
systemOnly: FALSE
searchFlags: 0
systemFlags: FLAG_SCHEMA_BASE_OBJECT | FLAG_ATTR_IS_CONSTRUCTED
```

Version-Specific Behavior: Implemented on ADAM, Windows Server 2008, AD LDS for Windows Vista, Windows Server 2008 R2, AD LDS for Windows 7, Windows Server 2012, AD LDS for Windows 8, Windows Server 2012 R2, AD LDS for Windows 8.1, Windows Server 2016 ~~Technical Preview~~, and AD LDS for Windows 10.

2.146 Attribute ms-DS-UserEncryptedTextPasswordAllowed

This attribute specifies a Boolean flag that controls whether Active Directory stores the password in reversible encryption format.

```
cn: ms-DS-User-Encrypted-Text-Password-Allowed
ldapDisplayName: ms-DS-UserEncryptedTextPasswordAllowed
attributeId: 1.2.840.113556.1.4.1856
attributeSyntax: 2.5.5.8
omSyntax: 1
isSingleValued: TRUE
schemaIdGuid: 5a87c7f2-93c5-454c-a8c5-8cb09613292e
systemOnly: FALSE
searchFlags: 0
systemFlags: FLAG_SCHEMA_BASE_OBJECT
```

Version-Specific Behavior: Implemented on ADAM, Windows Server 2008, AD LDS for Windows Vista, Windows Server 2008 R2, AD LDS for Windows 7, Windows Server 2012, AD LDS for Windows 8, Windows Server 2012 R2, AD LDS for Windows 8.1, Windows Server 2016 ~~Technical Preview~~, and AD LDS for Windows 10.

2.147 Attribute ms-DS-UserPasswordNotRequired

This attribute specifies a Boolean flag that controls whether a password is required for the account that this attribute references.

```
cn: ms-DS-User-Password-Not-Required
ldapDisplayName: ms-DS-UserPasswordNotRequired
attributeId: 1.2.840.113556.1.4.1854
attributeSyntax: 2.5.5.8
omSyntax: 1
isSingleValued: TRUE
schemaIdGuid: 8f066172-a25e-4f53-8dcd-0a67d5fb883d
systemOnly: FALSE
```

```
searchFlags: 0
systemFlags: FLAG_SCHEMA_BASE_OBJECT
```

Version-Specific Behavior: Implemented on ADAM, Windows Server 2008, AD LDS for Windows Vista, Windows Server 2008 R2, AD LDS for Windows 7, Windows Server 2012, AD LDS for Windows 8, Windows Server 2012 R2, AD LDS for Windows 8.1, Windows Server 2016 ~~Technical Preview~~, and AD LDS for Windows 10.

2.148 Attribute msDS-AllowedDNSSuffixes

This attribute specifies the list of allowed suffixes for the dnsHostName attribute in computer objects.

```
cn: ms-DS-Allowed-DNS-Suffixes
ldapDisplayName: msDS-AllowedDNSSuffixes
attributeId: 1.2.840.113556.1.4.1710
attributeSyntax: 2.5.5.12
omSyntax: 64
isSingleValued: FALSE
schemaIdGuid: 8469441b-9ac4-4e45-8205-bd219dbf672d
systemOnly: FALSE
searchFlags: 0
rangeLower: 0
rangeUpper: 2048
systemFlags: FLAG_SCHEMA_BASE_OBJECT
```

Version-Specific Behavior: Implemented on ADAM, Windows Server 2008, AD LDS for Windows Vista, Windows Server 2008 R2, AD LDS for Windows 7, Windows Server 2012, AD LDS for Windows 8, Windows Server 2012 R2, AD LDS for Windows 8.1, Windows Server 2016 ~~Technical Preview~~, and AD LDS for Windows 10.

2.149 Attribute msDS-Approx-Immed-Subordinates

The value returned by this attribute is based on index sizes. This value ~~may~~ be off by +/-10 percent on large containers, and the error is theoretically unbounded, but the use of this attribute is to assist the UI with determining how to display the contents of a container.

```
cn: ms-DS-Approx-Immed-Subordinates
ldapDisplayName: msDS-Approx-Immed-Subordinates
attributeId: 1.2.840.113556.1.4.1669
attributeSyntax: 2.5.5.9
omSyntax: 2
isSingleValued: TRUE
schemaIdGuid: e185d243-f6ce-4adb-b496-b0c005d7823c
systemOnly: TRUE
searchFlags: 0
attributeSecurityGuid: e48d0154-bcf8-11d1-8702-00c04fb96050
systemFlags: FLAG_SCHEMA_BASE_OBJECT | FLAG_ATTR_IS_CONSTRUCTED
```

Version-Specific Behavior: Implemented on ADAM, Windows Server 2008, AD LDS for Windows Vista, Windows Server 2008 R2, AD LDS for Windows 7, Windows Server 2012, AD LDS for Windows 8, Windows Server 2012 R2, AD LDS for Windows 8.1, Windows Server 2016 ~~Technical Preview~~, and AD LDS for Windows 10.

2.150 Attribute msDS-Auxiliary-Classes

This attribute lists the auxiliary classes that have been dynamically attached to an object. This attribute is not associated with a class. It is automatically populated by the Active Directory system.

```
cn: ms-DS-Auxiliary-Classes
ldapDisplayName: msDS-Auxiliary-Classes
attributeId: 1.2.840.113556.1.4.1458
attributeSyntax: 2.5.5.2
omSyntax: 6
isSingleValued: FALSE
schemaIdGuid: c4af1073-ee50-4be0-b8c0-89a41fe99abe
systemOnly: TRUE
searchFlags: fPRESERVEONDELETE
attributeSecurityGuid: e48d0154-bcf8-11d1-8702-00c04fb96050
systemFlags: FLAG_SCHEMA_BASE_OBJECT | FLAG_ATTR_IS_CONSTRUCTED
```

Version-Specific Behavior: Implemented on ADAM, Windows Server 2008, AD LDS for Windows Vista, Windows Server 2008 R2, AD LDS for Windows 7, Windows Server 2012, AD LDS for Windows 8, Windows Server 2012 R2, AD LDS for Windows 8.1, Windows Server 2016 ~~Technical Preview~~, and AD LDS for Windows 10.

2.151 Attribute msDS-AzApplicationData

This attribute specifies a string that is used by individual applications to store needed information.

```
cn: ms-DS-Az-Application-Data
ldapDisplayName: msDS-AzApplicationData
attributeId: 1.2.840.113556.1.4.1819
attributeSyntax: 2.5.5.12
omSyntax: 64
isSingleValued: TRUE
schemaIdGuid: 503fc3e8-1cc6-461a-99a3-9eee04f402a7
systemOnly: FALSE
searchFlags: 0
rangeLower: 0
```

Version-Specific Behavior: Implemented on ADAM, Windows Server 2008, AD LDS for Windows Vista, Windows Server 2008 R2, AD LDS for Windows 7, Windows Server 2012, AD LDS for Windows 8, Windows Server 2012 R2, AD LDS for Windows 8.1, Windows Server 2016 ~~Technical Preview~~, and AD LDS for Windows 10.

2.152 Attribute msDS-AzApplicationName

This attribute specifies a string that uniquely identifies an application object.

```
cn: ms-DS-Az-Application-Name
ldapDisplayName: msDS-AzApplicationName
attributeId: 1.2.840.113556.1.4.1798
attributeSyntax: 2.5.5.12
omSyntax: 64
isSingleValued: TRUE
schemaIdGuid: db5b0728-6208-4876-83b7-95d3e5695275
systemOnly: FALSE
searchFlags: 0
rangeLower: 0
rangeUpper: 512
```

Version-Specific Behavior: Implemented on ADAM, Windows Server 2008, AD LDS for Windows Vista, Windows Server 2008 R2, AD LDS for Windows 7, Windows Server 2012, AD LDS for Windows 8, Windows Server 2012 R2, AD LDS for Windows 8.1, Windows Server 2016 ~~Technical Preview~~, and AD LDS for Windows 10.

2.153 Attribute msDS-AzApplicationVersion

This attribute specifies a version number to indicate that the AzApplication is updated.

```
cn: ms-DS-Az-Application-Version
ldapDisplayName: msDS-AzApplicationVersion
attributeId: 1.2.840.113556.1.4.1817
attributeSyntax: 2.5.5.12
omSyntax: 64
isSingleValued: TRUE
schemaIdGuid: 7184a120-3ac4-47ae-848f-fe0ab20784d4
systemOnly: FALSE
searchFlags: 0
rangeLower: 0
```

Version-Specific Behavior: Implemented on ADAM, Windows Server 2008, AD LDS for Windows Vista, Windows Server 2008 R2, AD LDS for Windows 7, Windows Server 2012, AD LDS for Windows 8, Windows Server 2012 R2, AD LDS for Windows 8.1, Windows Server 2016 ~~Technical Preview~~, and AD LDS for Windows 10.

2.154 Attribute msDS-AzBizRule

This attribute specifies the text of the script implementing the business rule.

```
cn: ms-DS-Az-Biz-Rule
ldapDisplayName: msDS-AzBizRule
attributeId: 1.2.840.113556.1.4.1801
attributeSyntax: 2.5.5.12
omSyntax: 64
isSingleValued: TRUE
schemaIdGuid: 33d41ea8-c0c9-4c92-9494-f104878413fd
systemOnly: FALSE
searchFlags: 0
rangeLower: 0
rangeUpper: 65536
```

Version-Specific Behavior: Implemented on ADAM, Windows Server 2008, AD LDS for Windows Vista, Windows Server 2008 R2, AD LDS for Windows 7, Windows Server 2012, AD LDS for Windows 8, Windows Server 2012 R2, AD LDS for Windows 8.1, Windows Server 2016 ~~Technical Preview~~, and AD LDS for Windows 10.

2.155 Attribute msDS-AzBizRuleLanguage

This attribute specifies the language that the business rule script is in (for example, JScript or Visual Basic Scripting Edition).

```
cn: ms-DS-Az-Biz-Rule-Language
ldapDisplayName: msDS-AzBizRuleLanguage
attributeId: 1.2.840.113556.1.4.1802
attributeSyntax: 2.5.5.12
omSyntax: 64
isSingleValued: TRUE
schemaIdGuid: 52994b56-0e6c-4e07-aa5c-ef9d7f5a0e25
systemOnly: FALSE
searchFlags: 0
rangeLower: 0
rangeUpper: 64
```


Version-Specific Behavior: Implemented on ADAM, Windows Server 2008, AD LDS for Windows Vista, Windows Server 2008 R2, AD LDS for Windows 7, Windows Server 2012, AD LDS for Windows 8, Windows Server 2012 R2, AD LDS for Windows 8.1, Windows Server 2016 ~~Technical Preview~~, and AD LDS for Windows 10.

2.156 Attribute msDS-AzClassId

This attribute specifies a class ID that is required by the AzRoles UI on the AzApplication object.

```
cn: ms-DS-Az-Class-ID
ldapDisplayName: msDS-AzClassId
attributeId: 1.2.840.113556.1.4.1816
attributeSyntax: 2.5.5.12
omSyntax: 64
isSingleValued: TRUE
schemaIdGuid: 013a7277-5c2d-49ef-a7de-b765b36a3f6f
systemOnly: FALSE
searchFlags: 0
rangeLower: 0
rangeUpper: 40
```

Version-Specific Behavior: Implemented on ADAM, Windows Server 2008, AD LDS for Windows Vista, Windows Server 2008 R2, AD LDS for Windows 7, Windows Server 2012, AD LDS for Windows 8, Windows Server 2012 R2, AD LDS for Windows 8.1, Windows Server 2016 ~~Technical Preview~~, and AD LDS for Windows 10.

2.157 Attribute msDS-AzDomainTimeout

This attribute specifies the time (in milliseconds) after a domain is detected to be unreachable and before the DC is tried again.

```
cn: ms-DS-Az-Domain-Timeout
ldapDisplayName: msDS-AzDomainTimeout
attributeId: 1.2.840.113556.1.4.1795
attributeSyntax: 2.5.5.9
omSyntax: 2
isSingleValued: TRUE
schemaIdGuid: 6448f56a-ca70-4e2e-b0af-d20e4ce653d0
systemOnly: FALSE
searchFlags: 0
rangeLower: 0
```

Version-Specific Behavior: Implemented on ADAM, Windows Server 2008, AD LDS for Windows Vista, Windows Server 2008 R2, AD LDS for Windows 7, Windows Server 2012, AD LDS for Windows 8, Windows Server 2012 R2, AD LDS for Windows 8.1, Windows Server 2016 ~~Technical Preview~~, and AD LDS for Windows 10.

2.158 Attribute msDS-AzGenerateAudits

This attribute specifies a Boolean field indicating whether runtime audits need to be turned on (for example, audits for access checks).

```
cn: ms-DS-Az-Generate-Audits
ldapDisplayName: msDS-AzGenerateAudits
attributeId: 1.2.840.113556.1.4.1805
attributeSyntax: 2.5.5.8
omSyntax: 1
isSingleValued: TRUE
```

```
schemaIdGuid: f90abab0-186c-4418-bb85-88447c87222a
systemOnly: FALSE
searchFlags: 0
```

Version-Specific Behavior: Implemented on ADAM, Windows Server 2008, AD LDS for Windows Vista, Windows Server 2008 R2, AD LDS for Windows 7, Windows Server 2012, AD LDS for Windows 8, Windows Server 2012 R2, AD LDS for Windows 8.1, Windows Server 2016 ~~Technical Preview~~, and AD LDS for Windows 10.

2.159 Attribute msDS-AzGenericData

This attribute specifies AzMan-specific generic data.

```
cn: ms-DS-Az-Generic-Data
ldapDisplayName: msDS-AzGenericData
attributeId: 1.2.840.113556.1.4.1950
attributeSyntax: 2.5.5.12
omSyntax: 64
isSingleValued: TRUE
schemaIdGuid: a283ad81-aaac-448b-af22-6c7099a946e0
systemOnly: FALSE
searchFlags: 0
rangeUpper: 65536
```

Version-Specific Behavior: Implemented on ADAM, Windows Server 2008, AD LDS for Windows Vista, Windows Server 2008 R2, AD LDS for Windows 7, Windows Server 2012, AD LDS for Windows 8, Windows Server 2012 R2, AD LDS for Windows 8.1, Windows Server 2016 ~~Technical Preview~~, and AD LDS for Windows 10.

2.160 Attribute msDS-AzLastImportedBizRulePath

This attribute specifies the last imported business rule path.

```
cn: ms-DS-Az-Last-Imported-Biz-Rule-Path
ldapDisplayName: msDS-AzLastImportedBizRulePath
attributeId: 1.2.840.113556.1.4.1803
attributeSyntax: 2.5.5.12
omSyntax: 64
isSingleValued: TRUE
schemaIdGuid: 665acb5c-bb92-4dbc-8c59-b3638eab09b3
systemOnly: FALSE
searchFlags: 0
rangeLower: 0
rangeUpper: 65536
```

Version-Specific Behavior: Implemented on ADAM, Windows Server 2008, AD LDS for Windows Vista, Windows Server 2008 R2, AD LDS for Windows 7, Windows Server 2012, AD LDS for Windows 8, Windows Server 2012 R2, AD LDS for Windows 8.1, Windows Server 2016 ~~Technical Preview~~, and AD LDS for Windows 10.

2.161 Attribute msDS-AzLDAPQuery

This attribute specifies a string that defines the LDAP query (max length 4096) that determines the membership of a user object to the group.

```
cn: ms-DS-Az-LDAP-Query
ldapDisplayName: msDS-AzLDAPQuery
```

```
attributeId: 1.2.840.113556.1.4.1792
attributeSyntax: 2.5.5.12
omSyntax: 64
isSingleValued: TRUE
schemaIdGuid: 5e53368b-fc94-45c8-9d7d-daf31ee7112d
systemOnly: FALSE
searchFlags: 0
rangeLower: 0
rangeUpper: 4096
```

Version-Specific Behavior: Implemented on ADAM, Windows Server 2008, AD LDS for Windows Vista, Windows Server 2008 R2, AD LDS for Windows 7, Windows Server 2012, AD LDS for Windows 8, Windows Server 2012 R2, AD LDS for Windows 8.1, Windows Server 2016 ~~Technical Preview~~, and AD LDS for Windows 10.

2.162 Attribute msDS-AzMajorVersion

This attribute specifies the major version number for AzRoles.

```
cn: ms-DS-Az-Major-Version
ldapDisplayName: msDS-AzMajorVersion
attributeId: 1.2.840.113556.1.4.1824
attributeSyntax: 2.5.5.9
omSyntax: 2
isSingleValued: TRUE
schemaIdGuid: cfb9adb7-c4b7-4059-9568-1ed9db6b7248
systemOnly: FALSE
searchFlags: 0
rangeLower: 1
```

Version-Specific Behavior: Implemented on ADAM, Windows Server 2008, AD LDS for Windows Vista, Windows Server 2008 R2, AD LDS for Windows 7, Windows Server 2012, AD LDS for Windows 8, Windows Server 2012 R2, AD LDS for Windows 8.1, Windows Server 2016 ~~Technical Preview~~, and AD LDS for Windows 10.

2.163 Attribute msDS-AzMinorVersion

This attribute specifies the minor version number for AzRoles.

```
cn: ms-DS-Az-Minor-Version
ldapDisplayName: msDS-AzMinorVersion
attributeId: 1.2.840.113556.1.4.1825
attributeSyntax: 2.5.5.9
omSyntax: 2
isSingleValued: TRUE
schemaIdGuid: ee85ed93-b209-4788-8165-e702f51bfbf3
systemOnly: FALSE
searchFlags: 0
rangeLower: 0
```

Version-Specific Behavior: Implemented on ADAM, Windows Server 2008, AD LDS for Windows Vista, Windows Server 2008 R2, AD LDS for Windows 7, Windows Server 2012, AD LDS for Windows 8, Windows Server 2012 R2, AD LDS for Windows 8.1, Windows Server 2016 ~~Technical Preview~~, and AD LDS for Windows 10.

2.164 Attribute msDS-AzObjectGuid

This attribute specifies the unique and portable identifier of AzMan objects.

```
cn: ms-DS-Az-Object-Guid
ldapDisplayName: msDS-AzObjectGuid
attributeId: 1.2.840.113556.1.4.1949
attributeSyntax: 2.5.5.10
omSyntax: 4
isSingleValued: TRUE
schemaIdGuid: 8867b29c-9ccf-4ce2-be30-b67c0d2432c6
systemOnly: TRUE
searchFlags: fATTINDEX
rangeLower: 16
rangeUpper: 16
```

Version-Specific Behavior: Implemented on ADAM, Windows Server 2008, AD LDS for Windows Vista, Windows Server 2008 R2, AD LDS for Windows 7, Windows Server 2012, AD LDS for Windows 8, Windows Server 2012 R2, AD LDS for Windows 8.1, Windows Server 2016 ~~Technical Preview~~, and AD LDS for Windows 10.

2.165 Attribute msDS-AzOperationID

This attribute specifies the application-specific ID that makes the operation unique to the application.

```
cn: ms-DS-Az-Operation-ID
ldapDisplayName: msDS-AzOperationID
attributeId: 1.2.840.113556.1.4.1800
attributeSyntax: 2.5.5.9
omSyntax: 2
isSingleValued: TRUE
schemaIdGuid: a5f3b553-5d76-4cbe-ba3f-4312152cab18
systemOnly: FALSE
searchFlags: 0
rangeLower: 0
```

Version-Specific Behavior: Implemented on ADAM, Windows Server 2008, AD LDS for Windows Vista, Windows Server 2008 R2, AD LDS for Windows 7, Windows Server 2012, AD LDS for Windows 8, Windows Server 2012 R2, AD LDS for Windows 8.1, Windows Server 2016 ~~Technical Preview~~, and AD LDS for Windows 10.

2.166 Attribute msDS-AzScopeName

This attribute specifies a string that uniquely identifies a scope object.

```
cn: ms-DS-Az-Scope-Name
ldapDisplayName: msDS-AzScopeName
attributeId: 1.2.840.113556.1.4.1799
attributeSyntax: 2.5.5.12
omSyntax: 64
isSingleValued: TRUE
schemaIdGuid: 515a6b06-2617-4173-8099-d5605df043c6
systemOnly: FALSE
searchFlags: 0
rangeLower: 0
rangeUpper: 65536
```

Version-Specific Behavior: Implemented on ADAM, Windows Server 2008, AD LDS for Windows Vista, Windows Server 2008 R2, AD LDS for Windows 7, Windows Server 2012, AD LDS for Windows 8, Windows Server 2012 R2, AD LDS for Windows 8.1, Windows Server 2016 ~~Technical Preview~~, and AD LDS for Windows 10.

2.167 Attribute msDS-AzScriptEngineCacheMax

This attribute specifies the maximum number of scripts that are cached by the application.

```
cn: ms-DS-Az-Script-Engine-Cache-Max
ldapDisplayName: msDS-AzScriptEngineCacheMax
attributeId: 1.2.840.113556.1.4.1796
attributeSyntax: 2.5.5.9
omSyntax: 2
isSingleValued: TRUE
schemaIdGuid: 2629f66a-1f95-4bf3-a296-8e9d7b9e30c8
systemOnly: FALSE
searchFlags: 0
rangeLower: 0
```

Version-Specific Behavior: Implemented on ADAM, Windows Server 2008, AD LDS for Windows Vista, Windows Server 2008 R2, AD LDS for Windows 7, Windows Server 2012, AD LDS for Windows 8, Windows Server 2012 R2, AD LDS for Windows 8.1, Windows Server 2016 ~~Technical Preview~~, and AD LDS for Windows 10.

2.168 Attribute msDS-AzScriptTimeout

This attribute specifies the maximum time (in milliseconds) to wait for a script to finish auditing a specific policy.

```
cn: ms-DS-Az-Script-Timeout
ldapDisplayName: msDS-AzScriptTimeout
attributeId: 1.2.840.113556.1.4.1797
attributeSyntax: 2.5.5.9
omSyntax: 2
isSingleValued: TRUE
schemaIdGuid: 87d0fb41-2c8b-41f6-b972-11fd50d6b0
systemOnly: FALSE
searchFlags: 0
rangeLower: 0
```

Version-Specific Behavior: Implemented on ADAM, Windows Server 2008, AD LDS for Windows Vista, Windows Server 2008 R2, AD LDS for Windows 7, Windows Server 2012, AD LDS for Windows 8, Windows Server 2012 R2, AD LDS for Windows 8.1, Windows Server 2016 ~~Technical Preview~~, and AD LDS for Windows 10.

2.169 Attribute msDS-AzTaskIsRoleDefinition

This attribute specifies a Boolean field that indicates whether AzTask is a classic task or a role definition.

```
cn: ms-DS-Az-Task-Is-Role-Definition
ldapDisplayName: msDS-AzTaskIsRoleDefinition
attributeId: 1.2.840.113556.1.4.1818
attributeSyntax: 2.5.5.8
omSyntax: 1
isSingleValued: TRUE
schemaIdGuid: 7b078544-6c82-4fe9-872f-ff48ad2b2e26
systemOnly: FALSE
searchFlags: 0
```

Version-Specific Behavior: Implemented on ADAM, Windows Server 2008, AD LDS for Windows Vista, Windows Server 2008 R2, AD LDS for Windows 7, Windows Server 2012, AD LDS for Windows 8,

Windows Server 2012 R2, AD LDS for Windows 8.1, Windows Server 2016 ~~Technical Preview~~, and AD LDS for Windows 10.

2.170 Attribute msDS-Behavior-Version

This attribute is used to track the domain or forest behavior version. It is a monotonically increasing number that is used to enable certain Active Directory features.

```
cn: ms-DS-Behavior-Version
ldapDisplayName: msDS-Behavior-Version
attributeId: 1.2.840.113556.1.4.1459
attributeSyntax: 2.5.5.9
omSyntax: 2
isSingleValued: TRUE
schemaIdGuid: d31a8757-2447-4545-8081-3bb610cacbf2
systemOnly: TRUE
searchFlags: 0
rangeLower: 0
systemFlags: FLAG_SCHEMA_BASE_OBJECT
```

Version-Specific Behavior: Implemented on ADAM, Windows Server 2008, AD LDS for Windows Vista, Windows Server 2008 R2, AD LDS for Windows 7, Windows Server 2012, AD LDS for Windows 8, Windows Server 2012 R2, AD LDS for Windows 8.1, Windows Server 2016 ~~Technical Preview~~, and AD LDS for Windows 10.

2.171 Attribute msDS-BridgeHeadServersUsed

This attribute specifies a list of bridgehead servers used by the KCC in the previous run.

```
cn: ms-DS-BridgeHead-Servers-Used
ldapDisplayName: msDS-BridgeHeadServersUsed
attributeId: 1.2.840.113556.1.4.2049
attributeSyntax: 2.5.5.7
omSyntax: 127
omObjectClass: 1.2.840.113556.1.1.1.11
linkID: 2160
isSingleValued: FALSE
showInAdvancedViewOnly: TRUE
schemaIdGuid: 3ced1465-7b71-2541-8780-1e1ea6243a82
searchFlags: 0
systemFlags: FLAG_ATTR_NOT_REPLICATED | FLAG_ATTR_IS_OPERATIONAL |
FLAG_SCHEMA_BASE_OBJECT
```

Version-Specific Behavior: Implemented on Windows Server 2008 R2, AD LDS for Windows 7, Windows Server 2012, AD LDS for Windows 8, Windows Server 2012 R2, AD LDS for Windows 8.1, Windows Server 2016 ~~Technical Preview~~, and AD LDS for Windows 10.

2.172 Attribute msDS-DefaultNamingContext

This attribute specifies the default naming context (partition) for this AD LDS instance.

```
cn: ms-DS-Default-Naming-Context
ldapDisplayName: msDS-DefaultNamingContext
attributeId: 1.2.840.113556.1.4.1873
attributeSyntax: 2.5.5.1
omSyntax: 127
omObjectClass: 1.3.12.2.1011.28.0.714
isSingleValued: TRUE
schemaIdGuid: 09278375-bc53-e342-8a03-943043a1b573
```

```
systemOnly: FALSE
searchFlags: 0
linkID: 2044
systemFlags: FLAG_SCHEMA_BASE_OBJECT
```

Version-Specific Behavior: Implemented on ADAM, Windows Server 2008, AD LDS for Windows Vista, Windows Server 2008 R2, AD LDS for Windows 7, Windows Server 2012, AD LDS for Windows 8, Windows Server 2012 R2, AD LDS for Windows 8.1, Windows Server 2016 **Technical Preview**, and AD LDS for Windows 10.

2.173 Attribute msDS-DefaultNamingContextBL

This attribute specifies a backlink reference for the msDS-DefaultNamingContext attribute.

```
cn: ms-DS-Default-Naming-Context-BL
ldapDisplayName: msDS-DefaultNamingContextBL
attributeId: 1.2.840.113556.1.4.1874
attributeSyntax: 2.5.5.1
omSyntax: 127
omObjectClass: 1.3.12.2.1011.28.0.714
isSingleValued: FALSE
schemaIdGuid: 2a4e57c2-60bc-5040-b463-51e1d82df9a5
systemOnly: TRUE
searchFlags: 0
linkID: 2045
systemFlags: FLAG_SCHEMA_BASE_OBJECT | FLAG_ATTR_NOT_REPLICATED
```

Version-Specific Behavior: Implemented on ADAM, Windows Server 2008, AD LDS for Windows Vista, Windows Server 2008 R2, AD LDS for Windows 7, Windows Server 2012, AD LDS for Windows 8, Windows Server 2012 R2, AD LDS for Windows 8.1, Windows Server 2016 **Technical Preview**, and AD LDS for Windows 10.

2.174 Attribute msDS-DefaultQuota

This attribute specifies the default quota that will apply to a security principal that creates an object in the NC if no quota specification exists that covers the security principal.

```
cn: ms-DS-Default-Quota
ldapDisplayName: msDS-DefaultQuota
attributeId: 1.2.840.113556.1.4.1846
attributeSyntax: 2.5.5.9
omSyntax: 2
isSingleValued: TRUE
schemaIdGuid: 6818f726-674b-441b-8a3a-f40596374cea
systemOnly: FALSE
searchFlags: 0
systemFlags: FLAG_SCHEMA_BASE_OBJECT
```

Version-Specific Behavior: Implemented on ADAM, Windows Server 2008, AD LDS for Windows Vista, Windows Server 2008 R2, AD LDS for Windows 7, Windows Server 2012, AD LDS for Windows 8, Windows Server 2012 R2, AD LDS for Windows 8.1, Windows Server 2016 **Technical Preview**, and AD LDS for Windows 10.

2.175 Attribute msDS-DeletedObjectLifetime

If the Recycle Bin optional feature is enabled, this attribute specifies the number of days before a deleted object is converted to a recycled object. If the Recycle Bin optional feature is not enabled, values of this attribute have no meaning or effect.

```
cn: ms-DS-Deleted-Object-Lifetime
ldapDisplayName: msDS-DeletedObjectLifetime
attributeId: 1.2.840.113556.1.4.2068
attributeSyntax: 2.5.5.9
omSyntax: 10
isSingleValued: TRUE
schemaIdGuid: a9b38cb6-189a-4def-8a70-0fcfa158148e
systemOnly: FALSE
searchFlags: 0
systemFlags: FLAG_SCHEMA_BASE_OBJECT
```

Version-Specific Behavior: Implemented on Windows Server 2008 R2, AD LDS for Windows 7, Windows Server 2012, AD LDS for Windows 8, Windows Server 2012 R2, AD LDS for Windows 8.1, Windows Server 2016 **Technical Preview**, and AD LDS for Windows 10.

2.176 Attribute msDS-DisableForInstances

This attribute specifies the set of DSA objects, representing AD LDS instances, for which Service Connection Point publication **should be** disabled.

```
cn: ms-DS-Disable-For-Instances
ldapDisplayName: msDS-DisableForInstances
attributeId: 1.2.840.113556.1.4.1870
attributeSyntax: 2.5.5.1
omSyntax: 127
omObjectClass: 1.3.12.2.1011.28.0.714
isSingleValued: FALSE
schemaIdGuid: 5f8f45cb-0fb7-fc4f-b44f-66f781aa66dd
systemOnly: FALSE
searchFlags: 0
linkID: 2042
systemFlags: FLAG_SCHEMA_BASE_OBJECT
```

Version-Specific Behavior: Implemented on ADAM, Windows Server 2008, AD LDS for Windows Vista, Windows Server 2008 R2, AD LDS for Windows 7, Windows Server 2012, AD LDS for Windows 8, Windows Server 2012 R2, AD LDS for Windows 8.1, Windows Server 2016 **Technical Preview**, and AD LDS for Windows 10.

2.177 Attribute msDS-DisableForInstancesBL

This attribute specifies the backlink reference to the ms-DS-Service-Connection-Point-Publication-Service object.

```
cn: ms-DS-Disable-For-Instances-BL
ldapDisplayName: msDS-DisableForInstancesBL
attributeId: 1.2.840.113556.1.4.1871
attributeSyntax: 2.5.5.1
omSyntax: 127
omObjectClass: 1.3.12.2.1011.28.0.714
isSingleValued: FALSE
schemaIdGuid: 8f9d31dd-67ea-cd42-9b88-7cddb36c21f4
systemOnly: TRUE
searchFlags: 0
linkID: 2043
systemFlags: FLAG_SCHEMA_BASE_OBJECT | FLAG_ATTR_NOT_REPLICATED
```

Version-Specific Behavior: Implemented on ADAM, Windows Server 2008, AD LDS for Windows Vista, Windows Server 2008 R2, AD LDS for Windows 7, Windows Server 2012, AD LDS for Windows 8,

Windows Server 2012 R2, AD LDS for Windows 8.1, Windows Server 2016 ~~Technical Preview~~, and AD LDS for Windows 10.

2.178 Attribute msDS-DnsRootAlias

This attribute is used to store the domain alias.

```
cn: ms-DS-DnsRootAlias
ldapDisplayName: msDS-DnsRootAlias
attributeId: 1.2.840.113556.1.4.1719
attributeSyntax: 2.5.5.12
omSyntax: 64
isSingleValued: TRUE
schemaIdGuid: 2143acca-eead-4d29-b591-85fa49ce9173
systemOnly: FALSE
searchFlags: 0
rangeLower: 0
rangeUpper: 255
systemFlags: FLAG_SCHEMA_BASE_OBJECT
```

Version-Specific Behavior: Implemented on ADAM, Windows Server 2008, AD LDS for Windows Vista, Windows Server 2008 R2, AD LDS for Windows 7, Windows Server 2012, AD LDS for Windows 8, Windows Server 2012 R2, AD LDS for Windows 8.1, Windows Server 2016 ~~Technical Preview~~, and AD LDS for Windows 10.

2.179 Attribute msDS-EnabledFeature

This attribute lists the enabled optional features.

```
cn: ms-DS-Enabled-Feature
ldapDisplayName: msDS-EnabledFeature
attributeId: 1.2.840.113556.1.4.2061
attributeSyntax: 2.5.5.1
omSyntax: 127
omObjectClass: 1.3.12.2.1011.28.0.714
linkId: 2168
isSingleValued: FALSE
schemaIdGuid: 5706aeaf-b940-4fb2-bcfc-5268683ad9fe
isMemberOfPartialAttributeSet: TRUE
systemOnly: TRUE
searchFlags: 0
systemFlags: FLAG_SCHEMA_BASE_OBJECT
```

Version-Specific Behavior: Implemented on Windows Server 2008 R2, AD LDS for Windows 7, Windows Server 2012, AD LDS for Windows 8, Windows Server 2012 R2, AD LDS for Windows 8.1, Windows Server 2016 ~~Technical Preview~~, and AD LDS for Windows 10.

2.180 Attribute msDS-EnabledFeatureBL

This attribute is the backlink attribute of msDS-EnabledFeature, and it lists the scopes where an optional feature is enabled.

```
cn: ms-DS-Enabled-Feature-BL
ldapDisplayName: msDS-EnabledFeatureBL
attributeId: 1.2.840.113556.1.4.2069
attributeSyntax: 2.5.5.1
omSyntax: 127
omObjectClass: 1.3.12.2.1011.28.0.714
linkId: 2169
```

```
isSingleValued: FALSE
schemaIdGuid: ce5b01bc-17c6-44b8-9dc1-a9668b00901b
systemOnly: TRUE
searchFlags: 0
systemFlags: FLAG_SCHEMA_BASE_OBJECT|FLAG_ATTR_NOT_REPLICATED
```

Version-Specific Behavior: Implemented on Windows Server 2008 R2, AD LDS for Windows 7, Windows Server 2012, AD LDS for Windows 8, Windows Server 2012 R2, AD LDS for Windows 8.1, Windows Server 2016 **Technical Preview**, and AD LDS for Windows 10.

2.181 Attribute msDS-Entry-Time-To-Die

This attribute holds the absolute expiration time of a dynamic object in the directory.

```
cn: ms-DS-Entry-Time-To-Die
ldapDisplayName: msDS-Entry-Time-To-Die
attributeId: 1.2.840.113556.1.4.1622
attributeSyntax: 2.5.5.11
omSyntax: 24
isSingleValued: TRUE
schemaIdGuid: ele9bad7-c6dd-4101-a843-794cec85b038
systemOnly: TRUE
searchFlags: fPRESERVEONDELETE | fATTINDEX
isMemberOfPartialAttributeSet: TRUE
systemFlags: FLAG_SCHEMA_BASE_OBJECT | FLAG_ATTR_IS_OPERATIONAL
```

Version-Specific Behavior: Implemented on ADAM, Windows Server 2008, AD LDS for Windows Vista, Windows Server 2008 R2, AD LDS for Windows 7, Windows Server 2012, AD LDS for Windows 8, Windows Server 2012 R2, AD LDS for Windows 8.1, Windows Server 2016 **Technical Preview**, and AD LDS for Windows 10.

2.182 Attribute msDS-ExecuteScriptPassword

This attribute is used during domain rename operation. This value cannot be written to or read from with LDAP.

```
cn: ms-DS-ExecuteScriptPassword
ldapDisplayName: msDS-ExecuteScriptPassword
attributeId: 1.2.840.113556.1.4.1783
attributeSyntax: 2.5.5.10
omSyntax: 4
isSingleValued: TRUE
schemaIdGuid: 9d054a5a-d187-46c1-9d85-42dfc44a56dd
systemOnly: TRUE
searchFlags: 0
rangeLower: 0
rangeUpper: 64
systemFlags: FLAG_SCHEMA_BASE_OBJECT | FLAG_ATTR_NOT_REPLICATED
```

Version-Specific Behavior: Implemented on ADAM, Windows Server 2008, AD LDS for Windows Vista, Windows Server 2008 R2, AD LDS for Windows 7, Windows Server 2012, AD LDS for Windows 8, Windows Server 2012 R2, AD LDS for Windows 8.1, Windows Server 2016 **Technical Preview**, and AD LDS for Windows 10.

2.183 Attribute msDS-FilterContainers

A multivalued string attribute containing the names of classes that are used to determine which container types ~~should beare~~ shown by the Active Directory Users and Computers snap-in when filtering.

```
cn: ms-DS-Filter-Containers
ldapDisplayName: msDS-FilterContainers
attributeId: 1.2.840.113556.1.4.1703
attributeSyntax: 2.5.5.12
omSyntax: 64
isSingleValued: FALSE
schemaIdGuid: fb00dcdcf-ac37-483a-9c12-ac53a6603033
systemOnly: FALSE
rangeLower: 1
rangeUpper: 64
```

Version-Specific Behavior: Implemented on Windows Server 2008, AD LDS for Windows Vista, Windows Server 2008 R2, AD LDS for Windows 7, Windows Server 2012, AD LDS for Windows 8, Windows Server 2012 R2, AD LDS for Windows 8.1, Windows Server 2016 ~~Technical Preview~~, and AD LDS for Windows 10.

2.184 Attribute msDS-HasDomainNCs

This attribute specifies DS replication information that details the domain NCs that are present on a particular server.

```
cn: ms-DS-Has-Domain-NCs
ldapDisplayName: msDS-HasDomainNCs
attributeId: 1.2.840.113556.1.4.1820
attributeSyntax: 2.5.5.1
omSyntax: 127
omObjectClass: 1.3.12.2.1011.28.0.714
isSingleValued: FALSE
schemaIdGuid: 6f17e347-a842-4498-b8b3-15e007da4fed
systemOnly: TRUE
searchFlags: 0
rangeLower: 4
rangeUpper: 4
linkID: 2026
systemFlags: FLAG_SCHEMA_BASE_OBJECT
```

Version-Specific Behavior: Implemented on ADAM, Windows Server 2008, AD LDS for Windows Vista, Windows Server 2008 R2, AD LDS for Windows 7, Windows Server 2012, AD LDS for Windows 8, Windows Server 2012 R2, AD LDS for Windows 8.1, Windows Server 2016 ~~Technical Preview~~, and AD LDS for Windows 10.

2.185 Attribute msDS-HasInstantiatedNCs

This attribute specifies DS replication information that details the state of the NCs that are present on a particular server.

```
cn: ms-DS-Has-Instantiated-NCs
ldapDisplayName: msDS-HasInstantiatedNCs
attributeId: 1.2.840.113556.1.4.1709
attributeSyntax: 2.5.5.7
omSyntax: 127
omObjectClass: 1.2.840.113556.1.1.1.11
isSingleValued: FALSE
```

```
schemaIdGuid: 11e9a5bc-4517-4049-af9c-51554fb0fc09
systemOnly: TRUE
searchFlags: 0
rangeLower: 4
rangeUpper: 4
linkID: 2002
systemFlags: FLAG_SCHEMA_BASE_OBJECT
```

Version-Specific Behavior: Implemented on ADAM, Windows Server 2008, AD LDS for Windows Vista, Windows Server 2008 R2, AD LDS for Windows 7, Windows Server 2012, AD LDS for Windows 8, Windows Server 2012 R2, AD LDS for Windows 8.1, Windows Server 2016 **Technical Preview**, and AD LDS for Windows 10.

2.186 Attribute msDS-hasMasterNCs

This attribute specifies a list of the naming contexts contained by a DC.

```
cn: ms-DS-Has-Master-NCs
ldapDisplayName: msDS-hasMasterNCs
attributeId: 1.2.840.113556.1.4.1836
attributeSyntax: 2.5.5.1
omSyntax: 127
omObjectClass: 1.3.12.2.1011.28.0.714
isSingleValued: FALSE
schemaIdGuid: ae2de0e2-59d7-4d47-8d47-ed4dfe4357ad
systemOnly: TRUE
searchFlags: 0
linkID: 2036
systemFlags: FLAG_SCHEMA_BASE_OBJECT
```

Version-Specific Behavior: Implemented on ADAM, Windows Server 2008, AD LDS for Windows Vista, Windows Server 2008 R2, AD LDS for Windows 7, Windows Server 2012, AD LDS for Windows 8, Windows Server 2012 R2, AD LDS for Windows 8.1, Windows Server 2016 **Technical Preview**, and AD LDS for Windows 10.

2.187 Attribute msDS-IntId

The ms-DS-IntId attribute is for internal use only.

```
cn: ms-DS-IntId
ldapDisplayName: msDS-IntId
attributeId: 1.2.840.113556.1.4.1716
attributeSyntax: 2.5.5.9
omSyntax: 2
isSingleValued: TRUE
schemaIdGuid: bc60096a-1b47-4b30-8877-602c93f56532
systemOnly: TRUE
searchFlags: fPRESERVEONDELETE
systemFlags: FLAG_SCHEMA_BASE_OBJECT
```

Version-Specific Behavior: Implemented on ADAM, Windows Server 2008, AD LDS for Windows Vista, Windows Server 2008 R2, AD LDS for Windows 7, Windows Server 2012, AD LDS for Windows 8, Windows Server 2012 R2, AD LDS for Windows 8.1, Windows Server 2016 **Technical Preview**, and AD LDS for Windows 10.

2.188 Attribute msds-memberOfTransitive

This attribute specifies the set of distinguished names (DNs) in the memberOf attribute on the current object and the DN from the memberOf attributes of each of the objects specified in the memberOf attribute on the current object.

```
cn: ms-DS-Is-Member-Of-DL-Transitive
LDAPDisplayName: msds-memberOfTransitive
attributeID: 1.2.840.113556.1.4.2236
attributeSyntax: 2.5.5.1
omSyntax: 127
omObjectClass: 1.3.12.2.1011.28.0.714
isSingleValued: FALSE
systemOnly: TRUE
searchFlags: fBASEONLY
systemFlags: FLAG_ATTR_NOT_REPLICATED | FLAG_ATTR_IS_CONSTRUCTED |
  FLAG_ATTR_IS_OPERATIONAL | FLAG_SCHEMA_BASE_OBJECT
showInAdvancedViewOnly: TRUE
```

Version-Specific Behavior: Implemented on Windows Server 2012 R2, AD LDS for Windows 8.1, Windows Server 2016 ~~Technical Preview~~, and AD LDS for Windows 10.

2.189 Attribute msds-memberTransitive

This attribute specifies the set of distinguished names (DNs) in the member attribute on the current object and the DN from the member attribute of each of the objects specified in the member attribute on the current object.

```
cn: ms-DS-Member-Transitive
LDAPDisplayName: msds-memberTransitive
attributeID: 1.2.840.113556.1.4.2238
attributeSyntax: 2.5.5.1
omSyntax: 127
omObjectClass: 1.3.12.2.1011.28.0.714
isSingleValued: FALSE
systemOnly: TRUE
searchFlags: fBASEONLY
systemFlags: FLAG_ATTR_NOT_REPLICATED | FLAG_ATTR_IS_CONSTRUCTED |
  FLAG_ATTR_IS_OPERATIONAL | FLAG_SCHEMA_BASE_OBJECT
showInAdvancedViewOnly: TRUE
```

Version-Specific Behavior: Implemented on Windows Server 2012 R2, AD LDS for Windows 8.1, Windows Server 2016 ~~Technical Preview~~, and AD LDS for Windows 10.

2.190 Attribute msDS-LastKnownRDN

This attribute holds the original RDN of a deleted object.

```
cn: ms-DS-Last-Known-RDN
ldapDisplayName: msDS-LastKnownRDN
attributeId: 1.2.840.113556.1.4.2067
attributeSyntax: 2.5.5.12
omSyntax: 64
isSingleValued: TRUE
schemaIdGuid: 8ab15858-683e-466d-877f-d640e1f9a611
systemOnly: TRUE
searchFlags: 0
systemFlags: FLAG_SCHEMA_BASE_OBJECT
```

Version-Specific Behavior: Implemented on Windows Server 2008 R2, AD LDS for Windows 7, Windows Server 2012, AD LDS for Windows 8, Windows Server 2012 R2, AD LDS for Windows 8.1, Windows Server 2016 **Technical Preview**, and AD LDS for Windows 10.

2.191 Attribute msDS-LocalEffectiveDeletionTime

This attribute stores the deletion time of the object in the local domain controller.

```
cn: ms-DS-Local-Effective-Deletion-Time
ldapDisplayName: msDS-LocalEffectiveDeletionTime
attributeId: 1.2.840.113556.1.4.2059
attributeSyntax: 2.5.5.11
omSyntax: 24
isSingleValued: TRUE
schemaIdGuid: 94f2800c-531f-4aeb-975d-48ac39fd8ca4
systemOnly: TRUE
searchFlags: 0
systemFlags: FLAG_SCHEMA_BASE_OBJECT|FLAG_ATTR_IS_CONSTRUCTED
```

Version-Specific Behavior: Implemented on Windows Server 2008 R2, AD LDS for Windows 7, Windows Server 2012, AD LDS for Windows 8, Windows Server 2012 R2, AD LDS for Windows 8.1, Windows Server 2016 **Technical Preview**, and AD LDS for Windows 10.

2.192 Attribute msDS-LocalEffectiveRecycleTime

This attribute stores the recycle time of the object in the local domain controller.

```
cn: ms-DS-Local-Effective-Recycle-Time
ldapDisplayName: msDS-LocalEffectiveRecycleTime
attributeId: 1.2.840.113556.1.4.2060
attributeSyntax: 2.5.5.11
omSyntax: 24
isSingleValued: TRUE
schemaIdGuid: 4ad6016b-b0d2-4c9b-93b6-5964b17b968c
systemOnly: TRUE
searchFlags: 0
systemFlags: FLAG_SCHEMA_BASE_OBJECT|FLAG_ATTR_IS_CONSTRUCTED
```

Version-Specific Behavior: Implemented on Windows Server 2008 R2, AD LDS for Windows 7, Windows Server 2012, AD LDS for Windows 8, Windows Server 2012 R2, AD LDS for Windows 8.1, Windows Server 2016 **Technical Preview**, and AD LDS for Windows 10.

2.193 Attribute msDs-masteredBy

This attribute specifies the backlink for msDS-hasMasterNCs.

```
cn: ms-DS-Mastered-By
ldapDisplayName: msDs-masteredBy
attributeId: 1.2.840.113556.1.4.1837
attributeSyntax: 2.5.5.1
omSyntax: 127
omObjectClass: 1.3.12.2.1011.28.0.714
isSingleValued: FALSE
schemaIdGuid: 60234769-4819-4615-a1b2-49d2f119acb5
systemOnly: TRUE
searchFlags: 0
linkID: 2037
systemFlags: FLAG_SCHEMA_BASE_OBJECT | FLAG_ATTR_NOT_REPLICATED
```

Version-Specific Behavior: Implemented on ADAM, Windows Server 2008, AD LDS for Windows Vista, Windows Server 2008 R2, AD LDS for Windows 7, Windows Server 2012, AD LDS for Windows 8, Windows Server 2012 R2, AD LDS for Windows 8.1, Windows Server 2016 ~~Technical Preview~~, and AD LDS for Windows 10.

2.194 Attribute msDS-MembersForAzRole

This attribute specifies the list of member application groups or users linked to Az-Role.

```
cn: ms-DS-Members-For-Az-Role
ldapDisplayName: msDS-MembersForAzRole
attributeId: 1.2.840.113556.1.4.1806
attributeSyntax: 2.5.5.1
omSyntax: 127
omObjectClass: 1.3.12.2.1011.28.0.714
isSingleValued: FALSE
schemaIdGuid: cbf7e6cd-85a4-4314-8939-8bfe80597835
systemOnly: FALSE
searchFlags: 0
linkID: 2016
systemFlags: FLAG_SCHEMA_BASE_OBJECT
```

Version-Specific Behavior: Implemented on ADAM, Windows Server 2008, AD LDS for Windows Vista, Windows Server 2008 R2, AD LDS for Windows 7, Windows Server 2012, AD LDS for Windows 8, Windows Server 2012 R2, AD LDS for Windows 8.1, Windows Server 2016 ~~Technical Preview~~, and AD LDS for Windows 10.

2.195 Attribute msDS-MembersForAzRoleBL

This attribute specifies the backlink from a member application group or user to the Az-Role objects that link to it.

```
cn: ms-DS-Members-For-Az-Role-BL
ldapDisplayName: msDS-MembersForAzRoleBL
attributeId: 1.2.840.113556.1.4.1807
attributeSyntax: 2.5.5.1
omSyntax: 127
omObjectClass: 1.3.12.2.1011.28.0.714
isSingleValued: FALSE
schemaIdGuid: ececcd20-a7e0-4688-9ccf-02ece5e287f5
systemOnly: TRUE
searchFlags: 0
linkID: 2017
systemFlags: FLAG_SCHEMA_BASE_OBJECT | FLAG_ATTR_NOT_REPLICATED
```

Version-Specific Behavior: Implemented on ADAM, Windows Server 2008, AD LDS for Windows Vista, Windows Server 2008 R2, AD LDS for Windows 7, Windows Server 2012, AD LDS for Windows 8, Windows Server 2012 R2, AD LDS for Windows 8.1, Windows Server 2016 ~~Technical Preview~~, and AD LDS for Windows 10.

2.196 Attribute msDS-NC-Replica-Locations

This attribute specifies a list of servers that are the replica set for the corresponding non-domain naming context.

```
cn: ms-DS-NC-Replica-Locations
ldapDisplayName: msDS-NC-Replica-Locations
attributeId: 1.2.840.113556.1.4.1661
```

```
attributeSyntax: 2.5.5.1
omSyntax: 127
omObjectClass: 1.3.12.2.1011.28.0.714
isSingleValued: FALSE
schemaIdGuid: 97de9615-b537-46bc-ac0f-10720f3909f3
systemOnly: FALSE
searchFlags: 0
linkID: 1044
systemFlags: FLAG_SCHEMA_BASE_OBJECT
```

Version-Specific Behavior: Implemented on ADAM, Windows Server 2008, AD LDS for Windows Vista, Windows Server 2008 R2, AD LDS for Windows 7, Windows Server 2012, AD LDS for Windows 8, Windows Server 2012 R2, AD LDS for Windows 8.1, Windows Server 2016 ~~Technical Preview~~, and AD LDS for Windows 10.

2.197 Attribute msDS-NCReplCursors

This attribute specifies a list of past and present replication partners for a particular machine, and how up-to-date that machine is with each of them.

```
cn: ms-DS-NC-Repl-Cursors
ldapDisplayName: msDS-NCReplCursors
attributeId: 1.2.840.113556.1.4.1704
attributeSyntax: 2.5.5.12
omSyntax: 64
isSingleValued: FALSE
schemaIdGuid: 8a167ce4-f9e8-47eb-8d78-f7fe80abb2cc
systemOnly: FALSE
searchFlags: 0
systemFlags: FLAG_SCHEMA_BASE_OBJECT | FLAG_ATTR_IS_CONSTRUCTED
```

Version-Specific Behavior: Implemented on ADAM, Windows Server 2008, AD LDS for Windows Vista, Windows Server 2008 R2, AD LDS for Windows 7, Windows Server 2012, AD LDS for Windows 8, Windows Server 2012 R2, AD LDS for Windows 8.1, Windows Server 2016 ~~Technical Preview~~, and AD LDS for Windows 10.

2.198 Attribute msDS-NCReplInboundNeighbors

This attribute specifies replication partners for this partition. This server obtains replication data from these other servers, which act as sources.

```
cn: ms-DS-NC-Repl-Inbound-Neighbors
ldapDisplayName: msDS-NCReplInboundNeighbors
attributeId: 1.2.840.113556.1.4.1705
attributeSyntax: 2.5.5.12
omSyntax: 64
isSingleValued: FALSE
schemaIdGuid: 9edba85a-3e9e-431b-9b1a-a5b6e9eda796
systemOnly: FALSE
searchFlags: 0
systemFlags: FLAG_SCHEMA_BASE_OBJECT | FLAG_ATTR_IS_CONSTRUCTED
```

Version-Specific Behavior: Implemented on ADAM, Windows Server 2008, AD LDS for Windows Vista, Windows Server 2008 R2, AD LDS for Windows 7, Windows Server 2012, AD LDS for Windows 8, Windows Server 2012 R2, AD LDS for Windows 8.1, Windows Server 2016 ~~Technical Preview~~, and AD LDS for Windows 10.

2.199 Attribute msDS-NCReplOutboundNeighbors

This attribute specifies replication partners for this partition. This server sends replication data to these other servers, which act as destinations. This server will notify these other servers when new data is available.

```
cn: ms-DS-NC-Repl-Outbound-Neighbors
ldapDisplayName: msDS-NCReplOutboundNeighbors
attributeId: 1.2.840.113556.1.4.1706
attributeSyntax: 2.5.5.12
omSyntax: 64
isSingleValued: FALSE
schemaIdGuid: 855f2ef5-a1c5-4cc4-ba6d-32522848b61f
systemOnly: FALSE
searchFlags: 0
systemFlags: FLAG_SCHEMA_BASE_OBJECT | FLAG_ATTR_IS_CONSTRUCTED
```

Version-Specific Behavior: Implemented on ADAM, Windows Server 2008, AD LDS for Windows Vista, Windows Server 2008 R2, AD LDS for Windows 7, Windows Server 2012, AD LDS for Windows 8, Windows Server 2012 R2, AD LDS for Windows 8.1, Windows Server 2016 ~~Technical Preview~~, and AD LDS for Windows 10.

2.200 Attribute msDS-Non-Security-Group-Extra-Classes

This attribute specifies the common names of the nonstandard classes that can be added to a non-security group through the Active Directory Users and Computers snap-in.

```
cn: ms-DS-Non-Security-Group-Extra-Classes
ldapDisplayName: msDS-Non-Security-Group-Extra-Classes
attributeId: 1.2.840.113556.1.4.1689
attributeSyntax: 2.5.5.12
omSyntax: 64
isSingleValued: FALSE
schemaIdGuid: 2de144fc-1f52-486f-bdf4-16fcc3084e54
systemOnly: FALSE
```

Version-Specific Behavior: Implemented on Windows Server 2008, AD LDS for Windows Vista, Windows Server 2008 R2, AD LDS for Windows 7, Windows Server 2012, AD LDS for Windows 8, Windows Server 2012 R2, AD LDS for Windows 8.1, Windows Server 2016 ~~Technical Preview~~, and AD LDS for Windows 10.

2.201 Attribute msDS-NonMembers

This attribute serves the same purpose as the **Non-Security-Member** attribute but with scoping rules applied.

```
cn: ms-DS-Non-Members
ldapDisplayName: msDS-NonMembers
attributeId: 1.2.840.113556.1.4.1793
attributeSyntax: 2.5.5.1
omSyntax: 127
omObjectClass: 1.3.12.2.1011.28.0.714
isSingleValued: FALSE
schemaIdGuid: cafcb1de-f23c-46b5-adf7-1e64957bd5db
systemOnly: FALSE
searchFlags: 0
linkID: 2014
systemFlags: FLAG_SCHEMA_BASE_OBJECT
```

Version-Specific Behavior: Implemented on ADAM, Windows Server 2008, AD LDS for Windows Vista, Windows Server 2008 R2, AD LDS for Windows 7, Windows Server 2012, AD LDS for Windows 8, Windows Server 2012 R2, AD LDS for Windows 8.1, Windows Server 2016 ~~Technical Preview~~, and AD LDS for Windows 10.

2.202 Attribute msDS-NonMembersBL

This attribute specifies the backlink from a non-member group or user to the Az groups that link to it (has the same functionality as Non-Security-Member-BL).

```
cn: ms-DS-Non-Members-BL
ldapDisplayName: msDS-NonMembersBL
attributeId: 1.2.840.113556.1.4.1794
attributeSyntax: 2.5.5.1
omSyntax: 127
omObjectClass: 1.3.12.2.1011.28.0.714
isSingleValued: FALSE
schemaIdGuid: 2a8c68fc-3a7a-4e87-8720-fe77c51cbe74
systemOnly: TRUE
searchFlags: 0
linkID: 2015
systemFlags: FLAG_SCHEMA_BASE_OBJECT | FLAG_ATTR_NOT_REPLICATED
```

Version-Specific Behavior: Implemented on ADAM, Windows Server 2008, AD LDS for Windows Vista, Windows Server 2008 R2, AD LDS for Windows 7, Windows Server 2012, AD LDS for Windows 8, Windows Server 2012 R2, AD LDS for Windows 8.1, Windows Server 2016 ~~Technical Preview~~, and AD LDS for Windows 10.

2.203 Attribute msDS-OperationsForAzRole

This attribute specifies a list of operations linked to Az-Role.

```
cn: ms-DS-Operations-For-Az-Role
ldapDisplayName: msDS-OperationsForAzRole
attributeId: 1.2.840.113556.1.4.1812
attributeSyntax: 2.5.5.1
omSyntax: 127
omObjectClass: 1.3.12.2.1011.28.0.714
isSingleValued: FALSE
schemaIdGuid: 93f701be-fa4c-43b6-bc2f-4dbea718ffab
systemOnly: FALSE
searchFlags: 0
linkID: 2022
```

Version-Specific Behavior: Implemented on ADAM, Windows Server 2008, AD LDS for Windows Vista, Windows Server 2008 R2, AD LDS for Windows 7, Windows Server 2012, AD LDS for Windows 8, Windows Server 2012 R2, AD LDS for Windows 8.1, Windows Server 2016 ~~Technical Preview~~, and AD LDS for Windows 10.

2.204 Attribute msDS-OperationsForAzRoleBL

This attribute specifies the backlink from Az-Operation to the Az-Role objects that link to it.

```
cn: ms-DS-Operations-For-Az-Role-BL
ldapDisplayName: msDS-OperationsForAzRoleBL
attributeId: 1.2.840.113556.1.4.1813
attributeSyntax: 2.5.5.1
omSyntax: 127
```

```
omObjectClass: 1.3.12.2.1011.28.0.714
isSingleValued: FALSE
schemaIdGuid: f85b6228-3734-4525-b6b7-3f3bb220902c
systemOnly: TRUE
searchFlags: 0
linkID: 2023
systemFlags: FLAG_ATTR_NOT_REPLICATED
```

Version-Specific Behavior: Implemented on ADAM, Windows Server 2008, AD LDS for Windows Vista, Windows Server 2008 R2, AD LDS for Windows 7, Windows Server 2012, AD LDS for Windows 8, Windows Server 2012 R2, AD LDS for Windows 8.1, Windows Server 2016 ~~Technical Preview~~, and AD LDS for Windows 10.

2.205 Attribute msDS-OperationsForAzTask

This attribute specifies a list of operations linked to Az-Task.

```
cn: ms-DS-Operations-For-Az-Task
ldapDisplayName: msDS-OperationsForAzTask
attributeId: 1.2.840.113556.1.4.1808
attributeSyntax: 2.5.5.1
omSyntax: 127
omObjectClass: 1.3.12.2.1011.28.0.714
isSingleValued: FALSE
schemaIdGuid: 1aacb436-2e9d-44a9-9298-ce4debeb6ebf
systemOnly: FALSE
searchFlags: 0
linkID: 2018
showInAdvancedViewOnly: TRUE
```

Version-Specific Behavior: Implemented on ADAM, Windows Server 2008, AD LDS for Windows Vista, Windows Server 2008 R2, AD LDS for Windows 7, Windows Server 2012, AD LDS for Windows 8, Windows Server 2012 R2, AD LDS for Windows 8.1, Windows Server 2016 ~~Technical Preview~~, and AD LDS for Windows 10.

2.206 Attribute msDS-OperationsForAzTaskBL

This attribute specifies the backlink from Az-Operation to the Az-Task objects that link to it.

```
cn: ms-DS-Operations-For-Az-Task-BL
ldapDisplayName: msDS-OperationsForAzTaskBL
attributeId: 1.2.840.113556.1.4.1809
attributeSyntax: 2.5.5.1
omSyntax: 127
omObjectClass: 1.3.12.2.1011.28.0.714
isSingleValued: FALSE
schemaIdGuid: a637d211-5739-4ed1-89b2-88974548bc59
systemOnly: TRUE
searchFlags: 0
linkID: 2019
systemFlags: FLAG_ATTR_NOT_REPLICATED
```

Version-Specific Behavior: Implemented on ADAM, Windows Server 2008, AD LDS for Windows Vista, Windows Server 2008 R2, AD LDS for Windows 7, Windows Server 2012, AD LDS for Windows 8, Windows Server 2012 R2, AD LDS for Windows 8.1, Windows Server 2016 ~~Technical Preview~~, and AD LDS for Windows 10.

2.207 Attribute msDS-OptionalFeatureFlags

This attribute stores an integer value that contains flags that define behavior of an optional feature in Active Directory.

```
cn: ms-DS-Optional-Feature-Flags
ldapDisplayName: msDS-OptionalFeatureFlags
attributeId: 1.2.840.113556.1.4.2063
attributeSyntax: 2.5.5.9
omSyntax: 2
isSingleValued: TRUE
schemaIdGuid: 8a0560c1-97b9-4811-9db7-dc061598965b
systemOnly: TRUE
searchFlags: 0
systemFlags: FLAG_SCHEMA_BASE_OBJECT
```

Version-Specific Behavior: Implemented on Windows Server 2008 R2, AD LDS for Windows 7, Windows Server 2012, AD LDS for Windows 8, Windows Server 2012 R2, AD LDS for Windows 8.1, Windows Server 2016 [Technical Preview](#), and AD LDS for Windows 10.

2.208 Attribute msDS-OptionalFeatureGUID

This attribute stores the GUID of an optional feature.

```
cn: ms-DS-Optional-Feature-GUID
ldapDisplayName: msDS-OptionalFeatureGUID
attributeId: 1.2.840.113556.1.4.2062
attributeSyntax: 2.5.5.10
omSyntax: 4
isSingleValued: TRUE
schemaIdGuid: 9b88bda8-dd82-4998-a91d-5f2d2baf1927
systemOnly: TRUE
searchFlags: 0
rangeLower: 16
rangeUpper: 16
systemFlags: FLAG_SCHEMA_BASE_OBJECT
```

Version-Specific Behavior: Implemented on Windows Server 2008 R2, AD LDS for Windows 7, Windows Server 2012, AD LDS for Windows 8, Windows Server 2012 R2, AD LDS for Windows 8.1, Windows Server 2016 [Technical Preview](#), and AD LDS for Windows 10.

2.209 Attribute msDS-Other-Settings

This multivalued attribute is used to store any configurable setting for the DS stored in the NAME=VALUE format.

```
cn: ms-DS-Other-Settings
ldapDisplayName: msDS-Other-Settings
attributeId: 1.2.840.113556.1.4.1621
attributeSyntax: 2.5.5.12
omSyntax: 64
isSingleValued: FALSE
schemaIdGuid: 79d2f34c-9d7d-42bb-838f-866b3e4400e2
systemOnly: FALSE
searchFlags: 0
systemFlags: FLAG_SCHEMA_BASE_OBJECT
```

Version-Specific Behavior: Implemented on ADAM, Windows Server 2008, AD LDS for Windows Vista, Windows Server 2008 R2, AD LDS for Windows 7, Windows Server 2012, AD LDS for Windows 8,

Windows Server 2012 R2, AD LDS for Windows 8.1, Windows Server 2016 ~~Technical Preview~~, and AD LDS for Windows 10.

2.210 Attribute msDS-parentdistname

This attribute specifies the distinguished name (DN) of the parent object of the current object.

```
cn: ms-DS-Parent-Dist-Name
ldapDisplayName: msDS-parentdistname
attributeID: 1.2.840.113556.1.4.2203
attributeSyntax: 2.5.5.1
omSyntax: 127
omObjectClass: 1.3.12.2.1011.28.0.714
isSingleValued: TRUE
schemaIdGuid: b918fe7d-971a-f404-9e21-9261abec970b
systemOnly: TRUE
searchFlags: 0
systemFlags: FLAG_ATTR_NOT_REPLICATED | FLAG_ATTR_IS_CONSTRUCTED |
  FLAG_ATTR_IS_OPERATIONAL | FLAG_SCHEMA_BASE_OBJECT
showInAdvancedViewOnly: TRUE
```

Version-Specific Behavior: Implemented on Windows Server 2012 R2, AD LDS for Windows 8.1, Windows Server 2016 ~~Technical Preview~~, and AD LDS for Windows 10.

2.211 Attribute msDS-PortLDAP

This attribute is used to specify which port is used by the Directory Service to listen for LDAP requests. Currently, this attribute is only used for AD LDS.

```
cn: ms-DS-Port-LDAP
ldapDisplayName: msDS-PortLDAP
attributeId: 1.2.840.113556.1.4.1859
attributeSyntax: 2.5.5.9
omSyntax: 2
isSingleValued: TRUE
schemaIdGuid: 977225c1-5bdf-42b7-b6db-c3af077f558f
systemOnly: FALSE
searchFlags: 0
rangeLower: 0
rangeUpper: 65535
systemFlags: FLAG_SCHEMA_BASE_OBJECT
```

Version-Specific Behavior: Implemented on ADAM, Windows Server 2008, AD LDS for Windows Vista, Windows Server 2008 R2, AD LDS for Windows 7, Windows Server 2012, AD LDS for Windows 8, Windows Server 2012 R2, AD LDS for Windows 8.1, Windows Server 2016 ~~Technical Preview~~, and AD LDS for Windows 10.

2.212 Attribute msDS-PortSSL

ms-Ds-Port-SSL is used to specify which port is used by the Directory Service to listen for SSL-protected LDAP requests. Currently, this attribute is used only for AD LDS.

```
cn: ms-DS-Port-SSL
ldapDisplayName: msDS-PortSSL
attributeId: 1.2.840.113556.1.4.1860
attributeSyntax: 2.5.5.9
omSyntax: 2
isSingleValued: TRUE
schemaIdGuid: 2c85cfc2-2061-468c-a0ea-c8e0910f7374
```

```
systemOnly: FALSE
searchFlags: 0
rangeLower: 0
rangeUpper: 65535
systemFlags: FLAG_SCHEMA_BASE_OBJECT
```

Version-Specific Behavior: Implemented on ADAM, Windows Server 2008, AD LDS for Windows Vista, Windows Server 2008 R2, AD LDS for Windows 7, Windows Server 2012, AD LDS for Windows 8, Windows Server 2012 R2, AD LDS for Windows 8.1, Windows Server 2016 ~~Technical Preview~~, and AD LDS for Windows 10.

2.213 Attribute msDS-Preferred-GC-Site

The ms-DS-Preferred-GC-Site attribute is used by the security accounts manager for group expansion during token evaluation.

```
cn: ms-DS-Preferred-GC-Site
ldapDisplayName: msDS-Preferred-GC-Site
attributeId: 1.2.840.113556.1.4.1444
attributeSyntax: 2.5.5.1
omSyntax: 127
omObjectClass: 1.3.12.2.1011.28.0.714
isSingleValued: TRUE
schemaIdGuid: d921b50a-0ab2-42cd-87f6-09cf83a91854
systemOnly: FALSE
searchFlags: 0
systemFlags: FLAG_SCHEMA_BASE_OBJECT
```

Version-Specific Behavior: Implemented on ADAM, Windows Server 2008, AD LDS for Windows Vista, Windows Server 2008 R2, AD LDS for Windows 7, Windows Server 2012, AD LDS for Windows 8, Windows Server 2012 R2, AD LDS for Windows 8.1, Windows Server 2016 ~~Technical Preview~~, and AD LDS for Windows 10.

2.214 Attribute msDS-PrincipalName

This attribute specifies the account name for the security principal (constructed).

```
cn: ms-DS-Principal-Name
ldapDisplayName: msDS-PrincipalName
attributeId: 1.2.840.113556.1.4.1865
attributeSyntax: 2.5.5.12
omSyntax: 64
isSingleValued: TRUE
schemaIdGuid: 564e9325-d057-c143-9e3b-4f9e5ef46f93
systemOnly: FALSE
searchFlags: 0
systemFlags: FLAG_SCHEMA_BASE_OBJECT | FLAG_ATTR_IS_CONSTRUCTED
```

Version-Specific Behavior: Implemented on ADAM, Windows Server 2008, AD LDS for Windows Vista, Windows Server 2008 R2, AD LDS for Windows 7, Windows Server 2012, AD LDS for Windows 8, Windows Server 2012 R2, AD LDS for Windows 8.1, Windows Server 2016 ~~Technical Preview~~, and AD LDS for Windows 10.

2.215 Attribute msDS-QuotaAmount

This attribute specifies the assigned quota in terms of number of objects owned in the database.

```
cn: ms-DS-Quota-Amount
ldapDisplayName: msDS-QuotaAmount
attributeId: 1.2.840.113556.1.4.1845
attributeSyntax: 2.5.5.9
omSyntax: 2
isSingleValued: TRUE
schemaIdGuid: fbb9a00d-3a8c-4233-9cf9-7189264903a1
systemOnly: FALSE
searchFlags: 0
systemFlags: FLAG_SCHEMA_BASE_OBJECT
```

Version-Specific Behavior: Implemented on ADAM, Windows Server 2008, AD LDS for Windows Vista, Windows Server 2008 R2, AD LDS for Windows 7, Windows Server 2012, AD LDS for Windows 8, Windows Server 2012 R2, AD LDS for Windows 8.1, Windows Server 2016 ~~Technical Preview~~, and AD LDS for Windows 10.

2.216 Attribute msDS-QuotaEffective

This attribute specifies the effective quota for a security principal computed from the assigned quotas for a naming context.

```
cn: ms-DS-Quota-Effective
ldapDisplayName: msDS-QuotaEffective
attributeId: 1.2.840.113556.1.4.1848
attributeSyntax: 2.5.5.9
omSyntax: 2
isSingleValued: TRUE
schemaIdGuid: 6655b152-101c-48b4-b347-e1fceb60157
systemOnly: FALSE
searchFlags: 0
systemFlags: FLAG_SCHEMA_BASE_OBJECT | FLAG_ATTR_IS_CONSTRUCTED
```

Version-Specific Behavior: Implemented on ADAM, Windows Server 2008, AD LDS for Windows Vista, Windows Server 2008 R2, AD LDS for Windows 7, Windows Server 2012, AD LDS for Windows 8, Windows Server 2012 R2, AD LDS for Windows 8.1, Windows Server 2016 ~~Technical Preview~~, and AD LDS for Windows 10.

2.217 Attribute msDS-QuotaTrustee

This attribute specifies the SID, as defined in [MS-DTYP] section 2.4.2, of the security principal for which a quota is being assigned.

```
cn: ms-DS-Quota-Trustee
ldapDisplayName: msDS-QuotaTrustee
attributeId: 1.2.840.113556.1.4.1844
attributeSyntax: 2.5.5.17
omSyntax: 4
isSingleValued: TRUE
schemaIdGuid: 16378906-4ea5-49be-a8d1-bfd41dff4f65
systemOnly: FALSE
searchFlags: 0
rangeLower: 0
rangeUpper: 28
systemFlags: FLAG_SCHEMA_BASE_OBJECT
```

Version-Specific Behavior: Implemented on ADAM, Windows Server 2008, AD LDS for Windows Vista, Windows Server 2008 R2, AD LDS for Windows 7, Windows Server 2012, AD LDS for Windows 8,

Windows Server 2012 R2, AD LDS for Windows 8.1, Windows Server 2016 ~~Technical Preview~~, and AD LDS for Windows 10.

2.218 Attribute msDS-QuotaUsed

This attribute specifies the current quota being consumed by a security principal in the directory database.

```
cn: ms-DS-Quota-Used
ldapDisplayName: msDS-QuotaUsed
attributeId: 1.2.840.113556.1.4.1849
attributeSyntax: 2.5.5.9
omSyntax: 2
isSingleValued: TRUE
schemaIdGuid: b5a84308-615d-4bb7-b05f-2f1746aa439f
systemOnly: FALSE
searchFlags: 0
systemFlags: FLAG_SCHEMA_BASE_OBJECT | FLAG_ATTR_IS_CONSTRUCTED
```

Version-Specific Behavior: Implemented on ADAM, Windows Server 2008, AD LDS for Windows Vista, Windows Server 2008 R2, AD LDS for Windows 7, Windows Server 2012, AD LDS for Windows 8, Windows Server 2012 R2, AD LDS for Windows 8.1, Windows Server 2016 ~~Technical Preview~~, and AD LDS for Windows 10.

2.219 Attribute msDS-ReplAttributeMetaData

This attribute specifies a list of metadata for each replicated attribute. The metadata indicates who changed the attribute last.

```
cn: ms-DS-Repl-Attribute-Meta-Data
ldapDisplayName: msDS-ReplAttributeMetaData
attributeId: 1.2.840.113556.1.4.1707
attributeSyntax: 2.5.5.12
omSyntax: 64
isSingleValued: FALSE
schemaIdGuid: d7c53242-724e-4c39-9d4c-2df8c9d66c7a
systemOnly: FALSE
searchFlags: 0
systemFlags: FLAG_SCHEMA_BASE_OBJECT | FLAG_ATTR_IS_CONSTRUCTED
```

Version-Specific Behavior: Implemented on ADAM, Windows Server 2008, AD LDS for Windows Vista, Windows Server 2008 R2, AD LDS for Windows 7, Windows Server 2012, AD LDS for Windows 8, Windows Server 2012 R2, AD LDS for Windows 8.1, Windows Server 2016 ~~Technical Preview~~, and AD LDS for Windows 10.

2.220 Attribute msDS-ReplAuthenticationMode

The **ms-DS-Repl-Authentication-Mode** attribute is used to specify which authentication method is used to authenticate replication partners. This attribute applies to the configuration partition of an AD LDS instance.

```
cn: ms-DS-Repl-Authentication-Mode
ldapDisplayName: msDS-ReplAuthenticationMode
attributeId: 1.2.840.113556.1.4.1861
attributeSyntax: 2.5.5.9
omSyntax: 2
isSingleValued: TRUE
schemaIdGuid: 6e124d4f-1a3f-4cc6-8e09-4a54c81b1d50
```



```
systemOnly: FALSE
searchFlags: 0
rangeLower: 0
systemFlags: FLAG_SCHEMA_BASE_OBJECT
```

Version-Specific Behavior: Implemented on ADAM, Windows Server 2008, AD LDS for Windows Vista, Windows Server 2008 R2, AD LDS for Windows 7, Windows Server 2012, AD LDS for Windows 8, Windows Server 2012 R2, AD LDS for Windows 8.1, Windows Server 2016 ~~Technical Preview~~, and AD LDS for Windows 10.

2.221 Attribute msDS-Replication-Notify-First-DSA-Delay

This attribute controls the delay between changes to the DS and notification of the first replica partner for an NC.

```
cn: ms-DS-Replication-Notify-First-DSA-Delay
ldapDisplayName: msDS-Replication-Notify-First-DSA-Delay
attributeId: 1.2.840.113556.1.4.1663
attributeSyntax: 2.5.5.9
omSyntax: 2
isSingleValued: TRUE
schemaIdGuid: 85abd4f4-0a89-4e49-bdec-6f35bb2562ba
systemOnly: FALSE
searchFlags: 0
systemFlags: FLAG_SCHEMA_BASE_OBJECT
```

Version-Specific Behavior: Implemented on ADAM, Windows Server 2008, AD LDS for Windows Vista, Windows Server 2008 R2, AD LDS for Windows 7, Windows Server 2012, AD LDS for Windows 8, Windows Server 2012 R2, AD LDS for Windows 8.1, Windows Server 2016 ~~Technical Preview~~, and AD LDS for Windows 10.

2.222 Attribute msDS-Replication-Notify-Subsequent-DSA-Delay

This attribute controls the delay between notification of each subsequent replica partner for an NC.

```
cn: ms-DS-Replication-Notify-Subsequent-DSA-Delay
ldapDisplayName: msDS-Replication-Notify-Subsequent-DSA-Delay
attributeId: 1.2.840.113556.1.4.1664
attributeSyntax: 2.5.5.9
omSyntax: 2
isSingleValued: TRUE
schemaIdGuid: d63db385-dd92-4b52-b1d8-0d3ecc0e86b6
systemOnly: FALSE
searchFlags: 0
systemFlags: FLAG_SCHEMA_BASE_OBJECT
```

Version-Specific Behavior: Implemented on ADAM, Windows Server 2008, AD LDS for Windows Vista, Windows Server 2008 R2, AD LDS for Windows 7, Windows Server 2012, AD LDS for Windows 8, Windows Server 2012 R2, AD LDS for Windows 8.1, Windows Server 2016 ~~Technical Preview~~, and AD LDS for Windows 10.

2.223 Attribute msDS-ReplicationEpoch

This attribute is used to hold the epoch under which all of the DCs are replicating. An epoch is the period in which a domain has a specific name. A new epoch starts when a domain name change occurs.

```
cn: ms-DS-ReplicationEpoch
ldapDisplayName: msDS-ReplicationEpoch
attributeId: 1.2.840.113556.1.4.1720
attributeSyntax: 2.5.5.9
omSyntax: 2
isSingleValued: TRUE
schemaIdGuid: 08e3aa79-eb1c-45b5-af7b-8f94246c8e41
systemOnly: FALSE
searchFlags: 0
systemFlags: FLAG_SCHEMA_BASE_OBJECT | FLAG_ATTR_NOT_REPLICATED
```

Version-Specific Behavior: Implemented on ADAM, Windows Server 2008, AD LDS for Windows Vista, Windows Server 2008 R2, AD LDS for Windows 7, Windows Server 2012, AD LDS for Windows 8, Windows Server 2012 R2, AD LDS for Windows 8.1, Windows Server 2016 **Technical Preview**, and AD LDS for Windows 10.

2.224 Attribute msDS-RepValueMetaData

This attribute specifies a list of metadata for each value of an attribute. The metadata indicates who changed the value last.

```
cn: ms-DS-Repl-Value-Meta-Data
ldapDisplayName: msDS-ReplValueMetaData
attributeId: 1.2.840.113556.1.4.1708
attributeSyntax: 2.5.5.12
omSyntax: 64
isSingleValued: FALSE
schemaIdGuid: 2f5c8145-e1bd-410b-8957-8bfa81d5acfd
systemOnly: FALSE
searchFlags: 0
systemFlags: FLAG_SCHEMA_BASE_OBJECT | FLAG_ATTR_IS_CONSTRUCTED
```

Version-Specific Behavior: Implemented on ADAM, Windows Server 2008, AD LDS for Windows Vista, Windows Server 2008 R2, AD LDS for Windows 7, Windows Server 2012, AD LDS for Windows 8, Windows Server 2012 R2, AD LDS for Windows 8.1, Windows Server 2016 **Technical Preview**, and AD LDS for Windows 10.

2.225 Attribute msDS-RepValueMetaDataExt

This attribute contains no values on any object.

```
cn: ms-DS-Repl-Value-Meta-Data-Ext
ldapDisplayName: msDS-ReplValueMetaDataExt
attributeId: 1.2.840.113556.1.4.2235
attributeSyntax: 2.5.5.12
omSyntax: 64
isSingleValued: FALSE
schemaIdGuid: 1e02d2ef-44ad-46b2-a67d-9fd18d780bca
systemOnly: FALSE
searchFlags: 0
systemFlags: FLAG_ATTR_IS_CONSTRUCTED | FLAG_SCHEMA_BASE_OBJECT
showInAdvancedViewOnly: TRUE
```

Version-Specific Behavior: Implemented on Windows Server 2012 R2, AD LDS for Windows 8.1, Windows Server 2016 **Technical Preview**, and AD LDS for Windows 10.

2.226 Attribute msDS-RequiredDomainBehaviorVersion

This attribute specifies the required domain functional level for an optional feature enabled in a domain-wide scope.

```
cn: ms-DS-Required-Domain-Behavior-Version
ldapDisplayName: msDS-RequiredDomainBehaviorVersion
attributeId: 1.2.840.113556.1.4.2066
attributeSyntax: 2.5.5.9
omSyntax: 2
isSingleValued: TRUE
schemaIdGuid: eadd3dfe-ae0e-4cc2-b9b9-5fe5b6ed2dd2
systemOnly: TRUE
searchFlags: 0
systemFlags: FLAG_SCHEMA_BASE_OBJECT
```

Version-Specific Behavior: Implemented on Windows Server 2008 R2, AD LDS for Windows 7, Windows Server 2012, AD LDS for Windows 8, Windows Server 2012 R2, AD LDS for Windows 8.1, Windows Server 2016 **Technical Preview**, and AD LDS for Windows 10.

2.227 Attribute msDS-RequiredForestBehaviorVersion

This attribute specifies the required forest functional level for an optional feature.

```
cn: ms-DS-Required-Forest-Behavior-Version
ldapDisplayName: msDS-RequiredForestBehaviorVersion
attributeId: 1.2.840.113556.1.4.2079
attributeSyntax: 2.5.5.9
omSyntax: 2
isSingleValued: TRUE
schemaIdGuid: 4beca2e8-a653-41b2-8fee-721575474bec
systemOnly: TRUE
searchFlags: 0
systemFlags: FLAG_SCHEMA_BASE_OBJECT
```

Version-Specific Behavior: Implemented on Windows Server 2008 R2, AD LDS for Windows 7, Windows Server 2012, AD LDS for Windows 8, Windows Server 2012 R2, AD LDS for Windows 8.1, Windows Server 2016 **Technical Preview**, and AD LDS for Windows 10.

2.228 Attribute msDS-RetiredReplNCSignatures

This attribute specifies information about naming contexts that are no longer held on this computer.

```
cn: ms-DS-Retired-Repl-NC-Signatures
ldapDisplayName: msDS-RetiredReplNCSignatures
attributeId: 1.2.840.113556.1.4.1826
attributeSyntax: 2.5.5.10
omSyntax: 4
isSingleValued: TRUE
schemaIdGuid: d5b35506-19d6-4d26-9afb-11357ac99b5e
systemOnly: TRUE
searchFlags: 0
systemFlags: FLAG_SCHEMA_BASE_OBJECT | FLAG_ATTR_NOT_REPLICATED
```

Version-Specific Behavior: Implemented on ADAM, Windows Server 2008, AD LDS for Windows Vista, Windows Server 2008 R2, AD LDS for Windows 7, Windows Server 2012, AD LDS for Windows 8,

Windows Server 2012 R2, AD LDS for Windows 8.1, Windows Server 2016 ~~Technical Preview~~, and AD LDS for Windows 10.

2.229 Attribute msDs-Schema-Extensions

This attribute specifies a binary BLOB used to store information about extensions to schema objects.

```
cn: ms-ds-Schema-Extensions
ldapDisplayName: msDs-Schema-Extensions
attributeId: 1.2.840.113556.1.4.1440
attributeSyntax: 2.5.5.10
omSyntax: 4
isSingleValued: FALSE
schemaIdGuid: b39a61be-ed07-4cab-9a4a-4963ed0141e1
systemOnly: TRUE
searchFlags: 0
systemFlags: FLAG_SCHEMA_BASE_OBJECT
```

Version-Specific Behavior: Implemented on ADAM, Windows Server 2008, AD LDS for Windows Vista, Windows Server 2008 R2, AD LDS for Windows 7, Windows Server 2012, AD LDS for Windows 8, Windows Server 2012 R2, AD LDS for Windows 8.1, Windows Server 2016 ~~Technical Preview~~, and AD LDS for Windows 10.

2.230 Attribute msDS-SCPContainer

This attribute specifies the custom location to place SCP objects. This attribute ~~should contain~~contains a DN value (either FQDN or GUID-based) for the container in Active Directory.

```
cn: ms-DS-SCP-Container
ldapDisplayName: msDS-SCPContainer
attributeId: 1.2.840.113556.1.4.1872
attributeSyntax: 2.5.5.12
omSyntax: 64
isSingleValued: TRUE
schemaIdGuid: 454588e6-0b4e-b642-a6b8-ec03f6e1d9c5
systemOnly: FALSE
searchFlags: 0
rangeLower: 0
rangeUpper: 4096
systemFlags: FLAG_SCHEMA_BASE_OBJECT
```

Version-Specific Behavior: Implemented on ADAM, Windows Server 2008, AD LDS for Windows Vista, Windows Server 2008 R2, AD LDS for Windows 7, Windows Server 2012, AD LDS for Windows 8, Windows Server 2012 R2, AD LDS for Windows 8.1, Windows Server 2016 ~~Technical Preview~~, and AD LDS for Windows 10.

2.231 Attribute msDS-SDReferenceDomain

This attribute specifies the domain to be used for default security descriptor translation for a non-domain naming context.

```
cn: ms-DS-SD-Reference-Domain
ldapDisplayName: msDS-SDReferenceDomain
attributeId: 1.2.840.113556.1.4.1711
attributeSyntax: 2.5.5.1
omSyntax: 127
omObjectClass: 1.3.12.2.1011.28.0.714
isSingleValued: TRUE
schemaIdGuid: 4c51e316-f628-43a5-b06b-ffb695fcb4f3
```

```
systemOnly: FALSE
searchFlags: 0
linkID: 2000
systemFlags: FLAG_SCHEMA_BASE_OBJECT
```

Version-Specific Behavior: Implemented on ADAM, Windows Server 2008, AD LDS for Windows Vista, Windows Server 2008 R2, AD LDS for Windows 7, Windows Server 2012, AD LDS for Windows 8, Windows Server 2012 R2, AD LDS for Windows 8.1, Windows Server 2016 ~~Technical Preview~~, and AD LDS for Windows 10.

2.232 Attribute msDS-Security-Group-Extra-Classes

This attribute specifies the common names of the nonstandard classes that can be added to a security group through the Active Directory Users and Computers snap-in.

```
cn: ms-DS-Security-Group-Extra-Classes
ldapDisplayName: msDS-Security-Group-Extra-Classes
attributeId: 1.2.840.113556.1.4.1688
attributeSyntax: 2.5.5.12
omSyntax: 64
isSingleValued: FALSE
schemaIdGuid: 4f146ae8-a4fe-4801-a731-f51848a4f4e4
systemOnly: FALSE
```

Version-Specific Behavior: Implemented on Windows Server 2008, AD LDS for Windows Vista, Windows Server 2008 R2, AD LDS for Windows 7, Windows Server 2012, AD LDS for Windows 8, Windows Server 2012 R2, AD LDS for Windows 8.1, Windows Server 2016 ~~Technical Preview~~, and AD LDS for Windows 10.

2.233 Attribute msDS-ServiceAccount

This attribute specifies the FPO representing the AD LDS service account.

```
cn: ms-DS-Service-Account
ldapDisplayName: msDS-ServiceAccount
attributeId: 1.2.840.113556.1.4.1866
attributeSyntax: 2.5.5.1
omSyntax: 127
omObjectClass: 1.3.12.2.1011.28.0.714
isSingleValued: FALSE
schemaIdGuid: a7f73651-688b-401e-b0cf-9345857bab23
systemOnly: TRUE
searchFlags: 0
linkID: 2040
systemFlags: FLAG_SCHEMA_BASE_OBJECT
```

Version-Specific Behavior: Implemented on ADAM, Windows Server 2008, AD LDS for Windows Vista, Windows Server 2008 R2, AD LDS for Windows 7, Windows Server 2012, AD LDS for Windows 8, Windows Server 2012 R2, AD LDS for Windows 8.1, Windows Server 2016 ~~Technical Preview~~, and AD LDS for Windows 10.

2.234 Attribute msDS-ServiceAccountBL

This attribute specifies a backlink reference to the AD LDS DSA object that uses this service account.

```
cn: ms-DS-Service-Account-BL
ldapDisplayName: msDS-ServiceAccountBL
```

```
attributeId: 1.2.840.113556.1.4.1867
attributeSyntax: 2.5.5.1
omSyntax: 127
omObjectClass: 1.3.12.2.1011.28.0.714
isSingleValued: FALSE
schemaIdGuid: 1322c9ff-1334-3d4a-9396-4d9284d42636
systemOnly: TRUE
searchFlags: 0
linkID: 2041
systemFlags: FLAG_SCHEMA_BASE_OBJECT | FLAG_ATTR_NOT_REPLICATED
```

Version-Specific Behavior: Implemented on ADAM, Windows Server 2008, AD LDS for Windows Vista, Windows Server 2008 R2, AD LDS for Windows 7, Windows Server 2012, AD LDS for Windows 8, Windows Server 2012 R2, AD LDS for Windows 8.1, Windows Server 2016 ~~Technical Preview~~, and AD LDS for Windows 10.

2.235 Attribute msDS-ServiceAccountDNSDomain

This attribute specifies the domain of which the AD LDS service account is a member.

```
cn: ms-DS-Service-Account-DNS-Domain
ldapDisplayName: msDS-ServiceAccountDNSDomain
attributeId: 1.2.840.113556.1.4.1862
attributeSyntax: 2.5.5.12
omSyntax: 64
isSingleValued: TRUE
schemaIdGuid: fba633d4-20d7-4773-8b2c-c7445f54360d
systemOnly: TRUE
searchFlags: 0
rangeLower: 0
rangeUpper: 2048
systemFlags: FLAG_SCHEMA_BASE_OBJECT
```

Version-Specific Behavior: Implemented on ADAM, Windows Server 2008, AD LDS for Windows Vista, Windows Server 2008 R2, AD LDS for Windows 7, Windows Server 2012, AD LDS for Windows 8, Windows Server 2012 R2, AD LDS for Windows 8.1, Windows Server 2016 ~~Technical Preview~~, and AD LDS for Windows 10.

2.236 Attribute msDS-Settings

This attribute is used to store settings for an object. Its use is solely determined by the object's owner. It is recommended to use it to store name/value pairs; for example, color=blue.

```
cn: ms-DS-Settings
ldapDisplayName: msDS-Settings
attributeId: 1.2.840.113556.1.4.1697
attributeSyntax: 2.5.5.12
omSyntax: 64
isSingleValued: FALSE
schemaIdGuid: 0e1b47d7-40a3-4b48-8d1b-4cac0c1cdf21
systemOnly: FALSE
searchFlags: 0
rangeUpper: 1000000
```

Version-Specific Behavior: Implemented on ADAM, Windows Server 2008, AD LDS for Windows Vista, Windows Server 2008 R2, AD LDS for Windows 7, Windows Server 2012, AD LDS for Windows 8, Windows Server 2012 R2, AD LDS for Windows 8.1, Windows Server 2016 ~~Technical Preview~~, and AD LDS for Windows 10.

2.237 Attribute msDS-TasksForAzRole

This attribute specifies a list of tasks for Az-Role.

```
cn: ms-DS-Tasks-For-Az-Role
ldapDisplayName: msDS-TasksForAzRole
attributeId: 1.2.840.113556.1.4.1814
attributeSyntax: 2.5.5.1
omSyntax: 127
omObjectClass: 1.3.12.2.1011.28.0.714
isSingleValued: FALSE
schemaIdGuid: 35319082-8c4a-4646-9386-c2949d49894d
systemOnly: FALSE
searchFlags: 0
linkID: 2024
```

Version-Specific Behavior: Implemented on ADAM, Windows Server 2008, AD LDS for Windows Vista, Windows Server 2008 R2, AD LDS for Windows 7, Windows Server 2012, AD LDS for Windows 8, Windows Server 2012 R2, AD LDS for Windows 8.1, Windows Server 2016 ~~Technical Preview~~, and AD LDS for Windows 10.

2.238 Attribute msDS-TasksForAzRoleBL

This attribute specifies a backlink from Az-Task to the Az-Role objects that link to it.

```
cn: ms-DS-Tasks-For-Az-Role-BL
ldapDisplayName: msDS-TasksForAzRoleBL
attributeId: 1.2.840.113556.1.4.1815
attributeSyntax: 2.5.5.1
omSyntax: 127
omObjectClass: 1.3.12.2.1011.28.0.714
isSingleValued: FALSE
schemaIdGuid: a0dcd536-5158-42fe-8c40-c00a7ad37959
systemOnly: TRUE
searchFlags: 0
linkID: 2025
showInAdvancedViewOnly: TRUE
systemFlags: FLAG_ATTR_NOT_REPLICATED
```

Version-Specific Behavior: Implemented on ADAM, Windows Server 2008, AD LDS for Windows Vista, Windows Server 2008 R2, AD LDS for Windows 7, Windows Server 2012, AD LDS for Windows 8, Windows Server 2012 R2, AD LDS for Windows 8.1, Windows Server 2016 ~~Technical Preview~~, and AD LDS for Windows 10.

2.239 Attribute msDS-TasksForAzTask

This attribute specifies a list of tasks linked to Az-Task.

```
cn: ms-DS-Tasks-For-Az-Task
ldapDisplayName: msDS-TasksForAzTask
attributeId: 1.2.840.113556.1.4.1810
attributeSyntax: 2.5.5.1
omSyntax: 127
omObjectClass: 1.3.12.2.1011.28.0.714
isSingleValued: FALSE
schemaIdGuid: b11c8ee2-5fcd-46a7-95f0-f38333f096cf
systemOnly: FALSE
searchFlags: 0
linkID: 2020
```

Version-Specific Behavior: Implemented on ADAM, Windows Server 2008, AD LDS for Windows Vista, Windows Server 2008 R2, AD LDS for Windows 7, Windows Server 2012, AD LDS for Windows 8, Windows Server 2012 R2, AD LDS for Windows 8.1, Windows Server 2016 ~~Technical Preview~~, and AD LDS for Windows 10.

2.240 Attribute msDS-TasksForAzTaskBL

This attribute specifies a backlink from Az-Task to the Az-Task objects that link to it.

```
cn: ms-DS-Tasks-For-Az-Task-BL
ldapDisplayName: msDS-TasksForAzTaskBL
attributeId: 1.2.840.113556.1.4.1811
attributeSyntax: 2.5.5.1
omSyntax: 127
omObjectClass: 1.3.12.2.1011.28.0.714
isSingleValued: FALSE
schemaIdGuid: df446e52-b5fa-4ca2-a42f-13f98a526c8f
systemOnly: TRUE
searchFlags: 0
linkID: 2021
systemFlags: FLAG_ATTR_NOT_REPLICATED
```

Version-Specific Behavior: Implemented on ADAM, Windows Server 2008, AD LDS for Windows Vista, Windows Server 2008 R2, AD LDS for Windows 7, Windows Server 2012, AD LDS for Windows 8, Windows Server 2012 R2, AD LDS for Windows 8.1, Windows Server 2016 ~~Technical Preview~~, and AD LDS for Windows 10.

2.241 Attribute msDS-TombstoneQuotaFactor

This attribute specifies the percentage factor by which the tombstone object count ~~should be~~ reduced for the purpose of quota accounting.

```
cn: ms-DS-Tombstone-Quota-Factor
ldapDisplayName: msDS-TombstoneQuotaFactor
attributeId: 1.2.840.113556.1.4.1847
attributeSyntax: 2.5.5.9
omSyntax: 2
isSingleValued: TRUE
schemaIdGuid: 461744d7-f3b6-45ba-8753-fb9552a5df32
systemOnly: FALSE
searchFlags: 0
rangeLower: 0
rangeUpper: 100
systemFlags: FLAG_SCHEMA_BASE_OBJECT
```

Version-Specific Behavior: Implemented on ADAM, Windows Server 2008, AD LDS for Windows Vista, Windows Server 2008 R2, AD LDS for Windows 7, Windows Server 2012, AD LDS for Windows 8, Windows Server 2012 R2, AD LDS for Windows 8.1, Windows Server 2016 ~~Technical Preview~~, and AD LDS for Windows 10.

2.242 Attribute msDS-TopQuotaUsage

This attribute lists the top quota users, ordered by decreasing quota usage currently in the directory database.

```
cn: ms-DS-Top-Quota-Usage
ldapDisplayName: msDS-TopQuotaUsage
attributeId: 1.2.840.113556.1.4.1850
```



```
attributeSyntax: 2.5.5.12
omSyntax: 64
isSingleValued: FALSE
schemaIdGuid: 7b7cce4f-f1f5-4bb6-b7eb-23504af19e75
systemOnly: FALSE
searchFlags: 0
systemFlags: FLAG_SCHEMA_BASE_OBJECT | FLAG_ATTR_IS_CONSTRUCTED
```

Version-Specific Behavior: Implemented on ADAM, Windows Server 2008, AD LDS for Windows Vista, Windows Server 2008 R2, AD LDS for Windows 7, Windows Server 2012, AD LDS for Windows 8, Windows Server 2012 R2, AD LDS for Windows 8.1, Windows Server 2016 **Technical Preview**, and AD LDS for Windows 10.

2.243 Attribute msDS-UpdateScript

This attribute is used to hold the script with the domain restructure instructions.

```
cn: ms-DS-UpdateScript
ldapDisplayName: msDS-UpdateScript
attributeId: 1.2.840.113556.1.4.1721
attributeSyntax: 2.5.5.12
omSyntax: 64
isSingleValued: TRUE
schemaIdGuid: 146eb639-bb9f-4fc1-a825-e29e00c77920
systemOnly: FALSE
searchFlags: 0
systemFlags: FLAG_SCHEMA_BASE_OBJECT
```

Version-Specific Behavior: Implemented on ADAM, Windows Server 2008, AD LDS for Windows Vista, Windows Server 2008 R2, AD LDS for Windows 7, Windows Server 2012, AD LDS for Windows 8, Windows Server 2012 R2, AD LDS for Windows 8.1, Windows Server 2016 **Technical Preview**, and AD LDS for Windows 10.

2.244 Attribute msDS-User-Account-Control-Computed

This attribute specifies flags that control behavior of the user account. For more information, see [MS-ADTS] section 3.1.1.4.5.17.

```
cn: ms-DS-User-Account-Control-Computed
ldapDisplayName: msDS-User-Account-Control-Computed
attributeId: 1.2.840.113556.1.4.1460
attributeSyntax: 2.5.5.9
omSyntax: 2
isSingleValued: TRUE
schemaIdGuid: 2cc4b836-b63f-4940-8d23-ea7acf06af56
systemOnly: FALSE
searchFlags: 0
attributeSecurityGuid: 4c164200-20c0-11d0-a768-00aa006e0529
systemFlags: FLAG_SCHEMA_BASE_OBJECT | FLAG_ATTR_IS_CONSTRUCTED
```

Version-Specific Behavior: Implemented on ADAM, Windows Server 2008, AD LDS for Windows Vista, Windows Server 2008 R2, AD LDS for Windows 7, Windows Server 2012, AD LDS for Windows 8, Windows Server 2012 R2, AD LDS for Windows 8.1, Windows Server 2016 **Technical Preview**, and AD LDS for Windows 10.

2.245 Attribute msDS-UserAccountDisabled

This attribute specifies a Boolean flag that controls whether an account is disabled or enabled.

```
cn: ms-DS-User-Account-Disabled
ldapDisplayName: msDS-UserAccountDisabled
attributeId: 1.2.840.113556.1.4.1853
attributeSyntax: 2.5.5.8
omSyntax: 1
isSingleValued: TRUE
schemaIdGuid: 7c708658-7372-4211-b22b-13a45ffd1d61
systemOnly: FALSE
searchFlags: 0
systemFlags: FLAG_SCHEMA_BASE_OBJECT
```

Version-Specific Behavior: Implemented on ADAM, Windows Server 2008, AD LDS for Windows Vista, Windows Server 2008 R2, AD LDS for Windows 7, Windows Server 2012, AD LDS for Windows 8, Windows Server 2012 R2, AD LDS for Windows 8.1, Windows Server 2016 ~~Technical Preview~~, and AD LDS for Windows 10.

2.246 Attribute msDS-UserDontExpirePassword

This attribute specifies a Boolean flag that controls whether the password will expire for the account that this attribute references.

```
cn: ms-DS-User-Dont-Expire-Password
ldapDisplayName: msDS-UserDontExpirePassword
attributeId: 1.2.840.113556.1.4.1855
attributeSyntax: 2.5.5.8
omSyntax: 1
isSingleValued: TRUE
schemaIdGuid: 8788193a-2925-43d9-a221-bb7fff397675
systemOnly: FALSE
searchFlags: 0
systemFlags: FLAG_SCHEMA_BASE_OBJECT
```

Version-Specific Behavior: Implemented on ADAM, Windows Server 2008, AD LDS for Windows Vista, Windows Server 2008 R2, AD LDS for Windows 7, Windows Server 2012, AD LDS for Windows 8, Windows Server 2012 R2, AD LDS for Windows 8.1, Windows Server 2016 ~~Technical Preview~~, and AD LDS for Windows 10.

2.247 Attribute msDS-UserPasswordExpired

This attribute specifies a Boolean flag that indicates whether the password has expired for the account that this attribute references. TRUE means that the password has expired.

```
cn: ms-DS-User-Password-Expired
ldapDisplayName: msDS-UserPasswordExpired
attributeId: 1.2.840.113556.1.4.1858
attributeSyntax: 2.5.5.8
omSyntax: 1
isSingleValued: TRUE
schemaIdGuid: 565c7ab5-e13e-47f6-abb5-de741806f125
systemOnly: FALSE
searchFlags: 0
systemFlags: FLAG_SCHEMA_BASE_OBJECT | FLAG_ATTR_IS_CONSTRUCTED
```

Version-Specific Behavior: Implemented on ADAM, Windows Server 2008, AD LDS for Windows Vista, Windows Server 2008 R2, AD LDS for Windows 7, Windows Server 2012, AD LDS for Windows 8, Windows Server 2012 R2, AD LDS for Windows 8.1, Windows Server 2016 ~~Technical Preview~~, and AD LDS for Windows 10.

2.248 Attribute msDS-USNLastSyncSuccess

This attribute specifies the USN at which the last successful replication synchronization occurred.

```
cn: ms-DS-USN-Last-Sync-Success
ldapDisplayName: msDS-USNLastSyncSuccess
attributeId: 1.2.840.113556.1.4.2055
attributeSyntax: 2.5.5.16
omSyntax: 65
isSingleValued: TRUE
schemaIdGuid: 31f7b8b6-c9f8-4f2d-a37b-58a823030331
systemOnly: FALSE
searchFlags: 0
systemFlags: FLAG_SCHEMA_BASE_OBJECT | FLAG_ATTR_NOT_REPLICATED |
FLAG_ATTR_IS_OPERATIONAL
```

Version-Specific Behavior: Implemented on Windows Server 2008 R2, AD LDS for Windows 7, Windows Server 2012, AD LDS for Windows 8, Windows Server 2012 R2, AD LDS for Windows 8.1, Windows Server 2016 **Technical Preview**, and AD LDS for Windows 10.

2.249 Attribute mustContain

This attribute specifies the list of mandatory attributes for a class. These attributes **must have to** be specified when an instance of the class is created.

```
cn: Must-Contain
ldapDisplayName: mustContain
attributeId: 1.2.840.113556.1.2.24
attributeSyntax: 2.5.5.2
omSyntax: 6
isSingleValued: FALSE
schemaIdGuid: bf9679d3-0de6-11d0-a285-00aa003049e2
systemOnly: FALSE
searchFlags: 0
systemFlags: FLAG_SCHEMA_BASE_OBJECT
```

Version-Specific Behavior: Implemented on ADAM, Windows Server 2008, AD LDS for Windows Vista, Windows Server 2008 R2, AD LDS for Windows 7, Windows Server 2012, AD LDS for Windows 8, Windows Server 2012 R2, AD LDS for Windows 8.1, Windows Server 2016 **Technical Preview**, and AD LDS for Windows 10.

2.250 Attribute name

This attribute specifies the relative distinguished name of an object.

```
cn: RDN
ldapDisplayName: name
attributeId: 1.2.840.113556.1.4.1
attributeSyntax: 2.5.5.12
omSyntax: 64
isSingleValued: TRUE
schemaIdGuid: bf967a0e-0de6-11d0-a285-00aa003049e2
systemOnly: TRUE
searchFlags: fPRESERVEONDELETE| fANR | fATTINDEX
rangeLower: 1
rangeUpper: 255
attributeSecurityGuid: e48d0154-bcf8-11d1-8702-00c04fb96050
isMemberOfPartialAttributeSet: TRUE
systemFlags: FLAG_SCHEMA_BASE_OBJECT |
```

Version-Specific Behavior: Implemented on ADAM, Windows Server 2008, AD LDS for Windows Vista, Windows Server 2008 R2, AD LDS for Windows 7, Windows Server 2012, AD LDS for Windows 8, Windows Server 2012 R2, AD LDS for Windows 8.1, Windows Server 2016 ~~Technical Preview~~, and AD LDS for Windows 10.

2.251 Attribute nCName

This attribute specifies the distinguished name of the naming context for the object.

```
cn: NC-Name
ldapDisplayName: nCName
attributeId: 1.2.840.113556.1.2.16
attributeSyntax: 2.5.5.1
omSyntax: 127
omObjectClass: 1.3.12.2.1011.28.0.714
isSingleValued: TRUE
schemaIdGuid: bf9679d6-0de6-11d0-a285-00aa003049e2
systemOnly: TRUE
searchFlags: fPRESERVEONDELETE
systemFlags: FLAG_SCHEMA_BASE_OBJECT
```

Version-Specific Behavior: Implemented on ADAM, Windows Server 2008, AD LDS for Windows Vista, Windows Server 2008 R2, AD LDS for Windows 7, Windows Server 2012, AD LDS for Windows 8, Windows Server 2012 R2, AD LDS for Windows 8.1, Windows Server 2016 ~~Technical Preview~~, and AD LDS for Windows 10.

2.252 Attribute nETBIOSName

This attribute specifies the name of the object to be used over NetBIOS.

```
cn: NETBIOS-Name
ldapDisplayName: nETBIOSName
attributeId: 1.2.840.113556.1.4.87
attributeSyntax: 2.5.5.12
omSyntax: 64
isSingleValued: TRUE
schemaIdGuid: bf9679d8-0de6-11d0-a285-00aa003049e2
systemOnly: FALSE
searchFlags: fATTINDEX
rangeLower: 1
rangeUpper: 16
systemFlags: FLAG_SCHEMA_BASE_OBJECT
```

Version-Specific Behavior: Implemented on ADAM, Windows Server 2008, AD LDS for Windows Vista, Windows Server 2008 R2, AD LDS for Windows 7, Windows Server 2012, AD LDS for Windows 8, Windows Server 2012 R2, AD LDS for Windows 8.1, Windows Server 2016 ~~Technical Preview~~, and AD LDS for Windows 10.

2.253 Attribute networkAddress

This attribute specifies the TCP/IP address for a network segment. Also called the subnet address.

```
cn: Network-Address
ldapDisplayName: networkAddress
attributeId: 1.2.840.113556.1.2.459
```

```
attributeSyntax: 2.5.5.4
omSyntax: 20
isSingleValued: FALSE
schemaIdGuid: bf9679d9-0de6-11d0-a285-00aa003049e2
systemOnly: FALSE
searchFlags: 0
rangeLower: 0
rangeUpper: 256
```

Version-Specific Behavior: Implemented on ADAM, Windows Server 2008, AD LDS for Windows Vista, Windows Server 2008 R2, AD LDS for Windows 7, Windows Server 2012, AD LDS for Windows 8, Windows Server 2012 R2, AD LDS for Windows 8.1, Windows Server 2016 ~~Technical Preview~~, and AD LDS for Windows 10.

2.254 Attribute nonIndexedMetadata

ms-DS-Non-Indexed-Metadata

```
cn: ms-DS-Non-Indexed-Metadata
ldapDisplayName: nonIndexedMetadata
attributeId: 1.2.840.113556.1.4.1887
attributeSyntax: 2.5.5.12
omSyntax: 64
isSingleValued: FALSE
```

Version-Specific Behavior: Implemented on ADAM, Windows Server 2008, AD LDS for Windows Vista, Windows Server 2008 R2, AD LDS for Windows 7, Windows Server 2012, AD LDS for Windows 8, Windows Server 2012 R2, AD LDS for Windows 8.1, Windows Server 2016 ~~Technical Preview~~, and AD LDS for Windows 10.

2.255 Attribute notificationList

This attribute is not necessary for Active Directory to function. The protocol does not define a format beyond that required by the schema.

```
cn: Notification-List
ldapDisplayName: notificationList
attributeId: 1.2.840.113556.1.4.303
attributeSyntax: 2.5.5.1
omSyntax: 127
omObjectClass: 1.3.12.2.1011.28.0.714
isSingleValued: TRUE
schemaIdGuid: 19195a56-6da0-11d0-afd3-00c04fd930c9
systemOnly: FALSE
searchFlags: 0
systemFlags: FLAG_SCHEMA_BASE_OBJECT
```

Version-Specific Behavior: Implemented on ADAM, Windows Server 2008, AD LDS for Windows Vista, Windows Server 2008 R2, AD LDS for Windows 7, Windows Server 2012, AD LDS for Windows 8, Windows Server 2012 R2, AD LDS for Windows 8.1, Windows Server 2016 ~~Technical Preview~~, and AD LDS for Windows 10.

2.256 Attribute ntPwdHistory

This attribute specifies the password history of the user in Windows NT operating system one-way format (OWF). Windows 2000 operating system uses the Windows NT OWF.

```
cn: Nt-Pwd-History
ldapDisplayName: ntPwdHistory
attributeId: 1.2.840.113556.1.4.94
attributeSyntax: 2.5.5.10
omSyntax: 4
isSingleValued: FALSE
schemaIdGuid: bf9679e2-0de6-11d0-a285-00aa003049e2
systemOnly: FALSE
searchFlags: 0
systemFlags: FLAG_SCHEMA_BASE_OBJECT
```

Version-Specific Behavior: Implemented on ADAM, Windows Server 2008, AD LDS for Windows Vista, Windows Server 2008 R2, AD LDS for Windows 7, Windows Server 2012, AD LDS for Windows 8, Windows Server 2012 R2, AD LDS for Windows 8.1, Windows Server 2016 ~~Technical Preview~~, and AD LDS for Windows 10.

2.257 Attribute nTSecurityDescriptor

This attribute specifies the Windows NT security descriptor for an object.

```
cn: NT-Security-Descriptor
ldapDisplayName: nTSecurityDescriptor
attributeId: 1.2.840.113556.1.2.281
attributeSyntax: 2.5.5.15
omSyntax: 66
isSingleValued: TRUE
schemaIdGuid: bf9679e3-0de6-11d0-a285-00aa003049e2
systemOnly: FALSE
searchFlags: fPRESERVEONDELETE
rangeLower: 0
rangeUpper: 132096
isMemberOfPartialAttributeSet: TRUE
systemFlags: FLAG_SCHEMA_BASE_OBJECT | FLAG_ATTR_IS_OPERATIONAL |
FLAG_ATTR_REQ_PARTIAL_SET_MEMBER
```

Version-Specific Behavior: Implemented on ADAM, Windows Server 2008, AD LDS for Windows Vista, Windows Server 2008 R2, AD LDS for Windows 7, Windows Server 2012, AD LDS for Windows 8, Windows Server 2012 R2, AD LDS for Windows 8.1, Windows Server 2016 ~~Technical Preview~~, and AD LDS for Windows 10.

2.258 Attribute o

This attribute specifies the name of the company or organization.

```
cn: Organization-Name
ldapDisplayName: o
attributeId: 2.5.4.10
attributeSyntax: 2.5.5.12
omSyntax: 64
isSingleValued: FALSE
schemaIdGuid: bf9679ef-0de6-11d0-a285-00aa003049e2
systemOnly: FALSE
searchFlags: 0
rangeLower: 1
rangeUpper: 64
attributeSecurityGuid: e48d0154-bcf8-11d1-8702-00c04fb96050
isMemberOfPartialAttributeSet: TRUE
systemFlags: FLAG_SCHEMA_BASE_OBJECT |
FLAG_ATTR_REQ_PARTIAL_SET_MEMBER
```

Version-Specific Behavior: Implemented on ADAM, Windows Server 2008, AD LDS for Windows Vista, Windows Server 2008 R2, AD LDS for Windows 7, Windows Server 2012, AD LDS for Windows 8, Windows Server 2012 R2, AD LDS for Windows 8.1, Windows Server 2016 ~~Technical Preview~~, and AD LDS for Windows 10.

2.259 Attribute objectCategory

This attribute specifies an object class name used to group objects of this or derived classes.

```
cn: Object-Category
ldapDisplayName: objectCategory
attributeId: 1.2.840.113556.1.4.782
attributeSyntax: 2.5.5.1
omSyntax: 127
omObjectClass: 1.3.12.2.1011.28.0.714
isSingleValued: TRUE
schemaIdGuid: 26d97369-6070-11d1-a9c6-0000f80367c1
systemOnly: FALSE
searchFlags: fATTINDEX
attributeSecurityGuid: e48d0154-bcf8-11d1-8702-00c04fb96050
isMemberOfPartialAttributeSet: TRUE
systemFlags: FLAG_SCHEMA_BASE_OBJECT |
FLAG_ATTR_REQ_PARTIAL_SET_MEMBER
```

Version-Specific Behavior: Implemented on ADAM, Windows Server 2008, AD LDS for Windows Vista, Windows Server 2008 R2, AD LDS for Windows 7, Windows Server 2012, AD LDS for Windows 8, Windows Server 2012 R2, AD LDS for Windows 8.1, Windows Server 2016 ~~Technical Preview~~, and AD LDS for Windows 10.

2.260 Attribute objectClass

This attribute specifies the list of classes of which this object is an instance.

```
cn: Object-Class
ldapDisplayName: objectClass
attributeId: 2.5.4.0
attributeSyntax: 2.5.5.2
omSyntax: 6
isSingleValued: FALSE
schemaIdGuid: bf9679e5-0de6-11d0-a285-00aa003049e2
systemOnly: TRUE
searchFlags: fPRESERVEONDELETE | fATTINDEX
attributeSecurityGuid: e48d0154-bcf8-11d1-8702-00c04fb96050
isMemberOfPartialAttributeSet: TRUE
systemFlags: FLAG_SCHEMA_BASE_OBJECT |
FLAG_ATTR_REQ_PARTIAL_SET_MEMBER
```

Version-Specific Behavior: Implemented on ADAM, Windows Server 2008, AD LDS for Windows Vista, Windows Server 2008 R2, AD LDS for Windows 7, Windows Server 2012, AD LDS for Windows 8, Windows Server 2012 R2, AD LDS for Windows 8.1, Windows Server 2016 ~~Technical Preview~~, and AD LDS for Windows 10.

2.261 Attribute objectClassCategory

This attribute contains the class type, such as abstract, auxiliary, or structured.

```
cn: Object-Class-Category
ldapDisplayName: objectClassCategory
attributeId: 1.2.840.113556.1.2.370
```

```
attributeSyntax: 2.5.5.9
omSyntax: 10
isSingleValued: TRUE
schemaIdGuid: bf9679e6-0de6-11d0-a285-00aa003049e2
systemOnly: TRUE
searchFlags: 0
rangeLower: 0
rangeUpper: 3
systemFlags: FLAG_SCHEMA_BASE_OBJECT
```

Version-Specific Behavior: Implemented on ADAM, Windows Server 2008, AD LDS for Windows Vista, Windows Server 2008 R2, AD LDS for Windows 7, Windows Server 2012, AD LDS for Windows 8, Windows Server 2012 R2, AD LDS for Windows 8.1, Windows Server 2016 ~~Technical Preview~~, and AD LDS for Windows 10.

2.262 Attribute objectClasses

This attribute is a multivalued property containing strings that represent each class in the schema. Each value contains the governsID, LDAPDisplayName, mustContain, mayContain, and so on.

```
cn: Object-Classes
ldapDisplayName: objectClasses
attributeId: 2.5.21.6
attributeSyntax: 2.5.5.12
omSyntax: 64
isSingleValued: FALSE
schemaIdGuid: 9a7ad94b-ca53-11d1-bbd0-0080c76670c0
systemOnly: TRUE
searchFlags: 0
systemFlags: FLAG_SCHEMA_BASE_OBJECT | FLAG_ATTR_IS_CONSTRUCTED |
FLAG_DOMAIN_DISALLOW_RENAME
```

Version-Specific Behavior: Implemented on ADAM, Windows Server 2008, AD LDS for Windows Vista, Windows Server 2008 R2, AD LDS for Windows 7, Windows Server 2012, AD LDS for Windows 8, Windows Server 2012 R2, AD LDS for Windows 8.1, Windows Server 2016 ~~Technical Preview~~, and AD LDS for Windows 10.

2.263 Attribute objectGUID

This attribute specifies the unique identifier for an object.

```
cn: Object-Guid
ldapDisplayName: objectGUID
attributeId: 1.2.840.113556.1.4.2
attributeSyntax: 2.5.5.10
omSyntax: 4
isSingleValued: TRUE
schemaIdGuid: bf9679e7-0de6-11d0-a285-00aa003049e2
systemOnly: TRUE
searchFlags: fPRESERVEONDELETE | fATTINDEX
rangeLower: 16
rangeUpper: 16
attributeSecurityGuid: e48d0154-bcf8-11d1-8702-00c04fb96050
isMemberOfPartialAttributeSet: TRUE
systemFlags: FLAG_SCHEMA_BASE_OBJECT |
FLAG_ATTR_REQ_PARTIAL_SET_MEMBER | FLAG_ATTR_NOT_REPLICATED
```

Version-Specific Behavior: Implemented on ADAM, Windows Server 2008, AD LDS for Windows Vista, Windows Server 2008 R2, AD LDS for Windows 7, Windows Server 2012, AD LDS for Windows 8,

Windows Server 2012 R2, AD LDS for Windows 8.1, Windows Server 2016 ~~Technical Preview~~, and AD LDS for Windows 10.

2.264 Attribute objectSid

This attribute contains a binary value that specifies the security identifier (SID) of a security principal object. The SID is a unique value used to identify security principal objects.

```
cn: Object-Sid
ldapDisplayName: objectSid
attributeId: 1.2.840.113556.1.4.146
attributeSyntax: 2.5.5.17
omSyntax: 4
isSingleValued: TRUE
schemaIdGuid: bf9679e8-0de6-11d0-a285-00aa003049e2
systemOnly: TRUE
searchFlags: fPRESERVEONDELETE | fATTINDEX
rangeLower: 0
rangeUpper: 28
attributeSecurityGuid: 59ba2f42-79a2-11d0-9020-00c04fc2d3cf
isMemberOfPartialAttributeSet: TRUE
systemFlags: FLAG_SCHEMA_BASE_OBJECT |
  FLAG_ATTR_REQ_PARTIAL_SET_MEMBER
```

Version-Specific Behavior: Implemented on ADAM, Windows Server 2008, AD LDS for Windows Vista, Windows Server 2008 R2, AD LDS for Windows 7, Windows Server 2012, AD LDS for Windows 8, Windows Server 2012 R2, AD LDS for Windows 8.1, Windows Server 2016 ~~Technical Preview~~, and AD LDS for Windows 10.

2.265 Attribute objectVersion

This attribute can be used to store a version number for the object.

```
cn: Object-Version
ldapDisplayName: objectVersion
attributeId: 1.2.840.113556.1.2.76
attributeSyntax: 2.5.5.9
omSyntax: 2
isSingleValued: TRUE
schemaIdGuid: 16775848-47f3-11d1-a9c3-0000f80367c1
systemOnly: FALSE
searchFlags: 0
systemFlags: FLAG_SCHEMA_BASE_OBJECT
```

Version-Specific Behavior: Implemented on ADAM, Windows Server 2008, AD LDS for Windows Vista, Windows Server 2008 R2, AD LDS for Windows 7, Windows Server 2012, AD LDS for Windows 8, Windows Server 2012 R2, AD LDS for Windows 8.1, Windows Server 2016 ~~Technical Preview~~, and AD LDS for Windows 10.

2.266 Attribute oObjectClass

This attribute specifies the unique OID for the attribute or class.

```
cn: OM-Object-Class
ldapDisplayName: oObjectClass
attributeId: 1.2.840.113556.1.2.218
attributeSyntax: 2.5.5.10
omSyntax: 4
isSingleValued: TRUE
```

```
schemaIdGuid: bf9679ec-0de6-11d0-a285-00aa003049e2
systemOnly: TRUE
searchFlags: 0
systemFlags: FLAG_SCHEMA_BASE_OBJECT
```

Version-Specific Behavior: Implemented on ADAM, Windows Server 2008, AD LDS for Windows Vista, Windows Server 2008 R2, AD LDS for Windows 7, Windows Server 2012, AD LDS for Windows 8, Windows Server 2012 R2, AD LDS for Windows 8.1, Windows Server 2016 **Technical Preview**, and AD LDS for Windows 10.

2.267 Attribute oMSyntax

Used as part of specifying the syntax of an attribute. See [MS-ADTS] section 3.1.1.2.2.2, LDAP Representation, for information on how this object is used by the Active Directory service.

```
cn: OM-Syntax
ldapDisplayName: oMSyntax
attributeId: 1.2.840.113556.1.2.231
attributeSyntax: 2.5.5.9
omSyntax: 2
isSingleValued: TRUE
schemaIdGuid: bf9679ed-0de6-11d0-a285-00aa003049e2
systemOnly: TRUE
searchFlags: fPRESERVEONDELETE
systemFlags: FLAG_SCHEMA_BASE_OBJECT
```

Version-Specific Behavior: Implemented on ADAM, Windows Server 2008, AD LDS for Windows Vista, Windows Server 2008 R2, AD LDS for Windows 7, Windows Server 2012, AD LDS for Windows 8, Windows Server 2012 R2, AD LDS for Windows 8.1, Windows Server 2016 **Technical Preview**, and AD LDS for Windows 10.

2.268 Attribute options

This attribute is a bit field, where the meaning of the bits varies from objectClass to objectClass. Can occur on Inter-Site-Transport, NTDS-Connection, NTDS-DSA, NTDS-Site-Settings, and Site-Link objects.

```
cn: Options
ldapDisplayName: options
attributeId: 1.2.840.113556.1.4.307
attributeSyntax: 2.5.5.9
omSyntax: 2
isSingleValued: TRUE
schemaIdGuid: 19195a53-6da0-11d0-afd3-00c04fd930c9
systemOnly: FALSE
searchFlags: 0
systemFlags: FLAG_SCHEMA_BASE_OBJECT
```

Version-Specific Behavior: Implemented on ADAM, Windows Server 2008, AD LDS for Windows Vista, Windows Server 2008 R2, AD LDS for Windows 7, Windows Server 2012, AD LDS for Windows 8, Windows Server 2012 R2, AD LDS for Windows 8.1, Windows Server 2016 **Technical Preview**, and AD LDS for Windows 10.

2.269 Attribute otherFacsimileTelephoneNumber

This attribute specifies a list of alternate facsimile numbers.

```
cn: Phone-Fax-Other
ldapDisplayName: otherFacsimileTelephoneNumber
attributeId: 1.2.840.113556.1.4.646
attributeSyntax: 2.5.5.12
omSyntax: 64
isSingleValued: FALSE
schemaIdGuid: 0296c11d-40da-11d1-a9c0-0000f80367c1
systemOnly: FALSE
searchFlags: 0
rangeLower: 1
rangeUpper: 64
attributeSecurityGuid: 77b5b886-944a-11d1-aebd-0000f80367c1
```

Version-Specific Behavior: Implemented on ADAM, Windows Server 2008, AD LDS for Windows Vista, Windows Server 2008 R2, AD LDS for Windows 7, Windows Server 2012, AD LDS for Windows 8, Windows Server 2012 R2, AD LDS for Windows 8.1, Windows Server 2016 ~~Technical Preview~~, and AD LDS for Windows 10.

2.270 Attribute otherHomePhone

This attribute specifies a list of alternate home phone numbers.

```
cn: Phone-Home-Other
ldapDisplayName: otherHomePhone
attributeId: 1.2.840.113556.1.2.277
attributeSyntax: 2.5.5.12
omSyntax: 64
isSingleValued: FALSE
schemaIdGuid: f0f8ffa2-1191-11d0-a060-00aa006c33ed
systemOnly: FALSE
searchFlags: 0
rangeLower: 1
rangeUpper: 64
attributeSecurityGuid: 77b5b886-944a-11d1-aebd-0000f80367c1
```

Version-Specific Behavior: Implemented on ADAM, Windows Server 2008, AD LDS for Windows Vista, Windows Server 2008 R2, AD LDS for Windows 7, Windows Server 2012, AD LDS for Windows 8, Windows Server 2012 R2, AD LDS for Windows 8.1, Windows Server 2016 ~~Technical Preview~~, and AD LDS for Windows 10.

2.271 Attribute otherIpPhone

This attribute specifies the list of alternate TCP/IP addresses for the phone. Used by telephony.

```
cn: Phone-Ip-Other
ldapDisplayName: otherIpPhone
attributeId: 1.2.840.113556.1.4.722
attributeSyntax: 2.5.5.12
omSyntax: 64
isSingleValued: FALSE
schemaIdGuid: 4d146e4b-48d4-11d1-a9c3-0000f80367c1
systemOnly: FALSE
searchFlags: 0
attributeSecurityGuid: 77b5b886-944a-11d1-aebd-0000f80367c1
isMemberOfPartialAttributeSet: TRUE
```

Version-Specific Behavior: Implemented on ADAM, Windows Server 2008, AD LDS for Windows Vista, Windows Server 2008 R2, AD LDS for Windows 7, Windows Server 2012, AD LDS for Windows 8,

Windows Server 2012 R2, AD LDS for Windows 8.1, Windows Server 2016 ~~Technical Preview~~, and AD LDS for Windows 10.

2.272 Attribute otherMobile

This attribute specifies a list of alternate cell phone numbers.

```
cn: Phone-Mobile-Other
ldapDisplayName: otherMobile
attributeId: 1.2.840.113556.1.4.647
attributeSyntax: 2.5.5.12
omSyntax: 64
isSingleValued: FALSE
schemaIdGuid: 0296c11e-40da-11d1-a9c0-0000f80367c1
systemOnly: FALSE
searchFlags: 0
rangeLower: 1
rangeUpper: 64
attributeSecurityGuid: 77b5b886-944a-11d1-aebd-0000f80367c1
```

Version-Specific Behavior: Implemented on ADAM, Windows Server 2008, AD LDS for Windows Vista, Windows Server 2008 R2, AD LDS for Windows 7, Windows Server 2012, AD LDS for Windows 8, Windows Server 2012 R2, AD LDS for Windows 8.1, Windows Server 2016 ~~Technical Preview~~, and AD LDS for Windows 10.

2.273 Attribute otherPager

This attribute specifies a list of alternate pager numbers.

```
cn: Phone-Pager-Other
ldapDisplayName: otherPager
attributeId: 1.2.840.113556.1.2.118
attributeSyntax: 2.5.5.12
omSyntax: 64
isSingleValued: FALSE
schemaIdGuid: f0f8ffa4-1191-11d0-a060-00aa006c33ed
systemOnly: FALSE
searchFlags: 0
rangeLower: 1
rangeUpper: 64
attributeSecurityGuid: 77b5b886-944a-11d1-aebd-0000f80367c1
```

Version-Specific Behavior: Implemented on ADAM, Windows Server 2008, AD LDS for Windows Vista, Windows Server 2008 R2, AD LDS for Windows 7, Windows Server 2012, AD LDS for Windows 8, Windows Server 2012 R2, AD LDS for Windows 8.1, Windows Server 2016 ~~Technical Preview~~, and AD LDS for Windows 10.

2.274 Attribute otherTelephone

This attribute specifies a list of alternate office phone numbers.

```
cn: Phone-Office-Other
ldapDisplayName: otherTelephone
attributeId: 1.2.840.113556.1.2.18
attributeSyntax: 2.5.5.12
omSyntax: 64
isSingleValued: FALSE
schemaIdGuid: f0f8ffa5-1191-11d0-a060-00aa006c33ed
systemOnly: FALSE
```

```
searchFlags: 0
rangeLower: 1
rangeUpper: 64
attributeSecurityGuid: 77b5b886-944a-11d1-aebd-0000f80367c1
```

Version-Specific Behavior: Implemented on ADAM, Windows Server 2008, AD LDS for Windows Vista, Windows Server 2008 R2, AD LDS for Windows 7, Windows Server 2012, AD LDS for Windows 8, Windows Server 2012 R2, AD LDS for Windows 8.1, Windows Server 2016 **Technical Preview**, and AD LDS for Windows 10.

2.275 Attribute otherWellKnownObjects

This attribute contains a list of containers by GUID and distinguished name. This permits retrieving an object after it has been moved by using just the GUID and the domain name. Whenever the object is moved, the Active Directory system will automatically update the distinguished name.

```
cn: Other-Well-Known-Objects
ldapDisplayName: otherWellKnownObjects
attributeId: 1.2.840.113556.1.4.1359
attributeSyntax: 2.5.5.7
omSyntax: 127
omObjectClass: 1.2.840.113556.1.1.1.11
isSingleValued: FALSE
schemaIdGuid: 1ea64e5d-ac0f-11d2-90df-00c04fd91ab1
systemOnly: FALSE
searchFlags: 0
rangeLower: 16
rangeUpper: 16
systemFlags: FLAG_SCHEMA_BASE_OBJECT
```

Version-Specific Behavior: Implemented on ADAM, Windows Server 2008, AD LDS for Windows Vista, Windows Server 2008 R2, AD LDS for Windows 7, Windows Server 2012, AD LDS for Windows 8, Windows Server 2012 R2, AD LDS for Windows 8.1, Windows Server 2016 **Technical Preview**, and AD LDS for Windows 10.

2.276 Attribute ou

This attribute specifies the name of the organizational unit.

```
cn: Organizational-Unit-Name
ldapDisplayName: ou
attributeId: 2.5.4.11
attributeSyntax: 2.5.5.12
omSyntax: 64
isSingleValued: FALSE
schemaIdGuid: bf9679f0-0de6-11d0-a285-00aa003049e2
systemOnly: FALSE
searchFlags: fATTINDEX
rangeLower: 1
rangeUpper: 64
attributeSecurityGuid: e48d0154-bcf8-11d1-8702-00c04fb96050
isMemberOfPartialAttributeSet: TRUE
systemFlags: FLAG_SCHEMA_BASE_OBJECT |
FLAG_ATTR_REQ_PARTIAL_SET_MEMBER
```

Version-Specific Behavior: Implemented on ADAM, Windows Server 2008, AD LDS for Windows Vista, Windows Server 2008 R2, AD LDS for Windows 7, Windows Server 2012, AD LDS for Windows 8, Windows Server 2012 R2, AD LDS for Windows 8.1, Windows Server 2016 **Technical Preview**, and AD LDS for Windows 10.

2.277 Attribute owner

This attribute specifies the distinguished name of an object that has ownership of an object.

```
cn: Owner
ldapDisplayName: owner
attributeId: 2.5.4.32
attributeSyntax: 2.5.5.1
omSyntax: 127
omObjectClass: 1.3.12.2.1011.28.0.714
isSingleValued: TRUE
schemaIdGuid: bf9679f3-0de6-11d0-a285-00aa003049e2
systemOnly: FALSE
searchFlags: 0
linkID: 44
```

Version-Specific Behavior: Implemented on ADAM, Windows Server 2008, AD LDS for Windows Vista, Windows Server 2008 R2, AD LDS for Windows 7, Windows Server 2012, AD LDS for Windows 8, Windows Server 2012 R2, AD LDS for Windows 8.1, Windows Server 2016 ~~Technical Preview~~, and AD LDS for Windows 10.

2.278 Attribute ownerBL

This attribute specifies the backlink to the owner attribute. It contains a list of owners for an object.

```
cn: ms-Exch-Owner-BL
ldapDisplayName: ownerBL
attributeId: 1.2.840.113556.1.2.104
attributeSyntax: 2.5.5.1
omSyntax: 127
omObjectClass: 1.3.12.2.1011.28.0.714
isSingleValued: FALSE
schemaIdGuid: bf9679f4-0de6-11d0-a285-00aa003049e2
systemOnly: TRUE
searchFlags: 0
linkID: 45
systemFlags: FLAG_ATTR_NOT_REPLICATED
```

Version-Specific Behavior: Implemented on ADAM, Windows Server 2008, AD LDS for Windows Vista, Windows Server 2008 R2, AD LDS for Windows 7, Windows Server 2012, AD LDS for Windows 8, Windows Server 2012 R2, AD LDS for Windows 8.1, Windows Server 2016 ~~Technical Preview~~, and AD LDS for Windows 10.

2.279 Attribute pager

This attribute specifies the primary pager number.

```
cn: Phone-Pager-Primary
ldapDisplayName: pager
attributeId: 0.9.2342.19200300.100.1.42
attributeSyntax: 2.5.5.12
omSyntax: 64
isSingleValued: TRUE
schemaIdGuid: f0f8ffa6-1191-11d0-a060-00aa006c33ed
systemOnly: FALSE
searchFlags: 0
rangeLower: 1
rangeUpper: 64
attributeSecurityGuid: 77b5b886-944a-11d1-aebd-0000f80367c1
```

Version-Specific Behavior: Implemented on ADAM, Windows Server 2008, AD LDS for Windows Vista, Windows Server 2008 R2, AD LDS for Windows 7, Windows Server 2012, AD LDS for Windows 8, Windows Server 2012 R2, AD LDS for Windows 8.1, Windows Server 2016 ~~Technical Preview~~, and AD LDS for Windows 10.

2.280 Attribute parentGUID

This is a constructed attribute, invented to support the DirSync control. Holds the objectGuid of an object's parent when replicating an object's creation, rename, or move.

```
cn: Parent-GUID
ldapDisplayName: parentGUID
attributeId: 1.2.840.113556.1.4.1224
attributeSyntax: 2.5.5.10
omSyntax: 4
isSingleValued: TRUE
schemaIdGuid: 2df90d74-009f-11d2-aa4c-00c04fd7d83a
systemOnly: TRUE
searchFlags: 0
systemFlags: FLAG_SCHEMA_BASE_OBJECT | FLAG_ATTR_IS_CONSTRUCTED |
FLAG_DOMAIN_DISALLOW_RENAME
```

Version-Specific Behavior: Implemented on ADAM, Windows Server 2008, AD LDS for Windows Vista, Windows Server 2008 R2, AD LDS for Windows 7, Windows Server 2012, AD LDS for Windows 8, Windows Server 2012 R2, AD LDS for Windows 8.1, Windows Server 2016 ~~Technical Preview~~, and AD LDS for Windows 10.

2.281 Attribute partialAttributeDeletionList

~~This~~**This** attribute tracks the internal replication state of partial replicas (that is, on GCs). It is an attribute of the partial replica NC object, and is used when the GC is in the process of removing attributes from the objects in its partial replica NCs.

```
cn: Partial-Attribute-Deletion-List
ldapDisplayName: partialAttributeDeletionList
attributeId: 1.2.840.113556.1.4.663
attributeSyntax: 2.5.5.10
omSyntax: 4
isSingleValued: TRUE
schemaIdGuid: 28630ec0-41d5-11d1-a9c1-0000f80367c1
systemOnly: TRUE
searchFlags: 0
isMemberOfPartialAttributeSet: TRUE
systemFlags: FLAG_SCHEMA_BASE_OBJECT |
FLAG_ATTR_REQ_PARTIAL_SET_MEMBER | FLAG_ATTR_NOT_REPLICATED
```

Version-Specific Behavior: Implemented on ADAM, Windows Server 2008, AD LDS for Windows Vista, Windows Server 2008 R2, AD LDS for Windows 7, Windows Server 2012, AD LDS for Windows 8, Windows Server 2012 R2, AD LDS for Windows 8.1, Windows Server 2016 ~~Technical Preview~~, and AD LDS for Windows 10.

2.282 Attribute partialAttributeSet

This attribute tracks the internal replication state of partial replicas (that is, on GCs). It is an attribute of the partial replica NC object, and defines the set of attributes present on a particular partial replica NC.

```
cn: Partial-Attribute-Set
```

```
ldapDisplayName: partialAttributeSet
attributeId: 1.2.840.113556.1.4.640
attributeSyntax: 2.5.5.10
omSyntax: 4
isSingleValued: TRUE
schemaIdGuid: 19405b9e-3cfa-11d1-a9c0-0000f80367c1
systemOnly: TRUE
searchFlags: 0
isMemberOfPartialAttributeSet: TRUE
systemFlags: FLAG_SCHEMA_BASE_OBJECT |
FLAG_ATTR_REQ_PARTIAL_SET_MEMBER | FLAG_ATTR_NOT_REPLICATED
```

Version-Specific Behavior: Implemented on ADAM, Windows Server 2008, AD LDS for Windows Vista, Windows Server 2008 R2, AD LDS for Windows 7, Windows Server 2012, AD LDS for Windows 8, Windows Server 2012 R2, AD LDS for Windows 8.1, Windows Server 2016 ~~Technical Preview~~, and AD LDS for Windows 10.

2.283 Attribute pekList

This attribute specifies a list of password encryption keys. The attribute is used internally. It is not replicated and its content is not accessible through any protocol. For more information see [MS-ADTS] section 3.1.1.4.4 (Extended Access Checks).

```
cn: Pek-List
ldapDisplayName: pekList
attributeId: 1.2.840.113556.1.4.865
attributeSyntax: 2.5.5.10
omSyntax: 4
isSingleValued: TRUE
schemaIdGuid: 07383083-91df-11d1-aebc-0000f80367c1
systemOnly: FALSE
searchFlags: 0
systemFlags: FLAG_SCHEMA_BASE_OBJECT | FLAG_ATTR_NOT_REPLICATED
```

Version-Specific Behavior: Implemented on ADAM, Windows Server 2008, AD LDS for Windows Vista, Windows Server 2008 R2, AD LDS for Windows 7, Windows Server 2012, AD LDS for Windows 8, Windows Server 2012 R2, AD LDS for Windows 8.1, Windows Server 2016 ~~Technical Preview~~, and AD LDS for Windows 10.

2.284 Attribute personalTitle

This attribute specifies the user's title.

```
cn: Personal-Title
ldapDisplayName: personalTitle
attributeId: 1.2.840.113556.1.2.615
attributeSyntax: 2.5.5.12
omSyntax: 64
isSingleValued: TRUE
schemaIdGuid: 16775858-47f3-11d1-a9c3-0000f80367c1
systemOnly: FALSE
searchFlags: 0
rangeLower: 1
rangeUpper: 64
attributeSecurityGuid: 77b5b886-944a-11d1-aebd-0000f80367c1
```

Version-Specific Behavior: Implemented on ADAM, Windows Server 2008, AD LDS for Windows Vista, Windows Server 2008 R2, AD LDS for Windows 7, Windows Server 2012, AD LDS for Windows 8,

Windows Server 2012 R2, AD LDS for Windows 8.1, Windows Server 2016 ~~Technical Preview~~, and AD LDS for Windows 10.

2.285 Attribute photo

This attribute specifies an object encoded in G3 fax as explained in recommendation T.4, with an ASN.1 wrapper to make it compatible with an X.400 BodyPart as defined in X.420.

```
cn: photo
ldapDisplayName: photo
attributeId: 0.9.2342.19200300.100.1.7
attributeSyntax: 2.5.5.10
omSyntax: 4
isSingleValued: FALSE
schemaIdGuid: 9c979768-bala-4c08-9632-c6a5c1ed649a
systemOnly: FALSE
searchFlags: 0
showInAdvancedViewOnly: FALSE
```

Version-Specific Behavior: Implemented on ADAM, Windows Server 2008, AD LDS for Windows Vista, Windows Server 2008 R2, AD LDS for Windows 7, Windows Server 2012, AD LDS for Windows 8, Windows Server 2012 R2, AD LDS for Windows 8.1, Windows Server 2016 ~~Technical Preview~~, and AD LDS for Windows 10.

2.286 Attribute physicalDeliveryOfficeName

This attribute contains the office location in the user's place of business.

```
cn: Physical-Delivery-Office-Name
ldapDisplayName: physicalDeliveryOfficeName
attributeId: 2.5.4.19
attributeSyntax: 2.5.5.12
omSyntax: 64
isSingleValued: TRUE
schemaIdGuid: bf9679f7-0de6-11d0-a285-00aa003049e2
systemOnly: FALSE
searchFlags: fANR | fATTINDEX
rangeLower: 1
rangeUpper: 128
attributeSecurityGuid: 77b5b886-944a-11d1-aebd-0000f80367c1
systemFlags: FLAG_SCHEMA_BASE_OBJECT
```

Version-Specific Behavior: Implemented on ADAM, Windows Server 2008, AD LDS for Windows Vista, Windows Server 2008 R2, AD LDS for Windows 7, Windows Server 2012, AD LDS for Windows 8, Windows Server 2012 R2, AD LDS for Windows 8.1, Windows Server 2016 ~~Technical Preview~~, and AD LDS for Windows 10.

2.287 Attribute possibleInferiors

This attribute specifies the list of objects that this object can contain.

```
cn: Possible-Inferiors
ldapDisplayName: possibleInferiors
attributeId: 1.2.840.113556.1.4.915
attributeSyntax: 2.5.5.2
omSyntax: 6
isSingleValued: FALSE
schemaIdGuid: 9a7ad94c-ca53-11d1-bbd0-0080c76670c0
systemOnly: TRUE
```

```
searchFlags: 0
systemFlags: FLAG_SCHEMA_BASE_OBJECT | FLAG_ATTR_IS_CONSTRUCTED |
FLAG_DOMAIN_DISALLOW_RENAME
```

Version-Specific Behavior: Implemented on ADAM, Windows Server 2008, AD LDS for Windows Vista, Windows Server 2008 R2, AD LDS for Windows 7, Windows Server 2012, AD LDS for Windows 8, Windows Server 2012 R2, AD LDS for Windows 8.1, Windows Server 2016 ~~Technical Preview~~, and AD LDS for Windows 10.

2.288 Attribute `possSuperiors`

This attribute specifies the list of objects that can contain this class.

```
cn: Poss-Superiors
ldapDisplayName: possSuperiors
attributeId: 1.2.840.113556.1.2.8
attributeSyntax: 2.5.5.2
omSyntax: 6
isSingleValued: FALSE
schemaIdGuid: bf9679fa-0de6-11d0-a285-00aa003049e2
systemOnly: FALSE
searchFlags: 0
isMemberOfPartialAttributeSet: TRUE
systemFlags: FLAG_SCHEMA_BASE_OBJECT
```

Version-Specific Behavior: Implemented on ADAM, Windows Server 2008, AD LDS for Windows Vista, Windows Server 2008 R2, AD LDS for Windows 7, Windows Server 2012, AD LDS for Windows 8, Windows Server 2012 R2, AD LDS for Windows 8.1, Windows Server 2016 ~~Technical Preview~~, and AD LDS for Windows 10.

2.289 Attribute `postalAddress`

This attribute specifies the mailing address for the object.

```
cn: Postal-Address
ldapDisplayName: postalAddress
attributeId: 2.5.4.16
attributeSyntax: 2.5.5.12
omSyntax: 64
isSingleValued: FALSE
schemaIdGuid: bf9679fc-0de6-11d0-a285-00aa003049e2
systemOnly: FALSE
searchFlags: fCOPY
rangeLower: 1
rangeUpper: 4096
attributeSecurityGuid: 77b5b886-944a-11d1-aebd-0000f80367c1
systemFlags: FLAG_SCHEMA_BASE_OBJECT
```

Version-Specific Behavior: Implemented on ADAM, Windows Server 2008, AD LDS for Windows Vista, Windows Server 2008 R2, AD LDS for Windows 7, Windows Server 2012, AD LDS for Windows 8, Windows Server 2012 R2, AD LDS for Windows 8.1, Windows Server 2016 ~~Technical Preview~~, and AD LDS for Windows 10.

2.290 Attribute `postalCode`

This attribute specifies the postal or ZIP code for mail delivery.

```
cn: Postal-Code
ldapDisplayName: postalCode
attributeId: 2.5.4.17
attributeSyntax: 2.5.5.12
omSyntax: 64
isSingleValued: TRUE
schemaIdGuid: bf9679fd-0de6-11d0-a285-00aa003049e2
systemOnly: FALSE
searchFlags: fCOPY
rangeLower: 1
rangeUpper: 40
attributeSecurityGuid: 77b5b886-944a-11d1-aebd-0000f80367c1
systemFlags: FLAG_SCHEMA_BASE_OBJECT
```

Version-Specific Behavior: Implemented on ADAM, Windows Server 2008, AD LDS for Windows Vista, Windows Server 2008 R2, AD LDS for Windows 7, Windows Server 2012, AD LDS for Windows 8, Windows Server 2012 R2, AD LDS for Windows 8.1, Windows Server 2016 ~~Technical Preview~~, and AD LDS for Windows 10.

2.291 Attribute postOfficeBox

This attribute specifies the P.O. box number for this object.

```
cn: Post-Office-Box
ldapDisplayName: postOfficeBox
attributeId: 2.5.4.18
attributeSyntax: 2.5.5.12
omSyntax: 64
isSingleValued: FALSE
schemaIdGuid: bf9679fb-0de6-11d0-a285-00aa003049e2
systemOnly: FALSE
searchFlags: fCOPY
rangeLower: 1
rangeUpper: 40
attributeSecurityGuid: 77b5b886-944a-11d1-aebd-0000f80367c1
systemFlags: FLAG_SCHEMA_BASE_OBJECT
```

Version-Specific Behavior: Implemented on ADAM, Windows Server 2008, AD LDS for Windows Vista, Windows Server 2008 R2, AD LDS for Windows 7, Windows Server 2012, AD LDS for Windows 8, Windows Server 2012 R2, AD LDS for Windows 8.1, Windows Server 2016 ~~Technical Preview~~, and AD LDS for Windows 10.

2.292 Attribute preferredDeliveryMethod

This attribute specifies the X.500-preferred way [X500] to deliver to the addressee.

```
cn: Preferred-Delivery-Method
ldapDisplayName: preferredDeliveryMethod
attributeId: 2.5.4.28
attributeSyntax: 2.5.5.9
omSyntax: 10
isSingleValued: FALSE
schemaIdGuid: bf9679fe-0de6-11d0-a285-00aa003049e2
systemOnly: FALSE
searchFlags: 0
attributeSecurityGuid: 77b5b886-944a-11d1-aebd-0000f80367c1
systemFlags: FLAG_SCHEMA_BASE_OBJECT
```

Version-Specific Behavior: Implemented on ADAM, Windows Server 2008, AD LDS for Windows Vista, Windows Server 2008 R2, AD LDS for Windows 7, Windows Server 2012, AD LDS for Windows 8, Windows Server 2012 R2, AD LDS for Windows 8.1, Windows Server 2016 ~~Technical Preview~~, and AD LDS for Windows 10.

2.293 Attribute preferredLanguage

This attribute specifies the preferred written or spoken language for a person.

```
cn: preferredLanguage
ldapDisplayName: preferredLanguage
attributeId: 2.16.840.1.113730.3.1.39
attributeSyntax: 2.5.5.12
omSyntax: 64
isSingleValued: TRUE
schemaIdGuid: 856be0d0-18e7-46e1-8f5f-7ee4d9020e0d
systemOnly: FALSE
searchFlags: 0
showInAdvancedViewOnly: FALSE
```

Version-Specific Behavior: Implemented on ADAM, Windows Server 2008, AD LDS for Windows Vista, Windows Server 2008 R2, AD LDS for Windows 7, Windows Server 2012, AD LDS for Windows 8, Windows Server 2012 R2, AD LDS for Windows 8.1, Windows Server 2016 ~~Technical Preview~~, and AD LDS for Windows 10.

2.294 Attribute preferredOU

This attribute specifies the organizational unit to show by default on the user's desktop.

```
cn: Preferred-OU
ldapDisplayName: preferredOU
attributeId: 1.2.840.113556.1.4.97
attributeSyntax: 2.5.5.1
omSyntax: 127
omObjectClass: 1.3.12.2.1011.28.0.714
isSingleValued: TRUE
schemaIdGuid: bf9679ff-0de6-11d0-a285-00aa003049e2
systemOnly: FALSE
searchFlags: fCOPY
```

Version-Specific Behavior: Implemented on ADAM, Windows Server 2008, AD LDS for Windows Vista, Windows Server 2008 R2, AD LDS for Windows 7, Windows Server 2012, AD LDS for Windows 8, Windows Server 2012 R2, AD LDS for Windows 8.1, Windows Server 2016 ~~Technical Preview~~, and AD LDS for Windows 10.

2.295 Attribute prefixMap

The **Prefix-Map** attribute is for internal use only.

```
cn: Prefix-Map
ldapDisplayName: prefixMap
attributeId: 1.2.840.113556.1.4.538
attributeSyntax: 2.5.5.10
omSyntax: 4
isSingleValued: TRUE
schemaIdGuid: 52458022-ca6a-11d0-afff-0000f80367c1
systemOnly: TRUE
searchFlags: 0
```

```
systemFlags: FLAG_SCHEMA_BASE_OBJECT | FLAG_ATTR_NOT_REPLICATED
```

Version-Specific Behavior: Implemented on ADAM, Windows Server 2008, AD LDS for Windows Vista, Windows Server 2008 R2, AD LDS for Windows 7, Windows Server 2012, AD LDS for Windows 8, Windows Server 2012 R2, AD LDS for Windows 8.1, Windows Server 2016 ~~Technical Preview~~, and AD LDS for Windows 10.

2.296 Attribute primaryGroupToken

A computed attribute that is used in retrieving the membership list of a group such as Domain Users. The complete membership of such groups is not stored explicitly for scaling reasons.

```
cn: Primary-Group-Token
ldapDisplayName: primaryGroupToken
attributeId: 1.2.840.113556.1.4.1412
attributeSyntax: 2.5.5.9
omSyntax: 2
isSingleValued: TRUE
schemaIdGuid: c0ed8738-7efd-4481-84d9-66d2db8be369
systemOnly: TRUE
searchFlags: 0
systemFlags: FLAG_SCHEMA_BASE_OBJECT | FLAG_ATTR_IS_CONSTRUCTED
```

Version-Specific Behavior: Implemented on ADAM, Windows Server 2008, AD LDS for Windows Vista, Windows Server 2008 R2, AD LDS for Windows 7, Windows Server 2012, AD LDS for Windows 8, Windows Server 2012 R2, AD LDS for Windows 8.1, Windows Server 2016 ~~Technical Preview~~, and AD LDS for Windows 10.

2.297 Attribute primaryInternationalISDNNumber

This attribute specifies the primary ISDN number.

```
cn: Phone-ISDN-Primary
ldapDisplayName: primaryInternationalISDNNumber
attributeId: 1.2.840.113556.1.4.649
attributeSyntax: 2.5.5.12
omSyntax: 64
isSingleValued: TRUE
schemaIdGuid: 0296c11f-40da-11d1-a9c0-0000f80367c1
systemOnly: FALSE
searchFlags: 0
rangeLower: 1
rangeUpper: 64
attributeSecurityGuid: 77b5b886-944a-11d1-aebd-0000f80367c1
```

Version-Specific Behavior: Implemented on ADAM, Windows Server 2008, AD LDS for Windows Vista, Windows Server 2008 R2, AD LDS for Windows 7, Windows Server 2012, AD LDS for Windows 8, Windows Server 2012 R2, AD LDS for Windows 8.1, Windows Server 2016 ~~Technical Preview~~, and AD LDS for Windows 10.

2.298 Attribute primaryTelexNumber

This attribute specifies the primary telex number.

```
cn: Telex-Primary
ldapDisplayName: primaryTelexNumber
attributeId: 1.2.840.113556.1.4.648
```

```
attributeSyntax: 2.5.5.12
omSyntax: 64
isSingleValued: TRUE
schemaIdGuid: 0296c121-40da-11d1-a9c0-0000f80367c1
systemOnly: FALSE
searchFlags: 0
rangeLower: 1
rangeUpper: 64
attributeSecurityGuid: 77b5b886-944a-11d1-aebd-0000f80367c1
```

Version-Specific Behavior: Implemented on ADAM, Windows Server 2008, AD LDS for Windows Vista, Windows Server 2008 R2, AD LDS for Windows 7, Windows Server 2012, AD LDS for Windows 8, Windows Server 2012 R2, AD LDS for Windows 8.1, Windows Server 2016 ~~Technical Preview~~, and AD LDS for Windows 10.

2.299 Attribute proxiedObjectName

This attribute is used internally by Active Directory to help track interdomain moves.

```
cn: Proxied-Object-Name
ldapDisplayName: proxiedObjectName
attributeId: 1.2.840.113556.1.4.1249
attributeSyntax: 2.5.5.7
omSyntax: 127
omObjectClass: 1.2.840.113556.1.1.1.11
isSingleValued: TRUE
schemaIdGuid: e1aea402-cd5b-11d0-afff-0000f80367c1
systemOnly: TRUE
searchFlags: 0
isMemberOfPartialAttributeSet: TRUE
systemFlags: FLAG_SCHEMA_BASE_OBJECT |
FLAG_ATTR_REQ_PARTIAL_SET_MEMBER
```

Version-Specific Behavior: Implemented on ADAM, Windows Server 2008, AD LDS for Windows Vista, Windows Server 2008 R2, AD LDS for Windows 7, Windows Server 2012, AD LDS for Windows 8, Windows Server 2012 R2, AD LDS for Windows 8.1, Windows Server 2016 ~~Technical Preview~~, and AD LDS for Windows 10.

2.300 Attribute proxyAddresses

This attribute specifies proxy addresses. A proxy address is the address by which ~~an~~ Microsoft Exchange Server recipient object is recognized in a foreign mail system. Proxy addresses are required for all recipient objects, such as custom recipients and distribution lists.

```
cn: Proxy-Addresses
ldapDisplayName: proxyAddresses
attributeId: 1.2.840.113556.1.2.210
attributeSyntax: 2.5.5.12
omSyntax: 64
isSingleValued: FALSE
schemaIdGuid: bf967a06-0de6-11d0-a285-00aa003049e2
systemOnly: FALSE
searchFlags: fANR | fATTINDEX
rangeLower: 1
rangeUpper: 1123
attributeSecurityGuid: e48d0154-bcf8-11d1-8702-00c04fb96050
systemFlags: FLAG_SCHEMA_BASE_OBJECT
```

Version-Specific Behavior: Implemented on ADAM, Windows Server 2008, AD LDS for Windows Vista, Windows Server 2008 R2, AD LDS for Windows 7, Windows Server 2012, AD LDS for Windows 8,

Windows Server 2012 R2, AD LDS for Windows 8.1, Windows Server 2016 ~~Technical Preview~~, and AD LDS for Windows 10.

2.301 Attribute pwdLastSet

This attribute specifies the date and time that the password for this account was last changed. This value is stored as a large integer that represents the number of 100-nanosecond intervals since January 1, 1601 (UTC).

```
cn: Pwd-Last-Set
ldapDisplayName: pwdLastSet
attributeId: 1.2.840.113556.1.4.96
attributeSyntax: 2.5.5.16
omSyntax: 65
isSingleValued: TRUE
schemaIdGuid: bf967a0a-0de6-11d0-a285-00aa003049e2
systemOnly: FALSE
searchFlags: 0
attributeSecurityGuid: 4c164200-20c0-11d0-a768-00aa006e0529
systemFlags: FLAG_SCHEMA_BASE_OBJECT
```

Version-Specific Behavior: Implemented on ADAM, Windows Server 2008, AD LDS for Windows Vista, Windows Server 2008 R2, AD LDS for Windows 7, Windows Server 2012, AD LDS for Windows 8, Windows Server 2012 R2, AD LDS for Windows 8.1, Windows Server 2016 ~~Technical Preview~~, and AD LDS for Windows 10.

2.302 Attribute queryFilter

Query-Filter attribute.

```
cn: Query-Filter
ldapDisplayName: queryFilter
attributeId: 1.2.840.113556.1.4.1355
attributeSyntax: 2.5.5.12
omSyntax: 64
isSingleValued: TRUE
schemaIdGuid: cbf70a26-7e78-11d2-9921-0000f87a57d4
systemOnly: FALSE
```

Version-Specific Behavior: Implemented on Windows Server 2008, AD LDS for Windows Vista, Windows Server 2008 R2, AD LDS for Windows 7, Windows Server 2012, AD LDS for Windows 8, Windows Server 2012 R2, AD LDS for Windows 8.1, Windows Server 2016 ~~Technical Preview~~, and AD LDS for Windows 10.

2.303 Attribute queryPolicyBL

This attribute is the back link attribute of queryPolicy and lists all objects holding references to a given Query-Policy.

```
cn: Query-Policy-BL
ldapDisplayName: queryPolicyBL
attributeId: 1.2.840.113556.1.4.608
attributeSyntax: 2.5.5.1
omSyntax: 127
omObjectClass: 1.3.12.2.1011.28.0.714
isSingleValued: FALSE
schemaIdGuid: e1aea404-cd5b-11d0-afff-0000f80367c1
systemOnly: TRUE
```

```
searchFlags: 0
linkID: 69
systemFlags: FLAG_SCHEMA_BASE_OBJECT | FLAG_ATTR_NOT_REPLICATED
```

Version-Specific Behavior: Implemented on ADAM, Windows Server 2008, AD LDS for Windows Vista, Windows Server 2008 R2, AD LDS for Windows 7, Windows Server 2012, AD LDS for Windows 8, Windows Server 2012 R2, AD LDS for Windows 8.1, Windows Server 2016 ~~Technical Preview~~, and AD LDS for Windows 10.

2.304 Attribute queryPolicyObject

This attribute contains a reference to the default Query-Policy in force for this server.

```
cn: Query-Policy-Object
ldapDisplayName: queryPolicyObject
attributeId: 1.2.840.113556.1.4.607
attributeSyntax: 2.5.5.1
omSyntax: 127
omObjectClass: 1.3.12.2.1011.28.0.714
isSingleValued: TRUE
schemaIdGuid: e1aea403-cd5b-11d0-afff-0000f80367c1
systemOnly: FALSE
searchFlags: 0
linkID: 68
systemFlags: FLAG_SCHEMA_BASE_OBJECT
```

Version-Specific Behavior: Implemented on ADAM, Windows Server 2008, AD LDS for Windows Vista, Windows Server 2008 R2, AD LDS for Windows 7, Windows Server 2012, AD LDS for Windows 8, Windows Server 2012 R2, AD LDS for Windows 8.1, Windows Server 2016 ~~Technical Preview~~, and AD LDS for Windows 10.

2.305 Attribute rangeLower

This attribute specifies the minimum value or length of an attribute.

```
cn: Range-Lower
ldapDisplayName: rangeLower
attributeId: 1.2.840.113556.1.2.34
attributeSyntax: 2.5.5.9
omSyntax: 2
isSingleValued: TRUE
schemaIdGuid: bf967a0c-0de6-11d0-a285-00aa003049e2
systemOnly: FALSE
searchFlags: 0
isMemberOfPartialAttributeSet: TRUE
systemFlags: FLAG_SCHEMA_BASE_OBJECT
```

Version-Specific Behavior: Implemented on ADAM, Windows Server 2008, AD LDS for Windows Vista, Windows Server 2008 R2, AD LDS for Windows 7, Windows Server 2012, AD LDS for Windows 8, Windows Server 2012 R2, AD LDS for Windows 8.1, Windows Server 2016 ~~Technical Preview~~, and AD LDS for Windows 10.

2.306 Attribute rangeUpper

This attribute specifies the maximum value or length of an attribute.

```
cn: Range-Upper
```



```
ldapDisplayName: rangeUpper
attributeId: 1.2.840.113556.1.2.35
attributeSyntax: 2.5.5.9
omSyntax: 2
isSingleValued: TRUE
schemaIdGuid: bf967a0d-0de6-11d0-a285-00aa003049e2
systemOnly: FALSE
searchFlags: 0
isMemberOfPartialAttributeSet: TRUE
systemFlags: FLAG_SCHEMA_BASE_OBJECT
```

Version-Specific Behavior: Implemented on ADAM, Windows Server 2008, AD LDS for Windows Vista, Windows Server 2008 R2, AD LDS for Windows 7, Windows Server 2012, AD LDS for Windows 8, Windows Server 2012 R2, AD LDS for Windows 8.1, Windows Server 2016 ~~Technical Preview~~, and AD LDS for Windows 10.

2.307 Attribute rDNAttID

This attribute specifies the RDN for the attribute that is used to name a class.

```
cn: RDN-Att-ID
ldapDisplayName: rDNAttID
attributeId: 1.2.840.113556.1.2.26
attributeSyntax: 2.5.5.2
omSyntax: 6
isSingleValued: TRUE
schemaIdGuid: bf967a0f-0de6-11d0-a285-00aa003049e2
systemOnly: TRUE
searchFlags: 0
systemFlags: FLAG_SCHEMA_BASE_OBJECT
```

Version-Specific Behavior: Implemented on ADAM, Windows Server 2008, AD LDS for Windows Vista, Windows Server 2008 R2, AD LDS for Windows 7, Windows Server 2012, AD LDS for Windows 8, Windows Server 2012 R2, AD LDS for Windows 8.1, Windows Server 2016 ~~Technical Preview~~, and AD LDS for Windows 10.

2.308 Attribute registeredAddress

This attribute specifies a mnemonic for an address associated with an object at a particular city location. The mnemonic is registered in the country/region in which the city is located and is used in the provision of the Public Telegram Service.

```
cn: Registered-Address
ldapDisplayName: registeredAddress
attributeId: 2.5.4.26
attributeSyntax: 2.5.5.10
omSyntax: 4
isSingleValued: FALSE
schemaIdGuid: bf967a10-0de6-11d0-a285-00aa003049e2
systemOnly: FALSE
searchFlags: 0
rangeLower: 1
rangeUpper: 4096
attributeSecurityGuid: 77b5b886-944a-11d1-aebd-0000f80367c1
```

Version-Specific Behavior: Implemented on ADAM, Windows Server 2008, AD LDS for Windows Vista, Windows Server 2008 R2, AD LDS for Windows 7, Windows Server 2012, AD LDS for Windows 8, Windows Server 2012 R2, AD LDS for Windows 8.1, Windows Server 2016 ~~Technical Preview~~, and AD LDS for Windows 10.

2.309 Attribute replInterval

The attribute of Site-Link objects that defines the interval in minutes between replication cycles between the sites in the Site-List. It **must** be a multiple of 15 minutes (the granularity of cross-site DS replication), a minimum of 15 minutes, and a maximum of 10,080 minutes (one week).

```
cn: Repl-Interval
ldapDisplayName: replInterval
attributeId: 1.2.840.113556.1.4.1336
attributeSyntax: 2.5.5.9
omSyntax: 2
isSingleValued: TRUE
schemaIdGuid: 45ba9d1a-56fa-11d2-90d0-00c04fd91ab1
systemOnly: FALSE
searchFlags: 0
systemFlags: FLAG_SCHEMA_BASE_OBJECT
```

Version-Specific Behavior: Implemented on ADAM, Windows Server 2008, AD LDS for Windows Vista, Windows Server 2008 R2, AD LDS for Windows 7, Windows Server 2012, AD LDS for Windows 8, Windows Server 2012 R2, AD LDS for Windows 8.1, Windows Server 2016 ~~Technical Preview~~, and AD LDS for Windows 10.

2.310 Attribute replPropertyMetaData

This attribute tracks internal replication state information for DS objects. Information here can be extracted in public form through the public DsReplicaGetInfo() API. This attribute is present on all DS objects.

```
cn: Repl-Property-Meta-Data
ldapDisplayName: replPropertyMetaData
attributeId: 1.2.840.113556.1.4.3
attributeSyntax: 2.5.5.10
omSyntax: 4
isSingleValued: TRUE
schemaIdGuid: 281416c0-1968-11d0-a28f-00aa003049e2
systemOnly: TRUE
searchFlags: fPRESERVEONDELETE
isMemberOfPartialAttributeSet: TRUE
systemFlags: FLAG_SCHEMA_BASE_OBJECT | FLAG_ATTR_IS_OPERATIONAL |
FLAG_ATTR_REQ_PARTIAL_SET_MEMBER | FLAG_ATTR_NOT_REPLICATED
```

Version-Specific Behavior: Implemented on ADAM, Windows Server 2008, AD LDS for Windows Vista, Windows Server 2008 R2, AD LDS for Windows 7, Windows Server 2012, AD LDS for Windows 8, Windows Server 2012 R2, AD LDS for Windows 8.1, Windows Server 2016 ~~Technical Preview~~, and AD LDS for Windows 10.

2.311 Attribute replTopologyStayOfExecution

This attribute specifies the delay between deleting a server object and permanently removing it from the replication topology.

```
cn: Repl-Topology-Stay-Of-Execution
ldapDisplayName: replTopologyStayOfExecution
attributeId: 1.2.840.113556.1.4.677
attributeSyntax: 2.5.5.9
omSyntax: 2
isSingleValued: TRUE
schemaIdGuid: 7bfdcb83-4807-11d1-a9c3-0000f80367c1
systemOnly: FALSE
```

```
searchFlags: 0
systemFlags: FLAG_SCHEMA_BASE_OBJECT
```

Version-Specific Behavior: Implemented on ADAM, Windows Server 2008, AD LDS for Windows Vista, Windows Server 2008 R2, AD LDS for Windows 7, Windows Server 2012, AD LDS for Windows 8, Windows Server 2012 R2, AD LDS for Windows 8.1, Windows Server 2016 ~~Technical Preview~~, and AD LDS for Windows 10.

2.312 Attribute replUpToDateVector

This attribute tracks internal replication state information for an entire NC. Information here can be extracted in public form through the DsReplicaGetInfo() API. Present on all NC root objects.

```
cn: Repl-UpToDate-Vector
ldapDisplayName: replUpToDateVector
attributeId: 1.2.840.113556.1.4.4
attributeSyntax: 2.5.5.10
omSyntax: 4
isSingleValued: TRUE
schemaIdGuid: bf967a16-0de6-11d0-a285-00aa003049e2
systemOnly: TRUE
searchFlags: 0
isMemberOfPartialAttributeSet: TRUE
systemFlags: FLAG_SCHEMA_BASE_OBJECT |
FLAG_ATTR_REQ_PARTIAL_SET_MEMBER | FLAG_ATTR_NOT_REPLICATED
```

Version-Specific Behavior: Implemented on ADAM, Windows Server 2008, AD LDS for Windows Vista, Windows Server 2008 R2, AD LDS for Windows 7, Windows Server 2012, AD LDS for Windows 8, Windows Server 2012 R2, AD LDS for Windows 8.1, Windows Server 2016 ~~Technical Preview~~, and AD LDS for Windows 10.

2.313 Attribute repsFrom

This attribute lists the servers from which the directory will accept changes for the defined naming context (NC).

```
cn: Reps-From
ldapDisplayName: repsFrom
attributeId: 1.2.840.113556.1.2.91
attributeSyntax: 2.5.5.10
omSyntax: 127
omObjectClass: 1.2.840.113556.1.1.1.6
isSingleValued: FALSE
schemaIdGuid: bf967a1d-0de6-11d0-a285-00aa003049e2
systemOnly: TRUE
searchFlags: 0
isMemberOfPartialAttributeSet: TRUE
systemFlags: FLAG_SCHEMA_BASE_OBJECT |
FLAG_ATTR_REQ_PARTIAL_SET_MEMBER | FLAG_ATTR_NOT_REPLICATED
```

Version-Specific Behavior: Implemented on ADAM, Windows Server 2008, AD LDS for Windows Vista, Windows Server 2008 R2, AD LDS for Windows 7, Windows Server 2012, AD LDS for Windows 8, Windows Server 2012 R2, AD LDS for Windows 8.1, Windows Server 2016 ~~Technical Preview~~, and AD LDS for Windows 10.

2.314 Attribute repsTo

This attribute lists the servers that the directory will notify of changes and the servers that the directory will send changes to, upon request for the defined NC.

```
cn: Reps-To
ldapDisplayName: repsTo
attributeId: 1.2.840.113556.1.2.83
attributeSyntax: 2.5.5.10
omSyntax: 127
omObjectClass: 1.2.840.113556.1.1.1.6
isSingleValued: FALSE
schemaIdGuid: bf967a1e-0de6-11d0-a285-00aa003049e2
systemOnly: TRUE
searchFlags: 0
isMemberOfPartialAttributeSet: TRUE
systemFlags: FLAG_SCHEMA_BASE_OBJECT |
  FLAG_ATTR_REQ_PARTIAL_SET_MEMBER | FLAG_ATTR_NOT_REPLICATED
```

Version-Specific Behavior: Implemented on ADAM, Windows Server 2008, AD LDS for Windows Vista, Windows Server 2008 R2, AD LDS for Windows 7, Windows Server 2012, AD LDS for Windows 8, Windows Server 2012 R2, AD LDS for Windows 8.1, Windows Server 2016 ~~Technical Preview~~, and AD LDS for Windows 10.

2.315 Attribute retiredReplDSASignatures

This attribute tracks the past DS replication identities of a given DC.

```
cn: Retired-Repl-DSA-Signatures
ldapDisplayName: retiredReplDSASignatures
attributeId: 1.2.840.113556.1.4.673
attributeSyntax: 2.5.5.10
omSyntax: 4
isSingleValued: TRUE
schemaIdGuid: 7bfdcb7f-4807-11d1-a9c3-0000f80367c1
systemOnly: TRUE
searchFlags: 0
systemFlags: FLAG_SCHEMA_BASE_OBJECT
```

Version-Specific Behavior: Implemented on ADAM, Windows Server 2008, AD LDS for Windows Vista, Windows Server 2008 R2, AD LDS for Windows 7, Windows Server 2012, AD LDS for Windows 8, Windows Server 2012 R2, AD LDS for Windows 8.1, Windows Server 2016 ~~Technical Preview~~, and AD LDS for Windows 10.

2.316 Attribute revision

This attribute specifies the revision level for a security descriptor or other change. Only used in the sam-server and ds-ui-settings objects.

```
cn: Revision
ldapDisplayName: revision
attributeId: 1.2.840.113556.1.4.145
attributeSyntax: 2.5.5.9
omSyntax: 2
isSingleValued: TRUE
schemaIdGuid: bf967a21-0de6-11d0-a285-00aa003049e2
systemOnly: FALSE
searchFlags: 0
systemFlags: FLAG_SCHEMA_BASE_OBJECT
```

Version-Specific Behavior: Implemented on ADAM, Windows Server 2008, AD LDS for Windows Vista, Windows Server 2008 R2, AD LDS for Windows 7, Windows Server 2012, AD LDS for Windows 8, Windows Server 2012 R2, AD LDS for Windows 8.1, Windows Server 2016 ~~Technical Preview~~, and AD LDS for Windows 10.

2.317 Attribute rightsGuid

This attribute specifies the GUID that is used to represent an extended right within an access control entry.

```
cn: Rights-Guid
ldapDisplayName: rightsGuid
attributeId: 1.2.840.113556.1.4.340
attributeSyntax: 2.5.5.12
omSyntax: 64
isSingleValued: TRUE
schemaIdGuid: 8297931c-86d3-11d0-afda-00c04fd930c9
systemOnly: FALSE
searchFlags: 0
rangeLower: 36
rangeUpper: 36
systemFlags: FLAG_SCHEMA_BASE_OBJECT
```

Version-Specific Behavior: Implemented on ADAM, Windows Server 2008, AD LDS for Windows Vista, Windows Server 2008 R2, AD LDS for Windows 7, Windows Server 2012, AD LDS for Windows 8, Windows Server 2012 R2, AD LDS for Windows 8.1, Windows Server 2016 ~~Technical Preview~~, and AD LDS for Windows 10.

2.318 Attribute roomNumber

This attribute specifies the room number of an object.

```
cn: roomNumber
ldapDisplayName: roomNumber
attributeId: 0.9.2342.19200300.100.1.6
attributeSyntax: 2.5.5.12
omSyntax: 64
isSingleValued: FALSE
schemaIdGuid: 81d7f8c2-e327-4a0d-91c6-b42d4009115f
systemOnly: FALSE
searchFlags: 0
showInAdvancedViewOnly: FALSE
```

Version-Specific Behavior: Implemented on ADAM, Windows Server 2008, AD LDS for Windows Vista, Windows Server 2008 R2, AD LDS for Windows 7, Windows Server 2012, AD LDS for Windows 8, Windows Server 2012 R2, AD LDS for Windows 8.1, Windows Server 2016 ~~Technical Preview~~, and AD LDS for Windows 10.

2.319 Attribute rootTrust

This attribute specifies the distinguished name of another Cross-Ref.

```
cn: Root-Trust
ldapDisplayName: rootTrust
attributeId: 1.2.840.113556.1.4.674
attributeSyntax: 2.5.5.1
omSyntax: 127
omObjectClass: 1.3.12.2.1011.28.0.714
```

```
isSingleValued: FALSE
schemaIdGuid: 7bfdcb80-4807-11d1-a9c3-0000f80367c1
systemOnly: FALSE
searchFlags: 0
systemFlags: FLAG_SCHEMA_BASE_OBJECT
```

Version-Specific Behavior: Implemented on ADAM, Windows Server 2008, AD LDS for Windows Vista, Windows Server 2008 R2, AD LDS for Windows 7, Windows Server 2012, AD LDS for Windows 8, Windows Server 2012 R2, AD LDS for Windows 8.1, Windows Server 2016 ~~Technical Preview~~, and AD LDS for Windows 10.

2.320 Attribute schedule

This attribute specifies a schedule BLOB as defined by the NT Job Service. Used by replication.

```
cn: Schedule
ldapDisplayName: schedule
attributeId: 1.2.840.113556.1.4.211
attributeSyntax: 2.5.5.10
omSyntax: 4
isSingleValued: TRUE
schemaIdGuid: dd712224-10e4-11d0-a05f-00aa006c33ed
systemOnly: FALSE
searchFlags: 0
systemFlags: FLAG_SCHEMA_BASE_OBJECT
```

Version-Specific Behavior: Implemented on ADAM, Windows Server 2008, AD LDS for Windows Vista, Windows Server 2008 R2, AD LDS for Windows 7, Windows Server 2012, AD LDS for Windows 8, Windows Server 2012 R2, AD LDS for Windows 8.1, Windows Server 2016 ~~Technical Preview~~, and AD LDS for Windows 10.

2.321 Attribute schemaFlagsEx

This attribute specifies an integer value that contains flags that define additional properties of the attribute, as shown below. See [MS-ADTS] for more information. This is an optional attribute.

The schemaFlagsEx attribute contains bitwise flags. The following value is relevant to schema objects:

- **FLAG_ATTR_IS_CRITICAL**: Specifies that the attribute is not a member of the filtered attribute set even if the `fRODCFilteredAttribute` ([MS-ADTS] section 3.1.1.2.3.5) is set.

This attribute is defined as follows:

```
cn: Schema-Flags-Ex
ldapDisplayName: schemaFlagsEx
attributeId: 1.2.840.113556.1.4.120
attributeSyntax: 2.5.5.9
omSyntax: 2
isSingleValued: TRUE
schemaIdGuid: bf967a2b-0de6-11d0-a285-00aa003049e2
systemOnly: FALSE
searchFlags: 0
systemFlags: FLAG_SCHEMA_BASE_OBJECT
```

Version-Specific Behavior: Implemented on ADAM, Windows Server 2008, AD LDS for Windows Vista, Windows Server 2008 R2, AD LDS for Windows 7, Windows Server 2012, AD LDS for Windows 8, Windows Server 2012 R2, AD LDS for Windows 8.1, Windows Server 2016 ~~Technical Preview~~, and AD LDS for Windows 10.

The schemaFlagsEx attribute was added to this attribute definition in Windows Server 2008.

The FLAG_ATTR_IS_CRITICAL value was implemented in Windows Server 2008.

2.322 Attribute schemaIDGUID

This attribute specifies the unique identifier for a schema object.

```
cn: Schema-ID-GUID
ldapDisplayName: schemaIDGUID
attributeId: 1.2.840.113556.1.4.148
attributeSyntax: 2.5.5.10
omSyntax: 4
isSingleValued: TRUE
schemaIdGuid: bf967923-0de6-11d0-a285-00aa003049e2
systemOnly: TRUE
searchFlags: 0
rangeLower: 16
rangeUpper: 16
systemFlags: FLAG_SCHEMA_BASE_OBJECT
```

Version-Specific Behavior: Implemented on ADAM, Windows Server 2008, AD LDS for Windows Vista, Windows Server 2008 R2, AD LDS for Windows 7, Windows Server 2012, AD LDS for Windows 8, Windows Server 2012 R2, AD LDS for Windows 8.1, Windows Server 2016 ~~Technical Preview~~, and AD LDS for Windows 10.

2.323 Attribute schemaInfo

This attribute specifies an internal binary value used to detect schema changes between DCs and force a schema NC replication cycle before replicating any other NC. Used to resolve ties when the schema FSMO is seized and a change is made on more than one DC.

```
cn: Schema-Info
ldapDisplayName: schemaInfo
attributeId: 1.2.840.113556.1.4.1358
attributeSyntax: 2.5.5.10
omSyntax: 4
isSingleValued: FALSE
schemaIdGuid: f9fb64ae-93b4-11d2-9945-0000f87a57d4
systemOnly: TRUE
searchFlags: 0
systemFlags: FLAG_SCHEMA_BASE_OBJECT
```

Version-Specific Behavior: Implemented on ADAM, Windows Server 2008, AD LDS for Windows Vista, Windows Server 2008 R2, AD LDS for Windows 7, Windows Server 2012, AD LDS for Windows 8, Windows Server 2012 R2, AD LDS for Windows 8.1, Windows Server 2016 ~~Technical Preview~~, and AD LDS for Windows 10.

2.324 Attribute schemaUpdate

```
cn: Schema-Update
ldapDisplayName: schemaUpdate
attributeId: 1.2.840.113556.1.4.481
attributeSyntax: 2.5.5.11
omSyntax: 24
isSingleValued: TRUE
schemaIdGuid: 1e2d06b4-ac8f-11d0-afe3-00c04fd930c9
systemOnly: FALSE
searchFlags: 0
```

```
systemFlags: FLAG_SCHEMA_BASE_OBJECT | FLAG_ATTR_NOT_REPLICATED
```

Version-Specific Behavior: Implemented on ADAM, Windows Server 2008, AD LDS for Windows Vista, Windows Server 2008 R2, AD LDS for Windows 7, Windows Server 2012, AD LDS for Windows 8, Windows Server 2012 R2, AD LDS for Windows 8.1, Windows Server 2016 ~~Technical Preview~~, and AD LDS for Windows 10.

2.325 Attribute schemaVersion

This attribute specifies the version number for the schema.

```
cn: Schema-Version
ldapDisplayName: schemaVersion
attributeId: 1.2.840.113556.1.2.471
attributeSyntax: 2.5.5.9
omSyntax: 2
isSingleValued: FALSE
schemaIdGuid: bf967a2c-0de6-11d0-a285-00aa003049e2
systemOnly: FALSE
searchFlags: 0
systemFlags: FLAG_SCHEMA_BASE_OBJECT
```

Version-Specific Behavior: Implemented on ADAM, Windows Server 2008, AD LDS for Windows Vista, Windows Server 2008 R2, AD LDS for Windows 7, Windows Server 2012, AD LDS for Windows 8, Windows Server 2012 R2, AD LDS for Windows 8.1, Windows Server 2016 ~~Technical Preview~~, and AD LDS for Windows 10.

2.326 Attribute scopeFlags

```
cn: Scope-Flags
ldapDisplayName: scopeFlags
attributeId: 1.2.840.113556.1.4.1354
attributeSyntax: 2.5.5.9
omSyntax: 2
isSingleValued: TRUE
schemaIdGuid: 16f3a4c2-7e79-11d2-9921-0000f87a57d4
systemOnly: FALSE
```

Version-Specific Behavior: Implemented on Windows Server 2008, AD LDS for Windows Vista, Windows Server 2008 R2, AD LDS for Windows 7, Windows Server 2012, AD LDS for Windows 8, Windows Server 2012 R2, AD LDS for Windows 8.1, Windows Server 2016 ~~Technical Preview~~, and AD LDS for Windows 10.

2.327 Attribute sDRightsEffective

This constructed attribute returns a single DWORD value that can have up to three bits set: OWNER_SECURITY_INFORMATION, DACL_SECURITY_INFORMATION, and SACL_SECURITY_INFORMATION. If a bit is set, then the user has write access to the corresponding part of the security descriptor.

Note "Owner" means both owner and group.

```
cn: SD-Rights-Effective
ldapDisplayName: sDRightsEffective
attributeId: 1.2.840.113556.1.4.1304
attributeSyntax: 2.5.5.9
omSyntax: 2
isSingleValued: TRUE
```



```
schemaIdGuid: c3dbafa6-33df-11d2-98b2-0000f87a57d4
systemOnly: FALSE
searchFlags: 0
attributeSecurityGuid: 59ba2f42-79a2-11d0-9020-00c04fc2d3cf
systemFlags: FLAG_SCHEMA_BASE_OBJECT | FLAG_ATTR_IS_CONSTRUCTED |
FLAG_DOMAIN_DISALLOW_RENAME
```

Version-Specific Behavior: Implemented on ADAM, Windows Server 2008, AD LDS for Windows Vista, Windows Server 2008 R2, AD LDS for Windows 7, Windows Server 2012, AD LDS for Windows 8, Windows Server 2012 R2, AD LDS for Windows 8.1, Windows Server 2016 ~~Technical Preview~~, and AD LDS for Windows 10.

2.328 Attribute searchFlags

This attribute contains a set of flags that specify search and indexing information for an attribute.

```
cn: Search-Flags
ldapDisplayName: searchFlags
attributeId: 1.2.840.113556.1.2.334
attributeSyntax: 2.5.5.9
omSyntax: 10
isSingleValued: TRUE
schemaIdGuid: bf967a2d-0de6-11d0-a285-00aa003049e2
systemOnly: FALSE
searchFlags: 0
rangeLower: 0
systemFlags: FLAG_SCHEMA_BASE_OBJECT
```

Version-Specific Behavior: Implemented on ADAM, Windows Server 2008, AD LDS for Windows Vista, Windows Server 2008 R2, AD LDS for Windows 7, Windows Server 2012, AD LDS for Windows 8, Windows Server 2012 R2, AD LDS for Windows 8.1, Windows Server 2016 ~~Technical Preview~~, and AD LDS for Windows 10.

2.329 Attribute searchGuide

This attribute specifies information of suggested search criteria that ~~may~~ might be included in some entries that are expected to be a convenient base object for the search operation; for example, country/region or organization.

```
cn: Search-Guide
ldapDisplayName: searchGuide
attributeId: 2.5.4.14
attributeSyntax: 2.5.5.10
omSyntax: 4
isSingleValued: FALSE
schemaIdGuid: bf967a2e-0de6-11d0-a285-00aa003049e2
systemOnly: FALSE
searchFlags: 0
systemFlags: FLAG_SCHEMA_BASE_OBJECT
```

Version-Specific Behavior: Implemented on ADAM, Windows Server 2008, AD LDS for Windows Vista, Windows Server 2008 R2, AD LDS for Windows 7, Windows Server 2012, AD LDS for Windows 8, Windows Server 2012 R2, AD LDS for Windows 8.1, Windows Server 2016 ~~Technical Preview~~, and AD LDS for Windows 10.

2.330 Attribute secretary

This attribute contains the distinguished name of the secretary for an account.

```
cn: secretary
ldapDisplayName: secretary
attributeId: 0.9.2342.19200300.100.1.21
attributeSyntax: 2.5.5.1
omSyntax: 127
omObjectClass: 1.3.12.2.1011.28.0.714
isSingleValued: FALSE
schemaIdGuid: 01072d9a-98ad-4a53-9744-e83e287278fb
systemOnly: FALSE
searchFlags: 0
showInAdvancedViewOnly: FALSE
```

Version-Specific Behavior: Implemented on ADAM, Windows Server 2008, AD LDS for Windows Vista, Windows Server 2008 R2, AD LDS for Windows 7, Windows Server 2012, AD LDS for Windows 8, Windows Server 2012 R2, AD LDS for Windows 8.1, Windows Server 2016 ~~Technical Preview~~, and AD LDS for Windows 10.

2.331 Attribute seeAlso

This attribute specifies the list of DNs related to an object.

```
cn: See-Also
ldapDisplayName: seeAlso
attributeId: 2.5.4.34
attributeSyntax: 2.5.5.1
omSyntax: 127
omObjectClass: 1.3.12.2.1011.28.0.714
isSingleValued: FALSE
schemaIdGuid: bf967a31-0de6-11d0-a285-00aa003049e2
systemOnly: FALSE
searchFlags: 0
systemFlags: FLAG_SCHEMA_BASE_OBJECT
```

Version-Specific Behavior: Implemented on ADAM, Windows Server 2008, AD LDS for Windows Vista, Windows Server 2008 R2, AD LDS for Windows 7, Windows Server 2012, AD LDS for Windows 8, Windows Server 2012 R2, AD LDS for Windows 8.1, Windows Server 2016 ~~Technical Preview~~, and AD LDS for Windows 10.

2.332 Attribute serialNumber

This attribute is part of the X.500 specification [X500].

```
cn: Serial-Number
ldapDisplayName: serialNumber
attributeId: 2.5.4.5
attributeSyntax: 2.5.5.5
omSyntax: 19
isSingleValued: FALSE
schemaIdGuid: bf967a32-0de6-11d0-a285-00aa003049e2
systemOnly: FALSE
searchFlags: 0
rangeLower: 1
rangeUpper: 64
```

Version-Specific Behavior: Implemented on ADAM, Windows Server 2008, AD LDS for Windows Vista, Windows Server 2008 R2, AD LDS for Windows 7, Windows Server 2012, AD LDS for Windows 8, Windows Server 2012 R2, AD LDS for Windows 8.1, Windows Server 2016 ~~Technical Preview~~, and AD LDS for Windows 10.

2.333 Attribute serverReference

This attribute specifies a site computer object. The attribute is not necessary for Active Directory Lightweight Directory Services to function. The protocol does not define a format beyond that required by the schema.

```
cn: Server-Reference
ldapDisplayName: serverReference
attributeId: 1.2.840.113556.1.4.515
attributeSyntax: 2.5.5.1
omSyntax: 127
omObjectClass: 1.3.12.2.1011.28.0.714
isSingleValued: TRUE
schemaIdGuid: 26d9736d-6070-11d1-a9c6-0000f80367c1
systemOnly: FALSE
searchFlags: 0
linkID: 94
showInAdvancedViewOnly: TRUE
systemFlags: FLAG_SCHEMA_BASE_OBJECT
```

Version-Specific Behavior: Implemented on ADAM, Windows Server 2008, AD LDS for Windows Vista, Windows Server 2008 R2, AD LDS for Windows 7, Windows Server 2012, AD LDS for Windows 8, Windows Server 2012 R2, AD LDS for Windows 8.1, Windows Server 2016 ~~Technical Preview~~, and AD LDS for Windows 10.

2.334 Attribute serverReferenceBL

This attribute is the backlink attribute of serverReference, and it contains the DN of a server object under the sites folder. This attribute is not necessary for Active Directory Lightweight Directory Services to function. The protocol does not define a format beyond that required by the schema.

```
cn: Server-Reference-BL
ldapDisplayName: serverReferenceBL
attributeId: 1.2.840.113556.1.4.516
attributeSyntax: 2.5.5.1
omSyntax: 127
omObjectClass: 1.3.12.2.1011.28.0.714
isSingleValued: FALSE
schemaIdGuid: 26d9736e-6070-11d1-a9c6-0000f80367c1
systemOnly: TRUE
searchFlags: 0
linkID: 95
systemFlags: FLAG_SCHEMA_BASE_OBJECT | FLAG_ATTR_NOT_REPLICATED
```

Version-Specific Behavior: Implemented on ADAM, Windows Server 2008, AD LDS for Windows Vista, Windows Server 2008 R2, AD LDS for Windows 7, Windows Server 2012, AD LDS for Windows 8, Windows Server 2012 R2, AD LDS for Windows 8.1, Windows Server 2016 ~~Technical Preview~~, and AD LDS for Windows 10.

2.335 Attribute shellContextMenu

This attribute specifies the order number and GUID of the context menu for this object.

```
cn: Shell-Context-Menu
ldapDisplayName: shellContextMenu
attributeId: 1.2.840.113556.1.4.615
attributeSyntax: 2.5.5.12
omSyntax: 64
isSingleValued: FALSE
```

```
schemaIdGuid: 553fd039-f32e-11d0-b0bc-00c04fd8dca6
systemOnly: FALSE
```

Version-Specific Behavior: Implemented on Windows Server 2008, AD LDS for Windows Vista, Windows Server 2008 R2, AD LDS for Windows 7, Windows Server 2012, AD LDS for Windows 8, Windows Server 2012 R2, AD LDS for Windows 8.1, Windows Server 2016 ~~Technical Preview~~, and AD LDS for Windows 10.

2.336 Attribute shellPropertyPages

This attribute specifies the order number and GUID of property pages for managing Active Directory objects. These property pages can be accessed from the Windows shell. For more information, see the document "Extending the User Interface for Directory Objects" [MSDN-ExtUserIntDirObj].

```
cn: Shell-Property-Pages
ldapDisplayName: shellPropertyPages
attributeId: 1.2.840.113556.1.4.563
attributeSyntax: 2.5.5.12
omSyntax: 64
isSingleValued: FALSE
schemaIdGuid: 52458039-ca6a-11d0-afff-0000f80367c1
systemOnly: FALSE
```

Version-Specific Behavior: Implemented on Windows Server 2008, AD LDS for Windows Vista, Windows Server 2008 R2, AD LDS for Windows 7, Windows Server 2012, AD LDS for Windows 8, Windows Server 2012 R2, AD LDS for Windows 8.1, Windows Server 2016 ~~Technical Preview~~, and AD LDS for Windows 10.

2.337 Attribute showInAdvancedViewOnly

This attribute is TRUE if the corresponding attribute is to be visible in the advanced mode of the UI.

```
cn: Show-In-Advanced-View-Only
ldapDisplayName: showInAdvancedViewOnly
attributeId: 1.2.840.113556.1.2.169
attributeSyntax: 2.5.5.8
omSyntax: 1
isSingleValued: TRUE
schemaIdGuid: bf967984-0de6-11d0-a285-00aa003049e2
systemOnly: FALSE
searchFlags: fCOPY | fATTINDEX
attributeSecurityGuid: 59ba2f42-79a2-11d0-9020-00c04fc2d3cf
systemFlags: FLAG_SCHEMA_BASE_OBJECT
```

Version-Specific Behavior: Implemented on ADAM, Windows Server 2008, AD LDS for Windows Vista, Windows Server 2008 R2, AD LDS for Windows 7, Windows Server 2012, AD LDS for Windows 8, Windows Server 2012 R2, AD LDS for Windows 8.1, Windows Server 2016 ~~Technical Preview~~, and AD LDS for Windows 10.

2.338 Attribute siteLinkList

This attribute specifies a list of site links that are associated with this bridge.

```
cn: Site-Link-List
ldapDisplayName: siteLinkList
attributeId: 1.2.840.113556.1.4.822
attributeSyntax: 2.5.5.1
```

```
omSyntax: 127
omObjectClass: 1.3.12.2.1011.28.0.714
isSingleValued: FALSE
schemaIdGuid: d50c2cdd-8951-11d1-aebc-0000f80367c1
systemOnly: FALSE
searchFlags: 0
linkID: 142
systemFlags: FLAG_SCHEMA_BASE_OBJECT
```

Version-Specific Behavior: Implemented on ADAM, Windows Server 2008, AD LDS for Windows Vista, Windows Server 2008 R2, AD LDS for Windows 7, Windows Server 2012, AD LDS for Windows 8, Windows Server 2012 R2, AD LDS for Windows 8.1, Windows Server 2016 ~~Technical Preview~~, and AD LDS for Windows 10.

2.339 Attribute siteList

This attribute specifies a list of sites that are connected to this link object.

```
cn: Site-List
ldapDisplayName: siteList
attributeId: 1.2.840.113556.1.4.821
attributeSyntax: 2.5.5.1
omSyntax: 127
omObjectClass: 1.3.12.2.1011.28.0.714
isSingleValued: FALSE
schemaIdGuid: d50c2cdc-8951-11d1-aebc-0000f80367c1
systemOnly: FALSE
searchFlags: 0
linkID: 144
systemFlags: FLAG_SCHEMA_BASE_OBJECT
```

Version-Specific Behavior: Implemented on ADAM, Windows Server 2008, AD LDS for Windows Vista, Windows Server 2008 R2, AD LDS for Windows 7, Windows Server 2012, AD LDS for Windows 8, Windows Server 2012 R2, AD LDS for Windows 8.1, Windows Server 2016 ~~Technical Preview~~, and AD LDS for Windows 10.

2.340 Attribute siteObject

This attribute specifies the DN for the site to which this subnet belongs.

```
cn: Site-Object
ldapDisplayName: siteObject
attributeId: 1.2.840.113556.1.4.512
attributeSyntax: 2.5.5.1
omSyntax: 127
omObjectClass: 1.3.12.2.1011.28.0.714
isSingleValued: TRUE
schemaIdGuid: 3e10944c-c354-11d0-aff8-0000f80367c1
systemOnly: FALSE
searchFlags: 0
linkID: 46
systemFlags: FLAG_SCHEMA_BASE_OBJECT
```

Version-Specific Behavior: Implemented on ADAM, Windows Server 2008, AD LDS for Windows Vista, Windows Server 2008 R2, AD LDS for Windows 7, Windows Server 2012, AD LDS for Windows 8, Windows Server 2012 R2, AD LDS for Windows 8.1, Windows Server 2016 ~~Technical Preview~~, and AD LDS for Windows 10.

2.341 Attribute siteObjectBL

This attribute is the backlink attribute of siteObject and contains the list of subnet objects that belong to a site.

```
cn: Site-Object-BL
ldapDisplayName: siteObjectBL
attributeId: 1.2.840.113556.1.4.513
attributeSyntax: 2.5.5.1
omSyntax: 127
omObjectClass: 1.3.12.2.1011.28.0.714
isSingleValued: FALSE
schemaIdGuid: 3e10944d-c354-11d0-aff8-0000f80367c1
systemOnly: TRUE
searchFlags: 0
linkID: 47
systemFlags: FLAG_SCHEMA_BASE_OBJECT | FLAG_ATTR_NOT_REPLICATED
```

Version-Specific Behavior: Implemented on ADAM, Windows Server 2008, AD LDS for Windows Vista, Windows Server 2008 R2, AD LDS for Windows 7, Windows Server 2012, AD LDS for Windows 8, Windows Server 2012 R2, AD LDS for Windows 8.1, Windows Server 2016 ~~Technical Preview~~, and AD LDS for Windows 10.

2.342 Attribute siteServer

This attribute specifies the licensing master server for a given site.

```
cn: Site-Server
ldapDisplayName: siteServer
attributeId: 1.2.840.113556.1.4.494
attributeSyntax: 2.5.5.1
omSyntax: 127
omObjectClass: 1.3.12.2.1011.28.0.714
isSingleValued: FALSE
schemaIdGuid: 1be8f17c-a9ff-11d0-afe2-00c04fd930c9
systemOnly: FALSE
searchFlags: 0
systemFlags: FLAG_SCHEMA_BASE_OBJECT
```

Version-Specific Behavior: Implemented on ADAM, Windows Server 2008, AD LDS for Windows Vista, Windows Server 2008 R2, AD LDS for Windows 7, Windows Server 2012, AD LDS for Windows 8, Windows Server 2012 R2, AD LDS for Windows 8.1, Windows Server 2016 ~~Technical Preview~~, and AD LDS for Windows 10.

2.343 Attribute sn

This attribute contains the family or last name for a user.

```
cn: Surname
ldapDisplayName: sn
attributeId: 2.5.4.4
attributeSyntax: 2.5.5.12
omSyntax: 64
isSingleValued: TRUE
schemaIdGuid: bf967a41-0de6-11d0-a285-00aa003049e2
systemOnly: FALSE
searchFlags: fANR | fATTINDEX
rangeLower: 1
rangeUpper: 64
attributeSecurityGuid: e48d0154-bcf8-11d1-8702-00c04fb96050
```

```
isMemberOfPartialAttributeSet: TRUE
```

Version-Specific Behavior: Implemented on ADAM, Windows Server 2008, AD LDS for Windows Vista, Windows Server 2008 R2, AD LDS for Windows 7, Windows Server 2012, AD LDS for Windows 8, Windows Server 2012 R2, AD LDS for Windows 8.1, Windows Server 2016 ~~Technical Preview~~, and AD LDS for Windows 10.

2.344 Attribute sourceObjectGuid

ms-DS-Source-Object-Guid

```
cn: ms-DS-Source-Object-Guid
ldapDisplayName: sourceObjectGuid
attributeId: 1.2.840.113556.1.4.1885
attributeSyntax: 2.5.5.10
omSyntax: 4
isSingleValued: FALSE
searchFlags: fATTINDEX
```

Version-Specific Behavior: Implemented on ADAM, Windows Server 2008, AD LDS for Windows Vista, Windows Server 2008 R2, AD LDS for Windows 7, Windows Server 2012, AD LDS for Windows 8, Windows Server 2012 R2, AD LDS for Windows 8.1, Windows Server 2016 ~~Technical Preview~~, and AD LDS for Windows 10.

2.345 Attribute st

This attribute specifies the name of a user's state or province.

```
cn: State-Or-Province-Name
ldapDisplayName: st
attributeId: 2.5.4.8
attributeSyntax: 2.5.5.12
omSyntax: 64
isSingleValued: TRUE
schemaIdGuid: bf967a39-0de6-11d0-a285-00aa003049e2
systemOnly: FALSE
searchFlags: fCOPY
rangeLower: 1
rangeUpper: 128
attributeSecurityGuid: 77b5b886-944a-11d1-aebd-0000f80367c1
isMemberOfPartialAttributeSet: TRUE
systemFlags: FLAG_SCHEMA_BASE_OBJECT |
FLAG_ATTR_REQ_PARTIAL_SET_MEMBER
```

Version-Specific Behavior: Implemented on ADAM, Windows Server 2008, AD LDS for Windows Vista, Windows Server 2008 R2, AD LDS for Windows 7, Windows Server 2012, AD LDS for Windows 8, Windows Server 2012 R2, AD LDS for Windows 8.1, Windows Server 2016 ~~Technical Preview~~, and AD LDS for Windows 10.

2.346 Attribute street

This attribute specifies the user's street address.

```
cn: Street-Address
ldapDisplayName: street
attributeId: 2.5.4.9
attributeSyntax: 2.5.5.12
```

```
omSyntax: 64
isSingleValued: TRUE
schemaIdGuid: bf967a3a-0de6-11d0-a285-00aa003049e2
systemOnly: FALSE
searchFlags: fCOPY
rangeLower: 1
rangeUpper: 1024
attributeSecurityGuid: 77b5b886-944a-11d1-aebd-0000f80367c1
isMemberOfPartialAttributeSet: TRUE
systemFlags: FLAG_SCHEMA_BASE_OBJECT |
FLAG_ATTR_REQ_PARTIAL_SET_MEMBER
```

Version-Specific Behavior: Implemented on ADAM, Windows Server 2008, AD LDS for Windows Vista, Windows Server 2008 R2, AD LDS for Windows 7, Windows Server 2012, AD LDS for Windows 8, Windows Server 2012 R2, AD LDS for Windows 8.1, Windows Server 2016 **Technical Preview**, and AD LDS for Windows 10.

2.347 Attribute streetAddress

This attribute specifies the user's address.

```
cn: Address
ldapDisplayName: streetAddress
attributeId: 1.2.840.113556.1.2.256
attributeSyntax: 2.5.5.12
omSyntax: 64
isSingleValued: TRUE
schemaIdGuid: f0f8ff84-1191-11d0-a060-00aa006c33ed
systemOnly: FALSE
searchFlags: 0
rangeLower: 1
rangeUpper: 1024
attributeSecurityGuid: 77b5b886-944a-11d1-aebd-0000f80367c1
```

Version-Specific Behavior: Implemented on ADAM, Windows Server 2008, AD LDS for Windows Vista, Windows Server 2008 R2, AD LDS for Windows 7, Windows Server 2012, AD LDS for Windows 8, Windows Server 2012 R2, AD LDS for Windows 8.1, Windows Server 2016 **Technical Preview**, and AD LDS for Windows 10.

2.348 Attribute structuralObjectClass

This constructed attribute stores a list of classes contained in a class hierarchy, including abstract classes. This list contains dynamically linked auxiliary classes.

```
cn: Structural-Object-Class
ldapDisplayName: structuralObjectClass
attributeId: 2.5.21.9
attributeSyntax: 2.5.5.2
omSyntax: 6
isSingleValued: FALSE
schemaIdGuid: 3860949f-f6a8-4b38-9950-81ecb6bc2982
systemOnly: FALSE
searchFlags: 0
systemFlags: FLAG_SCHEMA_BASE_OBJECT | FLAG_ATTR_IS_CONSTRUCTED
```

Version-Specific Behavior: Implemented on ADAM, Windows Server 2008, AD LDS for Windows Vista, Windows Server 2008 R2, AD LDS for Windows 7, Windows Server 2012, AD LDS for Windows 8, Windows Server 2012 R2, AD LDS for Windows 8.1, Windows Server 2016 **Technical Preview**, and AD LDS for Windows 10.

2.349 Attribute subClassOf

This attribute specifies the parent class of a class.

```
cn: Sub-Class-Of
ldapDisplayName: subClassOf
attributeId: 1.2.840.113556.1.2.21
attributeSyntax: 2.5.5.2
omSyntax: 6
isSingleValued: TRUE
schemaIdGuid: bf967a3b-0de6-11d0-a285-00aa003049e2
systemOnly: TRUE
searchFlags: fPRESERVEONDELETE
systemFlags: FLAG_SCHEMA_BASE_OBJECT
```

Version-Specific Behavior: Implemented on ADAM, Windows Server 2008, AD LDS for Windows Vista, Windows Server 2008 R2, AD LDS for Windows 7, Windows Server 2012, AD LDS for Windows 8, Windows Server 2012 R2, AD LDS for Windows 8.1, Windows Server 2016 ~~Technical Preview~~, and AD LDS for Windows 10.

2.350 Attribute subRefs

This attribute specifies a list of subordinate references of a naming context.

```
cn: Sub-Refs
ldapDisplayName: subRefs
attributeId: 1.2.840.113556.1.2.7
attributeSyntax: 2.5.5.1
omSyntax: 127
omObjectClass: 1.3.12.2.1011.28.0.714
isSingleValued: FALSE
schemaIdGuid: bf967a3c-0de6-11d0-a285-00aa003049e2
systemOnly: TRUE
searchFlags: 0
isMemberOfPartialAttributeSet: TRUE
systemFlags: FLAG_SCHEMA_BASE_OBJECT |
FLAG_ATTR_REQ_PARTIAL_SET_MEMBER | FLAG_ATTR_NOT_REPLICATED
```

Version-Specific Behavior: Implemented on ADAM, Windows Server 2008, AD LDS for Windows Vista, Windows Server 2008 R2, AD LDS for Windows 7, Windows Server 2012, AD LDS for Windows 8, Windows Server 2012 R2, AD LDS for Windows 8.1, Windows Server 2016 ~~Technical Preview~~, and AD LDS for Windows 10.

2.351 Attribute subSchemaSubEntry

This attribute specifies the DN for the location of the subschema object where a class or attribute is defined.

```
cn: SubSchemaSubEntry
ldapDisplayName: subSchemaSubEntry
attributeId: 2.5.18.10
attributeSyntax: 2.5.5.1
omSyntax: 127
omObjectClass: 1.3.12.2.1011.28.0.714
isSingleValued: FALSE
schemaIdGuid: 9a7ad94d-ca53-11d1-bbd0-0080c76670c0
systemOnly: TRUE
searchFlags: 0
systemFlags: FLAG_SCHEMA_BASE_OBJECT | FLAG_ATTR_IS_CONSTRUCTED |
```

Version-Specific Behavior: Implemented on ADAM, Windows Server 2008, AD LDS for Windows Vista, Windows Server 2008 R2, AD LDS for Windows 7, Windows Server 2012, AD LDS for Windows 8, Windows Server 2012 R2, AD LDS for Windows 8.1, Windows Server 2016 ~~Technical Preview~~, and AD LDS for Windows 10.

2.352 Attribute superiorDNSRoot

This system attribute is used for referrals generation.

```
cn: Superior-DNS-Root
ldapDisplayName: superiorDNSRoot
attributeId: 1.2.840.113556.1.4.532
attributeSyntax: 2.5.5.12
omSyntax: 64
isSingleValued: TRUE
schemaIdGuid: 5245801d-ca6a-11d0-afff-0000f80367c1
systemOnly: FALSE
searchFlags: 0
systemFlags: FLAG_SCHEMA_BASE_OBJECT
```

Version-Specific Behavior: Implemented on ADAM, Windows Server 2008, AD LDS for Windows Vista, Windows Server 2008 R2, AD LDS for Windows 7, Windows Server 2012, AD LDS for Windows 8, Windows Server 2012 R2, AD LDS for Windows 8.1, Windows Server 2016 ~~Technical Preview~~, and AD LDS for Windows 10.

2.353 Attribute supplementalCredentials

This attribute specifies stored credentials for use in authenticating. It provides the encrypted version of the user's password. This attribute is neither readable nor writable.

```
cn: Supplemental-Credentials
ldapDisplayName: supplementalCredentials
attributeId: 1.2.840.113556.1.4.125
attributeSyntax: 2.5.5.10
omSyntax: 4
isSingleValued: FALSE
schemaIdGuid: bf967a3f-0de6-11d0-a285-00aa003049e2
systemOnly: FALSE
searchFlags: 0
systemFlags: FLAG_SCHEMA_BASE_OBJECT
```

Version-Specific Behavior: Implemented on ADAM, Windows Server 2008, AD LDS for Windows Vista, Windows Server 2008 R2, AD LDS for Windows 7, Windows Server 2012, AD LDS for Windows 8, Windows Server 2012 R2, AD LDS for Windows 8.1, Windows Server 2016 ~~Technical Preview~~, and AD LDS for Windows 10.

2.354 Attribute systemAuxiliaryClass

This attribute specifies a list of auxiliary classes that cannot be modified by the user.

```
cn: System-Auxiliary-Class
ldapDisplayName: systemAuxiliaryClass
attributeId: 1.2.840.113556.1.4.198
attributeSyntax: 2.5.5.2
omSyntax: 6
```

```
isSingleValued: FALSE
schemaIdGuid: bf967a43-0de6-11d0-a285-00aa003049e2
systemOnly: TRUE
searchFlags: 0
systemFlags: FLAG_SCHEMA_BASE_OBJECT
```

Version-Specific Behavior: Implemented on ADAM, Windows Server 2008, AD LDS for Windows Vista, Windows Server 2008 R2, AD LDS for Windows 7, Windows Server 2012, AD LDS for Windows 8, Windows Server 2012 R2, AD LDS for Windows 8.1, Windows Server 2016 ~~Technical Preview~~, and AD LDS for Windows 10.

2.355 Attribute systemFlags

This attribute specifies an integer value that contains flags that define additional properties of the class.

```
cn: System-Flags
ldapDisplayName: systemFlags
attributeId: 1.2.840.113556.1.4.375
attributeSyntax: 2.5.5.9
omSyntax: 2
isSingleValued: TRUE
schemaIdGuid: e0fale62-9b45-11d0-afdd-00c04fd930c9
systemOnly: TRUE
searchFlags: fPRESERVEONDELETE
attributeSecurityGuid: e48d0154-bcf8-11d1-8702-00c04fb96050
systemFlags: FLAG_SCHEMA_BASE_OBJECT
```

Version-Specific Behavior: Implemented on ADAM, Windows Server 2008, AD LDS for Windows Vista, Windows Server 2008 R2, AD LDS for Windows 7, Windows Server 2012, AD LDS for Windows 8, Windows Server 2012 R2, AD LDS for Windows 8.1, Windows Server 2016 ~~Technical Preview~~, and AD LDS for Windows 10.

2.356 Attribute systemMayContain

This attribute specifies the list of optional attributes for a class. The list of attributes can only be modified by the Active Directory system [MS-ADOD].

```
cn: System-May-Contain
ldapDisplayName: systemMayContain
attributeId: 1.2.840.113556.1.4.196
attributeSyntax: 2.5.5.2
omSyntax: 6
isSingleValued: FALSE
schemaIdGuid: bf967a44-0de6-11d0-a285-00aa003049e2
systemOnly: TRUE
searchFlags: 0
systemFlags: FLAG_SCHEMA_BASE_OBJECT
```

Version-Specific Behavior: Implemented on ADAM, Windows Server 2008, AD LDS for Windows Vista, Windows Server 2008 R2, AD LDS for Windows 7, Windows Server 2012, AD LDS for Windows 8, Windows Server 2012 R2, AD LDS for Windows 8.1, Windows Server 2016 ~~Technical Preview~~, and AD LDS for Windows 10.

2.357 Attribute systemMustContain

This attribute specifies the list of mandatory attributes for a class. These attributes **must have to** be specified when an instance of the class is created. The list of attributes can be modified only by the Active Directory system.

```
cn: System-Must-Contain
ldapDisplayName: systemMustContain
attributeId: 1.2.840.113556.1.4.197
attributeSyntax: 2.5.5.2
omSyntax: 6
isSingleValued: FALSE
schemaIdGuid: bf967a45-0de6-11d0-a285-00aa003049e2
systemOnly: TRUE
searchFlags: 0
systemFlags: FLAG_SCHEMA_BASE_OBJECT
```

Version-Specific Behavior: Implemented on ADAM, Windows Server 2008, AD LDS for Windows Vista, Windows Server 2008 R2, AD LDS for Windows 7, Windows Server 2012, AD LDS for Windows 8, Windows Server 2012 R2, AD LDS for Windows 8.1, Windows Server 2016 **Technical Preview**, and AD LDS for Windows 10.

2.358 Attribute systemOnly

This attribute is a Boolean value that specifies whether only Active Directory can modify the class. System-only classes can be created or deleted only by the directory system agent.

```
cn: System-Only
ldapDisplayName: systemOnly
attributeId: 1.2.840.113556.1.4.170
attributeSyntax: 2.5.5.8
omSyntax: 1
isSingleValued: TRUE
schemaIdGuid: bf967a46-0de6-11d0-a285-00aa003049e2
systemOnly: TRUE
searchFlags: 0
systemFlags: FLAG_SCHEMA_BASE_OBJECT
```

Version-Specific Behavior: Implemented on ADAM, Windows Server 2008, AD LDS for Windows Vista, Windows Server 2008 R2, AD LDS for Windows 7, Windows Server 2012, AD LDS for Windows 8, Windows Server 2012 R2, AD LDS for Windows 8.1, Windows Server 2016 **Technical Preview**, and AD LDS for Windows 10.

2.359 Attribute systemPossSuperiors

This attribute specifies the list of classes that can contain this class. This list can only be modified by the Active Directory system.

```
cn: System-Poss-Superiors
ldapDisplayName: systemPossSuperiors
attributeId: 1.2.840.113556.1.4.195
attributeSyntax: 2.5.5.2
omSyntax: 6
isSingleValued: FALSE
schemaIdGuid: bf967a47-0de6-11d0-a285-00aa003049e2
systemOnly: TRUE
searchFlags: 0
isMemberOfPartialAttributeSet: TRUE
systemFlags: FLAG_SCHEMA_BASE_OBJECT |
```

Version-Specific Behavior: Implemented on ADAM, Windows Server 2008, AD LDS for Windows Vista, Windows Server 2008 R2, AD LDS for Windows 7, Windows Server 2012, AD LDS for Windows 8, Windows Server 2012 R2, AD LDS for Windows 8.1, Windows Server 2016 ~~Technical Preview~~, and AD LDS for Windows 10.

2.360 Attribute telephoneNumber

This attribute specifies the primary telephone number.

```
cn: Telephone-Number
ldapDisplayName: telephoneNumber
attributeId: 2.5.4.20
attributeSyntax: 2.5.5.12
omSyntax: 64
isSingleValued: TRUE
schemaIdGuid: bf967a49-0de6-11d0-a285-00aa003049e2
systemOnly: FALSE
searchFlags: 0
rangeLower: 1
rangeUpper: 64
attributeSecurityGuid: 77b5b886-944a-11d1-aebd-0000f80367c1
isMemberOfPartialAttributeSet: TRUE
systemFlags: FLAG_SCHEMA_BASE_OBJECT
```

Version-Specific Behavior: Implemented on ADAM, Windows Server 2008, AD LDS for Windows Vista, Windows Server 2008 R2, AD LDS for Windows 7, Windows Server 2012, AD LDS for Windows 8, Windows Server 2012 R2, AD LDS for Windows 8.1, Windows Server 2016 ~~Technical Preview~~, and AD LDS for Windows 10.

2.361 Attribute teletexTerminalIdentifier

This attribute specifies the Teletex terminal identifier, and optionally parameters, for a Teletex terminal associated with an object.

```
cn: Teletex-Terminal-Identifier
ldapDisplayName: teletexTerminalIdentifier
attributeId: 2.5.4.22
attributeSyntax: 2.5.5.10
omSyntax: 4
isSingleValued: FALSE
schemaIdGuid: bf967a4a-0de6-11d0-a285-00aa003049e2
systemOnly: FALSE
searchFlags: 0
attributeSecurityGuid: 77b5b886-944a-11d1-aebd-0000f80367c1
systemFlags: FLAG_SCHEMA_BASE_OBJECT
```

Version-Specific Behavior: Implemented on ADAM, Windows Server 2008, AD LDS for Windows Vista, Windows Server 2008 R2, AD LDS for Windows 7, Windows Server 2012, AD LDS for Windows 8, Windows Server 2012 R2, AD LDS for Windows 8.1, Windows Server 2016 ~~Technical Preview~~, and AD LDS for Windows 10.

2.362 Attribute telexNumber

This attribute specifies a list of alternate telex numbers.

```
cn: Telex-Number
ldapDisplayName: telexNumber
attributeId: 2.5.4.21
attributeSyntax: 2.5.5.10
omSyntax: 4
isSingleValued: FALSE
schemaIdGuid: bf967a4b-0de6-11d0-a285-00aa003049e2
systemOnly: FALSE
searchFlags: 0
rangeLower: 1
rangeUpper: 32
attributeSecurityGuid: 77b5b886-944a-11d1-aebd-0000f80367c1
systemFlags: FLAG_SCHEMA_BASE_OBJECT
```

Version-Specific Behavior: Implemented on ADAM, Windows Server 2008, AD LDS for Windows Vista, Windows Server 2008 R2, AD LDS for Windows 7, Windows Server 2012, AD LDS for Windows 8, Windows Server 2012 R2, AD LDS for Windows 8.1, Windows Server 2016 ~~Technical Preview~~, and AD LDS for Windows 10.

2.363 Attribute thumbnailLogo

This attribute specifies a BLOB containing a logo for this object.

```
cn: Logo
ldapDisplayName: thumbnailLogo
attributeId: 2.16.840.1.113730.3.1.36
attributeSyntax: 2.5.5.10
omSyntax: 4
isSingleValued: TRUE
schemaIdGuid: bf9679a9-0de6-11d0-a285-00aa003049e2
systemOnly: FALSE
searchFlags: 0
rangeLower: 1
rangeUpper: 32767
systemFlags: FLAG_SCHEMA_BASE_OBJECT
```

Version-Specific Behavior: Implemented on ADAM, Windows Server 2008, AD LDS for Windows Vista, Windows Server 2008 R2, AD LDS for Windows 7, Windows Server 2012, AD LDS for Windows 8, Windows Server 2012 R2, AD LDS for Windows 8.1, Windows Server 2016 ~~Technical Preview~~, and AD LDS for Windows 10.

2.364 Attribute thumbnailPhoto

Picture

```
cn: Picture
ldapDisplayName: thumbnailPhoto
attributeId: 2.16.840.1.113730.3.1.35
attributeSyntax: 2.5.5.10
omSyntax: 4
isSingleValued: TRUE
schemaIdGuid: 8d3bca50-1d7e-11d0-a081-00aa006c33ed
systemOnly: FALSE
searchFlags: 0
rangeLower: 0
rangeUpper: 102400
attributeSecurityGuid: 77b5b886-944a-11d1-aebd-0000f80367c1
```

Version-Specific Behavior: Implemented on ADAM, Windows Server 2008, AD LDS for Windows Vista, Windows Server 2008 R2, AD LDS for Windows 7, Windows Server 2012, AD LDS for Windows 8, Windows Server 2012 R2, AD LDS for Windows 8.1, Windows Server 2016 ~~Technical Preview~~, and AD LDS for Windows 10.

2.365 Attribute title

This attribute contains the user's job title. This property is commonly used to indicate the formal job title, such as Senior Programmer, rather than occupational class, such as programmer. It is not typically used for suffix titles such as "Esq." or "DDS".

```
cn: Title
ldapDisplayName: title
attributeId: 2.5.4.12
attributeSyntax: 2.5.5.12
omSyntax: 64
isSingleValued: TRUE
schemaIdGuid: bf967a55-0de6-11d0-a285-00aa003049e2
systemOnly: FALSE
searchFlags: 0
rangeLower: 1
rangeUpper: 64
attributeSecurityGuid: e48d0154-bcf8-11d1-8702-00c04fb96050
```

Version-Specific Behavior: Implemented on ADAM, Windows Server 2008, AD LDS for Windows Vista, Windows Server 2008 R2, AD LDS for Windows 7, Windows Server 2012, AD LDS for Windows 8, Windows Server 2012 R2, AD LDS for Windows 8.1, Windows Server 2016 ~~Technical Preview~~, and AD LDS for Windows 10.

2.366 Attribute tokenGroups

This computed attribute contains the list of SIDs due to a transitive group membership expansion operation on a given user or computer. Token groups cannot be retrieved if no global catalog is present to retrieve the transitive reverse memberships.

```
cn: Token-Groups
ldapDisplayName: tokenGroups
attributeId: 1.2.840.113556.1.4.1301
attributeSyntax: 2.5.5.17
omSyntax: 4
isSingleValued: FALSE
schemaIdGuid: b7c69e6d-2cc7-11d2-854e-00a0c983f608
systemOnly: FALSE
searchFlags: 0
attributeSecurityGuid: 037088f8-0ae1-11d2-b422-00a0c968f939
systemFlags: FLAG_SCHEMA_BASE_OBJECT | FLAG_ATTR_IS_CONSTRUCTED |
FLAG_DOMAIN_DISALLOW_RENAME
```

Version-Specific Behavior: Implemented on ADAM, Windows Server 2008, AD LDS for Windows Vista, Windows Server 2008 R2, AD LDS for Windows 7, Windows Server 2012, AD LDS for Windows 8, Windows Server 2012 R2, AD LDS for Windows 8.1, Windows Server 2016 ~~Technical Preview~~, and AD LDS for Windows 10.

2.367 Attribute tombstoneLifetime

If the Recycle Bin optional feature is not enabled, this attribute specifies the number of days before a deleted object is removed from the directory services. If the Recycle Bin optional feature is enabled,

this attribute specifies the number of days before a recycled object is removed from the directory services.

```
cn: Tombstone-Lifetime
ldapDisplayName: tombstoneLifetime
attributeId: 1.2.840.113556.1.2.54
attributeSyntax: 2.5.5.9
omSyntax: 2
isSingleValued: TRUE
schemaIdGuid: 16c3a860-1273-11d0-a060-00aa006c33ed
systemOnly: FALSE
searchFlags: 0
systemFlags: FLAG_SCHEMA_BASE_OBJECT
```

Version-Specific Behavior: Implemented on ADAM, Windows Server 2008, AD LDS for Windows Vista, Windows Server 2008 R2, AD LDS for Windows 7, Windows Server 2012, AD LDS for Windows 8, Windows Server 2012 R2, AD LDS for Windows 8.1, Windows Server 2016 ~~Technical Preview~~, and AD LDS for Windows 10.

2.368 Attribute transportAddressAttribute

This attribute specifies the name of the address type for the transport.

```
cn: Transport-Address-Attribute
ldapDisplayName: transportAddressAttribute
attributeId: 1.2.840.113556.1.4.895
attributeSyntax: 2.5.5.2
omSyntax: 6
isSingleValued: TRUE
schemaIdGuid: c1dc867c-a261-11d1-b606-0000f80367c1
systemOnly: FALSE
searchFlags: 0
systemFlags: FLAG_SCHEMA_BASE_OBJECT
```

Version-Specific Behavior: Implemented on ADAM, Windows Server 2008, AD LDS for Windows Vista, Windows Server 2008 R2, AD LDS for Windows 7, Windows Server 2012, AD LDS for Windows 8, Windows Server 2012 R2, AD LDS for Windows 8.1, Windows Server 2016 ~~Technical Preview~~, and AD LDS for Windows 10.

2.369 Attribute transportDLLName

This attribute specifies the name of the DLL that will manage a transport.

```
cn: Transport-DLL-Name
ldapDisplayName: transportDLLName
attributeId: 1.2.840.113556.1.4.789
attributeSyntax: 2.5.5.12
omSyntax: 64
isSingleValued: TRUE
schemaIdGuid: 26d97372-6070-11d1-a9c6-0000f80367c1
systemOnly: FALSE
searchFlags: 0
rangeLower: 0
rangeUpper: 1024
systemFlags: FLAG_SCHEMA_BASE_OBJECT
```

Version-Specific Behavior: Implemented on ADAM, Windows Server 2008, AD LDS for Windows Vista, Windows Server 2008 R2, AD LDS for Windows 7, Windows Server 2012, AD LDS for Windows 8,

Windows Server 2012 R2, AD LDS for Windows 8.1, Windows Server 2016 ~~Technical Preview~~, and AD LDS for Windows 10.

2.370 Attribute transportType

This attribute specifies the DN for a type of transport that is being used to connect sites together. This value can point to an IP or SMTP transport.

```
cn: Transport-Type
ldapDisplayName: transportType
attributeId: 1.2.840.113556.1.4.791
attributeSyntax: 2.5.5.1
omSyntax: 127
omObjectClass: 1.3.12.2.1011.28.0.714
isSingleValued: TRUE
schemaIdGuid: 26d97374-6070-11d1-a9c6-0000f80367c1
systemOnly: FALSE
searchFlags: 0
systemFlags: FLAG_SCHEMA_BASE_OBJECT
```

Version-Specific Behavior: Implemented on ADAM, Windows Server 2008, AD LDS for Windows Vista, Windows Server 2008 R2, AD LDS for Windows 7, Windows Server 2012, AD LDS for Windows 8, Windows Server 2012 R2, AD LDS for Windows 8.1, Windows Server 2016 ~~Technical Preview~~, and AD LDS for Windows 10.

2.371 Attribute treatAsLeaf

This attribute defines a flag for display specifiers (see the displaySpecifier class in section 3). Display specifiers that have this attribute set to true force the related class to be displayed as a leaf class even if it has children.

```
cn: Treat-As-Leaf
ldapDisplayName: treatAsLeaf
attributeId: 1.2.840.113556.1.4.806
attributeSyntax: 2.5.5.8
omSyntax: 1
isSingleValued: TRUE
schemaIdGuid: 8fd044e3-771f-11d1-aeae-0000f80367c1
systemOnly: FALSE
```

Version-Specific Behavior: Implemented on Windows Server 2008, AD LDS for Windows Vista, Windows Server 2008 R2, AD LDS for Windows 7, Windows Server 2012, AD LDS for Windows 8, Windows Server 2012 R2, AD LDS for Windows 8.1, Windows Server 2016 ~~Technical Preview~~, and AD LDS for Windows 10.

2.372 Attribute trustParent

This attribute specifies the parent in the Kerberos trust hierarchy.

```
cn: Trust-Parent
ldapDisplayName: trustParent
attributeId: 1.2.840.113556.1.4.471
attributeSyntax: 2.5.5.1
omSyntax: 127
omObjectClass: 1.3.12.2.1011.28.0.714
isSingleValued: TRUE
schemaIdGuid: b000ea7a-a086-11d0-afdd-00c04fd930c9
systemOnly: FALSE
```

```
searchFlags: 0
systemFlags: FLAG_SCHEMA_BASE_OBJECT
```

Version-Specific Behavior: Implemented on ADAM, Windows Server 2008, AD LDS for Windows Vista, Windows Server 2008 R2, AD LDS for Windows 7, Windows Server 2012, AD LDS for Windows 8, Windows Server 2012 R2, AD LDS for Windows 8.1, Windows Server 2016 ~~Technical Preview~~, and AD LDS for Windows 10.

2.373 Attribute uid

This attribute specifies the user ID.

```
cn: uid
ldapDisplayName: uid
attributeId: 0.9.2342.19200300.100.1.1
attributeSyntax: 2.5.5.12
omSyntax: 64
isSingleValued: FALSE
schemaIdGuid: 0bb0fca0-1e89-429f-901a-1413894d9f59
systemOnly: FALSE
searchFlags: fPRESERVEONDELETE
attributeSecurityGuid: 59ba2f42-79a2-11d0-9020-00c04fc2d3cf
showInAdvancedViewOnly: FALSE
```

Version-Specific Behavior: Implemented on ADAM, Windows Server 2008, AD LDS for Windows Vista, Windows Server 2008 R2, AD LDS for Windows 7, Windows Server 2012, AD LDS for Windows 8, Windows Server 2012 R2, AD LDS for Windows 8.1, Windows Server 2016 ~~Technical Preview~~, and AD LDS for Windows 10.

2.374 Attribute unicodePwd

The password of the user in Windows NT one-way format (OWF). Windows 2000 uses the Windows NT OWF. This property is used only by the operating system.

Note The clear password cannot be derived back from the OWF form of the password.

```
cn: Unicode-Pwd
ldapDisplayName: unicodePwd
attributeId: 1.2.840.113556.1.4.90
attributeSyntax: 2.5.5.10
omSyntax: 4
isSingleValued: TRUE
schemaIdGuid: bf9679e1-0de6-11d0-a285-00aa003049e2
systemOnly: FALSE
searchFlags: 0
systemFlags: FLAG_SCHEMA_BASE_OBJECT
```

Version-Specific Behavior: Implemented on ADAM, Windows Server 2008, AD LDS for Windows Vista, Windows Server 2008 R2, AD LDS for Windows 7, Windows Server 2012, AD LDS for Windows 8, Windows Server 2012 R2, AD LDS for Windows 8.1, Windows Server 2016 ~~Technical Preview~~, and AD LDS for Windows 10.

2.375 Attribute uPNSuffixes

This attribute specifies the list of User-Principal-Name suffixes for a domain.

```
cn: UPN-Suffixes
```

```
ldapDisplayName: uPNSuffixes
attributeId: 1.2.840.113556.1.4.890
attributeSyntax: 2.5.5.12
omSyntax: 64
isSingleValued: FALSE
schemaIdGuid: 032160bf-9824-11d1-aec0-0000f80367c1
systemOnly: FALSE
searchFlags: 0
systemFlags: FLAG_SCHEMA_BASE_OBJECT
```

Version-Specific Behavior: Implemented on ADAM, Windows Server 2008, AD LDS for Windows Vista, Windows Server 2008 R2, AD LDS for Windows 7, Windows Server 2012, AD LDS for Windows 8, Windows Server 2012 R2, AD LDS for Windows 8.1, Windows Server 2016 ~~Technical Preview~~, and AD LDS for Windows 10.

2.376 Attribute url

This attribute specifies a list of alternate webpages.

```
cn: WWW-Page-Other
ldapDisplayName: url
attributeId: 1.2.840.113556.1.4.749
attributeSyntax: 2.5.5.12
omSyntax: 64
isSingleValued: FALSE
schemaIdGuid: 9a9a0221-4a5b-11d1-a9c3-0000f80367c1
systemOnly: FALSE
searchFlags: 0
attributeSecurityGuid: e45795b3-9455-11d1-aebd-0000f80367c1
systemFlags: FLAG_SCHEMA_BASE_OBJECT
```

Version-Specific Behavior: Implemented on ADAM, Windows Server 2008, AD LDS for Windows Vista, Windows Server 2008 R2, AD LDS for Windows 7, Windows Server 2012, AD LDS for Windows 8, Windows Server 2012 R2, AD LDS for Windows 8.1, Windows Server 2016 ~~Technical Preview~~, and AD LDS for Windows 10.

2.377 Attribute userCertificate

This attribute contains the DER-encoded X509v3 certificates issued to the user ([RFC3280]).

Note This property contains the public key certificates issued to this user by Microsoft Certificate Service.

```
cn: X509-Cert
ldapDisplayName: userCertificate
attributeId: 2.5.4.36
attributeSyntax: 2.5.5.10
omSyntax: 4
isSingleValued: FALSE
schemaIdGuid: bf967a7f-0de6-11d0-a285-00aa003049e2
systemOnly: FALSE
searchFlags: 0
rangeUpper: 32768
attributeSecurityGuid: 77b5b886-944a-11d1-aebd-0000f80367c1
isMemberOfPartialAttributeSet: TRUE
```

Version-Specific Behavior: Implemented on ADAM, Windows Server 2008, AD LDS for Windows Vista, Windows Server 2008 R2, AD LDS for Windows 7, Windows Server 2012, AD LDS for Windows 8,

Windows Server 2012 R2, AD LDS for Windows 8.1, Windows Server 2016 ~~Technical Preview~~, and AD LDS for Windows 10.

2.378 Attribute userParameters

This attribute specifies the user's parameters and is set aside for use by applications. Microsoft products use this member to store user data that is specific to the individual program.

```
cn: User-Parameters
ldapDisplayName: userParameters
attributeId: 1.2.840.113556.1.4.138
attributeSyntax: 2.5.5.12
omSyntax: 64
isSingleValued: TRUE
schemaIdGuid: bf967a6d-0de6-11d0-a285-00aa003049e2
systemOnly: FALSE
searchFlags: 0
rangeLower: 0
rangeUpper: 32767
attributeSecurityGuid: 4c164200-20c0-11d0-a768-00aa006e0529
```

Version-Specific Behavior: Implemented on ADAM, Windows Server 2008, AD LDS for Windows Vista, Windows Server 2008 R2, AD LDS for Windows 7, Windows Server 2012, AD LDS for Windows 8, Windows Server 2012 R2, AD LDS for Windows 8.1, Windows Server 2016 ~~Technical Preview~~, and AD LDS for Windows 10.

2.379 Attribute userPassword

This attribute specifies the user's password in UTF-8 format. This is a write-only attribute.

```
cn: User-Password
ldapDisplayName: userPassword
attributeId: 2.5.4.35
attributeSyntax: 2.5.5.10
omSyntax: 4
isSingleValued: FALSE
schemaIdGuid: bf967a6e-0de6-11d0-a285-00aa003049e2
systemOnly: FALSE
searchFlags: 0
rangeLower: 1
rangeUpper: 128
systemFlags: FLAG_SCHEMA_BASE_OBJECT
```

Version-Specific Behavior: Implemented on ADAM, Windows Server 2008, AD LDS for Windows Vista, Windows Server 2008 R2, AD LDS for Windows 7, Windows Server 2012, AD LDS for Windows 8, Windows Server 2012 R2, AD LDS for Windows 8.1, Windows Server 2016 ~~Technical Preview~~, and AD LDS for Windows 10.

2.380 Attribute userPKCS12

This attribute specifies PKCS #12 PFX PDU for exchange of personal identity information.

```
cn: userPKCS12
ldapDisplayName: userPKCS12
attributeId: 2.16.840.1.113730.3.1.216
attributeSyntax: 2.5.5.10
omSyntax: 4
isSingleValued: FALSE
schemaIdGuid: 23998ab5-70f8-4007-a4c1-a84a38311f9a
```

```
systemOnly: FALSE
searchFlags: 0
showInAdvancedViewOnly: FALSE
```

Version-Specific Behavior: Implemented on ADAM, Windows Server 2008, AD LDS for Windows Vista, Windows Server 2008 R2, AD LDS for Windows 7, Windows Server 2012, AD LDS for Windows 8, Windows Server 2012 R2, AD LDS for Windows 8.1, Windows Server 2016 ~~Technical Preview~~, and AD LDS for Windows 10.

2.381 Attribute userPrincipalName

This attribute contains the UPN that is an Internet-style logon name for a user, as specified in [RFC822]. The UPN is shorter than the DN and easier to remember.

By convention, this attribute ~~should map maps~~ to the user email name. The value set for this attribute is equal to the length of the user's ID and the domain name.

```
cn: User-Principal-Name
ldapDisplayName: userPrincipalName
attributeId: 1.2.840.113556.1.4.656
attributeSyntax: 2.5.5.12
omSyntax: 64
isSingleValued: TRUE
schemaIdGuid: 28630ebb-41d5-11d1-a9c1-0000f80367c1
systemOnly: FALSE
searchFlags: fATTINDEX
rangeUpper: 1024
attributeSecurityGuid: e48d0154-bcf8-11d1-8702-00c04fb96050
isMemberOfPartialAttributeSet: TRUE
systemFlags: FLAG_SCHEMA_BASE_OBJECT |
FLAG_ATTR_REQ_PARTIAL_SET_MEMBER
```

Version-Specific Behavior: Implemented on ADAM, Windows Server 2008, AD LDS for Windows Vista, Windows Server 2008 R2, AD LDS for Windows 7, Windows Server 2012, AD LDS for Windows 8, Windows Server 2012 R2, AD LDS for Windows 8.1, Windows Server 2016 ~~Technical Preview~~, and AD LDS for Windows 10.

2.382 Attribute userSMIMECertificate

This attribute specifies a certificate distribution object or tagged certificates.

```
cn: User-SMIME-Certificate
ldapDisplayName: userSMIMECertificate
attributeId: 2.16.840.1.113730.3.140
attributeSyntax: 2.5.5.10
omSyntax: 4
isSingleValued: FALSE
schemaIdGuid: e16a9db2-403c-11d1-a9c0-0000f80367c1
systemOnly: FALSE
searchFlags: 0
rangeUpper: 32768
attributeSecurityGuid: 77b5b886-944a-11d1-aebd-0000f80367c1
isMemberOfPartialAttributeSet: TRUE
```

Version-Specific Behavior: Implemented on ADAM, Windows Server 2008, AD LDS for Windows Vista, Windows Server 2008 R2, AD LDS for Windows 7, Windows Server 2012, AD LDS for Windows 8, Windows Server 2012 R2, AD LDS for Windows 8.1, Windows Server 2016 ~~Technical Preview~~, and AD LDS for Windows 10.

2.383 Attribute uSNChanged

This attribute specifies an update sequence number (USN) value assigned by the local directory for the latest change, including creation.

```
cn: USN-Changed
ldapDisplayName: uSNChanged
attributeId: 1.2.840.113556.1.2.120
attributeSyntax: 2.5.5.16
omSyntax: 65
isSingleValued: TRUE
schemaIdGuid: bf967a6f-0de6-11d0-a285-00aa003049e2
systemOnly: TRUE
searchFlags: fPRESERVEONDELETE | fATTINDEX
isMemberOfPartialAttributeSet: TRUE
systemFlags: FLAG_SCHEMA_BASE_OBJECT |
  FLAG_ATTR_REQ_PARTIAL_SET_MEMBER | FLAG_ATTR_NOT_REPLICATED
```

Version-Specific Behavior: Implemented on ADAM, Windows Server 2008, AD LDS for Windows Vista, Windows Server 2008 R2, AD LDS for Windows 7, Windows Server 2012, AD LDS for Windows 8, Windows Server 2012 R2, AD LDS for Windows 8.1, Windows Server 2016 ~~Technical Preview~~, and AD LDS for Windows 10.

2.384 Attribute uSNCreated

This attribute specifies a USN-Changed value that is assigned at object creation.

```
cn: USN-Created
ldapDisplayName: uSNCreated
attributeId: 1.2.840.113556.1.2.19
attributeSyntax: 2.5.5.16
omSyntax: 65
isSingleValued: TRUE
schemaIdGuid: bf967a70-0de6-11d0-a285-00aa003049e2
systemOnly: TRUE
searchFlags: fPRESERVEONDELETE | fATTINDEX
isMemberOfPartialAttributeSet: TRUE
systemFlags: FLAG_SCHEMA_BASE_OBJECT |
  FLAG_ATTR_REQ_PARTIAL_SET_MEMBER | FLAG_ATTR_NOT_REPLICATED
```

Version-Specific Behavior: Implemented on ADAM, Windows Server 2008, AD LDS for Windows Vista, Windows Server 2008 R2, AD LDS for Windows 7, Windows Server 2012, AD LDS for Windows 8, Windows Server 2012 R2, AD LDS for Windows 8.1, Windows Server 2016 ~~Technical Preview~~, and AD LDS for Windows 10.

2.385 Attribute uSNDSALastObjRemoved

This attribute contains the USN for the last system object that was removed from a server.

```
cn: USN-DSA-Last-Obj-Removed
ldapDisplayName: uSNDSALastObjRemoved
attributeId: 1.2.840.113556.1.2.267
attributeSyntax: 2.5.5.16
omSyntax: 65
isSingleValued: TRUE
schemaIdGuid: bf967a71-0de6-11d0-a285-00aa003049e2
systemOnly: TRUE
searchFlags: 0
systemFlags: FLAG_SCHEMA_BASE_OBJECT
```

Version-Specific Behavior: Implemented on ADAM, Windows Server 2008, AD LDS for Windows Vista, Windows Server 2008 R2, AD LDS for Windows 7, Windows Server 2012, AD LDS for Windows 8, Windows Server 2012 R2, AD LDS for Windows 8.1, Windows Server 2016 ~~Technical Preview~~, and AD LDS for Windows 10.

2.386 Attribute USNIntersite

This attribute specifies the USN for intersite replication.

```
cn: USN-Intersite
ldapDisplayName: USNIntersite
attributeId: 1.2.840.113556.1.2.469
attributeSyntax: 2.5.5.9
omSyntax: 2
isSingleValued: TRUE
schemaIdGuid: a8df7498-c5ea-11d1-bbcb-0080c76670c0
systemOnly: FALSE
searchFlags: fATTINDEX
systemFlags: FLAG_SCHEMA_BASE_OBJECT
```

Version-Specific Behavior: Implemented on ADAM, Windows Server 2008, AD LDS for Windows Vista, Windows Server 2008 R2, AD LDS for Windows 7, Windows Server 2012, AD LDS for Windows 8, Windows Server 2012 R2, AD LDS for Windows 8.1, Windows Server 2016 ~~Technical Preview~~, and AD LDS for Windows 10.

2.387 Attribute uSNLastObjRem

This attribute contains the USN for the last non-system object that was removed from a server.

```
cn: USN-Last-Obj-Rem
ldapDisplayName: uSNLastObjRem
attributeId: 1.2.840.113556.1.2.121
attributeSyntax: 2.5.5.16
omSyntax: 65
isSingleValued: TRUE
schemaIdGuid: bf967a73-0de6-11d0-a285-00aa003049e2
systemOnly: TRUE
searchFlags: 0
isMemberOfPartialAttributeSet: TRUE
systemFlags: FLAG_SCHEMA_BASE_OBJECT |
FLAG_ATTR_REQ_PARTIAL_SET_MEMBER | FLAG_ATTR_NOT_REPLICATED
```

Version-Specific Behavior: Implemented on ADAM, Windows Server 2008, AD LDS for Windows Vista, Windows Server 2008 R2, AD LDS for Windows 7, Windows Server 2012, AD LDS for Windows 8, Windows Server 2012 R2, AD LDS for Windows 8.1, Windows Server 2016 ~~Technical Preview~~, and AD LDS for Windows 10.

2.388 Attribute uSNSource

This attribute specifies the value of the **USN-Changed** attribute of the object from the remote directory that replicated the change to the local server.

```
cn: USN-Source
ldapDisplayName: uSNSource
attributeId: 1.2.840.113556.1.4.896
attributeSyntax: 2.5.5.16
omSyntax: 65
isSingleValued: TRUE
```

```
schemaIdGuid: 167758ad-47f3-11d1-a9c3-0000f80367c1
systemOnly: FALSE
searchFlags: 0
systemFlags: FLAG_SCHEMA_BASE_OBJECT
```

Version-Specific Behavior: Implemented on ADAM, Windows Server 2008, AD LDS for Windows Vista, Windows Server 2008 R2, AD LDS for Windows 7, Windows Server 2012, AD LDS for Windows 8, Windows Server 2012 R2, AD LDS for Windows 8.1, Windows Server 2016 ~~Technical Preview~~, and AD LDS for Windows 10.

2.389 Attribute validAccesses

This attribute specifies the type of access that is permitted with an extended right.

```
cn: Valid-Accesses
ldapDisplayName: validAccesses
attributeId: 1.2.840.113556.1.4.1356
attributeSyntax: 2.5.5.9
omSyntax: 2
isSingleValued: TRUE
schemaIdGuid: 4d2fa380-7f54-11d2-992a-0000f87a57d4
systemOnly: FALSE
searchFlags: 0
systemFlags: FLAG_SCHEMA_BASE_OBJECT
```

Version-Specific Behavior: Implemented on ADAM, Windows Server 2008, AD LDS for Windows Vista, Windows Server 2008 R2, AD LDS for Windows 7, Windows Server 2012, AD LDS for Windows 8, Windows Server 2012 R2, AD LDS for Windows 8.1, Windows Server 2016 ~~Technical Preview~~, and AD LDS for Windows 10.

2.390 Attribute wbemPath

This attribute specifies references to objects in other ADSI namespaces.

```
cn: Wbem-Path
ldapDisplayName: wbemPath
attributeId: 1.2.840.113556.1.4.301
attributeSyntax: 2.5.5.12
omSyntax: 64
isSingleValued: FALSE
schemaIdGuid: 244b2970-5abd-11d0-afd2-00c04fd930c9
systemOnly: FALSE
searchFlags: 0
systemFlags: FLAG_SCHEMA_BASE_OBJECT
```

Version-Specific Behavior: Implemented on ADAM, Windows Server 2008, AD LDS for Windows Vista, Windows Server 2008 R2, AD LDS for Windows 7, Windows Server 2012, AD LDS for Windows 8, Windows Server 2012 R2, AD LDS for Windows 8.1, Windows Server 2016 ~~Technical Preview~~, and AD LDS for Windows 10.

2.391 Attribute wellKnownObjects

This attribute contains a list of well-known object containers by GUID and distinguished name. The well-known objects are system containers. This information is used to retrieve an object after it has been moved by using just the GUID and the domain name.

Whenever the object is moved, the Active Directory system will automatically update the distinguished name portion of the Well-Known-Objects values that referred to the object.

For information on well-known objects, well-known GUIDs, and their symbolic names, see [MS-ADTS] section 6.1.1.4.

```
cn: Well-Known-Objects
ldapDisplayName: wellKnownObjects
attributeId: 1.2.840.113556.1.4.618
attributeSyntax: 2.5.5.7
omSyntax: 127
omObjectClass: 1.2.840.113556.1.1.1.11
isSingleValued: FALSE
schemaIdGuid: 05308983-7688-11d1-aded-00c04fd8d5cd
systemOnly: TRUE
searchFlags: 0
rangeLower: 16
rangeUpper: 16
isMemberOfPartialAttributeSet: TRUE
systemFlags: FLAG_SCHEMA_BASE_OBJECT |
FLAG_ATTR_REQ_PARTIAL_SET_MEMBER
```

Version-Specific Behavior: Implemented on ADAM, Windows Server 2008, AD LDS for Windows Vista, Windows Server 2008 R2, AD LDS for Windows 7, Windows Server 2012, AD LDS for Windows 8, Windows Server 2012 R2, AD LDS for Windows 8.1, Windows Server 2016 ~~Technical Preview~~, and AD LDS for Windows 10.

2.392 Attribute whenChanged

This attribute specifies the date when this object was last changed. This value is not replicated and exists in the global catalog.

```
cn: When-Changed
ldapDisplayName: whenChanged
attributeId: 1.2.840.113556.1.2.3
attributeSyntax: 2.5.5.11
omSyntax: 24
isSingleValued: TRUE
schemaIdGuid: bf967a77-0de6-11d0-a285-00aa003049e2
systemOnly: TRUE
searchFlags: 0
isMemberOfPartialAttributeSet: TRUE
systemFlags: FLAG_SCHEMA_BASE_OBJECT |
FLAG_ATTR_REQ_PARTIAL_SET_MEMBER | FLAG_ATTR_NOT_REPLICATED
```

Version-Specific Behavior: Implemented on ADAM, Windows Server 2008, AD LDS for Windows Vista, Windows Server 2008 R2, AD LDS for Windows 7, Windows Server 2012, AD LDS for Windows 8, Windows Server 2012 R2, AD LDS for Windows 8.1, Windows Server 2016 ~~Technical Preview~~, and AD LDS for Windows 10.

2.393 Attribute whenCreated

This attribute specifies the date when this object was created. This value is replicated and is in the global catalog.

```
cn: When-Created
ldapDisplayName: whenCreated
attributeId: 1.2.840.113556.1.2.2
attributeSyntax: 2.5.5.11
omSyntax: 24
```

```
isSingleValued: TRUE
schemaIdGuid: bf967a78-0de6-11d0-a285-00aa003049e2
systemOnly: TRUE
searchFlags: 0
isMemberOfPartialAttributeSet: TRUE
systemFlags: FLAG_SCHEMA_BASE_OBJECT |
FLAG_ATTR_REQ_PARTIAL_SET_MEMBER
```

Version-Specific Behavior: Implemented on ADAM, Windows Server 2008, AD LDS for Windows Vista, Windows Server 2008 R2, AD LDS for Windows 7, Windows Server 2012, AD LDS for Windows 8, Windows Server 2012 R2, AD LDS for Windows 8.1, Windows Server 2016 ~~Technical Preview~~, and AD LDS for Windows 10.

2.394 Attribute wWWHomePage

This attribute specifies the primary web page.

```
cn: WWW-Home-Page
ldapDisplayName: wWWHomePage
attributeId: 1.2.840.113556.1.2.464
attributeSyntax: 2.5.5.12
omSyntax: 64
isSingleValued: TRUE
schemaIdGuid: bf967a7a-0de6-11d0-a285-00aa003049e2
systemOnly: FALSE
searchFlags: 0
rangeLower: 1
rangeUpper: 2048
attributeSecurityGuid: e45795b3-9455-11d1-aebd-0000f80367c1
systemFlags: FLAG_SCHEMA_BASE_OBJECT
```

Version-Specific Behavior: Implemented on ADAM, Windows Server 2008, AD LDS for Windows Vista, Windows Server 2008 R2, AD LDS for Windows 7, Windows Server 2012, AD LDS for Windows 8, Windows Server 2012 R2, AD LDS for Windows 8.1, Windows Server 2016 ~~Technical Preview~~, and AD LDS for Windows 10.

2.395 Attribute x121Address

This attribute specifies the X.121 address for an object, as specified in [X121].

```
cn: X121-Address
ldapDisplayName: x121Address
attributeId: 2.5.4.24
attributeSyntax: 2.5.5.6
omSyntax: 18
isSingleValued: FALSE
schemaIdGuid: bf967a7b-0de6-11d0-a285-00aa003049e2
systemOnly: FALSE
searchFlags: 0
rangeLower: 1
rangeUpper: 15
attributeSecurityGuid: 77b5b886-944a-11d1-aebd-0000f80367c1
systemFlags: FLAG_SCHEMA_BASE_OBJECT
```

Version-Specific Behavior: Implemented on ADAM, Windows Server 2008, AD LDS for Windows Vista, Windows Server 2008 R2, AD LDS for Windows 7, Windows Server 2012, AD LDS for Windows 8, Windows Server 2012 R2, AD LDS for Windows 8.1, Windows Server 2016 ~~Technical Preview~~, and AD LDS for Windows 10.

2.396 Attribute x500uniqueIdentifier

This attribute is used to distinguish between objects when a DN has been reused.

Note This is a different attribute type from both the "uid" and "uniqueIdentifier" types.

```
cn: x500uniqueIdentifier
ldapDisplayName: x500uniqueIdentifier
attributeId: 2.5.4.45
attributeSyntax: 2.5.5.10
omSyntax: 4
isSingleValued: FALSE
schemaIdGuid: d07da11f-8a3d-42b6-b0aa-76c962be719a
systemOnly: FALSE
searchFlags: 0
showInAdvancedViewOnly: FALSE
```

Version-Specific Behavior: Implemented on ADAM, Windows Server 2008, AD LDS for Windows Vista, Windows Server 2008 R2, AD LDS for Windows 7, Windows Server 2012, AD LDS for Windows 8, Windows Server 2012 R2, AD LDS for Windows 8.1, Windows Server 2016 ~~Technical Preview~~, and AD LDS for Windows 10.

3 Classes

~~Note: Some of the information in this section is subject to change because it applies to a preliminary product version, and thus may differ from the final version of the software when released. All behavior notes that pertain to the preliminary product version contain specific references to it as an aid to the reader.~~

The following sections specify the classes in the **Active Directory Lightweight Directory Services** schema.

These sections normatively specify the schema definition of each class, as well as version-specific behavior of those schema definitions (such as when the class was added to the schema). As an aid to the reader, some of the sections also include informative notes about how the class can be used.

Note In the following class definitions, "<SchemaNCDN>" is the DN of the schema NC. For more information, see [MS-ADTS] section 3.1.1.1.7.

Note Lines of text in the class definitions that are excessively long have been "folded" in accordance with [RFC2849] Note 2.

3.1 Class applicationSettings

This is the base class for server-specific application settings.

```
cn: Application-Settings
ldapDisplayName: applicationSettings
governsId: 1.2.840.113556.1.5.7000.49
objectClassCategory: 2
rdnAttId: cn
subClassOf: top
systemMayContain: msDS-Settings
systemPossSuperiors: server
schemaIdGuid: f780acc1-56f0-11d1-a9c6-0000f80367c1
defaultHidingValue: TRUE
systemOnly: FALSE
defaultObjectCategory: CN=Application-Settings,<SchemaNCDN>
systemFlags: FLAG_SCHEMA_BASE_OBJECT
```

Version-Specific Behavior: Implemented on Active Directory Application Mode (ADAM), Windows Server 2008 operating system, Active Directory Lightweight Directory Services (AD LDS) for Windows Vista, Windows Server 2008 R2 operating system, Active Directory Lightweight Directory Services (AD LDS) for Windows 7, Windows Server 2012 operating system, Active Directory Lightweight Directory Services (AD LDS) for Windows 8 operating system, Windows Server 2012 R2 operating system, Active Directory Lightweight Directory Services (AD LDS) for Windows 8.1 operating system, Windows Server 2016 ~~Technical Preview~~ operating system, and Active Directory Lightweight Directory Services (AD LDS) for Windows 10 operating system.

3.2 Class applicationSiteSettings

This class specifies the container that holds all site-specific settings.

```
cn: Application-Site-Settings
ldapDisplayName: applicationSiteSettings
governsId: 1.2.840.113556.1.5.68
objectClassCategory: 2
rdnAttId: cn
subClassOf: top
systemPossSuperiors: site
schemaIdGuid: 19195a5c-6da0-11d0-afd3-00c04fd930c9
```

```
defaultSecurityDescriptor: D:S:
defaultHidingValue: TRUE
systemOnly: FALSE
defaultObjectCategory: CN=Application-Site-Settings,<SchemaNCDN>
systemFlags: FLAG_SCHEMA_BASE_OBJECT
```

Version-Specific Behavior: Implemented on ADAM, Windows Server 2008, AD LDS for Windows Vista, Windows Server 2008 R2, AD LDS for Windows 7, Windows Server 2012, AD LDS for Windows 8, Windows Server 2012 R2, AD LDS for Windows 8.1, Windows Server 2016 ~~Technical Preview~~, and AD LDS for Windows 10.

3.3 Class attributeSchema

This class defines an attribute object in the schema.

```
cn: Attribute-Schema
ldapDisplayName: attributeSchema
governsID: 1.2.840.113556.1.3.14
objectClassCategory: 1
rdnAttId: cn
subClassOf: top
systemMustContain: schemaIDGUID, oMSyntax, LDAPDisplayName,
  isSingleValued, cn, attributeSyntax, attributeID
systemMayContain: systemOnly, searchFlags, schemaFlagsEx, rangeUpper,
  rangeLower, oMOBJECTClass, msDs-Schema-Extensions, msDS-IntId,
  linkID, isMemberOfPartialAttributeSet, isEphemeral, isDefunct,
  extendedCharsAllowed, classDisplayName, attributeSecurityGUID
systemPossSuperiors: dMD
schemaIdGuid: bf967a80-0de6-11d0-a285-00aa003049e2
defaultSecurityDescriptor: D:S:
defaultHidingValue: TRUE
systemOnly: FALSE
defaultObjectCategory: CN=Attribute-Schema,<SchemaNCDN>
systemFlags: FLAG_SCHEMA_BASE_OBJECT | FLAG_DOMAIN_DISALLOW_RENAME
```

Version-Specific Behavior: Implemented on ADAM, Windows Server 2008, AD LDS for Windows Vista, Windows Server 2008 R2, AD LDS for Windows 7, Windows Server 2012, AD LDS for Windows 8, Windows Server 2012 R2, AD LDS for Windows 8.1, Windows Server 2016 ~~Technical Preview~~, and AD LDS for Windows 10.

3.4 Class classSchema

This class defines a class object in the schema.

```
cn: Class-Schema
ldapDisplayName: classSchema
governsID: 1.2.840.113556.1.3.13
objectClassCategory: 1
rdnAttId: cn
subClassOf: top
systemMustContain: subClassOf, schemaIDGUID, objectClassCategory,
  governsID, defaultObjectCategory, cn
systemMayContain: systemPossSuperiors, systemOnly, systemMustContain,
  systemMayContain, systemAuxiliaryClass, schemaFlagsEx, rDNAttID,
  possSuperiors, mustContain, msDs-Schema-Extensions, msDS-IntId,
  mayContain, LDAPDisplayName, isDefunct, defaultSecurityDescriptor,
  defaultHidingValue, classDisplayName, auxiliaryClass
systemPossSuperiors: dMD
schemaIdGuid: bf967a83-0de6-11d0-a285-00aa003049e2
defaultSecurityDescriptor: D:S:
defaultHidingValue: TRUE
systemOnly: FALSE
```

```
defaultObjectCategory: CN=Class-Schema,<SchemaNCDN>
systemFlags: FLAG_SCHEMA_BASE_OBJECT | FLAG_DOMAIN_DISALLOW_RENAME
```

Version-Specific Behavior: Implemented on ADAM, Windows Server 2008, AD LDS for Windows Vista, Windows Server 2008 R2, AD LDS for Windows 7, Windows Server 2012, AD LDS for Windows 8, Windows Server 2012 R2, AD LDS for Windows 8.1, Windows Server 2016 ~~Technical Preview~~, and AD LDS for Windows 10.

3.5 Class configuration

This class is a container that holds the configuration information for a domain.

```
cn: Configuration
ldapDisplayName: configuration
governsId: 1.2.840.113556.1.5.12
objectClassCategory: 1
rdnAttId: cn
subClassOf: top
systemMustContain: cn
systemMayContain: msDS-USNLastSyncSuccess, msDS-ReplAuthenticationMode
systemPossSuperiors: domainDNS
schemaIdGuid: bf967a87-0de6-11d0-a285-00aa003049e2
defaultSecurityDescriptor: D:S:
defaultHidingValue: TRUE
systemOnly: TRUE
defaultObjectCategory: CN=Configuration,<SchemaNCDN>
systemFlags: FLAG_SCHEMA_BASE_OBJECT
```

Version-Specific Behavior: Implemented on ADAM, Windows Server 2008, AD LDS for Windows Vista, Windows Server 2008 R2, AD LDS for Windows 7, Windows Server 2012, AD LDS for Windows 8, Windows Server 2012 R2, AD LDS for Windows 8.1, Windows Server 2016 ~~Technical Preview~~, and AD LDS for Windows 10.

3.6 Class container

This class is used to hold other classes.

```
cn: Container
ldapDisplayName: container
governsId: 1.2.840.113556.1.3.23
objectClassCategory: 1
rdnAttId: cn
subClassOf: top
systemMustContain: cn
systemMayContain: schemaVersion
possSuperiors: msDS-AzScope, msDS-AzApplication, msDS-AzAdminManager
systemPossSuperiors: subnet, server, nTDSservice, domainDNS,
  organization, configuration, container, organizationalUnit
schemaIdGuid: bf967a8b-0de6-11d0-a285-00aa003049e2
defaultSecurityDescriptor: D:S:
defaultHidingValue: TRUE
systemOnly: FALSE
defaultObjectCategory: CN=Container,<SchemaNCDN>
systemFlags: FLAG_SCHEMA_BASE_OBJECT
```

Version-Specific Behavior: Implemented on ADAM, Windows Server 2008, AD LDS for Windows Vista, Windows Server 2008 R2, AD LDS for Windows 7, Windows Server 2012, AD LDS for Windows 8, Windows Server 2012 R2, AD LDS for Windows 8.1, Windows Server 2016 ~~Technical Preview~~, and AD LDS for Windows 10.

3.7 Class controlAccessRight

This class identifies an extended right that can be granted or revoked via an access control list (ACL).

```
cn: Control-Access-Right
ldapDisplayName: controlAccessRight
governsId: 1.2.840.113556.1.5.77
objectClassCategory: 1
rdnAttId: cn
subClassOf: top
systemMayContain: validAccesses, rightsGuid, localizationDisplayId,
  appliesTo
systemPossSuperiors: container
schemaIdGuid: 8297931e-86d3-11d0-afda-00c04fd930c9
defaultSecurityDescriptor: D:S:
defaultHidingValue: TRUE
systemOnly: FALSE
defaultObjectCategory: CN=Control-Access-Right,<SchemaNCDN>
systemFlags: FLAG_SCHEMA_BASE_OBJECT
```

Version-Specific Behavior: Implemented on ADAM, Windows Server 2008, AD LDS for Windows Vista, Windows Server 2008 R2, AD LDS for Windows 7, Windows Server 2012, AD LDS for Windows 8, Windows Server 2012 R2, AD LDS for Windows 8.1, Windows Server 2016 ~~Technical Preview~~, and AD LDS for Windows 10.

3.8 Class country

This class specifies the country/region in the address of the user. This is the full name.

```
cn: Country
ldapDisplayName: country
governsId: 2.5.6.2
objectClassCategory: 0
rdnAttId: c
subClassOf: top
systemMustContain: c
systemMayContain: co, searchGuide
systemPossSuperiors: domainDNS, organization
schemaIdGuid: bf967a8c-0de6-11d0-a285-00aa003049e2
defaultSecurityDescriptor: D:S:
defaultHidingValue: TRUE
systemOnly: FALSE
defaultObjectCategory: CN=Country,<SchemaNCDN>
systemFlags: FLAG_SCHEMA_BASE_OBJECT
```

Version-Specific Behavior: Implemented on ADAM, Windows Server 2008, AD LDS for Windows Vista, Windows Server 2008 R2, AD LDS for Windows 7, Windows Server 2012, AD LDS for Windows 8, Windows Server 2012 R2, AD LDS for Windows 8.1, Windows Server 2016 ~~Technical Preview~~, and AD LDS for Windows 10.

3.9 Class crossRef

This class holds knowledge information about all directory service (DS) naming contexts and all external directories to which referrals can be generated.

```
cn: Cross-Ref
ldapDisplayName: crossRef
governsId: 1.2.840.113556.1.3.11
objectClassCategory: 1
rdnAttId: cn
```

```

subClassOf: top
systemMustContain: nCName, cn
systemMayContain: trustParent, superiorDNSRoot, rootTrust,
  nETBIOName, msDS-Other-Settings, Enabled, msDS-SDReferenceDomain,
  msDS-Replication-Notify-Subsequent-DSA-Delay,
  msDS-Replication-Notify-First-DSA-Delay, msDS-NC-Replica-Locations,
  msDS-DnsRootAlias, msDS-Behavior-Version, dnsRoot
systemPossSuperiors: crossRefContainer
schemaIdGuid: bf967a8d-0de6-11d0-a285-00aa003049e2
defaultSecurityDescriptor: D:S:
defaultHidingValue: TRUE
systemOnly: FALSE
defaultObjectCategory: CN=Cross-Ref,<SchemaNCDN>
systemFlags: FLAG_SCHEMA_BASE_OBJECT

```

Version-Specific Behavior: Implemented on ADAM, Windows Server 2008, AD LDS for Windows Vista, Windows Server 2008 R2, AD LDS for Windows 7, Windows Server 2012, AD LDS for Windows 8, Windows Server 2012 R2, AD LDS for Windows 8.1, Windows Server 2016 ~~Technical Preview~~, and AD LDS for Windows 10.

3.10 Class crossRefContainer

This class holds cross-reference objects for all naming contexts.

```

cn: Cross-Ref-Container
ldapDisplayName: crossRefContainer
governsId: 1.2.840.113556.1.5.7000.53
objectClassCategory: 1
rdnAttId: cn
subClassOf: top
systemMayContain: msDS-EnabledFeature, uPNSuffixes, msDS-UpdateScript,
  msDS-ExecuteScriptPassword, msDS-Behavior-Version
systemPossSuperiors: configuration
schemaIdGuid: ef9e60e0-56f7-11d1-a9c6-0000f80367c1
defaultSecurityDescriptor: D:S:
defaultHidingValue: FALSE
systemOnly: TRUE
defaultObjectCategory: CN=Cross-Ref-Container,<SchemaNCDN>
systemFlags: FLAG_SCHEMA_BASE_OBJECT

```

Version-Specific Behavior: Implemented on ADAM, Windows Server 2008, AD LDS for Windows Vista, Windows Server 2008 R2, AD LDS for Windows 7, Windows Server 2012, AD LDS for Windows 8, Windows Server 2012 R2, AD LDS for Windows 8.1, Windows Server 2016 ~~Technical Preview~~, and AD LDS for Windows 10.

3.11 Class displaySpecifier

This class describes the context menus and property pages to be used with an object in the directory.

```

cn: Display-Specifier
ldapDisplayName: displaySpecifier
governsId: 1.2.840.113556.1.5.84
objectClassCategory: 1
rdnAttId: cn
subClassOf: top
systemMayContain: treatAsLeaf, shellPropertyPages, shellContextMenu,
  scopeFlags, queryFilter, iconPath, extraColumns, creationWizard,
  createWizardExt, createDialog, contextMenu, classDisplayName,
  attributeDisplayNames, adminPropertyPages,
  adminMultiselectPropertyPages, adminContextMenu
systemPossSuperiors: container
schemaIdGuid: e0fa1e8a-9b45-11d0-afdd-00c04fd930c9

```



```
systemOnly: FALSE
defaultObjectCategory: CN=Display-Specifier,<SchemaNCDN>
```

Version-Specific Behavior: Implemented on Windows Server 2008, AD LDS for Windows Vista, Windows Server 2008 R2, AD LDS for Windows 7, Windows Server 2012, AD LDS for Windows 8, Windows Server 2012 R2, AD LDS for Windows 8.1, Windows Server 2016 ~~Technical Preview~~, and AD LDS for Windows 10.

3.12 Class dMD

This class specifies the Directory Management Domain. In Active Directory, this is the class that holds the schema.

```
cn: DMD
ldapDisplayName: dMD
governsId: 1.2.840.113556.1.3.9
objectClassCategory: 1
rdnAttId: cn
subClassOf: top
systemMustContain: cn
systemMayContain: msDS-USNLastSyncSuccess, schemaUpdate, schemaInfo,
  prefixMap, msDs-Schema-Extensions, msDS-IntId, dmdName
systemPossSuperiors: configuration
schemaIdGuid: bf967a8f-0de6-11d0-a285-00aa003049e2
defaultSecurityDescriptor: D:S:
defaultHidingValue: TRUE
systemOnly: TRUE
defaultObjectCategory: CN=DMD,<SchemaNCDN>
systemFlags: FLAG_SCHEMA_BASE_OBJECT
```

Version-Specific Behavior: Implemented on ADAM, Windows Server 2008, AD LDS for Windows Vista, Windows Server 2008 R2, AD LDS for Windows 7, Windows Server 2012, AD LDS for Windows 8, Windows Server 2012 R2, AD LDS for Windows 8.1, Windows Server 2016 ~~Technical Preview~~, and AD LDS for Windows 10.

3.13 Class domain

This class contains information about a domain.

```
cn: Domain
ldapDisplayName: domain
governsId: 1.2.840.113556.1.5.66
objectClassCategory: 2
rdnAttId: dc
subClassOf: top
systemMustContain: dc
systemPossSuperiors: domain, organization
schemaIdGuid: 19195a5a-6da0-11d0-afd3-00c04fd930c9
defaultHidingValue: TRUE
systemOnly: FALSE
defaultObjectCategory: CN=Domain-DNS,<SchemaNCDN>
systemFlags: FLAG_SCHEMA_BASE_OBJECT
```

Version-Specific Behavior: Implemented on ADAM, Windows Server 2008, AD LDS for Windows Vista, Windows Server 2008 R2, AD LDS for Windows 7, Windows Server 2012, AD LDS for Windows 8, Windows Server 2012 R2, AD LDS for Windows 8.1, Windows Server 2016 ~~Technical Preview~~, and AD LDS for Windows 10.

3.14 Class domainDNS

This class specifies a Windows NT operating system domain with DNS-based (DC=) naming.

```
cn: Domain-DNS
ldapDisplayName: domainDNS
governsId: 1.2.840.113556.1.5.67
objectClassCategory: 1
rdnAttId: dc
subClassOf: domain
systemMayContain: msDS-EnabledFeature, msDS-USNLastSyncSuccess,
  msDS-Behavior-Version, msDS-AllowedDNSSuffixes, managedBy
systemPossSuperiors: domainDNS
schemaIdGuid: 19195a5b-6da0-11d0-afd3-00c04fd930c9
defaultSecurityDescriptor: D:S:
defaultHidingValue: FALSE
systemOnly: FALSE
defaultObjectCategory: CN=Domain-DNS,<SchemaNCDN>
systemFlags: FLAG_SCHEMA_BASE_OBJECT
```

Version-Specific Behavior: Implemented on ADAM, Windows Server 2008, AD LDS for Windows Vista, Windows Server 2008 R2, AD LDS for Windows 7, Windows Server 2012, AD LDS for Windows 8, Windows Server 2012 R2, AD LDS for Windows 8.1, Windows Server 2016 ~~Technical Preview~~, and AD LDS for Windows 10.

3.15 Class dSUISettings

This class is used to store configuration settings used by the Active Directory Users and Computers snap-in.

```
cn: DS-UI-Settings
ldapDisplayName: dSUISettings
governsId: 1.2.840.113556.1.5.183
objectClassCategory: 1
rdnAttId: cn
subClassOf: top
systemMayContain: msDS-Security-Group-Extra-Classes,
  msDS-Non-Security-Group-Extra-Classes, msDS-FilterContainers,
  dSUIShellMaximum, dSUIAdminNotification, dSUIAdminMaximum
systemPossSuperiors: container
schemaIdGuid: 09b10f14-6f93-11d2-9905-0000f87a57d4
systemOnly: FALSE
defaultObjectCategory: CN=DS-UI-Settings,<SchemaNCDN>
```

Version-Specific Behavior: Implemented on Windows Server 2008, AD LDS for Windows Vista, Windows Server 2008 R2, AD LDS for Windows 7, Windows Server 2012, AD LDS for Windows 8, Windows Server 2012 R2, AD LDS for Windows 8.1, Windows Server 2016 ~~Technical Preview~~, and AD LDS for Windows 10.

3.16 Class dynamicObject

If present in an entry, this class indicates that this entry has a limited lifetime and ~~may~~ disappear automatically when its time-to-live has reached 0. If the client has not supplied a value for the entryTtl attribute, the server will provide one.

```
cn: Dynamic-Object
ldapDisplayName: dynamicObject
governsId: 1.3.6.1.4.1.1466.101.119.2
objectClassCategory: 3
rdnAttId: cn
```

```
subClassOf: top
systemMayContain: msDS-Entry-Time-To-Die, entryTTL
schemaIdGuid: 66d51249-3355-4c1f-b24e-81f252aca23b
defaultSecurityDescriptor: D:S:
defaultHidingValue: TRUE
systemOnly: FALSE
defaultObjectCategory: CN=Dynamic-Object,<SchemaNCDN>
systemFlags: FLAG_SCHEMA_BASE_OBJECT
```

Version-Specific Behavior: Implemented on ADAM, Windows Server 2008, AD LDS for Windows Vista, Windows Server 2008 R2, AD LDS for Windows 7, Windows Server 2012, AD LDS for Windows 8, Windows Server 2012 R2, AD LDS for Windows 8.1, Windows Server 2016 ~~Technical Preview~~, and AD LDS for Windows 10.

3.17 Class foreignSecurityPrincipal

This class specifies the security principal from an external source.

```
cn: Foreign-Security-Principal
ldapDisplayName: foreignSecurityPrincipal
governsId: 1.2.840.113556.1.5.76
objectClassCategory: 1
rdnAttId: cn
subClassOf: top
systemMustContain: objectSid
systemPossSuperiors: container
schemaIdGuid: 89e31c12-8530-11d0-afda-00c04fd930c9
defaultSecurityDescriptor: D:S:
defaultHidingValue: TRUE
systemOnly: FALSE
defaultObjectCategory: CN=Foreign-Security-Principal,<SchemaNCDN>
systemFlags: FLAG_SCHEMA_BASE_OBJECT
```

Version-Specific Behavior: Implemented on ADAM, Windows Server 2008, AD LDS for Windows Vista, Windows Server 2008 R2, AD LDS for Windows 7, Windows Server 2012, AD LDS for Windows 8, Windows Server 2012 R2, AD LDS for Windows 8.1, Windows Server 2016 ~~Technical Preview~~, and AD LDS for Windows 10.

3.18 Class group

This class stores a list of user names. Used to apply security principals on resources.

```
cn: Group
ldapDisplayName: group
governsId: 1.2.840.113556.1.5.8
objectClassCategory: 1
rdnAttId: cn
subClassOf: top
systemAuxiliaryClass: securityPrincipal
systemMustContain: groupType
mayContain: msDS-AzGenericData, msDS-AzObjectGuid,
  msDS-AzApplicationData, msDS-AzLastImportedBizRulePath,
  msDS-AzBizRuleLanguage, msDS-AzBizRule, msDS-AzLDAPQuery
systemMayContain: msDS-NonMembers, primaryGroupToken, member,
  managedBy, desktopProfile
possSuperiors: msDS-AzScope, msDS-AzApplication, msDS-AzAdminManager
systemPossSuperiors: container, organizationalUnit, domainDNS
schemaIdGuid: bf967a9c-0de6-11d0-a285-00aa003049e2
defaultSecurityDescriptor: D:S:
defaultHidingValue: FALSE
systemOnly: FALSE
defaultObjectCategory: CN=Group,<SchemaNCDN>
```

```
systemFlags: FLAG_SCHEMA_BASE_OBJECT
```

Version-Specific Behavior: Implemented on ADAM, Windows Server 2008, AD LDS for Windows Vista, Windows Server 2008 R2, AD LDS for Windows 7, Windows Server 2012, AD LDS for Windows 8, Windows Server 2012 R2, AD LDS for Windows 8.1, Windows Server 2016 ~~Technical Preview~~, and AD LDS for Windows 10.

3.19 Class groupOfNames

Group-Of-Names

```
cn: Group-Of-Names
ldapDisplayName: groupOfNames
governsId: 2.5.6.9
objectClassCategory: 0
rdnAttId: cn
subClassOf: top
systemMustContain: cn
systemMayContain: member, businessCategory, o, ou, owner, seeAlso
systemPossSuperiors: container, organization, locality,
  organizationalUnit
schemaIdGuid: bf967a9d-0de6-11d0-a285-00aa003049e2
defaultSecurityDescriptor: D:S:
defaultHidingValue: TRUE
systemOnly: FALSE
defaultObjectCategory: CN=Group-Of-Names,<SchemaNCDN>
```

Version-Specific Behavior: Implemented on ADAM, Windows Server 2008, AD LDS for Windows Vista, Windows Server 2008 R2, AD LDS for Windows 7, Windows Server 2012, AD LDS for Windows 8, Windows Server 2012 R2, AD LDS for Windows 8.1, Windows Server 2016 ~~Technical Preview~~, and AD LDS for Windows 10.

3.20 Class inetOrgPerson

This class represents people who are associated with an organization in some way.

```
cn: inetOrgPerson
ldapDisplayName: inetOrgPerson
governsId: 2.16.840.1.113730.3.2.2
objectClassCategory: 1
rdnAttId: cn
subClassOf: user
mayContain: audio, businessCategory, carLicense, departmentNumber,
  displayName, employeeNumber, employeeType, givenName, homePhone,
  homePostalAddress, initials, jpegPhoto, labeledURI, mail, manager,
  mobile, o, pager, photo, preferredLanguage, roomNumber, secretary,
  uid, userCertificate, userPKCS12, userSMIMECertificate,
  x500uniqueIdentifier
possSuperiors: container, organizationalUnit, domainDNS
schemaIdGuid: 4828cc14-1437-45bc-9b07-ad6f015e5f28
defaultSecurityDescriptor:
  D:(OA;;CR;ab721a53-1e2f-11d0-9819-00aa0040529b;;PS)S:
showInAdvancedViewOnly: FALSE
defaultHidingValue: FALSE
systemOnly: FALSE
defaultObjectCategory: CN=Person,<SchemaNCDN>
```

Version-Specific Behavior: Implemented on ADAM, Windows Server 2008, AD LDS for Windows Vista, Windows Server 2008 R2, AD LDS for Windows 7, Windows Server 2012, AD LDS for Windows 8,

Windows Server 2012 R2, AD LDS for Windows 8.1, Windows Server 2016 ~~Technical Preview~~, and AD LDS for Windows 10.

3.21 Class `interSiteTransport`

This class specifies an optional attribute of `nTDSConnection` objects. If present, it holds the DN of an `interSiteTransport` object in the `CN=Inter-Site Transports,CN=Sites,CN=Configuration,...` container.

```
cn: Inter-Site-Transport
ldapDisplayName: interSiteTransport
governsId: 1.2.840.113556.1.5.141
objectClassCategory: 1
rdnAttId: cn
subClassOf: top
systemMustContain: transportDLLName, transportAddressAttribute
systemMayContain: replInterval, options
systemPossSuperiors: interSiteTransportContainer
schemaIdGuid: 26d97376-6070-11d1-a9c6-0000f80367c1
defaultSecurityDescriptor: D:S:
defaultHidingValue: TRUE
systemOnly: FALSE
defaultObjectCategory: CN=Inter-Site-Transport,<SchemaNCDN>
systemFlags: FLAG_SCHEMA_BASE_OBJECT
```

Version-Specific Behavior: Implemented on ADAM, Windows Server 2008, AD LDS for Windows Vista, Windows Server 2008 R2, AD LDS for Windows 7, Windows Server 2012, AD LDS for Windows 8, Windows Server 2012 R2, AD LDS for Windows 8.1, Windows Server 2016 ~~Technical Preview~~, and AD LDS for Windows 10.

3.22 Class `interSiteTransportContainer`

This class holds Inter-Site-Transport objects.

```
cn: Inter-Site-Transport-Container
ldapDisplayName: interSiteTransportContainer
governsId: 1.2.840.113556.1.5.140
objectClassCategory: 1
rdnAttId: cn
subClassOf: top
systemPossSuperiors: sitesContainer
schemaIdGuid: 26d97375-6070-11d1-a9c6-0000f80367c1
defaultSecurityDescriptor: D:S:
defaultHidingValue: TRUE
systemOnly: FALSE
defaultObjectCategory: CN=Inter-Site-Transport-Container,<SchemaNCDN>
systemFlags: FLAG_SCHEMA_BASE_OBJECT
```

Version-Specific Behavior: Implemented on ADAM, Windows Server 2008, AD LDS for Windows Vista, Windows Server 2008 R2, AD LDS for Windows 7, Windows Server 2012, AD LDS for Windows 8, Windows Server 2012 R2, AD LDS for Windows 8.1, Windows Server 2016 ~~Technical Preview~~, and AD LDS for Windows 10.

3.23 Class `leaf`

This class is the base class for leaf objects.

```
cn: Leaf
ldapDisplayName: leaf
governsId: 1.2.840.113556.1.5.20
```

```
objectClassCategory: 2
rdnAttId: cn
subClassOf: top
schemaIdGuid: bf967a9e-0de6-11d0-a285-00aa003049e2
defaultSecurityDescriptor: D:S:
defaultHidingValue: TRUE
systemOnly: FALSE
defaultObjectCategory: CN=Leaf,<SchemaNCDN>
systemFlags: FLAG_SCHEMA_BASE_OBJECT
```

Version-Specific Behavior: Implemented on ADAM, Windows Server 2008, AD LDS for Windows Vista, Windows Server 2008 R2, AD LDS for Windows 7, Windows Server 2012, AD LDS for Windows 8, Windows Server 2012 R2, AD LDS for Windows 8.1, Windows Server 2016 ~~Technical Preview~~, and AD LDS for Windows 10.

3.24 Class locality

This class contains a locality, such as a street address, city, and state.

```
cn: Locality
ldapDisplayName: locality
governsId: 2.5.6.3
objectClassCategory: 1
rdnAttId: 1
subClassOf: top
systemMustContain: 1
systemMayContain: street, st, seeAlso, searchGuide
systemPossSuperiors: domainDNS, country, organizationalUnit,
  organization, locality
schemaIdGuid: bf967aa0-0de6-11d0-a285-00aa003049e2
defaultSecurityDescriptor: D:S:
defaultHidingValue: FALSE
systemOnly: FALSE
defaultObjectCategory: CN=Locality,<SchemaNCDN>
systemFlags: FLAG_SCHEMA_BASE_OBJECT
```

Version-Specific Behavior: Implemented on ADAM, Windows Server 2008, AD LDS for Windows Vista, Windows Server 2008 R2, AD LDS for Windows 7, Windows Server 2012, AD LDS for Windows 8, Windows Server 2012 R2, AD LDS for Windows 8.1, Windows Server 2016 ~~Technical Preview~~, and AD LDS for Windows 10.

3.25 Class lostAndFound

This class is a special container for orphaned objects.

```
cn: Lost-And-Found
ldapDisplayName: lostAndFound
governsId: 1.2.840.113556.1.5.139
objectClassCategory: 1
rdnAttId: cn
subClassOf: top
systemMayContain: moveTreeState
systemPossSuperiors: configuration, domainDNS, dMD
schemaIdGuid: 52ab8671-5709-11d1-a9c6-0000f80367c1
defaultSecurityDescriptor: D:S:
defaultHidingValue: TRUE
systemOnly: FALSE
defaultObjectCategory: CN=Lost-And-Found,<SchemaNCDN>
systemFlags: FLAG_SCHEMA_BASE_OBJECT
```

Version-Specific Behavior: Implemented on ADAM, Windows Server 2008, AD LDS for Windows Vista, Windows Server 2008 R2, AD LDS for Windows 7, Windows Server 2012, AD LDS for Windows 8, Windows Server 2012 R2, AD LDS for Windows 8.1, Windows Server 2016 **Technical Preview**, and AD LDS for Windows 10.

3.26 Class msDS-AzAdminManager

This class specifies the root of Authorization Policy store instance.

```
cn: ms-DS-Az-Admin-Manager
ldapDisplayName: msDS-AzAdminManager
governsId: 1.2.840.113556.1.5.234
objectClassCategory: 1
rdnAttId: cn
subClassOf: top
mayContain: msDS-AzGenericData, msDS-AzObjectGuid
systemMayContain: description, msDS-AzMinorVersion,
  msDS-AzMajorVersion, msDS-AzDomainTimeout,
  msDS-AzScriptEngineCacheMax, msDS-AzScriptTimeout,
  msDS-AzGenerateAudits, msDS-AzApplicationData
systemPossSuperiors: container, organizationalUnit, domainDNS
schemaIdGuid: cfeel051-5f28-4bae-a863-5d0cc18a8ed1
defaultSecurityDescriptor: D:(A;;RPWPCRCDCCLCLOCRCWOWSDSDTWSW;;;DA)
  (A;;RPWPCRCDCCLCLOCRCWOWSDSDTWSW;;;SY) (A;;RPLCLOCRC;;;AU)
  (A;;RPWPCRCDCCLCLOCRCWOWSDSDTWSW;;;CO)
defaultHidingValue: TRUE
systemOnly: FALSE
defaultObjectCategory: CN=ms-DS-Az-Admin-Manager,<SchemaNCDN>
```

Version-Specific Behavior: Implemented on ADAM, Windows Server 2008, AD LDS for Windows Vista, Windows Server 2008 R2, AD LDS for Windows 7, Windows Server 2012, AD LDS for Windows 8, Windows Server 2012 R2, AD LDS for Windows 8.1, Windows Server 2016 **Technical Preview**, and AD LDS for Windows 10.

3.27 Class msDS-AzApplication

This class defines an installed instance of an application that is bound to a particular policy store.

```
cn: ms-DS-Az-Application
ldapDisplayName: msDS-AzApplication
governsId: 1.2.840.113556.1.5.235
objectClassCategory: 1
rdnAttId: cn
subClassOf: top
mayContain: msDS-AzGenericData, msDS-AzObjectGuid
systemMayContain: description, msDS-AzApplicationName,
  msDS-AzClassId, msDS-AzApplicationVersion, msDS-AzGenerateAudits,
  msDS-AzApplicationData
systemPossSuperiors: msDS-AzAdminManager
schemaIdGuid: ddf8de9b-cba5-4e12-842e-28d8b66f75ec
defaultSecurityDescriptor: D:(A;;RPWPCRCDCCLCLOCRCWOWSDSDTWSW;;;DA)
  (A;;RPWPCRCDCCLCLOCRCWOWSDSDTWSW;;;SY) (A;;RPLCLOCRC;;;AU)
  (A;;RPWPCRCDCCLCLOCRCWOWSDSDTWSW;;;CO)
defaultHidingValue: TRUE
systemOnly: FALSE
defaultObjectCategory: CN=ms-DS-Az-Application,<SchemaNCDN>
```

Version-Specific Behavior: Implemented on ADAM, Windows Server 2008, AD LDS for Windows Vista, Windows Server 2008 R2, AD LDS for Windows 7, Windows Server 2012, AD LDS for Windows 8, Windows Server 2012 R2, AD LDS for Windows 8.1, Windows Server 2016 **Technical Preview**, and AD LDS for Windows 10.

3.28 Class msDS-AzOperation

This class describes a particular operation supported by an application.

```
cn: ms-DS-Az-Operation
ldapDisplayName: msDS-AzOperation
governsId: 1.2.840.113556.1.5.236
objectClassCategory: 1
rdnAttId: cn
subClassOf: top
systemMustContain: msDS-AzOperationID
mayContain: msDS-AzGenericData, msDS-AzObjectGuid
systemMayContain: description, msDS-AzApplicationData
systemPossSuperiors: container, msDS-AzApplication
schemaIdGuid: 860abe37-9a9b-4fa4-b3d2-b8ace5df9ec5
defaultSecurityDescriptor: D:(A;;RPWPCRCDCCLCLORCWOWSDSDDTSW;;;DA)
(A;;RPWPCRCDCCLCLORCWOWSDSDDTSW;;;SY)(A;;RPLCLORC;;;AU)
(A;;RPWPCRCDCCLCLORCWOWSDSDDTSW;;;CO)
defaultHidingValue: TRUE
systemOnly: FALSE
defaultObjectCategory: CN=ms-DS-Az-Operation,<SchemaNCDN>
```

Version-Specific Behavior: Implemented on ADAM, Windows Server 2008, AD LDS for Windows Vista, Windows Server 2008 R2, AD LDS for Windows 7, Windows Server 2012, AD LDS for Windows 8, Windows Server 2012 R2, AD LDS for Windows 8.1, Windows Server 2016 **Technical Preview**, and AD LDS for Windows 10.

3.29 Class msDS-AzRole

This class defines a set of operations that can be performed by a particular set of users within a particular scope.

```
cn: ms-DS-Az-Role
ldapDisplayName: msDS-AzRole
governsId: 1.2.840.113556.1.5.239
objectClassCategory: 1
rdnAttId: cn
subClassOf: top
mayContain: msDS-AzGenericData, msDS-AzObjectGuid
systemMayContain: description, msDS-MembersForAzRole,
msDS-OperationsForAzRole, msDS-TasksForAzRole, msDS-AzApplicationData
systemPossSuperiors: container, msDS-AzApplication, msDS-AzScope
schemaIdGuid: 8213eac9-9d55-44dc-925c-e9a52b927644
defaultSecurityDescriptor: D:(A;;RPWPCRCDCCLCLORCWOWSDSDDTSW;;;DA)
(A;;RPWPCRCDCCLCLORCWOWSDSDDTSW;;;SY)(A;;RPLCLORC;;;AU)
(A;;RPWPCRCDCCLCLORCWOWSDSDDTSW;;;CO)
defaultHidingValue: TRUE
systemOnly: FALSE
defaultObjectCategory: CN=ms-DS-Az-Role,<SchemaNCDN>
```

Version-Specific Behavior: Implemented on ADAM, Windows Server 2008, AD LDS for Windows Vista, Windows Server 2008 R2, AD LDS for Windows 7, Windows Server 2012, AD LDS for Windows 8, Windows Server 2012 R2, AD LDS for Windows 8.1, Windows Server 2016 **Technical Preview**, and AD LDS for Windows 10.

3.30 Class msDS-AzScope

This class describes a set of objects that is managed by an application.

```
cn: ms-DS-Az-Scope
```



```

ldapDisplayName: msDS-AzScope
governsId: 1.2.840.113556.1.5.237
objectClassCategory: 1
rdnAttId: cn
subClassOf: top
systemMustContain: msDS-AzScopeName
mayContain: msDS-AzGenericData, msDS-AzObjectGuid
systemMayContain: description, msDS-AzApplicationData
systemPossSuperiors: msDS-AzApplication
schemaIdGuid: 4feae054-ce55-47bb-860e-5b12063a51de
defaultSecurityDescriptor: D:(A;;RPWPCRCDCCLCLORCWOWSDDTSW;;;DA)
(A;;RPWPCRCDCCLCLORCWOWSDDTSW;;;SY)(A;;RPLCLORC;;;AU)
(A;;RPWPCRCDCCLCLORCWOWSDDTSW;;;CO)
defaultHidingValue: TRUE
systemOnly: FALSE
defaultObjectCategory: CN=ms-DS-Az-Scope,<SchemaNCDN>

```

Version-Specific Behavior: Implemented on ADAM, Windows Server 2008, AD LDS for Windows Vista, Windows Server 2008 R2, AD LDS for Windows 7, Windows Server 2012, AD LDS for Windows 8, Windows Server 2012 R2, AD LDS for Windows 8.1, Windows Server 2016 ~~Technical Preview~~, and AD LDS for Windows 10.

3.31 Class msDS-AzTask

This class describes a set of operations.

```

cn: ms-DS-Az-Task
ldapDisplayName: msDS-AzTask
governsId: 1.2.840.113556.1.5.238
objectClassCategory: 1
rdnAttId: cn
subClassOf: top
mayContain: msDS-AzGenericData, msDS-AzObjectGuid
systemMayContain: description, msDS-AzBizRule,
msDS-AzBizRuleLanguage, msDS-AzLastImportedBizRulePath,
msDS-AzTaskIsRoleDefinition, msDS-AzApplicationData,
msDS-OperationsForAzTask, msDS-TasksForAzTask
systemPossSuperiors: container, msDS-AzApplication, msDS-AzScope
schemaIdGuid: 1ed3a473-9b1b-418a-bfa0-3a37b95a5306
defaultSecurityDescriptor: D:(A;;RPWPCRCDCCLCLORCWOWSDDTSW;;;DA)
(A;;RPWPCRCDCCLCLORCWOWSDDTSW;;;SY)(A;;RPLCLORC;;;AU)
(A;;RPWPCRCDCCLCLORCWOWSDDTSW;;;CO)
defaultHidingValue: TRUE
systemOnly: FALSE
defaultObjectCategory: CN=ms-DS-Az-Task,<SchemaNCDN>

```

Version-Specific Behavior: Implemented on ADAM, Windows Server 2008, AD LDS for Windows Vista, Windows Server 2008 R2, AD LDS for Windows 7, Windows Server 2012, AD LDS for Windows 8, Windows Server 2012 R2, AD LDS for Windows 8.1, Windows Server 2016 ~~Technical Preview~~, and AD LDS for Windows 10.

3.32 Class msDS-BindableObject

This class specifies an auxiliary class to represent a bindable object. Any user-defined class that represents an entity that can be used to bind to the directory (that is, a user) ~~should include~~ includes this auxiliary class.

```

cn: ms-DS-Bindable-Object
ldapDisplayName: msDS-BindableObject
governsId: 1.2.840.113556.1.5.244
objectClassCategory: 3

```

```

rdnAttId: cn
subClassOf: securityPrincipal
systemMayContain: lastLogonTimestamp, accountExpires,
  msDS-User-Account-Control-Computed, ms-DS-UserAccountAutoLocked,
  msDS-UserPasswordExpired, ms-DS-UserEncryptedTextPasswordAllowed,
  ms-DS-UserPasswordNotRequired, msDS-UserAccountDisabled,
  msDS-UserDontExpirePassword, ntPwdHistory, lockoutTime, badPwdCount,
  badPasswordTime, pwdLastSet, unicodePwd
schemaIdGuid: 89f4a69f-4416-6b49-821d-6e3c4a0ff802
defaultHidingValue: TRUE
systemOnly: FALSE
defaultObjectCategory: CN=ms-DS-Bindable-Object,<SchemaNCDN>
systemFlags: FLAG_SCHEMA_BASE_OBJECT

```

Version-Specific Behavior: Implemented on ADAM, Windows Server 2008, AD LDS for Windows Vista, Windows Server 2008 R2, AD LDS for Windows 7, Windows Server 2012, AD LDS for Windows 8, Windows Server 2012 R2, AD LDS for Windows 8.1, Windows Server 2016 ~~Technical Preview~~, and AD LDS for Windows 10.

3.33 Class msDS-BindProxy

This class specifies an auxiliary class to represent a bind proxy in AD LDS. A bind proxy references a Windows security principal via its objectSid attribute. When a user performs a simple bind against a bind-proxy object, the bind is redirected to the corresponding Windows principal.

```

cn: ms-DS-Bind-Proxy
ldapDisplayName: msDS-BindProxy
governsId: 1.2.840.113556.1.5.245
objectClassCategory: 3
rdnAttId: cn
subClassOf: top
systemMustContain: objectSid
systemMayContain: msDS-PrincipalName
schemaIdGuid: 717532ab-66e9-684d-a62b-8af1e3985e2f
defaultHidingValue: TRUE
systemOnly: FALSE
defaultObjectCategory: CN=ms-DS-Bind-Proxy,<SchemaNCDN>
systemFlags: FLAG_SCHEMA_BASE_OBJECT

```

Version-Specific Behavior: Implemented on ADAM, Windows Server 2008, AD LDS for Windows Vista, Windows Server 2008 R2, AD LDS for Windows 7, Windows Server 2012, AD LDS for Windows 8, Windows Server 2012 R2, AD LDS for Windows 8.1, Windows Server 2016 ~~Technical Preview~~, and AD LDS for Windows 10.

3.34 Class msDS-OptionalFeature

This class defines the configuration object for an optional feature.

```

cn: ms-DS-Optional-Feature
ldapDisplayName: msDS-OptionalFeature
governsId: 1.2.840.113556.1.5.265
objectClassCategory: 1
rdnAttId: cn
subClassOf: top
systemMustContain: msDS-OptionalFeatureFlags, msDS-OptionalFeatureGUID
systemMayContain: msDS-RequiredDomainBehaviorVersion,
  msDS-RequiredForestBehaviorVersion
systemPossSuperiors: container
schemaIdGuid: 44f00041-35af-468b-b20a-6ce8737c580b
defaultSecurityDescriptor: D:(A;;RPLCLORC;;;AU)
(A;;RPWPCLRLCLOCCDCRCWDWOSDDTSW;;;EA)

```

```
(A;;RPWPCRLCLOCCDCRCWDWOSDDTSW;;;CO)
(A;;RPWPCRLCLOCCDCRCWDWOSDDTSW;;;SY)
defaultHidingValue: TRUE
systemOnly: TRUE
defaultObjectCategory: CN=ms-DS-Optional-Feature,<SchemaNCDN>
systemFlags: FLAG_SCHEMA_BASE_OBJECT
```

Version-Specific Behavior: Implemented on Windows Server 2008 R2, AD LDS for Windows 7, Windows Server 2012, AD LDS for Windows 8, Windows Server 2012 R2, AD LDS for Windows 8.1, Windows Server 2016 **Technical Preview**, and AD LDS for Windows 10.

3.35 Class msDS-QuotaContainer

This class specifies a special container that holds all quota specifications for the directory database.

```
cn: ms-DS-Quota-Container
ldapDisplayName: msDS-QuotaContainer
governsId: 1.2.840.113556.1.5.242
objectClassCategory: 1
rdnAttId: cn
subClassOf: top
systemMustContain: cn
systemMayContain: msDS-TopQuotaUsage, msDS-QuotaUsed,
  msDS-QuotaEffective, msDS-TombstoneQuotaFactor, msDS-DefaultQuota
systemPossSuperiors: configuration, domainDNS
schemaIdGuid: da83fc4f-076f-4aea-b4dc-8f4dab9b5993
defaultSecurityDescriptor: D:S:
defaultHidingValue: TRUE
systemOnly: FALSE
defaultObjectCategory: CN=ms-DS-Quota-Container,<SchemaNCDN>
systemFlags: FLAG_SCHEMA_BASE_OBJECT
```

Version-Specific Behavior: Implemented on ADAM, Windows Server 2008, AD LDS for Windows Vista, Windows Server 2008 R2, AD LDS for Windows 7, Windows Server 2012, AD LDS for Windows 8, Windows Server 2012 R2, AD LDS for Windows 8.1, Windows Server 2016 **Technical Preview**, and AD LDS for Windows 10.

3.36 Class msDS-QuotaControl

This class is used to represent quota specifications for the directory database.

```
cn: ms-DS-Quota-Control
ldapDisplayName: msDS-QuotaControl
governsId: 1.2.840.113556.1.5.243
objectClassCategory: 1
rdnAttId: cn
subClassOf: top
systemMustContain: msDS-QuotaAmount, msDS-QuotaTrustee, cn
systemPossSuperiors: msDS-QuotaContainer
schemaIdGuid: de91fc26-bd02-4b52-ae26-795999e96fc7
defaultSecurityDescriptor: D:S:
defaultHidingValue: TRUE
systemOnly: FALSE
defaultObjectCategory: CN=ms-DS-Quota-Control,<SchemaNCDN>
systemFlags: FLAG_SCHEMA_BASE_OBJECT
```

Version-Specific Behavior: Implemented on ADAM, Windows Server 2008, AD LDS for Windows Vista, Windows Server 2008 R2, AD LDS for Windows 7, Windows Server 2012, AD LDS for Windows 8, Windows Server 2012 R2, AD LDS for Windows 8.1, Windows Server 2016 **Technical Preview**, and AD LDS for Windows 10.

3.37 Class msDS-ServiceConnectionPointPublicationService

This class stores configuration options for the SCP publication service in AD LDS.

```
cn: ms-DS-Service-Connection-Point-Publication-Service
ldapDisplayName: msDS-ServiceConnectionPointPublicationService
governsId: 1.2.840.113556.1.5.247
objectClassCategory: 1
rdnAttId: cn
subClassOf: top
systemMayContain: Enabled, msDS-SCPContainer,
  msDS-DisableForInstances, keywords
systemPossSuperiors: nTDSservice
schemaIdGuid: d33f5da6-b009-7e48-8268-b2305529e933
defaultSecurityDescriptor: D:S:
defaultHidingValue: TRUE
systemOnly: TRUE
defaultObjectCategory:
  CN=ms-DS-Service-Connection-Point-Publication-Service,<SchemaNCDN>
```

Version-Specific Behavior: Implemented on ADAM, Windows Server 2008, AD LDS for Windows Vista, Windows Server 2008 R2, AD LDS for Windows 7, Windows Server 2012, AD LDS for Windows 8, Windows Server 2012 R2, AD LDS for Windows 8.1, Windows Server 2016 ~~Technical Preview~~, and AD LDS for Windows 10.

3.38 Class nTDSConnection

This class specifies a connection from a remote domain controller (DC).

```
cn: NTDS-Connection
ldapDisplayName: nTDSConnection
governsId: 1.2.840.113556.1.5.71
objectClassCategory: 1
rdnAttId: cn
subClassOf: leaf
systemMustContain: options, fromServer, enabledConnection
systemMayContain: transportType, schedule, mS-DS-ReplicatesNReason,
  generatedConnection
systemPossSuperiors: nTDSDSA
schemaIdGuid: 19195a60-6da0-11d0-afd3-00c04fd930c9
defaultSecurityDescriptor: D:S:
defaultHidingValue: TRUE
systemOnly: FALSE
defaultObjectCategory: CN=NTDS-Connection,<SchemaNCDN>
systemFlags: FLAG_SCHEMA_BASE_OBJECT
```

Version-Specific Behavior: Implemented on ADAM, Windows Server 2008, AD LDS for Windows Vista, Windows Server 2008 R2, AD LDS for Windows 7, Windows Server 2012, AD LDS for Windows 8, Windows Server 2012 R2, AD LDS for Windows 8.1, Windows Server 2016 ~~Technical Preview~~, and AD LDS for Windows 10.

3.39 Class nTDSDSA

This class represents the Active Directory DSA process on the server.

```
cn: NTDS-DSA
ldapDisplayName: nTDSDSA
governsId: 1.2.840.113556.1.5.7000.47
objectClassCategory: 1
rdnAttId: cn
```

```

subClassOf: applicationSettings
systemMayContain: msDS-DefaultNamingContext, serverReference,
  msDS-RetiredReplNCsSignatures, retiredReplDSASignatures,
  queryPolicyObject, options, networkAddress, msDS-ServiceAccount,
  msDS-ServiceAccountDNSDomain, msDS-PortSSL, msDS-PortLDAP,
  msDS-ReplicationEpoch, msDS-HasInstantiatedNCs, msDS-hasMasterNCs,
  msDS-HasDomainNCs, msDS-Behavior-Version, managedBy,
  lastBackupRestorationTime, invocationId, hasPartialReplicaNCs,
  hasMasterNCs, dMDLocation, msDS-EnabledFeature
systemPossSuperiors: organization, server
schemaIdGuid: f0f8ffab-1191-11d0-a060-00aa006c33ed
defaultSecurityDescriptor: D:S:
defaultHidingValue: TRUE
systemOnly: TRUE
defaultObjectCategory: CN=NTDS-DSA,<SchemaNCN>
systemFlags: FLAG_SCHEMA_BASE_OBJECT

```

Version-Specific Behavior: Implemented on ADAM, Windows Server 2008, AD LDS for Windows Vista, Windows Server 2008 R2, AD LDS for Windows 7, Windows Server 2012, AD LDS for Windows 8, Windows Server 2012 R2, AD LDS for Windows 8.1, Windows Server 2016 ~~Technical Preview~~, and AD LDS for Windows 10.

3.40 Class nTDSservice

This class is used for an NTDS services object, which contains information about the configuration of the directory service forest. This object is kept in the CN=Directory Service,CN=Windows NT,CN=Services,CN=Configuration,... container.

```

cn: NTDS-Service
ldapDisplayName: nTDSservice
governsId: 1.2.840.113556.1.5.72
objectClassCategory: 1
rdnAttId: cn
subClassOf: top
systemMayContain: msDS-DeletedObjectLifetime, tombstoneLifetime,
  replTopologyStayOfExecution, msDS-Other-Settings, garbageCollPeriod,
  dSHeuristics
systemPossSuperiors: container
schemaIdGuid: 19195a5f-6da0-11d0-afd3-00c04fd930c9
defaultSecurityDescriptor: D:S:
defaultHidingValue: TRUE
systemOnly: FALSE
defaultObjectCategory: CN=NTDS-Service,<SchemaNCN>
systemFlags: FLAG_SCHEMA_BASE_OBJECT

```

Version-Specific Behavior: Implemented on ADAM, Windows Server 2008, AD LDS for Windows Vista, Windows Server 2008 R2, AD LDS for Windows 7, Windows Server 2012, AD LDS for Windows 8, Windows Server 2012 R2, AD LDS for Windows 8.1, Windows Server 2016 ~~Technical Preview~~, and AD LDS for Windows 10.

3.41 Class nTDSsiteSettings

This class specifies a container for holding all Active Directory site-specific settings.

```

cn: NTDS-Site-Settings
ldapDisplayName: nTDSsiteSettings
governsId: 1.2.840.113556.1.5.69
objectClassCategory: 1
rdnAttId: cn
subClassOf: applicationSiteSettings
systemMayContain: schedule, queryPolicyObject, options,

```

```

msDS-Preferred-GC-Site, managedBy, interSiteTopologyRenew,
interSiteTopologyGenerator, interSiteTopologyFailover
systemPossSuperiors: site
schemaIdGuid: 19195a5d-6da0-11d0-afd3-00c04fd930c9
defaultSecurityDescriptor: D:S:
defaultHidingValue: TRUE
systemOnly: FALSE
defaultObjectCategory: CN=NTDS-Site-Settings,<SchemaNCDN>
systemFlags: FLAG_SCHEMA_BASE_OBJECT

```

Version-Specific Behavior: Implemented on ADAM, Windows Server 2008, AD LDS for Windows Vista, Windows Server 2008 R2, AD LDS for Windows 7, Windows Server 2012, AD LDS for Windows 8, Windows Server 2012 R2, AD LDS for Windows 8.1, Windows Server 2016 **Technical Preview**, and AD LDS for Windows 10.

3.42 Class organizationalPerson

This class is used for objects that contain organizational information about a user, such as the employee number, department, manager, title, and office address.

```

cn: Organizational-Person
ldapDisplayName: organizationalPerson
governsId: 2.5.6.7
objectClassCategory: 0
rdnAttId: cn
subClassOf: person
mayContain: homePostalAddress, houseIdentifier
systemMayContain: streetAddress, assistant, company, countryCode,
c, department, destinationIndicator, division, mail, employeeID,
facsimileTelephoneNumber, generationQualifier, givenName, initials,
internationalISDNNumber, l, thumbnailLogo, manager, o, ou,
middleName, personalTitle, otherFacsimileTelephoneNumber, homePhone,
otherHomePhone, otherIpPhone, ipPhone,
primaryInternationalISDNNumber, otherMobile, mobile, otherTelephone,
otherPager, pager, physicalDeliveryOfficeName, thumbnailPhoto,
postOfficeBox, postalAddress, postalCode, preferredDeliveryMethod,
registeredAddress, st, street, teletexTerminalIdentifier,
telexNumber, primaryTelexNumber, co, title, comment, x121Address
systemPossSuperiors: container, organization, organizationalUnit
schemaIdGuid: bf967aa4-0de6-11d0-a285-00aa003049e2
defaultSecurityDescriptor: D:S:
defaultHidingValue: TRUE
systemOnly: FALSE
defaultObjectCategory: CN=Person,<SchemaNCDN>

```

Version-Specific Behavior: Implemented on ADAM, Windows Server 2008, AD LDS for Windows Vista, Windows Server 2008 R2, AD LDS for Windows 7, Windows Server 2012, AD LDS for Windows 8, Windows Server 2012 R2, AD LDS for Windows 8.1, Windows Server 2016 **Technical Preview**, and AD LDS for Windows 10.

3.43 Class organization

This class stores information about a company or organization.

```

cn: Organization
ldapDisplayName: organization
governsId: 2.5.6.4
objectClassCategory: 1
rdnAttId: o
subClassOf: top
systemMustContain: o

```

```

systemMayContain: x121Address, userPassword, telexNumber,
  teletexTerminalIdentifier, telephoneNumber, street, st, seeAlso,
  searchGuide, registeredAddress, preferredDeliveryMethod, postalCode,
  postalAddress, postOfficeBox, physicalDeliveryOfficeName, 1,
  internationalISDNNumber, facsimileTelephoneNumber,
  destinationIndicator, businessCategory
systemPossSuperiors: locality, country, domainDNS
schemaIdGuid: bf967aa3-0de6-11d0-a285-00aa003049e2
defaultSecurityDescriptor: D:S:
defaultHidingValue: FALSE
systemOnly: FALSE
defaultObjectCategory: CN=Organization,<SchemaNCDN>
systemFlags: FLAG_SCHEMA_BASE_OBJECT

```

Version-Specific Behavior: Implemented on ADAM, Windows Server 2008, AD LDS for Windows Vista, Windows Server 2008 R2, AD LDS for Windows 7, Windows Server 2012, AD LDS for Windows 8, Windows Server 2012 R2, AD LDS for Windows 8.1, Windows Server 2016 ~~Technical Preview~~, and AD LDS for Windows 10.

3.44 Class organizationalUnit

This class specifies a container for storing users, computers, and other account objects.

```

cn: Organizational-Unit
ldapDisplayName: organizationalUnit
governsId: 2.5.6.5
objectClassCategory: 1
rdnAttId: ou
subClassOf: top
systemMustContain: ou
systemMayContain: x121Address, userPassword, uPNSuffixes, co,
  telexNumber, teletexTerminalIdentifier, telephoneNumber, street, st,
  seeAlso, searchGuide, registeredAddress, preferredDeliveryMethod,
  postalCode, postalAddress, postOfficeBox,
  physicalDeliveryOfficeName, managedBy, thumbnailLogo, 1,
  internationalISDNNumber, facsimileTelephoneNumber,
  destinationIndicator, desktopProfile, defaultGroup, countryCode, c,
  businessCategory
systemPossSuperiors: country, organization, organizationalUnit,
  domainDNS
schemaIdGuid: bf967aa5-0de6-11d0-a285-00aa003049e2
defaultSecurityDescriptor: D:S:
defaultHidingValue: FALSE
systemOnly: FALSE
defaultObjectCategory: CN=Organizational-Unit,<SchemaNCDN>
systemFlags: FLAG_SCHEMA_BASE_OBJECT

```

Version-Specific Behavior: Implemented on ADAM, Windows Server 2008, AD LDS for Windows Vista, Windows Server 2008 R2, AD LDS for Windows 7, Windows Server 2012, AD LDS for Windows 8, Windows Server 2012 R2, AD LDS for Windows 8.1, Windows Server 2016 ~~Technical Preview~~, and AD LDS for Windows 10.

3.45 Class person

This class contains personal information about a user.

```

cn: Person
ldapDisplayName: person
governsId: 2.5.6.6
objectClassCategory: 0
rdnAttId: cn
subClassOf: top

```

```
systemMustContain: cn
mayContain: attributeCertificateAttribute
systemMayContain: seeAlso, serialNumber, sn, telephoneNumber,
  userPassword
systemPossSuperiors: container, organizationalUnit
schemaIdGuid: bf967aa7-0de6-11d0-a285-00aa003049e2
defaultSecurityDescriptor: D:S:
defaultHidingValue: TRUE
systemOnly: FALSE
defaultObjectCategory: CN=Person,<SchemaNCDN>
```

Version-Specific Behavior: Implemented on ADAM, Windows Server 2008, AD LDS for Windows Vista, Windows Server 2008 R2, AD LDS for Windows 7, Windows Server 2012, AD LDS for Windows 8, Windows Server 2012 R2, AD LDS for Windows 8.1, Windows Server 2016 ~~Technical Preview~~, and AD LDS for Windows 10.

3.46 Class queryPolicy

This class holds administrative limits for LDAP server resources for sorted and paged results.

```
cn: Query-Policy
ldapDisplayName: queryPolicy
governsId: 1.2.840.113556.1.5.106
objectClassCategory: 1
rdnAttId: cn
subClassOf: top
systemMayContain: LDAPIPDenyList, LDAPAdminLimits
systemPossSuperiors: container
schemaIdGuid: 83cc7075-cca7-11d0-afff-0000f80367c1
defaultSecurityDescriptor: D:S:
defaultHidingValue: TRUE
systemOnly: FALSE
defaultObjectCategory: CN=Query-Policy,<SchemaNCDN>
systemFlags: FLAG_SCHEMA_BASE_OBJECT
```

Version-Specific Behavior: Implemented on ADAM, Windows Server 2008, AD LDS for Windows Vista, Windows Server 2008 R2, AD LDS for Windows 7, Windows Server 2012, AD LDS for Windows 8, Windows Server 2012 R2, AD LDS for Windows 8.1, Windows Server 2016 ~~Technical Preview~~, and AD LDS for Windows 10.

3.47 Class securityPrincipal

This class contains the security information for an object.

```
cn: Security-Principal
ldapDisplayName: securityPrincipal
governsId: 1.2.840.113556.1.5.6
objectClassCategory: 3
rdnAttId: cn
subClassOf: top
systemMustContain: objectSid
systemMayContain: supplementalCredentials, tokenGroups,
  nTSecurityDescriptor
schemaIdGuid: bf967ab0-0de6-11d0-a285-00aa003049e2
defaultHidingValue: TRUE
systemOnly: FALSE
defaultObjectCategory: CN=Security-Principal,<SchemaNCDN>
systemFlags: FLAG_SCHEMA_BASE_OBJECT
```


Version-Specific Behavior: Implemented on ADAM, Windows Server 2008, AD LDS for Windows Vista, Windows Server 2008 R2, AD LDS for Windows 7, Windows Server 2012, AD LDS for Windows 8, Windows Server 2012 R2, AD LDS for Windows 8.1, Windows Server 2016 ~~Technical Preview~~, and AD LDS for Windows 10.

3.48 Class server

This class represents a server computer within a site.

```
cn: Server
ldapDisplayName: server
governsId: 1.2.840.113556.1.5.17
objectClassCategory: 1
rdnAttId: cn
subClassOf: top
systemMayContain: mailAddress, serverReference, managedBy,
  nETBIOSName, dNSHostName, bridgeheadTransportList
systemPossSuperiors: serversContainer
schemaIdGuid: bf967a92-0de6-11d0-a285-00aa003049e2
defaultSecurityDescriptor: D:S:
defaultHidingValue: TRUE
systemOnly: FALSE
defaultObjectCategory: CN=Server,<SchemaNCDN>
systemFlags: FLAG_SCHEMA_BASE_OBJECT
```

Version-Specific Behavior: Implemented on ADAM, Windows Server 2008, AD LDS for Windows Vista, Windows Server 2008 R2, AD LDS for Windows 7, Windows Server 2012, AD LDS for Windows 8, Windows Server 2012 R2, AD LDS for Windows 8.1, Windows Server 2016 ~~Technical Preview~~, and AD LDS for Windows 10.

3.49 Class serversContainer

This class holds server objects within a site.

```
cn: Servers-Container
ldapDisplayName: serversContainer
governsId: 1.2.840.113556.1.5.7000.48
objectClassCategory: 1
rdnAttId: cn
subClassOf: top
systemPossSuperiors: site
schemaIdGuid: f780acc0-56f0-11d1-a9c6-0000f80367c1
defaultSecurityDescriptor: D:S:
defaultHidingValue: TRUE
systemOnly: FALSE
defaultObjectCategory: CN=Servers-Container,<SchemaNCDN>
systemFlags: FLAG_SCHEMA_BASE_OBJECT
```

Version-Specific Behavior: Implemented on ADAM, Windows Server 2008, AD LDS for Windows Vista, Windows Server 2008 R2, AD LDS for Windows 7, Windows Server 2012, AD LDS for Windows 8, Windows Server 2012 R2, AD LDS for Windows 8.1, Windows Server 2016 ~~Technical Preview~~, and AD LDS for Windows 10.

3.50 Class site

This class specifies a container for storing server objects. This class represents a physical location containing computers; it is used to manage replication.

```

cn: Site
ldapDisplayName: site
governsId: 1.2.840.113556.1.5.31
objectClassCategory: 1
rdnAttId: cn
subClassOf: top
systemMayContain: msDS-BridgeHeadServersUsed, notificationList,
  managedBy, location
systemPossSuperiors: sitesContainer
schemaIdGuid: bf967ab3-0de6-11d0-a285-00aa003049e2
defaultSecurityDescriptor: D:S:
defaultHidingValue: TRUE
systemOnly: FALSE
defaultObjectCategory: CN=Site,<SchemaNCDN>
systemFlags: FLAG_SCHEMA_BASE_OBJECT

```

Version-Specific Behavior: Implemented on ADAM, Windows Server 2008, AD LDS for Windows Vista, Windows Server 2008 R2, AD LDS for Windows 7, Windows Server 2012, AD LDS for Windows 8, Windows Server 2012 R2, AD LDS for Windows 8.1, Windows Server 2016 ~~Technical Preview~~, and AD LDS for Windows 10.

3.51 Class siteLink

This object represents the connection between two sites.

```

cn: Site-Link
ldapDisplayName: siteLink
governsId: 1.2.840.113556.1.5.147
objectClassCategory: 1
rdnAttId: cn
subClassOf: top
systemMustContain: siteList
systemMayContain: schedule, replInterval, options, cost
systemPossSuperiors: interSiteTransport
schemaIdGuid: d50c2cde-8951-11d1-aebc-0000f80367c1
defaultSecurityDescriptor: D:S:
defaultHidingValue: FALSE
systemOnly: FALSE
defaultObjectCategory: CN=Site-Link,<SchemaNCDN>
systemFlags: FLAG_SCHEMA_BASE_OBJECT

```

Version-Specific Behavior: Implemented on ADAM, Windows Server 2008, AD LDS for Windows Vista, Windows Server 2008 R2, AD LDS for Windows 7, Windows Server 2012, AD LDS for Windows 8, Windows Server 2012 R2, AD LDS for Windows 8.1, Windows Server 2016 ~~Technical Preview~~, and AD LDS for Windows 10.

3.52 Class siteLinkBridge

This class specifies an object for tracking the site links that are transitively connected.

```

cn: Site-Link-Bridge
ldapDisplayName: siteLinkBridge
governsId: 1.2.840.113556.1.5.148
objectClassCategory: 1
rdnAttId: cn
subClassOf: top
systemMustContain: siteLinkList
systemPossSuperiors: interSiteTransport
schemaIdGuid: d50c2cdf-8951-11d1-aebc-0000f80367c1
defaultSecurityDescriptor: D:S:
defaultHidingValue: FALSE

```

```
systemOnly: FALSE
defaultObjectCategory: CN=Site-Link-Bridge,<SchemaNCDN>
systemFlags: FLAG_SCHEMA_BASE_OBJECT
```

Version-Specific Behavior: Implemented on ADAM, Windows Server 2008, AD LDS for Windows Vista, Windows Server 2008 R2, AD LDS for Windows 7, Windows Server 2012, AD LDS for Windows 8, Windows Server 2012 R2, AD LDS for Windows 8.1, Windows Server 2016 ~~Technical Preview~~, and AD LDS for Windows 10.

3.53 Class sitesContainer

This class specifies a container for storing site objects. Located in the configuration naming context.

```
cn: Sites-Container
ldapDisplayName: sitesContainer
governsId: 1.2.840.113556.1.5.107
objectClassCategory: 1
rdnAttId: cn
subClassOf: top
systemPossSuperiors: configuration
schemaIdGuid: 7a4117da-cd67-11d0-afff-0000f80367c1
defaultSecurityDescriptor: D:S:
defaultHidingValue: TRUE
systemOnly: FALSE
defaultObjectCategory: CN=Sites-Container,<SchemaNCDN>
systemFlags: FLAG_SCHEMA_BASE_OBJECT
```

Version-Specific Behavior: Implemented on ADAM, Windows Server 2008, AD LDS for Windows Vista, Windows Server 2008 R2, AD LDS for Windows 7, Windows Server 2012, AD LDS for Windows 8, Windows Server 2012 R2, AD LDS for Windows 8.1, Windows Server 2016 ~~Technical Preview~~, and AD LDS for Windows 10.

3.54 Class subnet

This class represents a specific subnet in the network to which servers and workstations are attached.

```
cn: Subnet
ldapDisplayName: subnet
governsId: 1.2.840.113556.1.5.96
objectClassCategory: 1
rdnAttId: cn
subClassOf: top
systemMayContain: siteObject, location
systemPossSuperiors: subnetContainer
schemaIdGuid: b7b13124-b82e-11d0-afee-0000f80367c1
defaultSecurityDescriptor: D:S:
defaultHidingValue: TRUE
systemOnly: FALSE
defaultObjectCategory: CN=Subnet,<SchemaNCDN>
systemFlags: FLAG_SCHEMA_BASE_OBJECT
```

Version-Specific Behavior: Implemented on ADAM, Windows Server 2008, AD LDS for Windows Vista, Windows Server 2008 R2, AD LDS for Windows 7, Windows Server 2012, AD LDS for Windows 8, Windows Server 2012 R2, AD LDS for Windows 8.1, Windows Server 2016 ~~Technical Preview~~, and AD LDS for Windows 10.

3.55 Class subnetContainer

This class specifies a container for holding all subnet objects.

```
cn: Subnet-Container
ldapDisplayName: subnetContainer
governsId: 1.2.840.113556.1.5.95
objectClassCategory: 1
rdnAttId: cn
subClassOf: top
systemPossSuperiors: sitesContainer
schemaIdGuid: b7b13125-b82e-11d0-afee-0000f80367c1
defaultSecurityDescriptor: D:S:
defaultHidingValue: TRUE
systemOnly: FALSE
defaultObjectCategory: CN=Subnet-Container,<SchemaNCDN>
systemFlags: FLAG_SCHEMA_BASE_OBJECT
```

Version-Specific Behavior: Implemented on ADAM, Windows Server 2008, AD LDS for Windows Vista, Windows Server 2008 R2, AD LDS for Windows 7, Windows Server 2012, AD LDS for Windows 8, Windows Server 2012 R2, AD LDS for Windows 8.1, Windows Server 2016 ~~Technical Preview~~, and AD LDS for Windows 10.

3.56 Class subSchema

This class contains the schema definition.

```
cn: SubSchema
ldapDisplayName: subSchema
governsId: 2.5.20.1
objectClassCategory: 1
rdnAttId: cn
subClassOf: top
systemMayContain: objectClasses, modifyTimeStamp, extendedClassInfo,
  extendedAttributeInfo, dITContentRules, attributeTypes
systemPossSuperiors: dMD
schemaIdGuid: 5a8b3261-c38d-11d1-bbc9-0080c76670c0
defaultSecurityDescriptor: D:S:
defaultHidingValue: TRUE
systemOnly: TRUE
defaultObjectCategory: CN=SubSchema,<SchemaNCDN>
systemFlags: FLAG_SCHEMA_BASE_OBJECT | FLAG_DOMAIN_DISALLOW_RENAME
```

Version-Specific Behavior: Implemented on ADAM, Windows Server 2008, AD LDS for Windows Vista, Windows Server 2008 R2, AD LDS for Windows 7, Windows Server 2012, AD LDS for Windows 8, Windows Server 2012 R2, AD LDS for Windows 8.1, Windows Server 2016 ~~Technical Preview~~, and AD LDS for Windows 10.

3.57 Class syncEngineAuxConfiguration

ms-DS-Sync-Engine-Aux-Configuration

```
cn: ms-DS-Sync-Engine-Aux-Configuration
ldapDisplayName: syncEngineAuxConfiguration
governsId: 1.2.840.113556.1.4.1891
objectClassCategory: 3
rdnAttId: cn
subClassOf: top
systemMayContain: configurationFile
systemOnly: FALSE
```

```
defaultObjectCategory: CN=ms-DS-Sync-Engine-Aux-Configuration,  
<SchemaNCDN>
```

Version-Specific Behavior: Implemented on ADAM, Windows Server 2008, AD LDS for Windows Vista, Windows Server 2008 R2, AD LDS for Windows 7, Windows Server 2012, AD LDS for Windows 8, Windows Server 2012 R2, AD LDS for Windows 8.1, Windows Server 2016 ~~Technical Preview~~, and AD LDS for Windows 10.

3.58 Class syncEngineAuxObject

ms-DS-Sync-Engine-Aux-Object

```
cn: ms-DS-Sync-Engine-Aux-Object  
ldapDisplayName: syncEngineAuxObject  
governsId: 1.2.840.113556.1.4.1890  
objectClassCategory: 3  
rdnAttId: cn  
subClassOf: top  
systemMayContain: nonIndexedMetadata, lastAgedChange,  
configurationFileGuid, sourceObjectGuid  
systemOnly: FALSE  
defaultObjectCategory: CN=ms-DS-Sync-Engine-Aux-Object,<SchemaNCDN>
```

Version-Specific Behavior: Implemented on ADAM, Windows Server 2008, AD LDS for Windows Vista, Windows Server 2008 R2, AD LDS for Windows 7, Windows Server 2012, AD LDS for Windows 8, Windows Server 2012 R2, AD LDS for Windows 8.1, Windows Server 2016 ~~Technical Preview~~, and AD LDS for Windows 10.

3.59 Class top

This class is the top-level class from which all classes are derived.

```
cn: Top  
ldapDisplayName: top  
governsId: 2.5.6.0  
objectClassCategory: 2  
rdnAttId: cn  
subClassOf: top  
systemMustContain: objectClass, objectCategory, nTSecurityDescriptor,  
instanceType  
mayContain: directReports, ownerBL, msDS-TasksForAzRoleBL,  
msDS-OperationsForAzRoleBL, msDS-TasksForAzTaskBL,  
msDS-OperationsForAzTaskBL  
systemMayContain: msDS-EnabledFeatureBL, msDS-LastKnownRDN,  
msDS-LocalEffectiveRecycleTime, msDS-LocalEffectiveDeletionTime,  
isRecycled, url, wWWWHomePage, whenCreated, whenChanged,  
wellKnownObjects, wbemPath, uSNSource, uSNLastObjRem, USNIntersite,  
uSNDALastObjRemoved, uSNCreated, uSNChanged, systemFlags,  
subSchemaSubEntry, subRefs, structuralObjectClass, siteObjectBL,  
serverReferenceBL, sDRightsEffective, revision, repsTo, repsFrom,  
replUpToDateVector, replPropertyMetaData, name, queryPolicyBL,  
proxyAddresses, proxiedObjectName, possibleInferiors,  
partialAttributeSet, partialAttributeDeletionList,  
otherWellKnownObjects, objectVersion, objectGUID, distinguishedName,  
msDS-DisableForInstancesBL, msDS-ServiceAccountBL,  
msDS-ReplValueMetaData, msDS-ReplAttributeMetaData,  
msDS-NCReplOutboundNeighbors, msDS-NCReplInboundNeighbors,  
msDS-NCReplCursors, msDS-NonMembersBL, msDS-MembersForAzRoleBL,  
msDS-masteredBy, msDS-DefaultNamingContextBL, ms-DS-ConsistencyGuid,  
ms-DS-ConsistencyChildCount, msDS-Approx-Immed-Subordinates,  
modifyTimeStamp, masteredBy, managedObjects, lastKnownParent,  
memberOf, isDeleted, isCriticalSystemObject, showInAdvancedViewOnly,
```

```

fSMORoleOwner, fromEntry, dSASignature, dSCorePropagationData,
displayName, description, createTimeStamp, cn, canonicalName,
bridgeheadServerListBL, allowedChildClassesEffective,
allowedChildClasses, allowedAttributesEffective, allowedAttributes,
adminDisplayName, adminDescription, msds-memberOfTransitive,
msds-memberTransitive, msDS-parentdistname, msDS-ReplValueMetaDataExt
systemPossSuperiors: lostAndFound
schemaIdGuid: bf967ab7-0de6-11d0-a285-00aa003049e2
defaultSecurityDescriptor: D:S:
defaultHidingValue: TRUE
systemOnly: TRUE
defaultObjectCategory: CN=Top,<SchemaNCDN>
systemFlags: FLAG_SCHEMA_BASE_OBJECT

```

Version-Specific Behavior: Implemented on ADAM, Windows Server 2008, AD LDS for Windows Vista, Windows Server 2008 R2, AD LDS for Windows 7, Windows Server 2012, AD LDS for Windows 8, Windows Server 2012 R2, AD LDS for Windows 8.1, Windows Server 2016 ~~Technical Preview~~, and AD LDS for Windows 10.

3.60 Class userProxy

This class is the sample class for bind proxy implementation.

```

cn: User-Proxy
ldapDisplayName: userProxy
governsId: 1.2.840.113556.1.5.246
objectClassCategory: 1
rdnAttId: cn
subClassOf: top
systemAuxiliaryClass: msDS-BindProxy
systemMayContain: userPrincipalName
possSuperiors: organization, container, organizationalUnit, domainDNS
schemaIdGuid: 60d6186f-f3b6-4898-b0ad-6535afc07620
defaultSecurityDescriptor:
  D: (OA;;CR;ab721a53-1e2f-11d0-9819-00aa0040529b;;PS)S:
defaultHidingValue: TRUE
systemOnly: FALSE
defaultObjectCategory: CN=User-Proxy,<SchemaNCDN>

```

Version-Specific Behavior: Implemented on ADAM, Windows Server 2008, AD LDS for Windows Vista, Windows Server 2008 R2, AD LDS for Windows 7, Windows Server 2012, AD LDS for Windows 8, Windows Server 2012 R2, AD LDS for Windows 8.1, Windows Server 2016 ~~Technical Preview~~, and AD LDS for Windows 10.

3.61 Class userProxyFull

This class is the sample user proxy class with the same properties as the native user class.

```

cn: User-Proxy-Full
ldapDisplayName: userProxyFull
governsId: 1.2.840.113556.1.5.248
objectClassCategory: 1
rdnAttId: cn
subClassOf: organizationalPerson
systemAuxiliaryClass: msDS-BindProxy
mayContain: audio, carLicense, departmentNumber, displayName,
employeeNumber, employeeType, givenName, homePostalAddress,
jpegPhoto, labeledURI, photo, preferredLanguage, roomNumber,
secretary, uid, userPKCS12, userSMIMECertificate,
x500uniqueIdentifier
systemMayContain: defaultClassStore, dynamicLDAPServer,
lastLogonTimestamp, preferredOU, userParameters, userPrincipalName,

```

```
userCertificate, businessCategory, homePhone, initials, mail,
manager, mobile, o, pager
systemPossSuperiors: domainDNS, organizationalUnit
schemaIdGuid: 2210527a-eb01-4ff0-b883-186f40a92979
defaultSecurityDescriptor:
D: (OA;;CR;ab721a53-1e2f-11d0-9819-00aa0040529b;;PS)S:
defaultHidingValue: FALSE
systemOnly: FALSE
defaultObjectCategory: CN=Person,<SchemaNCDN>
```

Version-Specific Behavior: Implemented on ADAM, Windows Server 2008, AD LDS for Windows Vista, Windows Server 2008 R2, AD LDS for Windows 7, Windows Server 2012, AD LDS for Windows 8, Windows Server 2012 R2, AD LDS for Windows 8.1, Windows Server 2016 **Technical Preview**, and AD LDS for Windows 10.

3.62 Class user

This class is used to store information about an employee or contractor who works for an organization. It is also possible to apply this class to long-term visitors.

```
cn: User
ldapDisplayName: user
governsId: 1.2.840.113556.1.5.9
objectClassCategory: 1
rdnAttId: cn
subClassOf: organizationalPerson
systemAuxiliaryClass: msDS-BindableObject, securityPrincipal
mayContain: audio, carLicense, departmentNumber, displayName,
employeeNumber, employeeType, givenName, homePostalAddress,
jpegPhoto, labeledURI, photo, preferredLanguage, roomNumber,
secretary, uid, userPKCS12, userSMIMECertificate,
x500uniqueIdentifier
systemMayContain: defaultClassStore, dynamicLDAPServer,
lastLogonTimestamp, preferredOU, userParameters, userPrincipalName,
userCertificate, businessCategory, homePhone, initials, mail,
manager, mobile, o, pager
systemPossSuperiors: domainDNS, organizationalUnit
schemaIdGuid: bf967aba-0de6-11d0-a285-00aa003049e2
defaultSecurityDescriptor:
D: (OA;;CR;ab721a53-1e2f-11d0-9819-00aa0040529b;;PS)S:
defaultHidingValue: FALSE
systemOnly: FALSE
defaultObjectCategory: CN=Person,<SchemaNCDN>
```

Version-Specific Behavior: Implemented on ADAM, Windows Server 2008, AD LDS for Windows Vista, Windows Server 2008 R2, AD LDS for Windows 7, Windows Server 2012, AD LDS for Windows 8, Windows Server 2012 R2, AD LDS for Windows 8.1, Windows Server 2016 **Technical Preview**, and AD LDS for Windows 10.

4 Change Tracking

No table of changes is available. The document is either new or has had no changes since its last release.

5 Index

A

Active Directory Lightweight Directory Services attributes 15
Active Directory Lightweight Directory Services classes 164
Attributes 15

C

Change tracking 192
Classes 164

I

Introduction 13

S

Schema - Active Directory Lightweight Directory Services
attributes 15
classes 164

T

Tracking changes 192