

[MS-ADSC]: Active Directory Schema Classes

Active Directory Schema Classes contains a list of the objects of type "class" that exist in the Active Directory schema. Active Directory and all associated terms and concepts are described in the document titled "Active Directory Technical Specification", which has the following normative reference:

[MS-ADTS] Microsoft Corporation, "[Active Directory Technical Specification](#)".

Note This document is not intended to stand on its own; it is intended to act as an appendix to the Active Directory Technical Specification, as specified in the normative reference shown above. For details about the Active Directory schema, see [\[MS-ADTS\]](#) section 3.1.1.2 (Active Directory Schema).

Note The object definitions in this document are also available for download in LDAP Data Interchange Format (LDIF) at the following location: [\[MSFT-ADSCHEMA\]](#).

Intellectual Property Rights Notice for Open Specifications Documentation

- **Technical Documentation.** Microsoft publishes Open Specifications documentation for protocols, file formats, languages, standards as well as overviews of the interaction among each of these technologies.
- **Copyrights.** This documentation is covered by Microsoft copyrights. Regardless of any other terms that are contained in the terms of use for the Microsoft website that hosts this documentation, you may make copies of it in order to develop implementations of the technologies described in the Open Specifications and may distribute portions of it in your implementations using these technologies or your documentation as necessary to properly document the implementation. You may also distribute in your implementation, with or without modification, any schema, IDL's, or code samples that are included in the documentation. This permission also applies to any documents that are referenced in the Open Specifications.
- **No Trade Secrets.** Microsoft does not claim any trade secret rights in this documentation.
- **Patents.** Microsoft has patents that may cover your implementations of the technologies described in the Open Specifications. Neither this notice nor Microsoft's delivery of the documentation grants any licenses under those or any other Microsoft patents. However, a given Open Specification may be covered by Microsoft [Open Specification Promise](#) or the [Community Promise](#). If you would prefer a written license, or if the technologies described in the Open Specifications are not covered by the Open Specifications Promise or Community Promise, as applicable, patent licenses are available by contacting iplg@microsoft.com.
- **Trademarks.** The names of companies and products contained in this documentation may be covered by trademarks or similar intellectual property rights. This notice does not grant any licenses under those rights. For a list of Microsoft trademarks, visit www.microsoft.com/trademarks.
- **Fictitious Names.** The example companies, organizations, products, domain names, email addresses, logos, people, places, and events depicted in this documentation are fictitious. No

association with any real company, organization, product, domain name, email address, logo, person, place, or event is intended or should be inferred.

Reservation of Rights. All other rights are reserved, and this notice does not grant any rights other than specifically described above, whether by implication, estoppel, or otherwise.

Tools. The Open Specifications do not require the use of Microsoft programming tools or programming environments in order for you to develop an implementation. If you have access to Microsoft programming tools and environments you are free to take advantage of them. Certain Open Specifications are intended for use in conjunction with publicly available standard specifications and network programming art, and assumes that the reader either is familiar with the aforementioned material or has immediate access to it.

Revision Summary

Date	Revision History	Revision Class	Comments
02/22/2007	0.01		MCPP Milestone 3 Initial Availability
06/01/2007	1.0	Major	Updated and revised the technical content.
07/03/2007	2.0	Major	Added DFS content.
07/20/2007	2.1	Minor	Enhanced descriptions for MSMQ attributes
08/10/2007	2.1.1	Editorial	Revised and edited the technical content.
09/28/2007	2.1.2	Editorial	Revised and edited the technical content.
10/23/2007	2.1.3	Editorial	Revised and edited the technical content.
11/30/2007	3.0	Major	Added objects.
01/25/2008	3.0.1	Editorial	Revised and edited the technical content.
03/14/2008	3.0.2	Editorial	Revised and edited the technical content.
05/16/2008	3.0.3	Editorial	Revised and edited the technical content.
06/20/2008	3.1	Minor	Updated the technical content.
07/25/2008	3.1.1	Editorial	Revised and edited the technical content.
08/29/2008	4.0	Major	Updated and revised the technical content.
10/24/2008	5.0	Major	Updated and revised the technical content.
12/05/2008	6.0	Major	Updated and revised the technical content.
01/16/2009	6.0.1	Editorial	Revised and edited the technical content.
02/27/2009	6.0.2	Editorial	Revised and edited the technical content.
04/10/2009	7.0	Major	Updated and revised the technical content.

Date	Revision History	Revision Class	Comments
05/22/2009	8.0	Major	Updated and revised the technical content.
07/02/2009	8.1	Minor	Updated the technical content.
08/14/2009	8.1.1	Editorial	Revised and edited the technical content.
09/25/2009	9.0	Major	Updated and revised the technical content.
11/06/2009	9.1	Minor	Updated the technical content.
12/18/2009	10.0	Major	Updated and revised the technical content.
01/29/2010	10.1	Minor	Updated the technical content.
03/12/2010	10.1.1	Editorial	Revised and edited the technical content.
04/23/2010	11.0	Major	Updated and revised the technical content.
06/04/2010	12.0	Major	Updated and revised the technical content.
07/16/2010	12.0	No change	No changes to the meaning, language, or formatting of the technical content.
08/27/2010	13.0	Major	Significantly changed the technical content.
10/08/2010	14.0	Major	Significantly changed the technical content.
11/19/2010	14.0	No change	No changes to the meaning, language, or formatting of the technical content.
01/07/2011	14.1	Minor	Clarified the meaning of the technical content.
02/11/2011	14.1	No change	No changes to the meaning, language, or formatting of the technical content.
03/25/2011	14.1	No change	No changes to the meaning, language, or formatting of the technical content.
05/06/2011	14.2	Minor	Clarified the meaning of the technical content.
06/17/2011	14.3	Minor	Clarified the meaning of the technical content.
09/23/2011	14.3	No change	No changes to the meaning, language, or formatting of the technical content.
12/16/2011	15.0	Major	Significantly changed the technical content.
03/30/2012	15.0	No change	No changes to the meaning, language, or formatting of the technical content.
07/12/2012	16.0	Major	Significantly changed the technical content.
10/25/2012	16.1	Minor	Clarified the meaning of the technical content.

Date	Revision History	Revision Class	Comments
01/31/2013	16.1	No change	No changes to the meaning, language, or formatting of the technical content.
08/08/2013	17.0	Major	Significantly changed the technical content.
11/14/2013	17.0	No change	No changes to the meaning, language, or formatting of the technical content.
02/13/2014	17.0	No change	No changes to the meaning, language, or formatting of the technical content.

Contents

1	References	11
2	Classes	12
2.1	Class account	12
2.2	Class aCSPolicy	12
2.3	Class aCSResourceLimits	13
2.4	Class aCSSubnet	13
2.5	Class addressBookContainer.....	14
2.6	Class addressTemplate	14
2.7	Class applicationEntity.....	15
2.8	Class applicationProcess	15
2.9	Class applicationSettings	16
2.10	Class applicationSiteSettings	16
2.11	Class applicationVersion.....	17
2.12	Class attributeSchema	17
2.13	Class bootableDevice	18
2.14	Class builtinDomain.....	18
2.15	Class categoryRegistration	19
2.16	Class certificationAuthority	19
2.17	Class classRegistration	20
2.18	Class classSchema	20
2.19	Class classStore.....	21
2.20	Class comConnectionPoint.....	21
2.21	Class computer	22
2.22	Class configuration	23
2.23	Class connectionPoint	23
2.24	Class contact	24
2.25	Class container	24
2.26	Class controlAccessRight.....	25
2.27	Class country	25
2.28	Class cRLDistributionPoint	26
2.29	Class crossRef	26
2.30	Class crossRefContainer.....	27
2.31	Class device	27
2.32	Class dfsConfiguration	28
2.33	Class dHCPClass	28
2.34	Class displaySpecifier	29
2.35	Class displayTemplate	29
2.36	Class dMD.....	30
2.37	Class dnsNode	30
2.38	Class dnsZone	31
2.39	Class document	32
2.40	Class documentSeries.....	32
2.41	Class domain.....	33
2.42	Class domainDNS.....	33
2.43	Class domainPolicy.....	34
2.44	Class domainRelatedObject	35
2.45	Class dSA.....	35
2.46	Class dSUISettings.....	36
2.47	Class dynamicObject	36

2.48	Class fileLinkTracking	37
2.49	Class fileLinkTrackingEntry	37
2.50	Class foreignSecurityPrincipal	38
2.51	Class friendlyCountry	38
2.52	Class fTDfs	39
2.53	Class group	39
2.54	Class groupOfNames	40
2.55	Class groupOfUniqueNames	41
2.56	Class groupPolicyContainer	41
2.57	Class ieee802Device	42
2.58	Class indexServerCatalog	42
2.59	Class inetOrgPerson	42
2.60	Class infrastructureUpdate	43
2.61	Class intellimirrorGroup	44
2.62	Class intellimirrorSCP	44
2.63	Class interSiteTransport	45
2.64	Class interSiteTransportContainer	45
2.65	Class ipHost	46
2.66	Class ipNetwork	46
2.67	Class ipProtocol	47
2.68	Class ipsecBase	47
2.69	Class ipsecFilter	48
2.70	Class ipsecISAKMPPolicy	48
2.71	Class ipsecNegotiationPolicy	48
2.72	Class ipsecNFA	49
2.73	Class ipsecPolicy	49
2.74	Class ipService	50
2.75	Class leaf	50
2.76	Class licensingSiteSettings	51
2.77	Class linkTrackObjectMoveTable	51
2.78	Class linkTrackOMTEntry	52
2.79	Class linkTrackVolEntry	52
2.80	Class linkTrackVolumeTable	53
2.81	Class locality	53
2.82	Class lostAndFound	53
2.83	Class mailRecipient	54
2.84	Class meeting	55
2.85	Class ms-net-ieee-80211-GroupPolicy	55
2.86	Class ms-net-ieee-8023-GroupPolicy	56
2.87	Class mS-SQL-OLAPCube	56
2.88	Class mS-SQL-OLAPDatabase	57
2.89	Class mS-SQL-OLAPServer	57
2.90	Class mS-SQL-SQLDatabase	58
2.91	Class mS-SQL-SQLPublication	58
2.92	Class mS-SQL-SQLRepository	59
2.93	Class mS-SQL-SQLServer	59
2.94	Class msAuthz-CentralAccessPolicies	60
2.95	Class msAuthz-CentralAccessPolicy	60
2.96	Class msAuthz-CentralAccessRule	61
2.97	Class msAuthz-CentralAccessRules	61
2.98	Class msCOM-Partition	62
2.99	Class msCOM-PartitionSet	62
2.100	Class msDFS-DeletedLinkv2	62

2.101	Class msDFS-Linkv2	63
2.102	Class msDFS-NamespaceAnchor	63
2.103	Class msDFS-Namepacev2	64
2.104	Class msDFSR-Connection	64
2.105	Class msDFSR-Content	65
2.106	Class msDFSR-ContentSet	65
2.107	Class msDFSR-GlobalSettings	66
2.108	Class msDFSR-LocalSettings	66
2.109	Class msDFSR-Member	67
2.110	Class msDFSR-ReplicationGroup	67
2.111	Class msDFSR-Subscriber	68
2.112	Class msDFSR-Subscription	69
2.113	Class msDFSR-Topology	69
2.114	Class msDNS-ServerSettings	70
2.115	Class msDS-App-Configuration	70
2.116	Class msDS-AppData	71
2.117	Class msDS-AuthNPolicies	71
2.118	Class msDS-AuthNPolicy	71
2.119	Class msDS-AuthNPolicySilo	72
2.120	Class msDS-AuthNPolicySilos	72
2.121	Class msDS-AzAdminManager	73
2.122	Class msDS-AzApplication	73
2.123	Class msDS-AzOperation	74
2.124	Class msDS-AzRole	74
2.125	Class msDS-AzScope	75
2.126	Class msDS-AzTask	75
2.127	Class msDS-ClaimsTransformationPolicies	76
2.128	Class msDS-ClaimsTransformationPolicyType	76
2.129	Class msDS-ClaimType	77
2.130	Class msDS-ClaimTypePropertyBase	77
2.131	Class msDS-ClaimTypes	78
2.132	Class msDS-CloudExtensions	78
2.133	Class msDS-Device	79
2.134	Class msDS-DeviceContainer	79
2.135	Class msDS-DeviceRegistrationService	80
2.136	Class msDS-DeviceRegistrationServiceContainer	80
2.137	Class msDS-GroupManagedServiceAccount	80
2.138	Class msDS-ManagedServiceAccount	81
2.139	Class msDS-OptionalFeature	82
2.140	Class msDS-PasswordSettings	82
2.141	Class msDS-PasswordSettingsContainer	83
2.142	Class msDS-QuotaContainer	83
2.143	Class msDS-QuotaControl	84
2.144	Class msDS-ResourceProperties	84
2.145	Class msDS-ResourceProperty	85
2.146	Class msDS-ResourcePropertyList	85
2.147	Class msDS-ValueType	86
2.148	Class msExchConfigurationContainer	86
2.149	Class msFVE-RecoveryInformation	86
2.150	Class msieeee80211-Policy	87
2.151	Class msImaging-PostScanProcess	87
2.152	Class msImaging-PSPs	88
2.153	Class msKds-ProvRootKey	88

2.154	Class msKds-ProvServerConfiguration.....	89
2.155	Class msMQ-Custom-Recipient.....	89
2.156	Class msMQ-Group.....	90
2.157	Class mSMQConfiguration.....	90
2.158	Class mSMQEnterpriseSettings.....	91
2.159	Class mSMQMigratedUser.....	91
2.160	Class mSMQQueue.....	92
2.161	Class mSMQSettings.....	92
2.162	Class mSMQSiteLink.....	93
2.163	Class msPKI-Enterprise-Oid.....	93
2.164	Class msPKI-Key-Recovery-Agent.....	94
2.165	Class msPKI-PrivateKeyRecoveryAgent.....	94
2.166	Class msPrint-ConnectionPolicy.....	95
2.167	Class msSFU30DomainInfo.....	95
2.168	Class msSFU30MailAliases.....	96
2.169	Class msSFU30NetId.....	96
2.170	Class msSFU30NetworkUser.....	97
2.171	Class msSFU30NISMapConfig.....	97
2.172	Class msSPP-ActivationObject.....	98
2.173	Class msSPP-ActivationObjectsContainer.....	98
2.174	Class msTAPI-RtConference.....	98
2.175	Class msTAPI-RtPerson.....	99
2.176	Class msTPM-InformationObject.....	99
2.177	Class msTPM-InformationObjectsContainer.....	100
2.178	Class msWMI-IntRangeParam.....	100
2.179	Class msWMI-IntSetParam.....	101
2.180	Class msWMI-MergeablePolicyTemplate.....	101
2.181	Class msWMI-ObjectEncoding.....	102
2.182	Class msWMI-PolicyTemplate.....	102
2.183	Class msWMI-PolicyType.....	103
2.184	Class msWMI-RangeParam.....	103
2.185	Class msWMI-RealRangeParam.....	104
2.186	Class msWMI-Rule.....	104
2.187	Class msWMI-ShadowObject.....	105
2.188	Class msWMI-SimplePolicyTemplate.....	105
2.189	Class msWMI-Som.....	106
2.190	Class msWMI-StringSetParam.....	106
2.191	Class msWMI-UIntRangeParam.....	107
2.192	Class msWMI-UIntSetParam.....	107
2.193	Class msWMI-UnknownRangeParam.....	108
2.194	Class msWMI-WMIGPO.....	108
2.195	Class nisMap.....	109
2.196	Class nisNetgroup.....	109
2.197	Class nisObject.....	110
2.198	Class nTDSConnection.....	110
2.199	Class nTDSDSA.....	111
2.200	Class nTDSDSARO.....	111
2.201	Class nTDSService.....	112
2.202	Class nTDSsiteSettings.....	112
2.203	Class nTFRSMember.....	113
2.204	Class nTFRSReplicaSet.....	113
2.205	Class nTFRSSettings.....	114
2.206	Class nTFRSSubscriber.....	114

2.207	Class nTFRSSubscriptions.....	115
2.208	Class oncRpc	115
2.209	Class organization	116
2.210	Class organizationalPerson	116
2.211	Class organizationalRole.....	117
2.212	Class organizationalUnit	118
2.213	Class packageRegistration	118
2.214	Class person	119
2.215	Class physicalLocation	119
2.216	Class pKICertificateTemplate	120
2.217	Class pKIErollmentService	120
2.218	Class posixAccount	121
2.219	Class posixGroup	121
2.220	Class printQueue.....	122
2.221	Class queryPolicy	123
2.222	Class remoteMailRecipient	123
2.223	Class remoteStorageServicePoint	123
2.224	Class residentialPerson	124
2.225	Class rFC822LocalPart.....	124
2.226	Class rIDManager.....	125
2.227	Class rIDSet	126
2.228	Class room	126
2.229	Class rpcContainer	127
2.230	Class rpcEntry	127
2.231	Class rpcGroup	127
2.232	Class rpcProfile	128
2.233	Class rpcProfileElement.....	128
2.234	Class rpcServer.....	129
2.235	Class rpcServerElement	129
2.236	Class rRASAdministrationConnectionPoint.....	130
2.237	Class rRASAdministrationDictionary	130
2.238	Class samDomain.....	131
2.239	Class samDomainBase	132
2.240	Class samServer	133
2.241	Class secret.....	133
2.242	Class securityObject	134
2.243	Class securityPrincipal.....	134
2.244	Class server	135
2.245	Class serversContainer.....	135
2.246	Class serviceAdministrationPoint	136
2.247	Class serviceClass	136
2.248	Class serviceConnectionPoint	137
2.249	Class serviceInstance	137
2.250	Class shadowAccount.....	138
2.251	Class simpleSecurityObject.....	138
2.252	Class site	139
2.253	Class siteLink.....	139
2.254	Class siteLinkBridge.....	140
2.255	Class sitesContainer	140
2.256	Class storage.....	140
2.257	Class subnet	141
2.258	Class subnetContainer	141
2.259	Class subSchema	142

2.260	Class top.....	142
2.261	Class trustedDomain.....	143
2.262	Class typeLibrary	144
2.263	Class user	144
2.264	Class volume	146
3	Change Tracking.....	148
4	Index	149

1 References

References to Microsoft Open Specification documents do not include a publishing year because links are to the latest version of the documents, which are updated frequently. References to other documents include a publishing year when one is available.

We conduct frequent surveys of the normative references to assure their continued availability. If you have any issue with finding a normative reference, please contact dochelp@microsoft.com. We will assist you in finding the relevant information.

[MS-ADTS] Microsoft Corporation, "[Active Directory Technical Specification](#)".

[MS-DTYP] Microsoft Corporation, "[Windows Data Types](#)".

[MS-GLOS] Microsoft Corporation, "[Windows Protocols Master Glossary](#)".

[MSFT-ADSCHEMA] Microsoft Corporation, "Combined Active Directory Schema Classes and Attributes for Windows Server", February 2011, <http://www.microsoft.com/downloads/en/details.aspx?displaylang=en&FamilyID=da2fc73a-3d35-484c-9bea-f023dcb7275>

[RFC1035] Mockapetris, P., "Domain Names - Implementation and Specification", STD 13, RFC 1035, November 1987, <http://www.ietf.org/rfc/rfc1035.txt>

[RFC1831] Srinivasan, R., "RPC: Remote Procedure Call Protocol Specification Version 2", RFC 1831, August 1995, <http://www.ietf.org/rfc/rfc1831.txt>

[RFC2181] Elz, R., and Bush, R., "Clarifications to the DNS Specification", RFC 2181, July 1997, <http://www.ietf.org/rfc/rfc2181.txt>

[RFC2849] Good, G., "The LDAP Data Interchange Format (LDIF) - Technical Specification", RFC 2849, June 2000, <http://www.ietf.org/rfc/rfc2849.txt>

[RFC4524] Zeilenga, K., "COSINE LDAP/X.500 Schema", RFC 4524, June 2006, <http://www.ietf.org/rfc/rfc4524.txt>

2 Classes

The following sections specify the classes in the Active Directory schema.

These sections normatively specify the schema definition of each class and version-specific behavior of those schema definitions (such as when the class was added to the schema). Additionally, as an aid to the reader some of the sections include informative notes about how the class can be used.

Note In the following class definitions, "<SchemaNCDN>" is the DN of the schema NC. For more information, see [\[MS-ADTS\]](#) section 3.1.1.1.7.

Note Lines of text in the class definitions that are excessively long have been "folded" in accordance with [\[RFC2849\]](#) Note 2.

2.1 Class account

This class is not used. It is included for compatibility with [\[RFC4524\]](#) section 3.1.

```
cn: account
ldapDisplayName: account
governsId: 0.9.2342.19200300.100.4.5
objectClassCategory: 1
rdnAttId: cn
subClassOf: top
mayContain: uid, host, ou, o, l, seeAlso, description
possSuperiors: organizationalUnit, container
schemaIdGuid: 2628a46a-a6ad-4ae0-b854-2b12d9fe6f9e
defaultSecurityDescriptor: D: (A;;RPWPCRCDCCLCLOLORCOWWSDSDTDTSW;;;DA)
(A;;RPWPCRCDCCLCLOLORCOWWSDSDTDTSW;;;SY) (A;;RPLCLORC;;;AU)
defaultHidingValue: TRUE
systemOnly: FALSE
defaultObjectCategory: CN=account,<SchemaNCDN>
```

Version-Specific Behavior: Implemented on Windows Server 2003 operating system, Windows Server 2003 R2 operating system, Windows Server 2008 operating system, Windows Server 2008 R2 operating system, Windows Server 2012 operating system, and Windows Server 2012 R2 operating system.

2.2 Class aCSPolicy

The Admission Control Service (ACS) bandwidth allocation policy for a user or profile.

```
cn: ACS-Policy
ldapDisplayName: aCSPolicy
governsId: 1.2.840.113556.1.5.137
objectClassCategory: 1
rdnAttId: cn
subClassOf: top
systemMayContain: aCSTotalNoOfFlows, aCSTimeOfDay, aCSServiceType,
aCSPriority, aCSPermissionBits, aCSMinimumDelayVariation,
aCSMinimumLatency, aCSMaximumSDUSize, aCSMinimumPolicedSize,
aCSMaxTokenRatePerFlow, aCSMaxTokenBucketPerFlow,
aCSMaxPeakBandwidthPerFlow, aCSMaxDurationPerFlow,
aCSMaxAggregatePeakRatePerUser, aCSIdentityName, aCSDirection,
aCSAggregateTokenRatePerUser
systemPossSuperiors: container
```

```
schemaIdGuid: 7f561288-5301-11d1-a9c5-0000f80367c1
defaultSecurityDescriptor: D: (A;;RPWPCRCDCCLCLOLORCWOWSDDDTDTSW;;;DA)
(A;;RPWPCRCDCCLCLOLORCWOWSDDDTDTSW;;;SY) (A;;RPLCLORC;;;AU)
defaultHidingValue: TRUE
systemOnly: FALSE
defaultObjectCategory: CN=ACS-Policy,<SchemaNCDN>
systemFlags: FLAG_SCHEMA_BASE_OBJECT
```

Version-Specific Behavior: Implemented on Windows 2000 Server operating system, Windows Server 2003 operating system, Windows Server 2003 R2 operating system, Windows Server 2008 operating system, Windows Server 2008 R2 operating system, Windows Server 2012 operating system, and Windows Server 2012 R2 operating system.

2.3 Class aCSResourceLimits

Contains reservable resource limits for a subnet. These limits can be for each ACS service type or for all service types.

```
cn: ACS-Resource-Limits
ldapDisplayName: aCSResourceLimits
governsId: 1.2.840.113556.1.5.191
objectClassCategory: 1
rdnAttId: cn
subClassOf: top
systemMayContain: aCSMaxTokenRatePerFlow, aCSServiceType,
aCSMaxPeakBandwidthPerFlow, aCSMaxPeakBandwidth,
aCSAllocableRSVPBandwidth
systemPossSuperiors: container
schemaIdGuid: 2e899b04-2834-11d3-91d4-0000f87a57d4
defaultSecurityDescriptor: D: (A;;RPWPCRCDCCLCLOLORCWOWSDDDTDTSW;;;DA)
(A;;RPWPCRCDCCLCLOLORCWOWSDDDTDTSW;;;SY) (A;;RPLCLORC;;;AU)
defaultHidingValue: TRUE
systemOnly: FALSE
defaultObjectCategory: CN=ACS-Resource-Limits,<SchemaNCDN>
systemFlags: FLAG_SCHEMA_BASE_OBJECT
```

Version-Specific Behavior: Implemented on Windows 2000 Server operating system, Windows Server 2003 operating system, Windows Server 2003 R2 operating system, Windows Server 2008 operating system, Windows Server 2008 R2 operating system, Windows Server 2012 operating system, and Windows Server 2012 R2 operating system.

2.4 Class aCSSubnet

Contains configuration parameters for an ACS server.

```
cn: ACS-Subnet
ldapDisplayName: aCSSubnet
governsId: 1.2.840.113556.1.5.138
objectClassCategory: 1
rdnAttId: cn
subClassOf: top
systemMayContain: aCSServerList, aCSRSVPLogFilesLocation,
aCSRSVPAccountFilesLocation, aCSNonReservedTxSize,
aCSNonReservedTxLimit, aCSNonReservedTokenSize,
aCSNonReservedPeakRate, aCSNonReservedMinPolicedSize,
```

```

aCSNonReservedMaxSDUSize, aCSMaxTokenRatePerFlow,
aCSMaxSizeOfRSVPLogFile, aCSMaxSizeOfRSVPAccountFile,
aCSMaxPeakBandwidthPerFlow, aCSMaxPeakBandwidth, aCSMaxNoOfLogFiles,
aCSMaxNoOfAccountFiles, aCSMaxDurationPerFlow, aCSEventLogLevel,
aCSEnableRSVPMessageLogging, aCSEnableRSVPAccounting,
aCSEnableACSService, aCSDSBMRefresh, aCSDSBMPriority,
aCSDSBMDeadTime, aCSCacheTimeout, aCSAllocableRSVPBandwidth
systemPossSuperiors: container
schemaIdGuid: 7f561289-5301-11d1-a9c5-0000f80367c1
defaultSecurityDescriptor: D: (A;;RPWPCRCDCCLCLORCWOWSDSDTWSW;;;DA)
(A;;RPWPCRCDCCLCLORCWOWSDSDTWSW;;;SY) (A;;RPLCLORC;;;AU)
defaultHidingValue: TRUE
systemOnly: FALSE
defaultObjectCategory: CN=ACS-Subnet,<SchemaNCDN>
systemFlags: FLAG_SCHEMA_BASE_OBJECT

```

Version-Specific Behavior: Implemented on Windows 2000 Server operating system, Windows Server 2003 operating system, Windows Server 2003 R2 operating system, Windows Server 2008 operating system, Windows Server 2008 R2 operating system, Windows Server 2012 operating system, and Windows Server 2012 R2 operating system.

2.5 Class addressBookContainer

A container for holding members of an address-book view.

```

cn: Address-Book-Container
ldapDisplayName: addressBookContainer
governsId: 1.2.840.113556.1.5.125
objectClassCategory: 1
rdnAttId: cn
subClassOf: top
systemMustContain: displayName
systemMayContain: purportedSearch
systemPossSuperiors: addressBookContainer, configuration
schemaIdGuid: 3e74f60f-3e73-11d1-a9c0-0000f80367c1
defaultSecurityDescriptor: D: (A;;RPWPCRCDCCLCLORCWOWSDSDTWSW;;;DA)
(A;;RPWPCRCDCCLCLORCWOWSDSDTWSW;;;SY) (A;;RPLCLORC;;;AU)
(OA;;CR;a1990816-4298-11d1-ade2-00c04fd8d5cd;;;AU)
defaultHidingValue: TRUE
systemOnly: FALSE
defaultObjectCategory: CN=Address-Book-Container,<SchemaNCDN>
systemFlags: FLAG_SCHEMA_BASE_OBJECT

```

Version-Specific Behavior: Implemented on Windows 2000 Server operating system, Windows Server 2003 operating system, Windows Server 2003 R2 operating system, Windows Server 2008 operating system, Windows Server 2008 R2 operating system, Windows Server 2012 operating system, and Windows Server 2012 R2 operating system.

2.6 Class addressTemplate

Specifies information for a display template.

```

cn: Address-Template
ldapDisplayName: addressTemplate
governsId: 1.2.840.113556.1.3.58

```

```

objectClassCategory: 1
rdnAttId: cn
subClassOf: displayTemplate
systemMustContain: displayName
systemMayContain: proxyGenerationEnabled, perRecipDialogDisplayTable,
  perMsgDialogDisplayTable, addressType, addressSyntax
systemPossSuperiors: container
schemaIdGuid: 5fd4250a-1262-11d0-a060-00aa006c33ed
defaultSecurityDescriptor: D: (A;;RPWPCRCDCCLCLOCRCWOWSDDTSW;;;DA)
  (A;;RPWPCRCDCCLCLOCRCWOWSDDTSW;;;SY) (A;;RPLCLORC;;;AU)
defaultHidingValue: TRUE
systemOnly: FALSE
defaultObjectCategory: CN=Address-Template,<SchemaNCDN>

```

Version-Specific Behavior: Implemented on Windows 2000 Server operating system, Windows Server 2003 operating system, Windows Server 2003 R2 operating system, Windows Server 2008 operating system, Windows Server 2008 R2 operating system, Windows Server 2012 operating system, and Windows Server 2012 R2 operating system.

2.7 Class applicationEntity

The X.500 base class for applicationEntity.

```

cn: Application-Entity
ldapDisplayName: applicationEntity
governsId: 2.5.6.12
objectClassCategory: 1
rdnAttId: cn
subClassOf: top
systemMustContain: presentationAddress, cn
systemMayContain: supportedApplicationContext, seeAlso, ou, o, l
systemPossSuperiors: applicationProcess, organizationalUnit,
  container
schemaIdGuid: 3fdfee4f-47f4-11d1-a9c3-0000f80367c1
defaultSecurityDescriptor: D: (A;;RPWPCRCDCCLCLOCRCWOWSDDTSW;;;DA)
  (A;;RPWPCRCDCCLCLOCRCWOWSDDTSW;;;SY) (A;;RPLCLORC;;;AU)
defaultHidingValue: TRUE
systemOnly: FALSE
defaultObjectCategory: CN=Application-Entity,<SchemaNCDN>
systemFlags: FLAG_SCHEMA_BASE_OBJECT

```

Version-Specific Behavior: Implemented on Windows 2000 Server operating system, Windows Server 2003 operating system, Windows Server 2003 R2 operating system, Windows Server 2008 operating system, Windows Server 2008 R2 operating system, Windows Server 2012 operating system, and Windows Server 2012 R2 operating system.

2.8 Class applicationProcess

The X.500 base class for applicationProcess.

```

cn: Application-Process
ldapDisplayName: applicationProcess
governsId: 2.5.6.11
objectClassCategory: 1
rdnAttId: cn

```

```
subClassOf: top
systemMustContain: cn
systemMayContain: seeAlso, ou, l
systemPossSuperiors: organizationalUnit, organization, container,
computer
schemaIdGuid: 5fd4250b-1262-11d0-a060-00aa006c33ed
defaultSecurityDescriptor: D: (A;;RPWPCRCDCCLCLORCWOWSDDTSW;;;DA)
(A;;RPWPCRCDCCLCLORCWOWSDDTSW;;;SY) (A;;RPLCLORC;;;AU)
defaultHidingValue: TRUE
systemOnly: TRUE
defaultObjectCategory: CN=Application-Process,<SchemaNCDN>
systemFlags: FLAG_SCHEMA_BASE_OBJECT
```

Version-Specific Behavior: Implemented on Windows 2000 Server operating system, Windows Server 2003 operating system, Windows Server 2003 R2 operating system, Windows Server 2008 operating system, Windows Server 2008 R2 operating system, Windows Server 2012 operating system, and Windows Server 2012 R2 operating system.

2.9 Class applicationSettings

A base class for server-specific application settings.

```
cn: Application-Settings
ldapDisplayName: applicationSettings
governsId: 1.2.840.113556.1.5.7000.49
objectClassCategory: 2
rdnAttId: cn
subClassOf: top
systemMayContain: notificationList, msDS-Settings, applicationName
systemPossSuperiors: server
schemaIdGuid: f780acc1-56f0-11d1-a9c6-0000f80367c1
defaultHidingValue: TRUE
systemOnly: FALSE
defaultObjectCategory: CN=Application-Settings,<SchemaNCDN>
systemFlags: FLAG_SCHEMA_BASE_OBJECT
```

Version-Specific Behavior: Implemented on Windows 2000 Server operating system, Windows Server 2003 operating system, Windows Server 2003 R2 operating system, Windows Server 2008 operating system, Windows Server 2008 R2 operating system, Windows Server 2012 operating system, and Windows Server 2012 R2 operating system.

2.10 Class applicationSiteSettings

The container that holds all site-specific settings.

```
cn: Application-Site-Settings
ldapDisplayName: applicationSiteSettings
governsId: 1.2.840.113556.1.5.68
objectClassCategory: 2
rdnAttId: cn
subClassOf: top
systemMayContain: notificationList, applicationName
systemPossSuperiors: site
schemaIdGuid: 19195a5c-6da0-11d0-afd3-00c04fd930c9
defaultSecurityDescriptor: D: (A;;RPWPCRCDCCLCLORCWOWSDDTSW;;;DA)
```



```
(A;;RPWPCRCDCCLCLORCWOWSDSDTWSW;;;SY) (A;;RPLCLORC;;;AU)
defaultHidingValue: TRUE
systemOnly: FALSE
defaultObjectCategory: CN=Application-Site-Settings,<SchemaNCDN>
systemFlags: FLAG_SCHEMA_BASE_OBJECT
```

Version-Specific Behavior: Implemented on Windows 2000 Server operating system, Windows Server 2003 operating system, Windows Server 2003 R2 operating system, Windows Server 2008 operating system, Windows Server 2008 R2 operating system, Windows Server 2012 operating system, and Windows Server 2012 R2 operating system.

2.11 Class applicationVersion

Stores versioning information for an application and its schema.

```
cn: Application-Version
ldapDisplayName: applicationVersion
governsId: 1.2.840.113556.1.5.216
objectClassCategory: 1
rdnAttId: cn
subClassOf: applicationSettings
mayContain: owner, managedBy, keywords, versionNumberLo,
  versionNumberHi, versionNumber, vendor, appSchemaVersion
possSuperiors: organizationalUnit, computer, container
schemaIdGuid: ddc790ac-af4d-442a-8f0f-a1d4caa7dd92
defaultSecurityDescriptor: D: (A;;RPWPCRCDCCLCLORCWOWSDSDTWSW;;;DA)
  (A;;RPWPCRCDCCLCLORCWOWSDSDTWSW;;;SY) (A;;RPLCLORC;;;AU)
defaultHidingValue: TRUE
systemOnly: FALSE
defaultObjectCategory: CN=Application-Version,<SchemaNCDN>
```

Version-Specific Behavior: Implemented on Windows Server 2003 operating system, Windows Server 2003 R2 operating system, Windows Server 2008 operating system, Windows Server 2008 R2 operating system, Windows Server 2012 operating system, and Windows Server 2012 R2 operating system.

2.12 Class attributeSchema

Defines an attribute object in the schema.

```
cn: Attribute-Schema
ldapDisplayName: attributeSchema
governsId: 1.2.840.113556.1.3.14
objectClassCategory: 1
rdnAttId: cn
subClassOf: top
systemMustContain: schemaIDGUID, oMSyntax, LDAPDisplayName,
  isSingleValued, cn, attributeSyntax, attributeID
systemMayContain: systemOnly, searchFlags, schemaFlagsEx, rangeUpper,
  rangeLower, oObjectClass, msDs-Schema-Extensions, msDS-IntId,
  mAPIID, linkID, isMemberOfPartialAttributeSet, isEphemeral,
  isDefunct, extendedCharsAllowed, classDisplayName,
  attributeSecurityGUID
systemPossSuperiors: dMD
schemaIdGuid: bf967a80-0de6-11d0-a285-00aa003049e2
```

```
defaultSecurityDescriptor: D:S:
defaultHidingValue: TRUE
systemOnly: FALSE
defaultObjectCategory: CN=Attribute-Schema,<SchemaNCDN>
systemFlags: FLAG_SCHEMA_BASE_OBJECT | FLAG_DOMAIN_DISALLOW_RENAME
```

Version-Specific Behavior: Implemented on Windows 2000 Server operating system, Windows Server 2003 operating system, Windows Server 2003 R2 operating system, Windows Server 2008 operating system, Windows Server 2008 R2 operating system, Windows Server 2012 operating system, and Windows Server 2012 R2 operating system.

2.13 Class bootableDevice

Represents a device that has boot parameters.

```
cn: BootableDevice
ldapDisplayName: bootableDevice
governsId: 1.3.6.1.1.1.2.12
objectClassCategory: 3
rdnAttId: cn
subClassOf: top
mayContain: cn, bootParameter, bootFile
schemaIdGuid: 4bcb2477-4bb3-4545-a9fc-fb66e136b435
defaultSecurityDescriptor: D: (A;;RPWPCRCCLCCLORCWOWDSDDTSW;;;DA)
(A;;RPWPCRCCLCCLORCWOWDSDDTSW;;;SY) (A;;RPLCLORC;;;AU)
defaultHidingValue: TRUE
systemOnly: FALSE
defaultObjectCategory: CN=BootableDevice,<SchemaNCDN>
```

Version-Specific Behavior: Implemented on Windows Server 2003 R2 operating system, Windows Server 2008 operating system, Windows Server 2008 R2 operating system, Windows Server 2012 operating system, and Windows Server 2012 R2 operating system.

2.14 Class builtinDomain

The container that holds the default groups for a domain.

```
cn: Builtin-Domain
ldapDisplayName: builtinDomain
governsId: 1.2.840.113556.1.5.4
objectClassCategory: 1
rdnAttId: cn
subClassOf: top
systemAuxiliaryClass: samDomainBase
systemPossSuperiors: domainDNS
schemaIdGuid: bf967a81-0de6-11d0-a285-00aa003049e2
defaultSecurityDescriptor: D: (A;;RPLCLORC;;;DA)
(A;;RPWPCRCCLCCLORCWOWDSDDTSW;;;SY) (A;;RPLCLORC;;;AU)
defaultHidingValue: TRUE
systemOnly: FALSE
defaultObjectCategory: CN=Builtin-Domain,<SchemaNCDN>
systemFlags: FLAG_SCHEMA_BASE_OBJECT
```

Version-Specific Behavior: Implemented on Windows 2000 Server operating system, Windows Server 2003 operating system, Windows Server 2003 R2 operating system, Windows Server 2008 operating system, Windows Server 2008 R2 operating system, Windows Server 2012 operating system, and Windows Server 2012 R2 operating system.

2.15 Class categoryRegistration

The registration information for a component category.

```
cn: Category-Registration
ldapDisplayName: categoryRegistration
governsId: 1.2.840.113556.1.5.74
objectClassCategory: 1
rdnAttId: cn
subClassOf: leaf
systemMayContain: managedBy, localizedDescription, localeID,
  categoryId
systemPossSuperiors: classStore
schemaIdGuid: 7d6c0e9d-7e20-11d0-afd6-00c04fd930c9
defaultSecurityDescriptor: D: (A;;RPWPCRCDCCLCLORCWOWSDSDDTSW;;;DA)
  (A;;RPWPCRCDCCLCLORCWOWSDSDDTSW;;;SY) (A;;RPLCLORC;;;AU)
defaultHidingValue: TRUE
systemOnly: FALSE
defaultObjectCategory: CN=Category-Registration,<SchemaNCDN>
systemFlags: FLAG_SCHEMA_BASE_OBJECT
```

Version-Specific Behavior: Implemented on Windows 2000 Server operating system, Windows Server 2003 operating system, Windows Server 2003 R2 operating system, Windows Server 2008 operating system, Windows Server 2008 R2 operating system, Windows Server 2012 operating system, and Windows Server 2012 R2 operating system.

2.16 Class certificationAuthority

Represents a process that issues public key certificates, for example, Active Directory Certificate Services (AD CS).

```
cn: Certification-Authority
ldapDisplayName: certificationAuthority
governsId: 2.5.6.16
objectClassCategory: 0
rdnAttId: cn
subClassOf: top
systemMustContain: cn, certificateRevocationList, cACertificate,
  authorityRevocationList
systemMayContain: teletexTerminalIdentifier,
  supportedApplicationContext, signatureAlgorithms, searchGuide,
  previousParentCA, previousCACertificates, pendingParentCA,
  pendingCACertificates, parentCACertificateChain, parentCA,
  enrollmentProviders, domainPolicyObject, domainID, dnsHostName,
  deltaRevocationList, currentParentCA, crossCertificatePair,
  cRLObjct, certificateTemplates, cAWEbURL, cAUsages, cAConnect,
  cACertificateDN
systemPossSuperiors: container
schemaIdGuid: 3fdfee50-47f4-11d1-a9c3-0000f80367c1
defaultSecurityDescriptor: D: (A;;RPWPCRCDCCLCLORCWOWSDSDDTSW;;;DA)
  (A;;RPWPCRCDCCLCLORCWOWSDSDDTSW;;;SY) (A;;RPLCLORC;;;AU)
```

```
defaultHidingValue: TRUE
systemOnly: FALSE
defaultObjectCategory: CN=Certification-Authority,<SchemaNCDN>
systemFlags: FLAG_SCHEMA_BASE_OBJECT
```

Version-Specific Behavior: Implemented on Windows 2000 Server operating system, Windows Server 2003 operating system, Windows Server 2003 R2 operating system, Windows Server 2008 operating system, Windows Server 2008 R2 operating system, Windows Server 2012 operating system, and Windows Server 2012 R2 operating system.

2.17 Class classRegistration

The registration information for a Component Object Model (COM) object.

```
cn: Class-Registration
ldapDisplayName: classRegistration
governsId: 1.2.840.113556.1.5.10
objectClassCategory: 1
rdnAttId: cn
subClassOf: leaf
systemMayContain: requiredCategories, managedBy,
  implementedCategories, cOMTreatAsClassId, cOMProgID,
  cOMOtherProgId, cOMInterfaceID, cOMCLSID
systemPossSuperiors: classStore
schemaIdGuid: bf967a82-0de6-11d0-a285-00aa003049e2
defaultSecurityDescriptor: D: (A;;RPWPCRCDCCLCLORCWOWSDSDTSW;;;DA)
  (A;;RPWPCRCDCCLCLORCWOWSDSDTSW;;;SY) (A;;RPLCLORC;;;AU)
defaultHidingValue: TRUE
systemOnly: FALSE
defaultObjectCategory: CN=Class-Registration,<SchemaNCDN>
systemFlags: FLAG_SCHEMA_BASE_OBJECT
```

Version-Specific Behavior: Implemented on Windows 2000 Server operating system, Windows Server 2003 operating system, Windows Server 2003 R2 operating system, Windows Server 2008 operating system, Windows Server 2008 R2 operating system, Windows Server 2012 operating system, and Windows Server 2012 R2 operating system.

2.18 Class classSchema

Defines a class object in the schema.

```
cn: Class-Schema
ldapDisplayName: classSchema
governsId: 1.2.840.113556.1.3.13
objectClassCategory: 1
rdnAttId: cn
subClassOf: top
systemMustContain: subClassOf, schemaIDGUID, objectClassCategory,
  governsID, defaultObjectCategory, cn
systemMayContain: systemPossSuperiors, systemOnly, systemMustContain,
  systemMayContain, systemAuxiliaryClass, schemaFlagsEx, rDNAttID,
  possSuperiors, mustContain, msDs-Schema-Extensions, msDS-IntId,
  mayContain, LDAPDisplayName, isDefunct, defaultSecurityDescriptor,
  defaultHidingValue, classDisplayName, auxiliaryClass
systemPossSuperiors: dMD
```

```
schemaIdGuid: bf967a83-0de6-11d0-a285-00aa003049e2
defaultSecurityDescriptor: D:S:
defaultHidingValue: TRUE
systemOnly: FALSE
defaultObjectCategory: CN=Class-Schema,<SchemaNCDN>
systemFlags: FLAG_SCHEMA_BASE_OBJECT | FLAG_DOMAIN_DISALLOW_RENAME
```

Version-Specific Behavior: Implemented on Windows 2000 Server operating system, Windows Server 2003 operating system, Windows Server 2003 R2 operating system, Windows Server 2008 operating system, Windows Server 2008 R2 operating system, Windows Server 2012 operating system, and Windows Server 2012 R2 operating system.

2.19 Class classStore

Used to create the class store container, which provides the framework for deploying application resources in Active Directory Domain Services (on Windows Server 2008 operating system, Windows Server 2008 R2 operating system, and Windows Server 2012 operating system) and in the Active Directory directory service (on Windows Server 2003 R2 operating system, Windows Server 2003 operating system, and Windows 2000 Server operating system). This class makes the deployment policy available to policy recipients; that is, to users and machines. Access and administration privileges are controlled by standard access control properties on the class store container object.

```
cn: Class-Store
ldapDisplayName: classStore
governsId: 1.2.840.113556.1.5.44
objectClassCategory: 1
rdnAttId: cn
subClassOf: top
systemMayContain: versionNumber, nextLevelStore, lastUpdateSequence,
  appSchemaVersion
systemPossSuperiors: domainPolicy, computer, group, user, classStore,
  organizationalUnit, domainDNS, container
schemaIdGuid: bf967a84-0de6-11d0-a285-00aa003049e2
defaultSecurityDescriptor: D: (A;;RPWPCCDCLCLORCWOWDSDDTSW;;;DA)
  (A;;RPWPCCDCLCLORCWOWDSDDTSW;;;SY) (A;;RPLCLORC;;;AU)
defaultHidingValue: TRUE
systemOnly: FALSE
defaultObjectCategory: CN=Class-Store,<SchemaNCDN>
systemFlags: FLAG_SCHEMA_BASE_OBJECT
```

Version-Specific Behavior: Implemented on Windows 2000 Server, Windows Server 2003, Windows Server 2003 R2, Windows Server 2008, Windows Server 2008 R2, Windows Server 2012, and Windows Server 2012 R2 operating system.

2.20 Class comConnectionPoint

The binding for running the COM or DCOM service.

```
cn: Com-Connection-Point
ldapDisplayName: comConnectionPoint
governsId: 1.2.840.113556.1.5.11
objectClassCategory: 1
rdnAttId: cn
subClassOf: connectionPoint
systemMustContain: cn
```

```

systemMayContain: monikerDisplayName, moniker, marshalledInterface
systemPossSuperiors: container
schemaIdGuid: bf967a85-0de6-11d0-a285-00aa003049e2
defaultSecurityDescriptor: D: (A;;RPWPCRCDCCLCLORCWOWSDSDTTSW;;;DA)
(A;;RPWPCRCDCCLCLORCWOWSDSDTTSW;;;SY) (A;;RPLCLORC;;;AU)
defaultHidingValue: TRUE
systemOnly: FALSE
defaultObjectCategory: CN=Com-Connection-Point,<SchemaNCDN>
systemFlags: FLAG_SCHEMA_BASE_OBJECT

```

Version-Specific Behavior: Implemented on Windows 2000 Server operating system, Windows Server 2003 operating system, Windows Server 2003 R2 operating system, Windows Server 2008 operating system, Windows Server 2008 R2 operating system, Windows Server 2012 operating system, and Windows Server 2012 R2 operating system.

2.21 Class computer

A class that represents a computer account in the domain.

```

cn: Computer
ldapDisplayName: computer
governsId: 1.2.840.113556.1.3.30
objectClassCategory: 1
rdnAttId: cn
subClassOf: user
auxiliaryClass: ipHost
mayContain: msSFU30Aliases, msSFU30NisDomain, nisMapName,
msSFU30Name
systemMayContain: msTSSecondaryDesktopBL, msTSPrimaryDesktopBL,
msTSEndpointData, msTSEndpointType,
msTSEndpointPlugin, msDS-HostServiceAccount,
msDS-IsUserCachableAtRocd, msTSPProperty02,
msTSPProperty01, msTPM-OwnerInformation, msDS-RevealOnDemandGroup,
msDS-NeverRevealGroup, msDS-PromotionSettings, msDS-SiteName,
msDS-isRODC, msDS-isGC, msDS-AuthenticatedAtDC, msDS-RevealedList,
msDS-RevealedUsers, msDS-ExecuteScriptPassword, msDS-KrbTgtLink,
volumeCount, siteGUID, rIDSetReferences, policyReplicationFlags,
physicalLocationObject, operatingSystemVersion,
operatingSystemServicePack, operatingSystemHotfix, operatingSystem,
networkAddress, netbootDUID, netbootSIFFile, netbootMirrorDataFile,
netbootMachineFilePath, netbootInitialization, netbootGUID,
msDS-AdditionalSamAccountName, msDS-AdditionalDnsHostName,
managedBy, machineRole, location, localPolicyFlags, dnsHostName,
defaultLocalPolicyObject, cn, catalogs, msTPM-TpmInformationForComputer,
msDS-GenerationId, msImaging-ThumbprintHash, msImaging-HashAlgorithm
systemPossSuperiors: container, organizationalUnit, domainDNS
schemaIdGuid: bf967a86-0de6-11d0-a285-00aa003049e2
defaultSecurityDescriptor: D: (A;;RPWPCRCDCCLCLORCWOWSDSDTTSW;;;DA)
(A;;RPWPCRCDCCLCLORCWOWSDSDTTSW;;;AO)
(A;;RPWPCRCDCCLCLORCWOWSDSDTTSW;;;SY) (A;;RPCRLCLORCSSDDT;;;CO)
(OA;;WP;4c164200-20c0-11d0-a768-00aa006e0529;;;CO) (A;;RPLCLORC;;;AU)
(OA;;CR;ab721a53-1e2f-11d0-9819-00aa0040529b;;;WD) (A;;CCDC;;;PS)
(OA;;CCDC;bf967aa8-0de6-11d0-a285-00aa003049e2;;;PO)
(OA;;RPWP;bf967a7f-0de6-11d0-a285-00aa003049e2;;;CA)
(OA;;SW;f3a64788-5306-11d1-a9c5-0000f80367c1;;;PS)
(OA;;RPWP;77b5b886-944a-11d1-ae8d-0000f80367c1;;;PS)
(OA;;SW;72e39547-7b18-11d1-ade8-00c04fd8d5cd;;;PS)

```

```

(OA;;SW;72e39547-7b18-11d1-edef-00c04fd8d5cd;;CO)
(OA;;SW;f3a64788-5306-11d1-a9c5-0000f80367c1;;CO)
(OA;;WP;3e0abfd0-126a-11d0-a060-00aa006c33ed;
bf967a86-0de6-11d0-a285-00aa003049e2;CO)
(OA;;WP;5f202010-79a5-11d0-9020-00c04fc2d4cf;
bf967a86-0de6-11d0-a285-00aa003049e2;CO)
(OA;;WP;bf967950-0de6-11d0-a285-00aa003049e2;
bf967a86-0de6-11d0-a285-00aa003049e2;CO)
(OA;;WP;bf967953-0de6-11d0-a285-00aa003049e2;
bf967a86-0de6-11d0-a285-00aa003049e2;CO)
(OA;;RP;46a9b11d-60ae-405a-b7e8-ff8a58d456d2;;S-1-5-32-560)
defaultHidingValue: FALSE
systemOnly: FALSE
defaultObjectCategory: CN=Computer,<SchemaNCDN>
systemFlags: FLAG_SCHEMA_BASE_OBJECT

```

Version-Specific Behavior: Implemented on Windows 2000 Server operating system, Windows Server 2003 operating system, Windows Server 2003 R2 operating system, Windows Server 2008 operating system, Windows Server 2008 R2 operating system, Windows Server 2012 operating system, and Windows Server 2012 R2 operating system.

2.22 Class configuration

A container that holds the configuration information for a domain.

```

cn: Configuration
ldapDisplayName: configuration
governsId: 1.2.840.113556.1.5.12
objectClassCategory: 1
rdnAttId: cn
subClassOf: top
systemMustContain: cn
systemMayContain: msDS-USNLastSyncSuccess, gPOptions, gPLink
systemPossSuperiors: domainDNS
schemaIdGuid: bf967a87-0de6-11d0-a285-00aa003049e2
defaultSecurityDescriptor: D: (A;;RPWPCRCDCCLORCWOWDSW;;;DA)
(A;;RPWPCRCDCCLORCWOWSDDTSW;;;SY) (A;;RPLCLORC;;;AU)
defaultHidingValue: TRUE
systemOnly: TRUE
defaultObjectCategory: CN=Configuration,<SchemaNCDN>
systemFlags: FLAG_SCHEMA_BASE_OBJECT

```

Version-Specific Behavior: Implemented on Windows 2000 Server operating system, Windows Server 2003 operating system, Windows Server 2003 R2 operating system, Windows Server 2008 operating system, Windows Server 2008 R2 operating system, Windows Server 2012 operating system, and Windows Server 2012 R2 operating system.

2.23 Class connectionPoint

The base class from which all connectible objects are derived.

```

cn: Connection-Point
ldapDisplayName: connectionPoint
governsId: 1.2.840.113556.1.5.14
objectClassCategory: 2

```

```
rdnAttId: cn
subClassOf: leaf
systemMustContain: cn
systemMayContain: msDS-Settings, managedBy, keywords
systemPossSuperiors: container, computer
schemaIdGuid: 5cb41ecf-0e4c-11d0-a286-00aa003049e2
defaultSecurityDescriptor: D: (A;;;RPWPCRCDCCLCLORCWOWSDDTSW;;;DA)
(A;;;RPWPCRCDCCLCLORCWOWSDDTSW;;;SY) (A;;;RPLCLORC;;;AU)
defaultHidingValue: TRUE
systemOnly: FALSE
defaultObjectCategory: CN=Connection-Point,<SchemaNCDN>
systemFlags: FLAG_SCHEMA_BASE_OBJECT
```

Version-Specific Behavior: Implemented on Windows 2000 Server operating system, Windows Server 2003 operating system, Windows Server 2003 R2 operating system, Windows Server 2008 operating system, Windows Server 2008 R2 operating system, Windows Server 2012 operating system, and Windows Server 2012 R2 operating system.

2.24 Class contact

A class that contains information about a person or company that users may often contact.

```
cn: Contact
ldapDisplayName: contact
governsId: 1.2.840.113556.1.5.15
objectClassCategory: 1
rdnAttId: cn
subClassOf: organizationalPerson
systemAuxiliaryClass: mailRecipient
systemMustContain: cn
mayContain: msDS-SourceObjectDN
systemMayContain: notes
systemPossSuperiors: organizationalUnit, domainDNS
schemaIdGuid: 5cb41ed0-0e4c-11d0-a286-00aa003049e2
defaultSecurityDescriptor: D: (A;;;RPWPCRCDCCLCLORCWOWSDDTSW;;;DA)
(A;;;RPWPCRCDCCLCLORCWOWSDDTSW;;;SY) (A;;;RPLCLORC;;;AU)
defaultHidingValue: FALSE
systemOnly: FALSE
defaultObjectCategory: CN=Person,<SchemaNCDN>
systemFlags: FLAG_SCHEMA_BASE_OBJECT
```

Version-Specific Behavior: Implemented on Windows 2000 Server operating system, Windows Server 2003 operating system, Windows Server 2003 R2 operating system, Windows Server 2008 operating system, Windows Server 2008 R2 operating system, Windows Server 2012 operating system, and Windows Server 2012 R2 operating system.

2.25 Class container

A class that is used to hold other classes.

```
cn: Container
ldapDisplayName: container
governsId: 1.2.840.113556.1.3.23
objectClassCategory: 1
rdnAttId: cn
```



```

subClassOf: top
systemMustContain: cn
mayContain: msDS-ObjectReference
systemMayContain: schemaVersion, defaultClassStore
systemPossSuperiors: msDS-AzScope, msDS-AzApplication,
  msDS-AzAdminManager, subnet, server, nTDSservice, domainDNS,
  organization, configuration, container, organizationalUnit
schemaIdGuid: bf967a8b-0de6-11d0-a285-00aa003049e2
defaultSecurityDescriptor: D: (A;;RPWPCCDCLCLORCWOWSDDTSW;;;DA)
  (A;;RPWPCCDCLCLORCWOWSDDTSW;;;SY) (A;;RPLCLORC;;;AU)
defaultHidingValue: TRUE
systemOnly: FALSE
defaultObjectCategory: CN=Container,<SchemaNCDN>
systemFlags: FLAG_SCHEMA_BASE_OBJECT

```

Version-Specific Behavior: Implemented on Windows 2000 Server operating system, Windows Server 2003 operating system, Windows Server 2003 R2 operating system, Windows Server 2008 operating system, Windows Server 2008 R2 operating system, Windows Server 2012 operating system, and Windows Server 2012 R2 operating system.

2.26 Class controlAccessRight

Identifies an extended right that can be granted or revoked by means of an access control list (ACL).

```

cn: Control-Access-Right
ldapDisplayName: controlAccessRight
governsId: 1.2.840.113556.1.5.77
objectClassCategory: 1
rdnAttId: cn
subClassOf: top
systemMayContain: validAccesses, rightsGuid, localizationDisplayId,
  appliesTo
systemPossSuperiors: container
schemaIdGuid: 8297931e-86d3-11d0-afda-00c04fd930c9
defaultSecurityDescriptor: D: (A;;RPWPCCDCLCLORCWOWSDDTSW;;;DA)
  (A;;RPWPCCDCLCLORCWOWSDDTSW;;;SY) (A;;RPLCLORC;;;AU)
defaultHidingValue: TRUE
systemOnly: FALSE
defaultObjectCategory: CN=Control-Access-Right,<SchemaNCDN>
systemFlags: FLAG_SCHEMA_BASE_OBJECT

```

Version-Specific Behavior: Implemented on Windows 2000 Server operating system, Windows Server 2003 operating system, Windows Server 2003 R2 operating system, Windows Server 2008 operating system, Windows Server 2008 R2 operating system, Windows Server 2012 operating system, and Windows Server 2012 R2 operating system.

2.27 Class country

The country/region in the address of the user. This class specifies the full name of the country/region.

```

cn: Country
ldapDisplayName: country
governsId: 2.5.6.2

```

```

objectClassCategory: 0
rdnAttId: c
subClassOf: top
systemMustContain: c
systemMayContain: co, searchGuide
systemPossSuperiors: domainDNS, organization
schemaIdGuid: bf967a8c-0de6-11d0-a285-00aa003049e2
defaultSecurityDescriptor: D: (A;;RPWPCRCDCCLCLORCWOWSDSDTSW;;;DA)
(A;;RPWPCRCDCCLCLORCWOWSDSDTSW;;;SY) (A;;RPLCLORC;;;AU)
defaultHidingValue: TRUE
systemOnly: FALSE
defaultObjectCategory: CN=Country,<SchemaNCDN>
systemFlags: FLAG_SCHEMA_BASE_OBJECT

```

Version-Specific Behavior: Implemented on Windows 2000 Server operating system, Windows Server 2003 operating system, Windows Server 2003 R2 operating system, Windows Server 2008 operating system, Windows Server 2008 R2 operating system, Windows Server 2012 operating system, and Windows Server 2012 R2 operating system.

2.28 Class `cRLDistributionPoint`

The object that holds the certificate, authority, and delta revocation lists.

```

cn: CRL-Distribution-Point
ldapDisplayName: cRLDistributionPoint
governsId: 2.5.6.19
objectClassCategory: 1
rdnAttId: cn
subClassOf: top
systemMustContain: cn
systemMayContain: deltaRevocationList, cRLPartitionedRevocationList,
certificateRevocationList, certificateAuthorityObject,
authorityRevocationList
systemPossSuperiors: container
schemaIdGuid: 167758ca-47f3-11d1-a9c3-0000f80367c1
defaultSecurityDescriptor: D: (A;;RPWPCRCDCCLCLORCWOWSDSDTSW;;;DA)
(A;;RPWPCRCDCCLCLORCWOWSDSDTSW;;;SY) (A;;RPLCLORC;;;AU)
defaultHidingValue: TRUE
systemOnly: FALSE
defaultObjectCategory: CN=CRL-Distribution-Point,<SchemaNCDN>
systemFlags: FLAG_SCHEMA_BASE_OBJECT

```

Version-Specific Behavior: Implemented on Windows 2000 Server operating system, Windows Server 2003 operating system, Windows Server 2003 R2 operating system, Windows Server 2008 operating system, Windows Server 2008 R2 operating system, Windows Server 2012 operating system, and Windows Server 2012 R2 operating system.

2.29 Class `crossRef`

Holds knowledge information about all directory service (DS) naming contexts and all external directories to which referrals can be generated.

```

cn: Cross-Ref
ldapDisplayName: crossRef
governsId: 1.2.840.113556.1.3.11

```

```

objectClassCategory: 1
rdnAttId: cn
subClassOf: top
systemMustContain: nCName, dnsRoot, cn
systemMayContain: msDS-NC-RO-Replica-Locations, trustParent,
  superiorDNSRoot, rootTrust, nTMixedDomain, nETBIOSName, Enabled,
  msDS-SDReferenceDomain,
  msDS-Replication-Notify-Subsequent-DSA-Delay,
  msDS-Replication-Notify-First-DSA-Delay, msDS-NC-Replica-Locations,
  msDS-DnsRootAlias, msDS-Behavior-Version
systemPossSuperiors: crossRefContainer
schemaIdGuid: bf967a8d-0de6-11d0-a285-00aa003049e2
defaultSecurityDescriptor: D: (A;;RPWPCRCDCCLCLOCRCWOWSDDTSW;;;DA)
  (A;;RPWPCRCDCCLCLOCRCWOWSDDTSW;;;SY) (A;;RPLCLORC;;;AU)
defaultHidingValue: TRUE
systemOnly: FALSE
defaultObjectCategory: CN=Cross-Ref,<SchemaNCN>
systemFlags: FLAG_SCHEMA_BASE_OBJECT

```

Version-Specific Behavior: Implemented on Windows 2000 Server operating system, Windows Server 2003 operating system, Windows Server 2003 R2 operating system, Windows Server 2008 operating system, Windows Server 2008 R2 operating system, Windows Server 2012 operating system, and Windows Server 2012 R2 operating system.

2.30 Class crossRefContainer

Holds the cross-reference objects for all naming contexts.

```

cn: Cross-Ref-Container
ldapDisplayName: crossRefContainer
governsId: 1.2.840.113556.1.5.7000.53
objectClassCategory: 1
rdnAttId: cn
subClassOf: top
systemMayContain: msDS-EnabledFeature, msDS-SPNSuffixes, uPNSuffixes,
  msDS-UpdateScript, msDS-ExecuteScriptPassword, msDS-Behavior-Version
systemPossSuperiors: configuration
schemaIdGuid: ef9e60e0-56f7-11d1-a9c6-0000f80367c1
defaultSecurityDescriptor: D: (A;;GA;;;SY)
defaultHidingValue: FALSE
systemOnly: TRUE
defaultObjectCategory: CN=Cross-Ref-Container,<SchemaNCN>
systemFlags: FLAG_SCHEMA_BASE_OBJECT

```

Version-Specific Behavior: Implemented on Windows 2000 Server operating system, Windows Server 2003 operating system, Windows Server 2003 R2 operating system, Windows Server 2008 operating system, Windows Server 2008 R2 operating system, Windows Server 2012 operating system, and Windows Server 2012 R2 operating system.

2.31 Class device

A generic base class for physical devices.

```

cn: Device
ldapDisplayName: device

```

```

governsId: 2.5.6.14
objectClassCategory: 0
rdnAttId: cn
subClassOf: top
auxiliaryClass: ipHost, ieee802Device, bootableDevice
systemMustContain: cn
mayContain: msSFU30Name, msSFU30NisDomain, nisMapName, msSFU30Aliases
systemMayContain: serialNumber, seeAlso, owner, ou, o, l
systemPossSuperiors: domainDNS, organizationalUnit, organization,
  container
schemaIdGuid: bf967a8e-0de6-11d0-a285-00aa003049e2
defaultSecurityDescriptor: D: (A;;RPWPCRCDCCLCLORCWOWSDSDTSW;;;DA)
  (A;;RPWPCRCDCCLCLORCWOWSDSDTSW;;;SY) (A;;RPLCLORC;;;AU)
defaultHidingValue: TRUE
systemOnly: FALSE
defaultObjectCategory: CN=Device,<SchemaNCDN>
systemFlags: FLAG_SCHEMA_BASE_OBJECT

```

Version-Specific Behavior: Implemented on Windows 2000 Server operating system, Windows Server 2003 operating system, Windows Server 2003 R2 operating system, Windows Server 2008 operating system, Windows Server 2008 R2 operating system, Windows Server 2012 operating system, and Windows Server 2012 R2 operating system.

2.32 Class dfsConfiguration

Holds all fault-tolerant Distributed File System (DFS) configurations.

```

cn: Dfs-Configuration
ldapDisplayName: dfsConfiguration
governsId: 1.2.840.113556.1.5.42
objectClassCategory: 1
rdnAttId: cn
subClassOf: top
systemPossSuperiors: container, domainDNS
schemaIdGuid: 8447f9f2-1027-11d0-a05f-00aa006c33ed
defaultSecurityDescriptor: D: (A;;RPWPCRCDCCLCLORCWOWSDSDTSW;;;DA)
  (A;;RPWPCRCDCCLCLORCWOWSDSDTSW;;;SY) (A;;RPLCLORC;;;AU)
defaultHidingValue: TRUE
systemOnly: FALSE
defaultObjectCategory: CN=Dfs-Configuration,<SchemaNCDN>
systemFlags: FLAG_SCHEMA_BASE_OBJECT

```

Version-Specific Behavior: Implemented on Windows 2000 Server operating system, Windows Server 2003 operating system, Windows Server 2003 R2 operating system, Windows Server 2008 operating system, Windows Server 2008 R2 operating system, Windows Server 2012 operating system, and Windows Server 2012 R2 operating system.

2.33 Class dHCPClass

Represents a Dynamic Host Configuration Protocol (DHCP) server or set of servers.

```

cn: DHCP-Class
ldapDisplayName: dHCPClass
governsId: 1.2.840.113556.1.5.132
objectClassCategory: 1

```

```

rdnAttId: cn
subClassOf: top
systemMustContain: dhcpUniqueKey, dhcpType, dhcpIdentification,
dhcpFlags
systemMayContain: superScopes, superScopeDescription,
optionsLocation, optionDescription, networkAddress, mscopeId,
dhcpUpdateTime, dhcpSubnets, dhcpState, dhcpSites, dhcpServers,
dhcpReservations, dhcpRanges, dhcpProperties, dhcpOptions,
dhcpObjName, dhcpObjDescription, dhcpMaxKey, dhcpMask, dhcpClasses
systemPossSuperiors: container
schemaIdGuid: 963d2756-48be-11d1-a9c3-0000f80367c1
defaultSecurityDescriptor: D:(A;;;RPWPCRCDCCLCLOCRCWOWSDDTSW;;;DA)
(A;;;RPWPCRCDCCLCLOCRCWOWSDDTSW;;;SY)(A;;;RPLCLORC;;;AU)
defaultHidingValue: TRUE
systemOnly: FALSE
defaultObjectCategory: CN=DHCP-Class,<SchemaNCDN>
systemFlags: FLAG_SCHEMA_BASE_OBJECT

```

Version-Specific Behavior: Implemented on Windows 2000 Server operating system, Windows Server 2003 operating system, Windows Server 2003 R2 operating system, Windows Server 2008 operating system, Windows Server 2008 R2 operating system, Windows Server 2012 operating system, and Windows Server 2012 R2 operating system.

2.34 Class displaySpecifier

Describes the context menus and property pages to use with an object in the directory.

```

cn: Display-Specifier
ldapDisplayName: displaySpecifier
governsId: 1.2.840.113556.1.5.84
objectClassCategory: 1
rdnAttId: cn
subClassOf: top
systemMayContain: treatAsLeaf, shellPropertyPages, shellContextMenu,
scopeFlags, queryFilter, iconPath, extraColumns, creationWizard,
createWizardExt, createDialog, contextMenu, classDisplayName,
attributeDisplayNames, adminPropertyPages,
adminMultiselectPropertyPages, adminContextMenu
systemPossSuperiors: container
schemaIdGuid: e0fale8a-9b45-11d0-afdd-00c04fd930c9
defaultSecurityDescriptor: D:(A;;;RPWPCRCDCCLCLOCRCWOWSDDTSW;;;DA)
(A;;;RPWPCRCDCCLCLOCRCWOWSDDTSW;;;SY)(A;;;RPLCLORC;;;AU)
defaultHidingValue: TRUE
systemOnly: FALSE
defaultObjectCategory: CN=Display-Specifier,<SchemaNCDN>
systemFlags: FLAG_SCHEMA_BASE_OBJECT

```

Version-Specific Behavior: Implemented on Windows 2000 Server operating system, Windows Server 2003 operating system, Windows Server 2003 R2 operating system, Windows Server 2008 operating system, Windows Server 2008 R2 operating system, Windows Server 2012 operating system, and Windows Server 2012 R2 operating system.

2.35 Class displayTemplate

Specifies information for an address template.

```

cn: Display-Template
ldapDisplayName: displayTemplate
governsId: 1.2.840.113556.1.3.59
objectClassCategory: 1
rdnAttId: cn
subClassOf: top
systemMustContain: cn
systemMayContain: originalDisplayTableMSDOS, originalDisplayTable,
  helpFileName, helpData32, helpData16, addressEntryDisplayTableMSDOS,
  addressEntryDisplayTable
systemPossSuperiors: container
schemaIdGuid: 5fd4250c-1262-11d0-a060-00aa006c33ed
defaultSecurityDescriptor: D: (A;;RPWPCRCDCCLCLORCWOWSDDTSW;;;DA)
  (A;;RPWPCRCDCCLCLORCWOWSDDTSW;;;SY) (A;;RPLCLORC;;;AU)
defaultHidingValue: TRUE
systemOnly: FALSE
defaultObjectCategory: CN=Display-Template,<SchemaNCDN>

```

Version-Specific Behavior: Implemented on Windows 2000 Server operating system, Windows Server 2003 operating system, Windows Server 2003 R2 operating system, Windows Server 2008 operating system, Windows Server 2008 R2 operating system, Windows Server 2012 operating system, and Windows Server 2012 R2 operating system.

2.36 Class dMD

Holds the schema for Active Directory Domain Services (AD DS) and the Active Directory directory service. The Lightweight Directory Access Protocol (LDAP) name dMD stands for Directory Management Domain.

```

cn: DMD
ldapDisplayName: dMD
governsId: 1.2.840.113556.1.3.9
objectClassCategory: 1
rdnAttId: cn
subClassOf: top
systemMustContain: cn
systemMayContain: msDS-USNLastSyncSuccess, schemaUpdate, schemaInfo,
  prefixMap, msDs-Schema-Extensions, msDS-IntId, dmdName
systemPossSuperiors: configuration
schemaIdGuid: bf967a8f-0de6-11d0-a285-00aa003049e2
defaultSecurityDescriptor: D: (A;;RPWPCRCDCCLCLORCWOWSDDTSW;;;DA)
  (A;;RPWPCRCDCCLCLORCWOWSDDTSW;;;SY) (A;;RPLCLORC;;;AU)
defaultHidingValue: TRUE
systemOnly: TRUE
defaultObjectCategory: CN=DMD,<SchemaNCDN>
systemFlags: FLAG_SCHEMA_BASE_OBJECT

```

Version-Specific Behavior: Implemented on Windows 2000 Server operating system, Windows Server 2003 operating system, Windows Server 2003 R2 operating system, Windows Server 2008 operating system, Windows Server 2008 R2 operating system, Windows Server 2012 operating system, and Windows Server 2012 R2 operating system.

2.37 Class dnsNode

Holds the domain name system (DNS) resource records for a single host.

```

cn: Dns-Node
ldapDisplayName: dnsNode
governsId: 1.2.840.113556.1.5.86
objectClassCategory: 1
rdnAttId: dc
subClassOf: top
systemMustContain: dc
systemMayContain: dNSTombstoned, dnsRecord, dnsProperty
systemPossSuperiors: dnsZone
schemaIdGuid: e0fale8c-9b45-11d0-afdd-00c04fd930c9
defaultSecurityDescriptor: D: (A;;RPWPCRCDCCLCLORCWOWSDDTSW;;;DA)
(A;;RPWPCRCDCCLCLORCWOWSDDTSW;;;ED)
(A;;RPWPCRCDCCLCLORCWOWSDDTSW;;;SY)
(A;;RPWPCRCDCCLCLORCWOWSDDTSW;;;CO) (A;;RPLCLORC;;;WD)
defaultHidingValue: TRUE
systemOnly: FALSE
defaultObjectCategory: CN=Dns-Node,<SchemaNCDN>
systemFlags: FLAG_SCHEMA_BASE_OBJECT

```

Version-Specific Behavior: Implemented on Windows 2000 Server operating system, Windows Server 2003 operating system, Windows Server 2003 R2 operating system, Windows Server 2008 operating system, Windows Server 2008 R2 operating system, Windows Server 2012 operating system, and Windows Server 2012 R2 operating system.

2.38 Class dnsZone

The container for DNS nodes. This class holds zone metadata.

```

cn: Dns-Zone
ldapDisplayName: dnsZone
governsId: 1.2.840.113556.1.5.85
objectClassCategory: 1
rdnAttId: dc
subClassOf: top
systemMustContain: dc
systemMayContain: managedBy, dnsSecureSecondaries, dnsProperty,
dnsNotifySecondaries, dnsAllowXFR, dnsAllowDynamic, msDNS-IsSigned,
msDNS-SignWithNSEC3, msDNS-NSEC3OptOut, msDNS-MaintainTrustAnchor,
msDNS-DSRecordAlgorithms, msDNS-RFC5011KeyRollovers,
msDNS-NSEC3HashAlgorithm, msDNS-NSEC3RandomSaltLength,
msDNS-NSEC3Iterations, msDNS-DNSKEYRecordSetTTL, msDNS-DSRecordSetTTL,
msDNS-SignatureInceptionOffset, msDNS-SecureDelegationPollingPeriod,
msDNS-SigningKeyDescriptors, msDNS-SigningKeys, msDNS-DNSKEYRecords,
msDNS-ParentHasSecureDelegation, msDNS-PropagationTime,
msDNS-NSEC3UserSalt, msDNS-NSEC3CurrentSalt
systemPossSuperiors: container
schemaIdGuid: e0fale8b-9b45-11d0-afdd-00c04fd930c9
defaultSecurityDescriptor: D: (A;;RPWPCRCDCCLCLORCWOWSDDTSW;;;DA)
(A;;RPWPCRCDCCLCLORCWOWSDDTSW;;;ED)
(A;;RPWPCRCDCCLCLORCWOWSDDTSW;;;SY) (A;;CC;;;AU) (A;;RPLCLORC;;;WD)
(A;;RPWPCRCDCCLCLORCWOWSDDTSW;;;CO)
defaultHidingValue: TRUE
systemOnly: FALSE
defaultObjectCategory: CN=Dns-Zone,<SchemaNCDN>
systemFlags: FLAG_SCHEMA_BASE_OBJECT

```

Version-Specific Behavior: Implemented on Windows 2000 Server operating system, Windows Server 2003 operating system, Windows Server 2003 R2 operating system, Windows Server 2008 operating system, Windows Server 2008 R2 operating system, Windows Server 2012 operating system, and Windows Server 2012 R2 operating system.

2.39 Class document

Defines entries that represent documents.

```
cn: document
ldapDisplayName: document
governsId: 0.9.2342.19200300.100.4.6
objectClassCategory: 1
rdnAttId: cn
subClassOf: top
mayContain: documentIdentifier, documentPublisher, documentLocation,
  documentAuthor, documentVersion, documentTitle, ou, o, 1, seeAlso,
  description, cn
possSuperiors: organizationalUnit, container
schemaIdGuid: 39bad96d-c2d6-4baf-88ab-7e4207600117
defaultSecurityDescriptor: D: (A;;RPWPCRCCLCLOLORCWOWSDDDTDSW;;;DA)
  (A;;RPWPCRCCLCLOLORCWOWSDDDTDSW;;;SY) (A;;RPLCLORC;;;AU)
defaultHidingValue: TRUE
systemOnly: FALSE
defaultObjectCategory: CN=document,<SchemaNCDN>
```

Version-Specific Behavior: Implemented on Windows Server 2003 operating system, Windows Server 2003 R2 operating system, Windows Server 2008 operating system, Windows Server 2008 R2 operating system, Windows Server 2012 operating system, and Windows Server 2012 R2 operating system.

2.40 Class documentSeries

Defines an entry that represents a series of documents.

```
cn: documentSeries
ldapDisplayName: documentSeries
governsId: 0.9.2342.19200300.100.4.9
objectClassCategory: 1
rdnAttId: cn
subClassOf: top
mustContain: cn
mayContain: telephoneNumber, ou, o, 1, seeAlso, description
possSuperiors: organizationalUnit, container
schemaIdGuid: 7a2be07c-302f-4b96-bc90-0795d66885f8
defaultSecurityDescriptor: D: (A;;RPWPCRCCLCLOLORCWOWSDDDTDSW;;;DA)
  (A;;RPWPCRCCLCLOLORCWOWSDDDTDSW;;;SY) (A;;RPLCLORC;;;AU)
defaultHidingValue: TRUE
systemOnly: FALSE
defaultObjectCategory: CN=documentSeries,<SchemaNCDN>
```

Version-Specific Behavior: Implemented on Windows Server 2003 operating system, Windows Server 2003 R2 operating system, Windows Server 2008 operating system, Windows Server 2008 R2 operating system, Windows Server 2012 operating system, and Windows Server 2012 R2 operating system.

2.41 Class domain

Contains information about a domain.

```
cn: Domain
ldapDisplayName: domain
governsId: 1.2.840.113556.1.5.66
objectClassCategory: 2
rdnAttId: dc
subClassOf: top
systemMustContain: dc
systemPossSuperiors: domain, organization
schemaIdGuid: 19195a5a-6da0-11d0-afd3-00c04fd930c9
defaultHidingValue: TRUE
systemOnly: FALSE
defaultObjectCategory: CN=Domain-DNS,<SchemaNCDN>
systemFlags: FLAG_SCHEMA_BASE_OBJECT
```

Version-Specific Behavior: Implemented on Windows 2000 Server operating system, Windows Server 2003 operating system, Windows Server 2003 R2 operating system, Windows Server 2008 operating system, Windows Server 2008 R2 operating system, Windows Server 2012 operating system, and Windows Server 2012 R2 operating system.

2.42 Class domainDNS

A Windows NT operating system domain that has DNS-based (DC=) naming.

```
cn: Domain-DNS
ldapDisplayName: domainDNS
governsId: 1.2.840.113556.1.5.67
objectClassCategory: 1
rdnAttId: dc
subClassOf: domain
systemAuxiliaryClass: samDomain
systemMayContain: msDS-EnabledFeature, msDS-USNLastSyncSuccess,
  msDS-Behavior-Version, msDS-AllowedDNSSuffixes, managedBy
systemPossSuperiors: domainDNS
schemaIdGuid: 19195a5b-6da0-11d0-afd3-00c04fd930c9
defaultSecurityDescriptor: D:
(OA;;CR;1131f6aa-9c07-11d1-f79f-00c04fc2dcd2;;RO)(A;;RP;;;WD)
(OA;;CR;1131f6aa-9c07-11d1-f79f-00c04fc2dcd2;;ED)
(OA;;CR;1131f6ab-9c07-11d1-f79f-00c04fc2dcd2;;ED)
(OA;;CR;1131f6ac-9c07-11d1-f79f-00c04fc2dcd2;;ED)
(OA;;CR;1131f6aa-9c07-11d1-f79f-00c04fc2dcd2;;BA)
(OA;;CR;1131f6ab-9c07-11d1-f79f-00c04fc2dcd2;;BA)
(OA;;CR;1131f6ac-9c07-11d1-f79f-00c04fc2dcd2;;BA)(A;;RPLCLORC;;;AU)
(A;;RPWPCLCLCLOCCRCWDWOSW;;;DA)(A;CI;RPWPCLCLCLOCCRCWDWOSDSW;;;BA)
(A;;RPWPCLCLCLOCCDCRCWDWOSDDTSW;;;SY)
(A;CI;RPWPCLCLCLOCCDCRCWDWOSDDTSW;;;EA)(A;CI;LC;;;RU)
(OA;CIIO;RP;037088f8-0ae1-11d2-b422-00a0c968f939;
bf967aba-0de6-11d0-a285-00aa003049e2;RU)
(OA;CIIO;RP;59ba2f42-79a2-11d0-9020-00c04fc2d3cf;
bf967aba-0de6-11d0-a285-00aa003049e2;RU)
(OA;CIIO;RP;bc0ac240-79a9-11d0-9020-00c04fc2d4cf;
bf967aba-0de6-11d0-a285-00aa003049e2;RU)
(OA;CIIO;RP;4c164200-20c0-11d0-a768-00aa006e0529;
bf967aba-0de6-11d0-a285-00aa003049e2;RU)
```

```

(OA;CIIO;RP;5f202010-79a5-11d0-9020-00c04fc2d4cf;
bf967aba-0de6-11d0-a285-00aa003049e2;RU)
(OA;;RP;c7407360-20bf-11d0-a768-00aa006e0529;;RU)
(OA;CIIO;RPLCLORC;;bf967a9c-0de6-11d0-a285-00aa003049e2;RU)
(A;;RPRC;;;RU)
(OA;CIIO;RPLCLORC;;bf967aba-0de6-11d0-a285-00aa003049e2;RU)
(A;;LCRPLORC;;;ED) (OA;CIIO;RP;037088f8-0ae1-11d2-b422-00a0c968f939;
4828CC14-1437-45bc-9B07-AD6F015E5F28;RU)
(OA;CIIO;RP;59ba2f42-79a2-11d0-9020-00c04fc2d3cf;
4828CC14-1437-45bc-9B07-AD6F015E5F28;RU)
(OA;CIIO;RP;bc0ac240-79a9-11d0-9020-00c04fc2d4cf;
4828CC14-1437-45bc-9B07-AD6F015E5F28;RU)
(OA;CIIO;RP;4c164200-20c0-11d0-a768-00aa006e0529;
4828CC14-1437-45bc-9B07-AD6F015E5F28;RU)
(OA;CIIO;RP;5f202010-79a5-11d0-9020-00c04fc2d4cf;
4828CC14-1437-45bc-9B07-AD6F015E5F28;RU)
(OA;CIIO;RPLCLORC;;4828CC14-1437-45bc-9B07-AD6F015E5F28;RU)
(OA;;RP;b8119fd0-04f6-4762-ab7a-4986c76b3f9a;;RU)
(OA;;RP;b8119fd0-04f6-4762-ab7a-4986c76b3f9a;;AU)
(OA;CIIO;RP;b7c69e6d-2cc7-11d2-854e-00a0c983f608;
bf967aba-0de6-11d0-a285-00aa003049e2;ED)
(OA;CIIO;RP;b7c69e6d-2cc7-11d2-854e-00a0c983f608;
bf967a9c-0de6-11d0-a285-00aa003049e2;ED)
(OA;CIIO;RP;b7c69e6d-2cc7-11d2-854e-00a0c983f608;
bf967a86-0de6-11d0-a285-00aa003049e2;ED)
(OA;CIIO;WP;eal1b7b93-5e48-46d5-bc6c-4df4fda78a35;
bf967a86-0de6-11d0-a285-00aa003049e2;PS)
(OA;;CR;1131f6ad-9c07-11d1-f79f-00c04fc2dcd2;;DD)
(OA;;CR;89e95b76-444d-4c62-991a-0facbeda640c;;ED)
(OA;;CR;1131f6ad-9c07-11d1-f79f-00c04fc2dcd2;;BA)
(OA;;CR;89e95b76-444d-4c62-991a-0facbeda640c;;BA)
(OA;;CR;e2a36dc9-ae17-47c3-b58b-be34c55ba633;;S-1-5-32-557)
(OA;;CR;280f369c-67c7-438e-ae98-1d46f3c6f541;;AU)
(OA;;CR;ccc2dc7d-a6ad-4a7a-8846-c04e3cc53501;;AU)
(OA;;CR;05c74c5e-4deb-43b4-bd9f-86664c2a7fd5;;AU)
(OA;;CR;1131f6ae-9c07-11d1-f79f-00c04fc2dcd2;;ED)
(OA;;CR;1131f6ae-9c07-11d1-f79f-00c04fc2dcd2;;BA)
(OA;CIIO;CRPWP;91e647de-d96f-4b70-9557-d63ff4f3ccd8;;PS)
(OA;CIIO;RPWP;3f78c3e5-f79a-46bd-a0b8-9d18116ddc79;;PS)
S:(AU;SA;WDWOWP;;;WD) (AU;SA;CR;;;BA) (AU;SA;CR;;;DU)
(OU;CISA;WP;f30e3bbe-9ff0-11d1-b603-0000f80367c1;
bf967aa5-0de6-11d0-a285-00aa003049e2;WD)
(OU;CISA;WP;f30e3bbf-9ff0-11d1-b603-0000f80367c1;
bf967aa5-0de6-11d0-a285-00aa003049e2;WD)
defaultHidingValue: FALSE
systemOnly: FALSE
defaultObjectCategory: CN=Domain-DNS,<SchemaNC DN>
systemFlags: FLAG_SCHEMA_BASE_OBJECT

```

Version-Specific Behavior: Implemented on Windows 2000 Server operating system, Windows Server 2003 operating system, Windows Server 2003 R2 operating system, Windows Server 2008 operating system, Windows Server 2008 R2 operating system, Windows Server 2012 operating system, and Windows Server 2012 R2 operating system.

2.43 Class domainPolicy

Defines the Local Security Authority (LSA) policy for one or more domains.

```

cn: Domain-Policy
ldapDisplayName: domainPolicy
governsId: 1.2.840.113556.1.5.18
objectClassCategory: 1
rdnAttId: cn
subClassOf: leaf
systemMayContain: qualityOfService, pwdProperties, pwdHistoryLength,
publicKeyPolicy, proxyLifetime, minTicketAge, minPwdLength,
minPwdAge, maxTicketAge, maxRenewAge, maxPwdAge, managedBy,
lockoutThreshold, lockoutDuration, lockOutObservationWindow,
ipsecPolicyReference, forceLogoff, eFSPolicy, domainWidePolicy,
domainPolicyReference, domainCAs, defaultLocalPolicyObject,
authenticationOptions
systemPossSuperiors: organizationalUnit, domainDNS, container
schemaIdGuid: bf967a99-0de6-11d0-a285-00aa003049e2
defaultSecurityDescriptor: D: (A;;;RPWPCRCDCCLCLORCWOWSDDTSW;;;DA)
(A;;;RPWPCRCDCCLCLORCWOWSDDTSW;;;SY) (A;;;RPLCLORC;;;AU)
defaultHidingValue: TRUE
systemOnly: FALSE
defaultObjectCategory: CN=Domain-Policy,<SchemaNCDN>
systemFlags: FLAG_SCHEMA_BASE_OBJECT

```

Version-Specific Behavior: Implemented on Windows 2000 Server operating system, Windows Server 2003 operating system, Windows Server 2003 R2 operating system, Windows Server 2008 operating system, Windows Server 2008 R2 operating system, Windows Server 2012 operating system, and Windows Server 2012 R2 operating system.

2.44 Class domainRelatedObject

Defines an entry that represents a list of fully qualified domain names (FQDN) (see definition (2) for fully qualified domain name in [\[MS-GLOS\]](#), and also see [\[RFC1035\]](#) section 3.1 and [\[RFC2181\]](#) section 11).

```

cn: domainRelatedObject
ldapDisplayName: domainRelatedObject
governsId: 0.9.2342.19200300.100.4.17
objectClassCategory: 3
rdnAttId: cn
subClassOf: top
mayContain: associatedDomain
schemaIdGuid: 8bfd2d3d-efda-4549-852c-f85e137aedc6
defaultSecurityDescriptor: D: (A;;;RPWPCRCDCCLCLOLORCOWOWSDDTDTSW;;;DA)
(A;;;RPWPCRCDCCLCLORCOWOWSDDTSW;;;SY) (A;;;RPLCLORC;;;AU)
defaultHidingValue: TRUE
systemOnly: FALSE
defaultObjectCategory: CN=domainRelatedObject,<SchemaNCDN>

```

Version-Specific Behavior: Implemented on Windows Server 2003 operating system, Windows Server 2003 R2 operating system, Windows Server 2008 operating system, Windows Server 2008 R2 operating system, Windows Server 2012 operating system, and Windows Server 2012 R2 operating system.

2.45 Class dSA

The X.500 base class for dSA.

```

cn: DSA
ldapDisplayName: dSA
governsId: 2.5.6.13
objectClassCategory: 1
rdnAttId: cn
subClassOf: applicationEntity
systemMayContain: knowledgeInformation
systemPossSuperiors: server, computer
schemaIdGuid: 3fdfee52-47f4-11d1-a9c3-0000f80367c1
defaultSecurityDescriptor: D: (A;;RPWPCRCDCCLCLORCWOWSDSDTSW;;;DA)
(A;;RPWPCRCDCCLCLORCWOWSDSDTSW;;;SY) (A;;RPLCLORC;;;AU)
defaultHidingValue: TRUE
systemOnly: FALSE
defaultObjectCategory: CN=DSA,<SchemaNCDN>
systemFlags: FLAG_SCHEMA_BASE_OBJECT

```

Version-Specific Behavior: Implemented on Windows 2000 Server operating system, Windows Server 2003 operating system, Windows Server 2003 R2 operating system, Windows Server 2008 operating system, Windows Server 2008 R2 operating system, Windows Server 2012 operating system, and Windows Server 2012 R2 operating system.

2.46 Class dSUISettings

Stores configuration settings that are used by the Active Directory Users and Computers snap-in.

```

cn: DS-UI-Settings
ldapDisplayName: dSUISettings
governsId: 1.2.840.113556.1.5.183
objectClassCategory: 1
rdnAttId: cn
subClassOf: top
systemMayContain: msDS-Non-Security-Group-Extra-Classes,
msDS-Security-Group-Extra-Classes, msDS-FilterContainers,
dSUIShellMaximum, dSUIAdminNotification, dSUIAdminMaximum
systemPossSuperiors: container
schemaIdGuid: 09b10f14-6f93-11d2-9905-0000f87a57d4
defaultSecurityDescriptor: D: (A;;RPWPCRCDCCLCLORCWOWSDSDTSW;;;DA)
(A;;RPWPCRCDCCLCLORCWOWSDSDTSW;;;SY) (A;;RPLCLORC;;;AU)
defaultHidingValue: TRUE
systemOnly: FALSE
defaultObjectCategory: CN=DS-UI-Settings,<SchemaNCDN>
systemFlags: FLAG_SCHEMA_BASE_OBJECT

```

Version-Specific Behavior: Implemented on Windows 2000 Server operating system, Windows Server 2003 operating system, Windows Server 2003 R2 operating system, Windows Server 2008 operating system, Windows Server 2008 R2 operating system, Windows Server 2012 operating system, and Windows Server 2012 R2 operating system.

2.47 Class dynamicObject

If present in an entry, this class indicates that this entry has a limited lifetime and may disappear automatically when its Time to Live (TTL) reaches 0. If the client has not supplied a value for the entryTtl attribute, the server provides one.

```

cn: Dynamic-Object

```

```
ldapDisplayName: dynamicObject
governsId: 1.3.6.1.4.1.1466.101.119.2
objectClassCategory: 3
rdnAttId: cn
subClassOf: top
systemMayContain: msDS-Entry-Time-To-Die, entryTTL
schemaIdGuid: 66d51249-3355-4c1f-b24e-81f252aca23b
defaultSecurityDescriptor: D: (A;;RPWPCRCDCCLCLORCWOWSDDTSW;;;DA)
(A;;RPWPCRCDCCLCLORCWOWSDDTSW;;;SY) (A;;RPLCLORC;;;AU)
defaultHidingValue: TRUE
systemOnly: FALSE
defaultObjectCategory: CN=Dynamic-Object,<SchemaNCDN>
systemFlags: FLAG_SCHEMA_BASE_OBJECT
```

Version-Specific Behavior: Implemented on Windows Server 2003 operating system, Windows Server 2003 R2 operating system, Windows Server 2008 operating system, Windows Server 2008 R2 operating system, Windows Server 2012 operating system, and Windows Server 2012 R2 operating system.

2.48 Class fileLinkTracking

The container for [fileLinkTrackingEntry](#) objects.

```
cn: File-Link-Tracking
ldapDisplayName: fileLinkTracking
governsId: 1.2.840.113556.1.5.52
objectClassCategory: 1
rdnAttId: cn
subClassOf: top
systemPossSuperiors: container
schemaIdGuid: dd712229-10e4-11d0-a05f-00aa006c33ed
defaultSecurityDescriptor: D: (A;;RPWPCRCDCCLCLORCWOWSDDTSW;;;DA)
(A;;RPWPCRCDCCLCLORCWOWSDDTSW;;;SY) (A;;RPLCLORC;;;AU)
defaultHidingValue: TRUE
systemOnly: FALSE
defaultObjectCategory: CN=File-Link-Tracking,<SchemaNCDN>
systemFlags: FLAG_SCHEMA_BASE_OBJECT
```

Version-Specific Behavior: Implemented on Windows 2000 Server operating system, Windows Server 2003 operating system, Windows Server 2003 R2 operating system, Windows Server 2008 operating system, Windows Server 2008 R2 operating system, Windows Server 2012 operating system, and Windows Server 2012 R2 operating system.

2.49 Class fileLinkTrackingEntry

Holds the GUID and the current machine information for a link-tracked file. GUID is defined in [\[MS-DTYP\]](#) section 2.3.4.

```
cn: File-Link-Tracking-Entry
ldapDisplayName: fileLinkTrackingEntry
governsId: 1.2.840.113556.1.5.59
objectClassCategory: 1
rdnAttId: cn
subClassOf: top
systemPossSuperiors: fileLinkTracking
```

```

schemaIdGuid: 8e4eb2ed-4712-11d0-ala0-00c04fd930c9
defaultSecurityDescriptor: D: (A;;RPWPCRCDCCLCCLORCWOWDSDDTSW;;;DA)
(A;;RPWPCRCDCCLCCLORCWOWDSDDTSW;;;SY) (A;;RPLCLORC;;;AU)
defaultHidingValue: TRUE
systemOnly: FALSE
defaultObjectCategory: CN=File-Link-Tracking-Entry, <SchemaNCDN>
systemFlags: FLAG_SCHEMA_BASE_OBJECT

```

Version-Specific Behavior: Implemented on Windows 2000 Server operating system, Windows Server 2003 operating system, Windows Server 2003 R2 operating system, Windows Server 2008 operating system, Windows Server 2008 R2 operating system, Windows Server 2012 operating system, and Windows Server 2012 R2 operating system.

2.50 Class foreignSecurityPrincipal

Defines an entry that represents a security principal that is external to the forest.

```

cn: Foreign-Security-Principal
ldapDisplayName: foreignSecurityPrincipal
governsId: 1.2.840.113556.1.5.76
objectClassCategory: 1
rdnAttId: cn
subClassOf: top
systemMustContain: objectSid
systemMayContain: foreignIdentifier
systemPossSuperiors: container
schemaIdGuid: 89e31c12-8530-11d0-afda-00c04fd930c9
defaultSecurityDescriptor: D: (A;;RPWPCRCDCCLCCLORCWOWDSDDTSW;;;DA)
(A;;RPWPCRCDCCLCCLORCWOWDSDDTSW;;;SY)
(A;;RPWPCRCDCCLCCLORCWOWDSDDTSW;;;AO) (A;;RPLCLORC;;;PS)
(OA;;CR;ab721a53-1e2f-11d0-9819-00aa0040529b;;PS)
(OA;;CR;ab721a54-1e2f-11d0-9819-00aa0040529b;;PS)
(OA;;CR;ab721a56-1e2f-11d0-9819-00aa0040529b;;PS)
(OA;;RPWP;77B5B886-944A-11d1-AEBD-0000F80367C1;;PS)
(OA;;RPWP;E45795B2-9455-11d1-AEBD-0000F80367C1;;PS)
(OA;;RPWP;E45795B3-9455-11d1-AEBD-0000F80367C1;;PS) (A;;RC;;;AU)
(OA;;RP;59ba2f42-79a2-11d0-9020-00c04fc2d3cf;;AU)
(OA;;RP;77B5B886-944A-11d1-AEBD-0000F80367C1;;AU)
(OA;;RP;E45795B3-9455-11d1-AEBD-0000F80367C1;;AU)
(OA;;RP;e48d0154-bcf8-11d1-8702-00c04fb96050;;AU)
(OA;;CR;ab721a53-1e2f-11d0-9819-00aa0040529b;;WD)
defaultHidingValue: TRUE
systemOnly: FALSE
defaultObjectCategory: CN=Foreign-Security-Principal, <SchemaNCDN>
systemFlags: FLAG_SCHEMA_BASE_OBJECT

```

Version-Specific Behavior: Implemented on Windows 2000 Server operating system, Windows Server 2003 operating system, Windows Server 2003 R2 operating system, Windows Server 2008 operating system, Windows Server 2008 R2 operating system, Windows Server 2012 operating system, and Windows Server 2012 R2 operating system.

2.51 Class friendlyCountry

Defines country entries in the directory information tree.

```

cn: friendlyCountry
ldapDisplayName: friendlyCountry
governsId: 0.9.2342.19200300.100.4.18
objectClassCategory: 1
rdnAttId: cn
subClassOf: country
mustContain: co
schemaIdGuid: c498f152-dc6b-474a-9f52-7cdba3d7d351
defaultSecurityDescriptor: D: (A;;;RPWPCRCDCDCLCLOLORCWOWDSDDTDSW;;;DA)
(A;;;RPWPCRCDCDCLCLOLORCWOWDSDDTDSW;;;SY) (A;;;RPLCLORC;;;AU)
defaultHidingValue: TRUE
systemOnly: FALSE
defaultObjectCategory: CN=friendlyCountry,<SchemaNCDN>

```

Version-Specific Behavior: Implemented on Windows Server 2003 operating system, Windows Server 2003 R2 operating system, Windows Server 2008 operating system, Windows Server 2008 R2 operating system, Windows Server 2012 operating system, and Windows Server 2012 R2 operating system.

2.52 Class fTDfs

Defines a single fault-tolerant DFS configuration.

```

cn: FT-Dfs
ldapDisplayName: fTDfs
governsId: 1.2.840.113556.1.5.43
objectClassCategory: 1
rdnAttId: cn
subClassOf: top
systemMustContain: remoteServerName, pKTGuid, pKT
systemMayContain: uNCName, managedBy, keywords
systemPossSuperiors: dfsConfiguration
schemaIdGuid: 8447f9f3-1027-11d0-a05f-00aa006c33ed
defaultSecurityDescriptor: D: (A;;;RPWPCRCDCDCLCLOLORCWOWDSDDTDSW;;;DA)
(A;;;RPWPCRCDCDCLCLOLORCWOWDSDDTDSW;;;SY)
(A;;;RPWPCRCDCDCLCLOLORCWOWDSDDTDSW;;;CO) (A;;;RPLCLORC;;;AU)
defaultHidingValue: TRUE
systemOnly: FALSE
defaultObjectCategory: CN=FT-Dfs,<SchemaNCDN>
systemFlags: FLAG_SCHEMA_BASE_OBJECT

```

Version-Specific Behavior: Implemented on Windows 2000 Server operating system, Windows Server 2003 operating system, Windows Server 2003 R2 operating system, Windows Server 2008 operating system, Windows Server 2008 R2 operating system, Windows Server 2012 operating system, and Windows Server 2012 R2 operating system.

2.53 Class group

Stores a list of user names. This class is used to apply security principals on resources.

```

cn: Group
ldapDisplayName: group
governsId: 1.2.840.113556.1.5.8
objectClassCategory: 1
rdnAttId: cn

```

```

subClassOf: top
auxiliaryClass: posixGroup
systemAuxiliaryClass: mailRecipient, securityPrincipal
systemMustContain: groupType
mayContain: msSFU30Name, msSFU30NisDomain, msSFU30PosixMember
systemMayContain: msDS-AzApplicationData,
msDS-AzLastImportedBizRulePath, msDS-AzBizRuleLanguage,
msDS-AzBizRule, msDS-AzGenericData, msDS-AzObjectGuid,
primaryGroupToken, operatorCount, nTGroupMembers, nonSecurityMember,
msDS-NonMembers, msDS-AzLDAPQuery, member, managedBy,
groupMembershipSAM, groupAttributes, mail, desktopProfile,
controlAccessRights, adminCount, msDS-PrimaryComputer
systemPossSuperiors: msDS-AzScope, msDS-AzApplication,
msDS-AzAdminManager, container, builtinDomain, organizationalUnit,
domainDNS
schemaIdGuid: bf967a9c-0de6-11d0-a285-00aa003049e2
defaultSecurityDescriptor: D:(A;;RPWPCRCDCCLCLORCWOWSDDTSW;;;DA)
(A;;RPWPCRCDCCLCLORCWOWSDDTSW;;;SY)(A;;RPLCLORC;;;AU)
(A;;RPWPCRCDCCLCLORCWOWSDDTSW;;;AO)(A;;RPLCLORC;;;PS)
(OA;;CR;ab721a55-1e2f-11d0-9819-00aa0040529b;AU)
(OA;;RP;46a9b11d-60ae-405a-b7e8-ff8a58d456d2;;S-1-5-32-560)
defaultHidingValue: FALSE
systemOnly: FALSE
defaultObjectCategory: CN=Group,<SchemaNCDN>
systemFlags: FLAG_SCHEMA_BASE_OBJECT

```

Version-Specific Behavior: Implemented on Windows 2000 Server operating system, Windows Server 2003 operating system, Windows Server 2003 R2 operating system, Windows Server 2008 operating system, Windows Server 2008 R2 operating system, Windows Server 2012 operating system, and Windows Server 2012 R2 operating system.

2.54 Class groupOfNames

Used to define entries that represent an unordered set of names, which represent individual objects or other groups of names.

```

cn: Group-Of-Names
ldapDisplayName: groupOfNames
governsId: 2.5.6.9
objectClassCategory: 0
rdnAttId: cn
subClassOf: top
systemMustContain: member, cn
systemMayContain: seeAlso, owner, ou, o, businessCategory
systemPossSuperiors: organizationalUnit, locality, organization,
container
schemaIdGuid: bf967a9d-0de6-11d0-a285-00aa003049e2
defaultSecurityDescriptor: D:(A;;RPWPCRCDCCLCLORCWOWSDDTSW;;;DA)
(A;;RPWPCRCDCCLCLORCWOWSDDTSW;;;SY)(A;;RPLCLORC;;;AU)
defaultHidingValue: TRUE
systemOnly: FALSE
defaultObjectCategory: CN=Group-Of-Names,<SchemaNCDN>
systemFlags: FLAG_SCHEMA_BASE_OBJECT

```

Version-Specific Behavior: Implemented on Windows 2000 Server operating system, Windows Server 2003 operating system, Windows Server 2003 R2 operating system, Windows Server 2008

operating system, Windows Server 2008 R2 operating system, Windows Server 2012 operating system, and Windows Server 2012 R2 operating system.

2.55 Class groupOfUniqueNames

Defines the entries for a group of unique names.

```
cn: groupOfUniqueNames
ldapDisplayName: groupOfUniqueNames
governsId: 2.5.6.17
objectClassCategory: 1
rdnAttId: cn
subClassOf: top
mustContain: uniqueMember, cn
mayContain: seeAlso, owner, ou, o, description, businessCategory
possSuperiors: domainDNS, organizationalUnit, container
schemaIdGuid: 0310a911-93a3-4e21-a7a3-55d85ab2c48b
defaultSecurityDescriptor: D: (A;;RPWPCRCDCCLCLORCWOWSDSDTSW;;;DA)
(A;;RPWPCRCDCCLCLORCWOWSDSDTSW;;;SY) (A;;RPLCLORC;;;AU)
(A;;RPWPCRCDCCLCLORCWOWSDSDTSW;;;AO) (A;;RPLCLORC;;;PS)
defaultHidingValue: TRUE
systemOnly: FALSE
defaultObjectCategory: CN=groupOfUniqueNames,<SchemaNCDN>
```

Version-Specific Behavior: Implemented on Windows Server 2003 operating system, Windows Server 2003 R2 operating system, Windows Server 2008 operating system, Windows Server 2008 R2 operating system, Windows Server 2012 operating system, and Windows Server 2012 R2 operating system.

2.56 Class groupPolicyContainer

Represents the Group Policy Object (GPO). This class is used to define Group Policy settings.

```
cn: Group-Policy-Container
ldapDisplayName: groupPolicyContainer
governsId: 1.2.840.113556.1.5.157
objectClassCategory: 1
rdnAttId: cn
subClassOf: container
systemMayContain: versionNumber, gPCWQLFilter, gPCUserExtensionNames,
gPCMachineExtensionNames, gPCFunctionalityVersion, gPCFileSysPath,
flags
schemaIdGuid: f30e3bc2-9ff0-11d1-b603-0000f80367c1
defaultSecurityDescriptor: D:P (A;CI;RPWPCCDCCLCLOLORCWOWSDSDTSW;;;DA)
(A;CI;RPWPCCDCCLCLOLORCWOWSDSDTSW;;;EA)
(A;CI;RPWPCCDCCLCLOLORCWOWSDSDTSW;;;CO)
(A;CI;RPWPCCDCCLCLOLORCWOWSDSDTSW;;;SY) (A;CI;RPLCLORC;;;AU)
(OA;CI;CR;edacfd8f-ffb3-11d1-b41d-00a0c968f939;AU)
(A;CI;LCRPLORC;;;ED)
defaultHidingValue: TRUE
systemOnly: FALSE
defaultObjectCategory: CN=Group-Policy-Container,<SchemaNCDN>
systemFlags: FLAG_SCHEMA_BASE_OBJECT
```

Version-Specific Behavior: Implemented on Windows 2000 Server operating system, Windows Server 2003 operating system, Windows Server 2003 R2 operating system, Windows Server 2008

operating system, Windows Server 2008 R2 operating system, Windows Server 2012 operating system, and Windows Server 2012 R2 operating system.

2.57 Class `ieee802Device`

A device that has a media access control (MAC) address.

```
cn: IEEE802Device
ldapDisplayName: ieee802Device
governsId: 1.3.6.1.1.1.2.11
objectClassCategory: 3
rdnAttId: cn
subClassOf: top
mayContain: cn, macAddress
schemaIdGuid: a699e529-a637-4b7d-a0fb-5dc466a0b8a7
defaultSecurityDescriptor: D: (A;;;RPWPCRCDCCLCLORCWOWSDSDTWS;;;DA)
(A;;;RPWPCRCDCCLCLORCWOWSDSDTWS;;;SY) (A;;;RPLCLORC;;;AU)
defaultHidingValue: TRUE
systemOnly: FALSE
defaultObjectCategory: CN=IEEE802Device,<SchemaNCDN>
```

Version-Specific Behavior: Implemented on Windows Server 2003 R2 operating system, Windows Server 2008 operating system, Windows Server 2008 R2 operating system, Windows Server 2012 operating system, and Windows Server 2012 R2 operating system.

2.58 Class `indexServerCatalog`

Holds the information for an Index Server catalog.

```
cn: Index-Server-Catalog
ldapDisplayName: indexServerCatalog
governsId: 1.2.840.113556.1.5.130
objectClassCategory: 1
rdnAttId: cn
subClassOf: connectionPoint
systemMustContain: creator
systemMayContain: uNCName, queryPoint, indexedScopes, friendlyNames
systemPossSuperiors: organizationalUnit, container
schemaIdGuid: 7bfdcb8a-4807-11d1-a9c3-0000f80367c1
defaultSecurityDescriptor: D: (A;;;RPWPCRCDCCLCLORCWOWSDSDTWS;;;DA)
(A;;;RPWPCRCDCCLCLORCWOWSDSDTWS;;;SY) (A;;;RPLCLORC;;;AU)
defaultHidingValue: TRUE
systemOnly: FALSE
defaultObjectCategory: CN=Index-Server-Catalog,<SchemaNCDN>
systemFlags: FLAG_SCHEMA_BASE_OBJECT
```

Version-Specific Behavior: Implemented on Windows 2000 Server operating system, Windows Server 2003 operating system, Windows Server 2003 R2 operating system, Windows Server 2008 operating system, Windows Server 2008 R2 operating system, Windows Server 2012 operating system, and Windows Server 2012 R2 operating system.

2.59 Class `inetOrgPerson`

Represents people who are associated with an organization.

```

cn: inetOrgPerson
ldapDisplayName: inetOrgPerson
governsId: 2.16.840.1.113730.3.2.2
objectClassCategory: 1
rdnAttId: cn
subClassOf: user
mayContain: x500uniqueIdentifier, userSMIMECertificate, userPKCS12,
  userCertificate, uid, secretary, roomNumber, preferredLanguage,
  photo, pager, o, mobile, manager, mail, labeledURI, jpegPhoto,
  initials, homePostalAddress, homePhone, givenName, employeeType,
  employeeNumber, displayName, departmentNumber, carLicense,
  businessCategory, audio
possSuperiors: domainDNS, organizationalUnit, container
schemaIdGuid: 4828cc14-1437-45bc-9b07-ad6f015e5f28
defaultSecurityDescriptor: D: (A;;RPWPCCDCLCCLORCWOWSDDTSW;;;DA)
  (A;;RPWPCCDCLCCLORCWOWSDDTSW;;;SY)
  (A;;RPWPCCDCLCCLORCWOWSDDTSW;;;AO) (A;;RPLCLORC;;;PS)
  (OA;;CR;ab721a53-1e2f-11d0-9819-00aa0040529b;;;PS)
  (OA;;CR;ab721a54-1e2f-11d0-9819-00aa0040529b;;;PS)
  (OA;;CR;ab721a56-1e2f-11d0-9819-00aa0040529b;;;PS)
  (OA;;RPWP;77B5B886-944A-11d1-AEBD-0000F80367C1;;;PS)
  (OA;;RPWP;E45795B2-9455-11d1-AEBD-0000F80367C1;;;PS)
  (OA;;RPWP;E45795B3-9455-11d1-AEBD-0000F80367C1;;;PS)
  (OA;;RP;037088f8-0ae1-11d2-b422-00a0c968f939;;;RS)
  (OA;;RP;4c164200-20c0-11d0-a768-00aa006e0529;;;RS)
  (OA;;RP;bc0ac240-79a9-11d0-9020-00c04fc2d4cf;;;RS) (A;;RC;;;AU)
  (OA;;RP;59ba2f42-79a2-11d0-9020-00c04fc2d3cf;;;AU)
  (OA;;RP;77B5B886-944A-11d1-AEBD-0000F80367C1;;;AU)
  (OA;;RP;E45795B3-9455-11d1-AEBD-0000F80367C1;;;AU)
  (OA;;RP;e48d0154-bcf8-11d1-8702-00c04fb96050;;;AU)
  (OA;;CR;ab721a53-1e2f-11d0-9819-00aa0040529b;;;WD)
  (OA;;RP;5f202010-79a5-11d0-9020-00c04fc2d4cf;;;RS)
  (OA;;RPWP;bf967a7f-0de6-11d0-a285-00aa003049e2;;;CA)
  (OA;;RP;46a9b11d-60ae-405a-b7e8-ff8a58d456d2;;;S-1-5-32-560)
  (OA;;WPRP;6db69a1c-9422-11d1-aebd-0000f80367c1;;;S-1-5-32-561)
  (OA;;WPRE;5805bc62-bdc9-4428-a5e2-856a0f4c185e;;;S-1-5-32-561)
defaultHidingValue: FALSE
systemOnly: FALSE
defaultObjectCategory: CN=Person,<SchemaNCDN>

```

Version-Specific Behavior: Implemented on Windows Server 2003 operating system, Windows Server 2003 R2 operating system, Windows Server 2008 operating system, Windows Server 2008 R2 operating system, Windows Server 2012 operating system, and Windows Server 2012 R2 operating system.

2.60 Class infrastructureUpdate

Represents the infrastructure master for a domain.

```

cn: Infrastructure-Update
ldapDisplayName: infrastructureUpdate
governsId: 1.2.840.113556.1.5.175
objectClassCategory: 1
rdnAttId: cn
subClassOf: top
systemMayContain: dNReferenceUpdate
systemPossSuperiors: infrastructureUpdate, domain

```

```
schemaIdGuid: 2df90d89-009f-11d2-aa4c-00c04fd7d83a
defaultSecurityDescriptor: D: (A;;GA;;;SY)
defaultHidingValue: TRUE
systemOnly: TRUE
defaultObjectCategory: CN=Infrastructure-Update,<SchemaNCDN>
systemFlags: FLAG_SCHEMA_BASE_OBJECT
```

Version-Specific Behavior: Implemented on Windows 2000 Server operating system, Windows Server 2003 operating system, Windows Server 2003 R2 operating system, Windows Server 2008 operating system, Windows Server 2008 R2 operating system, Windows Server 2012 operating system, and Windows Server 2012 R2 operating system.

2.61 Class `intellimirrorGroup`

Remote boot legacy for managing groups of server machines.

```
cn: Intellimirror-Group
ldapDisplayName: intellimirrorGroup
governsId: 1.2.840.113556.1.5.152
objectClassCategory: 1
rdnAttId: cn
subClassOf: top
systemPossSuperiors: domainDNS, organizationalUnit, container
schemaIdGuid: 07383086-91df-11d1-aebc-0000f80367c1
defaultSecurityDescriptor: D: (A;;RPWPCRCCDCLCLORCWOWSDDTSW;;;SY)
(A;;RPWPCRCCDCLCLORCWOWSDDTSW;;;DA) (A;;CCDC;;;CO) (A;;RPLCLORC;;;AU)
defaultHidingValue: TRUE
systemOnly: FALSE
defaultObjectCategory: CN=Intellimirror-Group,<SchemaNCDN>
systemFlags: FLAG_SCHEMA_BASE_OBJECT
```

Version-Specific Behavior: Implemented on Windows 2000 Server operating system, Windows Server 2003 operating system, Windows Server 2003 R2 operating system, Windows Server 2008 operating system, Windows Server 2008 R2 operating system, Windows Server 2012 operating system, and Windows Server 2012 R2 operating system.

2.62 Class `intellimirrorSCP`

Contains configuration information for the service that responds to Remote Boot clients that are requesting attention from a Remote Install Server.

```
cn: Intellimirror-SCP
ldapDisplayName: intellimirrorSCP
governsId: 1.2.840.113556.1.5.151
objectClassCategory: 1
rdnAttId: cn
subClassOf: serviceAdministrationPoint
systemMayContain: netbootTools, netbootServer, netbootNewMachineOU,
netbootNewMachineNamingPolicy, netbootMaxClients,
netbootMachineFilePath, netbootLocallyInstalledOSes,
netbootLimitClients, netbootIntelliMirrorOSes,
netbootCurrentClientCount, netbootAnswerRequests,
netbootAnswerOnlyValidClients, netbootAllowNewClients
systemPossSuperiors: computer, intellimirrorGroup
schemaIdGuid: 07383085-91df-11d1-aebc-0000f80367c1
```

```
defaultSecurityDescriptor: D: (A;;;RPWPCRCDCCLCLOCRCWOWSDDTSW;;;DA)
  (A;;;RPWPCRCDCCLCLOCRCWOWSDDTSW;;;SY) (A;;;RPLCLORC;;;AU)
defaultHidingValue: TRUE
systemOnly: FALSE
defaultObjectCategory: CN=Intellimirror-SCP,<SchemaNCDN>
systemFlags: FLAG_SCHEMA_BASE_OBJECT
```

Version-Specific Behavior: Implemented on Windows 2000 Server operating system, Windows Server 2003 operating system, Windows Server 2003 R2 operating system, Windows Server 2008 operating system, Windows Server 2008 R2 operating system, Windows Server 2012 operating system, and Windows Server 2012 R2 operating system.

2.63 Class `interSiteTransport`

Contains information about the transport used for intersite replication. Objects of this class can contain information about IP or Simple Mail Transfer Protocol (SMTP) transport.

```
cn: Inter-Site-Transport
ldapDisplayName: interSiteTransport
governsId: 1.2.840.113556.1.5.141
objectClassCategory: 1
rdnAttId: cn
subClassOf: top
systemMustContain: transportDLLName, transportAddressAttribute
systemMayContain: replInterval, options
systemPossSuperiors: interSiteTransportContainer
schemaIdGuid: 26d97376-6070-11d1-a9c6-0000f80367c1
defaultSecurityDescriptor: D: (A;;;RPWPCRCDCCLCLOCRCWOWSDDTSW;;;DA)
  (A;;;RPWPCRCDCCLCLOCRCWOWSDDTSW;;;SY) (A;;;RPLCLORC;;;AU)
defaultHidingValue: TRUE
systemOnly: FALSE
defaultObjectCategory: CN=Inter-Site-Transport,<SchemaNCDN>
systemFlags: FLAG_SCHEMA_BASE_OBJECT
```

Version-Specific Behavior: Implemented on Windows 2000 Server operating system, Windows Server 2003 operating system, Windows Server 2003 R2 operating system, Windows Server 2008 operating system, Windows Server 2008 R2 operating system, Windows Server 2012 operating system, and Windows Server 2012 R2 operating system.

2.64 Class `interSiteTransportContainer`

Holds [interSiteTransport](#) objects.

```
cn: Inter-Site-Transport-Container
ldapDisplayName: interSiteTransportContainer
governsId: 1.2.840.113556.1.5.140
objectClassCategory: 1
rdnAttId: cn
subClassOf: top
systemPossSuperiors: sitesContainer
schemaIdGuid: 26d97375-6070-11d1-a9c6-0000f80367c1
defaultSecurityDescriptor: D: (A;;;RPWPCRCDCCLCLOCRCWOWSDDTSW;;;DA)
  (A;;;RPWPCRCDCCLCLOCRCWOWSDDTSW;;;SY) (A;;;RPLCLORC;;;AU)
defaultHidingValue: TRUE
systemOnly: FALSE
```

```
defaultObjectCategory: CN=Inter-Site-Transport-Container,<SchemaNCDN>
systemFlags: FLAG_SCHEMA_BASE_OBJECT
```

Version-Specific Behavior: Implemented on Windows 2000 Server operating system, Windows Server 2003 operating system, Windows Server 2003 R2 operating system, Windows Server 2008 operating system, Windows Server 2008 R2 operating system, Windows Server 2012 operating system, and Windows Server 2012 R2 operating system.

2.65 Class ipHost

An abstraction of a host; an IP device.

```
cn: IpHost
ldapDisplayName: ipHost
governsId: 1.3.6.1.1.1.2.6
objectClassCategory: 3
rdnAttId: cn
subClassOf: top
mayContain: manager, cn, description, ipHostNumber, uid, 1
schemaIdGuid: ab911646-8827-4f95-8780-5a8f008eb68f
defaultSecurityDescriptor: D: (A;;RPWPCRCDCCLCLORCWOWSDDTSW;;;DA)
(A;;RPWPCRCDCCLCLORCWOWSDDTSW;;;SY) (A;;RPLCLORC;;;AU)
defaultHidingValue: TRUE
systemOnly: FALSE
defaultObjectCategory: CN=IpHost,<SchemaNCDN>
```

Version-Specific Behavior: Implemented on Windows Server 2003 R2 operating system, Windows Server 2008 operating system, Windows Server 2008 R2 operating system, Windows Server 2012 operating system, and Windows Server 2012 R2 operating system.

2.66 Class ipNetwork

An abstraction of a network. The distinguished value of the cn attribute denotes the canonical name of the network.

```
cn: IpNetwork
ldapDisplayName: ipNetwork
governsId: 1.3.6.1.1.1.2.7
objectClassCategory: 1
rdnAttId: cn
subClassOf: top
mustContain: cn, ipNetworkNumber
mayContain: manager, description, ipNetmaskNumber, uid, 1,
msSFU30Name, msSFU30NisDomain, nisMapName, msSFU30Aliases
possSuperiors: domainDNS, nisMap, container, organizationalUnit
schemaIdGuid: d95836c3-143e-43fb-992a-b057f1ecadf9
defaultSecurityDescriptor: D: (A;;RPWPCRCDCCLCLORCWOWSDDTSW;;;DA)
(A;;RPWPCRCDCCLCLORCWOWSDDTSW;;;SY) (A;;RPLCLORC;;;AU)
defaultHidingValue: TRUE
systemOnly: FALSE
defaultObjectCategory: CN=IpNetwork,<SchemaNCDN>
```

Version-Specific Behavior: Implemented on Windows Server 2003 R2 operating system, Windows Server 2008 operating system, Windows Server 2008 R2 operating system, Windows Server 2012 operating system, and Windows Server 2012 R2 operating system.

2.67 Class ipProtocol

An abstraction of an IP protocol.

```
cn: IpProtocol
ldapDisplayName: ipProtocol
governsId: 1.3.6.1.1.1.2.4
objectClassCategory: 1
rdnAttId: cn
subClassOf: top
mustContain: cn, ipProtocolNumber
mayContain: description, msSFU30Name, msSFU30NisDomain, nisMapName,
  msSFU30Aliases
possSuperiors: domainDNS, nisMap, container, organizationalUnit
schemaIdGuid: 9c2dcbd2-fbf0-4dc7-ace0-8356dcd0f013
defaultSecurityDescriptor: D: (A;;RPWPCRCDCCLCLORCWOWSDDTSW;;;DA)
  (A;;RPWPCRCDCCLCLORCWOWSDDTSW;;;SY) (A;;RPLCLORC;;;AU)
defaultHidingValue: TRUE
systemOnly: FALSE
defaultObjectCategory: CN=IpProtocol,<SchemaNCDN>
```

Version-Specific Behavior: Implemented on Windows Server 2003 R2 operating system, Windows Server 2008 operating system, Windows Server 2008 R2 operating system, Windows Server 2012 operating system, and Windows Server 2012 R2 operating system.

2.68 Class ipsecBase

An Internet Protocol security (IPsec) base class from which all IPsec classes are derived.

```
cn: Ipsec-Base
ldapDisplayName: ipsecBase
governsId: 1.2.840.113556.1.5.7000.56
objectClassCategory: 2
rdnAttId: cn
subClassOf: top
systemMayContain: ipsecOwnersReference, ipsecName, ipsecID,
  ipsecDataType, ipsecData
schemaIdGuid: b40ff825-427a-11d1-a9c2-0000f80367c1
defaultSecurityDescriptor: D:
defaultHidingValue: TRUE
systemOnly: FALSE
defaultObjectCategory: CN=Ipsec-Base,<SchemaNCDN>
systemFlags: FLAG_SCHEMA_BASE_OBJECT
```

Version-Specific Behavior: Implemented on Windows 2000 Server operating system, Windows Server 2003 operating system, Windows Server 2003 R2 operating system, Windows Server 2008 operating system, Windows Server 2008 R2 operating system, Windows Server 2012 operating system, and Windows Server 2012 R2 operating system.

2.69 Class ipsecFilter

A filter expression for applying security.

```
cn: Ipsec-Filter
ldapDisplayName: ipsecFilter
governsId: 1.2.840.113556.1.5.118
objectClassCategory: 1
rdnAttId: cn
subClassOf: ipsecBase
systemPossSuperiors: organizationalUnit, computer, container
schemaIdGuid: b40ff826-427a-11d1-a9c2-0000f80367c1
defaultSecurityDescriptor: D:
defaultHidingValue: TRUE
systemOnly: FALSE
defaultObjectCategory: CN=Ipsec-Filter,<SchemaNCDN>
systemFlags: FLAG_SCHEMA_BASE_OBJECT
```

Version-Specific Behavior: Implemented on Windows 2000 Server operating system, Windows Server 2003 operating system, Windows Server 2003 R2 operating system, Windows Server 2008 operating system, Windows Server 2008 R2 operating system, Windows Server 2012 operating system, and Windows Server 2012 R2 operating system.

2.70 Class ipsecISAKMPPolicy

This class is for internal use only.

```
cn: Ipsec-ISAKMP-Policy
ldapDisplayName: ipsecISAKMPPolicy
governsId: 1.2.840.113556.1.5.120
objectClassCategory: 1
rdnAttId: cn
subClassOf: ipsecBase
systemPossSuperiors: container, computer, organizationalUnit
schemaIdGuid: b40ff828-427a-11d1-a9c2-0000f80367c1
defaultSecurityDescriptor: D:
defaultHidingValue: TRUE
systemOnly: FALSE
defaultObjectCategory: CN=Ipsec-ISAKMP-Policy,<SchemaNCDN>
systemFlags: FLAG_SCHEMA_BASE_OBJECT
```

Version-Specific Behavior: Implemented on Windows 2000 Server operating system, Windows Server 2003 operating system, Windows Server 2003 R2 operating system, Windows Server 2008 operating system, Windows Server 2008 R2 operating system, Windows Server 2012 operating system, and Windows Server 2012 R2 operating system.

2.71 Class ipsecNegotiationPolicy

This class is for internal use only.

```
cn: Ipsec-Negotiation-Policy
ldapDisplayName: ipsecNegotiationPolicy
governsId: 1.2.840.113556.1.5.119
objectClassCategory: 1
rdnAttId: cn
```



```
subClassOf: ipsecBase
systemMayContain: iPSECNegotiationPolicyType,
  iPSECNegotiationPolicyAction
systemPossSuperiors: organizationalUnit, computer, container
schemaIdGuid: b40ff827-427a-11d1-a9c2-0000f80367c1
defaultSecurityDescriptor: D:
defaultHidingValue: TRUE
systemOnly: FALSE
defaultObjectCategory: CN=Ipsec-Negotiation-Policy,<SchemaNCN>
systemFlags: FLAG_SCHEMA_BASE_OBJECT
```

Version-Specific Behavior: Implemented on Windows 2000 Server operating system, Windows Server 2003 operating system, Windows Server 2003 R2 operating system, Windows Server 2008 operating system, Windows Server 2008 R2 operating system, Windows Server 2012 operating system, and Windows Server 2012 R2 operating system.

2.72 Class ipsecNFA

This class is for internal use only.

```
cn: Ipsec-NFA
ldapDisplayName: ipsecNFA
governsId: 1.2.840.113556.1.5.121
objectClassCategory: 1
rdnAttId: cn
subClassOf: ipsecBase
systemMayContain: ipsecNegotiationPolicyReference,
  ipsecFilterReference
systemPossSuperiors: container, computer, organizationalUnit
schemaIdGuid: b40ff829-427a-11d1-a9c2-0000f80367c1
defaultSecurityDescriptor: D:
defaultHidingValue: TRUE
systemOnly: FALSE
defaultObjectCategory: CN=Ipsec-NFA,<SchemaNCN>
systemFlags: FLAG_SCHEMA_BASE_OBJECT
```

Version-Specific Behavior: Implemented on Windows 2000 Server operating system, Windows Server 2003 operating system, Windows Server 2003 R2 operating system, Windows Server 2008 operating system, Windows Server 2008 R2 operating system, Windows Server 2012 operating system, and Windows Server 2012 R2 operating system.

2.73 Class ipsecPolicy

This class is for internal use only.

```
cn: Ipsec-Policy
ldapDisplayName: ipsecPolicy
governsId: 1.2.840.113556.1.5.98
objectClassCategory: 1
rdnAttId: cn
subClassOf: ipsecBase
systemMayContain: ipsecNFAResource, ipsecISAKMPReference
systemPossSuperiors: organizationalUnit, computer, container
schemaIdGuid: b7b13121-b82e-11d0-afee-0000f80367c1
defaultSecurityDescriptor: D:
```

```
defaultHidingValue: TRUE
systemOnly: FALSE
defaultObjectCategory: CN=Ipsec-Policy,<SchemaNCDN>
systemFlags: FLAG_SCHEMA_BASE_OBJECT
```

Version-Specific Behavior: Implemented on Windows 2000 Server operating system, Windows Server 2003 operating system, Windows Server 2003 R2 operating system, Windows Server 2008 operating system, Windows Server 2008 R2 operating system, Windows Server 2012 operating system, and Windows Server 2012 R2 operating system.

2.74 Class ipService

An abstraction of an IP service.

```
cn: IpService
ldapDisplayName: ipService
governsId: 1.3.6.1.1.1.2.3
objectClassCategory: 1
rdnAttId: cn
subClassOf: top
mustContain: ipServiceProtocol, ipServicePort, cn
mayContain: description, msSFU30Name, msSFU30NisDomain,
  msSFU30Aliases, nisMapName
possSuperiors: domainDNS, nisMap, container, organizationalUnit
schemaIdGuid: 2517fadf-fa97-48ad-9de6-79ac5721f864
defaultSecurityDescriptor: D: (A;;RPWPCRCDCCLCLORCWOWSDDTSW;;;DA)
  (A;;RPWPCRCDCCLCLORCWOWSDDTSW;;;SY) (A;;RPLCLORC;;;AU)
defaultHidingValue: TRUE
systemOnly: FALSE
defaultObjectCategory: CN=IpService,<SchemaNCDN>
```

Version-Specific Behavior: Implemented on Windows Server 2003 R2 operating system, Windows Server 2008 operating system, Windows Server 2008 R2 operating system, Windows Server 2012 operating system, and Windows Server 2012 R2 operating system.

2.75 Class leaf

A base class for leaf objects.

```
cn: Leaf
ldapDisplayName: leaf
governsId: 1.2.840.113556.1.5.20
objectClassCategory: 2
rdnAttId: cn
subClassOf: top
schemaIdGuid: bf967a9e-0de6-11d0-a285-00aa003049e2
defaultSecurityDescriptor: D: (A;;RPWPCRCDCCLCLORCWOWSDDTSW;;;DA)
  (A;;RPWPCRCDCCLCLORCWOWSDDTSW;;;SY) (A;;RPLCLORC;;;AU)
defaultHidingValue: TRUE
systemOnly: FALSE
defaultObjectCategory: CN=Leaf,<SchemaNCDN>
systemFlags: FLAG_SCHEMA_BASE_OBJECT
```

Version-Specific Behavior: Implemented on Windows 2000 Server operating system, Windows Server 2003 operating system, Windows Server 2003 R2 operating system, Windows Server 2008 operating system, Windows Server 2008 R2 operating system, Windows Server 2012 operating system, and Windows Server 2012 R2 operating system.

2.76 Class `licensingSiteSettings`

Points to the licensing server for a site.

```
cn: Licensing-Site-Settings
ldapDisplayName: licensingSiteSettings
governsId: 1.2.840.113556.1.5.78
objectClassCategory: 1
rdnAttId: cn
subClassOf: applicationSiteSettings
systemMayContain: siteServer
systemPossSuperiors: site
schemaIdGuid: 1be8f17d-a9ff-11d0-afe2-00c04fd930c9
defaultSecurityDescriptor: D: (A;;RPWPCRCDCCLCLORCWOWDSDDTSW;;;DA)
(A;;RPWPCRCDCCLCLORCWOWDSDDTSW;;;SY) (A;;RPLCLORC;;;AU)
defaultHidingValue: TRUE
systemOnly: FALSE
defaultObjectCategory: CN=Licensing-Site-Settings,<SchemaNCDN>
systemFlags: FLAG_SCHEMA_BASE_OBJECT
```

Version-Specific Behavior: Implemented on Windows 2000 Server operating system, Windows Server 2003 operating system, Windows Server 2003 R2 operating system, Windows Server 2008 operating system, Windows Server 2008 R2 operating system, Windows Server 2012 operating system, and Windows Server 2012 R2 operating system.

2.77 Class `linkTrackObjectMoveTable`

A container for [linkTrackOMTEntry](#) objects.

```
cn: Link-Track-Object-Move-Table
ldapDisplayName: linkTrackObjectMoveTable
governsId: 1.2.840.113556.1.5.91
objectClassCategory: 1
rdnAttId: cn
subClassOf: fileLinkTracking
systemPossSuperiors: fileLinkTracking
schemaIdGuid: ddac0cf5-af8f-11d0-afeb-00c04fd930c9
defaultSecurityDescriptor: D: (A;;RPWPCRCDCCLCLORCWOWDSDDTSW;;;DA)
(A;;RPWPCRCDCCLCLORCWOWDSDDTSW;;;SY) (A;;RPLCLORC;;;AU)
defaultHidingValue: TRUE
systemOnly: FALSE
defaultObjectCategory: CN=Link-Track-Object-Move-Table,<SchemaNCDN>
systemFlags: FLAG_SCHEMA_BASE_OBJECT
```

Version-Specific Behavior: Implemented on Windows 2000 Server operating system, Windows Server 2003 operating system, Windows Server 2003 R2 operating system, Windows Server 2008 operating system, Windows Server 2008 R2 operating system, Windows Server 2012 operating system, and Windows Server 2012 R2 operating system.

2.78 Class linkTrackOMTEntry

Tracks the link for objects that have moved.

```
cn: Link-Track-OMT-Entry
ldapDisplayName: linkTrackOMTEntry
governsId: 1.2.840.113556.1.5.93
objectClassCategory: 1
rdnAttId: cn
subClassOf: leaf
systemMayContain: timeRefresh, oMTIndxGuid, oMTGuid, currentLocation,
  birthLocation
systemPossSuperiors: linkTrackObjectMoveTable
schemaIdGuid: ddac0cf7-af8f-11d0-afeb-00c04fd930c9
defaultSecurityDescriptor: D: (A;;RPWPCRCDCCLCLORCWOWSDSDTSW;;;DA)
  (A;;RPWPCRCDCCLCLORCWOWSDSDTSW;;;SY) (A;;RPLCLORC;;;AU)
defaultHidingValue: TRUE
systemOnly: FALSE
defaultObjectCategory: CN=Link-Track-OMT-Entry,<SchemaNCDN>
systemFlags: FLAG_SCHEMA_BASE_OBJECT
```

Version-Specific Behavior: Implemented on Windows 2000 Server operating system, Windows Server 2003 operating system, Windows Server 2003 R2 operating system, Windows Server 2008 operating system, Windows Server 2008 R2 operating system, Windows Server 2012 operating system, and Windows Server 2012 R2 operating system.

2.79 Class linkTrackVolEntry

The entry for a link to a file on a volume.

```
cn: Link-Track-Vol-Entry
ldapDisplayName: linkTrackVolEntry
governsId: 1.2.840.113556.1.5.92
objectClassCategory: 1
rdnAttId: cn
subClassOf: leaf
systemMayContain: volTableIdxGUID, volTableGUID, timeVolChange,
  timeRefresh, seqNotification, objectCount, linkTrackSecret,
  currMachineId
systemPossSuperiors: linkTrackVolumeTable
schemaIdGuid: ddac0cf6-af8f-11d0-afeb-00c04fd930c9
defaultSecurityDescriptor: D: (A;;RPWPCRCDCCLCLORCWOWSDSDTSW;;;DA)
  (A;;RPWPCRCDCCLCLORCWOWSDSDTSW;;;SY)
defaultHidingValue: TRUE
systemOnly: FALSE
defaultObjectCategory: CN=Link-Track-Vol-Entry,<SchemaNCDN>
systemFlags: FLAG_SCHEMA_BASE_OBJECT
```

Version-Specific Behavior: Implemented on Windows 2000 Server operating system, Windows Server 2003 operating system, Windows Server 2003 R2 operating system, Windows Server 2008 operating system, Windows Server 2008 R2 operating system, Windows Server 2012 operating system, and Windows Server 2012 R2 operating system.

2.80 Class linkTrackVolumeTable

A container for [linkTrackVolEntry](#) objects.

```
cn: Link-Track-Volume-Table
ldapDisplayName: linkTrackVolumeTable
governsId: 1.2.840.113556.1.5.90
objectClassCategory: 1
rdnAttId: cn
subClassOf: fileLinkTracking
systemPossSuperiors: fileLinkTracking
schemaIdGuid: ddac0cf4-af8f-11d0-afeb-00c04fd930c9
defaultSecurityDescriptor: D: (A;;RPWPCRCDCCLCLORCWOWSDDTSW;;;DA)
(A;;RPWPCRCDCCLCLORCWOWSDDTSW;;;SY) (A;;RPLCLORC;;;AU)
defaultHidingValue: TRUE
systemOnly: FALSE
defaultObjectCategory: CN=Link-Track-Volume-Table,<SchemaNCDN>
systemFlags: FLAG_SCHEMA_BASE_OBJECT
```

Version-Specific Behavior: Implemented on Windows 2000 Server operating system, Windows Server 2003 operating system, Windows Server 2003 R2 operating system, Windows Server 2008 operating system, Windows Server 2008 R2 operating system, Windows Server 2012 operating system, and Windows Server 2012 R2 operating system.

2.81 Class locality

Contains a locality, such as a street address, city, and state.

```
cn: Locality
ldapDisplayName: locality
governsId: 2.5.6.3
objectClassCategory: 1
rdnAttId: l
subClassOf: top
systemMustContain: l
systemMayContain: street, st, seeAlso, searchGuide
systemPossSuperiors: domainDNS, country, organizationalUnit,
organization, locality
schemaIdGuid: bf967aa0-0de6-11d0-a285-00aa003049e2
defaultSecurityDescriptor: D: (A;;RPWPCRCDCCLCLORCWOWSDDTSW;;;DA)
(A;;RPWPCRCDCCLCLORCWOWSDDTSW;;;SY) (A;;RPLCLORC;;;AU)
defaultHidingValue: FALSE
systemOnly: FALSE
defaultObjectCategory: CN=Locality,<SchemaNCDN>
systemFlags: FLAG_SCHEMA_BASE_OBJECT
```

Version-Specific Behavior: Implemented on Windows 2000 Server operating system, Windows Server 2003 operating system, Windows Server 2003 R2 operating system, Windows Server 2008 operating system, Windows Server 2008 R2 operating system, Windows Server 2012 operating system, and Windows Server 2012 R2 operating system.

2.82 Class lostAndFound

A special container for orphaned objects.

```
cn: Lost-And-Found
ldapDisplayName: lostAndFound
governsId: 1.2.840.113556.1.5.139
objectClassCategory: 1
rdnAttId: cn
subClassOf: top
systemMayContain: moveTreeState
systemPossSuperiors: configuration, domainDNS, dMD
schemaIdGuid: 52ab8671-5709-11d1-a9c6-0000f80367c1
defaultSecurityDescriptor: D: (A;;;RPWPCRCDCCLCLORCWOWSDSDTWS;;;DA)
(A;;;RPWPCRCDCCLCLORCWOWSDSDTWS;;;SY) (A;;;RPLCLORC;;;AU)
defaultHidingValue: TRUE
systemOnly: FALSE
defaultObjectCategory: CN=Lost-And-Found,<SchemaNCN>
systemFlags: FLAG_SCHEMA_BASE_OBJECT
```

Version-Specific Behavior: Implemented on Windows 2000 Server operating system, Windows Server 2003 operating system, Windows Server 2003 R2 operating system, Windows Server 2008 operating system, Windows Server 2008 R2 operating system, Windows Server 2012 operating system, and Windows Server 2012 R2 operating system.

2.83 Class mailRecipient

Stores email configuration information.

```
cn: Mail-Recipient
ldapDisplayName: mailRecipient
governsId: 1.2.840.113556.1.3.46
objectClassCategory: 3
rdnAttId: cn
subClassOf: top
systemMustContain: cn
mayContain: msDS-PhoneticDisplayName, userSMIMECertificate,
secretary, msExchLabeledURI, msExchAssistantName, labeledURI,
msDS-GeoCoordinatesAltitude, msDS-GeoCoordinatesLatitude,
msDS-GeoCoordinatesLongitude
systemMayContain: userCertificate, userCert, textEncodedORAddress,
telephoneNumber, showInAddressBook, legacyExchangeDN,
garbageCollPeriod, info
systemPossSuperiors: container
schemaIdGuid: bf967aa1-0de6-11d0-a285-00aa003049e2
defaultSecurityDescriptor: D: (A;;;RPWPCRCDCCLCLORCWOWSDSDTWS;;;DA)
(A;;;RPWPCRCDCCLCLORCWOWSDSDTWS;;;SY) (A;;;RPLCLORC;;;AU)
defaultHidingValue: TRUE
systemOnly: FALSE
defaultObjectCategory: CN=Mail-Recipient,<SchemaNCN>
systemFlags: FLAG_SCHEMA_BASE_OBJECT
```

Version-Specific Behavior: Implemented on Windows 2000 Server operating system, Windows Server 2003 operating system, Windows Server 2003 R2 operating system, Windows Server 2008 operating system, Windows Server 2008 R2 operating system, Windows Server 2012 operating system, and Windows Server 2012 R2 operating system.

2.84 Class meeting

Stores information for setting up a meeting.

```
cn: Meeting
ldapDisplayName: meeting
governsId: 1.2.840.113556.1.5.104
objectClassCategory: 1
rdnAttId: cn
subClassOf: top
systemMustContain: meetingName
systemMayContain: meetingURL, meetingType, meetingStartTime,
meetingScope, meetingRecurrence, meetingRating, meetingProtocol,
meetingOwner, meetingOriginator, meetingMaxParticipants,
meetingLocation, meetingLanguage, meetingKeyword,
meetingIsEncrypted, meetingIP, meetingID, meetingEndTime,
meetingDescription, meetingContactInfo, meetingBlob,
meetingBandwidth, meetingApplication, meetingAdvertiseScope
systemPossSuperiors: container
schemaIdGuid: 11b6cc94-48c4-11d1-a9c3-0000f80367c1
defaultSecurityDescriptor: D: (A;;RPWPCRCCLCCLORCWOWDSDDTSW;;;DA)
(A;;RPWPCRCCLCCLORCWOWDSDDTSW;;;SY) (A;;RPLCLORC;;;AU)
defaultHidingValue: TRUE
systemOnly: FALSE
defaultObjectCategory: CN=Meeting, <SchemaNCDN>
systemFlags: FLAG_SCHEMA_BASE_OBJECT
```

Version-Specific Behavior: Implemented on Windows 2000 Server operating system, Windows Server 2003 operating system, Windows Server 2003 R2 operating system, Windows Server 2008 operating system, Windows Server 2008 R2 operating system, Windows Server 2012 operating system, and Windows Server 2012 R2 operating system.

2.85 Class ms-net-ieee-80211-GroupPolicy

This class represents an 802.11 wireless network Group Policy Object and contains identifiers and configuration data relevant to an 802.11 wireless network.

```
cn: ms-net-ieee-80211-GroupPolicy
ldapDisplayName: ms-net-ieee-80211-GroupPolicy
governsID: 1.2.840.113556.1.5.251
objectClassCategory: 1
rdnAttID: cn
subClassOf: top
systemMayContain: ms-net-ieee-80211-GP-PolicyReserved,
ms-net-ieee-80211-GP-PolicyData, ms-net-ieee-80211-GP-PolicyGUID
systemPossSuperiors: computer, container, person
schemaIDGUID: 1cb81863-b822-4379-9ea2-5ff7bdc6386d
defaultSecurityDescriptor: D: (A;;RPWPCRCCLCCLORCWOWDSDDTSW;;;DA)
(A;;RPWPCRCCLCCLORCWOWDSDDTSW;;;SY) (A;;RPLCLORC;;;AU)
defaultHidingValue: TRUE
systemOnly: FALSE
defaultObjectCategory: CN=ms-net-ieee-80211-GroupPolicy,
<SchemaNCDN>
systemFlags: FLAG_SCHEMA_BASE_OBJECT
```

Version-Specific Behavior: Implemented on Windows Server 2008 operating system, Windows Server 2008 R2 operating system, Windows Server 2012 operating system, and Windows Server 2012 R2 operating system.

2.86 Class ms-net-ieee-8023-GroupPolicy

This class represents an 802.3 wired network GPO and contains identifiers and configuration data that are relevant to an 802.3 wired network.

```
cn: ms-net-ieee-8023-GroupPolicy
LDAPDisplayName: ms-net-ieee-8023-GroupPolicy
governsID: 1.2.840.113556.1.5.252
objectClassCategory: 1
rdnAttID: cn
subClassOf: top
systemMayContain: ms-net-ieee-8023-GP-PolicyReserved,
  ms-net-ieee-8023-GP-PolicyData, ms-net-ieee-8023-GP-PolicyGUID
systemPossSuperiors: computer, container, person
schemaIDGUID: 99a03a6a-ab19-4446-9350-0cb878ed2d9b
defaultSecurityDescriptor: D: (A;;RPWPCRCDCCLCLORCWOWDSDDTSW;;;DA)
  (A;;RPWPCRCDCCLCLORCWOWDSDDTSW;;;SY) (A;;RPLCLORC;;;AU)
defaultHidingValue: TRUE
systemOnly: FALSE
defaultObjectCategory: CN=ms-net-ieee-8023-GroupPolicy,<SchemaNCDN>
systemFlags: FLAG_SCHEMA_BASE_OBJECT
```

Version-Specific Behavior: Implemented on Windows Server 2008 operating system, Windows Server 2008 R2 operating system, Windows Server 2012 operating system, and Windows Server 2012 R2 operating system.

2.87 Class mS-SQL-OLAPCube

Stores Microsoft SQL Server online analytical processing (OLAP) cube properties.

```
cn: MS-SQL-OLAPCube
ldapDisplayName: mS-SQL-OLAPCube
governsId: 1.2.840.113556.1.5.190
objectClassCategory: 1
rdnAttId: cn
subClassOf: top
systemMayContain: mS-SQL-Keywords, mS-SQL-PublicationURL,
  mS-SQL-InformationURL, mS-SQL-Status, mS-SQL-LastUpdatedDate,
  mS-SQL-Size, mS-SQL-Description, mS-SQL-Contact, mS-SQL-Name
systemPossSuperiors: mS-SQL-OLAPDatabase
schemaIdGuid: 09f0506a-cd28-11d2-9993-0000f87a57d4
defaultSecurityDescriptor: D: (A;;RPWPCRCDCCLCLORCWOWDSDDTSW;;;DA)
  (A;;RPWPCRCDCCLCLORCWOWDSDDTSW;;;SY) (A;;RPLCLORC;;;AU)
defaultHidingValue: TRUE
systemOnly: FALSE
defaultObjectCategory: CN=MS-SQL-OLAPCube,<SchemaNCDN>
systemFlags: FLAG_SCHEMA_BASE_OBJECT
```

Version-Specific Behavior: Implemented on Windows 2000 Server operating system, Windows Server 2003 operating system, Windows Server 2003 R2 operating system, Windows Server 2008

operating system, Windows Server 2008 R2 operating system, Windows Server 2012 operating system, and Windows Server 2012 R2 operating system.

2.88 Class mS-SQL-OLAPDatabase

A container that stores [mS-SQL-OLAPCube](#) objects.

```
cn: MS-SQL-OLAPDatabase
ldapDisplayName: mS-SQL-OLAPDatabase
governsId: 1.2.840.113556.1.5.189
objectClassCategory: 1
rdnAttId: cn
subClassOf: top
systemMayContain: mS-SQL-Keywords, mS-SQL-PublicationURL,
  mS-SQL-ConnectionURL, mS-SQL-InformationURL, mS-SQL-Status,
  mS-SQL-Applications, mS-SQL-LastBackupDate, mS-SQL-LastUpdatedDate,
  mS-SQL-Size, mS-SQL-Type, mS-SQL-Description, mS-SQL-Contact,
  mS-SQL-Name
systemPossSuperiors: mS-SQL-OLAPServer
schemaIdGuid: 20af031a-ccef-11d2-9993-0000f87a57d4
defaultSecurityDescriptor: D: (A;;RPWPCRCDCCLORCWOWDSDDTSW;;;DA)
  (A;;RPWPCRCDCCLORCWOWDSDDTSW;;;SY) (A;;RPLCLORC;;;AU)
defaultHidingValue: TRUE
systemOnly: FALSE
defaultObjectCategory: CN=MS-SQL-OLAPDatabase,<SchemaNCDN>
systemFlags: FLAG_SCHEMA_BASE_OBJECT
```

Version-Specific Behavior: Implemented on Windows 2000 Server operating system, Windows Server 2003 operating system, Windows Server 2003 R2 operating system, Windows Server 2008 operating system, Windows Server 2008 R2 operating system, Windows Server 2012 operating system, and Windows Server 2012 R2 operating system.

2.89 Class mS-SQL-OLAPServer

A container that stores [mS-SQL-OLAPDatabase](#) objects.

```
cn: MS-SQL-OLAPServer
ldapDisplayName: mS-SQL-OLAPServer
governsId: 1.2.840.113556.1.5.185
objectClassCategory: 1
rdnAttId: cn
subClassOf: serviceConnectionPoint
systemMayContain: mS-SQL-Keywords, mS-SQL-PublicationURL,
  mS-SQL-InformationURL, mS-SQL-Status, mS-SQL-Language,
  mS-SQL-ServiceAccount, mS-SQL-Contact, mS-SQL-RegisteredOwner,
  mS-SQL-Build, mS-SQL-Version, mS-SQL-Name
systemPossSuperiors: serviceConnectionPoint
schemaIdGuid: 0c7e18ea-ccef-11d2-9993-0000f87a57d4
defaultSecurityDescriptor: D: (A;;RPWPCRCDCCLORCWOWDSDDTSW;;;DA)
  (A;;RPWPCRCDCCLORCWOWDSDDTSW;;;SY) (A;;RPLCLORC;;;AU)
defaultHidingValue: TRUE
systemOnly: FALSE
defaultObjectCategory: CN=MS-SQL-OLAPServer,<SchemaNCDN>
systemFlags: FLAG_SCHEMA_BASE_OBJECT
```

Version-Specific Behavior: Implemented on Windows 2000 Server operating system, Windows Server 2003 operating system, Windows Server 2003 R2 operating system, Windows Server 2008 operating system, Windows Server 2008 R2 operating system, Windows Server 2012 operating system, and Windows Server 2012 R2 operating system.

2.90 Class mS-SQL-SQLDatabase

Stores Microsoft SQL Server database properties.

```
cn: MS-SQL-SQLDatabase
ldapDisplayName: mS-SQL-SQLDatabase
governsId: 1.2.840.113556.1.5.188
objectClassCategory: 1
rdnAttId: cn
subClassOf: top
systemMayContain: mS-SQL-Keywords, mS-SQL-InformationURL,
  mS-SQL-Status, mS-SQL-Applications, mS-SQL-LastDiagnosticDate,
  mS-SQL-LastBackupDate, mS-SQL-CreationDate, mS-SQL-Size,
  mS-SQL-Contact, mS-SQL-Alias, mS-SQL-Description, mS-SQL-Name
systemPossSuperiors: mS-SQL-SQLServer
schemaIdGuid: 1d08694a-ccef-11d2-9993-0000f87a57d4
defaultSecurityDescriptor: D: (A;;;RPWPCRCDCCLCLOCRCWOWSDSDTWS;;;DA)
  (A;;;RPWPCRCDCCLCLOCRCWOWSDSDTWS;;;SY) (A;;;RPLCLORC;;;AU)
defaultHidingValue: TRUE
systemOnly: FALSE
defaultObjectCategory: CN=MS-SQL-SQLDatabase,<SchemaNCDN>
systemFlags: FLAG_SCHEMA_BASE_OBJECT
```

Version-Specific Behavior: Implemented on Windows 2000 Server operating system, Windows Server 2003 operating system, Windows Server 2003 R2 operating system, Windows Server 2008 operating system, Windows Server 2008 R2 operating system, Windows Server 2012 operating system, and Windows Server 2012 R2 operating system.

2.91 Class mS-SQL-SQLPublication

Stores Microsoft SQL Server publication properties. This class permits the user to browse the publications that are available for subscription.

```
cn: MS-SQL-SQLPublication
ldapDisplayName: mS-SQL-SQLPublication
governsId: 1.2.840.113556.1.5.187
objectClassCategory: 1
rdnAttId: cn
subClassOf: top
systemMayContain: mS-SQL-ThirdParty,
  mS-SQL-AllowSnapshotFilesFTPDownloading,
  mS-SQL-AllowQueuedUpdatingSubscription,
  mS-SQL-AllowImmediateUpdatingSubscription,
  mS-SQL-AllowKnownPullSubscription, mS-SQL-Publisher,
  mS-SQL-AllowAnonymousSubscription, mS-SQL-Database, mS-SQL-Type,
  mS-SQL-Status, mS-SQL-Description, mS-SQL-Name
systemPossSuperiors: mS-SQL-SQLServer
schemaIdGuid: 17c2f64e-ccef-11d2-9993-0000f87a57d4
defaultSecurityDescriptor: D: (A;;;RPWPCRCDCCLCLOCRCWOWSDSDTWS;;;DA)
  (A;;;RPWPCRCDCCLCLOCRCWOWSDSDTWS;;;SY) (A;;;RPLCLORC;;;AU)
defaultHidingValue: TRUE
```

```
systemOnly: FALSE
defaultObjectCategory: CN=MS-SQL-SQLPublication,<SchemaNCDN>
systemFlags: FLAG_SCHEMA_BASE_OBJECT
```

Version-Specific Behavior: Implemented on Windows 2000 Server operating system, Windows Server 2003 operating system, Windows Server 2003 R2 operating system, Windows Server 2008 operating system, Windows Server 2008 R2 operating system, Windows Server 2012 operating system, and Windows Server 2012 R2 operating system.

2.92 Class mS-SQL-SQLRepository

Stores Microsoft SQL Server repository properties.

```
cn: MS-SQL-SQLRepository
ldapDisplayName: mS-SQL-SQLRepository
governsId: 1.2.840.113556.1.5.186
objectClassCategory: 1
rdnAttId: cn
subClassOf: top
systemMayContain: mS-SQL-InformationDirectory, mS-SQL-Version,
mS-SQL-Description, mS-SQL-Status, mS-SQL-Build, mS-SQL-Contact,
mS-SQL-Name
systemPossSuperiors: mS-SQL-SQLServer
schemaIdGuid: 11d43c5c-ccef-11d2-9993-0000f87a57d4
defaultSecurityDescriptor: D:(A;;RPWPCRCDCCLCCLORCWOWDSDDTSW;;;DA)
(A;;RPWPCRCDCCLCCLORCWOWDSDDTSW;;;SY)(A;;RPLCLORC;;;AU)
defaultHidingValue: TRUE
systemOnly: FALSE
defaultObjectCategory: CN=MS-SQL-SQLRepository,<SchemaNCDN>
systemFlags: FLAG_SCHEMA_BASE_OBJECT
```

Version-Specific Behavior: Implemented on Windows 2000 Server operating system, Windows Server 2003 operating system, Windows Server 2003 R2 operating system, Windows Server 2008 operating system, Windows Server 2008 R2 operating system, Windows Server 2012 operating system, and Windows Server 2012 R2 operating system.

2.93 Class mS-SQL-SQLServer

A container that stores [mS-SQL-SQLDatabase](#), [mS-SQL-SQLPublication](#), and [mS-SQL-SQLRepository](#) objects.

```
cn: MS-SQL-SQLServer
ldapDisplayName: mS-SQL-SQLServer
governsId: 1.2.840.113556.1.5.184
objectClassCategory: 1
rdnAttId: cn
subClassOf: serviceConnectionPoint
systemMayContain: mS-SQL-Keywords, mS-SQL-GPSHeight,
mS-SQL-GPSLongitude, mS-SQL-GPSLatitude, mS-SQL-InformationURL,
mS-SQL-LastUpdatedDate, mS-SQL-Status, mS-SQL-Vines,
mS-SQL-AppleTalk, mS-SQL-TCPIP, mS-SQL-SPX, mS-SQL-MultiProtocol,
mS-SQL-NamedPipe, mS-SQL-Clustered, mS-SQL-UnicodeSortOrder,
mS-SQL-SortOrder, mS-SQL-CharacterSet, mS-SQL-ServiceAccount,
mS-SQL-Build, mS-SQL-Memory, mS-SQL-Location, mS-SQL-Contact,
mS-SQL-RegisteredOwner, mS-SQL-Name
```

```
systemPossSuperiors: serviceConnectionPoint
schemaIdGuid: 05f6c878-ccef-11d2-9993-0000f87a57d4
defaultSecurityDescriptor: D: (A;;RPWPCRCDCCLCLORCWOWSDSDTSW;;;DA)
(A;;RPWPCRCDCCLCLORCWOWSDSDTSW;;;SY) (A;;RPLCLORC;;;AU)
defaultHidingValue: TRUE
systemOnly: FALSE
defaultObjectCategory: CN=MS-SQL-SQLServer,<SchemaNCDN>
systemFlags: FLAG_SCHEMA_BASE_OBJECT
```

Version-Specific Behavior: Implemented on Windows 2000 Server operating system, Windows Server 2003 operating system, Windows Server 2003 R2 operating system, Windows Server 2008 operating system, Windows Server 2008 R2 operating system, Windows Server 2012 operating system, and Windows Server 2012 R2 operating system.

2.94 Class msAuthz-CentralAccessPolicies

A container of this class can contain Central Access Policy objects.

```
cn: ms-Authz-Central-Access-Policies
ldapDisplayName: msAuthz-CentralAccessPolicies
governsId: 1.2.840.113556.1.4.2161
objectClassCategory: 1
rdnAttId: cn
subClassOf: top
systemPossSuperiors: container
schemaIdGuid: 555c21c3-a136-455a-9397-796bbd358e25
defaultSecurityDescriptor: D: (A;;RPWPCRCDCCLCLORCWOWSDSDTSW;;;EA)
(A;;RPWPCRCDCCLCLORCWOWSDSDTSW;;;SY) (A;;RPLCLORC;;;AU)
defaultHidingValue: TRUE
systemOnly: FALSE
defaultObjectCategory: CN=ms-Authz-Central-Access-Policies,<SchemaNCDN>
systemFlags: FLAG_SCHEMA_BASE_OBJECT
```

Version-Specific Behavior: Implemented on Windows Server 2012 operating system and Windows Server 2012 R2 operating system.

2.95 Class msAuthz-CentralAccessPolicy

A class that defines Central Access Policy objects.

```
cn: ms-Authz-Central-Access-Policy
ldapDisplayName: msAuthz-CentralAccessPolicy
governsId: 1.2.840.113556.1.4.2164
objectClassCategory: 1
rdnAttId: cn
subClassOf: top
systemMayContain: msAuthz-MemberRulesInCentralAccessPolicy,
msAuthz-CentralAccessPolicyID
systemPossSuperiors: msAuthz-CentralAccessPolicies
schemaIdGuid: a5679cb0-6f9d-432c-8b75-1e3e834f02aa
defaultSecurityDescriptor: D: (A;;RPWPCRCDCCLCLORCWOWSDSDTSW;;;EA)
(A;;RPWPCRCDCCLCLORCWOWSDSDTSW;;;SY) (A;;RPLCLORC;;;AU)
defaultHidingValue: FALSE
systemOnly: FALSE
defaultObjectCategory: CN=ms-Authz-Central-Access-Policy,<SchemaNCDN>
```

```
systemFlags: FLAG_SCHEMA_BASE_OBJECT
```

Version-Specific Behavior: Implemented on Windows Server 2012 operating system and Windows Server 2012 R2 operating system.

2.96 Class msAuthz-CentralAccessRule

A class that defines central access rules used to construct a central access policy.

```
cn: ms-Authz-Central-Access-Rule
ldapDisplayName: msAuthz-CentralAccessRule
governsId: 1.2.840.113556.1.4.2163
objectClassCategory: 1
rdnAttId: cn
subClassOf: top
systemMayContain: msAuthz-ResourceCondition,
  msAuthz-MemberRulesInCentralAccessPolicyBL, msAuthz-LastEffectiveSecurityPolicy,
  msAuthz-ProposedSecurityPolicy, msAuthz-EffectiveSecurityPolicy, Enabled
systemPossSuperiors: msAuthz-CentralAccessRules
schemaIdGuid: 5b4a06dc-251c-4edb-8813-0bdd71327226
defaultSecurityDescriptor: D:(A;;RPWPCRCDCCLCCLORCWOWDSDDTSW;;;EA)
  (A;;RPWPCRCDCCLCCLORCWOWDSDDTSW;;;SY)(A;;RPLCLORC;;;AU)
defaultHidingValue: FALSE
systemOnly: FALSE
defaultObjectCategory: CN=ms-Authz-Central-Access-Rule,<SchemaNCDN>
systemFlags: FLAG_SCHEMA_BASE_OBJECT
```

Version-Specific Behavior: Implemented on Windows Server 2012 operating system and Windows Server 2012 R2 operating system.

2.97 Class msAuthz-CentralAccessRules

A container of this class can contain Central Access Policy Entry objects.

```
cn: ms-Authz-Central-Access-Rules
ldapDisplayName: msAuthz-CentralAccessRules
governsId: 1.2.840.113556.1.4.2162
objectClassCategory: 1
rdnAttId: cn
subClassOf: top
systemPossSuperiors: container
schemaIdGuid: 99bblb7a-606d-4f8b-800e-e15be554ca8d
defaultSecurityDescriptor: D:(A;;RPWPCRCDCCLCCLORCWOWDSDDTSW;;;EA)
  (A;;RPWPCRCDCCLCCLORCWOWDSDDTSW;;;SY)(A;;RPLCLORC;;;AU)
defaultHidingValue: TRUE
systemOnly: FALSE
defaultObjectCategory: CN=ms-Authz-Central-Access-Rules,<SchemaNCDN>
systemFlags: FLAG_SCHEMA_BASE_OBJECT
```

Version-Specific Behavior: Implemented on Windows Server 2012 operating system and Windows Server 2012 R2 operating system.

2.98 Class msCOM-Partition

A namespace that is used by COM+ to allow multiple versions of the same COM+ application to exist on the same physical machine.

```
cn: ms-COM-Partition
ldapDisplayName: msCOM-Partition
governsId: 1.2.840.113556.1.5.193
objectClassCategory: 1
rdnAttId: cn
subClassOf: top
systemMayContain: msCOM-ObjectId
systemPossSuperiors: domainDNS, organizationalUnit, container
schemaIdGuid: c9010e74-4e58-49f7-8a89-5e3e2340fcf8
defaultSecurityDescriptor: D: (A;;RPWPCRCDCCLCLORCWOWDSDDTSW;;;DA)
(A;;RPWPCRCDCCLCLORCWOWDSDDTSW;;;SY) (A;;RPLCLORC;;;AU)
defaultHidingValue: TRUE
systemOnly: FALSE
defaultObjectCategory: CN=ms-COM-Partition,<SchemaNCDN>
systemFlags: FLAG_SCHEMA_BASE_OBJECT
```

Version-Specific Behavior: Implemented on Windows Server 2003 operating system, Windows Server 2003 R2 operating system, Windows Server 2008 operating system, Windows Server 2008 R2 operating system, Windows Server 2012 operating system, and Windows Server 2012 R2 operating system.

2.99 Class msCOM-PartitionSet

A conceptual collection of COM+ partitions.

```
cn: ms-COM-PartitionSet
ldapDisplayName: msCOM-PartitionSet
governsId: 1.2.840.113556.1.5.194
objectClassCategory: 1
rdnAttId: cn
subClassOf: top
systemMayContain: msCOM-PartitionLink, msCOM-DefaultPartitionLink,
msCOM-ObjectId
systemPossSuperiors: domainDNS, organizationalUnit, container
schemaIdGuid: 250464ab-c417-497a-975a-9e0d459a7ca1
defaultSecurityDescriptor: D: (A;;RPWPCRCDCCLCLORCWOWDSDDTSW;;;DA)
(A;;RPWPCRCDCCLCLORCWOWDSDDTSW;;;SY) (A;;RPLCLORC;;;AU)
defaultHidingValue: TRUE
systemOnly: FALSE
defaultObjectCategory: CN=ms-COM-PartitionSet,<SchemaNCDN>
systemFlags: FLAG_SCHEMA_BASE_OBJECT
```

Version-Specific Behavior: Implemented on Windows Server 2003 operating system, Windows Server 2003 R2 operating system, Windows Server 2008 operating system, Windows Server 2008 R2 operating system, Windows Server 2012 operating system, and Windows Server 2012 R2 operating system.

2.100 Class msDFS-DeletedLinkv2

A DFS link in the DFS namespace.

```

cn: ms-DFS-Deleted-Link-v2
ldapDisplayName: msDFS-DeletedLinkv2
governsId: 1.2.840.113556.1.5.260
objectClassCategory: 1
rdnAttId: cn
subClassOf: top
systemMustContain: msDFS-NamespaceIdentityGUIDv2,
  msDFS-LinkIdentityGUIDv2, msDFS-LastModifiedv2, msDFS-LinkPathv2
systemMayContain: msDFS-Commentv2, msDFS-ShortNameLinkPathv2
systemPossSuperiors: msDFS-Namespavev2
schemaIdGuid: 25173408-04ca-40e8-865e-3f9ce9bf1bd3
defaultSecurityDescriptor: D: (A;;RPWPCRCDCCLCCLORCWOWSDSDTWS;;;DA)
  (A;;RPWPCRCDCCLCCLORCWOWSDSDTWS;;;SY)
  (A;;RPLCLORC;;;AU)
defaultHidingValue: TRUE
systemOnly: FALSE
defaultObjectCategory: CN=ms-DFS-Deleted-Link-v2,<SchemaNCDN>
systemFlags: FLAG_SCHEMA_BASE_OBJECT

```

Version-Specific Behavior: Implemented on Windows Server 2008 operating system, Windows Server 2008 R2 operating system, Windows Server 2012 operating system, and Windows Server 2012 R2 operating system.

2.101 Class msDFS-Linkv2

A DFS link in the DFS namespace.

```

cn: ms-DFS-Link-v2
ldapDisplayName: msDFS-Linkv2
governsId: 1.2.840.113556.1.5.259
objectClassCategory: 1
rdnAttId: cn
subClassOf: top
systemMustContain: msDFS-GenerationGUIDv2,
  msDFS-NamespaceIdentityGUIDv2, msDFS-LinkIdentityGUIDv2,
  msDFS-LastModifiedv2, msDFS-Ttlv2, msDFS-TargetListv2,
  msDFS-Propertiesv2, msDFS-LinkPathv2
systemMayContain: msDFS-Commentv2, msDFS-LinkSecurityDescriptorv2,
  msDFS-ShortNameLinkPathv2
systemPossSuperiors: msDFS-Namespavev2
schemaIdGuid: 7769fb7a-1159-4e96-9ccd-68bc487073eb
defaultSecurityDescriptor: D: (A;;RPWPCRCDCCLCCLORCWOWSDSDTWS;;;DA)
  (A;;RPWPCRCDCCLCCLORCWOWSDSDTWS;;;SY) (A;;RPLCLORC;;;AU)
defaultHidingValue: TRUE
systemOnly: FALSE
defaultObjectCategory: CN=ms-DFS-Link-v2,<SchemaNCDN>
systemFlags: FLAG_SCHEMA_BASE_OBJECT

```

Version-Specific Behavior: Implemented on Windows Server 2008 operating system, Windows Server 2008 R2 operating system, Windows Server 2012 operating system, and Windows Server 2012 R2 operating system.

2.102 Class msDFS-NamespaceAnchor

A DFS namespace anchor.

```

cn: ms-DFS-Namespace-Anchor
ldapDisplayName: msDFS-NamespaceAnchor
governsId: 1.2.840.113556.1.5.257
objectClassCategory: 1
rdnAttId: cn
subClassOf: top
systemMustContain: msDFS-SchemaMajorVersion
systemPossSuperiors: dfsConfiguration
schemaIdGuid: da73a085-6e64-4d61-b064-015d04164795
defaultSecurityDescriptor: D: (A;;RPWPCRCDCCLCLORCWOWSDSDDTSW;;;DA)
(A;;RPWPCRCDCCLCLORCWOWSDSDDTSW;;;SY) (A;;RPLCLORC;;;AU)
(A;;RPWPCRCDCCLCLORCWOWSDSDDTSW;;;CO)
defaultHidingValue: TRUE
systemOnly: FALSE
defaultObjectCategory: CN=ms-DFS-Namespace-Anchor,<SchemaNCDN>
systemFlags: FLAG_SCHEMA_BASE_OBJECT

```

Version-Specific Behavior: Implemented on Windows Server 2008 operating system, Windows Server 2008 R2 operating system, Windows Server 2012 operating system, and Windows Server 2012 R2 operating system.

2.103 Class msDFS-Namepacev2

A DFS namespace.

```

cn: ms-DFS-Namepace-v2
ldapDisplayName: msDFS-Namepacev2
governsId: 1.2.840.113556.1.5.258
objectClassCategory: 1
rdnAttId: cn
subClassOf: top
systemMustContain: msDFS-SchemaMajorVersion,
msDFS-SchemaMinorVersion, msDFS-GenerationGUIDv2,
msDFS-NamepaceIdentityGUIDv2, msDFS-LastModifiedv2, msDFS-Ttlv2,
msDFS-TargetListv2, msDFS-Propertiesv2
systemMayContain: msDFS-Commentv2
systemPossSuperiors: msDFS-NamepaceAnchor
schemaIdGuid: 21cb8628-f3c3-4bbf-bff6-060b2d8f299a
defaultSecurityDescriptor: D: (A;;RPWPCRCDCCLCLORCWOWSDSDDTSW;;;DA)
(A;;RPWPCRCDCCLCLORCWOWSDSDDTSW;;;SY) (A;;RPLCLORC;;;AU)
defaultHidingValue: TRUE
systemOnly: FALSE
defaultObjectCategory: CN=ms-DFS-Namepace-v2,<SchemaNCDN>
systemFlags: FLAG_SCHEMA_BASE_OBJECT

```

Version-Specific Behavior: Implemented on Windows Server 2008 operating system, Windows Server 2008 R2 operating system, Windows Server 2012 operating system, and Windows Server 2012 R2 operating system.

2.104 Class msDFSR-Connection

A directional connection between two members.

```

cn: ms-DFSR-Connection
ldapDisplayName: msDFSR-Connection

```



```

governsId: 1.2.840.113556.1.6.13.4.10
objectClassCategory: 1
rdnAttId: cn
subClassOf: top
mustContain: fromServer
mayContain: msDFSR-Options2, msDFSR-DisablePacketPrivacy,
  msDFSR-Priority, msDFSR-Enabled, msDFSR-RdcEnabled,
  msDFSR-RdcMinFileSizeInKb, msDFSR-Keywords, msDFSR-Schedule,
  msDFSR-Flags, msDFSR-Options, msDFSR-Extension
possSuperiors: msDFSR-Member
schemaIdGuid: e58f972e-64b5-46ef-8d8b-bbc3e1897eab
defaultSecurityDescriptor: D: (A;;RPLCLORC;;;AU)
  (A;;RPWPCLRLCLOCCDCRCWDWOSDDTSW;;;DA)
  (A;;RPWPCLRLCLOCCDCRCWDWOSDDTSW;;;CO)
  (A;;RPWPCLRLCLOCCDCRCWDWOSDDTSW;;;SY)
defaultHidingValue: TRUE
systemOnly: FALSE
defaultObjectCategory: CN=ms-DFSR-Connection,<SchemaNCDN>

```

Version-Specific Behavior: Implemented on Windows Server 2003 R2 operating system, Windows Server 2008 operating system, Windows Server 2008 R2 operating system, Windows Server 2012 operating system, and Windows Server 2012 R2 operating system.

2.105 Class msDFSR-Content

A container for [msDFSR-ContentSet](#) objects.

```

cn: ms-DFSR-Content
ldapDisplayName: msDFSR-Content
governsId: 1.2.840.113556.1.6.13.4.6
objectClassCategory: 1
rdnAttId: cn
subClassOf: top
mayContain: msDFSR-Options2, msDFSR-Flags, msDFSR-Options,
  msDFSR-Extension
possSuperiors: msDFSR-ReplicationGroup
schemaIdGuid: 64759b35-d3a1-42e4-b5f1-a3de162109b3
defaultSecurityDescriptor: D: (A;;RPLCLORC;;;AU)
  (A;;RPWPCLRLCLOCCDCRCWDWOSDDTSW;;;DA)
  (A;;RPWPCLRLCLOCCDCRCWDWOSDDTSW;;;CO)
  (A;;RPWPCLRLCLOCCDCRCWDWOSDDTSW;;;SY)
defaultHidingValue: TRUE
systemOnly: FALSE
defaultObjectCategory: CN=ms-DFSR-Content,<SchemaNCDN>

```

Version-Specific Behavior: Implemented on Windows Server 2003 R2 operating system, Windows Server 2008 operating system, Windows Server 2008 R2 operating system, Windows Server 2012 operating system, and Windows Server 2012 R2 operating system.

2.106 Class msDFSR-ContentSet

A Distributed File System Replication (DFSR) content set.

```

cn: ms-DFSR-ContentSet
ldapDisplayName: msDFSR-ContentSet

```

```

governsId: 1.2.840.113556.1.6.13.4.7
objectClassCategory: 1
rdnAttId: cn
subClassOf: top
mayContain: msDFSR-Options2, msDFSR-OnDemandExclusionDirectoryFilter,
  msDFSR-OnDemandExclusionFileFilter,
  msDFSR-DefaultCompressionExclusionFilter, msDFSR-DeletedSizeInMb,
  msDFSR-Priority, msDFSR-ConflictSizeInMb, msDFSR-StagingSizeInMb,
  msDFSR-RootSizeInMb, description, msDFSR-DfsPath, msDFSR-FileFilter,
  msDFSR-DirectoryFilter, msDFSR-Flags, msDFSR-Options,
  msDFSR-Extension
possSuperiors: msDFSR-Content
schemaIdGuid: 4937f40d-a6dc-4d48-97ca-06e5fbfd3f16
defaultSecurityDescriptor: D:(A;;RPLCLORC;;;AU)
  (A;;RPWPCLRLCLOCCDCRCWDWOSDDTSW;;;DA)
  (A;;RPWPCLRLCLOCCDCRCWDWOSDDTSW;;;CO)
  (A;;RPWPCLRLCLOCCDCRCWDWOSDDTSW;;;SY)
defaultHidingValue: TRUE
systemOnly: FALSE
defaultObjectCategory: CN=ms-DFSR-ContentSet,<SchemaNCDN>

```

Version-Specific Behavior: Implemented on Windows Server 2003 R2 operating system, Windows Server 2008 operating system, Windows Server 2008 R2 operating system, Windows Server 2012 operating system, and Windows Server 2012 R2 operating system.

2.107 Class msDFSR-GlobalSettings

The global settings that are applicable to all replication group members.

```

cn: ms-DFSR-GlobalSettings
ldapDisplayName: msDFSR-GlobalSettings
governsId: 1.2.840.113556.1.6.13.4.4
objectClassCategory: 1
rdnAttId: cn
subClassOf: top
mayContain: msDFSR-Options2, msDFSR-Flags, msDFSR-Options,
  msDFSR-Extension
possSuperiors: container
schemaIdGuid: 7b35dbad-b3ec-486a-aad4-2fec9d6ea6f6
defaultSecurityDescriptor: D:(A;;RPLCLORC;;;AU)
  (A;;RPWPCLRLCLOCCDCRCWDWOSDDTSW;;;DA)
  (A;;RPWPCLRLCLOCCDCRCWDWOSDDTSW;;;CO)
  (A;;RPWPCLRLCLOCCDCRCWDWOSDDTSW;;;SY)
defaultHidingValue: TRUE
systemOnly: FALSE
defaultObjectCategory: CN=ms-DFSR-GlobalSettings,<SchemaNCDN>

```

Version-Specific Behavior: Implemented on Windows Server 2003 R2 operating system, Windows Server 2008 operating system, Windows Server 2008 R2 operating system, Windows Server 2012 operating system, and Windows Server 2012 R2 operating system.

2.108 Class msDFSR-LocalSettings

The DFSR settings that are applicable to a local computer.

```

cn: ms-DFSR-LocalSettings
ldapDisplayName: msDFSR-LocalSettings
governsId: 1.2.840.113556.1.6.13.4.1
objectClassCategory: 1
rdnAttId: cn
subClassOf: top
mayContain: msDFSR-StagingCleanupTriggerInPercent,
  msDFSR-CommonStagingSizeInMb, msDFSR-CommonStagingPath,
  msDFSR-Options2, msDFSR-Version, msDFSR-Flags, msDFSR-Options,
  msDFSR-Extension
possSuperiors: computer
schemaIdGuid: fa85c591-197f-477e-83bd-ea5a43df2239
defaultSecurityDescriptor: D: (A;;RPLCLORC;;;AU)
  (A;;RPWPCLRLCLOCCDCRCWDWOSDDTSW;;;DA)
  (A;;RPWPCLRLCLOCCDCRCWDWOSDDTSW;;;CO)
  (A;;RPWPCLRLCLOCCDCRCWDWOSDDTSW;;;SY)
defaultHidingValue: TRUE
systemOnly: FALSE
defaultObjectCategory: CN=ms-DFSR-LocalSettings,<SchemaNCDN>

```

Version-Specific Behavior: Implemented on Windows Server 2003 R2 operating system, Windows Server 2008 operating system, Windows Server 2008 R2 operating system, Windows Server 2012 operating system, and Windows Server 2012 R2 operating system.

2.109 Class msDFSR-Member

A replication group member.

```

cn: ms-DFSR-Member
ldapDisplayName: msDFSR-Member
governsId: 1.2.840.113556.1.6.13.4.9
objectClassCategory: 1
rdnAttId: cn
subClassOf: top
mustContain: msDFSR-ComputerReference
mayContain: msDFSR-Options2, serverReference, msDFSR-Keywords,
  msDFSR-Flags, msDFSR-Options, msDFSR-Extension
possSuperiors: msDFSR-Topology
schemaIdGuid: 4229c897-c211-437c-a5ae-dbf705b696e5
defaultSecurityDescriptor: D: (A;;RPLCLORC;;;AU)
  (A;;RPWPCLRLCLOCCDCRCWDWOSDDTSW;;;DA)
  (A;;RPWPCLRLCLOCCDCRCWDWOSDDTSW;;;CO)
  (A;;RPWPCLRLCLOCCDCRCWDWOSDDTSW;;;SY)
defaultHidingValue: TRUE
systemOnly: FALSE
defaultObjectCategory: CN=ms-DFSR-Member,<SchemaNCDN>

```

Version-Specific Behavior: Implemented on Windows Server 2003 R2 operating system, Windows Server 2008 operating system, Windows Server 2008 R2 operating system, Windows Server 2012 operating system, and Windows Server 2012 R2 operating system.

2.110 Class msDFSR-ReplicationGroup

A replication group container.

```

cn: ms-DFSR-ReplicationGroup
ldapDisplayName: msDFSR-ReplicationGroup
governsId: 1.2.840.113556.1.6.13.4.5
objectClassCategory: 1
rdnAttId: cn
subClassOf: top
mustContain: msDFSR-ReplicationGroupType
mayContain: msDFSR-Options2, msDFSR-OnDemandExclusionDirectoryFilter,
  msDFSR-OnDemandExclusionFileFilter,
  msDFSR-DefaultCompressionExclusionFilter, msDFSR-DeletedSizeInMb,
  msDFSR-DirectoryFilter, msDFSR-FileFilter, msDFSR-ConflictSizeInMb,
  msDFSR-StagingSizeInMb, msDFSR-RootSizeInMb, description,
  msDFSR-TombstoneExpiryInMin, msDFSR-Flags, msDFSR-Options,
  msDFSR-Extension, msDFSR-Schedule, msDFSR-Version
possSuperiors: msDFSR-GlobalSettings
schemaIdGuid: 1c332fe0-0c2a-4f32-afca-23c5e45a9e77
defaultSecurityDescriptor: D:(A;;RPLCLORC;;;AU)
  (A;;RPWPCLRLCLOCCDCRCWDWOSDDTSW;;;DA)
  (A;;RPWPCLRLCLOCCDCRCWDWOSDDTSW;;;CO)
  (A;;RPWPCLRLCLOCCDCRCWDWOSDDTSW;;;SY)
defaultHidingValue: TRUE
systemOnly: FALSE
defaultObjectCategory: CN=ms-DFSR-ReplicationGroup,<SchemaNCDN>

```

Version-Specific Behavior: Implemented on Windows Server 2003 R2 operating system, Windows Server 2008 operating system, Windows Server 2008 R2 operating system, Windows Server 2012 operating system, and Windows Server 2012 R2 operating system.

2.111 Class msDFSR-Subscriber

Represents local computer membership of a replication group.

```

cn: ms-DFSR-Subscriber
ldapDisplayName: msDFSR-Subscriber
governsId: 1.2.840.113556.1.6.13.4.2
objectClassCategory: 1
rdnAttId: cn
subClassOf: top
mustContain: msDFSR-MemberReference, msDFSR-ReplicationGroupGuid
mayContain: msDFSR-Options2, msDFSR-Flags, msDFSR-Options,
  msDFSR-Extension
possSuperiors: msDFSR-LocalSettings
schemaIdGuid: e11505d7-92c4-43e7-bf5c-295832ffc896
defaultSecurityDescriptor: D:(A;;RPLCLORC;;;AU)
  (A;;RPWPCLRLCLOCCDCRCWDWOSDDTSW;;;DA)
  (A;;RPWPCLRLCLOCCDCRCWDWOSDDTSW;;;CO)
  (A;;RPWPCLRLCLOCCDCRCWDWOSDDTSW;;;SY)
defaultHidingValue: TRUE
systemOnly: FALSE
defaultObjectCategory: CN=ms-DFSR-Subscriber,<SchemaNCDN>

```

Version-Specific Behavior: Implemented on Windows Server 2003 R2 operating system, Windows Server 2008 operating system, Windows Server 2008 R2 operating system, Windows Server 2012 operating system, and Windows Server 2012 R2 operating system.

2.112 Class msDFSR-Subscription

Represents local computer participation of a content set.

```
cn: ms-DFSR-Subscription
ldapDisplayName: msDFSR-Subscription
governsId: 1.2.840.113556.1.6.13.4.3
objectClassCategory: 1
rdnAttId: cn
subClassOf: top
mustContain: msDFSR-ContentSetGuid, msDFSR-ReplicationGroupGuid
mayContain: msDFSR-StagingCleanupTriggerInPercent, msDFSR-Options2,
msDFSR-OnDemandExclusionDirectoryFilter,
msDFSR-OnDemandExclusionFileFilter, msDFSR-MaxAgeInCacheInMin,
msDFSR-MinDurationCacheInMin, msDFSR-CachePolicy, msDFSR-ReadOnly,
msDFSR-DeletedSizeInMb, msDFSR-DeletedPath, msDFSR-RootPath,
msDFSR-RootSizeInMb, msDFSR-StagingPath, msDFSR-StagingSizeInMb,
msDFSR-ConflictPath, msDFSR-ConflictSizeInMb, msDFSR-Enabled,
msDFSR-RootFence, msDFSR-DfsLinkTarget, msDFSR-Flags,
msDFSR-Options, msDFSR-Extension
possSuperiors: msDFSR-Subscriber
schemaIdGuid: 67212414-7bcc-4609-87e0-088dad8abdee
defaultSecurityDescriptor: D: (A;;RPLCLORC;;;AU)
(A;;RPWPCLCLCLOCCDCRCWDWOSDDTSW;;;DA)
(A;;RPWPCLCLCLOCCDCRCWDWOSDDTSW;;;CO)
(A;;RPWPCLCLCLOCCDCRCWDWOSDDTSW;;;SY)
defaultHidingValue: TRUE
systemOnly: FALSE
defaultObjectCategory: CN=ms-DFSR-Subscription,<SchemaNCDN>
```

Version-Specific Behavior: Implemented on Windows Server 2003 R2 operating system, Windows Server 2008 operating system, Windows Server 2008 R2 operating system, Windows Server 2012 operating system, and Windows Server 2012 R2 operating system.

2.113 Class msDFSR-Topology

A container for objects that form the replication topology.

```
cn: ms-DFSR-Topology
ldapDisplayName: msDFSR-Topology
governsId: 1.2.840.113556.1.6.13.4.8
objectClassCategory: 1
rdnAttId: cn
subClassOf: top
mayContain: msDFSR-Options2, msDFSR-Flags, msDFSR-Options,
msDFSR-Extension
possSuperiors: msDFSR-ReplicationGroup
schemaIdGuid: 04828aa9-6e42-4e80-b962-e2fe00754d17
defaultSecurityDescriptor: D: (A;;RPLCLORC;;;AU)
(A;;RPWPCLCLCLOCCDCRCWDWOSDDTSW;;;DA)
(A;;RPWPCLCLCLOCCDCRCWDWOSDDTSW;;;CO)
(A;;RPWPCLCLCLOCCDCRCWDWOSDDTSW;;;SY)
defaultHidingValue: TRUE
systemOnly: FALSE
defaultObjectCategory: CN=ms-DFSR-Topology,<SchemaNCDN>
```

Version-Specific Behavior: Implemented on Windows Server 2003 R2 operating system, Windows Server 2008 operating system, Windows Server 2008 R2 operating system, Windows Server 2012 operating system, and Windows Server 2012 R2 operating system.

2.114 Class msDNS-ServerSettings

Stores state information for DNS. The [msDNS-KeymasterZones](#) attribute is used to store values.

```
cn: ms-DNS-Server-Settings
ldapDisplayName: msDNS-ServerSettings
governsId: 1.2.840.113556.1.4.2129
objectClassCategory: 1
rdnAttId: cn
subClassOf: top
systemMayContain: msDNS-KeymasterZones
systemPossSuperiors: server
schemaIdGuid: ef2fc3ed-6e18-415b-99e4-3114a8cb124b
defaultSecurityDescriptor: D:(A;;RPWPCRCDCCLCLOLORCOWWSDDDTTSW;;;EA)
(A;;RPWPCRCDCCLCLOLORCOWWSDDDTTSW;;;SY)(A;;RPLCLORC;;;AU)
defaultHidingValue: FALSE
systemOnly: FALSE
defaultObjectCategory: CN=ms-DNS-Server-Settings,<SchemaNCDN>
systemFlags: FLAG_SCHEMA_BASE_OBJECT
```

Version-Specific Behavior: Implemented on Windows Server 2012 operating system and Windows Server 2012 R2 operating system.

2.115 Class msDS-App-Configuration

Stores the settings information for an application. The [msDS-Settings](#) attribute should be used to store the actual values.

```
cn: ms-DS-App-Configuration
ldapDisplayName: msDS-App-Configuration
governsId: 1.2.840.113556.1.5.220
objectClassCategory: 1
rdnAttId: cn
subClassOf: applicationSettings
mayContain: owner, msDS-ObjectReference, msDS-Integer, msDS-DateTime,
msDS-ByteArray, managedBy, keywords
possSuperiors: organizationalUnit, computer, container
schemaIdGuid: 90df3c3e-1854-4455-a5d7-cad40d56657a
defaultSecurityDescriptor: D:(A;;RPWPCRCDCCLCLOLORCOWWSDDDTTSW;;;DA)
(A;;RPWPCRCDCCLCLOLORCOWWSDDDTTSW;;;SY)(A;;RPLCLORC;;;AU)
defaultHidingValue: TRUE
systemOnly: FALSE
defaultObjectCategory: CN=ms-DS-App-Configuration,<SchemaNCDN>
```

Version-Specific Behavior: Implemented on Windows Server 2003 operating system, Windows Server 2003 R2 operating system, Windows Server 2008 operating system, Windows Server 2008 R2 operating system, Windows Server 2012 operating system, and Windows Server 2012 R2 operating system.

2.116 Class msDS-AppData

Stores data that is used by an object. For example, stores profile information for a user object.

```
cn: ms-DS-App-Data
ldapDisplayName: msDS-AppData
governsId: 1.2.840.113556.1.5.241
objectClassCategory: 1
rdnAttId: cn
subClassOf: applicationSettings
mayContain: owner, msDS-ObjectReference, msDS-Integer, msDS-DateTime,
msDS-ByteArray, managedBy, keywords
possSuperiors: organizationalUnit, computer, container
schemaIdGuid: 9e67d761-e327-4d55-bc95-682f875e2f8e
defaultSecurityDescriptor: D: (A;;RPWPCRCDCCLCLORCWOWSDSDTTSW;;;DA)
(A;;RPWPCRCDCCLCLORCWOWSDSDTTSW;;;SY) (A;;RPLCLORC;;;AU)
defaultHidingValue: TRUE
systemOnly: FALSE
defaultObjectCategory: CN=ms-DS-App-Data,<SchemaNCDN>
```

Version-Specific Behavior: Implemented on Windows Server 2003 operating system, Windows Server 2003 R2 operating system, Windows Server 2008 operating system, Windows Server 2008 R2 operating system, Windows Server 2012 operating system, and Windows Server 2012 R2 operating system.

2.117 Class msDS-AuthNPolicies

A container of this class can contain authentication policy objects.

```
cn: ms-DS-AuthN-Policies
ldapDisplayName: msDS-AuthNPolicies
governsId: 1.2.840.113556.1.5.293
objectClassCategory: 1
rdnAttId: cn
subClassOf: top
systemPossSuperiors: container
schemaIdGuid: 3a9adf5d-7b97-4f7e-abb4-e5b55c1c06b4
defaultSecurityDescriptor: D: (A;;RPWPCRCDCCLCLOLORCOWOWSDSDTDTTSW;;;EA)
(A;;RPWPCRCDCCLCLORCWOWSDSDTTSW;;;SY) (A;;RPLCLORC;;;AU)
defaultHidingValue: TRUE
systemOnly: FALSE
systemFlags: FLAG_SCHEMA_BASE_OBJECT
defaultObjectCategory: CN=ms-DS-AuthN-Policies,<SchemaNCDN>
showInAdvancedViewOnly: TRUE
```

Version-Specific Behavior: Implemented on Windows Server 2012 R2 operating system.

2.118 Class msDS-AuthNPolicy

An instance of this class defines authentication policy behaviors for assigned principals.

```
cn: ms-DS-AuthN-Policy
ldapDisplayName: msDS-AuthNPolicy
governsId: 1.2.840.113556.1.5.294
objectClassCategory: 1
```

```

rdnAttId: cn
subClassOf: top
systemMayContain: msDS-UserAllowedToAuthenticateTo,
msDS-UserAllowedToAuthenticateFrom, msDS-UserTGTLifetime,
msDS-ComputerAllowedToAuthenticateTo, msDS-ComputerTGTLifetime,
msDS-ServiceAllowedToAuthenticateTo, msDS-ServiceAllowedToAuthenticateFrom,
msDS-ServiceTGTLifetime, msDS-UserAuthNPolicyBL, msDS-ComputerAuthNPolicyBL,
msDS-ServiceAuthNPolicyBL, msDS-AssignedAuthNPolicyBL,
msDS-AuthNPolicyEnforced
systemPossSuperiors: msDS-AuthNPolicies
schemaIdGuid: ab6a1156-4dc7-40f5-9180-8e4ce42fe5cd
defaultSecurityDescriptor: D:(A;;RPWPCRCDCCLCLOLORCWOWSDDDTDSW;;;EA)
(A;;RPWPCRCDCCLCLOLORCWOWSDDDTDSW;;;SY)(A;;RPLCLORC;;;AU)
defaultHidingValue: FALSE
systemOnly: FALSE
systemFlags: FLAG_SCHEMA_BASE_OBJECT
defaultObjectCategory: CN=ms-DS-AuthN-Policy,<SchemaNCDN>
showInAdvancedViewOnly: TRUE

```

Version-Specific Behavior: Implemented on Windows Server 2012 R2 operating system.

2.119 Class msDS-AuthNPolicySilo

An instance of this class defines authentication policies and related behaviors for assigned users, computers, and services.

```

cn: ms-DS-AuthN-Policy-Silo
ldapDisplayName: msDS-AuthNPolicySilo
governsId: 1.2.840.113556.1.5.292
objectClassCategory: 1
rdnAttId: cn
subClassOf: top
systemPossSuperiors: msDS-AuthNPolicySilos
systemMayContain: msDS-AuthNPolicySiloMembers, msDS-UserAuthNPolicy,
msDS-ComputerAuthNPolicy, msDS-ServiceAuthNPolicy,
msDS-AssignedAuthNPolicySiloBL, msDS-AuthNPolicySiloEnforced
schemaIdGuid: f9f0461e-697d-4689-9299-37e61d617b0d
defaultSecurityDescriptor: D:(A;;RPWPCRCDCCLCLOLORCWOWSDDDTDSW;;;EA)
(A;;RPWPCRCDCCLCLOLORCWOWSDDDTDSW;;;SY)(A;;RPLCLORC;;;AU)
defaultHidingValue: FALSE
systemOnly: FALSE
systemFlags: FLAG_SCHEMA_BASE_OBJECT
defaultObjectCategory: CN=ms-DS-AuthN-Policy-Silo ,<SchemaNCDN>
showInAdvancedViewOnly: TRUE

```

Version-Specific Behavior: Implemented on Windows Server 2012 R2 operating system.

2.120 Class msDS-AuthNPolicySilos

A container of this class can contain authentication policy silo objects.

```

cn: ms-DS-AuthN-Policy-Silos
ldapDisplayName: msDS-AuthNPolicySilos
governsId: 1.2.840.113556.1.5.291
objectClassCategory: 1

```



```

rdnAttId: cn
subClassOf: top
systemPossSuperiors: container
schemaIdGuid: d2b1470a-8f84-491e-a752-b401ee00fe5c
defaultSecurityDescriptor: D: (A;;RPWPCRCDCCLCLOLORCOWOWSDDDTDSW;;;EA)
(A;;RPWPCRCDCCLCLOLORCOWOWSDDDTDSW;;;SY) (A;;RPLCLORC;;;AU)
defaultHidingValue: TRUE
systemOnly: FALSE
systemFlags: FLAG_SCHEMA_BASE_OBJECT
defaultObjectCategory: CN=ms-DS-AuthN-Policy-Silos ,<SchemaNCDN>
showInAdvancedViewOnly: TRUE

```

Version-Specific Behavior: Implemented on Windows Server 2012 R2 operating system.

2.121 Class msDS-AzAdminManager

The root of an authorization policy store instance.

```

cn: ms-DS-Az-Admin-Manager
ldapDisplayName: msDS-AzAdminManager
governsId: 1.2.840.113556.1.5.234
objectClassCategory: 1
rdnAttId: cn
subClassOf: top
systemMayContain: msDS-AzGenericData, msDS-AzObjectGuid,
msDS-AzMinorVersion, msDS-AzMajorVersion, msDS-AzApplicationData,
msDS-AzGenerateAudits, msDS-AzScriptTimeout,
msDS-AzScriptEngineCacheMax, msDS-AzDomainTimeout, description
systemPossSuperiors: domainDNS, organizationalUnit, container
schemaIdGuid: cfee1051-5f28-4bae-a863-5d0cc18a8ed1
defaultSecurityDescriptor: D: (A;;RPWPCRCDCCLCLOLORCOWOWSDDDTDSW;;;DA)
(A;;RPWPCRCDCCLCLOLORCOWOWSDDDTDSW;;;SY) (A;;RPLCLORC;;;AU)
(A;;RPWPCRCDCCLCLOLORCOWOWSDDDTDSW;;;CO)
defaultHidingValue: TRUE
systemOnly: FALSE
defaultObjectCategory: CN=ms-DS-Az-Admin-Manager,<SchemaNCDN>
systemFlags: FLAG_SCHEMA_BASE_OBJECT

```

Version-Specific Behavior: Implemented on Windows Server 2003 operating system, Windows Server 2003 R2 operating system, Windows Server 2008 operating system, Windows Server 2008 R2 operating system, Windows Server 2012 operating system, and Windows Server 2012 R2 operating system.

2.122 Class msDS-AzApplication

Defines an installed instance of an application that is bound to a particular policy store.

```

cn: ms-DS-Az-Application
ldapDisplayName: msDS-AzApplication
governsId: 1.2.840.113556.1.5.235
objectClassCategory: 1
rdnAttId: cn
subClassOf: top
systemMayContain: msDS-AzGenericData, msDS-AzObjectGuid,
msDS-AzApplicationData, msDS-AzGenerateAudits,

```

```

msDS-AzApplicationVersion, msDS-AzClassId, msDS-AzApplicationName,
description
systemPossSuperiors: msDS-AzAdminManager
schemaIdGuid: ddf8de9b-cba5-4e12-842e-28d8b66f75ec
defaultSecurityDescriptor: D: (A;;RPWPCRCDCCLCLORCWOWSDDTSW;;;DA)
(A;;RPWPCRCDCCLCLORCWOWSDDTSW;;;SY) (A;;RPLCLORC;;;AU)
(A;;RPWPCRCDCCLCLORCWOWSDDTSW;;;CO)
defaultHidingValue: TRUE
systemOnly: FALSE
defaultObjectCategory: CN=ms-DS-Az-Application,<SchemaNCDN>
systemFlags: FLAG_SCHEMA_BASE_OBJECT

```

Version-Specific Behavior: Implemented on Windows Server 2003 operating system, Windows Server 2003 R2 operating system, Windows Server 2008 operating system, Windows Server 2008 R2 operating system, Windows Server 2012 operating system, and Windows Server 2012 R2 operating system.

2.123 Class msDS-AzOperation

Describes a particular operation that is supported by an application.

```

cn: ms-DS-Az-Operation
ldapDisplayName: msDS-AzOperation
governsId: 1.2.840.113556.1.5.236
objectClassCategory: 1
rdnAttId: cn
subClassOf: top
systemMustContain: msDS-AzOperationID
systemMayContain: msDS-AzGenericData, msDS-AzObjectGuid,
msDS-AzApplicationData, description
systemPossSuperiors: container, msDS-AzApplication
schemaIdGuid: 860abe37-9a9b-4fa4-b3d2-b8ace5df9ec5
defaultSecurityDescriptor: D: (A;;RPWPCRCDCCLCLORCWOWSDDTSW;;;DA)
(A;;RPWPCRCDCCLCLORCWOWSDDTSW;;;SY) (A;;RPLCLORC;;;AU)
(A;;RPWPCRCDCCLCLORCWOWSDDTSW;;;CO)
defaultHidingValue: TRUE
systemOnly: FALSE
defaultObjectCategory: CN=ms-DS-Az-Operation,<SchemaNCDN>
systemFlags: FLAG_SCHEMA_BASE_OBJECT

```

Version-Specific Behavior: Implemented on Windows Server 2003 operating system, Windows Server 2003 R2 operating system, Windows Server 2008 operating system, Windows Server 2008 R2 operating system, Windows Server 2012 operating system, and Windows Server 2012 R2 operating system.

2.124 Class msDS-AzRole

Defines a set of operations that can be performed by a particular set of users within a particular scope.

```

cn: ms-DS-Az-Role
ldapDisplayName: msDS-AzRole
governsId: 1.2.840.113556.1.5.239
objectClassCategory: 1
rdnAttId: cn

```

```

subClassOf: top
systemMayContain: msDS-AzGenericData, msDS-AzObjectGuid,
  msDS-AzApplicationData, msDS-TasksForAzRole,
  msDS-OperationsForAzRole, msDS-MembersForAzRole, description
systemPossSuperiors: container, msDS-AzScope, msDS-AzApplication
schemaIdGuid: 8213eac9-9d55-44dc-925c-e9a52b927644
defaultSecurityDescriptor: D: (A;;RPWPCRCDCCLCLORCWOWSDDTSW;;;DA)
  (A;;RPWPCRCDCCLCLORCWOWSDDTSW;;;SY) (A;;RPLCLORC;;;AU)
  (A;;RPWPCRCDCCLCLORCWOWSDDTSW;;;CO)
defaultHidingValue: TRUE
systemOnly: FALSE
defaultObjectCategory: CN=ms-DS-Az-Role,<SchemaNCDN>
systemFlags: FLAG_SCHEMA_BASE_OBJECT

```

Version-Specific Behavior: Implemented on Windows Server 2003 operating system, Windows Server 2003 R2 operating system, Windows Server 2008 operating system, Windows Server 2008 R2 operating system, Windows Server 2012 operating system, and Windows Server 2012 R2 operating system.

2.125 Class msDS-AzScope

Describes a set of objects that are managed by an application.

```

cn: ms-DS-Az-Scope
ldapDisplayName: msDS-AzScope
governsId: 1.2.840.113556.1.5.237
objectClassCategory: 1
rdnAttId: cn
subClassOf: top
systemMustContain: msDS-AzScopeName
systemMayContain: msDS-AzGenericData, msDS-AzObjectGuid,
  msDS-AzApplicationData, description
systemPossSuperiors: msDS-AzApplication
schemaIdGuid: 4feae054-ce55-47bb-860e-5b12063a51de
defaultSecurityDescriptor: D: (A;;RPWPCRCDCCLCLORCWOWSDDTSW;;;DA)
  (A;;RPWPCRCDCCLCLORCWOWSDDTSW;;;SY) (A;;RPLCLORC;;;AU)
  (A;;RPWPCRCDCCLCLORCWOWSDDTSW;;;CO)
defaultHidingValue: TRUE
systemOnly: FALSE
defaultObjectCategory: CN=ms-DS-Az-Scope,<SchemaNCDN>
systemFlags: FLAG_SCHEMA_BASE_OBJECT

```

Version-Specific Behavior: Implemented on Windows Server 2003 operating system, Windows Server 2003 R2 operating system, Windows Server 2008 operating system, Windows Server 2008 R2 operating system, Windows Server 2012 operating system, and Windows Server 2012 R2 operating system.

2.126 Class msDS-AzTask

Describes a set of operations.

```

cn: ms-DS-Az-Task
ldapDisplayName: msDS-AzTask
governsId: 1.2.840.113556.1.5.238
objectClassCategory: 1

```

```

rdnAttId: cn
subClassOf: top
systemMayContain: msDS-AzGenericData, msDS-AzObjectGuid,
msDS-TasksForAzTask, msDS-OperationsForAzTask,
msDS-AzApplicationData, msDS-AzTaskIsRoleDefinition,
msDS-AzLastImportedBizRulePath, msDS-AzBizRuleLanguage,
msDS-AzBizRule, description
systemPossSuperiors: container, msDS-AzScope, msDS-AzApplication
schemaIdGuid: 1ed3a473-9b1b-418a-bfa0-3a37b95a5306
defaultSecurityDescriptor: D: (A;;RPWPCRCDCCLCLORCWOWSDDTSW;;;DA)
(A;;RPWPCRCDCCLCLORCWOWSDDTSW;;;SY) (A;;RPLCLORC;;;AU)
(A;;RPWPCRCDCCLCLORCWOWSDDTSW;;;CO)
defaultHidingValue: TRUE
systemOnly: FALSE
defaultObjectCategory: CN=ms-DS-Az-Task,<SchemaNCDN>
systemFlags: FLAG_SCHEMA_BASE_OBJECT

```

Version-Specific Behavior: Implemented on Windows Server 2003 operating system, Windows Server 2003 R2 operating system, Windows Server 2008 operating system, Windows Server 2008 R2 operating system, Windows Server 2012 operating system, and Windows Server 2012 R2 operating system.

2.127 Class msDS-ClaimsTransformationPolicies

An object of this class holds the one set of claims transformation policies for cross-forest claims transformation.

```

cn: ms-DS-Claims-Transformation-Policies
ldapDisplayName: msDS-ClaimsTransformationPolicies
governsId: 1.2.840.113556.1.5.281
objectClassCategory: 1
rdnAttId: cn
subClassOf: top
systemPossSuperiors: container
schemaIdGuid: c8fca9b1-7d88-bb4f-827a-448927710762
defaultSecurityDescriptor: D: (A;;RPWPCRCDCCLCLORCWOWSDDTSW;;;EA)
(A;;RPWPCRCDCCLCLORCWOWSDDTSW;;;SY)
defaultHidingValue: TRUE
systemOnly: FALSE
defaultObjectCategory: CN=ms-DS-Claims-Transformation-Policies,<SchemaNCDN>
systemFlags: FLAG_SCHEMA_BASE_OBJECT

```

Version-Specific Behavior: Implemented on Windows Server 2012 operating system and Windows Server 2012 R2 operating system.

2.128 Class msDS-ClaimsTransformationPolicyType

An object of this class holds the one set of claims transformation policies for cross-forest claims transformation.

```

cn: ms-DS-Claims-Transformation-Policy-Type
ldapDisplayName: msDS-ClaimsTransformationPolicyType
governsId: 1.2.840.113556.1.5.280
objectClassCategory: 1
rdnAttId: cn

```

```

subClassOf: top
systemMayContain: msDS-TransformationRulesCompiled, msDS-TransformationRules
systemPossSuperiors: msDS-ClaimsTransformationPolicies
schemaIdGuid: 2eeb62b3-1373-fe45-8101-387f1676edc7
defaultSecurityDescriptor: D: (A;;RPWPCRCDCCLCLORCWOWSDDTSW;;;EA)
(A;;RPWPCRCDCCLCLORCWOWSDDTSW;;;SY)
defaultHidingValue: TRUE
systemOnly: FALSE
defaultObjectCategory: CN=ms-DS-Claims-Transformation-Policy-Type,
<SchemaNCDN>
systemFlags: FLAG_SCHEMA_BASE_OBJECT

```

Version-Specific Behavior: Implemented on Windows Server 2012 operating system and Windows Server 2012 R2 operating system.

2.129 Class msDS-ClaimType

An instance of this class holds the definition of a claim type that can be defined on security principals.

```

cn: ms-DS-Claim-Type
ldapDisplayName: msDS-ClaimType
governsId: 1.2.840.113556.1.5.272
objectClassCategory: 1
rdnAttId: cn
subClassOf: msDS-ClaimTypePropertyBase
systemMayContain: msDS-ClaimIsSingleValued, msDS-ClaimIsValueSpaceRestricted,
msDS-ClaimValueType, msDS-ClaimSourceType, msDS-ClaimSource,
msDS-ClaimTypeAppliesToClass, msDS-ClaimAttributeSource
systemPossSuperiors: msDS-ClaimTypes
schemaIdGuid: 81a3857c-5469-4d8f-aae6-c27699762604
defaultSecurityDescriptor: D: (A;;RPWPCRCDCCLCLORCWOWSDDTSW;;;EA)
(A;;RPWPCRCDCCLCLORCWOWSDDTSW;;;SY) (A;;RPLCLORC;;;AU)
defaultHidingValue: FALSE
systemOnly: FALSE
defaultObjectCategory: CN=ms-DS-Claim-Type,<SchemaNCDN>
systemFlags: FLAG_SCHEMA_BASE_OBJECT

```

Version-Specific Behavior: Implemented on Windows Server 2012 operating system and Windows Server 2012 R2 operating system.

2.130 Class msDS-ClaimTypePropertyBase

An abstract class that defines the base class for claim type or resource property classes.

```

cn: ms-DS-Claim-Type-Property-Base
ldapDisplayName: msDS-ClaimTypePropertyBase
governsId: 1.2.840.113556.1.5.269
objectClassCategory: 2
rdnAttId: cn
subClassOf: top
systemMayContain: msDS-ClaimSharesPossibleValuesWith, Enabled,
msDS-ClaimPossibleValues
schemaIdGuid: b8442f58-c490-4487-8a9d-d80b883271ad
defaultSecurityDescriptor: D: (A;;RPWPCRCDCCLCLORCWOWSDDTSW;;;EA)

```

```
(A;;RPWPCRCDCCLCLORCWOWSDDTSW;;;SY)(A;;RPLCLORC;;;AU)
defaultHidingValue: FALSE
systemOnly: FALSE
defaultObjectCategory: CN=ms-DS-Claim-Type-Property-Base,<SchemaNCDN>
systemFlags: FLAG_SCHEMA_BASE_OBJECT
```

Version-Specific Behavior: Implemented on Windows Server 2012 operating system and Windows Server 2012 R2 operating system.

2.131 Class msDS-ClaimTypes

A container of this class can contain claim type objects.

```
cn: ms-DS-Claim-Types
ldapDisplayName: msDS-ClaimTypes
governsId: 1.2.840.113556.1.5.270
objectClassCategory: 1
rdnAttId: cn
subClassOf: top
systemPossSuperiors: container
schemaIdGuid: 36093235-c715-4821-ab6a-b56fb2805a58
defaultSecurityDescriptor: D:(A;;RPWPCRCDCCLCLORCWOWSDDTSW;;;EA)
(A;;RPWPCRCDCCLCLORCWOWSDDTSW;;;SY)(A;;RPLCLORC;;;AU)
defaultHidingValue: TRUE
systemOnly: FALSE
defaultObjectCategory: CN=ms-DS-Claim-Types,<SchemaNCDN>
systemFlags: FLAG_SCHEMA_BASE_OBJECT
```

Version-Specific Behavior: Implemented on Windows Server 2012 operating system and Windows Server 2012 R2 operating system.

2.132 Class msDS-CloudExtensions

A collection of attributes that contains application-specific strings for cloud scenarios.

```
cn: ms-DS-Cloud-Extensions
ldapDisplayName: msDS-CloudExtensions
governsId: 1.2.840.113556.1.5.283
objectClassCategory: 3
rdnAttId: cn
subClassOf: top
MayContain: msDS-cloudExtensionAttribute1, msDS-cloudExtensionAttribute2,
msDS-cloudExtensionAttribute3, msDS-cloudExtensionAttribute4,
msDS-cloudExtensionAttribute5, msDS-cloudExtensionAttribute6,
msDS-cloudExtensionAttribute7, msDS-cloudExtensionAttribute8,
msDS-cloudExtensionAttribute9, msDS-cloudExtensionAttribute10,
msDS-cloudExtensionAttribute11, msDS-cloudExtensionAttribute12,
msDS-cloudExtensionAttribute13, msDS-cloudExtensionAttribute14,
msDS-cloudExtensionAttribute15, msDS-cloudExtensionAttribute16,
msDS-cloudExtensionAttribute17, msDS-cloudExtensionAttribute18,
msDS-cloudExtensionAttribute19, msDS-cloudExtensionAttribute20
schemaIdGuid: 641e87a4-8326-4771-ba2d-c706df35e35a
defaultSecurityDescriptor: D:(A;;RPWPCRCDCCLCLORCWOWSDDTSW;;;DA)
(A;;RPWPCRCDCCLCLORCWOWSDDTSW;;;SY)(A;;RPLCLORC;;;AU)
defaultHidingValue: TRUE
```

```
systemOnly: FALSE
defaultObjectCategory: CN=ms-DS-Cloud-Extensions,<SchemaNCDN>
systemFlags: FLAG_SCHEMA_BASE_OBJECT
```

Version-Specific Behavior: Implemented on Windows Server 2012 operating system and Windows Server 2012 R2 operating system.

2.133 Class msDS-Device

This class represents a registered device.

```
cn: ms-DS-Device
ldapDisplayName: msDS-Device
governsId: 1.2.840.113556.1.5.286
objectClassCategory: 1
rDNAttID: cn
subClassOf: top
systemMustContain: altSecurityIdentities, displayName, msDS-DeviceID,
msDS-IsEnabled
systemMayContain: msDS-ApproximateLastLogonTimeStamp, msDS-CloudAnchor,
msDS-CloudIsManaged, msDS-DeviceObjectVersion, msDS-DeviceOSType,
msDS-DeviceOSVersion, msDS-DevicePhysicalIDs, msDS-IsManaged,
msDS-RegisteredOwner, msDS-RegisteredUsers
systemPossSuperiors: msDS-DeviceContainer
schemaIdGuid: 5df2b673-6d41-4774-b3e8-d52e8ee9ff99
defaultSecurityDescriptor: D: (A;;RPLCLORC;;;AU)
(A;;RPWPCRCDCCLCLORCWOWSDDDTDTSW;;;DA) (A;;RPWPCRCDCCLCLORCWOWSDDDTDTSW;;;SY)
defaultHidingValue: TRUE
systemOnly: FALSE
systemFlags: FLAG_SCHEMA_BASE_OBJECT
defaultObjectCategory: CN=ms-DS-Device,<SchemaNCDN>
showInAdvancedViewOnly: TRUE
```

Version-Specific Behavior: Implemented on Windows Server 2012 R2 operating system.

2.134 Class msDS-DeviceContainer

The container used to hold device objects.

```
cn: ms-DS-Device-Container
ldapDisplayName: msDS-DeviceContainer
governsId: 1.2.840.113556.1.5.289
objectClassCategory: 1
rDNAttID: cn
subClassOf: top
systemPossSuperiors: domainDNS
schemaIdGuid: 7c9e8c58-901b-4ea8-b6ec-4eb9e9fc0e11
defaultSecurityDescriptor: D: (A;;RPLCLORC;;;AU)
(A;;RPWPCRCDCCLCLORCWOWSDDDTDTSW;;;DA) (A;;RPWPCRCDCCLCLORCWOWSDDDTDTSW;;;SY)
defaultHidingValue: TRUE
systemOnly: FALSE
systemFlags: FLAG_SCHEMA_BASE_OBJECT
defaultObjectCategory: CN=ms-DS-Device-Container,<SchemaNCDN>
showInAdvancedViewOnly: TRUE
```

Version-Specific Behavior: Implemented on Windows Server 2012 R2 operating system.

2.135 Class msDS-DeviceRegistrationService

This class holds the registration service configuration that is used for devices.

```
cn: ms-DS-Device-Registration-Service
ldapDisplayName: msDS-DeviceRegistrationService
governsId: 1.2.840.113556.1.5.284
objectClassCategory: 1
rDNAttID: cn
subClassOf: top
systemMustContain: msDS-DeviceLocation, msDS-IsEnabled
systemMayContain: msDS-CloudIsEnabled, msDS-CloudIssuerPublicCertificates,
msDS-IssuerCertificates, msDS-IssuerPublicCertificates,
msDS-MaximumRegistrationInactivityPeriod, msDS-RegistrationQuota
systemPossSuperiors: msDS-DeviceRegistrationServiceContainer
schemaIdGuid: 96bc3ala-e3d2-49d3-af11-7b0df79d67f5
defaultSecurityDescriptor: D: (A;;RPLCLORC;;;AU)
(A;;RPWPCRCCDCLCLORCWOWDSDDTSW;;;EA) (A;;RPWPCRCCDCLCLORCWOWDSDDTSW;;;SY)
defaultHidingValue: TRUE
systemOnly: FALSE
systemFlags: FLAG_SCHEMA_BASE_OBJECT
defaultObjectCategory: CN=ms-DS-Device-Registration-Service,<SchemaNCDN>
showInAdvancedViewOnly: TRUE
```

Version-Specific Behavior: Implemented on Windows Server 2012 R2 operating system.

2.136 Class msDS-DeviceRegistrationServiceContainer

The container used to house all enrollment services used for device registrations.

```
cn: ms-DS-Device-Registration-Service-Container
ldapDisplayName: msDS-DeviceRegistrationServiceContainer
governsId: 1.2.840.113556.1.5.287
objectClassCategory: 1
rDNAttID: cn
subClassOf: top
systemPossSuperiors: container
schemaIdGuid: 310b55ce-3dcd-4392-a96d-c9e35397c24f
defaultSecurityDescriptor: D: (A;;RPLCLORC;;;AU)
(A;;RPWPCRCCDCLCLORCWOWDSDDTSW;;;EA) (A;;RPWPCRCCDCLCLORCWOWDSDDTSW;;;SY)
defaultHidingValue: TRUE
systemOnly: FALSE
systemFlags: FLAG_SCHEMA_BASE_OBJECT
defaultObjectCategory: CN=ms-DS-Device-Registration-Service-Container,
<SchemaNCDN>
showInAdvancedViewOnly: TRUE
```

Version-Specific Behavior: Implemented on Windows Server 2012 R2 operating system.

2.137 Class msDS-GroupManagedServiceAccount

The group managed service account class is used to create an account that can be shared by different computers in order to run Windows services.


```

cn: ms-DS-Group-Managed-Service-Account
ldapDisplayName: msDS-GroupManagedServiceAccount
governsId: 1.2.840.113556.1.5.282
objectClassCategory: 1
rdnAttId: cn
subClassOf: computer
systemMustContain: msDS-ManagedPasswordInterval
systemMayContain: msDS-GroupMSAMembership, msDS-ManagedPasswordPreviousId,
  msDS-ManagedPasswordId, msDS-ManagedPassword
systemPossSuperiors: computer, container, organizationalUnit, domainDNS
schemaIdGuid: 7b8b558a-93a5-4af7-adca-c017e67f1057
defaultSecurityDescriptor: D:
  (OD;;;CR;00299570-246d-11d0-a768-00aa006e0529;;WD)
  (A;;;RPWPCRCCDCLLORCWOWSDSDTWSW;;;DA) (A;;;RPWPCRCCDCLLORCWOWSDSDTWSW;;;AO)
  (A;;;RPWPCRCCDCLLORCWOWSDSDTWSW;;;SY) (A;;;RPCRLCLORCSDDT;;;CO)
  (OA;;;WP;4c164200-20c0-11d0-a768-00aa006e0529;;CO)
  (OA;;;SW;72e39547-7b18-11d1-edef-00c04fd8d5cd;;CO)
  (OA;;;SW;f3a64788-5306-11d1-a9c5-0000f80367c1;;CO)
  (OA;;;WP;3e0abfd0-126a-11d0-a060-00aa006c33ed;bf967a86-0de6-11d0-a285-
    00aa003049e2;CO) (OA;;;WP;5f202010-79a5-11d0-9020-00c04fc2d4cf;bf967a86-
    0de6-11d0-a285-00aa003049e2;CO) (OA;;;WP;bf967950-0de6-11d0-a285-
    00aa003049e2;bf967a86-0de6-11d0-a285-00aa003049e2;CO) (OA;;;WP;bf967953-
    0de6-11d0-a285-00aa003049e2;bf967a86-0de6-11d0-a285-00aa003049e2;CO)
  (OA;;;SW;f3a64788-5306-11d1-a9c5-0000f80367c1;;PS)
  (OA;;;RPWP;77B5B886-944A-11d1-AEBD-0000F80367C1;;PS)
  (OA;;;SW;72e39547-7b18-11d1-edef-00c04fd8d5cd;;PS) (A;;;RPLCLORC;;;AU)
  (OA;;;RPW;bf967a7f-0de6-11d0-a285-00aa003049e2;;CA)
  (OA;;;RP;46a9b11d-60ae-405a-b7e8-ff8a58d456d2;;S-1-5-32-560)
  (OA;;;RP;e362ed86-b728-0842-b27d-2dea7a9df218;;WD)
defaultHidingValue: FALSE
systemOnly: FALSE
defaultObjectCategory: CN=ms-DS-Group-Managed-Service-Account,<SchemaNCN>
systemFlags: FLAG_SCHEMA_BASE_OBJECT

```

Version-Specific Behavior: Implemented on Windows Server 2012 operating system and Windows Server 2012 R2 operating system.

2.138 Class msDS-ManagedServiceAccount

The service account class is used to create accounts that are used for running Windows services.

```

cn: ms-DS-Managed-Service-Account
ldapDisplayName: msDS-ManagedServiceAccount
governsId: 1.2.840.113556.1.5.264
objectClassCategory: 1
rdnAttId: cn
subClassOf: computer
systemPossSuperiors: domainDNS, organizationalUnit, container
schemaIdGuid: ce206244-5827-4a86-ba1c-1c0c386c1b64
defaultSecurityDescriptor: D: (A;;;RPWPCRCCDCLLORCWOWSDSDTWSW;;;DA)
  (A;;;RPWPCRCCDCLLORCWOWSDSDTWSW;;;AO)
  (A;;;RPWPCRCCDCLLORCWOWSDSDTWSW;;;SY) (A;;;RPCRLCLORCSDDT;;;CO)
  (OA;;;WP;4c164200-20c0-11d0-a768-00aa006e0529;;CO)
  (OA;;;SW;72e39547-7b18-11d1-edef-00c04fd8d5cd;;CO)
  (OA;;;SW;f3a64788-5306-11d1-a9c5-0000f80367c1;;CO)
  (OA;;;WP;3e0abfd0-126a-11d0-a060-00aa006c33ed;
  bf967a86-0de6-11d0-a285-00aa003049e2;CO)

```

```

(OA;;WP;5f202010-79a5-11d0-9020-00c04fc2d4cf;
bf967a86-0de6-11d0-a285-00aa003049e2;CO)
(OA;;WP;bf967950-0de6-11d0-a285-00aa003049e2;
bf967a86-0de6-11d0-a285-00aa003049e2;CO)
(OA;;WP;bf967953-0de6-11d0-a285-00aa003049e2;
bf967a86-0de6-11d0-a285-00aa003049e2;CO)
(OA;;SW;f3a64788-5306-11d1-a9c5-0000f80367c1;;PS)
(OA;;RPWP;77B5B886-944A-11d1-AEED-0000F80367C1;;PS)
(OA;;SW;72e39547-7b18-11d1-edef-00c04fd8d5cd;;PS) (A;;RPLCLORC;;;AU)
(OA;;CR;ab721a53-1e2f-11d0-9819-00aa0040529b;;WD)
(OA;;RPWP;bf967a7f-0de6-11d0-a285-00aa003049e2;;CA)
(OA;;RP;46a9b11d-60ae-405a-b7e8-ff8a58d456d2;;S-1-5-32-560)
(OA;;RP;b7c69e6d-2cc7-11d2-854e-00a0c983f608;;ED)
defaultHidingValue: FALSE
systemOnly: FALSE
defaultObjectCategory: CN=ms-DS-Managed-Service-Account,<SchemaNCDN>
systemFlags: FLAG_SCHEMA_BASE_OBJECT

```

Version-Specific Behavior: Implemented on Windows Server 2008 R2 operating system, Windows Server 2012 operating system, and Windows Server 2012 R2 operating system.

2.139 Class msDS-OptionalFeature

The configuration object for an optional feature.

```

cn: ms-DS-Optional-Feature
ldapDisplayName: msDS-OptionalFeature
governsId: 1.2.840.113556.1.5.265
objectClassCategory: 1
rdnAttId: cn
subClassOf: top
systemMustContain: msDS-OptionalFeatureFlags,
msDS-OptionalFeatureGUID
systemMayContain: msDS-RequiredDomainBehaviorVersion,
msDS-RequiredForestBehaviorVersion
systemPossSuperiors: container
schemaIdGuid: 44f00041-35af-468b-b20a-6ce8737c580b
defaultSecurityDescriptor: D: (A;;RPLCLORC;;;AU)
(A;;RPWPCRLCLOCCDCRCWDWOSDDTSW;;;EA)
(A;;RPWPCRLCLOCCDCRCWDWOSDDTSW;;;CO)
(A;;RPWPCRLCLOCCDCRCWDWOSDDTSW;;;SY)
defaultHidingValue: TRUE
systemOnly: TRUE
defaultObjectCategory: CN=ms-DS-Optional-Feature,<SchemaNCDN>
systemFlags: FLAG_SCHEMA_BASE_OBJECT

```

Version-Specific Behavior: Implemented on Windows Server 2008 R2 operating system, Windows Server 2012 operating system, and Windows Server 2012 R2 operating system.

2.140 Class msDS-PasswordSettings

The password settings object for accounts.

```

cn: ms-DS-Password-Settings
ldapDisplayName: msDS-PasswordSettings

```

```

governsId: 1.2.840.113556.1.5.255
objectClassCategory: 1
rdnAttId: cn
subClassOf: top
systemMustContain: msDS-MaximumPasswordAge, msDS-MinimumPasswordAge,
msDS-MinimumPasswordLength, msDS-PasswordComplexityEnabled,
msDS-LockoutObservationWindow, msDS-LockoutDuration,
msDS-LockoutThreshold, msDS-PasswordReversibleEncryptionEnabled,
msDS-PasswordSettingsPrecedence, msDS-PasswordHistoryLength
systemMayContain: msDS-PSOAppliesTo
systemPossSuperiors: msDS-PasswordSettingsContainer
schemaIdGuid: 3bcd9db8-f84b-451c-952f-6c52b81f9ec6
defaultSecurityDescriptor: D:(A;;;RPWPCRCDCCLCLOCRCWOWSDDTSW;;;DA)
(A;;;RPWPCRCDCCLCLOCRCWOWSDDTSW;;;SY)
systemOnly: FALSE
defaultObjectCategory: CN=ms-DS-Password-Settings,<SchemaNCDN>
systemFlags: FLAG_SCHEMA_BASE_OBJECT

```

Version-Specific Behavior: Implemented on Windows Server 2008 operating system, Windows Server 2008 R2 operating system, Windows Server 2012 operating system, and Windows Server 2012 R2 operating system.

2.141 Class msDS-PasswordSettingsContainer

A container for password settings objects.

```

cn: ms-DS-Password-Settings-Container
ldapDisplayName: msDS-PasswordSettingsContainer
governsId: 1.2.840.113556.1.5.256
objectClassCategory: 1
rdnAttId: cn
subClassOf: top
systemPossSuperiors: container
schemaIdGuid: 5b06b06a-4cf3-44c0-bd16-43bc10a987da
defaultSecurityDescriptor: D:(A;;;RPWPCRCDCCLCLOCRCWOWSDDTSW;;;DA)
(A;;;RPWPCRCDCCLCLOCRCWOWSDDTSW;;;SY)
systemOnly: FALSE
defaultObjectCategory: CN=ms-DS-Password-Settings-Container,
<SchemaNCDN>
systemFlags: FLAG_SCHEMA_BASE_OBJECT

```

Version-Specific Behavior: Implemented on Windows Server 2008 operating system, Windows Server 2008 R2 operating system, Windows Server 2012 operating system, and Windows Server 2012 R2 operating system.

2.142 Class msDS-QuotaContainer

A special container that holds all quota specifications for the directory database.

```

cn: ms-DS-Quota-Container
ldapDisplayName: msDS-QuotaContainer
governsId: 1.2.840.113556.1.5.242
objectClassCategory: 1
rdnAttId: cn
subClassOf: top

```

```

systemMustContain: cn
systemMayContain: msDS-TopQuotaUsage, msDS-QuotaUsed,
  msDS-QuotaEffective, msDS-TombstoneQuotaFactor, msDS-DefaultQuota
systemPossSuperiors: configuration, domainDNS
schemaIdGuid: da83fc4f-076f-4aea-b4dc-8f4dab9b5993
defaultSecurityDescriptor: D: (A;;RPWPCRCDCCLORCWOWDSDDTSW;;;DA)
  (A;;RPLCLORC;;;BA) (OA;;CR;4ecc03fe-ffc0-4947-b630-eb672a8a9dbc;;WD)
defaultHidingValue: TRUE
systemOnly: FALSE
defaultObjectCategory: CN=ms-DS-Quota-Container,<SchemaNCDN>
systemFlags: FLAG_SCHEMA_BASE_OBJECT

```

Version-Specific Behavior: Implemented on Windows Server 2003 operating system, Windows Server 2003 R2 operating system, Windows Server 2008 operating system, Windows Server 2008 R2 operating system, Windows Server 2012 operating system, and Windows Server 2012 R2 operating system.

2.143 Class msDS-QuotaControl

Represents quota specifications for the directory database.

```

cn: ms-DS-Quota-Control
ldapDisplayName: msDS-QuotaControl
governsId: 1.2.840.113556.1.5.243
objectClassCategory: 1
rdnAttId: cn
subClassOf: top
systemMustContain: msDS-QuotaAmount, msDS-QuotaTrustee, cn
systemPossSuperiors: msDS-QuotaContainer
schemaIdGuid: de91fc26-bd02-4b52-ae26-795999e96fc7
defaultSecurityDescriptor: D: (A;;RPWPCRCDCCLORCWOWDSDDTSW;;;DA)
  (A;;RPLCLORC;;;BA)
defaultHidingValue: TRUE
systemOnly: FALSE
defaultObjectCategory: CN=ms-DS-Quota-Control,<SchemaNCDN>
systemFlags: FLAG_SCHEMA_BASE_OBJECT

```

Version-Specific Behavior: Implemented on Windows Server 2003 operating system, Windows Server 2003 R2 operating system, Windows Server 2008 operating system, Windows Server 2008 R2 operating system, Windows Server 2012 operating system, and Windows Server 2012 R2 operating system.

2.144 Class msDS-ResourceProperties

A container of this class can contain resource properties.

```

cn: ms-DS-Resource-Properties
ldapDisplayName: msDS-ResourceProperties
governsId: 1.2.840.113556.1.5.271
objectClassCategory: 1
rdnAttId: cn
subClassOf: top
systemPossSuperiors: container
schemaIdGuid: 7a4a4584-b350-478f-acd6-b4b852d82cc0
defaultSecurityDescriptor: D: (A;;RPWPCRCDCCLORCWOWDSDDTSW;;;EA)

```

```
(A;;RPWPCRCCLCCLORCWOWSDSDTTSW;;;SY) (A;;RPLCLORC;;;AU)
defaultHidingValue: TRUE
systemOnly: FALSE
defaultObjectCategory: CN=ms-DS-Resource-Properties,<SchemaNCDN>
systemFlags: FLAG_SCHEMA_BASE_OBJECT
```

Version-Specific Behavior: Implemented on Windows Server 2012 operating system and Windows Server 2012 R2 operating system.

2.145 Class msDS-ResourceProperty

An instance of this class holds the definition of a property of resources.

```
cn: ms-DS-Resource-Property
ldapDisplayName: msDS-ResourceProperty
governsId: 1.2.840.113556.1.5.273
objectClassCategory: 1
rdnAttId: cn
subClassOf: msDS-ClaimTypePropertyBase
systemMustContain: msDS-ValueTypeReference
systemMayContain: msDS-AppliesToResourceTypes,
  msDS-IsUsedAsResourceSecurityAttribute
systemPossSuperiors: msDS-ResourceProperties
schemaIdGuid: 5b283d5e-8404-4195-9339-8450188c501a
defaultSecurityDescriptor: D: (A;;RPWPCRCCLCCLORCWOWSDSDTTSW;;;EA)
  (A;;RPWPCRCCLCCLORCWOWSDSDTTSW;;;SY) (A;;RPLCLORC;;;AU)
defaultHidingValue: FALSE
systemOnly: FALSE
defaultObjectCategory: CN=ms-DS-Resource-Property,<SchemaNCDN>
systemFlags: FLAG_SCHEMA_BASE_OBJECT
```

Version-Specific Behavior: Implemented on Windows Server 2012 operating system and Windows Server 2012 R2 operating system.

2.146 Class msDS-ResourcePropertyList

An object of this class contains a list of resource properties.

```
cn: ms-DS-Resource-Property-List
ldapDisplayName: msDS-ResourcePropertyList
governsId: 1.2.840.113556.1.5.274
objectClassCategory: 1
rdnAttId: cn
subClassOf: top
systemMayContain: msDS-MembersOfResourcePropertyList
systemPossSuperiors: container
schemaIdGuid: 72e3d47a-b342-4d45-8f56-baff803cabf9
defaultSecurityDescriptor: D: (A;;RPWPCRCCLCCLORCWOWSDSDTTSW;;;EA)
  (A;;RPWPCRCCLCCLORCWOWSDSDTTSW;;;SY) (A;;RPLCLORC;;;AU)
defaultHidingValue: FALSE
systemOnly: FALSE
defaultObjectCategory: CN=ms-DS-Resource-Property-List,<SchemaNCDN>
systemFlags: FLAG_SCHEMA_BASE_OBJECT
```

Version-Specific Behavior: Implemented on Windows Server 2012 operating system and Windows Server 2012 R2 operating system.

2.147 Class msDS-ValueType

A value-type object holds value-type information for a resource property.

```
cn: ms-DS-Value-Type
ldapDisplayName: msDS-ValueType
governsId: 1.2.840.113556.1.5.279
objectClassCategory: 1
rdnAttId: cn
subClassOf: top
systemMustContain: msDS-IsPossibleValuesPresent, msDS-ClaimIsSingleValued,
  msDS-ClaimIsValueSpaceRestricted, msDS-ClaimValueType
systemPossSuperiors: container
schemaIdGuid: e3c27fdf-b01d-4f4e-87e7-056eef0eb922
defaultSecurityDescriptor: D: (A;;RPWPCRCDCCLCLORCWOWSDSDTSW;;;EA)
  (A;;RPWPCRCDCCLCLORCWOWSDSDTSW;;;SY) (A;;RPWPCRCDCCLCLORCWOWSDSDTSW;;;DA)
defaultHidingValue: TRUE
systemOnly: FALSE
defaultObjectCategory: CN=ms-DS-Value-Type,<SchemaNCDN>
systemFlags: FLAG_SCHEMA_BASE_OBJECT
```

Version-Specific Behavior: Implemented on Windows Server 2012 operating system and Windows Server 2012 R2 operating system.

2.148 Class msExchConfigurationContainer

Stores configuration information for an Microsoft Exchange Server.

```
cn: ms-Exch-Configuration-Container
ldapDisplayName: msExchConfigurationContainer
governsId: 1.2.840.113556.1.5.176
objectClassCategory: 1
rdnAttId: cn
subClassOf: container
systemMayContain: templateRoots, addressBookRoots, globalAddressList,
  templateRoots2, addressBookRoots2, globalAddressList2
schemaIdGuid: d03d6858-06f4-11d2-aa53-00c04fd7d83a
defaultSecurityDescriptor: D: (A;;RPWPCRCDCCLCLORCWOWSDSDTSW;;;DA)
  (A;;RPWPCRCDCCLCLORCWOWSDSDTSW;;;SY) (A;;RPLCLORC;;;AU)
defaultHidingValue: TRUE
systemOnly: FALSE
defaultObjectCategory: CN=ms-Exch-Configuration-Container,<SchemaNCDN>
systemFlags: FLAG_SCHEMA_BASE_OBJECT
```

Version-Specific Behavior: Implemented on Windows 2000 Server operating system, Windows Server 2003 operating system, Windows Server 2003 R2 operating system, Windows Server 2008 operating system, Windows Server 2008 R2 operating system, Windows Server 2012 operating system, and Windows Server 2012 R2 operating system.

2.149 Class msFVE-RecoveryInformation

Contains a full-volume encryption recovery password with its associated GUID.

```

cn: ms-FVE-RecoveryInformation
ldapDisplayName: msFVE-RecoveryInformation
governsId: 1.2.840.113556.1.5.253
objectClassCategory: 1
rdnAttId: cn
subClassOf: top
systemMustContain: msFVE-RecoveryPassword, msFVE-RecoveryGuid
mayContain: msFVE-KeyPackage, msFVE-VolumeGuid
systemPossSuperiors: computer
schemaIdGuid: ea715d30-8f53-40d0-bd1e-6109186d782c
defaultSecurityDescriptor: D: (A;;RPWPCRCDCCLORCWOWSDSDTSW;;;DA)
(A;;RPWPCRCDCCLORCWOWSDSDTSW;;;SY)
defaultHidingValue: TRUE
systemOnly: FALSE
defaultObjectCategory: CN=ms-FVE-RecoveryInformation,<SchemaNCDN>
systemFlags: FLAG_SCHEMA_BASE_OBJECT

```

Version-Specific Behavior: Implemented on Windows Server 2008 operating system, Windows Server 2008 R2 operating system, Windows Server 2012 operating system, and Windows Server 2012 R2 operating system.

2.150 Class msieeee80211-Policy

Stores a Wireless Network Policy object.

```

cn: ms-ieee-80211-Policy
ldapDisplayName: msieeee80211-Policy
governsId: 1.2.840.113556.1.5.240
objectClassCategory: 1
rdnAttId: cn
subClassOf: top
systemMayContain: msieeee80211-ID, msieeee80211-DataType,
msieeee80211-Data
systemPossSuperiors: organizationalUnit, container, computer
schemaIdGuid: 7b9a2d92-b7eb-4382-9772-c3e0f9baaf94
defaultSecurityDescriptor: D: (A;;RPWPCRCDCCLORCWOWSDSDTSW;;;DA)
(A;;RPWPCRCDCCLORCWOWSDSDTSW;;;SY) (A;;RPLCLORC;;;AU)
defaultHidingValue: TRUE
systemOnly: FALSE
defaultObjectCategory: CN=ms-ieee-80211-Policy,<SchemaNCDN>
systemFlags: FLAG_SCHEMA_BASE_OBJECT

```

Version-Specific Behavior: Implemented on Windows Server 2003 operating system, Windows Server 2003 R2 operating system, Windows Server 2008 operating system, Windows Server 2008 R2 operating system, Windows Server 2012 operating system, and Windows Server 2012 R2 operating system.

2.151 Class msImaging-PostScanProcess

The container for all Business Scan Post Scan Process objects.

```

cn: ms-Imaging-PostScanProcess
ldapDisplayName: msImaging-PostScanProcess
governsId: 1.2.840.113556.1.5.263
objectClassCategory: 1

```

```

rdnAttId: cn
subClassOf: top
systemMayContain: msImaging-PSPString, serverName
systemMustContain: displayName, msImaging-PSPIdentifier
systemPossSuperiors: msImaging-PSPs
schemaIdGuid: 1f7c257c-b8a3-4525-82f8-11ccc7bee36e
defaultSecurityDescriptor: D: (A;;RPWPCRCDCCLCLORCWOWSDSDTWS;;;DA)
(A;;RPWPCRCDCCLCLORCWOWSDSDTWS;;;SY) (A;;RPLCLORC;;;AU)
defaultHidingValue: FALSE
systemOnly: FALSE
defaultObjectCategory: CN=ms-Imaging-PostScanProcess,<SchemaNCDN>
systemFlags: FLAG_SCHEMA_BASE_OBJECT

```

Version-Specific Behavior: Implemented on Windows Server 2008 R2 operating system, Windows Server 2012 operating system, and Windows Server 2012 R2 operating system.

2.152 Class msImaging-PSPs

The container for all Business Scan Post Scan Process objects.

```

cn: ms-Imaging-PSPs
ldapDisplayName: msImaging-PSPs
governsId: 1.2.840.113556.1.5.262
objectClassCategory: 1
rdnAttId: cn
subClassOf: container
systemPossSuperiors: container
schemaIdGuid: a0ed2ac1-970c-4777-848e-ec63a0ec44fc
defaultSecurityDescriptor: D: (A;;RPWPCRCDCCLCLORCWOWSDSDTWS;;;DA)
(A;;RPWPCRCDCCLCLORCWOWSDSDTWS;;;SY) (A;;RPLCLORC;;;AU)
defaultHidingValue: FALSE
systemOnly: FALSE
defaultObjectCategory: CN=ms-Imaging-PSPs,<SchemaNCDN>
systemFlags: FLAG_SCHEMA_BASE_OBJECT

```

Version-Specific Behavior: Implemented on Windows Server 2008 R2 operating system, Windows Server 2012 operating system, and Windows Server 2012 R2 operating system.

2.153 Class msKds-ProvRootKey

Root keys for the Group Key Distribution Service.

```

cn: ms-Kds-Prov-RootKey
ldapDisplayName: msKds-ProvRootKey
governsId: 1.2.840.113556.1.5.278
objectClassCategory: 1
rdnAttId: cn
subClassOf: top
systemMustContain: msKds-CreateTime, msKds-RootKeyData,
msKds-PrivateKeyLength, msKds-PublicKeyLength,
msKds-SecretAgreementAlgorithmID, msKds-KDFAlgorithmID,
msKds-UseStartTime, msKds-DomainID, msKds-Version, cn
systemMayContain: msKds-SecretAgreementParam, msKds-KDFParam
systemPossSuperiors: container
schemaIdGuid: aa02fd41-17e0-4f18-8687-b2239649736b

```



```
defaultSecurityDescriptor: D: (A;;RPWPCRCDCCLCLORCWOWSDSDTWSW;;;EA)
  (A;;RPWPCRCDCCLCLORCWOWSDSDTWSW;;;SY) (A;;RPWPCRCDCCLCLORCWOWSDSDTWSW;;;DA)
defaultHidingValue: TRUE
systemOnly: FALSE
defaultObjectCategory: CN=ms-Kds-Prov-RootKey,<SchemaNCDN>
systemFlags: FLAG_SCHEMA_BASE_OBJECT
```

Version-Specific Behavior: Implemented on Windows Server 2012 operating system and Windows Server 2012 R2 operating system.

2.154 Class msKds-ProvServerConfiguration

Configuration for the Group Key Distribution Service.

```
cn: ms-Kds-Prov-ServerConfiguration
ldapDisplayName: msKds-ProvServerConfiguration
governsId: 1.2.840.113556.1.5.277
objectClassCategory: 1
rdnAttId: cn
subClassOf: top
systemMustContain: msKds-Version
systemMayContain: msKds-PrivateKeyLength, msKds-PublicKeyLength,
  msKds-SecretAgreementParam, msKds-SecretAgreementAlgorithmID,
  msKds-KDFParam, msKds-KDFAlgorithmID
systemPossSuperiors: container
schemaIdGuid: 5ef243a8-2a25-45a6-8b73-08a71ae677ce
defaultSecurityDescriptor: D: (A;;RPWPCRCDCCLCLORCWOWSDSDTWSW;;;EA)
  (A;;RPWPCRCDCCLCLORCWOWSDSDTWSW;;;SY) (A;;RPWPCRCDCCLCLORCWOWSDSDTWSW;;;DA)
defaultHidingValue: TRUE
systemOnly: FALSE
defaultObjectCategory: CN=ms-Kds-Prov-ServerConfiguration,<SchemaNCDN>
systemFlags: FLAG_SCHEMA_BASE_OBJECT
```

Version-Specific Behavior: Implemented on Windows Server 2012 operating system and Windows Server 2012 R2 operating system.

2.155 Class msMQ-Custom-Recipient

Defines a custom Microsoft Message Queuing (MSMQ) recipient; that is, an alias queue. This class defines an alias for an out-of-enterprise queue and contains the format name of that queue.

```
cn: MSMQ-Custom-Recipient
ldapDisplayName: msMQ-Custom-Recipient
governsId: 1.2.840.113556.1.5.218
objectClassCategory: 1
rdnAttId: cn
subClassOf: top
systemMayContain: msMQ-Recipient-FormatName
systemPossSuperiors: organizationalUnit, domainDNS, container
schemaIdGuid: 876d6817-35cc-436c-acea-5ef7174dd9be
defaultSecurityDescriptor: D: (A;;RPWPCRCDCCLCLORCWOWSDSDTWSW;;;DA)
  (A;;RPWPCRCDCCLCLORCWOWSDSDTWSW;;;SY) (A;;RPLCLORC;;;AU)
defaultHidingValue: FALSE
systemOnly: FALSE
defaultObjectCategory: CN=MSMQ-Custom-Recipient,<SchemaNCDN>
```

```
systemFlags: FLAG_SCHEMA_BASE_OBJECT
```

Version-Specific Behavior: Implemented on Windows Server 2003 operating system, Windows Server 2003 R2 operating system, Windows Server 2008 operating system, Windows Server 2008 R2 operating system, Windows Server 2012 operating system, and Windows Server 2012 R2 operating system.

2.156 Class msMQ-Group

Defines a group of MSMQ queues; that is, a distribution list.

```
cn: MSMQ-Group
ldapDisplayName: msMQ-Group
governsId: 1.2.840.113556.1.5.219
objectClassCategory: 1
rdnAttId: cn
subClassOf: top
systemMustContain: member
systemPossSuperiors: organizationalUnit
schemaIdGuid: 46b27aac-aafa-4ffb-b773-e5bf621ee87b
defaultSecurityDescriptor: D:(A;;;RPWPCRCDCCLCLORCWOWSDSDTSW;;;DA)
(A;;;RPWPCRCDCCLCLORCWOWSDSDTSW;;;SY)(A;;;RPLCLORC;;;AU)
defaultHidingValue: TRUE
systemOnly: FALSE
defaultObjectCategory: CN=MSMQ-Group,<SchemaNCDN>
systemFlags: FLAG_SCHEMA_BASE_OBJECT
```

Version-Specific Behavior: Implemented on Windows Server 2003 operating system, Windows Server 2003 R2 operating system, Windows Server 2008 operating system, Windows Server 2008 R2 operating system, Windows Server 2012 operating system, and Windows Server 2012 R2 operating system.

2.157 Class mSMQConfiguration

An object that contains MSMQ configuration parameters for a specific computer. The attributes of this class are MSMQ-specific and are used for MSMQ routing decisions.

```
cn: MSMQ-Configuration
ldapDisplayName: mSMQConfiguration
governsId: 1.2.840.113556.1.5.162
objectClassCategory: 1
rdnAttId: cn
subClassOf: top
systemMayContain: mSMQSites, mSMQSignKey, mSMQServiceType,
mSMQRoutingServices, mSMQQuota, mSMQOwnerID, mSMQOutRoutingServers,
mSMQOSType, mSMQJournalQuota, mSMQInRoutingServers, mSMQForeign,
mSMQEncryptKey, mSMQDsServices, mSMQDependentClientServices,
mSMQComputerTypeEx, mSMQComputerType
systemPossSuperiors: computer
schemaIdGuid: 9a0dc344-c100-11d1-bbc5-0080c76670c0
defaultSecurityDescriptor: D:(A;;;RPWPCRCDCCLCLORCWOWSDSDTSW;;;DA)
(A;;;RPWPCRCDCCLCLORCWOWSDSDTSW;;;SY)(A;;;RPLCLORC;;;AU)
defaultHidingValue: TRUE
systemOnly: FALSE
defaultObjectCategory: CN=MSMQ-Configuration,<SchemaNCDN>
```

```
systemFlags: FLAG_SCHEMA_BASE_OBJECT
```

Version-Specific Behavior: Implemented on Windows 2000 Server operating system, Windows Server 2003 operating system, Windows Server 2003 R2 operating system, Windows Server 2008 operating system, Windows Server 2008 R2 operating system, Windows Server 2012 operating system, and Windows Server 2012 R2 operating system.

2.158 Class mSMQEnterpriseSettings

An object that has general MSMQ information. This object is placed under \configuration\Services and contains organization-wide configuration information for Message Queuing. A forest can have only one of these objects.

```
cn: MSMQ-Enterprise-Settings
ldapDisplayName: mSMQEnterpriseSettings
governsId: 1.2.840.113556.1.5.163
objectClassCategory: 1
rdnAttId: cn
subClassOf: top
systemMayContain: mSMQVersion, mSMQNameStyle, mSMQLongLived,
  mSMQInterval2, mSMQInterval1, mSMQCSPName
systemPossSuperiors: container
schemaIdGuid: 9a0dc345-c100-11d1-bbc5-0080c76670c0
defaultSecurityDescriptor: D: (A;;;RPWPCRCCLCLORCWOWSDDTSW;;;DA)
  (A;;;RPWPCRCCLCLORCWOWSDDTSW;;;SY) (A;;;RPLCLORC;;;AU)
defaultHidingValue: TRUE
systemOnly: FALSE
defaultObjectCategory: CN=MSMQ-Enterprise-Settings,<SchemaNCN>
systemFlags: FLAG_SCHEMA_BASE_OBJECT
```

Version-Specific Behavior: Implemented on Windows 2000 Server operating system, Windows Server 2003 operating system, Windows Server 2003 R2 operating system, Windows Server 2008 operating system, Windows Server 2008 R2 operating system, Windows Server 2012 operating system, and Windows Server 2012 R2 operating system.

2.159 Class mSMQMigratedUser

An object that is associated with a migrated user. MSMQ 1.0 used a proprietary directory service that contained specific user information. As part of MSMQ integration with the Windows 2000 operating system directory service, MSMQ provides a migration tool. During migration, for each user that is not in the Windows 2000 domain, a migrated user is created.

```
cn: MSMQ-Migrated-User
ldapDisplayName: mSMQMigratedUser
governsId: 1.2.840.113556.1.5.179
objectClassCategory: 1
rdnAttId: cn
subClassOf: top
systemMayContain: mSMQUserSid, mSMQSignCertificatesMig,
  mSMQSignCertificates, mSMQDigestsMig, mSMQDigests, objectSid
systemPossSuperiors: organizationalUnit, domainDNS, builtinDomain
schemaIdGuid: 50776997-3c3d-11d2-90cc-00c04fd91ab1
defaultSecurityDescriptor: D: (A;;;RPWPCRCCLCLORCWOWSDDTSW;;;DA)
  (A;;;RPWPCRCCLCLORCWOWSDDTSW;;;SY) (A;;;RPLCLORC;;;AU)
defaultHidingValue: TRUE
```

```
systemOnly: FALSE
defaultObjectCategory: CN=MSMQ-Migrated-User,<SchemaNCDN>
systemFlags: FLAG_SCHEMA_BASE_OBJECT
```

Version-Specific Behavior: Implemented on Windows 2000 Server operating system, Windows Server 2003 operating system, Windows Server 2003 R2 operating system, Windows Server 2008 operating system, Windows Server 2008 R2 operating system, Windows Server 2012 operating system, and Windows Server 2012 R2 operating system.

2.160 Class mSMQQueue

A queue that is associated with a specific computer and is placed under the MSMQ-Configuration of that computer. MSMQ users create queues according to their requirements by using the Microsoft Management Console (MMC) or the MSMQ API. There is no limit to the number of queues per computer.

```
cn: MSMQ-Queue
ldapDisplayName: mSMQQueue
governsId: 1.2.840.113556.1.5.161
objectClassCategory: 1
rdnAttId: cn
subClassOf: top
systemMayContain: mSMQTransactional, MSMQ-SecuredSource,
  mSMQQueueType, mSMQQueueQuota, mSMQQueueNameExt,
  mSMQQueueJournalQuota, mSMQPrivacyLevel, mSMQOwnerID,
  MSMQ-MulticastAddress, mSMQLabelEx, mSMQLabel, mSMQJournal,
  mSMQBasePriority, mSMQAuthenticate
systemPossSuperiors: mSMQConfiguration
schemaIdGuid: 9a0dc343-c100-11d1-bbc5-0080c76670c0
defaultSecurityDescriptor: D: (A;;RPWPCRCDCCLCLORCWOWSDSDTSW;;;DA)
  (A;;RPWPCRCDCCLCLORCWOWSDSDTSW;;;SY) (A;;RPLCLORC;;;AU)
defaultHidingValue: FALSE
systemOnly: FALSE
defaultObjectCategory: CN=MSMQ-Queue,<SchemaNCDN>
systemFlags: FLAG_SCHEMA_BASE_OBJECT
```

Version-Specific Behavior: Implemented on Windows 2000 Server operating system, Windows Server 2003 operating system, Windows Server 2003 R2 operating system, Windows Server 2008 operating system, Windows Server 2008 R2 operating system, Windows Server 2012 operating system, and Windows Server 2012 R2 operating system.

2.161 Class mSMQSettings

An object that enables fast query of MSMQ servers at a specific site. This object holds information such as Message Queuing services, which the server provides.

```
cn: MSMQ-Settings
ldapDisplayName: mSMQSettings
governsId: 1.2.840.113556.1.5.165
objectClassCategory: 1
rdnAttId: cn
subClassOf: top
systemMayContain: mSMQSiteNameEx, mSMQSiteName, mSMQServices,
  mSMQRoutingService, mSMQQMID, mSMQOwnerID, mSMQnt4Flags,
  mSMQMigrated, mSMQDsService, mSMQDependentClientService
```

```

systemPossSuperiors: server
schemaIdGuid: 9a0dc347-c100-11d1-bbc5-0080c76670c0
defaultSecurityDescriptor: D:(A;;RPWPCRCDCCLCLORCWOWDSDDTSW;;;DA)
(A;;RPWPCRCDCCLCLORCWOWDSDDTSW;;;SY)(A;;RPLCLORC;;;AU)
defaultHidingValue: TRUE
systemOnly: FALSE
defaultObjectCategory: CN=MSMQ-Settings,<SchemaNCDN>
systemFlags: FLAG_SCHEMA_BASE_OBJECT

```

Version-Specific Behavior: Implemented on Windows 2000 Server operating system, Windows Server 2003 operating system, Windows Server 2003 R2 operating system, Windows Server 2008 operating system, Windows Server 2008 R2 operating system, Windows Server 2012 operating system, and Windows Server 2012 R2 operating system.

2.162 Class mSMQSiteLink

Contains information about MSMQ routing connectivity between sites. This object is created for each routing link and contains connectivity information. An object of this type is contained by an MSMQ Services object.

```

cn: MSMQ-Site-Link
ldapDisplayName: mSMQSiteLink
governsId: 1.2.840.113556.1.5.164
objectClassCategory: 1
rdnAttId: cn
subClassOf: top
systemMustContain: mSMQSite2, mSMQSite1, mSMQCost
systemMayContain: mSMQSiteGatesMig, mSMQSiteGates
systemPossSuperiors: mSMQEnterpriseSettings
schemaIdGuid: 9a0dc346-c100-11d1-bbc5-0080c76670c0
defaultSecurityDescriptor: D:(A;;RPWPCRCDCCLCLORCWOWDSDDTSW;;;DA)
(A;;RPWPCRCDCCLCLORCWOWDSDDTSW;;;SY)(A;;RPLCLORC;;;AU)
defaultHidingValue: FALSE
systemOnly: FALSE
defaultObjectCategory: CN=MSMQ-Site-Link,<SchemaNCDN>
systemFlags: FLAG_SCHEMA_BASE_OBJECT

```

Version-Specific Behavior: Implemented on Windows 2000 Server operating system, Windows Server 2003 operating system, Windows Server 2003 R2 operating system, Windows Server 2008 operating system, Windows Server 2008 R2 operating system, Windows Server 2012 operating system, and Windows Server 2012 R2 operating system.

2.163 Class msPKI-Enterprise-Oid

The value that is used when a certificate user interface (UI) displays a friendly name for a certificate template, enhanced key usage, application policy, and issuance policy. The UI component tries to locate a string in the attribute that matches the default language locale.

```

cn: ms-PKI-Enterprise-Oid
ldapDisplayName: msPKI-Enterprise-Oid
governsId: 1.2.840.113556.1.5.196
objectClassCategory: 1
rdnAttId: cn
subClassOf: top
systemMayContain: msDS-OIDToGroupLink, msPKI-OID-User-Notice,

```

```

msPKI-OIDLocalizedName, msPKI-OID-CPS, msPKI-OID-Attribute,
msPKI-Cert-Template-OID
systemPossSuperiors: msPKI-Enterprise-Oid, container
schemaIdGuid: 37cfd85c-6719-4ad8-8f9e-8678ba627563
defaultSecurityDescriptor: D: (A;;RPWPCRCDCCLCLORCWOWDSDDTSW;;;DA)
(A;;RPWPCRCDCCLCLORCWOWDSDDTSW;;;SY) (A;;RPLCLORC;;;AU)
defaultHidingValue: TRUE
systemOnly: FALSE
defaultObjectCategory: CN=ms-PKI-Enterprise-Oid,<SchemaNCDN>
systemFlags: FLAG_SCHEMA_BASE_OBJECT

```

Version-Specific Behavior: Implemented on Windows Server 2003 operating system, Windows Server 2003 R2 operating system, Windows Server 2008 operating system, Windows Server 2008 R2 operating system, Windows Server 2012 operating system, and Windows Server 2012 R2 operating system.

2.164 Class msPKI-Key-Recovery-Agent

An object that is associated with a key recovery agent (KRA) instance. One KRA object instance is created for each installed Cert Server (with a unique common name) during Cert Server setup. If two certificate authorities (CAs) are given the same common name during CA setup, they share a single KRA object instance.

```

cn: ms-PKI-Key-Recovery-Agent
ldapDisplayName: msPKI-Key-Recovery-Agent
governsId: 1.2.840.113556.1.5.195
objectClassCategory: 1
rdnAttId: cn
subClassOf: user
systemPossSuperiors: container
schemaIdGuid: 26ccf238-a08e-4b86-9a82-a8c9ac7ee5cb
defaultSecurityDescriptor: D: (A;;RPWPCRCDCCLCLORCWOWDSDDTSW;;;DA)
(A;;RPWPCRCDCCLCLORCWOWDSDDTSW;;;SY) (A;;RPLCLORC;;;AU)
defaultHidingValue: TRUE
systemOnly: FALSE
defaultObjectCategory: CN=ms-PKI-Key-Recovery-Agent,<SchemaNCDN>
systemFlags: FLAG_SCHEMA_BASE_OBJECT

```

Version-Specific Behavior: Implemented on Windows Server 2003 operating system, Windows Server 2003 R2 operating system, Windows Server 2008 operating system, Windows Server 2008 R2 operating system, Windows Server 2012 operating system, and Windows Server 2012 R2 operating system.

2.165 Class msPKI-PrivateKeyRecoveryAgent

Publishes the KRA certificate in the KRA container.

```

cn: ms-PKI-Private-Key-Recovery-Agent
ldapDisplayName: msPKI-PrivateKeyRecoveryAgent
governsId: 1.2.840.113556.1.5.223
objectClassCategory: 1
rdnAttId: cn
subClassOf: top
systemMustContain: userCertificate
systemPossSuperiors: container

```

```
schemaIdGuid: 1562a632-44b9-4a7e-a2d3-e426c96a3acc
defaultSecurityDescriptor: D: (A;;RPWPCRCDCCLCLORCWOWSDDTSW;;;DA)
(A;;RPWPCRCDCCLCLORCWOWSDDTSW;;;SY) (A;;RPLCLORC;;;AU)
defaultHidingValue: TRUE
systemOnly: FALSE
defaultObjectCategory: CN=ms-PKI-Private-Key-Recovery-Agent,<SchemaNCDN>
systemFlags: FLAG_SCHEMA_BASE_OBJECT
```

Version-Specific Behavior: Implemented on Windows Server 2003 operating system, Windows Server 2003 R2 operating system, Windows Server 2008 operating system, Windows Server 2008 R2 operating system, Windows Server 2012 operating system, and Windows Server 2012 R2 operating system.

2.166 Class msPrint-ConnectionPolicy

Contains the printer connection policy.

```
cn: ms-Print-ConnectionPolicy
ldapDisplayName: msPrint-ConnectionPolicy
governsId: 1.2.840.113556.1.6.23.2
objectClassCategory: 1
rdnAttId: cn
subClassOf: top
mustContain: cn
mayContain: printerName, printAttributes, serverName, uNCName
possSuperiors: container
schemaIdGuid: a16f33c7-7fd6-4828-9364-435138fda08d
defaultSecurityDescriptor: D: (A;;RPWPCRCDCCLCLORCWOWSDDTSW;;;DA)
(A;;RPWPCRCDCCLCLORCWOWSDDTSW;;;SY) (A;;RPLCLORC;;;AU)
defaultHidingValue: TRUE
systemOnly: FALSE
defaultObjectCategory: CN=ms-Print-ConnectionPolicy,<SchemaNCDN>
```

Version-Specific Behavior: Implemented on Windows Server 2003 R2 operating system, Windows Server 2008 operating system, Windows Server 2008 R2 operating system, Windows Server 2012 operating system, and Windows Server 2012 R2 operating system.

2.167 Class msSFU30DomainInfo

Represents an internal data structure that is used by the server for Network Information Service (NIS).

```
cn: msSFU-30-Domain-Info
ldapDisplayName: msSFU30DomainInfo
governsId: 1.2.840.113556.1.6.18.2.215
objectClassCategory: 1
rdnAttId: cn
subClassOf: top
mayContain: msSFU30Domains, msSFU30YpServers, msSFU30SearchContainer,
msSFU30IsValidContainer, msSFU30MasterServerName,
msSFU30OrderNumber, msSFU30MaxGidNumber, msSFU30MaxUidNumber,
msSFU30CryptMethod
possSuperiors: container
schemaIdGuid: 36297dce-656b-4423-ab65-dabb2770819e
defaultSecurityDescriptor: D: (A;;RPWPCRCDCCLCLORCWOWSDDTSW;;;DA)
```

```
(A;;RPWPCRCDCCLCLORCWOWSDDTSW;;;SY)(A;;RPLCLORC;;;AU)
defaultHidingValue: TRUE
systemOnly: FALSE
defaultObjectCategory: CN=msSFU-30-Domain-Info,<SchemaNCDN>
```

Version-Specific Behavior: Implemented on Windows Server 2003 R2 operating system, Windows Server 2008 operating system, Windows Server 2008 R2 operating system, Windows Server 2012 operating system, and Windows Server 2012 R2 operating system.

2.168 Class msSFU30MailAliases

Represents email file data for Windows Services for UNIX.

```
cn: msSFU-30-Mail-Aliases
ldapDisplayName: msSFU30MailAliases
governsId: 1.2.840.113556.1.6.18.2.211
objectClassCategory: 1
rdnAttId: cn
subClassOf: top
mayContain: msSFU30Name, msSFU30NisDomain, msSFU30Aliases, nisMapName
possSuperiors: domainDNS, nisMap, container
schemaIdGuid: d6710785-86ff-44b7-85b5-f1f8689522ce
defaultSecurityDescriptor: D:(A;;RPWPCRCDCCLCLORCWOWSDDTSW;;;DA)
(A;;RPWPCRCDCCLCLORCWOWSDDTSW;;;SY)(A;;RPLCLORC;;;AU)
defaultHidingValue: TRUE
systemOnly: FALSE
defaultObjectCategory: CN=msSFU-30-Mail-Aliases,<SchemaNCDN>
```

Version-Specific Behavior: Implemented on Windows Server 2003 R2 operating system, Windows Server 2008 operating system, Windows Server 2008 R2 operating system, Windows Server 2012 operating system, and Windows Server 2012 R2 operating system.

2.169 Class msSFU30NetId

Stores the network ID.

```
cn: msSFU-30-Net-Id
ldapDisplayName: msSFU30NetId
governsId: 1.2.840.113556.1.6.18.2.212
objectClassCategory: 1
rdnAttId: cn
subClassOf: top
mayContain: msSFU30KeyValues, msSFU30Name, msSFU30NisDomain,
nisMapName
possSuperiors: domainDNS, nisMap, container
schemaIdGuid: e263192c-2a02-48df-9792-94f2328781a0
defaultSecurityDescriptor: D:(A;;RPWPCRCDCCLCLORCWOWSDDTSW;;;DA)
(A;;RPWPCRCDCCLCLORCWOWSDDTSW;;;SY)(A;;RPLCLORC;;;AU)
defaultHidingValue: TRUE
systemOnly: FALSE
defaultObjectCategory: CN=msSFU-30-Net-Id,<SchemaNCDN>
```


Version-Specific Behavior: Implemented on Windows Server 2003 R2 operating system, Windows Server 2008 operating system, Windows Server 2008 R2 operating system, Windows Server 2012 operating system, and Windows Server 2012 R2 operating system.

2.170 Class msSFU30NetworkUser

Represents network file data.

```
cn: msSFU-30-Network-User
ldapDisplayName: msSFU30NetworkUser
governsId: 1.2.840.113556.1.6.18.2.216
objectClassCategory: 1
rdnAttId: cn
subClassOf: top
mayContain: msSFU30KeyValues, msSFU30Name, msSFU30NisDomain,
  nisMapName
possSuperiors: domainDNS, nisMap, container
schemaIdGuid: e15334a3-0bf0-4427-b672-11f5d84acc92
defaultSecurityDescriptor: D: (A;;RPWPCRCDCCLCLORCWOWSDDTSW;;;DA)
  (A;;RPWPCRCDCCLCLORCWOWSDDTSW;;;SY) (A;;RPLCLORC;;;AU)
defaultHidingValue: TRUE
systemOnly: FALSE
defaultObjectCategory: CN=msSFU-30-Network-User,<SchemaNCDN>
```

Version-Specific Behavior: Implemented on Windows Server 2003 R2 operating system, Windows Server 2008 operating system, Windows Server 2008 R2 operating system, Windows Server 2012 operating system, and Windows Server 2012 R2 operating system.

2.171 Class msSFU30NISMapConfig

Represents an internal data structure that is used by the server for NIS.

```
cn: msSFU-30-NIS-Map-Config
ldapDisplayName: msSFU30NISMapConfig
governsId: 1.2.840.113556.1.6.18.2.217
objectClassCategory: 1
rdnAttId: cn
subClassOf: top
mayContain: msSFU30KeyAttributes, msSFU30FieldSeparator,
  msSFU30NSMAPFieldPosition, msSFU30IntraFieldSeparator,
  msSFU30SearchAttributes, msSFU30ResultAttributes, msSFU30MapFilter
possSuperiors: container
schemaIdGuid: faf733d0-f8eb-4dcf-8d75-f1753af6a50b
defaultSecurityDescriptor: D: (A;;RPWPCRCDCCLCLORCWOWSDDTSW;;;DA)
  (A;;RPWPCRCDCCLCLORCWOWSDDTSW;;;SY) (A;;RPLCLORC;;;AU)
defaultHidingValue: TRUE
systemOnly: FALSE
defaultObjectCategory: CN=msSFU-30-NIS-Map-Config,<SchemaNCDN>
```

Version-Specific Behavior: Implemented on Windows Server 2003 R2 operating system, Windows Server 2008 operating system, Windows Server 2008 R2 operating system, Windows Server 2012 operating system, and Windows Server 2012 R2 operating system.

2.172 Class msSPP-ActivationObject

An activation object used in Active Directory Domain Services-based activation.

```
cn: ms-SPP-Activation-Object
ldapDisplayName: msSPP-ActivationObject
governsId: 1.2.840.113556.1.5.267
objectClassCategory: 1
rdnAttId: cn
subClassOf: top
systemMustContain: msSPP-KMSIds, msSPP-CSVLKSkuid,
  msSPP-CSVLKPartialProductKey, msSPP-CSVLKPid
systemMayContain: msSPP-IssuanceLicense, msSPP-ConfigLicense,
  msSPP-PhoneLicense, msSPP-OnlineLicense, msSPP-ConfirmationId,
  msSPP-InstallationId
systemPossSuperiors: msSPP-ActivationObjectsContainer
schemaIdGuid: 51a0e68c-0dc5-43ca-935d-c1c911bf2ee5
defaultSecurityDescriptor: O:BAG:BAD: (A;;RPWPCRCDCCLCLORCWOWSDDTSW;;;DA)
  (A;;RPLCLORC;;;AU)
defaultHidingValue: TRUE
systemOnly: FALSE
defaultObjectCategory: CN=ms-SPP-Activation-Object,<SchemaNCDN>
systemFlags: FLAG_SCHEMA_BASE_OBJECT
```

Version-Specific Behavior: Implemented on Windows Server 2012 operating system and Windows Server 2012 R2 operating system.

2.173 Class msSPP-ActivationObjectsContainer

A container for activation objects used by Active Directory Domain Services-based activation.

```
cn: ms-SPP-Activation-Objects-Container
ldapDisplayName: msSPP-ActivationObjectsContainer
governsId: 1.2.840.113556.1.5.266
objectClassCategory: 1
rdnAttId: cn
subClassOf: top
systemPossSuperiors: container
schemaIdGuid: b72f862b-bb25-4d5d-aa51-62c59bdf90ae
defaultSecurityDescriptor: O:BAG:BAD: (A;;RPWPCRCDCCLCLORCWOWSDDTSW;;;DA)
  (A;;RPLCLORC;;;AU)
defaultHidingValue: TRUE
systemOnly: FALSE
defaultObjectCategory: CN=ms-SPP-Activation-Objects-Container,<SchemaNCDN>
systemFlags: FLAG_SCHEMA_BASE_OBJECT
```

Version-Specific Behavior: Implemented on Windows Server 2012 operating system and Windows Server 2012 R2 operating system.

2.174 Class msTAPI-RtConference

Publishes a real-time Telephony API (TAPI) multicast conference.

```
cn: ms-TAPI-Rt-Conference
ldapDisplayName: msTAPI-RtConference
```

```

governsId: 1.2.840.113556.1.5.221
objectClassCategory: 1
rdnAttId: msTAPI-uid
subClassOf: top
systemMustContain: msTAPI-uid
systemMayContain: msTAPI-ConferenceBlob, msTAPI-ProtocolId
systemPossSuperiors: organizationalUnit
schemaIdGuid: ca7b9735-4b2a-4e49-89c3-99025334dc94
defaultSecurityDescriptor: D: (A;;RPWPCRCDCCLCLOCRCWOWSDDTSW;;;DA)
(A;;RPWPCRCDCCLCLOCRCWOWSDDTSW;;;SY) (A;;RPLCLORC;;;AU)
defaultHidingValue: TRUE
systemOnly: FALSE
defaultObjectCategory: CN=ms-TAPI-Rt-Conference,<SchemaNCDN>
systemFlags: FLAG_SCHEMA_BASE_OBJECT

```

Version-Specific Behavior: Implemented on Windows Server 2003 operating system, Windows Server 2003 R2 operating system, Windows Server 2008 operating system, Windows Server 2008 R2 operating system, Windows Server 2012 operating system, and Windows Server 2012 R2 operating system.

2.175 Class msTAPI-RtPerson

Maps a user to the IP address of the machine that the user is logged on to for use by TAPI multicast conferences.

```

cn: ms-TAPI-Rt-Person
ldapDisplayName: msTAPI-RtPerson
governsId: 1.2.840.113556.1.5.222
objectClassCategory: 1
rdnAttId: cn
subClassOf: top
systemMayContain: msTAPI-uid, msTAPI-IpAddress
systemPossSuperiors: organization, organizationalUnit
schemaIdGuid: 53ealcb5-b704-4df9-818f-5cb4ec86cac1
defaultSecurityDescriptor: D: (A;;RPWPCRCDCCLCLOCRCWOWSDDTSW;;;DA)
(A;;RPWPCRCDCCLCLOCRCWOWSDDTSW;;;SY) (A;;RPLCLORC;;;AU)
defaultHidingValue: TRUE
systemOnly: FALSE
defaultObjectCategory: CN=ms-TAPI-Rt-Person,<SchemaNCDN>
systemFlags: FLAG_SCHEMA_BASE_OBJECT

```

Version-Specific Behavior: Implemented on Windows Server 2003 operating system, Windows Server 2003 R2 operating system, Windows Server 2008 operating system, Windows Server 2008 R2 operating system, Windows Server 2012 operating system, and Windows Server 2012 R2 operating system.

2.176 Class msTPM-InformationObject

This class contains recovery information for a Trusted Platform Module (TPM) device.

```

cn: ms-TPM-Information-Object
ldapDisplayName: msTPM-InformationObject
governsId: 1.2.840.113556.1.5.275
objectClassCategory: 1
rdnAttId: cn

```

```

subClassOf: top
systemMustContain: msTPM-OwnerInformation
systemMayContain: msTPM-OwnerInformationTemp, msTPM-SrkPubThumbprint
systemPossSuperiors: msTPM-InformationObjectsContainer
schemaIdGuid: 85045b6a-47a6-4243-a7cc-6890701f662c
defaultSecurityDescriptor: D: (A;;RPWPCRCDCCLORCWOWSDSDTWS;;;DA)
(A;;RPWPCRCDCCLORCWOWSDSDTWS;;;SY) (A;;RPLO;;;DC) (A;;WP;;;CO)
defaultHidingValue: TRUE
systemOnly: FALSE
defaultObjectCategory: CN=ms-TPM-Information-Object,<SchemaNCDN>
systemFlags: FLAG_SCHEMA_BASE_OBJECT

```

Version-Specific Behavior: Implemented on Windows Server 2012 operating system and Windows Server 2012 R2 operating system.

2.177 Class msTPM-InformationObjectsContainer

A container for Trusted Platform Module (TPM) objects.

```

cn: ms-TPM-Information-Objects-Container
ldapDisplayName: msTPM-InformationObjectsContainer
governsId: 1.2.840.113556.1.5.276
objectClassCategory: 1
rdnAttId: cn
subClassOf: top
systemMustContain: cn
systemPossSuperiors: domainDNS, domain
schemaIdGuid: e027a8bd-6456-45de-90a3-38593877ee74
defaultSecurityDescriptor: D: (A;;RPWPCRCDCCLORCWOWSDSDTWS;;;DA)
(A;;RPWPCRCDCCLORCWOWSDSDTWS;;;SY) (A;;LOLCCCRP;;;DC)
defaultHidingValue: TRUE
systemOnly: FALSE
defaultObjectCategory: CN=ms-TPM-Information-Objects-Container,<SchemaNCDN>
systemFlags: FLAG_SCHEMA_BASE_OBJECT

```

Version-Specific Behavior: Implemented on Windows Server 2012 operating system and Windows Server 2012 R2 operating system.

2.178 Class msWMI-IntRangeParam

An object for a signed integer range parameter.

```

cn: ms-WMI-IntRangeParam
ldapDisplayName: msWMI-IntRangeParam
governsId: 1.2.840.113556.1.5.205
objectClassCategory: 1
rdnAttId: cn
subClassOf: msWMI-RangeParam
systemMustContain: msWMI-IntDefault
systemMayContain: msWMI-IntMax, msWMI-IntMin
systemPossSuperiors: msWMI-MergeablePolicyTemplate
schemaIdGuid: 50ca5d7d-5c8b-4ef3-b9df-5b66d491e526
defaultSecurityDescriptor: D: (A;;RPWPCRCDCCLORCWOWSDSDTWS;;;DA)
(A;;RPWPCRCDCCLORCWOWSDSDTWS;;;SY) (A;;RPLCLORC;;;AU)
defaultHidingValue: TRUE

```

```
systemOnly: FALSE
defaultObjectCategory: CN=ms-WMI-IntRangeParam,<SchemaNCDN>
systemFlags: FLAG_SCHEMA_BASE_OBJECT
```

Version-Specific Behavior: Implemented on Windows Server 2003 operating system, Windows Server 2003 R2 operating system, Windows Server 2008 operating system, Windows Server 2008 R2 operating system, Windows Server 2012 operating system, and Windows Server 2012 R2 operating system.

2.179 Class msWMI-IntSetParam

An object for a signed integer set parameter.

```
cn: ms-WMI-IntSetParam
ldapDisplayName: msWMI-IntSetParam
governsId: 1.2.840.113556.1.5.206
objectClassCategory: 1
rdnAttId: cn
subClassOf: msWMI-RangeParam
systemMustContain: msWMI-IntDefault
systemMayContain: msWMI-IntValidValues
systemPossSuperiors: msWMI-MergeablePolicyTemplate
schemaIdGuid: 292f0d9a-cf76-42b0-841f-b650f331df62
defaultSecurityDescriptor: D: (A;;;RPWPCRCDCCLCLOCRCWOWSDSDTWSW;;;DA)
(A;;;RPWPCRCDCCLCLOCRCWOWSDSDTWSW;;;SY) (A;;;RPCDCCLCLOCLODTRC;;;AU)
defaultHidingValue: TRUE
systemOnly: FALSE
defaultObjectCategory: CN=ms-WMI-IntSetParam,<SchemaNCDN>
systemFlags: FLAG_SCHEMA_BASE_OBJECT
```

Version-Specific Behavior: Implemented on Windows Server 2003 operating system, Windows Server 2003 R2 operating system, Windows Server 2008 operating system, Windows Server 2008 R2 operating system, Windows Server 2012 operating system, and Windows Server 2012 R2 operating system.

2.180 Class msWMI-MergeablePolicyTemplate

Provides a policy template that can be merged with other templates.

```
cn: ms-WMI-MergeablePolicyTemplate
ldapDisplayName: msWMI-MergeablePolicyTemplate
governsId: 1.2.840.113556.1.5.202
objectClassCategory: 1
rdnAttId: cn
subClassOf: msWMI-PolicyTemplate
systemPossSuperiors: container
schemaIdGuid: 07502414-fdca-4851-b04a-13645b11d226
defaultSecurityDescriptor: D: (A;;;RPWPCRCDCCLCLOCRCWOWSDSDTWSW;;;DA)
(A;;;RPWPCRCDCCLCLOCRCWOWSDSDTWSW;;;SY) (A;;;RPCDCCLCLOCLODTRC;;;AU)
defaultHidingValue: TRUE
systemOnly: FALSE
defaultObjectCategory: CN=ms-WMI-MergeablePolicyTemplate,<SchemaNCDN>
systemFlags: FLAG_SCHEMA_BASE_OBJECT
```

Version-Specific Behavior: Implemented on Windows Server 2003 operating system, Windows Server 2003 R2 operating system, Windows Server 2008 operating system, Windows Server 2008 R2 operating system, Windows Server 2012 operating system, and Windows Server 2012 R2 operating system.

2.181 Class msWMI-ObjectEncoding

Holds encoding data for a Windows Management Instrumentation (WMI) class or instance object and also holds other information about the object.

```
cn: ms-WMI-ObjectEncoding
ldapDisplayName: msWMI-ObjectEncoding
governsId: 1.2.840.113556.1.5.217
objectClassCategory: 1
rdnAttId: cn
subClassOf: top
systemMustContain: msWMI-Class, msWMI-ScopeGuid, msWMI-Parm1,
msWMI-Parm2, msWMI-Parm3, msWMI-Parm4, msWMI-Genus, msWMI-intFlags1,
msWMI-intFlags2, msWMI-intFlags3, msWMI-intFlags4, msWMI-ID,
msWMI-TargetObject
systemPossSuperiors: container
schemaIdGuid: 55dd81c9-c312-41f9-a84d-c6adbdf1e8e1
defaultSecurityDescriptor: D: (A;;RPWPCRCDCCLCLOCRCWOWSDDTSW;;;DA)
(A;;RPWPCRCDCCLCLOCRCWOWSDDTSW;;;SY) (A;;RPLCLORC;;;AU)
defaultHidingValue: TRUE
systemOnly: FALSE
defaultObjectCategory: CN=ms-WMI-ObjectEncoding,<SchemaNCDN>
systemFlags: FLAG_SCHEMA_BASE_OBJECT
```

Version-Specific Behavior: Implemented on Windows Server 2003 operating system, Windows Server 2003 R2 operating system, Windows Server 2008 operating system, Windows Server 2008 R2 operating system, Windows Server 2012 operating system, and Windows Server 2012 R2 operating system.

2.182 Class msWMI-PolicyTemplate

Provides a template for creating a class instance in the target namespace.

```
cn: ms-WMI-PolicyTemplate
ldapDisplayName: msWMI-PolicyTemplate
governsId: 1.2.840.113556.1.5.200
objectClassCategory: 1
rdnAttId: cn
subClassOf: top
systemMustContain: msWMI-NormalizedClass, msWMI-TargetPath,
msWMI-TargetClass, msWMI-TargetNameSpace, msWMI-Name, msWMI-ID
systemMayContain: msWMI-TargetType, msWMI-SourceOrganization,
msWMI-Parm4, msWMI-Parm3, msWMI-Parm2, msWMI-Parm1, msWMI-intFlags4,
msWMI-intFlags3, msWMI-intFlags2, msWMI-intFlags1,
msWMI-CreationDate, msWMI-ChangeDate, msWMI-Author
systemPossSuperiors: container
schemaIdGuid: e2bc80f1-244a-4d59-acc6-ca5c4f82e6e1
defaultSecurityDescriptor: D: (A;;RPLCLORC;;;AU)
(A;;RPWPCRLCLOCDCRCWDWOSW;;;DA) (A;;CC;;;PA)
(A;;RPWPCRLCLOCDCRCWDWOSDDTSW;;;SY)
defaultHidingValue: TRUE
```

```
systemOnly: FALSE
defaultObjectCategory: CN=ms-WMI-PolicyTemplate,<SchemaNCDN>
systemFlags: FLAG_SCHEMA_BASE_OBJECT
```

Version-Specific Behavior: Implemented on Windows Server 2003 operating system, Windows Server 2003 R2 operating system, Windows Server 2008 operating system, Windows Server 2008 R2 operating system, Windows Server 2012 operating system, and Windows Server 2012 R2 operating system.

2.183 Class msWMI-PolicyType

Communicates schema for WMI policy objects.

```
cn: ms-WMI-PolicyType
ldapDisplayName: msWMI-PolicyType
governsId: 1.2.840.113556.1.5.211
objectClassCategory: 1
rdnAttId: cn
subClassOf: top
systemMustContain: msWMI-TargetObject, msWMI-ID
systemMayContain: msWMI-SourceOrganization, msWMI-Parm4,
  msWMI-Parm3, msWMI-Parm2, msWMI-Parm1, msWMI-intFlags4,
  msWMI-intFlags3, msWMI-intFlags2, msWMI-intFlags1,
  msWMI-CreationDate, msWMI-ChangeDate, msWMI-Author
systemPossSuperiors: container
schemaIdGuid: 595b2613-4109-4e77-9013-a3bb4ef277c7
defaultSecurityDescriptor: D:(A;;RPLCLORC;;;AU)
  (A;;RPWPCRLCLOCCDCRCWDWOSW;;;DA)(A;;CC;;;PA)
  (A;;RPWPCRLCLOCCDCRCWDWOSDDTSW;;;SY)
defaultHidingValue: TRUE
systemOnly: FALSE
defaultObjectCategory: CN=ms-WMI-PolicyType,<SchemaNCDN>
systemFlags: FLAG_SCHEMA_BASE_OBJECT
```

Version-Specific Behavior: Implemented on Windows Server 2003 operating system, Windows Server 2003 R2 operating system, Windows Server 2008 operating system, Windows Server 2008 R2 operating system, Windows Server 2012 operating system, and Windows Server 2012 R2 operating system.

2.184 Class msWMI-RangeParam

The range parameter class that is the basis of the [msWMI-PolicyTemplate](#) class. This class describes one target property that can be merged. Each subclass of this class implements a specific type. This class implements a merge method to support merging and implements a resolve method to generate the final target property.

```
cn: ms-WMI-RangeParam
ldapDisplayName: msWMI-RangeParam
governsId: 1.2.840.113556.1.5.203
objectClassCategory: 1
rdnAttId: cn
subClassOf: top
systemMustContain: msWMI-TargetType, msWMI-TargetClass,
  msWMI-PropertyName
systemPossSuperiors: msWMI-MergeablePolicyTemplate
```

```
schemaIdGuid: 45fb5a57-5018-4d0f-9056-997c8c9122d9
defaultSecurityDescriptor: D: (A;;RPWPCRCDCCLCLORCWOWDSDDTSW;;;DA)
(A;;RPWPCRCDCCLCLORCWOWDSDDTSW;;;SY) (A;;RPCDCCLCLODTRC;;;AU)
defaultHidingValue: TRUE
systemOnly: FALSE
defaultObjectCategory: CN=ms-WMI-RangeParam,<SchemaNCDN>
systemFlags: FLAG_SCHEMA_BASE_OBJECT
```

Version-Specific Behavior: Implemented on Windows Server 2003 operating system, Windows Server 2003 R2 operating system, Windows Server 2008 operating system, Windows Server 2008 R2 operating system, Windows Server 2012 operating system, and Windows Server 2012 R2 operating system.

2.185 Class msWMI-RealRangeParam

An object for a real number range parameter.

```
cn: ms-WMI-RealRangeParam
ldapDisplayName: msWMI-RealRangeParam
governsId: 1.2.840.113556.1.5.209
objectClassCategory: 1
rdnAttId: cn
subClassOf: msWMI-RangeParam
systemMustContain: msWMI-Int8Default
systemMayContain: msWMI-Int8Max, msWMI-Int8Min
systemPossSuperiors: msWMI-MergeablePolicyTemplate
schemaIdGuid: 6afe8fe2-70bc-4cce-b166-a96f7359c514
defaultSecurityDescriptor: D: (A;;RPWPCRCDCCLCLORCWOWDSDDTSW;;;DA)
(A;;RPWPCRCDCCLCLORCWOWDSDDTSW;;;SY) (A;;RPLCLORC;;;AU)
defaultHidingValue: TRUE
systemOnly: FALSE
defaultObjectCategory: CN=ms-WMI-RealRangeParam,<SchemaNCDN>
systemFlags: FLAG_SCHEMA_BASE_OBJECT
```

Version-Specific Behavior: Implemented on Windows Server 2003 operating system, Windows Server 2003 R2 operating system, Windows Server 2008 operating system, Windows Server 2008 R2 operating system, Windows Server 2012 operating system, and Windows Server 2012 R2 operating system.

2.186 Class msWMI-Rule

Defines a single rule in a scope of management (SOM).

```
cn: ms-WMI-Rule
ldapDisplayName: msWMI-Rule
governsId: 1.2.840.113556.1.5.214
objectClassCategory: 1
rdnAttId: cn
subClassOf: top
systemMustContain: msWMI-QueryLanguage, msWMI-TargetNameSpace,
msWMI-Query
systemPossSuperiors: msWMI-Som, container
schemaIdGuid: 3c7e6f83-dd0e-481b-a0c2-74cd96ef2a66
defaultSecurityDescriptor: D: (A;;RPWPCRCDCCLCLORCWOWDSDDTSW;;;DA)
(A;;RPWPCRCDCCLCLORCWOWDSDDTSW;;;SY) (A;;RPLCLORC;;;AU)
```



```
defaultHidingValue: TRUE
systemOnly: FALSE
defaultObjectCategory: CN=ms-WMI-Rule,<SchemaNCDN>
systemFlags: FLAG_SCHEMA_BASE_OBJECT
```

Version-Specific Behavior: Implemented on Windows Server 2003 operating system, Windows Server 2003 R2 operating system, Windows Server 2008 operating system, Windows Server 2008 R2 operating system, Windows Server 2012 operating system, and Windows Server 2012 R2 operating system.

2.187 Class msWMI-ShadowObject

Holds a WMI-compiled object instance.

```
cn: ms-WMI-ShadowObject
ldapDisplayName: msWMI-ShadowObject
governsId: 1.2.840.113556.1.5.212
objectClassCategory: 1
rdnAttId: cn
subClassOf: top
systemMustContain: msWMI-TargetObject
systemPossSuperiors: msWMI-PolicyType
schemaIdGuid: f1e44bdf-8dd3-4235-9c86-f91f31f5b569
defaultSecurityDescriptor: D: (A;;;RPWPCRCCDCLCLORCWOWDSDDTSW;;;DA)
(A;;;RPWPCRCCDCLCLORCWOWDSDDTSW;;;SY) (A;;;RPLCLORC;;;AU)
defaultHidingValue: TRUE
systemOnly: FALSE
defaultObjectCategory: CN=ms-WMI-ShadowObject,<SchemaNCDN>
systemFlags: FLAG_SCHEMA_BASE_OBJECT
```

Version-Specific Behavior: Implemented on Windows Server 2003 operating system, Windows Server 2003 R2 operating system, Windows Server 2008 operating system, Windows Server 2008 R2 operating system, Windows Server 2012 operating system, and Windows Server 2012 R2 operating system.

2.188 Class msWMI-SimplePolicyTemplate

Provides a type of template that cannot be merged. This class is used when the target object is not intended to be combined; that is, merged.

```
cn: ms-WMI-SimplePolicyTemplate
ldapDisplayName: msWMI-SimplePolicyTemplate
governsId: 1.2.840.113556.1.5.201
objectClassCategory: 1
rdnAttId: cn
subClassOf: msWMI-PolicyTemplate
systemMustContain: msWMI-TargetObject
systemPossSuperiors: container
schemaIdGuid: 6cc8b2b5-12df-44f6-8307-e74f5cdee369
defaultSecurityDescriptor: D: (A;;;RPWPCRCCDCLCLORCWOWDSDDTSW;;;DA)
(A;;;RPWPCRCCDCLCLORCWOWDSDDTSW;;;SY) (A;;;RPCDCLCLODTRC;;;AU)
defaultHidingValue: TRUE
systemOnly: FALSE
defaultObjectCategory: CN=ms-WMI-SimplePolicyTemplate,<SchemaNCDN>
```

```
systemFlags: FLAG_SCHEMA_BASE_OBJECT
```

Version-Specific Behavior: Implemented on Windows Server 2003 operating system, Windows Server 2003 R2 operating system, Windows Server 2008 operating system, Windows Server 2008 R2 operating system, Windows Server 2012 operating system, and Windows Server 2012 R2 operating system.

2.189 Class msWMI-Som

Refines the SOM for a GPO. Adds a list of rules, expressed as WMI Query Language (WQL) queries, that are executed on the target machine. All queries must return results in order for this SOM to be applicable to the target.

```
cn: ms-WMI-Som
ldapDisplayName: msWMI-Som
governsId: 1.2.840.113556.1.5.213
objectClassCategory: 1
rdnAttId: cn
subClassOf: top
systemMustContain: msWMI-Name, msWMI-ID
systemMayContain: msWMI-SourceOrganization, msWMI-Parm4, msWMI-Parm3,
msWMI-Parm2, msWMI-Parm1, msWMI-intFlags4, msWMI-intFlags3,
msWMI-intFlags2, msWMI-intFlags1, msWMI-CreationDate,
msWMI-ChangeDate, msWMI-Author
systemPossSuperiors: container
schemaIdGuid: ab857078-0142-4406-945b-34c9b6b13372
defaultSecurityDescriptor: D: (A;;RPLCLORC;;;AU)
(A;;RPWPCRLCLOCCDCRCWDWOSW;;;DA) (A;;CC;;;PA)
(A;;RPWPCRLCLOCCDCRCWDWOSDDTSW;;;SY)
defaultHidingValue: TRUE
systemOnly: FALSE
defaultObjectCategory: CN=ms-WMI-Som,<SchemaNCDN>
systemFlags: FLAG_SCHEMA_BASE_OBJECT
```

Version-Specific Behavior: Implemented on Windows Server 2003 operating system, Windows Server 2003 R2 operating system, Windows Server 2008 operating system, Windows Server 2008 R2 operating system, Windows Server 2012 operating system, and Windows Server 2012 R2 operating system.

2.190 Class msWMI-StringSetParam

An object for a string set parameter.

```
cn: ms-WMI-StringSetParam
ldapDisplayName: msWMI-StringSetParam
governsId: 1.2.840.113556.1.5.210
objectClassCategory: 1
rdnAttId: cn
subClassOf: msWMI-RangeParam
systemMustContain: msWMI-StringDefault
systemMayContain: msWMI-StringValidValues
systemPossSuperiors: msWMI-MergeablePolicyTemplate
schemaIdGuid: 0bc579a2-1da7-4cea-b699-807f3b9d63a4
defaultSecurityDescriptor: D: (A;;RPWPCRCCLCLOCCDCRCWDWOSDDTSW;;;DA)
(A;;RPWPCRCCLCLOCCDCRCWDWOSDDTSW;;;SY) (A;;RPCCLCLODTRC;;;AU)
```

```
defaultHidingValue: TRUE
systemOnly: FALSE
defaultObjectCategory: CN=ms-WMI-StringSetParam,<SchemaNCDN>
systemFlags: FLAG_SCHEMA_BASE_OBJECT
```

Version-Specific Behavior: Implemented on Windows Server 2003 operating system, Windows Server 2003 R2 operating system, Windows Server 2008 operating system, Windows Server 2008 R2 operating system, Windows Server 2012 operating system, and Windows Server 2012 R2 operating system.

2.191 Class msWMI-UintRangeParam

An object for an unsigned integer range parameter.

```
cn: ms-WMI-UintRangeParam
ldapDisplayName: msWMI-UintRangeParam
governsId: 1.2.840.113556.1.5.207
objectClassCategory: 1
rdnAttId: cn
subClassOf: msWMI-RangeParam
systemMustContain: msWMI-IntDefault
systemMayContain: msWMI-IntMax, msWMI-IntMin
systemPossSuperiors: msWMI-MergeablePolicyTemplate
schemaIdGuid: d9a799b2-cef3-48b3-b5ad-fb85f8dd3214
defaultSecurityDescriptor: D:(A;;RPWPCRCDCCLCLOCRCWOWSDDTSW;;;DA)
(A;;RPWPCRCDCCLCLOCRCWOWSDDTSW;;;SY)(A;;RPLCLOCRC;;;AU)
defaultHidingValue: TRUE
systemOnly: FALSE
defaultObjectCategory: CN=ms-WMI-UintRangeParam,<SchemaNCDN>
systemFlags: FLAG_SCHEMA_BASE_OBJECT
```

Version-Specific Behavior: Implemented on Windows Server 2003 operating system, Windows Server 2003 R2 operating system, Windows Server 2008 operating system, Windows Server 2008 R2 operating system, Windows Server 2012 operating system, and Windows Server 2012 R2 operating system.

2.192 Class msWMI-UintSetParam

An object for an unsigned integer set parameter.

```
cn: ms-WMI-UintSetParam
ldapDisplayName: msWMI-UintSetParam
governsId: 1.2.840.113556.1.5.208
objectClassCategory: 1
rdnAttId: cn
subClassOf: msWMI-RangeParam
systemMustContain: msWMI-IntDefault
systemMayContain: msWMI-IntValidValues
systemPossSuperiors: msWMI-MergeablePolicyTemplate
schemaIdGuid: 8f4beb31-4e19-46f5-932e-5fa03c339b1d
defaultSecurityDescriptor: D:(A;;RPWPCRCDCCLCLOCRCWOWSDDTSW;;;DA)
(A;;RPWPCRCDCCLCLOCRCWOWSDDTSW;;;SY)(A;;RPCDCCLCLOCRC;;;AU)
defaultHidingValue: TRUE
systemOnly: FALSE
defaultObjectCategory: CN=ms-WMI-UintSetParam,<SchemaNCDN>
```

```
systemFlags: FLAG_SCHEMA_BASE_OBJECT
```

Version-Specific Behavior: Implemented on Windows Server 2003 operating system, Windows Server 2003 R2 operating system, Windows Server 2008 operating system, Windows Server 2008 R2 operating system, Windows Server 2012 operating system, and Windows Server 2012 R2 operating system.

2.193 Class msWMI-UnknownRangeParam

Supports parameter types that are unknown. They are transported as compiled WMI objects.

```
cn: ms-WMI-UnknownRangeParam
ldapDisplayName: msWMI-UnknownRangeParam
governsId: 1.2.840.113556.1.5.204
objectClassCategory: 1
rdnAttId: cn
subClassOf: msWMI-RangeParam
systemMustContain: msWMI-TargetObject, msWMI-NormalizedClass
systemPossSuperiors: msWMI-MergeablePolicyTemplate
schemaIdGuid: b82ac26b-c6db-4098-92c6-49c18a3336e1
defaultSecurityDescriptor: D: (A;;RPWPCRCDCCLORCWOWSDDTSW;;;DA)
(A;;RPWPCRCDCCLORCWOWSDDTSW;;;SY) (A;;RPLCLORC;;;AU)
defaultHidingValue: TRUE
systemOnly: FALSE
defaultObjectCategory: CN=ms-WMI-UnknownRangeParam,<SchemaNCDN>
systemFlags: FLAG_SCHEMA_BASE_OBJECT
```

Version-Specific Behavior: Implemented on Windows Server 2003 operating system, Windows Server 2003 R2 operating system, Windows Server 2008 operating system, Windows Server 2008 R2 operating system, Windows Server 2012 operating system, and Windows Server 2012 R2 operating system.

2.194 Class msWMI-WMIGPO

Ties the objects that express the WMI extensions to the Group Policy infrastructure. This value is written to Active Directory in the path pointed to by the corresponding Group Policy Object.

```
cn: ms-WMI-WMIGPO
ldapDisplayName: msWMI-WMIGPO
governsId: 1.2.840.113556.1.5.215
objectClassCategory: 1
rdnAttId: cn
subClassOf: top
systemMustContain: msWMI-TargetClass
systemMayContain: msWMI-Param4, msWMI-Param3, msWMI-Param2, msWMI-Param1,
msWMI-intFlags4, msWMI-intFlags3, msWMI-intFlags2, msWMI-intFlags1
systemPossSuperiors: container
schemaIdGuid: 05630000-3927-4ede-bf27-ca91f275c26f
defaultSecurityDescriptor: D: (A;;RPLCLORC;;;AU)
(A;;RPWPCRLCLOCCDCRCWDWOSW;;;DA) (A;;CC;;;PA)
(A;;RPWPCRLCLOCCDCRCWDWOSDDTSW;;;SY)
defaultHidingValue: TRUE
systemOnly: FALSE
defaultObjectCategory: CN=ms-WMI-WMIGPO,<SchemaNCDN>
```

systemFlags: FLAG_SCHEMA_BASE_OBJECT

Version-Specific Behavior: Implemented on Windows Server 2003 operating system, Windows Server 2003 R2 operating system, Windows Server 2008 operating system, Windows Server 2008 R2 operating system, Windows Server 2012 operating system, and Windows Server 2012 R2 operating system.

2.195 Class nisMap

A generic abstraction of a Network Information Service (NIS) map.

```
cn: NisMap
ldapDisplayName: nisMap
governsId: 1.3.6.1.1.1.2.9
objectClassCategory: 1
rdnAttId: cn
subClassOf: top
mustContain: cn, nisMapName
mayContain: description
possSuperiors: domainDNS, container, organizationalUnit
schemaIdGuid: 7672666c-02c1-4f33-9ecf-f649c1dd9b7c
defaultSecurityDescriptor: D: (A;;RPWPCRCDCCLCLORCWOWSDSDTSW;;;DA)
(A;;RPWPCRCDCCLCLORCWOWSDSDTSW;;;SY) (A;;RPLCLORC;;;AU)
defaultHidingValue: TRUE
systemOnly: FALSE
defaultObjectCategory: CN=NisMap,<SchemaNCDN>
```

Version-Specific Behavior: Implemented on Windows Server 2003 R2 operating system, Windows Server 2008 operating system, Windows Server 2008 R2 operating system, Windows Server 2012 operating system, and Windows Server 2012 R2 operating system.

2.196 Class nisNetgroup

An abstraction of a netgroup. This class may refer to other netgroups.

```
cn: NisNetgroup
ldapDisplayName: nisNetgroup
governsId: 1.3.6.1.1.1.2.8
objectClassCategory: 1
rdnAttId: cn
subClassOf: top
mustContain: cn
mayContain: description, memberNisNetgroup, nisNetgroupTriple,
msSFU30Name, msSFU30NisDomain, nisMapName,
msSFU30NetgroupHostAtDomain, msSFU30NetgroupUserAtDomain
possSuperiors: domainDNS, nisMap, container, organizationalUnit
schemaIdGuid: 72efbf84-6e7b-4a5c-a8db-8a75a7cad254
defaultSecurityDescriptor: D: (A;;RPWPCRCDCCLCLORCWOWSDSDTSW;;;DA)
(A;;RPWPCRCDCCLCLORCWOWSDSDTSW;;;SY) (A;;RPLCLORC;;;AU)
defaultHidingValue: TRUE
systemOnly: FALSE
defaultObjectCategory: CN=NisNetgroup,<SchemaNCDN>
```

Version-Specific Behavior: Implemented on Windows Server 2003 R2 operating system, Windows Server 2008 operating system, Windows Server 2008 R2 operating system, Windows Server 2012 operating system, and Windows Server 2012 R2 operating system.

2.197 Class nisObject

An entry in an NIS map.

```
cn: NisObject
ldapDisplayName: nisObject
governsId: 1.3.6.1.1.1.2.10
objectClassCategory: 1
rdnAttId: cn
subClassOf: top
mustContain: cn, nisMapName, nisMapEntry
mayContain: description, msSFU30Name, msSFU30NisDomain
possSuperiors: domainDNS, nisMap, container, organizationalUnit
schemaIdGuid: 904f8a93-4954-4c5f-b1e1-53c097a31e13
defaultSecurityDescriptor: D: (A;;RPWPCRCDCCLCLORCWOWSDDTSW;;;DA)
(A;;RPWPCRCDCCLCLORCWOWSDDTSW;;;SY) (A;;RPLCLORC;;;AU)
defaultHidingValue: TRUE
systemOnly: FALSE
defaultObjectCategory: CN=NisObject,<SchemaNCDN>
```

Version-Specific Behavior: Implemented on Windows Server 2003 R2 operating system, Windows Server 2008 operating system, Windows Server 2008 R2 operating system, Windows Server 2012 operating system, and Windows Server 2012 R2 operating system.

2.198 Class nTDSConnection

A connection from a remote domain controller.

```
cn: NTDS-Connection
ldapDisplayName: nTDSConnection
governsId: 1.2.840.113556.1.5.71
objectClassCategory: 1
rdnAttId: cn
subClassOf: leaf
systemMustContain: options, fromServer, enabledConnection
systemMayContain: transportType, schedule, mS-DS-ReplicatesNCRReason,
generatedConnection
systemPossSuperiors: nTFRSMember, nTFRSReplicaSet, nTDSDSA
schemaIdGuid: 19195a60-6da0-11d0-afd3-00c04fd930c9
defaultSecurityDescriptor: D: (A;;RPWPCRCDCCLCLORCWOWSDDTSW;;;DA)
(A;;RPWPCRCDCCLCLORCWOWSDDTSW;;;SY) (A;;RPLCLORC;;;AU)
defaultHidingValue: TRUE
systemOnly: FALSE
defaultObjectCategory: CN=NTDS-Connection,<SchemaNCDN>
systemFlags: FLAG_SCHEMA_BASE_OBJECT
```

Version-Specific Behavior: Implemented on Windows 2000 Server operating system, Windows Server 2003 operating system, Windows Server 2003 R2 operating system, Windows Server 2008 operating system, Windows Server 2008 R2 operating system, Windows Server 2012 operating system, and Windows Server 2012 R2 operating system.

2.199 Class nTDSDSA

Represents the AD DS and Active Directory directory service agent (DSA) process on the server.

```
cn: NTDS-DSA
ldapDisplayName: nTDSDSA
governsId: 1.2.840.113556.1.5.7000.47
objectClassCategory: 1
rdnAttId: cn
subClassOf: applicationSettings
systemMayContain: msDS-EnabledFeature, msDS-IsUserCachableAtRocd, msDS-SiteName,
msDS-isRODC, msDS-isGC, msDS-RevealedUsers,
msDS-NeverRevealGroup, msDS-RevealOnDemandGroup,
msDS-hasFullReplicaNCs, serverReference,
msDS-RetiredReplNCSignatures, retiredReplDSASignatures,
queryPolicyObject, options, networkAddress, msDS-ReplicationEpoch,
msDS-HasInstantiatedNCs, msDS-hasMasterNCs, msDS-HasDomainNCs,
msDS-Behavior-Version, managedBy, lastBackupRestorationTime,
invocationId, hasPartialReplicaNCs, hasMasterNCs, frsRootPath,
dMDLocation
systemPossSuperiors: organization, server
schemaIdGuid: f0f8ffab-1191-11d0-a060-00aa006c33ed
defaultSecurityDescriptor: D: (A;;RPWPCRCDCCLCLORCWOWSDDTSW;;;DA)
(A;;RPWPCRCDCCLCLORCWOWSDDTSW;;;SY) (A;;RPLCLORC;;;AU)
defaultHidingValue: TRUE
systemOnly: TRUE
defaultObjectCategory: CN=NTDS-DSA,<SchemaNCDN>
systemFlags: FLAG_SCHEMA_BASE_OBJECT
```

Version-Specific Behavior: Implemented on Windows 2000 Server operating system, Windows Server 2003 operating system, Windows Server 2003 R2 operating system, Windows Server 2008 operating system, Windows Server 2008 R2 operating system, Windows Server 2012 operating system, and Windows Server 2012 R2 operating system.

2.200 Class nTDSARSAR

A subclass of the DSA, which is distinguished by its reduced privilege level.

```
cn: NTDS-DSA-RO
ldapDisplayName: nTDSARSAR
governsId: 1.2.840.113556.1.5.254
objectClassCategory: 1
rdnAttId: cn
subClassOf: nTDSDSA
systemPossSuperiors: server, organization
schemaIdGuid: 85d16ec1-0791-4bc8-8ab3-70980602ff8c
defaultSecurityDescriptor: D: (A;;RPWPCRCDCCLCLORCWOWSDDTSW;;;DA)
(A;;RPWPCRCDCCLCLORCWOWSDDTSW;;;SY) (A;;RPLCLORC;;;AU)
defaultHidingValue: TRUE
systemOnly: TRUE
defaultObjectCategory: CN=NTDS-DSA-RO,<SchemaNCDN>
systemFlags: FLAG_SCHEMA_BASE_OBJECT
```

Version-Specific Behavior: Implemented on Windows Server 2008 operating system, Windows Server 2008 R2 operating system, Windows Server 2012 operating system, and Windows Server 2012 R2 operating system.

2.201 Class nTDSservice

Used for an NTDS services object, which contains information about the configuration of the directory service forest. This object is kept in the CN=Directory Service,CN=Windows NT,CN=Services,CN=Configuration,... container.

```
cn: NTDS-Service
ldapDisplayName: nTDSservice
governsId: 1.2.840.113556.1.5.72
objectClassCategory: 1
rdnAttId: cn
subClassOf: top
systemMayContain: msDS-DeletedObjectLifetime, tombstoneLifetime,
  sPNMappings, replTopologyStayOfExecution, msDS-Other-Settings,
  garbageCollPeriod, dsHeuristics
systemPossSuperiors: container
schemaIdGuid: 19195a5f-6da0-11d0-afd3-00c04fd930c9
defaultSecurityDescriptor: D: (A;;RPWPCRCDCCLCLORCWOWSDDTSW;;;DA)
  (A;;RPWPCRCDCCLCLORCWOWSDDTSW;;;SY) (A;;RPLCLORC;;;AU)
defaultHidingValue: TRUE
systemOnly: FALSE
defaultObjectCategory: CN=NTDS-Service,<SchemaNCDN>
systemFlags: FLAG_SCHEMA_BASE_OBJECT
```

Version-Specific Behavior: Implemented on Windows 2000 Server operating system, Windows Server 2003 operating system, Windows Server 2003 R2 operating system, Windows Server 2008 operating system, Windows Server 2008 R2 operating system, Windows Server 2012 operating system, and Windows Server 2012 R2 operating system.

2.202 Class nTDSsiteSettings

A container that holds all AD DS and Active Directory site-specific settings.

```
cn: NTDS-Site-Settings
ldapDisplayName: nTDSsiteSettings
governsId: 1.2.840.113556.1.5.69
objectClassCategory: 1
rdnAttId: cn
subClassOf: applicationSiteSettings
systemMayContain: schedule, queryPolicyObject, options,
  msDS-Preferred-GC-Site, managedBy, interSiteTopologyRenew,
  interSiteTopologyGenerator, interSiteTopologyFailover
systemPossSuperiors: site
schemaIdGuid: 19195a5d-6da0-11d0-afd3-00c04fd930c9
defaultSecurityDescriptor: D: (A;;RPWPCRCDCCLCLORCWOWSDDTSW;;;DA)
  (A;;RPWPCRCDCCLCLORCWOWSDDTSW;;;SY) (A;;RPLCLORC;;;AU)
defaultHidingValue: TRUE
systemOnly: FALSE
defaultObjectCategory: CN=NTDS-Site-Settings,<SchemaNCDN>
systemFlags: FLAG_SCHEMA_BASE_OBJECT
```

Version-Specific Behavior: Implemented on Windows 2000 Server operating system, Windows Server 2003 operating system, Windows Server 2003 R2 operating system, Windows Server 2008 operating system, Windows Server 2008 R2 operating system, Windows Server 2012 operating system, and Windows Server 2012 R2 operating system.

2.203 Class nTFRSMember

Identifies a File Replication Service (FRS) replica set member.

```
cn: NTFRS-Member
ldapDisplayName: nTFRSMember
governsId: 1.2.840.113556.1.5.153
objectClassCategory: 1
rdnAttId: cn
subClassOf: top
systemMayContain: serverReference, fRSUpdateTimeout,
  fRSServiceCommand, fRSRootSecurity, fRSPartnerAuthLevel, fRSFlags,
  fRSExtensions, fRSControlOutboundBacklog, fRSControlInboundBacklog,
  fRSControlDataCreation, frsComputerReference
systemPossSuperiors: nTFRSReplicaSet
schemaIdGuid: 2a132586-9373-11d1-aebc-0000f80367c1
defaultSecurityDescriptor: D: (A;;RPLCLORC;;;AU)
  (A;;RPWPCLRLCLOCCDCRCWDWOSDDTSW;;;DA)
  (A;;RPWPCLRLCLOCCDCRCWDWOSDDTSW;;;CO)
  (A;;RPWPCLRLCLOCCDCRCWDWOSDDTSW;;;SY)
defaultHidingValue: TRUE
systemOnly: FALSE
defaultObjectCategory: CN=NTFRS-Member,<SchemaNCDN>
systemFlags: FLAG_SCHEMA_BASE_OBJECT
```

Version-Specific Behavior: Implemented on Windows 2000 Server operating system, Windows Server 2003 operating system, Windows Server 2003 R2 operating system, Windows Server 2008 operating system, Windows Server 2008 R2 operating system, Windows Server 2012 operating system, and Windows Server 2012 R2 operating system.

2.204 Class nTFRSReplicaSet

Defines the replica set for the FRS.

```
cn: NTFRS-Replica-Set
ldapDisplayName: nTFRSReplicaSet
governsId: 1.2.840.113556.1.5.102
objectClassCategory: 1
rdnAttId: cn
subClassOf: top
systemMayContain: schedule, msFRS-Topology-Pref, msFRS-Hub-Member,
  managedBy, fRSVersionGUID, fRSServiceCommand, fRSRootSecurity,
  fRSReplicaSetType, fRSReplicaSetGUID, fRSPrimaryMember,
  fRSPartnerAuthLevel, fRSLevelLimit, fRSFlags, fRSFileFilter,
  fRSExtensions, fRSDSPoll, fRSDirectoryFilter
systemPossSuperiors: nTFRSSettings
schemaIdGuid: 5245803a-ca6a-11d0-afff-0000f80367c1
defaultSecurityDescriptor: D: (A;;RPLCLORC;;;AU)
  (A;;RPWPCLRLCLOCCDCRCWDWOSDDTSW;;;DA)
  (A;;RPWPCLRLCLOCCDCRCWDWOSDDTSW;;;CO)
  (A;;RPWPCLRLCLOCCDCRCWDWOSDDTSW;;;SY)
  (OA;;CCDC;2a132586-9373-11d1-aebc-0000f80367c1;;ED)
defaultHidingValue: TRUE
systemOnly: FALSE
defaultObjectCategory: CN=NTFRS-Replica-Set,<SchemaNCDN>
systemFlags: FLAG_SCHEMA_BASE_OBJECT
```

Version-Specific Behavior: Implemented on Windows 2000 Server operating system, Windows Server 2003 operating system, Windows Server 2003 R2 operating system, Windows Server 2008 operating system, Windows Server 2008 R2 operating system, Windows Server 2012 operating system, and Windows Server 2012 R2 operating system.

2.205 Class nTFRSSettings

Identifies the specific settings for FRS.

```
cn: NTFRS-Settings
ldapDisplayName: nTFRSSettings
governsId: 1.2.840.113556.1.5.89
objectClassCategory: 1
rdnAttId: cn
subClassOf: applicationSettings
systemMayContain: managedBy, frSExtensions
systemPossSuperiors: nTFRSSettings, container, organizationalUnit,
  organization
schemaIdGuid: f780acc2-56f0-11d1-a9c6-0000f80367c1
defaultSecurityDescriptor: D: (A;;RPLCLORC;;;AU)
  (A;;RPWPCRLCLOCCDCRCWDWOSDDTSW;;;DA)
  (A;;RPWPCRLCLOCCDCRCWDWOSDDTSW;;;CO)
  (A;;RPWPCRLCLOCCDCRCWDWOSDDTSW;;;SY)
defaultHidingValue: TRUE
systemOnly: FALSE
defaultObjectCategory: CN=NTFRS-Settings,<SchemaNCDN>
systemFlags: FLAG_SCHEMA_BASE_OBJECT
```

Version-Specific Behavior: Implemented on Windows 2000 Server operating system, Windows Server 2003 operating system, Windows Server 2003 R2 operating system, Windows Server 2008 operating system, Windows Server 2008 R2 operating system, Windows Server 2012 operating system, and Windows Server 2012 R2 operating system.

2.206 Class nTFRSSubscriber

Identifies a subscriber to a replica set.

```
cn: NTFRS-Subscriber
ldapDisplayName: nTFRSSubscriber
governsId: 1.2.840.113556.1.5.155
objectClassCategory: 1
rdnAttId: cn
subClassOf: top
systemMustContain: fRSStagingPath, fRSRootPath
systemMayContain: schedule, fRSUpdateTimeout,
  fRSTimeLastConfigChange, fRSTimeLastCommand,
  fRSServiceCommandStatus, fRSServiceCommand, fRSMemberReference,
  fRSFlags, fRSFaultCondition, frSExtensions
systemPossSuperiors: nTFRSSubscriptions
schemaIdGuid: 2a132588-9373-11d1-aebc-0000f80367c1
defaultSecurityDescriptor: D: (A;;RPLCLORC;;;AU)
  (A;;RPWPCRCCLCLORCWOWDSDDTSW;;;DA)
  (A;;RPWPCRCCLCLORCWOWDSDDTSW;;;SY)
  (A;;RPWPCRCCLCLORCWOWDSDDTSW;;;CO)
defaultHidingValue: TRUE
systemOnly: FALSE
```

```
defaultObjectCategory: CN=NTFRS-Subscriber,<SchemaNC DN>
systemFlags: FLAG_SCHEMA_BASE_OBJECT
```

Version-Specific Behavior: Implemented on Windows 2000 Server operating system, Windows Server 2003 operating system, Windows Server 2003 R2 operating system, Windows Server 2008 operating system, Windows Server 2008 R2 operating system, Windows Server 2012 operating system, and Windows Server 2012 R2 operating system.

2.207 Class nTFRSSubscriptions

Holds a set of subscriptions to a replica set.

```
cn: NTFRS-Subscriptions
ldapDisplayName: nTFRSSubscriptions
governsId: 1.2.840.113556.1.5.154
objectClassCategory: 1
rdnAttId: cn
subClassOf: top
systemMayContain: fRSWorkingPath, fRSVersion, fRSExtensions
systemPossSuperiors: user, computer, nTFRSSubscriptions
schemaIdGuid: 2a132587-9373-11d1-aebc-0000f80367c1
defaultSecurityDescriptor: D: (A;;RPLCLORC;;;AU)
(A;;RPWPCRCDCCLCLORCWOWDSDDTSW;;;DA)
(A;;RPWPCRCDCCLCLORCWOWDSDDTSW;;;SY)
(A;;RPWPCRCDCCLCLORCWOWDSDDTSW;;;CO)
defaultHidingValue: TRUE
systemOnly: FALSE
defaultObjectCategory: CN=NTFRS-Subscriptions,<SchemaNC DN>
systemFlags: FLAG_SCHEMA_BASE_OBJECT
```

Version-Specific Behavior: Implemented on Windows 2000 Server operating system, Windows Server 2003 operating system, Windows Server 2003 R2 operating system, Windows Server 2008 operating system, Windows Server 2008 R2 operating system, Windows Server 2012 operating system, and Windows Server 2012 R2 operating system.

2.208 Class oncRpc

An abstraction of an Open Network Computing (ONC) remote procedure call (RPC) binding, as specified in [RFC1831](#).

```
cn: OncRpc
ldapDisplayName: oncRpc
governsId: 1.3.6.1.1.1.2.5
objectClassCategory: 1
rdnAttId: cn
subClassOf: top
mustContain: cn, oncRpcNumber
mayContain: description, msSFU30Name, msSFU30NisDomain, nisMapName,
msSFU30Aliases
possSuperiors: domainDNS, nisMap, container, organizationalUnit
schemaIdGuid: caddle5e-fe5c-4f3f-b5a9-70e994204303
defaultSecurityDescriptor: D: (A;;RPWPCRCDCCLCLORCWOWDSDDTSW;;;DA)
(A;;RPWPCRCDCCLCLORCWOWDSDDTSW;;;SY) (A;;RPLCLORC;;;AU)
defaultHidingValue: TRUE
systemOnly: FALSE
```

```
defaultObjectCategory: CN=OncRpc,<SchemaNCDN>
```

Version-Specific Behavior: Implemented on Windows Server 2003 R2 operating system, Windows Server 2008 operating system, Windows Server 2008 R2 operating system, Windows Server 2012 operating system, and Windows Server 2012 R2 operating system.

2.209 Class organization

Stores information about a company or organization.

```
cn: Organization
ldapDisplayName: organization
governsId: 2.5.6.4
objectClassCategory: 1
rdnAttId: o
subClassOf: top
systemMustContain: o
systemMayContain: x121Address, userPassword, telexNumber,
  teletexTerminalIdentifier, telephoneNumber, street, st, seeAlso,
  searchGuide, registeredAddress, preferredDeliveryMethod, postalCode,
  postalAddress, postOfficeBox, physicalDeliveryOfficeName, l,
  internationalISDNNumber, facsimileTelephoneNumber,
  destinationIndicator, businessCategory
systemPossSuperiors: locality, country, domainDNS
schemaIdGuid: bf967aa3-0de6-11d0-a285-00aa003049e2
defaultSecurityDescriptor: D: (A;;RPWPCRCDCCLCLORCWOWSDDTSW;;;DA)
  (A;;RPWPCRCDCCLCLORCWOWSDDTSW;;;SY) (A;;RPLCLORC;;;AU)
defaultHidingValue: FALSE
systemOnly: FALSE
defaultObjectCategory: CN=Organization,<SchemaNCDN>
systemFlags: FLAG_SCHEMA_BASE_OBJECT
```

Version-Specific Behavior: Implemented on Windows 2000 Server operating system, Windows Server 2003 operating system, Windows Server 2003 R2 operating system, Windows Server 2008 operating system, Windows Server 2008 R2 operating system, Windows Server 2012 operating system, and Windows Server 2012 R2 operating system.

2.210 Class organizationalPerson

Used for objects that contain organizational information about a user, such as the employee number, department, manager, title, office, or address.

```
cn: Organizational-Person
ldapDisplayName: organizationalPerson
governsId: 2.5.6.7
objectClassCategory: 0
rdnAttId: cn
subClassOf: person
mayContain: msDS-HABSEniorityIndex, msDS-PhoneticDisplayName,
  msDS-PhoneticCompanyName, msDS-PhoneticDepartment,
  msDS-PhoneticLastName, msDS-PhoneticFirstName, houseIdentifier,
  msExchHouseIdentifier, homePostalAddress
systemMayContain: x121Address, comment, title, co,
  primaryTelexNumber, telexNumber, teletexTerminalIdentifier, street,
  st, registeredAddress, preferredDeliveryMethod, postalCode,
```

```

postalAddress, postOfficeBox, thumbnailPhoto,
physicalDeliveryOfficeName, pager, otherPager, otherTelephone,
mobile, otherMobile, primaryInternationalISDNNumber, ipPhone,
otherIpPhone, otherHomePhone, homePhone,
otherFacsimileTelephoneNumber, personalTitle, middleName,
otherMailbox, ou, o, mhsORAddress, msDS-AllowedToDelegateTo,
manager, thumbnailLogo, l, internationalISDNNumber, initials,
givenName, generationQualifier, facsimileTelephoneNumber,
employeeID, mail, division, destinationIndicator, department, c,
countryCode, company, assistant, streetAddress,
msDS-AllowedToActOnBehalfOfOtherIdentity
systemPossSuperiors: organizationalUnit, organization, container
schemaIdGuid: bf967aa4-0de6-11d0-a285-00aa003049e2
defaultSecurityDescriptor: D: (A;;RPWPCRCCLCCLORCWOWSDSDTWSW;;;DA)
(A;;RPWPCRCCLCCLORCWOWSDSDTWSW;;;SY) (A;;RPLCLORC;;;AU)
defaultHidingValue: TRUE
systemOnly: FALSE
defaultObjectCategory: CN=Person,<SchemaNCDN>
systemFlags: FLAG_SCHEMA_BASE_OBJECT

```

Version-Specific Behavior: Implemented on Windows 2000 Server operating system, Windows Server 2003 operating system, Windows Server 2003 R2 operating system, Windows Server 2008 operating system, Windows Server 2008 R2 operating system, Windows Server 2012 operating system, and Windows Server 2012 R2 operating system.

2.211 Class organizationalRole

Used for objects that contain information that pertains to a position or role in an organization, such as a system administrator or manager. This class can also be used for a nonhuman identity in an organization.

```

cn: Organizational-Role
ldapDisplayName: organizationalRole
governsId: 2.5.6.8
objectClassCategory: 1
rdnAttId: cn
subClassOf: top
systemMustContain: cn
systemMayContain: x121Address, telexNumber,
teletexTerminalIdentifier, telephoneNumber, street, st, seeAlso,
roleOccupant, registeredAddress, preferredDeliveryMethod,
postalCode, postalAddress, postOfficeBox,
physicalDeliveryOfficeName, ou, l, internationalISDNNumber,
facsimileTelephoneNumber, destinationIndicator
systemPossSuperiors: organizationalUnit, organization, container
schemaIdGuid: a8df74bf-c5ea-11d1-bbcb-0080c76670c0
defaultSecurityDescriptor: D: (A;;RPWPCRCCLCCLORCWOWSDSDTWSW;;;DA)
(A;;RPWPCRCCLCCLORCWOWSDSDTWSW;;;SY) (A;;RPLCLORC;;;AU)
defaultHidingValue: TRUE
systemOnly: FALSE
defaultObjectCategory: CN=Organizational-Role,<SchemaNCDN>
systemFlags: FLAG_SCHEMA_BASE_OBJECT

```

Version-Specific Behavior: Implemented on Windows 2000 Server operating system, Windows Server 2003 operating system, Windows Server 2003 R2 operating system, Windows Server 2008

operating system, Windows Server 2008 R2 operating system, Windows Server 2012 operating system, and Windows Server 2012 R2 operating system.

2.212 Class organizationalUnit

A container for storing users, computers, and other account objects.

```
cn: Organizational-Unit
ldapDisplayName: organizationalUnit
governsId: 2.5.6.5
objectClassCategory: 1
rdnAttId: ou
subClassOf: top
systemMustContain: ou
systemMayContain: x121Address, userPassword, uPNSuffixes, co,
  telexNumber, teletexTerminalIdentifier, telephoneNumber, street, st,
  seeAlso, searchGuide, registeredAddress, preferredDeliveryMethod,
  postalCode, postalAddress, postOfficeBox,
  physicalDeliveryOfficeName, msCOM-UserPartitionSetLink, managedBy,
  thumbnailLogo, l, internationalISDNNumber, gPOptions, gPLink,
  facsimileTelephoneNumber, destinationIndicator, desktopProfile,
  defaultGroup, countryCode, c, businessCategory
systemPossSuperiors: country, organization, organizationalUnit,
  domainDNS
schemaIdGuid: bf967aa5-0de6-11d0-a285-00aa003049e2
defaultSecurityDescriptor: D: (A;;RPWPCRCDCCLCLORCWOWSDDTSW;;;SY)
  (A;;RPWPCRCDCCLCLORCWOWSDDTSW;;;DA)
  (OA;;CCDC;bf967a86-0de6-11d0-a285-00aa003049e2;;;AO)
  (OA;;CCDC;bf967aba-0de6-11d0-a285-00aa003049e2;;;AO)
  (OA;;CCDC;bf967a9c-0de6-11d0-a285-00aa003049e2;;;AO)
  (OA;;CCDC;bf967aa8-0de6-11d0-a285-00aa003049e2;;;PO)
  (A;;RPLCLORC;;;AU) (A;;LCRPLORC;;;ED)
  (OA;;CCDC;4828CC14-1437-45bc-9B07-AD6F015E5F28;;;AO)
defaultHidingValue: FALSE
systemOnly: FALSE
defaultObjectCategory: CN=Organizational-Unit,<SchemaNCN>
systemFlags: FLAG_SCHEMA_BASE_OBJECT
```

Version-Specific Behavior: Implemented on Windows 2000 Server operating system, Windows Server 2003 operating system, Windows Server 2003 R2 operating system, Windows Server 2008 operating system, Windows Server 2008 R2 operating system, Windows Server 2012 operating system, and Windows Server 2012 R2 operating system.

2.213 Class packageRegistration

The registration information for an application.

```
cn: Package-Registration
ldapDisplayName: packageRegistration
governsId: 1.2.840.113556.1.5.49
objectClassCategory: 1
rdnAttId: cn
subClassOf: top
systemMayContain: versionNumberLo, versionNumberHi, vendor,
  upgradeProductCode, setupCommand, productCode, packageType,
  packageName, packageFlags, msiScriptSize, msiScriptPath,
```

```

msiScriptName, msiScript, msiFileList, managedBy,
machineArchitecture, localeID, lastUpdateSequence, installUiLevel,
iconPath, fileExtPriority, cOMTypelibId, cOMProgID, cOMInterfaceID,
cOMClassID, categories, canUpgradeScript
systemPossSuperiors: classStore
schemaIdGuid: bf967aa6-0de6-11d0-a285-00aa003049e2
defaultSecurityDescriptor: D: (A;;;RPWPCRCCLCCLORCWOWSDSDTWSW;;;DA)
(A;;;RPWPCRCCLCCLORCWOWSDSDTWSW;;;SY) (A;;;RPLCLORC;;;AU)
defaultHidingValue: TRUE
systemOnly: FALSE
defaultObjectCategory: CN=Package-Registration,<SchemaNCDN>
systemFlags: FLAG_SCHEMA_BASE_OBJECT

```

Version-Specific Behavior: Implemented on Windows 2000 Server operating system, Windows Server 2003 operating system, Windows Server 2003 R2 operating system, Windows Server 2008 operating system, Windows Server 2008 R2 operating system, Windows Server 2012 operating system, and Windows Server 2012 R2 operating system.

2.214 Class person

Contains personal information about a user.

```

cn: Person
ldapDisplayName: person
governsId: 2.5.6.6
objectClassCategory: 0
rdnAttId: cn
subClassOf: top
systemMustContain: cn
mayContain: attributeCertificateAttribute
systemMayContain: userPassword, telephoneNumber, sn, serialNumber,
seeAlso
systemPossSuperiors: organizationalUnit, container
schemaIdGuid: bf967aa7-0de6-11d0-a285-00aa003049e2
defaultSecurityDescriptor: D: (A;;;RPWPCRCCLCCLORCWOWSDSDTWSW;;;DA)
(A;;;RPWPCRCCLCCLORCWOWSDSDTWSW;;;SY) (A;;;RPLCLORC;;;AU)
defaultHidingValue: TRUE
systemOnly: FALSE
defaultObjectCategory: CN=Person,<SchemaNCDN>
systemFlags: FLAG_SCHEMA_BASE_OBJECT

```

Version-Specific Behavior: Implemented on Windows 2000 Server operating system, Windows Server 2003 operating system, Windows Server 2003 R2 operating system, Windows Server 2008 operating system, Windows Server 2008 R2 operating system, Windows Server 2012 operating system, and Windows Server 2012 R2 operating system.

2.215 Class physicalLocation

Stores physical address information.

```

cn: Physical-Location
ldapDisplayName: physicalLocation
governsId: 1.2.840.113556.1.5.97
objectClassCategory: 1
rdnAttId: cn

```

```

subClassOf: locality
systemMayContain: managedBy
systemPossSuperiors: physicalLocation, configuration
schemaIdGuid: b7b13122-b82e-11d0-afee-0000f80367c1
defaultSecurityDescriptor: D: (A;;RPWPCRCDCCLCLORCWOWSDSDTSW;;;DA)
(A;;RPWPCRCDCCLCLORCWOWSDSDTSW;;;SY) (A;;RPLCLORC;;;AU)
defaultHidingValue: TRUE
systemOnly: FALSE
defaultObjectCategory: CN=Physical-Location,<SchemaNCDN>
systemFlags: FLAG_SCHEMA_BASE_OBJECT

```

Version-Specific Behavior: Implemented on Windows 2000 Server operating system, Windows Server 2003 operating system, Windows Server 2003 R2 operating system, Windows Server 2008 operating system, Windows Server 2008 R2 operating system, Windows Server 2012 operating system, and Windows Server 2012 R2 operating system.

2.216 Class pKICertificateTemplate

Contains information for certificates that are issued by Active Directory Certificate Services (AD CS).

```

cn: PKI-Certificate-Template
ldapDisplayName: pKICertificateTemplate
governsId: 1.2.840.113556.1.5.177
objectClassCategory: 1
rdnAttId: cn
subClassOf: top
systemMayContain: pKIOverlapPeriod, pKIMaxIssuingDepth, pKIKeyUsage,
pKIExtendedKeyUsage, pKIExpirationPeriod, pKIEnrollmentAccess,
pKIDefaultCSPs, pKIDefaultKeySpec, pKICriticalExtensions,
msPKI-RA-Signature, msPKI-RA-Policies,
msPKI-RA-Application-Policies, msPKI-Template-Schema-Version,
msPKI-Template-Minor-Revision, msPKI-Supersede-Templates,
msPKI-Private-Key-Flag, msPKI-Minimal-Key-Size,
msPKI-Enrollment-Flag, msPKI-Certificate-Policy,
msPKI-Certificate-Name-Flag, msPKI-Certificate-Application-Policy,
msPKI-Cert-Template-OID, flags, displayName
systemPossSuperiors: container
schemaIdGuid: e5209ca2-3bba-11d2-90cc-00c04fd91ab1
defaultSecurityDescriptor: D: (A;;RPWPCRCDCCLCLORCWOWSDSDTSW;;;DA)
(A;;RPWPCRCDCCLCLORCWOWSDSDTSW;;;SY) (A;;RPLCLORC;;;AU)
defaultHidingValue: TRUE
systemOnly: FALSE
defaultObjectCategory: CN=PKI-Certificate-Template,<SchemaNCDN>
systemFlags: FLAG_SCHEMA_BASE_OBJECT

```

Version-Specific Behavior: Implemented on Windows 2000 Server operating system, Windows Server 2003 operating system, Windows Server 2003 R2 operating system, Windows Server 2008 operating system, Windows Server 2008 R2 operating system, Windows Server 2012 operating system, and Windows Server 2012 R2 operating system.

2.217 Class pKIEnrollmentService

The certificate server that can process certificate requests and issue certificates.

```

cn: PKI-Enrollment-Service

```



```

ldapDisplayName: pKIErollmentService
governsId: 1.2.840.113556.1.5.178
objectClassCategory: 1
rdnAttId: cn
subClassOf: top
systemMayContain: msPKI-Enrollment-Servers, msPKI-Site-Name,
signatureAlgorithms, enrollmentProviders, dnsHostName,
certificateTemplates, cACertificateDN, cACertificate
systemPossSuperiors: container
schemaIdGuid: ee4aa692-3bba-11d2-90cc-00c04fd91ab1
defaultSecurityDescriptor: D: (A;;RPWPCRCDCCLCLORCWOWSDDTSW;;;DA)
(A;;RPWPCRCDCCLCLORCWOWSDDTSW;;;SY) (A;;RPLCLORC;;;AU)
defaultHidingValue: TRUE
systemOnly: FALSE
defaultObjectCategory: CN=PKI-Enrollment-Service,<SchemaNCDN>
systemFlags: FLAG_SCHEMA_BASE_OBJECT

```

Version-Specific Behavior: Implemented on Windows 2000 Server operating system, Windows Server 2003 operating system, Windows Server 2003 R2 operating system, Windows Server 2008 operating system, Windows Server 2008 R2 operating system, Windows Server 2012 operating system, and Windows Server 2012 R2 operating system.

2.218 Class posixAccount

An abstraction of an account that has Portable Operating System Interface (POSIX) attributes.

```

cn: PosixAccount
ldapDisplayName: posixAccount
governsId: 1.3.6.1.1.1.2.0
objectClassCategory: 3
rdnAttId: uid
subClassOf: top
mayContain: uid, cn, uidNumber, gidNumber, unixHomeDirectory,
homeDirectory, userPassword, unixUserPassword, loginShell, gecos,
description
schemaIdGuid: ad44bb41-67d5-4d88-b575-7b20674e76d8
defaultSecurityDescriptor: D: (A;;RPWPCRCDCCLCLORCWOWSDDTSW;;;DA)
(A;;RPWPCRCDCCLCLORCWOWSDDTSW;;;SY) (A;;RPLCLORC;;;AU)
defaultHidingValue: TRUE
systemOnly: FALSE
defaultObjectCategory: CN=PosixAccount,<SchemaNCDN>

```

Version-Specific Behavior: Implemented on Windows Server 2003 R2 operating system, Windows Server 2008 operating system, Windows Server 2008 R2 operating system, Windows Server 2012 operating system, and Windows Server 2012 R2 operating system.

2.219 Class posixGroup

An abstraction of a group of accounts.

```

cn: PosixGroup
ldapDisplayName: posixGroup
governsId: 1.3.6.1.1.1.2.2
objectClassCategory: 3
rdnAttId: cn

```

```

subClassOf: top
mayContain: cn, userPassword, unixUserPassword, description,
  gidNumber, memberId
schemaIdGuid: 2a9350b8-062c-4ed0-9903-dde10d06deba
defaultSecurityDescriptor: D: (A;;RPWPCRCDCCLCLORCWOWSDDTSW;;;DA)
  (A;;RPWPCRCDCCLCLORCWOWSDDTSW;;;SY) (A;;RPLCLORC;;;AU)
defaultHidingValue: TRUE
systemOnly: FALSE
defaultObjectCategory: CN=PosixGroup,<SchemaNCDN>

```

Version-Specific Behavior: Implemented on Windows Server 2003 R2 operating system, Windows Server 2008 operating system, Windows Server 2008 R2 operating system, Windows Server 2012 operating system, and Windows Server 2012 R2 operating system.

2.220 Class printQueue

Contains information about a print queue.

```

cn: Print-Queue
ldapDisplayName: printQueue
governsId: 1.2.840.113556.1.5.23
objectClassCategory: 1
rdnAttId: cn
subClassOf: connectionPoint
systemMustContain: versionNumber, uNCName, shortServerName,
  serverName, printerName
systemMayContain: priority, printStatus, printStartTime,
  printStaplingSupported, printSpooling, printShareName,
  printSeparatorFile, printRateUnit, printRate, printPagesPerMinute,
  printOwner, printOrientationsSupported, printNumberUp, printNotify,
  printNetworkAddress, printMinYExtent, printMinXExtent, printMemory,
  printMediaSupported, printMediaReady, printMaxYExtent,
  printMaxXExtent, printMaxResolutionSupported, printMaxCopies,
  printMACAddress, printLanguage, printKeepPrintedJobs, printFormName,
  printEndTime, printDuplexSupported, printColor, printCollate,
  printBinNames, printAttributes, portName, physicalLocationObject,
  operatingSystemVersion, operatingSystemServicePack,
  operatingSystemHotfix, operatingSystem, location, driverVersion,
  driverName, defaultPriority, bytesPerMinute, assetNumber
systemPossSuperiors: organizationalUnit, domainDNS, container,
  computer
schemaIdGuid: bf967aa8-0de6-11d0-a285-00aa003049e2
defaultSecurityDescriptor: D: (A;;RPWPCRCDCCLCLORCWOWSDDTSW;;;DA)
  (A;;RPWPCRCDCCLCLORCWOWSDDTSW;;;SY)
  (A;;RPWPCRCDCCLCLORCWOWSDDTSW;;;PO)
  (A;;RPWPCRCDCCLCLORCWOWSDDTSW;;;CO) (A;;RPLCLORC;;;AU)
defaultHidingValue: FALSE
systemOnly: FALSE
defaultObjectCategory: CN=Print-Queue,<SchemaNCDN>
systemFlags: FLAG_SCHEMA_BASE_OBJECT

```

Version-Specific Behavior: Implemented on Windows 2000 Server operating system, Windows Server 2003 operating system, Windows Server 2003 R2 operating system, Windows Server 2008 operating system, Windows Server 2008 R2 operating system, Windows Server 2012 operating system, and Windows Server 2012 R2 operating system.

2.221 Class queryPolicy

Holds administrative limits for LDAP server resources for sorted and paged results.

```
cn: Query-Policy
ldapDisplayName: queryPolicy
governsId: 1.2.840.113556.1.5.106
objectClassCategory: 1
rdnAttId: cn
subClassOf: top
systemMayContain: LDAPIPDenyList, LDAPAdminLimits
systemPossSuperiors: container
schemaIdGuid: 83cc7075-cca7-11d0-afff-0000f80367c1
defaultSecurityDescriptor: D: (A;;;RPWPCRCDCCLCLORCWOWSDSDTWS;;;DA)
(A;;;RPWPCRCDCCLCLORCWOWSDSDTWS;;;SY) (A;;;RPLCLORC;;;AU)
defaultHidingValue: TRUE
systemOnly: FALSE
defaultObjectCategory: CN=Query-Policy,<SchemaNCDN>
systemFlags: FLAG_SCHEMA_BASE_OBJECT
```

Version-Specific Behavior: Implemented on Windows 2000 Server operating system, Windows Server 2003 operating system, Windows Server 2003 R2 operating system, Windows Server 2008 operating system, Windows Server 2008 R2 operating system, Windows Server 2012 operating system, and Windows Server 2012 R2 operating system.

2.222 Class remoteMailRecipient

An external mail recipient. This attribute is obsolete.

```
cn: Remote-Mail-Recipient
ldapDisplayName: remoteMailRecipient
governsId: 1.2.840.113556.1.5.24
objectClassCategory: 1
rdnAttId: cn
subClassOf: top
systemAuxiliaryClass: mailRecipient
systemMayContain: remoteSourceType, remoteSource, managedBy
systemPossSuperiors: organizationalUnit, domainDNS
schemaIdGuid: bf967aa9-0de6-11d0-a285-00aa003049e2
defaultSecurityDescriptor: D: (A;;;RPWPCRCDCCLCLORCWOWSDSDTWS;;;DA)
(A;;;RPWPCRCDCCLCLORCWOWSDSDTWS;;;SY) (A;;;RPLCLORC;;;AU)
(OA;;CR;ab721a55-1e2f-11d0-9819-00aa0040529b;;AU)
defaultHidingValue: TRUE
systemOnly: FALSE
defaultObjectCategory: CN=Remote-Mail-Recipient,<SchemaNCDN>
systemFlags: FLAG_SCHEMA_BASE_OBJECT
```

Version-Specific Behavior: Implemented on Windows 2000 Server operating system, Windows Server 2003 operating system, Windows Server 2003 R2 operating system, Windows Server 2008 operating system, Windows Server 2008 R2 operating system, Windows Server 2012 operating system, and Windows Server 2012 R2 operating system.

2.223 Class remoteStorageServicePoint

Holds information about the remote storage location for files that are stored offline.

```

cn: Remote-Storage-Service-Point
ldapDisplayName: remoteStorageServicePoint
governsId: 1.2.840.113556.1.5.146
objectClassCategory: 1
rdnAttId: cn
subClassOf: serviceAdministrationPoint
systemMayContain: remoteStorageGUID
systemPossSuperiors: computer
schemaIdGuid: 2a39c5bd-8960-11d1-aebc-0000f80367c1
defaultSecurityDescriptor: D: (A;;RPLCLORC;;;AU)
(A;;RPWPCRLCLOCCDCRCWDWOSDDTSW;;;DA)
(A;;RPWPCRLCLOCCDCRCWDWOSDDTSW;;;CO)
(A;;RPWPCRLCLOCCDCRCWDWOSDDTSW;;;SY)
defaultHidingValue: TRUE
systemOnly: FALSE
defaultObjectCategory: CN=Remote-Storage-Service-Point,<SchemaNCDN>
systemFlags: FLAG_SCHEMA_BASE_OBJECT

```

Version-Specific Behavior: Implemented on Windows 2000 Server operating system, Windows Server 2003 operating system, Windows Server 2003 R2 operating system, Windows Server 2008 operating system, Windows Server 2008 R2 operating system, Windows Server 2012 operating system, and Windows Server 2012 R2 operating system.

2.224 Class residentialPerson

Defines entries that represent a person in the residential environment.

```

cn: Residential-Person
ldapDisplayName: residentialPerson
governsId: 2.5.6.10
objectClassCategory: 1
rdnAttId: cn
subClassOf: person
systemMayContain: x121Address, title, telexNumber,
teletexTerminalIdentifier, street, st, registeredAddress,
preferredDeliveryMethod, postalCode, postalAddress, postOfficeBox,
physicalDeliveryOfficeName, ou, l, internationalISDNNumber,
facsimileTelephoneNumber, destinationIndicator, businessCategory
systemPossSuperiors: locality, container
schemaIdGuid: a8df74d6-c5ea-11d1-bbcb-0080c76670c0
defaultSecurityDescriptor: D: (A;;RPWPCRCDCCLCLORCWOWDSDDTSW;;;DA)
(A;;RPWPCRCDCCLCLORCWOWDSDDTSW;;;SY) (A;;RPLCLORC;;;AU)
defaultHidingValue: TRUE
systemOnly: FALSE
defaultObjectCategory: CN=Residential-Person,<SchemaNCDN>
systemFlags: FLAG_SCHEMA_BASE_OBJECT

```

Version-Specific Behavior: Implemented on Windows 2000 Server operating system, Windows Server 2003 operating system, Windows Server 2003 R2 operating system, Windows Server 2008 operating system, Windows Server 2008 R2 operating system, Windows Server 2012 operating system, and Windows Server 2012 R2 operating system.

2.225 Class rFC822LocalPart

Defines entries that represent the local part of mail addresses.

```

cn: rFC822LocalPart
ldapDisplayName: rFC822LocalPart
governsId: 0.9.2342.19200300.100.4.14
objectClassCategory: 1
rdnAttId: cn
subClassOf: domain
mayContain: x121Address, telexNumber, teletexTerminalIdentifier,
  telephoneNumber, street, sn, seeAlso, registeredAddress,
  preferredDeliveryMethod, postOfficeBox, postalCode, postalAddress,
  physicalDeliveryOfficeName, internationalISDNNumber,
  facsimileTelephoneNumber, destinationIndicator, description, cn
possSuperiors: organizationalUnit, container
schemaIdGuid: b93e3a78-cbae-485e-a07b-5ef4ae505686
defaultSecurityDescriptor: D: (A;;RPWPCRCDCCLCLOLORCWOWSDDDTDSW;;;DA)
  (A;;RPWPCRCDCCLCLOLORCWOWSDDDTDSW;;;SY) (A;;RPLCLORC;;;AU)
defaultHidingValue: TRUE
systemOnly: FALSE
defaultObjectCategory: CN=rFC822LocalPart,<SchemaNCDN>

```

Version-Specific Behavior: Implemented on Windows Server 2003 operating system, Windows Server 2003 R2 operating system, Windows Server 2008 operating system, Windows Server 2008 R2 operating system, Windows Server 2012 operating system, and Windows Server 2012 R2 operating system.

2.226 Class rIDManager

Contains the relative ID (RID) operations master (also known as flexible single master operations or FSMO) and the RID-Available-Pool location that is used by the RID Manager. The RID Manager is a component that runs on the domain controller and is responsible for allocating security identifiers.

```

cn: RID-Manager
ldapDisplayName: rIDManager
governsId: 1.2.840.113556.1.5.83
objectClassCategory: 1
rdnAttId: cn
subClassOf: top
systemMustContain: rIDAvailablePool
systemMayContain: msDS-RIDPoolAllocationEnabled
systemPossSuperiors: container
schemaIdGuid: 6617188d-8f3c-11d0-afda-00c04fd930c9
defaultSecurityDescriptor: D: (A;;RPWPCRCDCCLCLOLORCWOWSDDDTDSW;;;DA)
  (A;;RPWPCRCDCCLCLOLORCWOWSDDDTDSW;;;SY) (A;;RPLCLORC;;;AU)
  S: (AU;SA;CRWP;;;WD)
defaultHidingValue: TRUE
systemOnly: TRUE
defaultObjectCategory: CN=RID-Manager,<SchemaNCDN>
systemFlags: FLAG_SCHEMA_BASE_OBJECT

```

Version-Specific Behavior: Implemented on Windows 2000 Server operating system, Windows Server 2003 operating system, Windows Server 2003 R2 operating system, Windows Server 2008 operating system, Windows Server 2008 R2 operating system, Windows Server 2012 operating system, and Windows Server 2012 R2 operating system.

2.227 Class rIDSet

Holds the RID pools that were allocated by the domain controller. There is one rIDSet for each writable domain controller. Since read-only domain controllers cannot originate the creation of security principals (or other objects), they do not require RID pools or the rIDSet objects that maintain them.

```
cn: RID-Set
ldapDisplayName: rIDSet
governsId: 1.2.840.113556.1.5.129
objectClassCategory: 1
rdnAttId: cn
subClassOf: top
systemMustContain: rIDUsedPool, rIDPreviousAllocationPool,
  rIDNextRID, rIDAllocationPool
systemPossSuperiors: user, container, computer
schemaIdGuid: 7bfdcb89-4807-11d1-a9c3-0000f80367c1
defaultSecurityDescriptor: D: (A;;RPWPCRCDCCLCLORCWOWSDSDTTSW;;;DA)
  (A;;RPWPCRCDCCLCLORCWOWSDSDTTSW;;;SY) (A;;RPLCLORC;;;AU)
defaultHidingValue: TRUE
systemOnly: TRUE
defaultObjectCategory: CN=RID-Set,<SchemaNCDN>
systemFlags: FLAG_SCHEMA_BASE_OBJECT
```

Version-Specific Behavior: Implemented on Windows 2000 Server operating system, Windows Server 2003 operating system, Windows Server 2003 R2 operating system, Windows Server 2008 operating system, Windows Server 2008 R2 operating system, Windows Server 2012 operating system, and Windows Server 2012 R2 operating system.

2.228 Class room

Defines entries that represent rooms.

```
cn: room
ldapDisplayName: room
governsId: 0.9.2342.19200300.100.4.7
objectClassCategory: 1
rdnAttId: cn
subClassOf: top
mustContain: cn
mayContain: location, telephoneNumber, seeAlso, description,
  roomNumber
possSuperiors: organizationalUnit, container
schemaIdGuid: 7860e5d2-c8b0-4cbb-bd45-d9455beb9206
defaultSecurityDescriptor: D: (A;;RPWPCRCDCCLCLOLORCOWSDSDTDTTSW;;;DA)
  (A;;RPWPCRCDCCLCLORCWOWSDSDTTSW;;;SY) (A;;RPLCLORC;;;AU)
defaultHidingValue: TRUE
systemOnly: FALSE
defaultObjectCategory: CN=room,<SchemaNCDN>
```

Version-Specific Behavior: Implemented on Windows Server 2003 operating system, Windows Server 2003 R2 operating system, Windows Server 2008 operating system, Windows Server 2008 R2 operating system, Windows Server 2012 operating system, and Windows Server 2012 R2 operating system.

2.229 Class rpcContainer

The default container for RPC endpoints.

```
cn: Rpc-Container
ldapDisplayName: rpcContainer
governsId: 1.2.840.113556.1.5.136
objectClassCategory: 1
rdnAttId: cn
subClassOf: container
systemMayContain: nameServiceFlags
systemPossSuperiors: container
schemaIdGuid: 80212842-4bdc-11d1-a9c4-0000f80367c1
defaultSecurityDescriptor: D: (A;;;RPWPCRCDCCLCLORCWOWSDDTSW;;;DA)
(A;;;RPWPCRCDCCLCLORCWOWSDDTSW;;;SY) (A;;;RPLCLORC;;;AU)
defaultHidingValue: TRUE
systemOnly: FALSE
defaultObjectCategory: CN=Rpc-Container,<SchemaNCDN>
systemFlags: FLAG_SCHEMA_BASE_OBJECT
```

Version-Specific Behavior: Implemented on Windows 2000 Server operating system, Windows Server 2003 operating system, Windows Server 2003 R2 operating system, Windows Server 2008 operating system, Windows Server 2008 R2 operating system, Windows Server 2012 operating system, and Windows Server 2012 R2 operating system.

2.230 Class rpcEntry

An abstract class whose subclasses are used by the RPC Name Service (Ns), which is accessed through the RpcNs* functions in the Win32 API.

```
cn: rpc-Entry
ldapDisplayName: rpcEntry
governsId: 1.2.840.113556.1.5.27
objectClassCategory: 2
rdnAttId: cn
subClassOf: connectionPoint
systemPossSuperiors: container
schemaIdGuid: bf967aac-0de6-11d0-a285-00aa003049e2
defaultSecurityDescriptor: D: (A;;;RPWPCRCDCCLCLORCWOWSDDTSW;;;DA)
(A;;;RPWPCRCDCCLCLORCWOWSDDTSW;;;SY) (A;;;RPLCLORC;;;AU)
defaultHidingValue: TRUE
systemOnly: FALSE
defaultObjectCategory: CN=rpc-Entry,<SchemaNCDN>
systemFlags: FLAG_SCHEMA_BASE_OBJECT
```

Version-Specific Behavior: Implemented on Windows 2000 Server operating system, Windows Server 2003 operating system, Windows Server 2003 R2 operating system, Windows Server 2008 operating system, Windows Server 2008 R2 operating system, Windows Server 2012 operating system, and Windows Server 2012 R2 operating system.

2.231 Class rpcGroup

Represents an RPC group.

```
cn: rpc-Group
```

```
ldapDisplayName: rpcGroup
governsId: 1.2.840.113556.1.5.80
objectClassCategory: 1
rdnAttId: cn
subClassOf: rpcEntry
systemMayContain: rpcNsObjectID, rpcNsGroup
systemPossSuperiors: container
schemaIdGuid: 88611bdf-8cf4-11d0-afda-00c04fd930c9
defaultSecurityDescriptor: D: (A;;RPWPCRCDCCLCLORCWOWDSDDTSW;;;DA)
(A;;RPWPCRCDCCLCLORCWOWDSDDTSW;;;SY) (A;;RPLCLORC;;;AU)
defaultHidingValue: TRUE
systemOnly: FALSE
defaultObjectCategory: CN=rpc-Group,<SchemaNCDN>
systemFlags: FLAG_SCHEMA_BASE_OBJECT
```

Version-Specific Behavior: Implemented on Windows 2000 Server operating system, Windows Server 2003 operating system, Windows Server 2003 R2 operating system, Windows Server 2008 operating system, Windows Server 2008 R2 operating system, Windows Server 2012 operating system, and Windows Server 2012 R2 operating system.

2.232 Class rpcProfile

Represents an RPC profile.

```
cn: rpc-Profile
ldapDisplayName: rpcProfile
governsId: 1.2.840.113556.1.5.82
objectClassCategory: 1
rdnAttId: cn
subClassOf: rpcEntry
systemPossSuperiors: container
schemaIdGuid: 88611be1-8cf4-11d0-afda-00c04fd930c9
defaultSecurityDescriptor: D: (A;;RPWPCRCDCCLCLORCWOWDSDDTSW;;;DA)
(A;;RPWPCRCDCCLCLORCWOWDSDDTSW;;;SY) (A;;RPLCLORC;;;AU)
defaultHidingValue: TRUE
systemOnly: FALSE
defaultObjectCategory: CN=rpc-Profile,<SchemaNCDN>
systemFlags: FLAG_SCHEMA_BASE_OBJECT
```

Version-Specific Behavior: Implemented on Windows 2000 Server operating system, Windows Server 2003 operating system, Windows Server 2003 R2 operating system, Windows Server 2008 operating system, Windows Server 2008 R2 operating system, Windows Server 2012 operating system, and Windows Server 2012 R2 operating system.

2.233 Class rpcProfileElement

Holds an entry in an RPC profile.

```
cn: rpc-Profile-Element
ldapDisplayName: rpcProfileElement
governsId: 1.2.840.113556.1.5.26
objectClassCategory: 1
rdnAttId: cn
subClassOf: rpcEntry
systemMustContain: rpcNsPriority, rpcNsInterfaceID
```



```
systemMayContain: rpcNsProfileEntry, rpcNsAnnotation
systemPossSuperiors: rpcProfile
schemaIdGuid: f29653cf-7ad0-11d0-afd6-00c04fd930c9
defaultSecurityDescriptor: D: (A;;RPWPCRCDDCLCLORCWOWDSDDTSW;;;DA)
(A;;RPWPCRCDDCLCLORCWOWDSDDTSW;;;SY) (A;;RPLCLORC;;;AU)
defaultHidingValue: TRUE
systemOnly: FALSE
defaultObjectCategory: CN=rpc-Profile-Element,<SchemaNCDN>
systemFlags: FLAG_SCHEMA_BASE_OBJECT
```

Version-Specific Behavior: Implemented on Windows 2000 Server operating system, Windows Server 2003 operating system, Windows Server 2003 R2 operating system, Windows Server 2008 operating system, Windows Server 2008 R2 operating system, Windows Server 2012 operating system, and Windows Server 2012 R2 operating system.

2.234 Class rpcServer

Represents a particular server that is holding one or more RPC interfaces.

```
cn: rpc-Server
ldapDisplayName: rpcServer
governsId: 1.2.840.113556.1.5.81
objectClassCategory: 1
rdnAttId: cn
subClassOf: rpcEntry
systemMayContain: rpcNsObjectID, rpcNsEntryFlags, rpcNsCodeset
systemPossSuperiors: container
schemaIdGuid: 88611be0-8cf4-11d0-afda-00c04fd930c9
defaultSecurityDescriptor: D: (A;;RPWPCRCDDCLCLORCWOWDSDDTSW;;;DA)
(A;;RPWPCRCDDCLCLORCWOWDSDDTSW;;;SY) (A;;RPLCLORC;;;AU)
defaultHidingValue: TRUE
systemOnly: FALSE
defaultObjectCategory: CN=rpc-Server,<SchemaNCDN>
systemFlags: FLAG_SCHEMA_BASE_OBJECT
```

Version-Specific Behavior: Implemented on Windows 2000 Server operating system, Windows Server 2003 operating system, Windows Server 2003 R2 operating system, Windows Server 2008 operating system, Windows Server 2008 R2 operating system, Windows Server 2012 operating system, and Windows Server 2012 R2 operating system.

2.235 Class rpcServerElement

Represents a single interface in a specified RPC server.

```
cn: rpc-Server-Element
ldapDisplayName: rpcServerElement
governsId: 1.2.840.113556.1.5.73
objectClassCategory: 1
rdnAttId: cn
subClassOf: rpcEntry
systemMustContain: rpcNsTransferSyntax, rpcNsInterfaceID,
rpcNsBindings
systemPossSuperiors: rpcServer
schemaIdGuid: f29653d0-7ad0-11d0-afd6-00c04fd930c9
defaultSecurityDescriptor: D: (A;;RPWPCRCDDCLCLORCWOWDSDDTSW;;;DA)
```

```
(A;;RPWPCCDCLCLORCWOWSDDTSW;;;SY) (A;;RPLCLORC;;;AU)
defaultHidingValue: TRUE
systemOnly: FALSE
defaultObjectCategory: CN=rpc-Server-Element,<SchemaNCDN>
systemFlags: FLAG_SCHEMA_BASE_OBJECT
```

Version-Specific Behavior: Implemented on Windows 2000 Server operating system, Windows Server 2003 operating system, Windows Server 2003 R2 operating system, Windows Server 2008 operating system, Windows Server 2008 R2 operating system, Windows Server 2012 operating system, and Windows Server 2012 R2 operating system.

2.236 Class rRASAdministrationConnectionPoint

Contains the connection point for the Routing and Remote Access service.

```
cn: RRAS-Administration-Connection-Point
ldapDisplayName: rRASAdministrationConnectionPoint
governsId: 1.2.840.113556.1.5.150
objectClassCategory: 1
rdnAttId: cn
subClassOf: serviceAdministrationPoint
systemMayContain: msRRASAttribute
systemPossSuperiors: computer
schemaIdGuid: 2a39c5be-8960-11d1-aebc-0000f80367c1
defaultSecurityDescriptor: D: (A;;RPLCLORC;;;AU)
(A;;RPWPCCDCLCLOCCDCRCWDWOSDDTSW;;;DA)
(A;;RPWPCCDCLCLOCCDCRCWDWOSDDTSW;;;CO)
(A;;RPWPCCDCLCLOCCDCRCWDWOSDDTSW;;;SY)
defaultHidingValue: TRUE
systemOnly: FALSE
defaultObjectCategory: CN=RRAS-Administration-Connection-Point,
<SchemaNCDN>
systemFlags: FLAG_SCHEMA_BASE_OBJECT
```

Version-Specific Behavior: Implemented on Windows 2000 Server operating system, Windows Server 2003 operating system, Windows Server 2003 R2 operating system, Windows Server 2008 operating system, Windows Server 2008 R2 operating system, Windows Server 2012 operating system, and Windows Server 2012 R2 operating system.

2.237 Class rRASAdministrationDictionary

A dictionary object for translating vendor-specific routing attributes to names.

```
cn: RRAS-Administration-Dictionary
ldapDisplayName: rRASAdministrationDictionary
governsId: 1.2.840.113556.1.5.156
objectClassCategory: 1
rdnAttId: cn
subClassOf: top
systemMayContain: msRRASVendorAttributeEntry
systemPossSuperiors: container
schemaIdGuid: f39b98ae-938d-11d1-aebd-0000f80367c1
defaultSecurityDescriptor: D: (A;;RPLCLORC;;;AU)
(A;;RPWPCCDCLCLORCWOWSDDTSW;;;DA)
(A;;RPWPCCDCLCLORCWOWSDDTSW;;;SY)
```

```
(A;;RPWPCRCDCCLCLOCRCWOWSDDTSW;;;CO)
defaultHidingValue: TRUE
systemOnly: FALSE
defaultObjectCategory: CN=RRAS-Administration-Dictionary,<SchemaNCN>
systemFlags: FLAG_SCHEMA_BASE_OBJECT
```

Version-Specific Behavior: Implemented on Windows 2000 Server operating system, Windows Server 2003 operating system, Windows Server 2003 R2 operating system, Windows Server 2008 operating system, Windows Server 2008 R2 operating system, Windows Server 2012 operating system, and Windows Server 2012 R2 operating system.

2.238 Class samDomain

An auxiliary class that holds common properties for Windows NT operating system domains.

```
cn: Sam-Domain
ldapDisplayName: samDomain
governsId: 1.2.840.113556.1.5.3
objectClassCategory: 3
rdnAttId: cn
subClassOf: top
systemAuxiliaryClass: samDomainBase
systemMayContain: treeName, rIDManagerReference, replicaSource,
pwdProperties, pwdHistoryLength, privateKey, pekList,
pekKeyChangeInterval, nTMixedDomain, nextRid, nETBIOSName,
msDS-PerUserTrustTombstonesQuota, msDS-PerUserTrustQuota,
ms-DS-MachineAccountQuota, msDS-LogonTimeSyncInterval,
msDS-AllUsersTrustQuota, modifiedCountAtLastProm, minPwdLength,
minPwdAge, maxPwdAge, lSAModifiedCount, lSACreationTime,
lockoutThreshold, lockoutDuration, lockOutObservationWindow,
gPOptions, gPLink, eFSPolicy, domainPolicyObject, desktopProfile,
description, defaultLocalPolicyObject, creationTime,
controlAccessRights, cACertificate, builtinModifiedCount,
builtinCreationTime, auditingPolicy
schemaIdGuid: bf967a90-0de6-11d0-a285-00aa003049e2
defaultSecurityDescriptor: D:
(OA;;CR;1131f6aa-9c07-11d1-f79f-00c04fc2dcd2;;RO)(A;;RP;;;WD)
(OA;;CR;1131f6aa-9c07-11d1-f79f-00c04fc2dcd2;;ED)
(OA;;CR;1131f6ab-9c07-11d1-f79f-00c04fc2dcd2;;ED)
(OA;;CR;1131f6ac-9c07-11d1-f79f-00c04fc2dcd2;;ED)
(OA;;CR;1131f6aa-9c07-11d1-f79f-00c04fc2dcd2;;BA)
(OA;;CR;1131f6ab-9c07-11d1-f79f-00c04fc2dcd2;;BA)
(OA;;CR;1131f6ac-9c07-11d1-f79f-00c04fc2dcd2;;BA)(A;;RPLCLORC;;;AU)
(A;;RPWPCRLCLOCCRCWDWOSW;;;DA)(A;CI;RPWPCRLCLOCCRCWDWOSDSW;;;BA)
(A;;RPWPCRLCLOCCDCRCWDWOSDDTSW;;;SY)
(A;CI;RPWPCRLCLOCCDCRCWDWOSDDTSW;;;EA)(A;CI;LC;;;RU)
(OA;CIIO;RP;037088f8-0ae1-11d2-b422-00a0c968f939;
bf967aba-0de6-11d0-a285-00aa003049e2;RU)
(OA;CIIO;RP;59ba2f42-79a2-11d0-9020-00c04fc2d3cf;
bf967aba-0de6-11d0-a285-00aa003049e2;RU)
(OA;CIIO;RP;bc0ac240-79a9-11d0-9020-00c04fc2d4cf;
bf967aba-0de6-11d0-a285-00aa003049e2;RU)
(OA;CIIO;RP;4c164200-20c0-11d0-a768-00aa006e0529;
bf967aba-0de6-11d0-a285-00aa003049e2;RU)
(OA;CIIO;RP;5f202010-79a5-11d0-9020-00c04fc2d4cf;
bf967aba-0de6-11d0-a285-00aa003049e2;RU)
(OA;;RP;c7407360-20bf-11d0-a768-00aa006e0529;;RU)
```

```

(OA;CIIO;RPLCLORC;;bf967a9c-0de6-11d0-a285-00aa003049e2;RU)
(A;;RPRC;;;RU) (OA;CIIO;RPLCLORC;;
bf967aba-0de6-11d0-a285-00aa003049e2;RU) (A;;LCRPLORC;;;ED)
(OA;CIIO;RP;037088f8-0ae1-11d2-b422-00a0c968f939;
4828CC14-1437-45bc-9B07-AD6F015E5F28;RU)
(OA;CIIO;RP;59ba2f42-79a2-11d0-9020-00c04fc2d3cf;
4828CC14-1437-45bc-9B07-AD6F015E5F28;RU)
(OA;CIIO;RP;bc0ac240-79a9-11d0-9020-00c04fc2d4cf;
4828CC14-1437-45bc-9B07-AD6F015E5F28;RU)
(OA;CIIO;RP;4c164200-20c0-11d0-a768-00aa006e0529;
4828CC14-1437-45bc-9B07-AD6F015E5F28;RU)
(OA;CIIO;RP;5f202010-79a5-11d0-9020-00c04fc2d4cf;
4828CC14-1437-45bc-9B07-AD6F015E5F28;RU)
(OA;CIIO;RPLCLORC;;4828CC14-1437-45bc-9B07-AD6F015E5F28;RU)
(OA;;RP;b8119fd0-04f6-4762-ab7a-4986c76b3f9a;;RU)
(OA;;RP;b8119fd0-04f6-4762-ab7a-4986c76b3f9a;;AU)
(OA;CIIO;RP;b7c69e6d-2cc7-11d2-854e-00a0c983f608;
bf967aba-0de6-11d0-a285-00aa003049e2;ED)
(OA;CIIO;RP;b7c69e6d-2cc7-11d2-854e-00a0c983f608;
bf967a9c-0de6-11d0-a285-00aa003049e2;ED)
(OA;CIIO;RP;b7c69e6d-2cc7-11d2-854e-00a0c983f608;
bf967a86-0de6-11d0-a285-00aa003049e2;ED)
(OA;CIIO;WP;ea1b7b93-5e48-46d5-bc6c-4df4fda78a35;
bf967a86-0de6-11d0-a285-00aa003049e2;PS)
(OA;;CR;1131f6ad-9c07-11d1-f79f-00c04fc2dcd2;;DD)
(OA;;CR;89e95b76-444d-4c62-991a-0facbeda640c;;ED)
(OA;;CR;1131f6ad-9c07-11d1-f79f-00c04fc2dcd2;;BA)
(OA;;CR;89e95b76-444d-4c62-991a-0facbeda640c;;BA)
(OA;;CR;e2a36dc9-ae17-47c3-b58b-be34c55ba633;;S-1-5-32-557)
(OA;;CR;280f369c-67c7-438e-ae98-1d46f3c6f541;;AU)
(OA;;CR;ccc2dc7d-a6ad-4a7a-8846-c04e3cc53501;;AU)
(OA;;CR;05c74c5e-4deb-43b4-bd9f-86664c2a7fd5;;AU)
(OA;;CR;1131f6ae-9c07-11d1-f79f-00c04fc2dcd2;;ED)
(OA;;CR;1131f6ae-9c07-11d1-f79f-00c04fc2dcd2;;BA)
(OA;CIIO;RRPWP;91e647de-d96f-4b70-9557-d63ff4f3ccd8;;PS)
(OA;CIIO;RPWP;3f78c3e5-f79a-46bd-a0b8-9d18116ddc79;;PS)
S: (AU;SA;WDWOWP;;;WD) (AU;SA;CR;;;BA) (AU;SA;CR;;;DU)
(OU;CISA;WP;f30e3bbe-9ff0-11d1-b603-0000f80367c1;
bf967aa5-0de6-11d0-a285-00aa003049e2;WD)
(OU;CISA;WP;f30e3bbf-9ff0-11d1-b603-0000f80367c1;
bf967aa5-0de6-11d0-a285-00aa003049e2;WD)
defaultHidingValue: TRUE
systemOnly: FALSE
defaultObjectCategory: CN=Sam-Domain,<SchemaNCDN>
systemFlags: FLAG_SCHEMA_BASE_OBJECT

```

Version-Specific Behavior: Implemented on Windows 2000 Server operating system, Windows Server 2003 operating system, Windows Server 2003 R2 operating system, Windows Server 2008 operating system, Windows Server 2008 R2 operating system, Windows Server 2012 operating system, and Windows Server 2012 R2 operating system.

2.239 Class samDomainBase

A base class for defining domains.

```

cn: Sam-Domain-Base
ldapDisplayName: samDomainBase

```

```

governsId: 1.2.840.113556.1.5.2
objectClassCategory: 3
rdnAttId: cn
subClassOf: top
systemMayContain: uASCompat, serverState, serverRole, revision,
  pwdProperties, pwdHistoryLength, oEMInformation, objectSid,
  nTSecurityDescriptor, nextRid, modifiedCountAtLastProm,
  modifiedCount, minPwdLength, minPwdAge, maxPwdAge, lockoutThreshold,
  lockoutDuration, lockOutObservationWindow, forceLogoff,
  domainReplica, creationTime
schemaIdGuid: bf967a91-0de6-11d0-a285-00aa003049e2
defaultHidingValue: TRUE
systemOnly: FALSE
defaultObjectCategory: CN=Sam-Domain-Base,<SchemaNCDN>
systemFlags: FLAG_SCHEMA_BASE_OBJECT

```

Version-Specific Behavior: Implemented on Windows 2000 Server operating system, Windows Server 2003 operating system, Windows Server 2003 R2 operating system, Windows Server 2008 operating system, Windows Server 2008 R2 operating system, Windows Server 2012 operating system, and Windows Server 2012 R2 operating system.

2.240 Class samServer

Holds a revision level and a security descriptor that specifies who can make remote procedure calls (RPCs) through the Security Accounts Manager (SAM) interface.

```

cn: Sam-Server
ldapDisplayName: samServer
governsId: 1.2.840.113556.1.5.5
objectClassCategory: 1
rdnAttId: cn
subClassOf: securityObject
systemMayContain: samDomainUpdates
systemPossSuperiors: domainDNS
schemaIdGuid: bf967aad-0de6-11d0-a285-00aa003049e2
defaultSecurityDescriptor: D:(A;;RPWPCRCDCCLCLORCWOWSDSDTWS;;;DA)
  (A;;RPWPCRCDCCLCLORCWOWSDSDTWS;;;SY)(A;;RPLCLORC;;;AU)
  (A;;RPLCLORC;;;RU)(OA;;CR;91d67418-0135-4acc-8d79-c08e857cfbec;;;AU)
  (OA;;CR;91d67418-0135-4acc-8d79-c08e857cfbec;;;RU)
defaultHidingValue: TRUE
systemOnly: FALSE
defaultObjectCategory: CN=Sam-Server,<SchemaNCDN>
systemFlags: FLAG_SCHEMA_BASE_OBJECT

```

Version-Specific Behavior: Implemented on Windows 2000 Server operating system, Windows Server 2003 operating system, Windows Server 2003 R2 operating system, Windows Server 2008 operating system, Windows Server 2008 R2 operating system, Windows Server 2012 operating system, and Windows Server 2012 R2 operating system.

2.241 Class secret

A Local Security Authority secret that is used for trust relationships and to save service passwords.

```

cn: Secret
ldapDisplayName: secret

```

```
governsId: 1.2.840.113556.1.5.28
objectClassCategory: 1
rdnAttId: cn
subClassOf: leaf
systemMayContain: priorValue, priorSetTime, lastSetTime, currentValue
systemPossSuperiors: container
schemaIdGuid: bf967aae-0de6-11d0-a285-00aa003049e2
defaultSecurityDescriptor: D:(A;;;RPWPCRCDCCLCLORCWOWDSDDTSW;;;SY)
defaultHidingValue: TRUE
systemOnly: FALSE
defaultObjectCategory: CN=Secret,<SchemaNCDN>
systemFlags: FLAG_SCHEMA_BASE_OBJECT
```

Version-Specific Behavior: Implemented on Windows 2000 Server operating system, Windows Server 2003 operating system, Windows Server 2003 R2 operating system, Windows Server 2008 operating system, Windows Server 2008 R2 operating system, Windows Server 2012 operating system, and Windows Server 2012 R2 operating system.

2.242 Class securityObject

An auxiliary class that identifies security principals.

```
cn: Security-Object
ldapDisplayName: securityObject
governsId: 1.2.840.113556.1.5.1
objectClassCategory: 2
rdnAttId: cn
subClassOf: top
systemMustContain: cn
systemPossSuperiors: container
schemaIdGuid: bf967aaf-0de6-11d0-a285-00aa003049e2
defaultSecurityDescriptor: D:(A;;;RPWPCRCDCCLCLORCWOWDSDDTSW;;;DA)
(A;;;RPWPCRCDCCLCLORCWOWDSDDTSW;;;SY)(A;;;RPLCLORC;;;AU)
defaultHidingValue: TRUE
systemOnly: FALSE
defaultObjectCategory: CN=Security-Object,<SchemaNCDN>
systemFlags: FLAG_SCHEMA_BASE_OBJECT
```

Version-Specific Behavior: Implemented on Windows 2000 Server operating system, Windows Server 2003 operating system, Windows Server 2003 R2 operating system, Windows Server 2008 operating system, Windows Server 2008 R2 operating system, Windows Server 2012 operating system, and Windows Server 2012 R2 operating system.

2.243 Class securityPrincipal

Contains the security information for an object.

```
cn: Security-Principal
ldapDisplayName: securityPrincipal
governsId: 1.2.840.113556.1.5.6
objectClassCategory: 3
rdnAttId: cn
subClassOf: top
systemMustContain: sAMAccountName, objectSid
systemMayContain: supplementalCredentials, sIDHistory,
```

```
securityIdentifier, sAMAccountType, rid, tokenGroupsNoGCAcceptable,
tokenGroupsGlobalAndUniversal, tokenGroups, nTSecurityDescriptor,
msDS-KeyVersionNumber, altSecurityIdentities, accountNameHistory
schemaIdGuid: bf967ab0-0de6-11d0-a285-00aa003049e2
defaultHidingValue: TRUE
systemOnly: FALSE
defaultObjectCategory: CN=Security-Principal,<SchemaNCDN>
systemFlags: FLAG_SCHEMA_BASE_OBJECT
```

Version-Specific Behavior: Implemented on Windows 2000 Server operating system, Windows Server 2003 operating system, Windows Server 2003 R2 operating system, Windows Server 2008 operating system, Windows Server 2008 R2 operating system, Windows Server 2012 operating system, and Windows Server 2012 R2 operating system.

2.244 Class server

Represents a server computer within a site.

```
cn: Server
ldapDisplayName: server
governsId: 1.2.840.113556.1.5.17
objectClassCategory: 1
rdnAttId: cn
subClassOf: top
systemMayContain: msDS-IsUserCachableAtRodc, msDS-SiteName,
msDS-isRODC, msDS-isGC, mailAddress, serverReference, serialNumber,
managedBy, dnsHostName, bridgeheadTransportList
systemPossSuperiors: serversContainer
schemaIdGuid: bf967a92-0de6-11d0-a285-00aa003049e2
defaultSecurityDescriptor: D: (A;CI;RPWPCRCDCCLCLOCRCWOWSDDTSW;;DA)
(A;;RPWPCRCDCCLCLOCRCWOWSDDTSW;;SY) (A;;RPLCLOCRC;;AU)
defaultHidingValue: TRUE
systemOnly: FALSE
defaultObjectCategory: CN=Server,<SchemaNCDN>
systemFlags: FLAG_SCHEMA_BASE_OBJECT
```

Version-Specific Behavior: Implemented on Windows 2000 Server operating system, Windows Server 2003 operating system, Windows Server 2003 R2 operating system, Windows Server 2008 operating system, Windows Server 2008 R2 operating system, Windows Server 2012 operating system, and Windows Server 2012 R2 operating system.

2.245 Class serversContainer

Holds server objects within a site.

```
cn: Servers-Container
ldapDisplayName: serversContainer
governsId: 1.2.840.113556.1.5.7000.48
objectClassCategory: 1
rdnAttId: cn
subClassOf: top
systemPossSuperiors: site
schemaIdGuid: f780acc0-56f0-11d1-a9c6-0000f80367c1
defaultSecurityDescriptor: D: (A;;CC;;;BA)
(A;;RPWPCRCDCCLCLOCRCWOWSDDTSW;;SY) (A;;RPLCLOCRC;;AU)
```

```
defaultHidingValue: TRUE
systemOnly: FALSE
defaultObjectCategory: CN=Servers-Container,<SchemaNCDN>
systemFlags: FLAG_SCHEMA_BASE_OBJECT
```

Version-Specific Behavior: Implemented on Windows 2000 Server operating system, Windows Server 2003 operating system, Windows Server 2003 R2 operating system, Windows Server 2008 operating system, Windows Server 2008 R2 operating system, Windows Server 2012 operating system, and Windows Server 2012 R2 operating system.

2.246 Class serviceAdministrationPoint

Holds binding information for connecting to a service in order to administer it.

```
cn: Service-Administration-Point
ldapDisplayName: serviceAdministrationPoint
governsId: 1.2.840.113556.1.5.94
objectClassCategory: 1
rdnAttId: cn
subClassOf: serviceConnectionPoint
systemPossSuperiors: computer
schemaIdGuid: b7b13123-b82e-11d0-afee-0000f80367c1
defaultSecurityDescriptor: D: (A;;;RPWPCRCDCCLCLORCWOWSDSDTWSW;;;DA)
(A;;;RPWPCRCDCCLCLORCWOWSDSDTWSW;;;SY) (A;;;RPLCLORC;;;AU)
defaultHidingValue: TRUE
systemOnly: FALSE
defaultObjectCategory: CN=Service-Administration-Point,<SchemaNCDN>
systemFlags: FLAG_SCHEMA_BASE_OBJECT
```

Version-Specific Behavior: Implemented on Windows 2000 Server operating system, Windows Server 2003 operating system, Windows Server 2003 R2 operating system, Windows Server 2008 operating system, Windows Server 2008 R2 operating system, Windows Server 2012 operating system, and Windows Server 2012 R2 operating system.

2.247 Class serviceClass

Stores the properties of a Winsock service.

```
cn: Service-Class
ldapDisplayName: serviceClass
governsId: 1.2.840.113556.1.5.29
objectClassCategory: 1
rdnAttId: cn
subClassOf: leaf
systemMustContain: serviceClassID, displayName
systemMayContain: serviceClassInfo
systemPossSuperiors: container
schemaIdGuid: bf967ab1-0de6-11d0-a285-00aa003049e2
defaultSecurityDescriptor: D: (A;;;RPWPCRCDCCLCLORCWOWSDSDTWSW;;;DA)
(A;;;RPWPCRCDCCLCLORCWOWSDSDTWSW;;;SY) (A;;;RPLCLORC;;;AU)
defaultHidingValue: TRUE
systemOnly: FALSE
defaultObjectCategory: CN=Service-Class,<SchemaNCDN>
systemFlags: FLAG_SCHEMA_BASE_OBJECT
```


Version-Specific Behavior: Implemented on Windows 2000 Server operating system, Windows Server 2003 operating system, Windows Server 2003 R2 operating system, Windows Server 2008 operating system, Windows Server 2008 R2 operating system, Windows Server 2012 operating system, and Windows Server 2012 R2 operating system.

2.248 Class serviceConnectionPoint

Publishes information that client applications can use to bind to a service.

```
cn: Service-Connection-Point
ldapDisplayName: serviceConnectionPoint
governsId: 1.2.840.113556.1.5.126
objectClassCategory: 1
rdnAttId: cn
subClassOf: connectionPoint
systemMayContain: versionNumberLo, versionNumberHi, versionNumber,
  vendor, serviceDNSNameType, serviceDNSName, serviceClassName,
  serviceBindingInformation, appSchemaVersion
systemPossSuperiors: organizationalUnit, container, computer
schemaIdGuid: 28630ec1-41d5-11d1-a9c1-0000f80367c1
defaultSecurityDescriptor: D: (A;;RPWPCRCDCCLCCLORCWOWSDSDTTSW;;;DA)
  (A;;RPWPCRCDCCLCCLORCWOWSDSDTTSW;;;CO)
  (A;;RPWPCRCDCCLCCLORCWOWSDSDTTSW;;;SY) (A;;RPLCLORC;;;AU)
defaultHidingValue: TRUE
systemOnly: FALSE
defaultObjectCategory: CN=Service-Connection-Point,<SchemaNCDN>
systemFlags: FLAG_SCHEMA_BASE_OBJECT
```

Version-Specific Behavior: Implemented on Windows 2000 Server operating system, Windows Server 2003 operating system, Windows Server 2003 R2 operating system, Windows Server 2008 operating system, Windows Server 2008 R2 operating system, Windows Server 2012 operating system, and Windows Server 2012 R2 operating system.

2.249 Class serviceInstance

A connection point object that is used by the Windows Sockets Registration and Resolution (RnR) name service. The serviceInstance object class is used by various namespace providers (such as DNS) to differentiate the type of data returned during service publication.

```
cn: Service-Instance
ldapDisplayName: serviceInstance
governsId: 1.2.840.113556.1.5.30
objectClassCategory: 1
rdnAttId: cn
subClassOf: connectionPoint
systemMustContain: serviceClassID, displayName
systemMayContain: winsockAddresses, serviceInstanceVersion
systemPossSuperiors: container
schemaIdGuid: bf967ab2-0de6-11d0-a285-00aa003049e2
defaultSecurityDescriptor: D: (A;;RPWPCRCDCCLCCLORCWOWSDSDTTSW;;;DA)
  (A;;RPWPCRCDCCLCCLORCWOWSDSDTTSW;;;SY) (A;;RPLCLORC;;;AU)
defaultHidingValue: TRUE
systemOnly: FALSE
defaultObjectCategory: CN=Service-Instance,<SchemaNCDN>
systemFlags: FLAG_SCHEMA_BASE_OBJECT
```

Version-Specific Behavior: Implemented on Windows 2000 Server operating system, Windows Server 2003 operating system, Windows Server 2003 R2 operating system, Windows Server 2008 operating system, Windows Server 2008 R2 operating system, Windows Server 2012 operating system, and Windows Server 2012 R2 operating system.

2.250 Class shadowAccount

Provides additional attributes for shadow passwords.

```
cn: ShadowAccount
ldapDisplayName: shadowAccount
governsId: 1.3.6.1.1.1.2.1
objectClassCategory: 3
rdnAttId: uid
subClassOf: top
mayContain: uid, userPassword, description, shadowLastChange,
  shadowMin, shadowMax, shadowWarning, shadowInactive, shadowExpire,
  shadowFlag
schemaIdGuid: 5b6d8467-1a18-4174-b350-9cc6e7b4ac8d
defaultSecurityDescriptor: D: (A;;RPWPCRCDCCLCLORCWOWSDSDTTSW;;;DA)
  (A;;RPWPCRCDCCLCLORCWOWSDSDTTSW;;;SY) (A;;RPLCLORC;;;AU)
defaultHidingValue: TRUE
systemOnly: FALSE
defaultObjectCategory: CN=ShadowAccount,<SchemaNCDN>
```

Version-Specific Behavior: Implemented on Windows Server 2003 R2 operating system, Windows Server 2008 operating system, Windows Server 2008 R2 operating system, Windows Server 2012 operating system, and Windows Server 2012 R2 operating system.

2.251 Class simpleSecurityObject

Allows an entry to have a userPassword attribute when the principal object classes of an entry do not allow userPassword as an attribute type.

```
cn: simpleSecurityObject
ldapDisplayName: simpleSecurityObject
governsId: 0.9.2342.19200300.100.4.19
objectClassCategory: 3
rdnAttId: cn
subClassOf: top
mayContain: userPassword
schemaIdGuid: 5fe69b0b-e146-4f15-b0ab-c1e5d488e094
defaultSecurityDescriptor: D: (A;;RPWPCRCDCCLCLORCWOWSDSDTTSW;;;DA)
  (A;;RPWPCRCDCCLCLORCWOWSDSDTTSW;;;SY) (A;;RPLCLORC;;;AU)
defaultHidingValue: TRUE
systemOnly: FALSE
defaultObjectCategory: CN=simpleSecurityObject,<SchemaNCDN>
```

Version-Specific Behavior: Implemented on Windows Server 2003 operating system, Windows Server 2003 R2 operating system, Windows Server 2008 operating system, Windows Server 2008 R2 operating system, Windows Server 2012 operating system, and Windows Server 2012 R2 operating system.

2.252 Class site

A container for storing server objects. This class represents a physical location that contains computers. It is used to manage replication.

```
cn: Site
ldapDisplayName: site
governsId: 1.2.840.113556.1.5.31
objectClassCategory: 1
rdnAttId: cn
subClassOf: top
systemMayContain: notificationList, mSMQSiteID, mSMQSiteForeign,
  mSMQNT4Stub, mSMQInterval2, mSMQInterval1, managedBy, location,
  gPOptions, gPLink, msDS-BridgeHeadServersUsed
systemPossSuperiors: sitesContainer
schemaIdGuid: bf967ab3-0de6-11d0-a285-00aa003049e2
defaultSecurityDescriptor: D: (A;;RPWPCRCDCCLCLORCWOWSDDTSW;;;SY)
  (A;;RPLCLORC;;;AU) (A;;LCRPLORC;;;ED)
defaultHidingValue: TRUE
systemOnly: FALSE
defaultObjectCategory: CN=Site,<SchemaNCDN>
systemFlags: FLAG_SCHEMA_BASE_OBJECT
```

Version-Specific Behavior: Implemented on Windows 2000 Server operating system, Windows Server 2003 operating system, Windows Server 2003 R2 operating system, Windows Server 2008 operating system, Windows Server 2008 R2 operating system, Windows Server 2012 operating system, and Windows Server 2012 R2 operating system.

2.253 Class siteLink

Represents the connection between two sites.

```
cn: Site-Link
ldapDisplayName: siteLink
governsId: 1.2.840.113556.1.5.147
objectClassCategory: 1
rdnAttId: cn
subClassOf: top
systemMustContain: siteList
systemMayContain: schedule, replInterval, options, cost
systemPossSuperiors: interSiteTransport
schemaIdGuid: d50c2cde-8951-11d1-aebc-0000f80367c1
defaultSecurityDescriptor: D: (A;;RPWPCRCDCCLCLORCWOWSDDTSW;;;DA)
  (A;;RPWPCRCDCCLCLORCWOWSDDTSW;;;SY) (A;;RPLCLORC;;;AU)
defaultHidingValue: FALSE
systemOnly: FALSE
defaultObjectCategory: CN=Site-Link,<SchemaNCDN>
systemFlags: FLAG_SCHEMA_BASE_OBJECT
```

Version-Specific Behavior: Implemented on Windows 2000 Server operating system, Windows Server 2003 operating system, Windows Server 2003 R2 operating system, Windows Server 2008 operating system, Windows Server 2008 R2 operating system, Windows Server 2012 operating system, and Windows Server 2012 R2 operating system.

2.254 Class siteLinkBridge

An object that tracks the site links that are transitively connected.

```
cn: Site-Link-Bridge
ldapDisplayName: siteLinkBridge
governsId: 1.2.840.113556.1.5.148
objectClassCategory: 1
rdnAttId: cn
subClassOf: top
systemMustContain: siteLinkList
systemPossSuperiors: interSiteTransport
schemaIdGuid: d50c2cdf-8951-11d1-aebc-0000f80367c1
defaultSecurityDescriptor: D: (A;;RPWPCRCDCCLCLORCWOWSDSDTSW;;;DA)
(A;;RPWPCRCDCCLCLORCWOWSDSDTSW;;;SY) (A;;RPLCLORC;;;AU)
defaultHidingValue: FALSE
systemOnly: FALSE
defaultObjectCategory: CN=Site-Link-Bridge,<SchemaNCDN>
systemFlags: FLAG_SCHEMA_BASE_OBJECT
```

Version-Specific Behavior: Implemented on Windows 2000 Server operating system, Windows Server 2003 operating system, Windows Server 2003 R2 operating system, Windows Server 2008 operating system, Windows Server 2008 R2 operating system, Windows Server 2012 operating system, and Windows Server 2012 R2 operating system.

2.255 Class sitesContainer

A container that stores site objects. This class is located in the configuration naming context.

```
cn: Sites-Container
ldapDisplayName: sitesContainer
governsId: 1.2.840.113556.1.5.107
objectClassCategory: 1
rdnAttId: cn
subClassOf: top
systemPossSuperiors: configuration
schemaIdGuid: 7a4117da-cd67-11d0-afff-0000f80367c1
defaultSecurityDescriptor: D: (A;;RPWPCRCDCCLCLORCWOWSDSDTSW;;;DA)
(A;;RPWPCRCDCCLCLORCWOWSDSDTSW;;;SY) (A;;RPLCLORC;;;AU)
defaultHidingValue: TRUE
systemOnly: FALSE
defaultObjectCategory: CN=Sites-Container,<SchemaNCDN>
systemFlags: FLAG_SCHEMA_BASE_OBJECT
```

Version-Specific Behavior: Implemented on Windows 2000 Server operating system, Windows Server 2003 operating system, Windows Server 2003 R2 operating system, Windows Server 2008 operating system, Windows Server 2008 R2 operating system, Windows Server 2012 operating system, and Windows Server 2012 R2 operating system.

2.256 Class storage

A generic object that publishes Universal Naming Conventions (UNCs) for files.

```
cn: Storage
ldapDisplayName: storage
```

```
governsId: 1.2.840.113556.1.5.33
objectClassCategory: 1
rdnAttId: cn
subClassOf: connectionPoint
systemMayContain: monikerDisplayName, moniker, iconPath
systemPossSuperiors: container
schemaIdGuid: bf967ab5-0de6-11d0-a285-00aa003049e2
defaultSecurityDescriptor: D: (A;;RPWPCRCDCCLCLORCWOWSDSDTWSW;;;DA)
(A;;RPWPCRCDCCLCLORCWOWSDSDTWSW;;;SY) (A;;RPLCLORC;;;AU)
defaultHidingValue: TRUE
systemOnly: FALSE
defaultObjectCategory: CN=Storage,<SchemaNCDN>
systemFlags: FLAG_SCHEMA_BASE_OBJECT
```

Version-Specific Behavior: Implemented on Windows 2000 Server operating system, Windows Server 2003 operating system, Windows Server 2003 R2 operating system, Windows Server 2008 operating system, Windows Server 2008 R2 operating system, Windows Server 2012 operating system, and Windows Server 2012 R2 operating system.

2.257 Class subnet

Represents a specific network subnet to which servers and workstations are attached.

```
cn: Subnet
ldapDisplayName: subnet
governsId: 1.2.840.113556.1.5.96
objectClassCategory: 1
rdnAttId: cn
subClassOf: top
systemMayContain: siteObject, physicalLocationObject, location
systemPossSuperiors: subnetContainer
schemaIdGuid: b7b13124-b82e-11d0-afee-0000f80367c1
defaultSecurityDescriptor: D: (A;;RPWPCRCDCCLCLORCWOWSDSDTWSW;;;DA)
(A;;RPWPCRCDCCLCLORCWOWSDSDTWSW;;;SY) (A;;RPLCLORC;;;AU)
defaultHidingValue: TRUE
systemOnly: FALSE
defaultObjectCategory: CN=Subnet,<SchemaNCDN>
systemFlags: FLAG_SCHEMA_BASE_OBJECT
```

Version-Specific Behavior: Implemented on Windows 2000 Server operating system, Windows Server 2003 operating system, Windows Server 2003 R2 operating system, Windows Server 2008 operating system, Windows Server 2008 R2 operating system, Windows Server 2012 operating system, and Windows Server 2012 R2 operating system.

2.258 Class subnetContainer

A container that holds all subnet objects.

```
cn: Subnet-Container
ldapDisplayName: subnetContainer
governsId: 1.2.840.113556.1.5.95
objectClassCategory: 1
rdnAttId: cn
subClassOf: top
systemPossSuperiors: sitesContainer
```

```
schemaIdGuid: b7b13125-b82e-11d0-afee-0000f80367c1
defaultSecurityDescriptor: D: (A;;RPWPCRCDCCLCLORCWOWDSW;;;DA)
(A;;RPWPCRCDCCLCLORCWOWDSDDTSW;;;SY) (A;;RPLCLORC;;;AU)
defaultHidingValue: TRUE
systemOnly: FALSE
defaultObjectCategory: CN=Subnet-Container,<SchemaNCDN>
systemFlags: FLAG_SCHEMA_BASE_OBJECT
```

Version-Specific Behavior: Implemented on Windows 2000 Server operating system, Windows Server 2003 operating system, Windows Server 2003 R2 operating system, Windows Server 2008 operating system, Windows Server 2008 R2 operating system, Windows Server 2012 operating system, and Windows Server 2012 R2 operating system.

2.259 Class subSchema

Contains the schema definition.

```
cn: SubSchema
ldapDisplayName: subSchema
governsId: 2.5.20.1
objectClassCategory: 1
rdnAttId: cn
subClassOf: top
systemMayContain: objectClasses, modifyTimeStamp, extendedClassInfo,
extendedAttributeInfo, dITContentRules, attributeTypes
systemPossSuperiors: dMD
schemaIdGuid: 5a8b3261-c38d-11d1-bbc9-0080c76670c0
defaultSecurityDescriptor: D:S:
defaultHidingValue: TRUE
systemOnly: TRUE
defaultObjectCategory: CN=SubSchema,<SchemaNCDN>
systemFlags: FLAG_SCHEMA_BASE_OBJECT | FLAG_DOMAIN_DISALLOW_RENAME
```

Version-Specific Behavior: Implemented on Windows 2000 Server operating system, Windows Server 2003 operating system, Windows Server 2003 R2 operating system, Windows Server 2008 operating system, Windows Server 2008 R2 operating system, Windows Server 2012 operating system, and Windows Server 2012 R2 operating system.

2.260 Class top

The top-level class from which all classes are derived.

```
cn: Top
ldapDisplayName: top
governsId: 2.5.6.0
objectClassCategory: 2
rdnAttId: cn
subClassOf: top
systemMustContain: objectClass, objectCategory, nTSecurityDescriptor,
instanceType
mayContain: msSFU30PosixMemberOf, msDFSR-ComputerReferenceBL,
msDFSR-MemberReferenceBL, msDS-ObjectReferenceBL
systemMayContain: msDS-EnabledFeatureBL, msDS-LastKnownRDN,
msDS-HostServiceAccountBL,
msDS-OIDToGroupLinkBl, msDS-LocalEffectiveRecycleTime,
```

```

msDS-LocalEffectiveDeletionTime, isRecycled, msDS-NcType,
msDS-PSOApplied, msDS-PrincipalName,
msDS-RevealedListBL, msDS-AuthenticatedToAccountlist,
msDS-IsPartialReplicaFor, msDS-IsDomainFor, msDS-IsFullReplicaFor,
msDS-RevealedDSAs, msDS-KrbTgtLinkBL, url, wWWHomePage, whenCreated,
whenChanged, wellKnownObjects, wbemPath, uSNSource, uSNLastObjRem,
USNIntersite, uSNSALastObjRemoved, uSNCreated, uSNChanged,
systemFlags, subSchemaSubEntry, subRefs, structuralObjectClass,
siteObjectBL, serverReferenceBL, sDRightsEffective, revision,
repsTo, repsFrom, directReports, replUpToDateVector,
replPropertyMetaData, name, queryPolicyBL, proxyAddresses,
proxiedObjectName, possibleInferiors, partialAttributeSet,
partialAttributeDeletionList, otherWellKnownObjects, objectVersion,
objectGUID, distinguishedName, nonSecurityMemberBL, netbootSCPBL,
ownerBL, msDS-ReplValueMetaData, msDS-ReplAttributeMetaData,
msDS-NonMembersBL, msDS-NCReplOutboundNeighbors,
msDS-NCReplInboundNeighbors, msDS-NCReplCursors,
msDS-TasksForAzRoleBL, msDS-TasksForAzTaskBL,
msDS-OperationsForAzRoleBL, msDS-OperationsForAzTaskBL,
msDS-MembersForAzRoleBL, msDs-masteredBy, mS-DS-ConsistencyGuid,
mS-DS-ConsistencyChildCount, msDS-Approx-Immed-Subordinates,
msCOM-PartitionSetLink, msCOM-UserLink, modifyTimeStamp, masteredBy,
managedObjects, lastKnownParent, isPrivilegeHolder, memberOf,
isDeleted, isCriticalSystemObject, showInAdvancedViewOnly,
fSMORoleOwner, frsMemberReferenceBL, frsComputerReferenceBL,
fromEntry, flags, extensionName, dSASignature,
dSCorePropagationData, displayNamePrintable, displayName,
description, createTimeStamp, cn, canonicalName,
bridgeheadServerListBL, allowedChildClassesEffective,
allowedChildClasses, allowedAttributesEffective, allowedAttributes,
adminDisplayName, adminDescription, msDS-NC-RO-Replica-Locations-BL,
msDS-ClaimSharesPossibleValuesWithBL, msDS-MembersOfResourcePropertyListBL,
msDS-IsPrimaryComputerFor, msDS-ValueTypeReferenceBL, msDS-TDOIngressBL,
msDS-TDOEgressBL, msds-memberTransitive, msds-memberOfTransitive,
msDS-parentdistname, msDS-ReplValueMetaDataExt
systemPossSuperiors: lostAndFound
schemaIdGuid: bf967ab7-0de6-11d0-a285-00aa003049e2
defaultSecurityDescriptor: D: (A;;RPWPCRCDCCLCLOCRCWOWSDDTSW;;;DA)
(A;;RPWPCRCDCCLCLOCRCWOWSDDTSW;;;SY) (A;;RPLCLOCRC;;;AU)
defaultHidingValue: TRUE
systemOnly: TRUE
defaultObjectCategory: CN=Top,<SchemaNCDN>
systemFlags: FLAG_SCHEMA_BASE_OBJECT

```

Version-Specific Behavior: Implemented on Windows 2000 Server operating system, Windows Server 2003 operating system, Windows Server 2003 R2 operating system, Windows Server 2008 operating system, Windows Server 2008 R2 operating system, Windows Server 2012 operating system, and Windows Server 2012 R2 operating system.

2.261 Class trustedDomain

An object that represents a domain that is trusted by, or trusting, the local domain.

```

cn: Trusted-Domain
ldapDisplayName: trustedDomain
governsId: 1.2.840.113556.1.5.34
objectClassCategory: 1

```

```

rdnAttId: cn
subClassOf: leaf
systemMayContain: msDS-SupportedEncryptionTypes, trustType,
trustPosixOffset, trustPartner, trustDirection, trustAuthOutgoing,
trustAuthIncoming, trustAttributes, securityIdentifier,
msDS-TrustForestTrustInfo, mS-DS-CreatorSID, initialAuthOutgoing,
initialAuthIncoming, flatName, domainIdentifier, domainCrossRef,
additionalTrustedServiceNames, msDS-IngressClaimsTransformationPolicy,
msDS-EgressClaimsTransformationPolicy
systemPossSuperiors: container
schemaIdGuid: bf967ab8-0de6-11d0-a285-00aa003049e2
defaultSecurityDescriptor: D:(A;;;RPWPCRCDCCLCLORCWOWSDSDTSW;;;DA)
(A;;;RPWPCRCDCCLCLORCWOWSDSDTSW;;;SY)(A;;;RPLCLORC;;;AU)
(OA;;;WP;736e4812-af31-11d2-b7df-00805f48caeb;
bf967ab8-0de6-11d0-a285-00aa003049e2;CO)(A;;;SD;;;CO)
defaultHidingValue: TRUE
systemOnly: FALSE
defaultObjectCategory: CN=Trusted-Domain,<SchemaNCDN>
systemFlags: FLAG_SCHEMA_BASE_OBJECT

```

Version-Specific Behavior: Implemented on Windows 2000 Server operating system, Windows Server 2003 operating system, Windows Server 2003 R2 operating system, Windows Server 2008 operating system, Windows Server 2008 R2 operating system, Windows Server 2012 operating system, and Windows Server 2012 R2 operating system.

2.262 Class typeLibrary

Contains information about a type library.

```

cn: Type-Library
ldapDisplayName: typeLibrary
governsId: 1.2.840.113556.1.5.53
objectClassCategory: 1
rdnAttId: cn
subClassOf: top
systemMayContain: cOMUniqueLIBID, cOMInterfaceID, cOMClassID
systemPossSuperiors: classStore
schemaIdGuid: 281416e2-1968-11d0-a28f-00aa003049e2
defaultSecurityDescriptor: D:(A;;;RPWPCRCDCCLCLORCWOWSDSDTSW;;;DA)
(A;;;RPWPCRCDCCLCLORCWOWSDSDTSW;;;SY)(A;;;RPLCLORC;;;AU)
defaultHidingValue: TRUE
systemOnly: FALSE
defaultObjectCategory: CN=Type-Library,<SchemaNCDN>
systemFlags: FLAG_SCHEMA_BASE_OBJECT

```

Version-Specific Behavior: Implemented on Windows 2000 Server operating system, Windows Server 2003 operating system, Windows Server 2003 R2 operating system, Windows Server 2008 operating system, Windows Server 2008 R2 operating system, Windows Server 2012 operating system, and Windows Server 2012 R2 operating system.

2.263 Class user

Stores information about an employee or contractor who works for an organization. It is also possible to apply this class to long-term visitors.

cn: User
ldapDisplayName: user
governsId: 1.2.840.113556.1.5.9
objectClassCategory: 1
rdnAttId: cn
subClassOf: organizationalPerson
auxiliaryClass: shadowAccount, posixAccount
systemAuxiliaryClass: securityPrincipal, mailRecipient, msDS-CloudExtensions
mayContain: msSFU30NisDomain, msSFU30Name, msDS-SourceObjectDN,
x500uniqueIdentifier, userSMIMECertificate, userPKCS12, uid,
secretary, roomNumber, preferredLanguage, photo, labeledURI,
jpegPhoto, homePostalAddress, givenName, employeeType,
employeeNumber, displayName, departmentNumber, carLicense, audio
systemMayContain: msTSPrimaryDesktop, msTSSecondaryDesktops,
msPKI-CredentialRoamingTokens, msDS-ResultantPSO, msTSLSPProperty01,
msTSLSPProperty02, msTSMManagingLS2, msTSMManagingLS3, msTSMManagingLS4,
msTSLicenseVersion2, msTSLicenseVersion3, msTSLicenseVersion4,
msTSExpireDate2, msTSExpireDate3, msTSExpireDate4,
msDS-AuthenticatedAtDC, msDS-UserPasswordExpiryTimeComputed,
msTSMManagingLS, msTSLicenseVersion, msTSExpireDate, msTSProperty02,
msTSProperty01, msTSInitialProgram, msTSWorkDirectory,
msTSDefaultToMainPrinter, msTSConnectPrinterDrives,
msTSConnectClientDrives, msTSBrokenConnectionAction,
msTSReconnectionAction, msTSMaxIdleTime, msTSMaxConnectionTime,
msTSMaxDisconnectionTime, msTSRemoteControl, msTSAllowLogon,
msTSHomeDrive, msTSHomeDirectory, msTSProfilePath,
msDS-FailedInteractiveLogonCountAtLastSuccessfulLogon,
msDS-FailedInteractiveLogonCount,
msDS-LastFailedInteractiveLogonTime,
msDS-LastSuccessfulInteractiveLogonTime,
msRADIUS-SavedFramedIpv6Route, msRADIUS-FramedIpv6Route,
msRADIUS-SavedFramedIpv6Prefix, msRADIUS-FramedIpv6Prefix,
msRADIUS-SavedFramedInterfaceId, msRADIUS-FramedInterfaceId,
msPKIAccountCredentials, msPKIDPAPIMasterKeys,
msPKIRoamingTimeStamp, msDS-SupportedEncryptionTypes,
msDS-SecondaryKrbTgtNumber, pager, o, mobile, manager, mail,
initials, homePhone, businessCategory, userCertificate,
userWorkstations, userSharedFolderOther, userSharedFolder,
userPrincipalName, userParameters, userAccountControl, unicodePwd,
terminalServer, servicePrincipalName, scriptPath, pwdLastSet,
profilePath, primaryGroupID, preferredOU, otherLoginWorkstations,
operatorCount, ntPwdHistory, networkAddress, msRASSavedFramedRoute,
msRASSavedFramedIPAddress, msRASSavedCallbackNumber,
msRADIUSServiceType, msRADIUSFramedRoute, msRADIUSFramedIPAddress,
msRADIUSCallbackNumber, msNPSavedCallingStationID,
msNPCallingStationID, msNPAllowDialin, mSMQSignCertificatesMig,
mSMQSignCertificates, mSMQDigestsMig, mSMQDigests, msIIS-FTPRoot,
msIIS-FTPDir, msDS-User-Account-Control-Computed,
msDS-Site-Affinity, ms-DS-CreatorSID,
msDS-Cached-Membership-Time-Stamp, msDS-Cached-Membership,
msDRM-IdentityCertificate, msCOM-UserPartitionSetLink, maxStorage,
logonWorkstation, logonHours, logonCount, lockoutTime, localeID,
lmPwdHistory, lastLogonTimestamp, lastLogon, lastLogoff, homeDrive,
homeDirectory, groupsToIgnore, groupPriority, groupMembershipSAM,
dynamicLDAPServer, desktopProfile, defaultClassStore, dBCSPwd,
controlAccessRights, codePage, badPwdCount, badPasswordTime,
adminCount, aCSPolicyName, accountExpires, msDS-PrimaryComputer,
msDS-SyncServerUrl, msDS-AssignedAuthNPolicy, msDS-AssignedAuthNPolicySilo,
msDS-AuthNPolicySiloMembersBL

```

schemaIdGuid: bf967aba-0de6-11d0-a285-00aa003049e2
defaultSecurityDescriptor: D: (A;;RPWPCRCDCCLCLORCWOWSDSDTSW;;;DA)
(A;;RPWPCRCDCCLCLORCWOWSDSDTSW;;;SY)
(A;;RPWPCRCDCCLCLORCWOWSDSDTSW;;;AO) (A;;RPLCLORC;;;PS)
(OA;;CR;ab721a53-1e2f-11d0-9819-00aa0040529b;;PS)
(OA;;CR;ab721a54-1e2f-11d0-9819-00aa0040529b;;PS)
(OA;;CR;ab721a56-1e2f-11d0-9819-00aa0040529b;;PS)
(OA;;RPWP;77B5B886-944A-11d1-AEBD-0000F80367C1;;PS)
(OA;;RPWP;E45795B2-9455-11d1-AEBD-0000F80367C1;;PS)
(OA;;RPWP;E45795B3-9455-11d1-AEBD-0000F80367C1;;PS)
(OA;;RP;037088f8-0ae1-11d2-b422-00a0c968f939;;RS)
(OA;;RP;4c164200-20c0-11d0-a768-00aa006e0529;;RS)
(OA;;RP;bc0ac240-79a9-11d0-9020-00c04fc2d4cf;;RS) (A;;RC;;;AU)
(OA;;RP;59ba2f42-79a2-11d0-9020-00c04fc2d3cf;;AU)
(OA;;RP;77B5B886-944A-11d1-AEBD-0000F80367C1;;AU)
(OA;;RP;E45795B3-9455-11d1-AEBD-0000F80367C1;;AU)
(OA;;RP;e48d0154-bcf8-11d1-8702-00c04fb96050;;AU)
(OA;;CR;ab721a53-1e2f-11d0-9819-00aa0040529b;;WD)
(OA;;RP;5f202010-79a5-11d0-9020-00c04fc2d4cf;;RS)
(OA;;RPWP;bf967a7f-0de6-11d0-a285-00aa003049e2;;CA)
(OA;;RP;46a9b11d-60ae-405a-b7e8-ff8a58d456d2;;S-1-5-32-560)
(OA;;WPRP;6db69a1c-9422-11d1-aebd-0000f80367c1;;S-1-5-32-561)
(OA;;WPRP;5805bc62-bdc9-4428-a5e2-856a0f4c185e;;S-1-5-32-561)
systemPossSuperiors: builtinDomain, organizationalUnit, domainDNS
defaultHidingValue: FALSE
systemOnly: FALSE
defaultObjectCategory: CN=Person,<SchemaNCDN>
systemFlags: FLAG_SCHEMA_BASE_OBJECT

```

Version-Specific Behavior: Implemented on Windows 2000 Server operating system, Windows Server 2003 operating system, Windows Server 2003 R2 operating system, Windows Server 2008 operating system, Windows Server 2008 R2 operating system, Windows Server 2012 operating system, and Windows Server 2012 R2 operating system.

2.264 Class volume

Contains information about a storage device or file. This class is used to create shared folders.

```

cn: Volume
ldapDisplayName: volume
governsId: 1.2.840.113556.1.5.36
objectClassCategory: 1
rdnAttId: cn
subclassOf: connectionPoint
systemMustContain: uNCName
systemMayContain: lastContentIndexed, contentIndexingAllowed
systemPossSuperiors: organizationalUnit, domainDNS
schemaIdGuid: bf967abb-0de6-11d0-a285-00aa003049e2
defaultSecurityDescriptor: D: (A;;RPWPCRCDCCLCLORCWOWSDSDTSW;;;DA)
(A;;RPWPCRCDCCLCLORCWOWSDSDTSW;;;SY) (A;;RPLCLORC;;;AU)
defaultHidingValue: FALSE
systemOnly: FALSE
defaultObjectCategory: CN=Volume,<SchemaNCDN>
systemFlags: FLAG_SCHEMA_BASE_OBJECT

```

Version-Specific Behavior: Implemented on Windows 2000 Server operating system, Windows Server 2003 operating system, Windows Server 2003 R2 operating system, Windows Server 2008 operating system, Windows Server 2008 R2 operating system, Windows Server 2012 operating system, and Windows Server 2012 R2 operating system.

3 Change Tracking

No table of changes is available. The document is either new or has had no changes since its last release.

4 Index

A

[Active Directory classes](#) 12
[Active Directory references](#) 11

C

[Change tracking](#) 148
[Classes - Active Directory](#) 12

R

[References - Active Directory](#) 11

T

[Tracking changes](#) 148