

## [MS-AZMP]:

# Authorization Manager (AzMan) Policy File Format

---

### Intellectual Property Rights Notice for Open Specifications Documentation

- **Technical Documentation.** Microsoft publishes Open Specifications documentation for protocols, file formats, languages, standards as well as overviews of the interaction among each of these technologies.
- **Copyrights.** This documentation is covered by Microsoft copyrights. Regardless of any other terms that are contained in the terms of use for the Microsoft website that hosts this documentation, you may make copies of it in order to develop implementations of the technologies described in the Open Specifications and may distribute portions of it in your implementations using these technologies or your documentation as necessary to properly document the implementation. You may also distribute in your implementation, with or without modification, any schema, IDL's, or code samples that are included in the documentation. This permission also applies to any documents that are referenced in the Open Specifications.
- **No Trade Secrets.** Microsoft does not claim any trade secret rights in this documentation.
- **Patents.** Microsoft has patents that may cover your implementations of the technologies described in the Open Specifications. Neither this notice nor Microsoft's delivery of the documentation grants any licenses under those or any other Microsoft patents. However, a given Open Specification may be covered by Microsoft [Open Specification Promise](#) or the [Community Promise](#). If you would prefer a written license, or if the technologies described in the Open Specifications are not covered by the Open Specifications Promise or Community Promise, as applicable, patent licenses are available by contacting [iplg@microsoft.com](mailto:iplg@microsoft.com).
- **Trademarks.** The names of companies and products contained in this documentation may be covered by trademarks or similar intellectual property rights. This notice does not grant any licenses under those rights. For a list of Microsoft trademarks, visit [www.microsoft.com/trademarks](http://www.microsoft.com/trademarks).
- **Fictitious Names.** The example companies, organizations, products, domain names, e-mail addresses, logos, people, places, and events depicted in this documentation are fictitious. No association with any real company, organization, product, domain name, email address, logo, person, place, or event is intended or should be inferred.

**Reservation of Rights.** All other rights are reserved, and this notice does not grant any rights other than specifically described above, whether by implication, estoppel, or otherwise.

**Tools.** The Open Specifications do not require the use of Microsoft programming tools or programming environments in order for you to develop an implementation. If you have access to Microsoft programming tools and environments you are free to take advantage of them. Certain Open Specifications are intended for use in conjunction with publicly available standard specifications and network programming art, and assumes that the reader either is familiar with the aforementioned material or has immediate access to it.

## Revision Summary

Date	Revision History	Revision Class	Comments
6/17/2011	0.1	Major	Released new document.
9/23/2011	0.1	None	No changes to the meaning, language, or formatting of the technical content.
12/16/2011	0.1	None	No changes to the meaning, language, or formatting of the technical content.
3/30/2012	1.0	None	No changes to the meaning, language, or formatting of the technical content.
7/12/2012	1.0	None	No changes to the meaning, language, or formatting of the technical content.
10/25/2012	1.0	None	No changes to the meaning, language, or formatting of the technical content.
1/31/2013	1.0	None	No changes to the meaning, language, or formatting of the technical content.
8/8/2013	2.0	Major	Significantly changed the technical content.
11/14/2013	2.0	None	No changes to the meaning, language, or formatting of the technical content.
2/13/2014	2.0	None	No changes to the meaning, language, or formatting of the technical content.
5/15/2014	3.0	Major	Significantly changed the technical content.
6/30/2015	4.0	Major	Significantly changed the technical content.
10/16/2015	4.0	No Change	No changes to the meaning, language, or formatting of the technical content.

# Table of Contents

<b>1</b>	<b>Introduction</b>	<b>4</b>
1.1	Glossary	4
1.2	References	4
1.2.1	Normative References	4
1.2.2	Informative References	5
1.3	Structure Overview (Synopsis)	5
1.4	Relationship to Protocols and Other Structures	5
1.5	Applicability Statement	5
1.6	Versioning and Localization	5
1.7	Vendor-Extensible Fields	5
<b>2</b>	<b>Structures</b>	<b>6</b>
2.1	AzAdminManager	6
2.2	AzApplicationGroup	7
2.3	AzRole	9
2.4	AzTask	10
<b>3</b>	<b>Structure Examples</b>	<b>11</b>
<b>4</b>	<b>Security Considerations</b>	<b>13</b>
4.1	Security Considerations for Implementers	13
<b>5</b>	<b>Appendix A: Full XML Schema</b>	<b>14</b>
<b>6</b>	<b>Appendix B: Product Behavior</b>	<b>16</b>
<b>7</b>	<b>Change Tracking</b>	<b>17</b>
<b>8</b>	<b>Index</b>	<b>18</b>

# 1 Introduction

This document describes the structure of the XML file format used to preserve policy settings for Microsoft Authorization Manager (AzMan). Other formats are possible, but are not addressed in this document. This structure is currently used by all Windows AzMan implementations.

The AzMan XML policy format is used in order to enable interoperability by implementers. By using the specifications in this document, an implementer can:

- Create a AzMan XML policy file readable by the Microsoft Management Console (MMC) Authorization Manager snap-in, and by the authorization manager runtime used by applications to make authorization decisions.
- Read an AzMan XML policy file that was created using the MMC Authorization Manager snap-in.

Sections 1.7 and 2 of this specification are normative and can contain the terms MAY, SHOULD, MUST, MUST NOT, and SHOULD NOT as defined in [\[RFC2119\]](#). All other sections and examples in this specification are informative.

## 1.1 Glossary

The following terms are specific to this document:

**globally unique identifier (GUID):** A term used interchangeably with universally unique identifier (UUID) in Microsoft protocol technical documents (TDs). Interchanging the usage of these terms does not imply or require a specific algorithm or mechanism to generate the value. Specifically, the use of this term does not imply or require that the algorithms described in [\[RFC4122\]](#) or [\[C706\]](#) must be used for generating the **GUID**. See also universally unique identifier (UUID).

**security identifier (SID):** An identifier for security principals in Windows that is used to identify an account or a group. Conceptually, the **SID** is composed of an account authority portion (typically a domain) and a smaller integer representing an identity relative to the account authority, termed the relative identifier (RID). The **SID** format is specified in [\[MS-DTYP\]](#) section 2.4.2; a string representation of **SIDs** is specified in [\[MS-DTYP\]](#) section 2.4.2 and [\[MS-AZOD\]](#) section 1.1.1.2.

**MAY, SHOULD, MUST, SHOULD NOT, MUST NOT:** These terms (in all caps) are used as defined in [\[RFC2119\]](#). All statements of optional behavior use either MAY, SHOULD, or SHOULD NOT.

## 1.2 References

Links to a document in the Microsoft Open Specifications library point to the correct section in the most recently published version of the referenced document. However, because individual documents in the library are not updated at the same time, the section numbers in the documents may not match. You can confirm the correct section numbering by checking the [Errata](#).

### 1.2.1 Normative References

We conduct frequent surveys of the normative references to assure their continued availability. If you have any issue with finding a normative reference, please contact [dochelp@microsoft.com](mailto:dochelp@microsoft.com). We will assist you in finding the relevant information.

[RFC2119] Bradner, S., "Key words for use in RFCs to Indicate Requirement Levels", BCP 14, RFC 2119, March 1997, <http://www.rfc-editor.org/rfc/rfc2119.txt>

[RFC2251] Wahl, M., Howes, T., and Kille, S., "Lightweight Directory Access Protocol (v3)", RFC 2251, December 1997, <http://www.ietf.org/rfc/rfc2251.txt>

[XSD1.1-1] Gao, S., Sperberg-McQueen, C.M., and Thompson, H.S., Eds., "W3C XML Schema Definition Language (XSD) 1.1 Part 1: Structures", W3C Working Draft, December 2009, <http://www.w3.org/TR/2009/WD-xmlschema11-1-20091203/>

[XSD1.1-2] Peterson, D., Gao, S., Malhotra, A., et al., Eds., "W3C XML Schema Definition Language (XSD) 1.1 Part 2: Datatypes", W3C Working Draft, December 2009, <http://www.w3.org/TR/2009/WD-xmlschema11-2-20091203/>

## 1.2.2 Informative References

[MSDN-JScript] Microsoft Corporation, "JScript Language Reference (Windows Scripting - JScript)", [http://msdn.microsoft.com/en-us/library/yek4tbz0\(v=VS.85\).aspx](http://msdn.microsoft.com/en-us/library/yek4tbz0(v=VS.85).aspx)

[MSDN-VBScript] Microsoft Corporation, "VBScript Language Reference", [http://msdn.microsoft.com/en-us/library/d1wf56tt\(v=VS.85\).aspx](http://msdn.microsoft.com/en-us/library/d1wf56tt(v=VS.85).aspx)

## 1.3 Structure Overview (Synopsis)

The XML structure (as described in [\[XSD1.1-1\]](#) and [\[XSD1.1-2\]](#)) defined in this document describes the Microsoft Authorization Manager (AzMan) policy. AzMan policy files are typically used in two ways:

1. Loaded by the Microsoft Management Console (MMC) Authorization Manager (AzMan) snap-in which allows the administrator to create and modify the authorization manager policy.
2. Loaded by the authorization manager runtime to allow applications to make authorization decisions.

## 1.4 Relationship to Protocols and Other Structures

The authorization manager policy file is used only by the authorization manager runtime and the Authorization Manager Microsoft Management Console snap-in. Otherwise, the structure is independent of any other structures or protocols except those referenced in this document.

## 1.5 Applicability Statement

The Microsoft Authorization Manager Policy XML policy file can be used in any environment where AzMan is supported. See Appendix C for a list of supported Operating System versions. It may be used in Active Directory domain-based environments or on stand-alone servers.

## 1.6 Versioning and Localization

Microsoft Authorization Manager policy files may be either version 1.0 or 2.0<sup><1></sup>. The differences between version 1.0 and version 2.0 are minor and are pointed out in section [2](#).

## 1.7 Vendor-Extensible Fields

None.

## 2 Structures

### 2.1 AzAdminManager

The **AzAdminManager** complex type defines an instance of an authorization manager policy.

The following is the XSD definition for the **AzAdminManager** complex type.

```
<xs:element name="AzAdminManager">
  <xs:complexType>
    <xs:sequence>
      <xs:element name="AzApplication" minOccurs="0" maxOccurs="unbounded">
        <xs:complexType>
          <xs:sequence>
            <xs:element ref="AzApplicationGroup" minOccurs="0" maxOccurs="unbounded" />
            <xs:element ref="AzTask" minOccurs="0" maxOccurs="unbounded" />
            <xs:element name="AzOperation" minOccurs="0" maxOccurs="unbounded">
              <xs:complexType>
                <xs:sequence>
                  <xs:element name="OperationID" type="xs:string" minOccurs="0"/>
                </xs:sequence>
              </xs:complexType>
            </xs:element>
            <xs:element ref="AzRole" minOccurs="0" maxOccurs="unbounded" />
            <xs:element name="AzScope" minOccurs="0" maxOccurs="unbounded">
              <xs:complexType>
                <xs:sequence>
                  <xs:element ref="AzApplicationGroup" minOccurs="0" maxOccurs="unbounded" />
                  <xs:element ref="AzTask" minOccurs="0" maxOccurs="unbounded" />
                  <xs:element ref="AzRole" minOccurs="0" maxOccurs="unbounded" />
                </xs:sequence>
                <xs:attribute name="Guid" type="xs:string" />
                <xs:attribute name="Name" type="xs:string" />
                <xs:attribute name="Description" type="xs:string" />
              </xs:complexType>
            </xs:element>
          </xs:sequence>
          <xs:attribute name="Guid" type="xs:string" />
          <xs:attribute name="Name" type="xs:string" />
          <xs:attribute name="Description" type="xs:string" />
          <xs:attribute name="ApplicationVersion" type="xs:string" />
        </xs:complexType>
      </xs:element>
      <xs:element ref="AzApplicationGroup" minOccurs="0" maxOccurs="unbounded" />
      <xs:attribute name="MajorVersion" type="xs:string" />
      <xs:attribute name="MinorVersion" type="xs:string" />
      <xs:attribute name="Guid" type="xs:string" />
      <xs:attribute name="Description" type="xs:string" />
    </xs:sequence>
  </xs:complexType>
</xs:element>
```

**AzApplication:** Defines an instance of an authorization manager application.

**AzApplication.AzApplicationGroup:** This element defines an **AzApplicationGroup** contained within the scope of an **AzApplication**. See section [2.2](#) for more details.

**AzApplication.AzTask:** This element defines an **AzTask** contained within the scope of an **AzApplication**. See section [2.4](#) for more details.

**AzApplication.AzOperation:** The AzOperation complex type defines each authorization manager operation in the policy.

**AzApplication.AzOperation.OperationID:** An integer value represented as a string which is the operation identifier for the **AzOperation**.

**AzApplication.AzOperation.Guid:** The unique identifier for the **AzOperation**.

**AzApplication.AzOperation.Name:** The name of the **AzOperation**.

**AzApplication.AzOperation.Description:** The description for the **AzOperation**.

**AzApplication.AzRole:** This element defines an **AzRole** contained within the scope of an **AzApplication**. See section [2.3](#) for more details.

**AzApplication.AzScope:** This element defines an **AzScope** contained within the scope of an **AzApplication**. A scope is a logical resource for which a specific authorization policy is defined.

**AzApplication.AzScope.AzApplicationGroup:** This element defines an **AzApplicationGroup** contained within this AzScope. See section 2.2 for more details.

**AzApplication.AzScope.AzTask:** This element defines an **AzTask** contained within this AzScope. See section 2.4 for more details.

**AzApplication.AzScope.AzRole:** This element defines an **AzRole** contained within this AzScope. See section 2.3 for more details.

**AzApplication.AzScope.Guid:** A **GUID** in string format which is the unique identifier for the **AzScope**.

**AzApplication.AzScope.Name:** The name of the **AzScope**.

**AzApplication.AzScope.Description:** The description for the **AzScope**.

**AzApplication.Guid:** The unique identifier for the **AzApplication**.

**AzApplication.Name:** The name of the **AzApplication**.

**AzApplication.Description:** The description for the **AzApplication**.

**AzApplication.ApplicationVersion:** An optional version of the **AzApplication** policy element.

**AzApplicationGroup:** This element defines an **AzApplicationGroup** that is global for every **AzApplication** instance, which differs from the **AzApplication.AzApplicationGroup** element. See section 2.2 for more details.

**MajorVersion:** The major version of the **AzAdminManager** policy. This MUST be set to either 1 or 2.

**MinorVersion:** The major version of the **AzAdminManager** policy. This MUST be set to 0.

**Guid:** The unique identifier for the **AzAdminManager** policy.

**Description:** The description for the **AzAdminManager** policy.

## 2.2 AzApplicationGroup

This element defines an authorization manager group. **AzApplicationGroup** can be used to define a global group that is used by all applications (every instance of **AzApplication**) in the policy or to define a local group that is specific to one specific application in the policy store. When the **AzApplicationGroup** element appears in the XML policy file at the highest level (child of

**AzAdminManager**) the **AzApplicationGroup** is global. When the **AzApplicationGroup** element appears as a child of **AzApplication**, it defines a group local to the **AzApplication**.

The following is the XSD definition for the **AzApplicationGroup** complex type.

```
<xs:element name="AzApplicationGroup">
  <xs:complexType>
    <xs:sequence>
      <xs:element name="BizRuleLanguage" type="xs:string" minOccurs="0" />
      <xs:element name="LdapQuery" type="xs:string" minOccurs="0" />
      <xs:element name="BizRule" type="xs:string" minOccurs="0" />
      <xs:element name="BizRuleImportedPath" type="xs:string" minOccurs="0" />
      <xs:element name="AppMemberLink" type="xs:string" minOccurs="0" />
      <xs:element name="Member" nillable="true" minOccurs="0" maxOccurs="unbounded">
        <xs:complexType>
          <xs:simpleContent>
            <xs:extension base="xs:string">
            </xs:extension>
          </xs:simpleContent>
        </xs:complexType>
      </xs:element>
      <xs:element name="NonMember" nillable="true" minOccurs="0" maxOccurs="unbounded">
        <xs:complexType>
          <xs:simpleContent>
            <xs:extension base="xs:string">
            </xs:extension>
          </xs:simpleContent>
        </xs:complexType>
      </xs:element>
    </xs:sequence>
    <xs:attribute name="Guid" type="xs:string" />
    <xs:attribute name="Name" type="xs:string" />
    <xs:attribute name="Description" type="xs:string" />
    <xs:attribute name="GroupType" type="xs:string" />
  </xs:complexType>
</xs:element>
```

**BizRuleLanguage:** The language used to express a business rule in an **AzApplicationGroup** when **GroupType** equals "Bizrule". The possible values are "VBScript" (for more information, see [\[MSDN-VBScript\]](#)) or "JScript" (for more information, see [\[MSDN-JScript\]](#)). The **BizRuleLanguage** element is required for all **AzApplicationGroup** elements if **GroupType** equals "Bizrule". Otherwise, it is optional.

**LdapQuery:** When **GroupType** equals "LdapQuery", this element contains an LDAP query as described in [\[RFC2251\]](#). If **GroupType** does not equal "LdapQuery", this element MUST NOT be present. In version 1.0 schema policy files, only queries against "user" (meaning where objectcategory=user) objects are supported. In version 2.0 schema policy files, any object type can be queried.

**BizRule:** When **GroupType** equals "Bizrule", this element contains a business rule in the form of script text (HTML-encoded) in the language specified by **BizRuleLanguage**. If **GroupType** does not equal "Bizrule", this element MUST NOT be present.

**BizRuleImportedPath:** When **GroupType** equals "Bizrule", this element contains a fully qualified file system path to a file that contains the business rule as defined in **BizRule**. If **GroupType** does not equal "Bizrule", this element MUST NOT be present.

**AppMemberLink:** Optional element that specifies the GUID of an **AzApplicationGroup** which is a member of the **AzApplicationGroup** defined by this section.

**Member:** Optional element that describes an explicit member of the **AzApplicationGroup**.

**NonMember:** Optional element that describes an explicit nonmember of the **AzApplicationGroup**.



**Guid:** The Globally Unique Identifier (GUID) of the **AzApplicationGroup**.

**Name:** The name of the **AzApplicationGroup**.

**Description:** The description for the **AzApplicationGroup**.

**GroupType:** This element defines the type of the **AzApplicationGroup**. The value MUST be one of the following strings:

- "Basic"
- "Bizrule"
- "LdapQuery"

**Note** The "Bizrule" **GroupType** is supported only in version 2.0 AzMan policies.

## 2.3 AzRole

The **AzRole** complex type defines each authorization manager role assignment in the policy.

The following is the XSD definition for the **AzRole** complex type.

```
<xs:element name="AzRole">
  <xs:complexType>
    <xs:sequence>
      <xs:element name="TaskLink" type="xs:string" minOccurs="0" />
      <xs:element name="Member" type="xs:string" minOccurs="0" />
      <xs:element name="AppMemberLink" nillable="true" minOccurs="0" maxOccurs="unbounded">
        <xs:complexType>
          <xs:simpleContent >
            <xs:extension base="xs:string">
              </xs:extension>
            </xs:simpleContent>
          </xs:complexType>
        </xs:element>
      </xs:sequence>
      <xs:attribute name="Guid" type="xs:string" />
      <xs:attribute name="Name" type="xs:string" />
      <xs:attribute name="Description" type="xs:string" />
    </xs:complexType>
  </xs:element>
```

**AzRole.TaskLink:** An optional GUID(s) of one or more **AzTask** elements which is a subordinate task for this **AzTask** element. It MUST be a valid **AzTask** element in the **AzApplication** scope.

**AzRole.Member:** An optional element that describes a member of the **AzRole**. If present, the element MUST specify a **SID** for an Active Directory object, local computer user, or group object.

**AzRole.AppMemberLink:** An optional element that specifies the GUID of an **AzApplicationGroup** which defines the **AzRole**.

**AzRole.Guid:** The unique identifier for the **AzRole**.

**AzRole.Name:** The name of the **AzRole**.

**AzRole.Description:** The description for the **AzRole**.

## 2.4 AzTask

The **AzTask** complex type defines each authorization manager task and authorization manager role definition in the policy.

```
<xs:element name="AzTask">
  <xs:complexType>
    <xs:sequence>
      <xs:element name="TaskLink" type="xs:string" minOccurs="0" />
      <xs:element name="OperationLink" nillable="true" minOccurs="0" maxOccurs="unbounded">
        <xs:complexType>
          <xs:simpleContent msdata:ColumnName="OperationLink_Text">
            <xs:extension base="xs:string">
              </xs:extension>
            </xs:simpleContent>
          </xs:complexType>
        </xs:element>
      </xs:sequence>
      <xs:attribute name="Guid" type="xs:string" />
      <xs:attribute name="Name" type="xs:string" />
      <xs:attribute name="Description" type="xs:string" />
      <xs:attribute name="BizRuleImportedPath" type="xs:string" />
      <xs:attribute name="RoleDefinition" type="xs:string" />
    </xs:complexType>
  </xs:element>
```

**AzTask.TaskLink:** An optional unique identifier of one or more **AzTask** elements which is a subordinate task for this **AzTask** element. It MUST be a valid **AzTask** element in the **AzApplication** scope.

**AzTask.OperationLink:** An optional unique identifier of one or more **AzOperation** elements which is a subordinate operation for this **AzTask** element. It MUST be a valid **AzOperation** element in the **AzApplication** scope.

**AzTask.Guid:** The unique identifier for the **AzTask**.

**AzTask.Name:** The name of the **AzTask**.

**AzTask.Description:** The description for the **AzTask**.

**AzTask.BizRuleImportedPath:** When **AzTask.RoleDefinition** is set to "true", this optional element specifies a fully qualified path to a script which defines an authorization rule for the role definition.

**AzTask.RoleDefinition:** When set to "true", this **AzTask** element defines an authorization manager role definition. When False, it defines an authorization manager task. No other value is permitted.

### 3 Structure Examples

The following is an example of an AzMan XML policy file:

```
<?xml version="1.0" encoding="utf-8"?>
<AzAdminManager MajorVersion="2" MinorVersion="0" Guid="c5217693-1a84-48ee-a9ae-65f0e10bd314"
Description="This is the description">
  <AzApplication Guid="f6ae8a28-57c3-4db8-9b7f-848aec862518" Name="Application#1"
Description="Application#1-Desc" ApplicationVersion="Application#1-Version">
    <AzApplicationGroup Guid="3736a1f3-3f3d-44f7-9fa4-eb6f9032e962" Name="App Group #1 -
Basic" Description="App Group #1 Description - Basic " GroupType="Basic">
      <BizRuleLanguage></BizRuleLanguage>
      <Member>S-1-5-21-3104031619-1062013444-2593988815-1115</Member>
      <Member>S-1-5-21-3104031619-1062013444-2593988815-1118</Member>
      <NonMember>S-1-5-21-3104031619-1062013444-2593988815-1116</NonMember>
      <NonMember>S-1-5-21-3104031619-1062013444-2593988815-1119</NonMember>
      <AppMemberLink>2db22bd5-4395-4645-9950-5509eb9d83b1</AppMemberLink>
    </AzApplicationGroup>
    <AzApplicationGroup Guid="f5fd6ac2-d435-4c51-8a9b-646d627ae448" Name="App Group #3 - Biz
Rule" Description="App Group #3 Desc - Biz Rule" GroupType="Bizrule">
      <BizRuleLanguage>JScript</BizRuleLanguage>
      <BizRule>
        AzBizRuleContext.BusinessRuleResult = false;
        dt = new Date();
        hour = dt.getHours();

        if (hour > 9 && hour < 17)
        {
          AzBizRuleContext.BusinessRuleResult = true;
        }
      </BizRule>
      <BizRuleImportedPath>C:\Users\Administrator\Desktop\bizrule1.js</BizRuleImportedPath>
    </AzApplicationGroup>
    <AzTask Guid="82a494ed-dec3-4ae9-92a1-1d9e5fe436b1" Name="Role Definition #1"
Description="Desc - Role Definition #1" BizRuleImportedPath="" RoleDefinition="True">
      <TaskLink>26834981-a122-4fd1-9f00-8ff2b63f7f49</TaskLink>
    </AzTask>
    <AzOperation Guid="8f274e4c-3f73-4b56-85ee-df83df9d313a" Name="Operation #1"
Description="Desc - Operation #1">
      <OperationID>1</OperationID>
    </AzOperation>
    <AzOperation Guid="943864c8-869f-4ef4-9c84-e51fc380bb99" Name="Operation #2"
Description="Desc - Operation #2">
      <OperationID>2</OperationID>
    </AzOperation>
    <AzTask Guid="26834981-a122-4fd1-9f00-8ff2b63f7f49" Name="Task #1" Description="Desc -
Task #1" BizRuleImportedPath="">
      <OperationLink>8f274e4c-3f73-4b56-85ee-df83df9d313a</OperationLink>
      <OperationLink>943864c8-869f-4ef4-9c84-e51fc380bb99</OperationLink>
    </AzTask>
    <AzRole Guid="831d638d-9f9e-4883-a024-360f82afc705" Name="Role Assignment #1"
Description="Role Assignment #1">
      <TaskLink>82a494ed-dec3-4ae9-92a1-1d9e5fe436b1</TaskLink>
      <Member>S-1-5-21-1022818538-2633080746-2542160322-501</Member>
      <AppMemberLink>3736a1f3-3f3d-44f7-9fa4-eb6f9032e962</AppMemberLink>
      <AppMemberLink>99f5aabc-3c3a-47a8-8b0a-d5aa373c33e4</AppMemberLink>
    </AzRole>
    <AzApplicationGroup Guid="2ebce7bb-d172-46a8-8844-c1d7638103dd" Name="App Group #2 - Ldap
Query Group" Description="App Group #2 - Ldap Query Group" GroupType="LdapQuery">
      <BizRuleLanguage></BizRuleLanguage>
      <LdapQuery>(&(& (objectCategory=person) (objectClass=user) (cn=david
mowers))</LdapQuery>
    </AzApplicationGroup>
    <AzApplicationGroup Guid="ab24f52f-ab12-43ff-818d-e6de1492acbf" Name="App Group #4 - Biz
Rule VBS" Description="App Group #4 - Biz Rule VBS" GroupType="Bizrule">
      <BizRuleLanguage>VBScript</BizRuleLanguage>
      <BizRule>
```

```
AzBizRuleContext.BusinessRuleResult = FALSE
Dim Amount
Amount = AzBizRuleContext.GetParameter("Age")
if Amount &gt; 25 then AzBizRuleContext.BusinessRuleResult = TRUE
</BizRule>
<BizRuleImportedPath>C:\Users\Administrator\Desktop\bizrule2.vbs</BizRuleImportedPath>
</AzApplicationGroup>
</AzApplication>
<AzApplicationGroup Guid="99f5aabc-3c3a-47a8-8b0a-d5aa373c33e4" Name="AzMan Global Group#1
Basic Application Group" Description="AzMan Global Group#1-Desc" GroupType="Basic">
  <BizRuleLanguage></BizRuleLanguage>
</AzApplicationGroup>
<AzApplicationGroup Guid="2db22bd5-4395-4645-9950-5509eb9d83b1" Name="AzMan Global Group#2
LDAP Query Application Group" Description="AzMan Global Group#2-Desc" GroupType="LdapQuery">
  <BizRuleLanguage></BizRuleLanguage>
  <LdapQuery>This is the query</LdapQuery>
</AzApplicationGroup>
<AzApplicationGroup Guid="f2f3e0f1-4334-4736-b27d-b996240714ae" Name="AzMan Global Group#3
Business Rule Application Group" Description="AzMan Global Group#3-Desc" GroupType="Bizrule">
  <BizRuleLanguage>VBScript</BizRuleLanguage>
</AzApplicationGroup>
</AzAdminManager>
```

## **4 Security Considerations**

### **4.1 Security Considerations for Implementers**

None.

## 5 Appendix A: Full XML Schema

For ease of implementation, the following is the full XML schema for this protocol.

```
<?xml version="1.0" encoding="utf-8"?>
<xs:schema id="NewDataSet" xmlns="" xmlns:xs="http://www.w3.org/2001/XMLSchema"
xmlns:msdata="urn:schemas-microsoft-com:xml-msdata">
  <xs:element name="AzApplicationGroup">
    <xs:complexType>
      <xs:sequence>
        <xs:element name="BizRuleLanguage" type="xs:string" minOccurs="0" />
        <xs:element name="LdapQuery" type="xs:string" minOccurs="0" />
        <xs:element name="BizRule" type="xs:string" minOccurs="0" />
        <xs:element name="BizRuleImportedPath" type="xs:string" minOccurs="0" />
        <xs:element name="AppMemberLink" type="xs:string" minOccurs="0" />
        <xs:element name="Member" nillable="true" minOccurs="0" maxOccurs="unbounded">
          <xs:complexType>
            <xs:simpleContent >
              <xs:extension base="xs:string">
            </xs:extension>
            </xs:simpleContent>
          </xs:complexType>
        </xs:element>
        <xs:element name="NonMember" nillable="true" minOccurs="0" maxOccurs="unbounded">
          <xs:complexType>
            <xs:simpleContent >
              <xs:extension base="xs:string">
            </xs:extension>
            </xs:simpleContent>
          </xs:complexType>
        </xs:element>
      </xs:sequence>
      <xs:attribute name="Guid" type="xs:string" />
      <xs:attribute name="Name" type="xs:string" />
      <xs:attribute name="Description" type="xs:string" />
      <xs:attribute name="GroupType" type="xs:string" />
    </xs:complexType>
  </xs:element>
  <xs:element name="AzTask">
    <xs:complexType>
      <xs:sequence>
        <xs:element name="TaskLink" type="xs:string" minOccurs="0" />
        <xs:element name="OperationLink" nillable="true" minOccurs="0" maxOccurs="unbounded">
          <xs:complexType>
            <xs:simpleContent >
              <xs:extension base="xs:string">
            </xs:extension>
            </xs:simpleContent>
          </xs:complexType>
        </xs:element>
      </xs:sequence>
      <xs:attribute name="Guid" type="xs:string" />
      <xs:attribute name="Name" type="xs:string" />
      <xs:attribute name="Description" type="xs:string" />
      <xs:attribute name="BizRuleImportedPath" type="xs:string" />
      <xs:attribute name="RoleDefinition" type="xs:string" />
    </xs:complexType>
  </xs:element>
  <xs:element name="AzRole">
    <xs:complexType>
      <xs:sequence>
        <xs:element name="TaskLink" type="xs:string" minOccurs="0" />
        <xs:element name="Member" type="xs:string" minOccurs="0" />
        <xs:element name="AppMemberLink" nillable="true" minOccurs="0" maxOccurs="unbounded">
          <xs:complexType>
            <xs:simpleContent >
              <xs:extension base="xs:string">
            </xs:extension>
            </xs:simpleContent>
          </xs:complexType>
        </xs:element>
      </xs:sequence>
    </xs:complexType>
  </xs:element>
</xs:schema>
```

```

        </xs:extension>
      </xs:simpleContent>
    </xs:complexType>
  </xs:element>
</xs:sequence>
<xs:attribute name="Guid" type="xs:string" />
<xs:attribute name="Name" type="xs:string" />
<xs:attribute name="Description" type="xs:string" />
</xs:complexType>
</xs:element>
<xs:element name="AzAdminManager">
  <xs:complexType>
    <xs:sequence>
      <xs:element name="AzApplication" minOccurs="0" maxOccurs="unbounded">
        <xs:complexType>
          <xs:sequence>
            <xs:element ref="AzApplicationGroup" minOccurs="0" maxOccurs="unbounded" />
            <xs:element ref="AzTask" minOccurs="0" maxOccurs="unbounded" />
            <xs:element name="AzOperation" minOccurs="0" maxOccurs="unbounded">
              <xs:complexType>
                <xs:sequence>
                  <xs:element name="OperationID" type="xs:string" minOccurs="0" />
                </xs:sequence>
              </xs:complexType>
            </xs:element>
            <xs:element ref="AzRole" minOccurs="0" maxOccurs="unbounded" />
            <xs:element name="AzScope" minOccurs="0" maxOccurs="unbounded">
              <xs:complexType>
                <xs:sequence>
                  <xs:element ref="AzApplicationGroup" minOccurs="0" maxOccurs="unbounded" />
                  <xs:element ref="AzTask" minOccurs="0" maxOccurs="unbounded" />
                  <xs:element ref="AzRole" minOccurs="0" maxOccurs="unbounded" />
                </xs:sequence>
              </xs:complexType>
            </xs:element>
            <xs:sequence>
              <xs:attribute name="Guid" type="xs:string" />
              <xs:attribute name="Name" type="xs:string" />
              <xs:attribute name="Description" type="xs:string" />
            </xs:complexType>
          </xs:sequence>
          <xs:attribute name="Guid" type="xs:string" />
          <xs:attribute name="Name" type="xs:string" />
          <xs:attribute name="Description" type="xs:string" />
          <xs:attribute name="ApplicationVersion" type="xs:string" />
        </xs:complexType>
      </xs:element>
      <xs:element ref="AzApplicationGroup" minOccurs="0" maxOccurs="unbounded" />
    </xs:sequence>
    <xs:attribute name="MajorVersion" type="xs:string" />
    <xs:attribute name="MinorVersion" type="xs:string" />
    <xs:attribute name="Guid" type="xs:string" />
    <xs:attribute name="Description" type="xs:string" />
  </xs:complexType>
</xs:element>
<xs:element name="NewDataSet" >
  <xs:complexType>
    <xs:choice minOccurs="0" maxOccurs="unbounded">
      <xs:element ref="AzApplicationGroup" />
      <xs:element ref="AzTask" />
      <xs:element ref="AzRole" />
      <xs:element ref="AzAdminManager" />
    </xs:choice>
  </xs:complexType>
</xs:element>
</xs:schema>

```

## 6 Appendix B: Product Behavior

The information in this specification is applicable to the following Microsoft products or supplemental software. References to product versions include released service packs.

Note: Some of the information in this section is subject to change because it applies to a preliminary product version, and thus may differ from the final version of the software when released. All behavior notes that pertain to the preliminary product version contain specific references to it as an aid to the reader.

- Windows XP operating system
- Windows Server 2003 operating system
- Windows Server 2003 R2 operating system
- Windows Vista operating system
- Windows Server 2008 operating system
- Windows 7 operating system
- Windows Server 2008 R2 operating system
- Windows 8 operating system
- Windows Server 2012 operating system
- Windows 8.1 operating system
- Windows Server 2012 R2 operating system
- Windows 10 operating system
- Windows Server 2016 Technical Preview operating system

Exceptions, if any, are noted below. If a service pack or Quick Fix Engineering (QFE) number appears with the product version, behavior changed in that service pack or QFE. The new behavior also applies to subsequent service packs of the product unless otherwise specified. If a product edition appears with the product version, behavior is different in that product edition.

Unless otherwise specified, any statement of optional behavior in this specification that is prescribed using the terms SHOULD or SHOULD NOT implies product behavior in accordance with the SHOULD or SHOULD NOT prescription. Unless otherwise specified, the term MAY implies that the product does not follow the prescription.

[<1> Section 1.6](#): Windows XP, Windows Server 2003, Windows Server 2003 R2, and Windows Vista do not support the version 2.0 schema.



## 7 Change Tracking

No table of changes is available. The document is either new or has had no changes since its last release.

## 8 Index

### A

[Applicability](#) 5

### C

[Change tracking](#) 17

### E

[Examples](#) 11

### F

[Fields - vendor-extensible](#) 5

[Full XML schema](#) 14

### G

[Glossary](#) 4

### I

[Implementer - security considerations](#) 13

[Informative references](#) 5

[Introduction](#) 4

### L

[Localization](#) 5

### N

[Normative references](#) 4

### O

[Overview \(synopsis\)](#) 5

### P

[Product behavior](#) 16

### R

[References](#) 4

[informative](#) 5

[normative](#) 4

[Relationship to protocols and other structures](#) 5

### S

Security

[implementer considerations](#) 13

[Security - implementer considerations](#) 13

### T

[Tracking changes](#) 17

### V

[Vendor-extensible fields](#) 5

[Versioning](#) 5

### X

[XML](#) 14

[XML schema](#) 14