

[MS-GPSB]: Group Policy: Security Protocol Extension

This topic lists the Errata found in [MS-GPSB] since it was last published. Since this topic is updated frequently, we recommend that you subscribe to these RSS or Atom feeds to receive update notifications.



Errata are subject to the same terms as the Open Specifications documentation referenced.

Errata below are for Protocol Document Version [V21.0 – 2017/12/01](#).

Errata Published*	Description
2018/07/02	<p>In Section 2.2, Message Syntax, the syntax was changed from:</p> <pre>InfFile = UnicodePreamble VersionPreamble Sections UnicodePreamble = *("[Unicode]" LineBreak "Unicode=yes" LineBreak) VersionPreamble = "[Version]" LineBreak "signature=" DQUOTE "\$CHICAGO\$" DQUOTE LineBreak "Revision=1" LineBreak Sections = Section / Section Sections Section = Header Settings Header = "[" HeaderValue "]" LineBreak HeaderValue = stringWithSpaces Settings = Setting / Setting Settings Setting = Key Wsp "=" Wsp ValueList LineBreak / ValueList = Value / Value Wsp "," Wsp ValueList Key = String Value = String / QuotedString</pre> <p>Changed to:</p> <pre>InfFile = UnicodePreamble VersionPreamble Sections UnicodePreamble = *("[Unicode]" LineBreak "Unicode=yes" LineBreak) VersionPreamble = "[Version]" LineBreak "signature=" DQUOTE "\$CHICAGO\$" DQUOTE LineBreak "Revision=1" LineBreak Sections = Section / Section Sections Section = Header Settings Header = "[" HeaderValue "]" LineBreak HeaderValue = stringWithSpaces Settings = Setting / Setting Settings Setting = Key Wsp "=" Wsp ValueList LineBreak / Name ", " Mode ", " AclString LineBreak Name = String / QuotedString Mode = [0-9]+ AclString = SDDL / DQUOTE SDDL DQUOTE ValueList = Value / Value Wsp "," Wsp ValueList Key = String Value = String / QuotedString</pre> <p>Also, throughout this section, "Service General Settings" was changed to "Service General Setting".</p> <p>In Section 2.2.8, Service General Settings, the section title was changed to Service General Setting.</p>

Errata Published*	Description
	<p>In this section the syntax was changed from:</p> <pre>Header = "[" HeaderValue "]" LineBreak HeaderValue = "Service General Setting" Settings = Setting / Setting Settings ServiceName = 1*256IdCharacter / DQUOTE 1*256IdCharacter DQUOTE IdCharacter = ALPHANUM/ %d33 / %d35-43 / %d45-46 / %d58-64 / %d91 / %d93-96 / %d123-126 Setting = ServiceName "," StartupMode "," AclString LineBreak StartupMode = DIGIT AclString = SDDL / DQUOTE SDDL DQUOTE</pre> <p>Changed to:</p> <pre>Header = "[" HeaderValue "]" LineBreak HeaderValue = "Service General Setting" Settings = Setting / Setting Settings Setting = ServiceName "," StartupMode "," AclString LineBreak ServiceName = 1*256IdCharacter / DQUOTE 1*256IdCharacter DQUOTE IdCharacter = ALPHANUM/ %d33 / %d35-43 / %d45-46 / %d58-64 / %d91 / %d93-96 / %d123-126 StartupMode = DIGIT AclString = SDDL / DQUOTE SDDL DQUOTE</pre> <p>In Section 3.2.5.10, Service General Setting, "Service General Settings" was changed to "Service General Setting" throughout.</p>

*Date format: YYYY/MM/DD