

## [MS-IRP-Diff]:

# Internet Information Services (IIS) Inetinfo Remote Protocol

---

### Intellectual Property Rights Notice for Open Specifications Documentation

- **Technical Documentation.** Microsoft publishes Open Specifications documentation (“this documentation”) for protocols, file formats, data portability, computer languages, and standards support. Additionally, overview documents cover inter-protocol relationships and interactions.
- **Copyrights.** This documentation is covered by Microsoft copyrights. Regardless of any other terms that are contained in the terms of use for the Microsoft website that hosts this documentation, you can make copies of it in order to develop implementations of the technologies that are described in this documentation and can distribute portions of it in your implementations that use these technologies or in your documentation as necessary to properly document the implementation. You can also distribute in your implementation, with or without modification, any schemas, IDLs, or code samples that are included in the documentation. This permission also applies to any documents that are referenced in the Open Specifications documentation.
- **No Trade Secrets.** Microsoft does not claim any trade secret rights in this documentation.
- **Patents.** Microsoft has patents that might cover your implementations of the technologies described in the Open Specifications documentation. Neither this notice nor Microsoft's delivery of this documentation grants any licenses under those patents or any other Microsoft patents. However, a given Open Specifications document might be covered by the Microsoft [Open Specifications Promise](#) or the [Microsoft Community Promise](#). If you would prefer a written license, or if the technologies described in this documentation are not covered by the Open Specifications Promise or Community Promise, as applicable, patent licenses are available by contacting [iplg@microsoft.com](mailto:iplg@microsoft.com).
- **License Programs.** To see all of the protocols in scope under a specific license program and the associated patents, visit the [Patent Map](#).
- **Trademarks.** The names of companies and products contained in this documentation might be covered by trademarks or similar intellectual property rights. This notice does not grant any licenses under those rights. For a list of Microsoft trademarks, visit [www.microsoft.com/trademarks](http://www.microsoft.com/trademarks).
- **Fictitious Names.** The example companies, organizations, products, domain names, email addresses, logos, people, places, and events that are depicted in this documentation are fictitious. No association with any real company, organization, product, domain name, email address, logo, person, place, or event is intended or should be inferred.

**Reservation of Rights.** All other rights are reserved, and this notice does not grant any rights other than as specifically described above, whether by implication, estoppel, or otherwise.

**Tools.** The Open Specifications documentation does not require the use of Microsoft programming tools or programming environments in order for you to develop an implementation. If you have access to Microsoft programming tools and environments, you are free to take advantage of them. Certain Open Specifications documents are intended for use in conjunction with publicly available standards specifications and network programming art and, as such, assume that the reader either is familiar with the aforementioned material or has immediate access to it.

**Support.** For questions and support, please contact [dochelp@microsoft.com](mailto:dochelp@microsoft.com).

## Revision Summary

Date	Revision History	Revision Class	Comments
7/20/2007	0.1	Major	MCPP Milestone 5 Initial Availability
9/28/2007	0.2	Minor	Clarified the meaning of the technical content.
10/23/2007	0.2.1	Editorial	Changed language and formatting in the technical content.
11/30/2007	0.2.2	Editorial	Changed language and formatting in the technical content.
1/25/2008	0.2.3	Editorial	Changed language and formatting in the technical content.
3/14/2008	1.0	Major	Updated and revised the technical content.
5/16/2008	1.0.1	Editorial	Changed language and formatting in the technical content.
6/20/2008	1.1	Minor	Clarified the meaning of the technical content.
7/25/2008	1.2	Minor	Clarified the meaning of the technical content.
8/29/2008	2.0	Major	Updated and revised the technical content.
10/24/2008	2.0.1	Editorial	Changed language and formatting in the technical content.
12/5/2008	2.0.2	Editorial	Changed language and formatting in the technical content.
1/16/2009	3.0	Major	Updated and revised the technical content.
2/27/2009	3.0.1	Editorial	Changed language and formatting in the technical content.
4/10/2009	3.0.2	Editorial	Changed language and formatting in the technical content.
5/22/2009	3.0.3	Editorial	Changed language and formatting in the technical content.
7/2/2009	3.0.4	Editorial	Changed language and formatting in the technical content.
8/14/2009	3.1	Minor	Clarified the meaning of the technical content.
9/25/2009	3.2	Minor	Clarified the meaning of the technical content.
11/6/2009	3.2.1	Editorial	Changed language and formatting in the technical content.
12/18/2009	3.2.2	Editorial	Changed language and formatting in the technical content.
1/29/2010	4.0	Major	Updated and revised the technical content.
3/12/2010	4.0.1	Editorial	Changed language and formatting in the technical content.
4/23/2010	4.0.2	Editorial	Changed language and formatting in the technical content.
6/4/2010	4.0.3	Editorial	Changed language and formatting in the technical content.
7/16/2010	4.0.3	None	No changes to the meaning, language, or formatting of the technical content.
8/27/2010	4.0.3	None	No changes to the meaning, language, or formatting of the technical content.
10/8/2010	4.0.3	None	No changes to the meaning, language, or formatting of the technical content.

<b>Date</b>	<b>Revision History</b>	<b>Revision Class</b>	<b>Comments</b>
11/19/2010	4.0.3	None	No changes to the meaning, language, or formatting of the technical content.
1/7/2011	4.0.3	None	No changes to the meaning, language, or formatting of the technical content.
2/11/2011	4.0.3	None	No changes to the meaning, language, or formatting of the technical content.
3/25/2011	4.0.3	None	No changes to the meaning, language, or formatting of the technical content.
5/6/2011	4.0.3	None	No changes to the meaning, language, or formatting of the technical content.
6/17/2011	4.1	Minor	Clarified the meaning of the technical content.
9/23/2011	4.1	None	No changes to the meaning, language, or formatting of the technical content.
12/16/2011	5.0	Major	Updated and revised the technical content.
3/30/2012	5.0	None	No changes to the meaning, language, or formatting of the technical content.
7/12/2012	5.0	None	No changes to the meaning, language, or formatting of the technical content.
10/25/2012	5.0	None	No changes to the meaning, language, or formatting of the technical content.
1/31/2013	5.0	None	No changes to the meaning, language, or formatting of the technical content.
8/8/2013	6.0	Major	Updated and revised the technical content.
11/14/2013	6.0	None	No changes to the meaning, language, or formatting of the technical content.
2/13/2014	6.0	None	No changes to the meaning, language, or formatting of the technical content.
5/15/2014	6.0	None	No changes to the meaning, language, or formatting of the technical content.
6/30/2015	7.0	Major	Significantly changed the technical content.
10/16/2015	7.0	None	No changes to the meaning, language, or formatting of the technical content.
7/14/2016	7.0	None	No changes to the meaning, language, or formatting of the technical content.
6/1/2017	8.0	Major	Significantly changed the technical content.
9/15/2017	9.0	Major	Significantly changed the technical content.
12/1/2017	9.0	None	No changes to the meaning, language, or formatting of the technical content.
9/12/2018	10.0	Major	Significantly changed the technical content.

Date	Revision History	Revision Class	Comments
4/7/2021	11.0	Major	Significantly changed the technical content.
6/25/2021	12.0	Major	Significantly changed the technical content.

# Table of Contents

<b>1</b>	<b>Introduction</b>	<b>7</b>
1.1	Glossary	7
1.2	References	8
1.2.1	Normative References	9
1.2.2	Informative References	9
1.3	Overview	9
1.4	Relationship to Other Protocols	10
1.5	Prerequisites/Preconditions	10
1.6	Applicability Statement	10
1.7	Versioning and Capability Negotiation	10
1.8	Vendor-Extensible Fields	10
1.9	Standards Assignments	10
<b>2</b>	<b>Messages</b>	<b>11</b>
2.1	Transport	11
2.1.1	Server	11
2.1.2	Client	11
2.2	Common Data Types	11
2.2.1	INET_INFO_IMPERSONATE_HANDLE	11
2.2.2	Internet Protocol Server Identifiers	12
2.2.3	INET_INFO_CONFIG_INFO	12
2.2.4	INET_LOG_CONFIGURATION	15
2.2.5	INET_INFO_IP_SEC_LIST	16
2.2.6	INET_INFO_IP_SEC_ENTRY	16
2.2.7	INET_INFO_VIRTUAL_ROOT_LIST	17
2.2.8	INET_INFO_VIRTUAL_ROOT_ENTRY	17
2.2.9	INET_INFO_SITE_LIST	17
2.2.10	INET_INFO_SITE_ENTRY	18
2.2.11	INET_INFO_GLOBAL_CONFIG_INFO	18
2.2.12	INET_INFO_STATISTICS_INFO	18
2.2.13	INET_INFO_STATISTICS_0	19
2.2.14	INETA_ATQ_STATISTICS	19
2.2.15	INETA_CACHE_STATISTICS	20
2.2.16	INET_INFO_CAPABILITIES_STRUCT	21
2.2.17	INET_INFO_CAP_FLAGS	22
2.2.18	W3_STATISTICS_STRUCT	24
2.2.19	W3_STATISTICS_1	25
2.2.20	FTP_STATISTICS_STRUCT	27
2.2.21	FTP_STATISTICS_0	28
2.2.22	IIS_USER_ENUM_STRUCT	29
2.2.23	IIS_USER_INFO_1_CONTAINER	29
2.2.24	IIS_USER_INFO_1	30
2.2.25	Common Error Codes	30
<b>3</b>	<b>Protocol Details</b>	<b>31</b>
3.1	Inetinfo Server Details	31
3.1.1	Abstract Data Model	31
3.1.2	Timers	31
3.1.3	Initialization	31
3.1.4	Higher-Layer Triggered Events	31
3.1.5	Message Processing Events and Sequencing Rules	31
3.1.5.1	R_InetInfoGetVersion (Opnum 0)	34
3.1.5.2	R_InetInfoGetAdminInformation (Opnum 1)	35
3.1.5.3	R_InetInfoGetSites (Opnum 2)	35
3.1.5.4	R_InetInfoSetAdminInformation (Opnum 3)	36

3.1.5.5	R_InetInfoGetGlobalAdminInformation (Opnum 4)	37
3.1.5.6	R_InetInfoSetGlobalAdminInformation (Opnum 5)	37
3.1.5.7	R_InetInfoQueryStatistics (Opnum 6)	38
3.1.5.8	R_InetInfoClearStatistics (Opnum 7)	39
3.1.5.9	R_InetInfoFlushMemoryCache (Opnum 8)	39
3.1.5.10	R_InetInfoGetServerCapabilities (Opnum 9)	40
3.1.5.11	R_W3QueryStatistics2 (Opnum 10)	40
3.1.5.12	R_W3ClearStatistics2 (Opnum 11)	41
3.1.5.13	R_FtpQueryStatistics2 (Opnum 12)	42
3.1.5.14	R_FtpClearStatistics2 (Opnum 13)	43
3.1.5.15	R_IISEnumerateUsers (Opnum 14)	44
3.1.5.16	R_IISDisconnectUser (Opnum 15)	44
3.1.6	Timer Events	45
3.1.7	Other Local Events	45
<b>4</b>	<b>Protocol Examples</b>	<b>46</b>
<b>5</b>	<b>Security</b>	<b>47</b>
5.1	Security Considerations for Implementers	47
5.2	Index of Security Parameters	47
<b>6</b>	<b>Appendix A: Full IDL</b>	<b>48</b>
<b>7</b>	<b>(Updated Section) Appendix B: Product Behavior</b>	<b>55</b>
<b>8</b>	<b>Change Tracking</b>	<b>59</b>
<b>9</b>	<b>Index</b>	<b>60</b>

# 1 Introduction

The Internet Information Services (IIS) Inetinfo Remote Protocol is a remote procedure call (RPC)-based client/server protocol that is used for managing Internet protocol servers such as those hosted by Microsoft Internet Information Services (IIS). Managed servers can include servers for HTTP, FTP, SMTP, or other Internet protocols. For more information on IIS, see [MSDN-IIS].

The universally unique identifier (UUID) for the IIS Inetinfo Remote Protocol interface is {82ad4280-036b-11cf-972c-00aa006887b0}.

The version for this interface is 2.0.

Sections 1.5, 1.8, 1.9, 2, and 3 of this specification are normative. All other sections and examples in this specification are informative.

## 1.1 Glossary

This document uses the following terms:

**authentication level:** A numeric value indicating the level of authentication or message protection that remote procedure call (RPC) will apply to a specific message exchange. For more information, see [C706] section 13.1.2.1 and [MS-RPCE].

**Authentication Service (AS):** A service that issues ticket granting tickets (TGTs), which are used for authenticating principals within the realm or domain served by the Authentication Service.

**Binary Gateway Interface (BGI):** An extension API for HTTP servers that is analogous to the Common Gateway Interface (CGI) but relies on direct method calls and parameter passing. In the IIS HTTP server, BGI is equivalent to the Internet Server API (ISAPI).

**binary large object (BLOB):** A discrete packet of data that is stored in a database and is treated as a sequence of uninterpreted bytes.

**endpoint:** (1) A client that is on a network and is requesting access to a network access server (NAS).

(2) A network-specific address of a remote procedure call (RPC) server process for remote procedure calls. The actual name and type of the endpoint depends on the RPC protocol sequence that is being used. For example, for RPC over TCP (RPC Protocol Sequence `ncacn_ip_tcp`), an endpoint might be TCP port 1025. For RPC over Server Message Block (RPC Protocol Sequence `ncacn_np`), an endpoint might be the name of a named pipe. For more information, see [C706].

**Interface Definition Language (IDL):** The International Standards Organization (ISO) standard language for specifying the interface for remote procedure calls. For more information, see [C706] section 4.

**Internet Information Services (IIS):** The services provided in Windows implementation that support web server functionality. IIS consists of a collection of standard Internet protocol servers such as HTTP and FTP in addition to common infrastructures that are used by other Microsoft Internet protocol servers such as SMTP, NNTP, and so on. IIS has been part of the Windows operating system in some versions and a separate install package in others. IIS version 5.0 shipped as part of Windows 2000 operating system, IIS version 5.1 as part of Windows XP operating system, IIS version 6.0 as part of Windows Server 2003 operating system, and IIS version 7.0 as part of Windows Vista operating system and Windows Server 2008 operating system.

**Internet protocol server:** A software program that implements the server host of a standard Internet protocol such as HTTP or FTP.

**Internet protocol server instance (server instance):** A configuration collection for an Internet protocol server that will establish its own network protocol endpoint. A single Internet protocol server may configure multiple server instances that would each appear to clients as an independent host (also referred to as a site).

**network byte order:** The order in which the bytes of a multiple-byte number are transmitted on a network, most significant byte first (in big-endian storage). This may or may not match the order in which numbers are normally stored in memory for a particular processor.

**opnum:** An operation number or numeric identifier that is used to identify a specific remote procedure call (RPC) method or a method in an interface. For more information, see [C706] section 12.5.2.12 or [MS-RPCE].

**remote procedure call (RPC):** A communication protocol used primarily between client and server. The term has three definitions that are often used interchangeably: a runtime environment providing for communication facilities between computers (the RPC runtime); a set of request-and-response message exchanges between computers (the RPC exchange); and the single message from an RPC exchange (the RPC message). For more information, see [C706].

**RPC client:** A computer on the network that sends messages using remote procedure call (RPC) as its transport, waits for responses, and is the initiator in an RPC exchange.

**RPC protocol sequence:** A character string that represents a valid combination of a remote procedure call (RPC) protocol, a network layer protocol, and a transport layer protocol, as described in [C706] and [MS-RPCE].

**Server Message Block (SMB):** A protocol that is used to request file and print services from server systems over a network. The SMB protocol extends the CIFS protocol with additional security, file, and disk management support. For more information, see [CIFS] and [MS-SMB].

**stub:** Used as specified in [C706] section 2.1.2.2. A stub that is used on the client is called a "client stub", and a stub that is used on the server is called a "server stub".

**universally unique identifier (UUID):** A 128-bit value. UUIDs can be used for multiple purposes, from tagging objects with an extremely short lifetime, to reliably identifying very persistent objects in cross-process communication such as client and server interfaces, manager entry-point vectors, and RPC objects. UUIDs are highly likely to be unique. UUIDs are also known as globally unique identifiers (GUIDs) and these terms are used interchangeably in the Microsoft protocol technical documents (TDs). Interchanging the usage of these terms does not imply or require a specific algorithm or mechanism to generate the UUID. Specifically, the use of this term does not imply or require that the algorithms described in [RFC4122] or [C706] must be used for generating the UUID.

**virtual root:** A configured mapping within an Internet protocol server instance between an instance URI and a file system directory. For example, a virtual root could map the URI "/somepath" to the file system directory "d:\webcontent". For more information about the syntax of a URI, see [RFC3986].

**well-known endpoint:** A preassigned, network-specific, stable address for a particular client/server instance. For more information, see [C706].

**MAY, SHOULD, MUST, SHOULD NOT, MUST NOT:** These terms (in all caps) are used as defined in [RFC2119]. All statements of optional behavior use either MAY, SHOULD, or SHOULD NOT.

## 1.2 References

Links to a document in the Microsoft Open Specifications library point to the correct section in the most recently published version of the referenced document. However, because individual documents



in the library are not updated at the same time, the section numbers in the documents may not match. You can confirm the correct section numbering by checking the Errata.

### 1.2.1 Normative References

We conduct frequent surveys of the normative references to assure their continued availability. If you have any issue with finding a normative reference, please contact [dochelp@microsoft.com](mailto:dochelp@microsoft.com). We will assist you in finding the relevant information.

[MS-DTYP] Microsoft Corporation, "Windows Data Types".

[MS-ERREF] Microsoft Corporation, "Windows Error Codes".

[MS-LCID] Microsoft Corporation, "Windows Language Code Identifier (LCID) Reference".

[MS-RPCE] Microsoft Corporation, "Remote Procedure Call Protocol Extensions".

[RFC2119] Bradner, S., "Key words for use in RFCs to Indicate Requirement Levels", BCP 14, RFC 2119, March 1997, <http://www.rfc-editor.org/rfc/rfc2119.txt>

### 1.2.2 Informative References

[MSDN-IIS] Microsoft Corporation, "Internet Information Services (IIS)", <http://msdn.microsoft.com/en-us/library/aa286507.aspx>

[MSDN-MIDL] Microsoft Corporation, "Microsoft Interface Definition Language (MIDL)", <http://msdn.microsoft.com/en-us/library/ms950375.aspx>

[MSFT-CAL] Microsoft Corporation, "Client Access Licenses and Management Licenses", <https://www.microsoft.com/en-us/licensing/product-licensing/client-access-license.aspx>

[RFC2068] Fielding, R., Gettys, J., Mogul, J., et al., "Hypertext Transfer Protocol -- HTTP/1.1", RFC 2068, January 1997, <http://www.ietf.org/rfc/rfc2068.txt>

[RFC2518] Goland, Y., Whitehead, E., Faizi, A., et al., "HTTP Extensions for Distributed Authoring - WebDAV", RFC 2518, February 1999, <http://www.ietf.org/rfc/rfc2518.txt>

[RFC2818] Rescorla, E., "HTTP Over TLS", RFC 2818, May 2000, <http://www.rfc-editor.org/rfc/rfc2818.txt>

[RFC3875] Robinson, D., and Coar, K., "The Common Gateway Interface (CGI) Version 1.1", October 2004, <http://www.ietf.org/rfc/rfc3875>

## 1.3 Overview

The Internet Information Services (IIS) Inetinfo Remote Protocol provides functions that allow remote administration and statistics gathering from an Internet protocol server such as a server implementing the HTTP or FTP protocol. The protocol provides methods for gathering statistical data on users, sites, requests, and performance. For more information about HTTP and securing HTTP connections, see [RFC2068] and [RFC2818].

The server does not maintain client state information. Although some client call sequences might be logically related, the protocol operation is stateless.

## **1.4 Relationship to Other Protocols**

The Internet Information Services (IIS) Inetinfo Remote Protocol uses RPC as its protocol transport, as specified in [MS-RPCE].

## **1.5 Prerequisites/Preconditions**

This protocol requires that the client and server be able to communicate by means of an RPC connection, as specified in section 2.1.

## **1.6 Applicability Statement**

The Internet Information Services (IIS) Inetinfo Remote Protocol is appropriate for managing an Internet protocol server or a collection of such servers on a remote computer.

## **1.7 Versioning and Capability Negotiation**

The Internet Information Services (IIS) Inetinfo Remote Protocol has been modified between versions of IIS in ways that make interoperability between different server implementations difficult. Modifications to the interface between IIS versions will be noted in section 2.2 or section 3.1.<1>

## **1.8 Vendor-Extensible Fields**

This protocol uses Win32 error codes. These values are taken from the Windows error number space as specified in [MS-ERREF] section 2.2. Vendors SHOULD reuse those values with their indicated meaning. Choosing any other value runs the risk of a collision in the future.

## **1.9 Standards Assignments**

None.

## 2 Messages

### 2.1 Transport

The Internet Information Services (IIS) Inetinfo Remote Protocol MUST use RPC as the transport protocol.

#### 2.1.1 Server

The server interface MUST be identified by UUID "82ad4280-036b-11cf-972c-00aa006887b0", version 2.0.

The server MUST specify RPC over Server Message Block (SMB) as the RPC protocol sequence to the RPC implementation (as specified in [MS-RPCE] section 2.1.1.2), using the RPC well-known endpoint `\PIPE\inetinfo`.

The server MUST also specify RPC over TCP/IP as an RPC protocol sequence to the RPC implementation, as specified in [MS-RPCE] section 2.1.1.1.

The server SHOULD specify "NTLM" (0xA) as the RPC authentication service, as specified in [MS-RPCE] section 3.<2>

#### 2.1.2 Client

The client SHOULD use RPC over SMB (`ncacn_np`) or RPC over TCP/IP (`ncacn_ip_tcp`) as the RPC protocol sequence to communicate with the server. Using other protocol sequences MAY work depending on the configuration and implementation of the server.

The client MAY use an authentication level of privacy to connect to the server and if the server does not support this authentication level, it MAY fall back to connection. Authentication levels are specified in [MS-RPCE].

### 2.2 Common Data Types

In addition to the RPC data types that are specified in [MS-RPCE], the sections that follow use the definitions of `DWORD`, `WCHAR`, `LPWSTR`, `LCID`, `LARGE_INTEGER`, and `BYTE`, as specified in [MS-DTYP].

For more information on the additional data types in the following sections, see [MSDN-MIDL].

#### 2.2.1 INET\_INFO\_IMPERSONATE\_HANDLE

The `INET_INFO_IMPERSONATE_HANDLE` type defines a pointer to an array of `WCHAR` elements. The client uses this pointer as a custom binding handle, which it converts to an explicit server binding handle for a target server. On the client, the value MUST be sufficient to generate an appropriate server binding handle. The value of this parameter MUST NOT be used on the server.

This type is declared as follows:

```
typedef [handle] [string] LPWSTR INET_INFO_IMPERSONATE_HANDLE;
```

## 2.2.2 Internet Protocol Server Identifiers

The service identifiers listed below are used by several methods of the Internet Information Services (IIS) Inetinfo Remote Protocol to indicate the type of Internet protocol server targeted by the method. Server implementations MAY implement the Internet Information Services (IIS) Inetinfo Remote Protocol for some or all of the server types specified below.

If the specified Internet protocol server is not being managed by an Internet Information Services (IIS) Inetinfo Remote Protocol implementation or if the server is unavailable or inactive, method calls that target that server SHOULD return `ERROR_SERVICE_NOT_ACTIVE`, as specified in section 2.2.7.

Constant/value	Description
<code>INET_FTP_SVC_ID</code> <code>0x00000001</code>	Identifies the File Transfer Protocol (FTP) service.
<code>INET_GOPHER_SVC_ID</code> <code>0x00000002</code>	Identifies the Gopher service.
<code>INET_HTTP_SVC_ID</code> <code>0x00000004</code>	Identifies the Hypertext Transfer Protocol (HTTP) service.
<code>INET_DNS_SVC_ID</code> <code>0x00000008</code>	Identifies the Domain Name System (DNS).
<code>INET_HTTP_PROXY</code> <code>0x00000010</code>	Identifies the HTTP proxy service.
<code>INET_NNTP_SVC_ID</code> <code>0x00000040</code>	Identifies the Network News Transfer Protocol (NNTP) service.
<code>INET_SMTP_SVC_ID</code> <code>0x00000080</code>	Identifies the Simple Mail Transfer Protocol (SMTP) service.
<code>INET_GATEWAY_SVC_ID</code> <code>0x00000100</code>	Identifies the Internet gateway service.
<code>INET_POP3_SVC_ID</code> <code>0x00000200</code>	Identifies the Post Office Protocol 3 (POP3) service.
<code>INET_CHAT_SVC_ID</code> <code>0x00000400</code>	Identifies the Internet Relay Chat (IRC) service.
<code>INET_LDAP_SVC_ID</code> <code>0x00000800</code>	Identifies the Lightweight Directory Access Protocol (LDAP) service.
<code>INET_IMAP_SVC_ID</code> <code>0x00001000</code>	Identifies the Internet Message Access Protocol (IMAP) service.

## 2.2.3 INET\_INFO\_CONFIG\_INFO

The `INET_INFO_CONFIG_INFO` structure stores configuration values for an Internet protocol server. <3>

This type is declared as follows:

```
typedef struct _INET_INFO_CONFIG_INFO {  
    DWORD FieldControl;
```

```

DWORD dwConnectionTimeout;
DWORD dwMaxConnections;
[string] LPWSTR lpszAdminName;
[string] LPWSTR lpszAdminEmail;
[string] LPWSTR lpszServerComment;
LPINET_LOG_CONFIGURATION lpLogConfig;
WORD LangId;
LCID LocalId;
BYTE ProductId[64];
BOOL fLogAnonymous;
BOOL fLogNonAnonymous;
[string] LPWSTR lpszAnonUserName;
WCHAR szAnonPassword[257];
DWORD dwAuthentication;
short sPort;
LPINET_INFO_IP_SEC_LIST DenyIPList;
LPINET_INFO_IP_SEC_LIST GrantIPList;
LPINET_INFO_VIRTUAL_ROOT_LIST VirtualRoots;
} INET_INFO_CONFIG_INFO,
*LPINET_INFO_CONFIG_INFO;

```

**FieldControl:** A 32-bit unsigned integer that specifies a bit field. This field specifies the values of the **INET\_INFO\_CONFIG\_INFO** structure that contain valid data. An implementation MUST set the flag corresponding to the structure field when returning or updating configuration data. This field MUST be set to a valid combination of the following values.

Name	Value
FC_INET_INFO_CONNECTION_TIMEOUT	0x00000001
FC_INET_INFO_MAX_CONNECTIONS	0x00000002
FC_INET_INFO_LOG_CONFIG	0x00000004
FC_INET_INFO_ADMIN_NAME	0x00000008
FC_INET_INFO_SERVER_COMMENT	0x00000010
FC_INET_INFO_ADMIN_EMAIL	0x00000020
FC_INET_INFO_HOST_NAME	0x00000040
FC_INET_INFO_SERVER_SIZE	0x00000080
FC_INET_INFO_DEF_LOGON_DOMAIN	0x00008000
FC_INET_INFO_AUTHENTICATION	0x00010000
FC_INET_INFO_ALLOW_ANONYMOUS	0x00020000
FC_INET_INFO_LOG_ANONYMOUS	0x00040000
FC_INET_INFO_LOG_NONANONYMOUS	0x00080000
FC_INET_INFO_ANON_USER_NAME	0x00100000
FC_INET_INFO_ANON_PASSWORD	0x00200000
FC_INET_INFO_PORT_NUMBER	0x00400000
FC_INET_INFO_SITE_SECURITY	0x00800000
FC_INET_INFO_VIRTUAL_ROOTS	0x01000000
FC_INET_INFO_SECURE_PORT_NUMBER	0x02000000

Name	Value
FC_INET_INFO_SERVER_NAME	0x04000000
FC_INET_INFO_AUTO_START	0x08000000
FC_INET_INFO_ADDRESS_TYPE	0x10000000
FC_INET_INFO_IP_ADDRESS	0x20000000

**dwConnectionTimeout:** The time limit to maintain an inactive connection specified as the number of seconds from the last request.

**dwMaxConnections:** The maximum number of allowed connections to the Internet protocol server.

**lpzAdminName:** A pointer to a null-terminated Unicode string that contains the name of the Internet protocol server administrator.

**lpzAdminEmail:** A pointer to a null-terminated Unicode string that contains the email address of the Internet protocol server administrator.

**lpzServerComment:** A pointer to a null-terminated Unicode string that contains a comment that describes the Internet protocol server instance.

**lpLogConfig:** A pointer to an INET\_LOG\_CONFIGURATION structure that specifies the configuration of the Internet protocol server log.

**LangId:** A WORD containing the language identifier, a standard international numerical identifier for the language in the country or region where the server is in use, as specified in [MS-LCID] section 2.1.

**LocalId:** A locale identifier that is a DWORD value that consists of a language identifier, such as one specified for the **LangID** member, combined with a sort identifier indicating location. For example, the **LangID** member might indicate French, where the **LocalID** indicates Canada. The **LocalID** member is given as specified in [MS-LCID] section 2.1.

**ProductId:** An array of 64 bytes that MAY contain a string value, which identifies the server implementation.

**fLogAnonymous:** A value that is set to TRUE if data transfers from anonymous users are to be logged.

**fLogNonAnonymous:** A value that is set to TRUE if data transfers from non-anonymous users are to be logged.

**lpzAnonUserName:** A pointer to a null-terminated Unicode string that contains the name requested and accepted from an anonymous user.

**szAnonPassword:** An array of 257 Unicode characters containing a null-terminated Unicode string that contains a password requested and accepted from an anonymous user.<4>

**dwAuthentication:** A value that indicates what authentication methods can be used.

**sPort:** A 16-bit unsigned integer that specifies the network port on which the Internet protocol server instance is running.

**DenyIPList:** A pointer to an INET\_INFO\_IP\_SEC\_LIST structure that contains a list of IP addresses that will be denied connections to the Internet protocol server.

**GrantIPList:** A pointer to an INET\_INFO\_IP\_SEC\_LIST structure that contains a list of IP addresses that will be granted connections to the Internet protocol server.

**VirtualRoots:** A pointer to an INET\_INFO\_VIRTUAL\_ROOT\_LIST structure that contains a list of virtual root directories for the Internet protocol server instance.

## 2.2.4 INET\_LOG\_CONFIGURATION

The **INET\_LOG\_CONFIGURATION** structure contains configuration information for Internet protocol server logging.

This type is declared as follows:

```
typedef struct _INET_LOG_CONFIGURATION {
    DWORD inetLogType;
    DWORD ilPeriod;
    WCHAR rgchLogFileDirectory[260];
    DWORD cbSizeForTruncation;
    WCHAR rgchDataSource[260];
    WCHAR rgchTableName[30];
    WCHAR rgchUserName[257];
    WCHAR rgchPassword[257];
} INET_LOG_CONFIGURATION,
*LPINET_LOG_CONFIGURATION;
```

**inetLogType:** A 32-bit integer that specifies the type of log to be written. This field **MUST** be set to one of the following values.

Value	Meaning
INET_LOG_DISABLED 0x00000000	Logging is disabled.
INET_LOG_TO_FILE 0x00000001	The log is written to a file.
INET_LOG_TO_SQL 0x00000002	The log is written to a Structured Query Language (SQL) database.
INET_LOG_INVALID 0xFFFFFFFF	The log is not valid.

**ilPeriod:** Specifies the periodicity of Internet protocol server logging. This field **MUST** be set to one of the following values.

Value	Meaning
INET_LOG_PERIOD_NONE 0x00000000	There is no log period.
INET_LOG_PERIOD_DAILY 0x00000001	The log period is daily.
INET_LOG_PERIOD_WEEKLY 0x00000002	The log period is weekly.
INET_LOG_PERIOD_MONTHLY 0x00000003	The log period is monthly.
INET_LOG_PERIOD_HOURLY 0x00000004	The log period is hourly.

Value	Meaning
INET_LOG_PERIOD_YEARLY 0x00000005	The log period is yearly.
INET_LOG_PERIOD_INVALID 0xFFFFFFFF	The log period is not valid.

**rgchLogFileDirectory:** A null-terminated string that specifies the destination of the Internet protocol server log.

**cbSizeForTruncation:** Specifies the maximum size in bytes for each log file.

**rgchDataSource:** A null-terminated string that specifies the Open Database Connectivity (ODBC) data source name to which the Internet protocol server log is to be written.

**rgchTableName:** A null-terminated string that specifies the name of the table on **rgchDataSource** to which the Internet protocol server log is to be written.

**rgchUserName:** A null-terminated string that specifies the name of the user for the ODBC connection.

**rgchPassword:** A null-terminated string that specifies the password associated with the **rgchUserName** user name.

## 2.2.5 INET\_INFO\_IP\_SEC\_LIST

The **INET\_INFO\_IP\_SEC\_LIST** structure contains a list of **INET\_INFO\_IP\_SEC\_ENTRY** entries.

This type is declared as follows:

```
typedef struct _INET_INFO_IP_SEC_LIST {
    DWORD cEntries;
    [size_is(cEntries)] INET_INFO_IP_SEC_ENTRY aIPSecEntry[];
} INET_INFO_IP_SEC_LIST,
*LPINET_INFO_IP_SEC_LIST;
```

**cEntries:** The number of entries contained in the list.

**aIPSecEntry:** An array of **INET\_INFO\_IP\_SEC\_ENTRY** entries.

## 2.2.6 INET\_INFO\_IP\_SEC\_ENTRY

The **INET\_INFO\_IP\_SEC\_ENTRY** structure contains Internet Protocol Security (IPv4) entries.

This type is declared as follows:

```
typedef struct _INET_INFO_IP_SEC_ENTRY {
    DWORD dwMask;
    DWORD dwNetwork;
} INET_INFO_IP_SEC_ENTRY,
*LPINET_INFO_IP_SEC_ENTRY;
```

**dwMask:** The subnet mask. Data is stored in network byte order.

**dwNetwork:** The IP address. Data is stored in network byte order.



## 2.2.7 INET\_INFO\_VIRTUAL\_ROOT\_LIST

The **INET\_INFO\_VIRTUAL\_ROOT\_LIST** structure contains a list of **INET\_INFO\_VIRTUAL\_ROOT\_ENTRY** virtual root entries.

This type is declared as follows:

```
typedef struct _INET_INFO_VIRTUAL_ROOT_LIST {
    DWORD cEntries;
    [size_is(cEntries)] INET_INFO_VIRTUAL_ROOT_ENTRY aVirtRootEntry[];
} INET_INFO_VIRTUAL_ROOT_LIST,
*LPINET_INFO_VIRTUAL_ROOT_LIST;
```

**cEntries:** The number of entries contained in the list.

**aVirtRootEntry:** An array of **INET\_INFO\_VIRTUAL\_ROOT\_ENTRY** entries.

## 2.2.8 INET\_INFO\_VIRTUAL\_ROOT\_ENTRY

The **INET\_INFO\_VIRTUAL\_ROOT\_ENTRY** structure contains data describing a virtual root for the Internet protocol server instance.

This type is declared as follows:

```
typedef struct _INET_INFO_VIRTUAL_ROOT_ENTRY {
    [string] LPWSTR pszRoot;
    [string] LPWSTR pszAddress;
    [string] LPWSTR pszDirectory;
    DWORD dwMask;
    [string] LPWSTR pszAccountName;
    WCHAR AccountPassword[257];
    DWORD dwError;
} INET_INFO_VIRTUAL_ROOT_ENTRY,
*LPINET_INFO_VIRTUAL_ROOT_ENTRY;
```

**pszRoot:** The virtual root name.

**pszAddress:** The optional IP address.

**pszDirectory:** The physical directory.

**dwMask:** The Access Mask for this virtual root.

**pszAccountName:** The account to connect as.

**AccountPassword:** Null-terminated WCHAR array containing the password for **pszAccountName**.<5>

**dwError:** The error code stored for the virtual root.

## 2.2.9 INET\_INFO\_SITE\_LIST

The **INET\_INFO\_SITE\_LIST** structure contains a list of **INET\_INFO\_SITE\_ENTRY** site entries.

This type is declared as follows:

```
typedef struct _INET_INFO_SITE_LIST {
    DWORD cEntries;
    [size_is(cEntries)] INET_INFO_SITE_ENTRY aSiteEntry[];
} INET_INFO_SITE_LIST,
```

```
*LPINET_INFO_SITE_LIST;
```

**cEntries:** The number of entries contained in the list.

**aSiteEntry:** An array of **INET\_INFO\_SITE\_ENTRY** site entries.

## 2.2.10 INET\_INFO\_SITE\_ENTRY

The **INET\_INFO\_SITE\_ENTRY** structure contains information describing an Internet protocol server instance.

This type is declared as follows:

```
typedef struct _INET_INFO_SITE_ENTRY {  
    [string] LPWSTR pszComment;  
    DWORD dwInstance;  
} INET_INFO_SITE_ENTRY,  
*LPINET_INFO_SITE_ENTRY;
```

pszComment: The server instance comment.

dwInstance: The server instance identifier.

## 2.2.11 INET\_INFO\_GLOBAL\_CONFIG\_INFO

The **INET\_INFO\_GLOBAL\_CONFIG\_INFO** structure contains configuration data global to all the Internet protocol services managed by this protocol.

This type is declared as follows:

```
typedef struct _INET_INFO_GLOBAL_CONFIG_INFO {  
    DWORD FieldControl;  
    DWORD BandwidthLevel;  
    DWORD cbMemoryCacheSize;  
} INET_INFO_GLOBAL_CONFIG_INFO,  
*LPINET_INFO_GLOBAL_CONFIG_INFO;
```

**FieldControl:** A bit-field that specifies the values of the **INET\_INFO\_GLOBAL\_CONFIG\_INFO** structure that have been initialized. An implementation MUST set the flag corresponding to the structure field when returning or updating configuration data. This field MUST be set to a valid combination of the following values.

Value	Meaning
0x00000001	FC_GINET_INFO_BANDWIDTH_LEVEL
0x00000002	FC_GINET_INFO_MEMORY_CACHE_SIZE

**BandwidthLevel:** The bytes per second to send over the network for the Internet protocol servers.

**cbMemoryCacheSize:** The size of the in-memory file cache for the Internet protocol servers.

## 2.2.12 INET\_INFO\_STATISTICS\_INFO

The **INET\_INFO\_STATISTICS\_INFO** union contains a pointer to an **INET\_INFO\_STATISTICS\_0** structure.

This type is declared as follows:

```
typedef
[switch_type(unsigned long)]
union _INET_INFO_STATISTICS_INFO {
    [case(0)]
        LPINET_INFO_STATISTICS_0 InetStats0;
    [default]
        ;
} INET_INFO_STATISTICS_INFO,
*LPINET_INFO_STATISTICS_INFO;
```

**InetStats0:** The pointer to an **INET\_INFO\_STATISTICS\_0** structure that contains statistical information relevant to the Internet protocol server.

### 2.2.13 INET\_INFO\_STATISTICS\_0

The **INET\_INFO\_STATISTICS\_0** structure contains statistics for an Internet protocol server.

This type is declared as follows:

```
typedef struct _INET_INFO_STATISTICS_0 {
    INETA_CACHE_STATISTICS CacheCtrs;
    INETA_ATQ_STATISTICS AtqCtrs;
    DWORD nAuxCounters;
    DWORD rgCounters[20];
} INET_INFO_STATISTICS_0,
*LPINET_INFO_STATISTICS_0;
```

**CacheCtrs:** The structure of type **INETA\_CACHE\_STATISTICS** that contains statistics on the Internet protocol server cache.

**AtqCtrs:** The structure of type **INETA\_ATQ\_STATISTICS** that contains statistics on the Internet protocol server network I/O.

**nAuxCounters:** The number of initialized elements in **rgCounters**. MUST be 0.

**rgCounters:** An array of 20 elements. This field is unused and MUST be ignored by clients.

### 2.2.14 INETA\_ATQ\_STATISTICS

The **INETA\_ATQ\_STATISTICS** structure contains network I/O statistics and client connection information for an Internet protocol server.

This type is declared as follows:

```
typedef struct _INETA_ATQ_STATISTICS {
    DWORD TotalBlockedRequests;
    DWORD TotalRejectedRequests;
    DWORD TotalAllowedRequests;
    DWORD CurrentBlockedRequests;
    DWORD MeasuredBandwidth;
} INETA_ATQ_STATISTICS,
*LPINETA_ATQ_STATISTICS;
```

**TotalBlockedRequests:** The total number of blocked requests.

**TotalRejectedRequests:** The total number of rejected requests.

**TotalAllowedRequests:** The total number of allowed requests.

**CurrentBlockedRequests:** The total number of currently blocked requests.

**MeasuredBandwidth:** The measured network bandwidth in bytes per second.

## 2.2.15 INETA\_CACHE\_STATISTICS

The **INETA\_CACHE\_STATISTICS** structure contains statistics for the Internet protocol server's caches. <6>

This type is declared as follows:

```
typedef struct _INETA_CACHE_STATISTICS {
    DWORD FilesCached;
    DWORD TotalFilesCached;
    DWORD FileHits;
    DWORD FileMisses;
    DWORD FileFlushes;
    DWORDLONG CurrentFileCacheSize;
    DWORDLONG MaximumFileCacheSize;
    DWORD FlushedEntries;
    DWORD TotalFlushed;
    DWORD URICached;
    DWORD TotalURICached;
    DWORD URIHits;
    DWORD URIMisses;
    DWORD URIFlushes;
    DWORD TotalURIFlushed;
    DWORD BlobCached;
    DWORD TotalBlobCached;
    DWORD BlobHits;
    DWORD BlobMisses;
    DWORD BlobFlushes;
    DWORD TotalBlobFlushed;
} INETA_CACHE_STATISTICS,
*LPINETA_CACHE_STATISTICS;
```

**FilesCached:** The current number of files whose content is in the Internet protocol server file cache.

**TotalFilesCached:** The total number of files whose content has been cached since Internet protocol server startup.

**FileHits:** The number of successful lookups in the Internet protocol server's file cache.

**FileMisses:** The number of unsuccessful lookups in the Internet protocol server's file cache.

**FileFlushes:** The number of file cache flushes since Internet protocol server startup.

**CurrentFileCacheSize:** The current number of bytes used for the Internet protocol server's file cache.

**MaximumFileCacheSize:** The maximum number of bytes used for the Internet protocol server's file cache.

**FlushedEntries:** The number of files that are marked for removal from the Internet protocol server cache after the current transfers are complete.

**TotalFlushed:** The number of files removed from the cache since Internet protocol server startup.

**URICached:** The number of URI information blocks currently cached by the Internet protocol server.

**TotalURICached:** The total number of URI information blocks ever added to the cache for the Internet protocol server.

**URIHits:** The number of successful lookups in the Internet protocol server's URI cache.

**URIMisses:** The number of unsuccessful lookups in the Internet protocol server's URI cache.

**URIFlushes:** The number of URI cache flushes since Internet protocol server startup.

**TotalURIFlushed:** The total number of URI information blocks that have been removed from the cache since Internet protocol server startup.

**BlobCached:** The number of BLOB information blocks currently cached by the Internet protocol server.

**TotalBlobCached:** The total number of BLOB information blocks ever added to the Internet protocol server's cache.

**BlobHits:** The number of successful lookups in the Internet protocol server's BLOB cache.

**BlobMisses:** The number of unsuccessful lookups in the Internet protocol server's BLOB cache.

**BlobFlushes:** The number of BLOB cache flushes since Internet protocol server startup.

**TotalBlobFlushed:** The total number of BLOB information blocks that have been removed from the cache since Internet protocol server startup.

## 2.2.16 INET\_INFO\_CAPABILITIES\_STRUCT

The **INET\_INFO\_CAPABILITIES\_STRUCT** structure specifies the features supported by an Internet protocol server implementation.

This type is declared as follows:

```
typedef struct _INET_INFO_CAPABILITIES_STRUCT {
    DWORD CapVersion;
    DWORD ProductType;
    DWORD MajorVersion;
    DWORD MinorVersion;
    DWORD BuildNumber;
    DWORD NumCapFlags;
    [size_is(NumCapFlags)] LPINET_INFO_CAP_FLAGS CapFlags;
} INET_INFO_CAPABILITIES_STRUCT;
*LPINET_INFO_CAPABILITIES_STRUCT;
```

**CapVersion:** The version number of this structure. MUST be 1.

**ProductType:** The value that indicates the Windows operating system product type hosting the implementation. This field MUST be set to one of the following values.

Value	Meaning
INET_INFO_PRODUCT_NTSERVER 0x00000001	The operating system product type is a Windows server.
INET_INFO_PRODUCT_NTWKSTA 0x00000002	The operating system product type is a Windows client or Windows NT Workstation operating system.
INET_INFO_PRODUCT_UNKNOWN 0xFFFFFFFF	The operating system product type is unknown.

Value	Meaning
INET_INFO_PRODUCT_WINDOWS95 0x00000003	The operating system product type is Windows 95 operating system.

**MajorVersion:** The major version number of the Internet Information Services (IIS) Inetinfo Remote Protocol server.

**MinorVersion:** The minor version number of the Internet Information Services (IIS) Inetinfo Remote Protocol server.

**BuildNumber:** The build number of the version of the Windows operating system running on the Internet Information Services (IIS) Inetinfo Remote Protocol server.

**NumCapFlags:** The number of INET\_INFO\_CAP\_FLAGS structures pointed to by the CapFlags member. MUST be 1.

**CapFlags:** The pointer to an array of **INET\_INFO\_CAP\_FLAGS** structures that defines the server's capabilities.

### 2.2.17 INET\_INFO\_CAP\_FLAGS

The **INET\_INFO\_CAP\_FLAGS** structure contains information on features that are available for a protocol server.

This type is declared as follows:

```
typedef struct _INET_INFO_CAP_FLAGS {
    DWORD Flag;
    DWORD Mask;
} INET_INFO_CAP_FLAGS,
*LPINET_INFO_CAP_FLAGS;
```

**Flag:** A value that indicates the features supported by the current running instance of the Internet protocol server implementation. The possible values for this member result from a bitwise OR of zero or more of the flags defined in the following table.

Value	Meaning
IIS_CAP1_ODBC_LOGGING 0x00000001	The Internet protocol server supports the Open Database Connectivity (ODBC) log format feature.
IIS_CAP1_FILE_LOGGING 0x00000002	The Internet protocol server supports the file system logging feature.
IIS_CAP1_VIRTUAL_SERVER 0x00000004	The Internet protocol server supports multiple instances of the protocol server network endpoint (1) aliases.
IIS_CAP1_BW_THROTTLING 0x00000008	The Internet protocol server supports network bandwidth throttling.
IIS_CAP1_IP_ACCESS_CHECK 0x00000010	The Internet protocol server supports blocking client connections using IP restrictions.
IIS_CAP1_MAX_CONNECTIONS 0x00000020	The Internet protocol server supports connection limiting.

Value	Meaning
IIS_CAP1_10_CONNECTION_LIMIT 0x00000040	The Internet protocol server supports a limit of 10 concurrent connections.
IIS_CAP1_MULTIPLE_INSTANCE 0x00000080	The Internet protocol server supports multiple instances.
IIS_CAP1_SSL_SUPPORT 0x00000100	The Internet protocol server supports the SSL protocol.
IIS_CAP1_OPERATORS_LIST 0x00000200	The Internet protocol server supports administrative operations by identities other than Windows operating system administrators.
IIS_CAP1_FP_INSTALLED 0x00000400	Front Page Server Extensions are installed on the server.
IIS_CAP1_CPU_AUDITING 0x00000800	The Internet protocol server supports CPU limits.
IIS_CAP1_SERVER_COMPRESSION 0x00001000	The Internet protocol server supports compression of network data.
IIS_CAP1_DAV 0x00002000	The Internet protocol server supports the WebDAV protocol.
IIS_CAP1_DIGEST_SUPPORT 0x00004000	The Internet protocol server supports the Digest Authentication Protocol.
IIS_CAP1_NT_CERTMAP_SUPPORT 0x00008000	The Internet protocol server supports mapping client certificates to Windows user accounts.
IIS_CAP1_POOLED_OOP 0x00010000	The Internet protocol server supports running a pool of applications in a separate process.

**Mask:** A value that indicates the capabilities that can be enabled for the protocol servers in the current implementation. The possible values for this member result from a bitwise OR operation of zero or more of the following flags.

**Note** The **Mask** value contains all the capabilities that the current version of the protocol server implementation can support. The **Flag** value indicates the features that the current running server instance does support. The server sets the mask value to a bitwise OR of all the flags it knows about. The server then sets the flags to the bitwise OR of the features supported for the current platform, a subset of those set in the mask field. A given version of the software reports the same mask values, but might support different flags values depending on the operating system type.

Value	Meaning
IIS_CAP1_ODBC_LOGGING 0x00000001	The Internet protocol server supports the Open Database Connectivity (ODBC) log format feature.
IIS_CAP1_FILE_LOGGING 0x00000002	The Internet protocol server supports the file system logging feature.
IIS_CAP1_VIRTUAL_SERVER 0x00000004	The Internet protocol server supports multiple instances of the protocol server network endpoint (2) aliases.
IIS_CAP1_BW_THROTTLING	The Internet protocol server supports network bandwidth throttling.

Value	Meaning
0x00000008	
IIS_CAP1_IP_ACCESS_CHECK 0x00000010	The Internet protocol server supports blocking client connections by using IP restrictions.
IIS_CAP1_MAX_CONNECTIONS 0x00000020	The Internet protocol server supports connection limiting.
IIS_CAP1_10_CONNECTION_LIMIT 0x00000040	The Internet protocol server supports a limit of 10 concurrent connections.
IIS_CAP1_MULTIPLE_INSTANCE 0x00000080	The Internet protocol server supports multiple instances.
IIS_CAP1_SSL_SUPPORT 0x00000100	The Internet protocol server supports the SSL protocol.
IIS_CAP1_OPERATORS_LIST 0x00000200	The Internet protocol server supports administrative operations by identities other than Windows operating system administrators.
IIS_CAP1_FP_INSTALLED 0x00000400	Front Page Server Extensions are installed on the server.
IIS_CAP1_CPU_AUDITING 0x00000800	The Internet protocol server supports CPU limits.
IIS_CAP1_SERVER_COMPRESSION 0x00001000	The Internet protocol server supports compression of network data.
IIS_CAP1_DAV 0x00002000	The Internet protocol server supports the WebDAV protocol.
IIS_CAP1_DIGEST_SUPPORT 0x00004000	The Internet protocol server supports the Digest Authentication Protocol.
IIS_CAP1_NT_CERTMAP_SUPPORT 0x00008000	The Internet protocol server supports mapping client certificates to Windows user accounts.
IIS_CAP1_POOLED_OOP 0x00010000	The Internet protocol server supports running a pool of applications in a separate process.

## 2.2.18 W3\_STATISTICS\_STRUCT

The **W3\_STATISTICS\_STRUCT** union contains a pointer to a **W3\_STATISTICS\_1** structure.

This type is declared as follows:

```
typedef
[switch_type(unsigned long)]
union _W3_STATISTICS_UNION {
    [case(0)]
        LPW3_STATISTICS_1 StatInfo1;
    [default]
        ;
} W3_STATISTICS_STRUCT,
*LPW3_STATISTICS_STRUCT;
```



**StatInfo1:** The pointer to a **W3\_STATISTICS\_1** structure that contains the HTTP protocol statistics.

## 2.2.19 W3\_STATISTICS\_1

The **W3\_STATISTICS\_1** structure contains statistics on the usage of the HTTP server.

This type is declared as follows:

```
typedef struct _W3_STATISTICS_1 {
    LARGE_INTEGER TotalBytesSent;
    LARGE_INTEGER TotalBytesReceived;
    DWORD TotalFilesSent;
    DWORD TotalFilesReceived;
    DWORD CurrentAnonymousUsers;
    DWORD CurrentNonAnonymousUsers;
    DWORD TotalAnonymousUsers;
    DWORD TotalNonAnonymousUsers;
    DWORD MaxAnonymousUsers;
    DWORD MaxNonAnonymousUsers;
    DWORD CurrentConnections;
    DWORD MaxConnections;
    DWORD ConnectionAttempts;
    DWORD LogonAttempts;
    DWORD TotalOptions;
    DWORD TotalGets;
    DWORD TotalPosts;
    DWORD TotalHeads;
    DWORD TotalPuts;
    DWORD TotalDeletes;
    DWORD TotalTraces;
    DWORD TotalMove;
    DWORD TotalCopy;
    DWORD TotalMkcol;
    DWORD TotalPropfind;
    DWORD TotalProppatch;
    DWORD TotalSearch;
    DWORD TotalLock;
    DWORD TotalUnlock;
    DWORD TotalOthers;
    DWORD TotalCGIRequests;
    DWORD TotalBGIRequests;
    DWORD TotalNotFoundErrors;
    DWORD TotalLockedErrors;
    DWORD CurrentCalAuth;
    DWORD MaxCalAuth;
    DWORD TotalFailedCalAuth;
    DWORD CurrentCalSsl;
    DWORD MaxCalSsl;
    DWORD TotalFailedCalSsl;
    DWORD CurrentCGIRequests;
    DWORD CurrentBGIRequests;
    DWORD MaxCGIRequests;
    DWORD MaxBGIRequests;
    DWORD CurrentBlockedRequests;
    DWORD TotalBlockedRequests;
    DWORD TotalAllowedRequests;
    DWORD TotalRejectedRequests;
    DWORD MeasuredBw;
    DWORD ServiceUptime;
    DWORD TimeOfLastClear;
    DWORD nAuxCounters;
    DWORD rgCounters[20];
} W3_STATISTICS_1,
*LPW3_STATISTICS_1;
```

**TotalBytesSent:** The total number of bytes sent.

**TotalBytesReceived:** The total number of bytes received.

**TotalFilesSent:** The total number of files sent by the HTTP server.

**TotalFilesReceived:** The total number of files received by the HTTP server.

**CurrentAnonymousUsers:** The current number of anonymous users connected to the HTTP server.

**CurrentNonAnonymousUsers:** The current number of non-anonymous users connected to the HTTP server.

**TotalAnonymousUsers:** The total number of anonymous users that have ever connected to the HTTP server.

**TotalNonAnonymousUsers:** The total number of non-anonymous users that have ever connected to the HTTP server.

**MaxAnonymousUsers:** The maximum number of anonymous users who simultaneously connected to the HTTP server.

**MaxNonAnonymousUsers:** The maximum number of non-anonymous users who simultaneously connected to the HTTP server.

**CurrentConnections:** The current number of connections to the HTTP server.

**MaxConnections:** The maximum number of connections to the HTTP server.

**ConnectionAttempts:** The number of connection attempts that have been made to the HTTP server.

**LogonAttempts:** The number of logon attempts that have been made to the HTTP server.

**TotalOptions:** The total number of HTTP requests made with the OPTIONS method.

**TotalGets:** The total number of HTTP requests made using the GET method.

**TotalPosts:** The total number of HTTP requests made using the POST method.

**TotalHeads:** The total number of HTTP requests made using the HEAD method.

**TotalPuts:** The total number of HTTP requests made using the PUT method.

**TotalDeletes:** The total number of HTTP requests made using the DELETE method.

**TotalTraces:** The total number of HTTP requests made using the TRACE method.

**TotalMove:** The total number of WebDAV requests made using the MOVE method. For more information on WebDAV requests, see [RFC2518].

**TotalCopy:** The total number of WebDAV requests made using the COPY method.

**TotalMkcol:** The total number of WebDAV requests made using the MKCOL method.

**TotalPropfind:** The total number of WebDAV requests made using the PROPFIND method.

**TotalProppatch:** The total number of WebDAV requests made using the PROPPATCH method.

**TotalSearch:** The total number of requests made using the SEARCH method.

**TotalLock:** The total number of WebDAV requests made using the LOCK method.

**TotalUnlock:** The total number of WebDAV requests made using the UNLOCK method.

**TotalOthers:** The total number of HTTP requests made to methods not already listed.

**TotalCGIRequests:** The total number of Common Gateway Interface (CGI) requests ever made to the HTTP server.

**TotalBGIRequests:** The total number of Binary Gateway Interface (BGI) requests ever made to the HTTP server.

**TotalNotFoundErrors:** The total number of requests that could not be satisfied by the server because the requested document could not be found. These requests are generally reported as an HTTP 404 error code to the client.

**TotalLockedErrors:** The total number of locked errors.

**CurrentCalAuth:** The current number of Client Access Licenses (CALs) that are authorized (for more information, see [MSFT-CAL]).

**MaxCalAuth:** The maximum number of CALs that are authorized.

**TotalFailedCalAuth:** The total number of failed CAL authorizations.

**CurrentCalSsl:** The current number of CALs for a Secure Sockets Layer (SSL) connection.

**MaxCalSsl:** The maximum number of CALs for an SSL connection.

**TotalFailedCalSsl:** The total number of failed CAL SSL connections.

**CurrentCGIRequests:** The current number of CGI requests. For more information on CGI, see [RFC3875].

**CurrentBGIRequests:** The current number of BGI requests.

**MaxCGIRequests:** The maximum number of CGI requests allowed.

**MaxBGIRequests:** The maximum number of BGI requests allowed.

**CurrentBlockedRequests:** The current number of blocked requests.

**TotalBlockedRequests:** The total number of blocked requests.

**TotalAllowedRequests:** The total number of allowed requests to the HTTP server.

**TotalRejectedRequests:** The total number of rejected requests.

**MeasuredBw:** The measured network bandwidth for the HTTP server.

**ServiceUptime:** The HTTP server uptime.

**TimeOfLastClear:** The time of the last clear.

**nAuxCounters:** The number of initialized elements in **rgCounters**. MUST be 0.

**rgCounters:** An array of 20 elements. This field is unused and MUST be ignored by clients.

## 2.2.20 FTP\_STATISTICS\_STRUCT

The **FTP\_STATISTICS\_STRUCT** union contains a pointer to an **FTP\_STATISTICS\_0** structure.

This type is declared as follows:

```
typedef
[switch_type(unsigned long)]
union _FTP_STATISTICS_UNION {
    [case(0)]
```

```

    LPFTP_STATISTICS_0 StatInfo0;
    [default]      ;
} FTP_STATISTICS_STRUCT,
*LPFTP_STATISTICS_STRUCT;

```

**StatInfo0:** The pointer to an **FTP\_STATISTICS\_0** structure that contains the FTP server statistics.

### 2.2.21 FTP\_STATISTICS\_0

The **FTP\_STATISTICS\_0** structure contains statistics on the usage of the FTP server.

This type is declared as follows:

```

typedef struct _FTP_STATISTICS_0 {
    LARGE_INTEGER TotalBytesSent;
    LARGE_INTEGER TotalBytesReceived;
    DWORD TotalFilesSent;
    DWORD TotalFilesReceived;
    DWORD CurrentAnonymousUsers;
    DWORD CurrentNonAnonymousUsers;
    DWORD TotalAnonymousUsers;
    DWORD TotalNonAnonymousUsers;
    DWORD MaxAnonymousUsers;
    DWORD MaxNonAnonymousUsers;
    DWORD CurrentConnections;
    DWORD MaxConnections;
    DWORD ConnectionAttempts;
    DWORD LogonAttempts;
    DWORD ServiceUptime;
    DWORD TotalAllowedRequests;
    DWORD TotalRejectedRequests;
    DWORD TotalBlockedRequests;
    DWORD CurrentBlockedRequests;
    DWORD MeasuredBandwidth;
    DWORD TimeOfLastClear;
} FTP_STATISTICS_0,
*LPFTP_STATISTICS_0;

```

**TotalBytesSent:** The total number of bytes sent.

**TotalBytesReceived:** The total number of bytes received.

**TotalFilesSent:** The total number of files sent by the FTP server.

**TotalFilesReceived:** The total number of files received by the FTP server.

**CurrentAnonymousUsers:** The current number of anonymous users connected to the FTP server.

**CurrentNonAnonymousUsers:** The current number of non-anonymous users connected to the FTP server.

**TotalAnonymousUsers:** The total number of anonymous users that have ever connected to the FTP server.

**TotalNonAnonymousUsers:** The total number of non-anonymous users that have ever connected to the FTP server.

**MaxAnonymousUsers:** The maximum number of anonymous users allowed to simultaneously connect to the FTP server.

**MaxNonAnonymousUsers:** The maximum number of non-anonymous users allowed to simultaneously connect to the FTP server.

**CurrentConnections:** The current number of connections to the FTP server.

**MaxConnections:** The maximum number of connections to the FTP server.

**ConnectionAttempts:** The number of connection attempts that have been made to the FTP server.

**LogonAttempts:** The number of logon attempts that have been made to the FTP server.

**ServiceUptime:** The time that the FTP server has been operational.

**TotalAllowedRequests:** The total number of requests allowed to the FTP server.

**TotalRejectedRequests:** The total number of rejected requests.

**TotalBlockedRequests:** The total number of blocked requests.

**CurrentBlockedRequests:** The current number of blocked requests.

**MeasuredBandwidth:** The measured network bandwidth for the FTP server.

**TimeOfLastClear:** The time of the last clear.

### 2.2.22 IIS\_USER\_ENUM\_STRUCT

The **IIS\_USER\_ENUM\_STRUCT** structure contains a pointer to an **IIS\_USER\_INFO\_1\_CONTAINER**.

This type is declared as follows:

```
typedef struct _IIS_USER_ENUM_STRUCT {
    DWORD Level;
    [switch_is(Level)] union _USER_ENUM_UNION {
        [case(1)]
            LPIIS_USER_INFO_1_CONTAINER Level1;
        [default]
            ;
    } ConfigInfo;
} IIS_USER_ENUM_STRUCT,
*LPIIS_USER_ENUM_STRUCT;
```

**Level:** The value that indicates the level of detail in the information provided. This member **MUST** be set to 1.

**ConfigInfo:** The name of the contained union.

**Level1:** The pointer to an **IIS\_USER\_INFO\_1\_CONTAINER** structure that contains the user information collection.

### 2.2.23 IIS\_USER\_INFO\_1\_CONTAINER

The **IIS\_USER\_INFO\_1\_CONTAINER** structure contains a list of **IIS\_USER\_INFO\_1** structures describing users who are actively connected to the Internet protocol server.

This type is declared as follows:

```
typedef struct _IIS_USER_INFO_1_CONTAINER {
    DWORD EntriesRead;
    [size_is(EntriesRead)] LPIIS_USER_INFO_1 Buffer;
} IIS_USER_INFO_1_CONTAINER,
*LPIIS_USER_INFO_1_CONTAINER;
```

**EntriesRead:** The total number of IIS\_USER\_INFO objects in Buffer.

**Buffer:** The pointer to an array of **IIS\_USER\_INFO\_1** structures.

### 2.2.24 IIS\_USER\_INFO\_1

The **IIS\_USER\_INFO\_1** structure describes a user connected to an Internet protocol server.

This type is declared as follows:

```
typedef struct _IIS_USER_INFO_1 {
    DWORD idUser;
    [string] LPWSTR pszUser;
    BOOL fAnonymous;
    DWORD inetHost;
    DWORD tConnect;
} IIS_USER_INFO_1,
*LPIIS_USER_INFO_1;
```

**idUser:** A unique identifier for the user.

**pszUser:** A name for the user, not necessarily unique.

**fAnonymous:** Indicates whether or not the user connected anonymously. This field **MUST** be one of the following values.

Value	Meaning
TRUE 1	The user is logged on as Anonymous.
FALSE 0	The user is not logged on as Anonymous.

**inetHost:** The host IPv4 address. Data is stored in network byte order.

**tConnect:** The user connection time measured in elapsed seconds.

### 2.2.25 Common Error Codes

Unless specified explicitly, the methods of the Internet Information Services (IIS) Inetinfo Remote Protocol **MUST** return 0 to indicate success and a nonzero implementation-specific value to indicate failure in the return code of the response. All failure values **MUST** be treated as equivalent for protocol purposes and **SHOULD** simply be passed back to the invoking application. A list of error codes that are potentially returned is available, as specified in [MS-ERREF].<7>

## 3 Protocol Details

The following sections specify details of the Internet Information Services (IIS) Inetinfo Remote Protocol, including abstract data models, interface method syntax, and message processing rules.

The client side of this protocol is simply a pass-through. That is, no additional timers or other state is required on the client side of this protocol. Calls made by the higher-layer protocol or application are passed directly to the transport, and the results returned by the transport are passed directly back to the higher-layer protocol or application.

### 3.1 Inetinfo Server Details

The IIS Inetinfo Remote Protocol server handles client requests for any of the messages that are specified in section 2. For each of those messages, the behavior of the server is specified in section 3.1.4.

An implementation MAY implement only a subset of the methods specified in the inetinfo interface. Or a particular Internet protocol server might only be able to support a subset of methods specified in the interface. For methods that are not implemented, the server SHOULD return ERROR\_NOT\_SUPPORTED (0x00000032).

#### 3.1.1 Abstract Data Model

The Internet Information Services (IIS) Inetinfo Remote Protocol provides runtime status and statistical data and manages runtime configuration for the Internet protocol server. The Internet protocol server MUST provide a mechanism to collect runtime data and expose it through the Internet Information Services (IIS) Inetinfo Remote Protocol server. Some methods operate on configuration data that SHOULD be persisted beyond the lifetime of an Internet protocol server process.

#### 3.1.2 Timers

None.

#### 3.1.3 Initialization

The Internet Information Services (IIS) Inetinfo Remote Protocol server MUST be initialized by registering the RPC interface and listening on the RPC well-known endpoint, as specified in section 2.1. The server MUST then wait for Internet Information Services (IIS) Inetinfo Remote Protocol clients to establish a connection.

#### 3.1.4 Higher-Layer Triggered Events

The Internet Information Services (IIS) Inetinfo Remote Protocol is invoked explicitly by an application.

#### 3.1.5 Message Processing Events and Sequencing Rules

The remainder of this section describes the server behavior for the RPC methods on the inetinfo interface that makes up the IIS Inetinfo Remote Protocol. IIS Inetinfo Remote Protocol clients can invoke the RPC methods that are specified in this section in any order after an Internet Information Services (IIS) Inetinfo Remote Protocol session is established with the server. The outcome of the calls depends on the parameters that are passed to each of those calls and not on a particular call sequence or state maintained across method invocations.

Methods in RPC Opnum Order

<b>Method</b>	<b>Description</b>
R_InetInfoGetVersion	Called by the client. In response, the server returns its version information. Opnum: 0
R_InetInfoGetAdminInformation	Called by the client. In response, the server returns configuration data for the specified Internet protocol server. Opnum: 1
R_InetInfoGetSites	Called by the client. In response, the server retrieves a list of service instances for the specified Internet protocol server. Opnum: 2
R_InetInfoSetAdminInformation	Called by the client. In response, the server sets configurable properties for the specified Internet protocol server. Opnum: 3
R_InetInfoGetGlobalAdminInformation	Called by the client. In response, the server retrieves configuration data shared by all Internet protocol servers. Opnum: 4
R_InetInfoSetGlobalAdminInformation	Called by the client. In response, the server sets configuration data shared by all Internet protocol servers. Opnum: 5
R_InetInfoQueryStatistics	Called by the client. In response, the server retrieves statistical data for the specified Internet protocol server. Opnum: 6
R_InetInfoClearStatistics	Called by the client. In response, the server resets the statistical data maintained by the specified Internet protocol server. Opnum: 7
R_InetInfoFlushMemoryCache	Called by the client. In response, the server flushes data from the internal caches of the specified Internet protocol server. Opnum: 8
R_InetInfoGetServerCapabilities	Called by the client. In response, the server returns information on the features of the Internet protocol servers and the host operating system. Opnum: 9
R_W3QueryStatistics2	Called by the client. In response, the server returns statistical data from the HTTP server. Opnum: 10
R_W3ClearStatistics2	Called by the client. In response, the server resets statistical data for the HTTP server. Opnum: 11
R_FtpQueryStatistics2	Called by the client. In response, the server returns statistical data from the FTP server. Opnum: 12
R_FtpClearStatistics2	Called by the client. In response, the server resets statistical data for the FTP server. Opnum: 13
R_IISEnumerateUsers	Called by the client. In response, the server returns a list of clients connected to the specified Internet protocol server.



Method	Description
	Opnum: 14
R_IISDisconnectUser	Called by the client. In response, the server disconnects the specified user from the specified Internet protocol server. Opnum: 15
Opnum16NotUsedOnWire	Reserved for local use. Opnum: 16
Opnum17NotUsedOnWire	Reserved for local use. Opnum: 17

## Structures

The **Message Processing Events and Sequencing Rules** interface defines the following structures.

Structure	Description
INET_INFO_CONFIG_INFO	This structure stores configuration values for an Internet protocol server.
INET_LOG_CONFIGURATION	This structure contains configuration information for Internet protocol server logging.
INET_INFO_IP_SEC_LIST	This structure contains a list of INET_INFO_IP_SEC_ENTRY entries.
<b>INET_INFO_IP_SEC_ENTRY</b>	This structure contains Internet protocol security (IPv4) entries.
INET_INFO_VIRTUAL_ROOT_LIST	This structure contains a list of INET_INFO_VIRTUAL_ROOT_ENTRY virtual root entries.
<b>INET_INFO_VIRTUAL_ROOT_ENTRY</b>	This structure contains data describing a virtual root for the Internet protocol server instance.
INET_INFO_SITE_LIST	This structure contains a list of INET_INFO_SITE_ENTRY site entries.
<b>INET_INFO_SITE_ENTRY</b>	This structure contains information describing an Internet protocol server instance.
INET_INFO_GLOBAL_CONFIG_INFO	This structure contains configuration data global to all the Internet protocol services managed by this protocol.
INET_INFO_STATISTICS_0	This structure contains statistics for an Internet protocol server.
INETA_ATQ_STATISTICS	This structure contains network I/O statistics and client connection information for an Internet protocol server.
INETA_CACHE_STATISTICS	This structure contains statistics for the Internet protocol server's caches.
INET_INFO_CAPABILITIES_STRUCT	This structure specifies the features supported by an Internet protocol server implementation.
INET_INFO_CAP_FLAGS	This structure contains information on features that are available for a protocol server.
W3_STATISTICS_1	This structure contains statistics on the usage of the HTTP server.
FTP_STATISTICS_0	This structure contains statistics on the usage of the FTP server.
IIS_USER_ENUM_STRUCT	This structure contains a pointer to an

Structure	Description
	IIS_USER_INFO_1_CONTAINER.
<b>IIS_USER_INFO_1_CONTAINER</b>	This structure contains a list of IIS_USER_INFO_1 structures describing users who are actively connected to the Internet protocol server.
<b>IIS_USER_INFO_1</b>	This structure describes a user connected to an Internet protocol server.

Unions

The **Message Processing Events and Sequencing Rules** interface defines the following unions.

Union	Description
INET_INFO_STATISTICS_INFO	This union contains a pointer to an <b>INET_INFO_STATISTICS_0</b> structure.
W3_STATISTICS_STRUCT	This union contains a pointer to a <b>W3_STATISTICS_1</b> structure.
FTP_STATISTICS_STRUCT	This union contains a pointer to an <b>FTP_STATISTICS_0</b> structure.

In the preceding tables, "Reserved for local use" means that the client MUST NOT send the opnum, and the server behavior is undefined because it does not affect interoperability.<8>

### 3.1.5.1 R\_InetInfoGetVersion (Opnum 0)

The **R\_InetInfoGetVersion** method is called by the client. In response, the server returns its version information.

```

DWORD R_InetInfoGetVersion(
    [in, string, unique] INET_INFO_IMPERSONATE_HANDLE pszServer,
    [in] DWORD dwReserved,
    [out] DWORD* pdwVersion
);

```

**pszServer:** A custom binding handle for the target system, as specified in section 2.1.1. The value MUST NOT be used by the server implementation.

**dwReserved:** An unused parameter. MUST be ignored by the server implementation.

**pdwVersion:** A pointer to a variable. On successful return, it MUST contain a major and minor version number for the server implementation. The major version is stored in the low WORD, and the minor version is stored in the high WORD.

**Return Values:** The method returns 0 (ERROR\_SUCCESS) to indicate success; otherwise, it returns a nonzero error code, as specified in [MS-ERREF] section 2.2 or [MS-ERREF] section 2.3.1.

ERROR\_SUCCESS (0x00000000)

**Exceptions Thrown:** No exceptions are thrown beyond those thrown by the underlying RPC protocol, as specified in [MS-RPCE].

The value returned in *pdwVersion* SHOULD<9> correspond to the version of the Internet protocol servers managed by the Internet Information Services (IIS) Inetinfo Remote Protocol server.

### 3.1.5.2 R\_InetInfoGetAdminInformation (Opnum 1)

The **R\_InetInfoGetAdminInformation** method is called by the client. In response, the server retrieves configuration data for the specified Internet protocol server.

```
DWORD R_InetInfoGetAdminInformation(  
    [in, string, unique] INET_INFO_IMPERSONATE_HANDLE pszServer,  
    [in] DWORD dwServerMask,  
    [out] LPINET_INFO_CONFIG_INFO* ppConfig  
);
```

**pszServer:** The custom binding handle for the target system, as specified in section 2.1.1. The value MUST NOT be used by the server implementation.

**dwServerMask:** The identifier for the target Internet protocol server, as specified in section 2.2.2.

**ppConfig:** The pointer to a pointer to an INET\_INFO\_CONFIG\_INFO structure that contains configuration data for the specified Internet protocol server.

**Return Values:** The method returns 0 (ERROR\_SUCCESS) to indicate success; otherwise, it returns a nonzero error code, as specified in [MS-ERREF] section 2.2 or [MS-ERREF] section 2.3.1. The most common error codes are listed in the following table.

Return value/code	Description
0x00000002 ERROR_FILE_NOT_FOUND	The system cannot find the specified file.
0x00000426 ERROR_SERVICE_NOT_ACTIVE	The service is not running.

**Exceptions Thrown:** No exceptions are thrown beyond those thrown by the underlying RPC protocol, as specified in [MS-RPCE].

In response to this request from the client, the server MUST return the data specified in *ppConfig* and set the **FieldControl** member, as specified in **INET\_INFO\_CONFIG\_INFO**.

Data returned MAY be a configuration that is persisted in a configuration store for the protocol server, runtime or derived data, or default operating values.

An implementation MAY support only a subset of the configuration data specified in the **INET\_INFO\_CONFIG\_INFO** structure, but it MUST set the **FieldControl** member for any valid value returned.

### 3.1.5.3 R\_InetInfoGetSites (Opnum 2)

The **R\_InetInfoGetSites** method is called by the client. In response, the server retrieves a list of server instances for the specified Internet protocol server.

```
DWORD R_InetInfoGetSites(  
    [in, string, unique] INET_INFO_IMPERSONATE_HANDLE pszServer,  
    [in] DWORD dwServerMask,  
    [out] LPINET_INFO_SITE_LIST* ppSites  
);
```

**pszServer:** The custom binding handle for the target system, as specified in section 2.1.1. The value MUST NOT be used by the server implementation.

**dwServerMask:** The identifier for the target Internet protocol server, as specified in section 2.2.2.

**ppSites:** The pointer to a pointer to INET\_INFO\_SITE\_LIST that specifies the list of defined server instances for the Internet protocol server specified by *dwServerMask*.

**Return Values:** The method returns 0 (ERROR\_SUCCESS) to indicate success; otherwise, it returns a nonzero error code, as specified in [MS-ERREF] section 2.2 or [MS-ERREF] section 2.3.1. The most common error codes are listed in the following table.

Return value/code	Description
0x00000426 ERROR_SERVICE_NOT_ACTIVE	The service is not running.

**Exceptions Thrown:** No exceptions are thrown beyond those thrown by the underlying RPC protocol, as specified in [MS-RPCE].

In response to this request from the client, the server SHOULD return a list of defined server instances in *ppSites* if the return code indicates success.<10>

### 3.1.5.4 R\_InetInfoSetAdminInformation (Opnum 3)

The **R\_InetInfoSetAdminInformation** method is called by the client. In response, the server sets configurable properties for the specified Internet protocol server.

```
DWORD R_InetInfoSetAdminInformation(  
    [in, string, unique] INET_INFO_IMPERSONATE_HANDLE pszServer,  
    [in] DWORD dwServerMask,  
    [in, ref] INET_INFO_CONFIG_INFO* pConfig  
);
```

**pszServer:** The custom binding handle for the target system, as specified in section 2.1.1. The value MUST NOT be used by the server implementation.

**dwServerMask:** The identifier for the target Internet protocol server, as specified in section 2.2.2.

**pConfig:** The pointer to an INET\_INFO\_CONFIG\_INFO structure containing the property configuration to set. The client MUST set the appropriate flag in the **FieldControl** member for any data field in *pConfig* that is to be set by the server.

**Return Values:** The method returns 0 (ERROR\_SUCCESS) to indicate success; otherwise, it returns a nonzero error code, as specified in [MS-ERREF] section 2.2, or [MS-ERREF] section 2.3.1. The most common error codes are listed in the following table.

Return value/code	Description
0x00000002 ERROR_FILE_NOT_FOUND	The system cannot find the specified file.
0x00000005 ERROR_ACCESS_DENIED	Access is denied.
0x00000426 ERROR_SERVICE_NOT_ACTIVE	The service is not running.

**Exceptions Thrown:** No exceptions are thrown beyond those thrown by the underlying RPC protocol, as specified in [MS-RPCE].

In response to this request from the client, the server SHOULD set the configurable properties in *pConfig* into the configuration store for the Internet protocol server specified by *dwServerMask*.

The server MUST NOT access a field value in *pConfig* unless the corresponding flag in the **FieldControl** field is set.

The implementation MAY choose not to save some fields of the **INET\_INFO\_CONFIG\_INFO** structure. If so, the server MUST ignore the field values sent by the client.

The implementation MAY return an error if it is unable to persist a field value due to some internal error.

### 3.1.5.5 R\_InetInfoGetGlobalAdminInformation (Opnum 4)

The **R\_InetInfoGetGlobalAdminInformation** method is called by the client. In response, the server retrieves configuration data shared by all Internet protocol servers.

```
DWORD R_InetInfoGetGlobalAdminInformation(  
    [in, string, unique] INET_INFO_IMPERSONATE_HANDLE pszServer,  
    [in] DWORD dwServerMask,  
    [out] LPINET_INFO_GLOBAL_CONFIG_INFO* ppConfig  
);
```

**pszServer:** The custom binding handle for the target system, as specified in section 2.1.1. The value MUST NOT be used by the server implementation.

**dwServerMask:** This value MUST be ignored by the server.

**ppConfig:** The pointer to a pointer to an INET\_INFO\_GLOBAL\_CONFIG\_INFO structure.

**Return Values:** The method returns 0 (ERROR\_SUCCESS) to indicate success; otherwise, it returns a nonzero error code, as specified in [MS-ERREF] section 2.2 or [MS-ERREF] section 2.3.1.

ERROR\_SUCCESS (0x00000000)

**Exceptions Thrown:** No exceptions are thrown beyond those thrown by the underlying RPC protocol, as specified in [MS-RPCE].

In response to this request from the client, the server MUST return the configuration data in *ppConfig*, if the return code indicates success.

### 3.1.5.6 R\_InetInfoSetGlobalAdminInformation (Opnum 5)

The **R\_InetInfoSetGlobalAdminInformation** assigns global settings for all Internet protocol servers present on the host system.

```
DWORD R_InetInfoSetGlobalAdminInformation(  
    [in, string, unique] INET_INFO_IMPERSONATE_HANDLE pszServer,  
    [in] DWORD dwServerMask,  
    [in, ref] INET_INFO_GLOBAL_CONFIG_INFO* pConfig  
);
```

**pszServer:** The custom binding handle for the target system, as specified in section 2.1.1. The value MUST NOT be used by the server implementation.

**dwServerMask:** This value MUST be ignored by the server.

**pConfig:** The pointer to an INET\_INFO\_GLOBAL\_CONFIG\_INFO structure that contains global administrative information.

**Return Values:** The method returns 0 (ERROR\_SUCCESS) to indicate success; otherwise, it returns a nonzero error code, as specified in [MS-ERREF] section 2.2 or [MS-ERREF] section 2.3.1. The most common error codes are listed in the following table.

Return value/code	Description
0x00000005 ERROR_ACCESS_DENIED	Access is denied.
0x00000032 ERROR_NOT_SUPPORTED	The request is not supported.

**Exceptions Thrown:** No exceptions are thrown beyond those thrown by the underlying RPC protocol, as specified in [MS-RPCE].

In response to this request from the client, the server MUST set the configurable properties in *pConfig* into the configuration store for the Internet protocol servers if the return code indicates success.

### 3.1.5.7 R\_InetInfoQueryStatistics (Opnum 6)

The **R\_InetInfoQueryStatistics** method is called by the client. In response, the server retrieves statistical data for the specified Internet protocol server.

```
DWORD R_InetInfoQueryStatistics(  
    [in, string, unique] INET_INFO_IMPERSONATE_HANDLE pszServer,  
    [in] DWORD Level,  
    [in] DWORD dwServerMask,  
    [out, switch_is(Level)] LPINET_INFO_STATISTICS_INFO StatsInfo  
);
```

**pszServer:** The custom binding handle for the target system, as specified in section 2.1.1. The value MUST NOT be used by the server implementation.

**Level:** The level of detail to be retrieved. This member MUST be set to 0. If another value is sent by the client, the server MUST return ERROR\_INVALID\_LEVEL (0x0000007C).

**dwServerMask:** The identifier for the target Internet protocol server, as specified in section 2.2.2. A value of 0 indicates that aggregate statistical data is to be returned for all protocol servers.

**StatsInfo:** The pointer to an INET\_INFO\_STATISTICS\_INFO union that contains the data to be returned.

**Return Values:** The method returns 0 (ERROR\_SUCCESS) to indicate success; otherwise, it returns a nonzero error code, as specified in [MS-ERREF] section 2.2 or [MS-ERREF] section 2.3.1. The following table describes possible error code values.

Return value/code	Description
0x0000007C ERROR_INVALID_LEVEL	The system call level is not correct.

**Exceptions Thrown:** No exceptions are thrown beyond those thrown by the underlying RPC protocol, as specified in [MS-RPCE].

In response to this request from the client, the server MAY return the statistical data in *StatsInfo* if the return code indicates success.<11>

### 3.1.5.8 R\_InetInfoClearStatistics (Opnum 7)

The **R\_InetInfoClearStatistics** is called by the client. In response, the server resets the statistical data maintained by the specified Internet protocol server.

```
DWORD R_InetInfoClearStatistics(  
    [in, string, unique] INET_INFO_IMPERSONATE_HANDLE pszServer,  
    [in] DWORD dwServerMask  
);
```

**pszServer:** The custom binding handle for the target system, as specified in section 2.1.1. The value MUST NOT be used by the server implementation.

**dwServerMask:** The identifier for the target Internet protocol server, as specified in section 2.2.2.

**Return Values:** The method returns 0 (ERROR\_SUCCESS) to indicate success; otherwise, it returns a nonzero error code, as specified in [MS-ERREF] section 2.2 or [MS-ERREF] section 2.3.1. The most common error codes are listed in the following table.

Return value/code	Description
0x00000005 ERROR_ACCESS_DENIED	Access is denied.
0x00000032 ERROR_NOT_SUPPORTED	The request is not supported.
0x00000057 ERROR_INVALID_PARAMETER	The parameter is incorrect.

**Exceptions Thrown:** No exceptions are thrown beyond those thrown by the underlying RPC protocol, as specified in [MS-RPCE].

In response to this request from the client, the server MAY clear any accumulated data that would be returned by R\_InetInfoQueryStatistics.<12>

### 3.1.5.9 R\_InetInfoFlushMemoryCache (Opnum 8)

The **R\_InetInfoFlushMemoryCache** method is called by the client. In response, the server flushes data from the internal caches of the specified Internet protocol server.

```
DWORD R_InetInfoFlushMemoryCache(  
    [in, string, unique] INET_INFO_IMPERSONATE_HANDLE pszServer,  
    [in] DWORD dwServerMask  
);
```

**pszServer:** The custom binding handle for the target system, as specified in section 2.1.1. The value MUST NOT be used by the server implementation.

**dwServerMask:** The identifier for the target Internet protocol server, as specified in section 2.2.2.

**Return Values:** The method returns 0 (ERROR\_SUCCESS) to indicate success; otherwise, it returns a nonzero error code, as specified in [MS-ERREF] section 2.2 or [MS-ERREF] section 2.3.1. The most common error codes are listed in the following table.

Return value/code	Description
0x00000005 ERROR_ACCESS_DENIED	Access is denied.

**Exceptions Thrown:** No exceptions are thrown beyond those thrown by the underlying RPC protocol, as specified in [MS-RPCE].

In response to this request from the client, the server MUST flush data from the internal caches of the specified Internet protocol server. If *dwServerMask* is 0, caches are flushed for all protocol servers.

### 3.1.5.10 R\_InetInfoGetServerCapabilities (Opnum 9)

The **R\_InetInfoGetServerCapabilities** method is called by the client. In response, the server returns information on the features of the Internet protocol servers and the host operating system.

```
DWORD R_InetInfoGetServerCapabilities(  
    [in, string, unique] INET_INFO_IMPERSONATE_HANDLE pszServer,  
    [in] DWORD dwReserved,  
    [out] LPINET_INFO_CAPABILITIES_STRUCT* ppCap  
);
```

**pszServer:** The custom binding handle for the target system, as specified in section 2.1.1. The value MUST NOT be used by the server implementation.

**dwReserved:** This value MUST be ignored by the server.

**ppCap:** The pointer to an INET\_INFO\_CAPABILITIES\_STRUCT structure that indicates the capabilities of the Internet protocol servers on the host system.

**Return Values:** The method returns 0 (ERROR\_SUCCESS) to indicate success; otherwise, it returns a nonzero error code, as specified in [MS-ERREF] section 2.2 or [MS-ERREF] section 2.3.1.

**ERROR\_SUCCESS** (0x00000000)

**Exceptions Thrown:** No exceptions are thrown beyond those thrown by the underlying RPC protocol, as specified in [MS-RPCE].

In response to this request from the client, the server MUST initialize *ppCap* with those features supported by the current version of the Internet protocol servers if the return code indicates success.

### 3.1.5.11 R\_W3QueryStatistics2 (Opnum 10)

The **R\_W3QueryStatistics2** method is called by the client. In response, the server returns statistical data from the HTTP server.

```
DWORD R_W3QueryStatistics2(  
    [in, string, unique] INET_INFO_IMPERSONATE_HANDLE pszServer,  
    [in] DWORD dwLevel,  
    [in] DWORD dwInstance,  
    [in] DWORD dwReserved,  
    [out, switch_is(dwLevel)] LPW3_STATISTICS_STRUCT InfoStruct  
);
```



**pszServer:** The custom binding handle for the target system, as specified in section 2.1.1. The value MUST NOT be used by the server implementation.

**dwLevel:** The level of detail to be retrieved. This parameter MUST be set to 0 by the client. Other values MUST generate a return code of ERROR\_INVALID\_LEVEL (0x0000007C).

**dwInstance:** The ID of the protocol server instance whose statistical data is being requested. The following values have special meanings.

Value	Meaning
0x00000000	Return global (not per server instance) statistics data.
0xf0000003	Return statistics aggregated across all protocol server instances.

**dwReserved:** This value MUST be ignored by the server.

**InfoStruct:** The pointer to a W3\_STATISTICS\_STRUCT union to contain the retrieved statistics data.

**Return Values:** The method returns 0 (ERROR\_SUCCESS) to indicate success; otherwise, it returns a nonzero error code, as specified in [MS-ERREF] section 2.2 or [MS-ERREF] section 2.3.1. The most common error codes are listed in the following table.

Return value/code	Description
0x00000002 ERROR_FILE_NOT_FOUND	The system cannot find the specified file.
0x0000007C ERROR_INVALID_LEVEL	The system call level is not correct.
0x00000426 ERROR_SERVICE_NOT_ACTIVE	The service is not running.

**Exceptions Thrown:** No exceptions are thrown beyond those thrown by the underlying RPC protocol, as specified in [MS-RPCE].

In response to this request from the client, the server MUST initialize *InfoStruct* with the statistical data for the HTTP server if the return code indicates success.

### 3.1.5.12 R\_W3ClearStatistics2 (Opnum 11)

The **R\_W3ClearStatistics2** method is called by the client. In response, the server resets statistical data for the HTTP server.

```
DWORD R_W3ClearStatistics2(  
    [in, string, unique] INET_INFO_IMPERSONATE_HANDLE pszServer,  
    [in] DWORD dwInstance  
);
```

**pszServer:** The custom binding handle for the target system, as specified in section 2.1.1. Value MUST NOT be used by the server implementation.

**dwInstance:** The ID of the protocol server instance whose statistical data is being cleared.

**Return Values:** The method returns 0 (ERROR\_SUCCESS) to indicate success; otherwise, it returns a nonzero error code, as specified in [MS-ERREF] section 2.2 or [MS-ERREF] section 2.3.1. The most common error codes are listed in the following table.

Return value/code	Description
0x00000002 ERROR_FILE_NOT_FOUND	The system cannot find the specified file.
0x00000005 ERROR_ACCESS_DENIED	Access is denied.
0x00000426 ERROR_SERVICE_NOT_ACTIVE	The service is not running.

**Exceptions Thrown:** No exceptions are thrown beyond those thrown by the underlying RPC protocol, as specified in [MS-RPCE].

In response to this request from the client, the server MAY reset the statistical data for the HTTP server if the return code indicates success. If the data is reset, a time stamp SHOULD be saved. This time stamp SHOULD be used to populate the **TimeOfLastClear** field of the W3\_STATISTICS\_1 structure in subsequent calls to R\_W3QueryStatistics2.<13>

### 3.1.5.13 R\_FtpQueryStatistics2 (Opnum 12)

The **R\_FtpQueryStatistics2** method is called by the client. In response, the server returns statistical data from the FTP server.

```
DWORD R_FtpQueryStatistics2(
    [in, string, unique] INET_INFO_IMPERSONATE_HANDLE pszServer,
    [in] DWORD dwLevel,
    [in] DWORD dwInstance,
    [in] DWORD dwReserved,
    [out, switch_is(dwLevel)] LPFTP_STATISTICS_STRUCT InfoStruct
);
```

**pszServer:** The custom binding handle for the target system, as specified in section 2.1.1. The value MUST NOT be used by the server implementation.

**dwLevel:** The level of detail to be retrieved. This parameter MUST be set to 0 by the client. Other values MUST generate a return code of ERROR\_INVALID\_LEVEL (0x0000007C).

**dwInstance:** The ID of the protocol server instance whose statistical data is being requested. The following values have special meanings.

Value	Meaning
0x00000000	Return global (not per server instance) statistics data.
0xF0000003	Return statistics aggregated across all protocol server instances.

**dwReserved:** This value MUST be ignored by the server.

**InfoStruct:** The pointer to an FTP\_STATISTICS\_STRUCT union to contain the retrieved statistics data.

**Return Values:** The method returns 0 (ERROR\_SUCCESS) to indicate success; otherwise, it returns a nonzero error code, as specified in [MS-ERREF] section 2.2 or [MS-ERREF] section 2.3.1. The most common error codes are listed in the following table.

Return value/code	Description
0x00000002	The system cannot find the specified file.

Return value/code	Description
ERROR_FILE_NOT_FOUND	
0x0000007C ERROR_INVALID_LEVEL	The system call level is not correct.
0x00000426 ERROR_SERVICE_NOT_ACTIVE	The service is not running.

**Exceptions Thrown:** No exceptions are thrown beyond those thrown by the underlying RPC protocol, as specified in [MS-RPCE].

In response to this request from the client, the server MUST initialize *InfoStruct* with the statistical data for the FTP server if the return code indicates success.

### 3.1.5.14 R\_FtpClearStatistics2 (Opnum 13)

The **R\_FtpClearStatistics2** method is called by the client. In response, the server resets statistical data for the FTP server.

```

DWORD R_FtpClearStatistics2(
    [in, string, unique] INET_INFO_IMPERSONATE_HANDLE pszServer,
    [in] DWORD dwInstance
);

```

**pszServer:** The custom binding handle for the target system, as specified in section 2.1.1. The value MUST NOT be used by the server implementation.

**dwInstance:** The ID of the protocol server instance whose statistical data is being cleared.

**Return Values:** The method returns 0 (ERROR\_SUCCESS) to indicate success; otherwise, it returns a nonzero error code, as specified in [MS-ERREF] section 2.2 or [MS-ERREF] section 2.3.1. The most common error codes are listed in the following table.

Return value/code	Description
0x00000002 ERROR_FILE_NOT_FOUND	The system cannot find the specified file.
0x00000005 ERROR_ACCESS_DENIED	Access is denied.
0x00000426 ERROR_SERVICE_NOT_ACTIVE	The service is not running.

**Exceptions Thrown:** No exceptions are thrown beyond those thrown by the underlying RPC protocol, as specified in [MS-RPCE].

In response to this request from the client, the server MAY reset the statistical data for the FTP server if the return code indicates success. If the data is reset, a time stamp SHOULD be saved. This time stamp SHOULD be used to populate the **TimeOfLastClear** field of the FTP\_STATISTICS\_0 structure in subsequent calls to R\_FtpQueryStatistics2.<14>

### 3.1.5.15 R\_IISEnumerateUsers (Opnum 14)

The **R\_IISEnumerateUsers** method is called by the client. In response, the server returns a list of clients connected to the specified Internet protocol server.

```
DWORD R_IISEnumerateUsers(  
    [in, string, unique] INET_INFO_IMPERSONATE_HANDLE pszServer,  
    [in] DWORD dwServiceId,  
    [in] DWORD dwInstance,  
    [in, out] LPIIS_USER_ENUM_STRUCT InfoStruct  
);
```

**pszServer:** The custom binding handle for the target system, as specified in section 2.1.1. The value MUST NOT be used by the server implementation.

**dwServiceId:** The identifier for the specified Internet protocol server, as specified in section 2.2.2.

**dwInstance:** The ID of the Internet protocol server instance whose users are being enumerated.

**InfoStruct:** The pointer to an IIS\_USER\_ENUM\_STRUCT that contains the list of active users for this server.

**Return Values:** The method returns 0 (ERROR\_SUCCESS) to indicate success; otherwise, it returns a nonzero error code, as specified in [MS-ERREF] section 2.2 or [MS-ERREF] section 2.3.1. The most common error codes are listed in the following table.

Return value/code	Description
0x00000002 ERROR_FILE_NOT_FOUND	The system cannot find the specified file.
0x00000005 ERROR_ACCESS_DENIED	Access is denied.
0x00000426 ERROR_SERVICE_NOT_ACTIVE	The service is not running.

**Exceptions Thrown:** No exceptions are thrown beyond those thrown by the underlying RPC protocol, as specified in [MS-RPCE].

In response to this request from the client, the server MAY return a list of the clients connected to the protocol server if the return code indicates success.<15>

### 3.1.5.16 R\_IISDisconnectUser (Opnum 15)

The **R\_IISDisconnectUser** method is called by the client. In response, the server disconnects the specified user from the specified Internet protocol server.

```
DWORD R_IISDisconnectUser(  
    [in, string, unique] INET_INFO_IMPERSONATE_HANDLE pszServer,  
    [in] DWORD dwServiceId,  
    [in] DWORD dwInstance,  
    [in] DWORD dwIdUser  
);
```

**pszServer:** The custom binding handle for the target system, as specified in section 2.1.1. The value MUST NOT be used by the server implementation.

**dwServiceId:** The identifier for the specified Internet protocol server, as specified in section 2.2.2.

**dwInstance:** The ID of the Internet protocol server instance whose user is being disconnected.

**dwIdUser:** The identifier of the user to disconnect, as found in the **idUser** field of the **IIS\_USER\_INFO\_1** structure returned by the **R\_IISEnumerateUsers** method. A value of 0 for this parameter indicates that the server implementation **MUST** attempt to disconnect all users from this Internet protocol server instance.

**Return Values:** The method returns 0 (**ERROR\_SUCCESS**) to indicate success; otherwise, it returns a nonzero error code, as specified in [MS-ERREF] section 2.2 or [MS-ERREF] section 2.3.1. The most common error codes are listed in the following table.

Return value/code	Description
0x00000002 ERROR_FILE_NOT_FOUND	The system cannot find the specified file.
0x00000005 ERROR_ACCESS_DENIED	Access is denied.
0x00000426 ERROR_SERVICE_NOT_ACTIVE	The service is not running.
0x000008AD NERR_UserNotFound	The user name could not be found.

**Exceptions Thrown:** No exceptions are thrown beyond those thrown by the underlying RPC protocol, as specified in [MS-RPCE].

In response to this request from the client, the server **MAY** disconnect a specific user if the *dwIdUser* value specifies that user and **SHOULD** attempt to disconnect all users if *dwIdUser* is 0.<16>

### 3.1.6 Timer Events

None.

### 3.1.7 Other Local Events

None.

## 4 Protocol Examples

This section describes a sequence of operations to illustrate the function of the Internet Information Services (IIS) Inetinfo Remote Protocol.

1. The client receives a request from an application to retrieve the virtual root directory of the FTP server on the server host.
2. The client sends an `R_InetInfoGetAdminInformation` message to the server by first invoking the **`R_InetInfoGetAdminInformation`** RPC client Stub method with the following parameters:
  - `pszServer` = "server host name"
  - `dwServerMask` = 0x00000001 (`INET_FTP_SVC_ID`)
  - `ppConfig` = address of `LPINET_INFO_CONFIG_INFO`
3. The client establishes a connection to the remote server by building an explicit server binding handle as specified in section 2.2.1.
4. When the server receives this request from the client, it allocates and initializes the `INET_INFO_CONFIG_INFO` structure and populates it with data from the FTP server. The server then returns 0 (`ERROR_SUCCESS`) and the pointer to the **`INET_INFO_CONFIG_INFO`** structure in the `ppConfig` parameter of the response.
5. The client retrieves the virtual root data from the returned **`INET_INFO_CONFIG_INFO`** structure, returns it to the application, and frees the data allocated by the RPC client Stub.

## 5 Security

### 5.1 Security Considerations for Implementers

None.

### 5.2 Index of Security Parameters

Security parameter	Section
RPC_C_AUTHN_WINNT	2.1.1
RPC_C_AUTHN_LEVEL_CONNECT	2.1.2
RPC_C_AUTHN_LEVEL_PKT_PRIVACY	2.1.2

## 6 Appendix A: Full IDL

For ease of implementation, the full IDL is provided where "ms-dtyp.idl" is the IDL, as specified in [MS-DTYP] Appendix A.

```
import "ms-dtyp.idl";

[
    uuid(82ad4280-036b-11cf-972c-00aa006887b0),
    version(2.0),
    ms_union,
    pointer_default(unique)
]
interface inetinfo
{

    typedef [handle] [string] LPWSTR INET_INFO_IMPERSONATE_HANDLE;

    typedef struct _INET_INFO_CAP_FLAGS {
        DWORD    Flag;
        DWORD    Mask;
    } INET_INFO_CAP_FLAGS,
        * LPINET_INFO_CAP_FLAGS;

    typedef struct _INET_INFO_CAPABILITIES_STRUCT {
        DWORD    CapVersion;
        DWORD    ProductType;
        DWORD    MajorVersion;
        DWORD    MinorVersion;
        DWORD    BuildNumber;
        DWORD    NumCapFlags;

        [size_is(NumCapFlags)] LPINET_INFO_CAP_FLAGS    CapFlags;
    } INET_INFO_CAPABILITIES_STRUCT,
        * LPINET_INFO_CAPABILITIES_STRUCT;

    typedef struct _INET_LOG_CONFIGURATION {
        DWORD    inetLogType;
        DWORD    ilPeriod;
        WCHAR    rgchLogFileDirectory[260];
        DWORD    cbSizeForTruncation;
        WCHAR    rgchDataSource[260];
        WCHAR    rgchTableName[30];
        WCHAR    rgchUserName[257];
        WCHAR    rgchPassword[257];
    } INET_LOG_CONFIGURATION,
        * LPINET_LOG_CONFIGURATION;

    typedef struct _INET_INFO_IP_SEC_ENTRY {
        DWORD    dwMask;
        DWORD    dwNetwork;
    } INET_INFO_IP_SEC_ENTRY,
        *LPINET_INFO_IP_SEC_ENTRY;

    typedef struct _INET_INFO_IP_SEC_LIST {
        DWORD    cEntries;
        [size_is( cEntries)] INET_INFO_IP_SEC_ENTRY    aIPSecEntry[];
    } INET_INFO_IP_SEC_LIST,
        *LPINET_INFO_IP_SEC_LIST;

    typedef struct _INET_INFO_VIRTUAL_ROOT_ENTRY {
        [string] LPWSTR    pszRoot;
        [string] LPWSTR    pszAddress;
    }
```



```

    [string] LPWSTR  pszDirectory;
    DWORD   dwMask;
    [string] LPWSTR  pszAccountName;
    WCHAR   AccountPassword[257];
    DWORD   dwError;
} INET_INFO_VIRTUAL_ROOT_ENTRY,
*LPINET_INFO_VIRTUAL_ROOT_ENTRY;

typedef struct _INET_INFO_VIRTUAL_ROOT_LIST
{
    DWORD           cEntries;
    [size_is( cEntries)]
        INET_INFO_VIRTUAL_ROOT_ENTRY  aVirtRootEntry[];
} INET_INFO_VIRTUAL_ROOT_LIST,
*LPINET_INFO_VIRTUAL_ROOT_LIST;

typedef struct _INET_INFO_CONFIG_INFO {
    DWORD           FieldControl;
    DWORD           dwConnectionTimeout;
    DWORD           dwMaxConnections;
    [string] LPWSTR lpszAdminName;
    [string] LPWSTR lpszAdminEmail;
    [string] LPWSTR lpszServerComment;
    LPINET_LOG_CONFIGURATION lpLogConfig;
    WORD           LangId;
    LCID           LocalId;
    BYTE           ProductId[64];
    BOOL           fLogAnonymous;
    BOOL           fLogNonAnonymous;
    [string] LPWSTR lpszAnonUserName;
    WCHAR          szAnonPassword[257];
    DWORD           dwAuthentication;
    short          sPort;
    LPINET_INFO_IP_SEC_LIST DenyIPList;
    LPINET_INFO_IP_SEC_LIST GrantIPList;
    LPINET_INFO_VIRTUAL_ROOT_LIST VirtualRoots;
} INET_INFO_CONFIG_INFO,
* LPINET_INFO_CONFIG_INFO;

typedef struct _INET_INFO_SITE_ENTRY {
    [string] LPWSTR  pszComment;
    DWORD   dwInstance;
} INET_INFO_SITE_ENTRY,
*LPINET_INFO_SITE_ENTRY;

typedef struct _INET_INFO_SITE_LIST {
    DWORD           cEntries;
    [size_is( cEntries)] INET_INFO_SITE_ENTRY  aSiteEntry[];
} INET_INFO_SITE_LIST,
*LPINET_INFO_SITE_LIST;

typedef struct _INET_INFO_GLOBAL_CONFIG_INFO {
    DWORD           FieldControl;
    DWORD           BandwidthLevel;
    DWORD           cbMemoryCacheSize;
} INET_INFO_GLOBAL_CONFIG_INFO,
* LPINET_INFO_GLOBAL_CONFIG_INFO;

typedef struct _INETA_CACHE_STATISTICS {
    DWORD FilesCached;
    DWORD TotalFilesCached;
    DWORD FileHits;
    DWORD FileMisses;
    DWORD FileFlushes;
    DWORDLONG CurrentFileCacheSize;
    DWORDLONG MaximumFileCacheSize;
    DWORD FlushedEntries;
    DWORD TotalFlushed;
    DWORD URICached;
    DWORD TotalURICached;
}

```

```

    DWORD URIFlushes;
    DWORD TotalURIFlushed;
    DWORD BlobCached;
    DWORD TotalBlobCached;
    DWORD BlobHits;
    DWORD BlobMisses;
    DWORD BlobFlushes;
    DWORD TotalBlobFlushed;
} INETA_CACHE_STATISTICS,
*LPINETA_CACHE_STATISTICS;

typedef struct _INETA_ATQ_STATISTICS {
    DWORD TotalBlockedRequests;
    DWORD TotalRejectedRequests;
    DWORD TotalAllowedRequests;
    DWORD CurrentBlockedRequests;
    DWORD MeasuredBandwidth;
} INETA_ATQ_STATISTICS,
*LPINETA_ATQ_STATISTICS;

typedef struct _INET_INFO_STATISTICS_0 {
    INETA_CACHE_STATISTICS CacheCtrs;
    INETA_ATQ_STATISTICS AtqCtrs;
    DWORD nAuxCounters;
    DWORD rgCounters[20];
} INET_INFO_STATISTICS_0,
* LPINET_INFO_STATISTICS_0;

typedef [switch_type(unsigned long)]
union _INET_INFO_STATISTICS_INFO {
    [case(0)]
        LPINET_INFO_STATISTICS_0 InetStats0;
    [default]
        ;
} INET_INFO_STATISTICS_INFO,
*LPINET_INFO_STATISTICS_INFO;

typedef struct _W3_STATISTICS_1 {
    LARGE_INTEGER TotalBytesSent;
    LARGE_INTEGER TotalBytesReceived;
    DWORD TotalFilesSent;
    DWORD TotalFilesReceived;
    DWORD CurrentAnonymousUsers;
    DWORD CurrentNonAnonymousUsers;
    DWORD TotalAnonymousUsers;
    DWORD TotalNonAnonymousUsers;
    DWORD MaxAnonymousUsers;
    DWORD MaxNonAnonymousUsers;
    DWORD CurrentConnections;
    DWORD MaxConnections;
    DWORD ConnectionAttempts;
    DWORD LogonAttempts;
    DWORD TotalOptions;
    DWORD TotalGets;
    DWORD TotalPosts;
    DWORD TotalHeads;
    DWORD TotalPuts;
    DWORD TotalDeletes;
    DWORD TotalTraces;
    DWORD TotalMove;
    DWORD TotalCopy;
    DWORD TotalMkcol;
    DWORD TotalPropfind;
    DWORD TotalProppatch;
    DWORD TotalSearch;
    DWORD TotalLock;
    DWORD TotalUnlock;
    DWORD TotalOthers;

```

```

        DWORD        TotalCGIRequests;
        DWORD        TotalBGIRequests;
        DWORD        TotalNotFoundErrors;
        DWORD        TotalLockedErrors;
        DWORD        CurrentCalAuth;
        DWORD        MaxCalAuth;
        DWORD        TotalFailedCalAuth;
        DWORD        CurrentCalSsl;
        DWORD        MaxCalSsl;
        DWORD        TotalFailedCalSsl;
        DWORD        CurrentCGIRequests;
        DWORD        CurrentBGIRequests;
        DWORD        MaxCGIRequests;
        DWORD        MaxBGIRequests;
        DWORD        CurrentBlockedRequests;
        DWORD        TotalBlockedRequests;
        DWORD        TotalAllowedRequests;
        DWORD        TotalRejectedRequests;
        DWORD        MeasuredBw;
        DWORD        ServiceUptime;
        DWORD        TimeOfLastClear;
        DWORD        nAuxCounters;
        DWORD        rgCounters[20];
} W3_STATISTICS_1,
* LPW3_STATISTICS_1;

typedef [switch_type(unsigned long)]
union _W3_STATISTICS_UNION {
    [case(0)]
        LPW3_STATISTICS_1 StatInfo1;
    [default]
        ;
} W3_STATISTICS_STRUCT,
*LPW3_STATISTICS_STRUCT;

typedef struct _FTP_STATISTICS_0 {
    LARGE_INTEGER TotalBytesSent;
    LARGE_INTEGER TotalBytesReceived;
    DWORD        TotalFilesSent;
    DWORD        TotalFilesReceived;
    DWORD        CurrentAnonymousUsers;
    DWORD        CurrentNonAnonymousUsers;
    DWORD        TotalAnonymousUsers;
    DWORD        TotalNonAnonymousUsers;
    DWORD        MaxAnonymousUsers;
    DWORD        MaxNonAnonymousUsers;
    DWORD        CurrentConnections;
    DWORD        MaxConnections;
    DWORD        ConnectionAttempts;
    DWORD        LogonAttempts;
    DWORD        ServiceUptime;
    DWORD        TotalAllowedRequests;
    DWORD        TotalRejectedRequests;
    DWORD        TotalBlockedRequests;
    DWORD        CurrentBlockedRequests;
    DWORD        MeasuredBandwidth;
    DWORD        TimeOfLastClear;
} FTP_STATISTICS_0,
* LPFTP_STATISTICS_0;

typedef [switch_type(unsigned long)]
union _FTP_STATISTICS_UNION {
    [case(0)]
        LPFTP_STATISTICS_0 StatInfo0;
    [default]
        ;
} FTP_STATISTICS_STRUCT,
*LPFTP_STATISTICS_STRUCT;

typedef struct _IIS_USER_INFO_1 {

```

```

        DWORD            idUser;
        [string] LPWSTR  pszUser;
        BOOL             fAnonymous;
        DWORD            inetHost;
        DWORD            tConnect;
    } IIS_USER_INFO_1,
    * LPIIS_USER_INFO_1;

typedef struct _IIS_USER_INFO_1_CONTAINER {
    DWORD EntriesRead;
    [size_is(EntriesRead)] LPIIS_USER_INFO_1 Buffer;
} IIS_USER_INFO_1_CONTAINER,
*LPIIS_USER_INFO_1_CONTAINER;

typedef struct _IIS_USER_ENUM_STRUCT {
    DWORD Level;
    [switch_is(Level)] union _USER_ENUM_UNION
    {
        [case(1)]
            LPIIS_USER_INFO_1_CONTAINER Level1;
        [default]
            ;
    } ConfigInfo;
} IIS_USER_ENUM_STRUCT,
*LPIIS_USER_ENUM_STRUCT;

DWORD
R_InetInfoGetVersion(
    [in, string, unique] INET_INFO_IMPERSONATE_HANDLE pszServer,
    [in] DWORD dwReserved,
    [out] DWORD *pdwVersion
);

DWORD
R_InetInfoGetAdminInformation(
    [in, string, unique] INET_INFO_IMPERSONATE_HANDLE pszServer,
    [in] DWORD dwServerMask,
    [out] LPINET_INFO_CONFIG_INFO *ppConfig
);

DWORD
R_InetInfoGetSites(
    [in, string, unique] INET_INFO_IMPERSONATE_HANDLE pszServer,
    [in] DWORD dwServerMask,
    [out] LPINET_INFO_SITE_LIST * ppSites
);

DWORD
R_InetInfoSetAdminInformation(
    [in, string, unique] INET_INFO_IMPERSONATE_HANDLE pszServer,
    [in] DWORD dwServerMask,
    [in, ref] INET_INFO_CONFIG_INFO *pConfig
);

DWORD
R_InetInfoGetGlobalAdminInformation(
    [in, string, unique] INET_INFO_IMPERSONATE_HANDLE      pszServer,
    [in] DWORD dwServerMask,
    [out] LPINET_INFO_GLOBAL_CONFIG_INFO *ppConfig
);

DWORD
R_InetInfoSetGlobalAdminInformation(
    [in, string, unique] INET_INFO_IMPERSONATE_HANDLE      pszServer,
    [in] DWORD dwServerMask,
    [in, ref] INET_INFO_GLOBAL_CONFIG_INFO * pConfig
);

DWORD
R_InetInfoQueryStatistics(

```

```

[in, string, unique] INET_INFO_IMPERSONATE_HANDLE pszServer,
[in] DWORD Level,
[in] DWORD dwServerMask,
[out, switch_is(Level)] LPINET_INFO_STATISTICS_INFO StatsInfo
);

DWORD
R_InetInfoClearStatistics(
[in, string, unique] INET_INFO_IMPERSONATE_HANDLE pszServer,
[in] DWORD dwServerMask
);

DWORD
R_InetInfoFlushMemoryCache(
[in, string, unique] INET_INFO_IMPERSONATE_HANDLE pszServer,
[in] DWORD dwServerMask
);

DWORD
R_InetInfoGetServerCapabilities(
[in, string, unique] INET_INFO_IMPERSONATE_HANDLE pszServer,
[in] DWORD dwReserved,
[out] LPINET_INFO_CAPABILITIES_STRUCT *ppCap
);

DWORD
R_W3QueryStatistics2(
[in, string, unique] INET_INFO_IMPERSONATE_HANDLE pszServer,
[in] DWORD dwLevel,
[in] DWORD dwInstance,
[in] DWORD dwReserved,
[out, switch_is(dwLevel)] LPW3_STATISTICS_STRUCT InfoStruct
);

DWORD
R_W3ClearStatistics2(
[in, string, unique] INET_INFO_IMPERSONATE_HANDLE pszServer,
[in] DWORD dwInstance
);

DWORD
R_FtpQueryStatistics2(
[in, string, unique] INET_INFO_IMPERSONATE_HANDLE pszServer,
[in] DWORD dwLevel,
[in] DWORD dwInstance,
[in] DWORD dwReserved,
[out, switch_is(dwLevel)] LPFTP_STATISTICS_STRUCT InfoStruct
);

DWORD
R_FtpClearStatistics2(
[in, string, unique] INET_INFO_IMPERSONATE_HANDLE pszServer,
[in] DWORD dwInstance
);

DWORD
R_IISEnumerateUsers(
[in, string, unique] INET_INFO_IMPERSONATE_HANDLE pszServer,
[in] DWORD dwServiceId,
[in] DWORD dwInstance,
[in, out] LPIIS_USER_ENUM_STRUCT InfoStruct
);

DWORD
R_IISDisconnectUser(
[in, string, unique] INET_INFO_IMPERSONATE_HANDLE pszServer,
[in] DWORD dwServiceId,
[in] DWORD dwInstance,
[in] DWORD dwIdUser
);

```

```
DWORD  
Opnum16NotUsedOnWire();
```

```
DWORD  
Opnum17NotUsedOnWire();  
}
```

## 7 (Updated Section) Appendix B: Product Behavior

The information in this specification is applicable to the following Microsoft products or supplemental software. References to product versions include updates to those products.

- Windows NT 4.0 operating system
- Windows 2000 Professional operating system
- Windows 2000 Server operating system
- Windows XP operating system
- Windows Server 2003 operating system
- Windows Vista operating system
- Windows Server 2008 operating system
- Windows 7 operating system
- Windows Server 2008 R2 operating system
- Windows 8 operating system
- Windows Server 2012 operating system
- Windows 8.1 operating system
- Windows Server 2012 R2 operating system
- Windows 10 operating system
- Windows Server 2016 operating system
- Windows Server operating system
- Windows Server 2019 operating system
- Windows Server 2022 operating system
- Windows 11 operating system

Exceptions, if any, are noted in this section. If an update version, service pack or Knowledge Base (KB) number appears with a product name, the behavior changed in that update. The new behavior also applies to subsequent updates unless otherwise specified. If a product edition appears with the product version, behavior is different in that product edition.

Unless otherwise specified, any statement of optional behavior in this specification that is prescribed using the terms "SHOULD" or "SHOULD NOT" implies product behavior in accordance with the SHOULD or SHOULD NOT prescription. Unless otherwise specified, the term "MAY" implies that the product does not follow the prescription.

<1> Section 1.7: The Internet Information Services (IIS) Inetinfo Remote Protocol is implemented in Windows by Internet Information Services (IIS). The RPC interface and data types have been modified between versions of IIS (without changing the version number) in ways that make complete interoperability between versions difficult if not impossible.

The version described as the standard in this document is IIS version 5.0 that shipped with Windows 2000 Professional, and Windows 2000 Server.

<2> Section 2.1.1: When the Windows implementation specifies "ncacn\_np" as the RPC protocol, a security descriptor is set on the endpoint (2) by using the RPC API RpcServerUseProtseqEpW(). The security descriptor grants access to members of the administrators group. The RPC runtime will then validate the client's identity against this security descriptor.

<3> Section 2.2.3: Some members of the INET\_INFO\_CONFIG\_INFO structure are not persisted such as **LangId** and **LocalId**. These vary by version and by protocol.

<4> Section 2.2.3: The Windows implementation will return an empty string when retrieving **szAnonPassword**, even if the configuration value is set.

<5> Section 2.2.8: The Windows implementation will return an empty string when retrieving **AccountPassword**, even if the configuration value is set.

<6> Section 2.2.15: The INETA\_CACHE\_STATISTICS structure has been modified twice in different versions of IIS.

IIS version 3.0 of the structure is defined as follows:

```
typedef struct _INETA_CACHE_STATISTICS
{
    DWORD      CacheBytesTotal;
    DWORD      CacheBytesInUse;
    DWORD      CurrentOpenFileHandles;
    DWORD      CurrentDirLists;
    DWORD      CurrentObjects;
    DWORD      FlushesFromDirChanges;
    DWORD      CacheHits;
    DWORD      CacheMisses;
} INETA_CACHE_STATISTICS * LPINETA_CACHE_STATISTICS;
```

**CacheBytesTotal:** The total size of the cache in bytes.

**CacheBytesInUse:** The number of bytes in the cache currently in use.

**CurrentOpenFileHandles:** The number of handles to currently open files stored in the cache.

**CurrentDirLists:** The number of current directory lists stored in the cache.

**CurrentObjects:** The number of current objects stored in the cache.

**FlushesFromDirChanges:** The number of flushes that have taken place as a result of directory changes.

**CacheHits:** The number of hits to the cache.

**CacheMisses:** The number of misses to the cache.

IIS version 6.0 of the structure is defined as follows:

```
typedef struct _INETA_CACHE_STATISTICS
{
    DWORD FilesCached;
    DWORD TotalFilesCached;
```



```

    DWORD FileHits;
    DWORD FileMisses;
    DWORD FileFlushes;
    DWORDLONG CurrentFileCacheSize;
    DWORDLONG MaximumFileCacheSize;
    DWORD FlushedEntries;
    DWORD TotalFlushed;
    DWORD URICached;
    DWORD TotalURICached;
    DWORD URITHits;
    DWORD URIMisses;
    DWORD URIFlushes;
    DWORD TotalURIFlushed;
    DWORD BlobCached;
    DWORD TotalBlobCached;
    DWORD BlobHits;
    DWORD BlobMisses;
    DWORD BlobFlushes;
    DWORD TotalBlobFlushed;
} INETA_CACHE_STATISTICS, *LPINETA_CACHE_STATISTICS;

```

**CurrentFileCacheSize** and **MaximumFileCacheSize** are the only fields changed from the IIS version 5.0. Their data types have been changed from DWORD to DWORDLONG.

<7> Section 2.2.25: The Windows implementation can return error codes that have additional semantic meaning because it relates to the protocol beyond that which is specified in [MS-ERREF]. The following table summarizes these additional semantics.

Return value/code	Interpretation/condition
0x00000426 ERROR_SERVICE_NOT_ACTIVE	Used to indicate that the specified Internet protocol service is not recognized by the implementation.
0x00000002 ERROR_FILE_NOT_FOUND	Used by methods that operate on an Internet protocol server instance to indicate that the instance ID passed by the client is not recognized.

<8> Section 3.1.5: Opnums reserved for local use apply to Windows as follows.

Opnum	Description
16, 17	Only used locally by Windows, never remotely. These methods were added to the inetinfo interface in Windows 2000 Server and deprecated in Windows Server 2003.

<9> Section 3.1.5.1: The Windows implementation of R\_InetInfoGetVersion does not return Major Version = 5 and Minor Version = 1 for implementations of IIS released on Windows NT 4.0, Windows 2000 Professional, and Windows 2000 Server.

<10> Section 3.1.5.3: In IIS version 3.0, the R\_InetInfoGetSites method is not implemented. Instead, the following method is defined at opnum 2.

```

R_InetInfoDummy(
    [in, string, unique] INET_INFO_IMPERSONATE_HANDLE pszServer,
    [in] DWORD dwServerMask,
    [out] LPINET_INFO_CONFIG_INFO *ppConfig

```

);

This method returns 0 and does nothing.

<11> Section 3.1.5.7: The Windows implementation of `R_InetInfoQueryStatistics` returns valid statistical data only when the `dwServerMask` parameter is 0.

<12> Section 3.1.5.8: The Windows implementation of `R_InetInfoClearStatistics` does nothing and returns `ERROR_NOT_SUPPORTED`. If `dwServerMask` is greater than `0x00000004`, the return code is `ERROR_INVALID_PARAMETER`.

<13> Section 3.1.5.12: The Windows implementation of `R_W3ClearStatistics2` does not reset all statistics values in the `W3_STATISTICS_1` structure. Values related to client network connections and network bandwidth are not reset.

<14> Section 3.1.5.14: The Windows implementation of `R_FtpClearStatistics2` does not reset all statistics values in the `FTP_STATISTICS_0` structure. Values related to client network connections and network bandwidth are not reset.

<15> Section 3.1.5.15: The Windows implementation of `R_IISEnumerateUsers` returns `ERROR_SUCCESS` (`0x00000000`) for the HTTP server when the method is not implemented.

<16> Section 3.1.5.16: The Windows implementation of `R_IISDisconnectUser` for the FTP server will attempt to disconnect specific users in addition to all users, given appropriate values of `dwIdUser`. The HTTP server will only attempt to disconnect all users if `dwIdUser` is 0 and will ignore other values of this parameter and return `ERROR_SUCCESS`.

## 8 Change Tracking

This section identifies changes that were made to this document since the last release. Changes are classified as Major, Minor, or None.

The revision class **Major** means that the technical content in the document was significantly revised. Major changes affect protocol interoperability or implementation. Examples of major changes are:

- A document revision that incorporates changes to interoperability requirements.
- A document revision that captures changes to protocol functionality.

The revision class **Minor** means that the meaning of the technical content was clarified. Minor changes do not affect protocol interoperability or implementation. Examples of minor changes are updates to clarify ambiguity at the sentence, paragraph, or table level.

The revision class **None** means that no new technical changes were introduced. Minor editorial and formatting changes may have been made, but the relevant technical content is identical to the last released version.

The changes made to this document are listed in the following table. For more information, please contact [dochelp@microsoft.com](mailto:dochelp@microsoft.com).

Section	Description	Revision class
7 Appendix B: Product Behavior	Updated for this version of Windows Client.	Major

## 9 Index

### A

Abstract data model  
  server 31  
Abstract data model - server 31  
Applicability 10

### C

Capability negotiation 10  
Change tracking 59  
Client - transport 11  
Common data types 11

### D

Data model - abstract  
  server 31  
Data model - abstract - server 31  
Data types 11  
  common - overview 11

### E

Events  
  local - server 45  
  timer - server 45  
Examples 46  
  overview 46

### F

Fields - vendor-extensible 10  
FTP\_STATISTICS\_0 structure 28  
Full IDL 48

### G

Glossary 7

### H

Higher-layer triggered events - server 31

### I

IDL 48  
IIS\_USER\_ENUM\_STRUCT structure 29  
IIS\_USER\_INFO\_1 structure 30  
IIS\_USER\_INFO\_1\_CONTAINER structure 29  
Implementer - security considerations 47  
Index of security parameters 47  
INET\_CHAT\_SVC\_ID 12  
INET\_DNS\_SVC\_ID 12  
INET\_FTP\_SVC\_ID 12  
INET\_GATEWAY\_SVC\_ID 12  
INET\_GOPHER\_SVC\_ID 12  
INET\_HTTP\_PROXY 12  
INET\_HTTP\_SVC\_ID 12  
INET\_IMAP\_SVC\_ID 12  
INET\_INFO\_CAP\_FLAGS structure 22

- INET\_INFO\_CAPABILITIES\_STRUCT structure 21
- INET\_INFO\_CONFIG\_INFO structure 12
- INET\_INFO\_GLOBAL\_CONFIG\_INFO structure 18
- INET\_INFO\_IP\_SEC\_ENTRY structure 16
- INET\_INFO\_IP\_SEC\_LIST structure 16
- INET\_INFO\_SITE\_ENTRY structure 18
- INET\_INFO\_SITE\_LIST structure 17
- INET\_INFO\_STATISTICS\_0 structure 19
- INET\_INFO\_VIRTUAL\_ROOT\_ENTRY structure 17
- INET\_INFO\_VIRTUAL\_ROOT\_LIST structure 17
- INET\_LDAP\_SVC\_ID 12
- INET\_LOG\_CONFIGURATION structure 15
- INET\_NNTP\_SVC\_ID 12
- INET\_POP3\_SVC\_ID 12
- INET\_SMTP\_SVC\_ID 12
- INETA\_ATQ\_STATISTICS structure 19
- INETA\_CACHE\_STATISTICS structure 20
- inetinfo interface 31
- Informative references 9
- Initialization
  - server 31
- Initialization - server 31
- Interfaces - server
  - inetinfo 31
- Introduction 7

## L

- Local events
  - server 45
- Local events - server 45
- LPFTP\_STATISTICS\_0 28
- LPIIS\_USER\_ENUM\_STRUCT 29
- LPIIS\_USER\_INFO\_1 30
- LPIIS\_USER\_INFO\_1\_CONTAINER 29
- LPINET\_INFO\_CAP\_FLAGS 22
- LPINET\_INFO\_CAPABILITIES\_STRUCT 21
- LPINET\_INFO\_CONFIG\_INFO 12
- LPINET\_INFO\_GLOBAL\_CONFIG\_INFO 18
- LPINET\_INFO\_IP\_SEC\_ENTRY 16
- LPINET\_INFO\_IP\_SEC\_LIST 16
- LPINET\_INFO\_SITE\_ENTRY 18
- LPINET\_INFO\_SITE\_LIST 17
- LPINET\_INFO\_STATISTICS\_0 19
- LPINET\_INFO\_VIRTUAL\_ROOT\_ENTRY 17
- LPINET\_INFO\_VIRTUAL\_ROOT\_LIST 17
- LPINET\_LOG\_CONFIGURATION 15
- LPINETA\_ATQ\_STATISTICS 19
- LPINETA\_CACHE\_STATISTICS 20
- LPW3\_STATISTICS\_1 25

## M

- Message processing
  - server 31
- Message processing - server 31
- Messages
  - common data types 11
  - data types 11
  - transport 11
- Methods
  - R\_FtpClearStatistics2 (Opnum 13) 43
  - R\_FtpQueryStatistics2 (Opnum 12) 42
  - R\_IISDisconnectUser (Opnum 15) 44
  - R\_IISEnumerateUsers (Opnum 14) 44

R\_InetInfoClearStatistics (Opnum 7) 39  
R\_InetInfoFlushMemoryCache (Opnum 8) 39  
R\_InetInfoGetAdminInformation (Opnum 1) 35  
R\_InetInfoGetGlobalAdminInformation (Opnum 4) 37  
R\_InetInfoGetServerCapabilities (Opnum 9) 40  
R\_InetInfoGetSites (Opnum 2) 35  
R\_InetInfoGetVersion (Opnum 0) 34  
R\_InetInfoQueryStatistics (Opnum 6) 38  
R\_InetInfoSetAdminInformation (Opnum 3) 36  
R\_InetInfoSetGlobalAdminInformation (Opnum 5) 37  
R\_W3ClearStatistics2 (Opnum 11) 41  
R\_W3QueryStatistics2 (Opnum 10) 40

## N

Normative references 9

## O

Overview (synopsis) 9

## P

Parameters - security index 47  
Preconditions 10  
Prerequisites 10  
Product behavior 55  
Protocol Details  
    overview 31

## R

R\_FtpClearStatistics2 (Opnum 13) method 43  
R\_FtpClearStatistics2 method 43  
R\_FtpQueryStatistics2 (Opnum 12) method 42  
R\_FtpQueryStatistics2 method 42  
R\_IISDisconnectUser (Opnum 15) method 44  
R\_IISDisconnectUser method 44  
R\_IISEnumerateUsers (Opnum 14) method 44  
R\_IISEnumerateUsers method 44  
R\_InetInfoClearStatistics (Opnum 7) method 39  
R\_InetInfoClearStatistics method 39  
R\_InetInfoFlushMemoryCache (Opnum 8) method 39  
R\_InetInfoFlushMemoryCache method 39  
R\_InetInfoGetAdminInformation (Opnum 1) method 35  
R\_InetInfoGetAdminInformation method 35  
R\_InetInfoGetGlobalAdminInformation (Opnum 4) method 37  
R\_InetInfoGetGlobalAdminInformation method 37  
R\_InetInfoGetServerCapabilities (Opnum 9) method 40  
R\_InetInfoGetServerCapabilities method 40  
R\_InetInfoGetSites (Opnum 2) method 35  
R\_InetInfoGetSites method 35  
R\_InetInfoGetVersion (Opnum 0) method 34  
R\_InetInfoGetVersion method 34  
R\_InetInfoQueryStatistics (Opnum 6) method 38  
R\_InetInfoQueryStatistics method 38  
R\_InetInfoSetAdminInformation (Opnum 3) method 36  
R\_InetInfoSetAdminInformation method 36  
R\_InetInfoSetGlobalAdminInformation (Opnum 5) method 37  
R\_InetInfoSetGlobalAdminInformation method 37  
R\_W3ClearStatistics2 (Opnum 11) method 41  
R\_W3ClearStatistics2 method 41  
R\_W3QueryStatistics2 (Opnum 10) method 40  
R\_W3QueryStatistics2 method 40  
References 8

- informative 9
- normative 9
- Relationship to other protocols 10

## S

- Security
  - implementer considerations 47
  - parameter index 47
- Sequencing rules
  - server 31
- Sequencing rules - server 31
- Server
  - abstract data model 31
  - higher-layer triggered events 31
  - inetsvc interface 31
  - initialization 31
  - local events 45
  - message processing 31
  - overview 31
  - R\_FtpClearStatistics2 (Opnum 13) method 43
  - R\_FtpQueryStatistics2 (Opnum 12) method 42
  - R\_IISDisconnectUser (Opnum 15) method 44
  - R\_IISEnumerateUsers (Opnum 14) method 44
  - R\_InetInfoClearStatistics (Opnum 7) method 39
  - R\_InetInfoFlushMemoryCache (Opnum 8) method 39
  - R\_InetInfoGetAdminInformation (Opnum 1) method 35
  - R\_InetInfoGetGlobalAdminInformation (Opnum 4) method 37
  - R\_InetInfoGetServerCapabilities (Opnum 9) method 40
  - R\_InetInfoGetSites (Opnum 2) method 35
  - R\_InetInfoGetVersion (Opnum 0) method 34
  - R\_InetInfoQueryStatistics (Opnum 6) method 38
  - R\_InetInfoSetAdminInformation (Opnum 3) method 36
  - R\_InetInfoSetGlobalAdminInformation (Opnum 5) method 37
  - R\_W3ClearStatistics2 (Opnum 11) method 41
  - R\_W3QueryStatistics2 (Opnum 10) method 40
  - sequencing rules 31
  - timer events 45
  - timers 31
  - transport 11
- Standards assignments 10

## T

- Timer events
  - server 45
- Timer events - server 45
- Timers
  - server 31
- Timers - server 31
- Tracking changes 59
- Transport 11
  - client 11
  - overview 11
  - server 11
- Triggered events - higher-layer - server 31

## V

- Vendor-extensible fields 10
- Versioning 10

## W

- W3\_STATISTICS\_1 structure 25

