

[MS-OAPX]: OAuth 2.0 Protocol Extensions

This topic lists the Errata found in [MS-OAPX] since it was last published. Since this topic is updated frequently, we recommend that you subscribe to these RSS or Atom feeds to receive update notifications.



Errata are subject to the same terms as the Open Specifications documentation referenced.

Errata below are for Protocol Document Version [V4.0 – 2016/07/14](#).

Errata Published*	Description								
2016/08/04 (updated) 2016/07/18	<p>In several sections, added and updated information about the prompt URI parameter regarding its existing behavior and behavior that is modified through KB/QFE 3172614.</p> <p>In Section 1.2.1, Normative References, included the following reference: [MSKB-3172614] Microsoft Corporation, "July 2016 update rollup for Windows RT 8.1, Windows 8.1, and Windows Server 2012 R2", https://support.microsoft.com/en-us/kb/3172614.</p> <p>In Section 2.2.2, Common URI Parameters, changed from:</p> <table border="1" data-bbox="402 919 1458 1150"> <thead> <tr> <th data-bbox="402 919 932 972">URI parameter</th> <th data-bbox="937 919 1458 972">Description</th> </tr> </thead> <tbody> <tr> <td data-bbox="402 978 932 1150">prompt</td> <td data-bbox="937 978 1458 1150">OPTIONAL. This query parameter is used in the same way as the prompt parameter defined in [OIDCCore] section 3.1.2.1. The AD FS server ignores this parameter unless its ad_fs_behavior_level is AD_FS_BEHAVIOR_LEVEL_2 or higher.</td> </tr> </tbody> </table> <p>Changed to:</p> <table border="1" data-bbox="402 1230 1458 1520"> <thead> <tr> <th data-bbox="402 1230 932 1283">URI parameter</th> <th data-bbox="937 1230 1458 1283">Description</th> </tr> </thead> <tbody> <tr> <td data-bbox="402 1289 932 1520">prompt</td> <td data-bbox="937 1289 1458 1520">OPTIONAL. This query parameter is used in the same way as the prompt parameter defined in [OIDCCore] section 3.1.2.1, but the only accepted values for this parameter are "none" and "login". This parameter and the accepted values specified above SHOULD<2> be supported for all values of ad_fs_behavior_level.</td> </tr> </tbody> </table> <p><2> Section 2.2.2: The prompt parameter is not supported on Windows Server 2012 R2 unless [MSKB-3172614] is installed. Even with [MSKB-3172614] installed, the "none" value for the parameter is not supported on Windows Server 2012 R2.</p> <p>In Section 2.2.2.7, prompt, changed from: ... The prompt query parameter is OPTIONAL, and can be specified by the client role of the OAuth 2.0 Protocol Extensions. This parameter has the same behavior as the prompt parameter defined in [OIDCCore] section 3.1.2.1, but can be specified regardless of whether the client role also requests the "openid" scope. The AD FS server ignores this parameter unless its ad_fs_behavior_level is AD_FS_BEHAVIOR_LEVEL_2 or higher.</p>	URI parameter	Description	prompt	OPTIONAL. This query parameter is used in the same way as the prompt parameter defined in [OIDCCore] section 3.1.2.1. The AD FS server ignores this parameter unless its ad_fs_behavior_level is AD_FS_BEHAVIOR_LEVEL_2 or higher.	URI parameter	Description	prompt	OPTIONAL. This query parameter is used in the same way as the prompt parameter defined in [OIDCCore] section 3.1.2.1, but the only accepted values for this parameter are "none" and "login". This parameter and the accepted values specified above SHOULD<2> be supported for all values of ad_fs_behavior_level.
URI parameter	Description								
prompt	OPTIONAL. This query parameter is used in the same way as the prompt parameter defined in [OIDCCore] section 3.1.2.1. The AD FS server ignores this parameter unless its ad_fs_behavior_level is AD_FS_BEHAVIOR_LEVEL_2 or higher.								
URI parameter	Description								
prompt	OPTIONAL. This query parameter is used in the same way as the prompt parameter defined in [OIDCCore] section 3.1.2.1, but the only accepted values for this parameter are "none" and "login". This parameter and the accepted values specified above SHOULD<2> be supported for all values of ad_fs_behavior_level.								

Errata Published*	Description
	<p>...</p> <p>Changed to:</p> <p>...</p> <p>The prompt query parameter is OPTIONAL, and can be specified by the client role of the OAuth 2.0 Protocol Extensions. This parameter has the same behavior as the prompt parameter defined in [OIDCCore] section 3.1.2.1 (see section 2.2.2 for exceptions and support information), but can be specified regardless of whether the client role also requests the "openid" scope.</p> <p>...</p> <p>In Section 3.2.5.1.1, GET, changed from:</p> <p>...</p> <p>prompt: OPTIONAL. The client can choose to specify this optional query parameter. It is used in the same way as the prompt parameter defined in [OIDCCore] section 3.1.2.1.</p> <p>...</p> <p>Changed to:</p> <p>...</p> <p>prompt: OPTIONAL. The client can choose to specify this optional query parameter. It is used in the same way as the prompt parameter defined in [OIDCCore] section 3.1.2.1.</p> <p>Note Support for the prompt parameter depends on the AD FS server's ad_fs_behavior_level and the product version. See section 2.2.2 for support information.</p> <p>...</p> <p>In Section 3.2.5.1.1.3, Processing Details, changed from:</p> <p>...</p> <ul style="list-style-type: none"> • If the AD FS server's ad_fs_behavior_level is AD_FS_BEHAVIOR_LEVEL_2 or higher and the OAuth 2.0 client provided a value of "none" or "login" for the prompt query parameter, the AD FS server follows the behavior described for the prompt parameter in [OIDCCore] section 3.1.2.1. <p>...</p> <p>Changed to:</p> <p>...</p> <ul style="list-style-type: none"> • If the prompt query parameter is supported and the OAuth 2.0 client provided a value of "none" or "login" for the prompt query parameter, the AD FS server follows the behavior described for the prompt parameter in [OIDCCore] section 3.1.2.1. <p>Note Support for the prompt parameter depends on the AD FS server's ad_fs_behavior_level and the product version. See section 2.2.2 for support information.</p> <p>...</p> <p>In Section 4.10, Authorization Code Request with prompt Parameter, changed from:</p> <p>Refer to [RFC6749] section 4.1.1 (Authorization Request). For more information on the prompt parameter, see [OIDCCore] section 3.1.2.1.</p> <p>...</p> <p>Changed to:</p> <p>Refer to [RFC6749] section 4.1.1 (Authorization Request). For more information on the prompt parameter, see section 2.2.2 and [OIDCCore] section 3.1.2.1.</p> <p>...</p>

* Date format: YYYY/MM/DD

