

[MS-TSTS]: Terminal Services Terminal Server Runtime Interface Protocol

This topic lists the Errata found in [MS-TSTS] since it was last published. Since this topic is updated frequently, we recommend that you subscribe to these RSS or Atom feeds to receive update notifications.



Errata are subject to the same terms as the Open Specifications documentation referenced.

Errata below are for Protocol Document Version [V26.0 – 2018/09/12](#).

| Errata Published* | Description |
|-------------------|--|
| 2019/04/15 | <p>In Section 3.10.4.1.1, RpcShadow2 (Opnum 0), the format of the pszInvitation field has been clarified. In addition, a reference to a Windows platform-specific API has been removed and substituted with a link to MS-RAI Section 2.2.2.</p> <p>Changed from:</p> <p>pszInvitation: The output data containing the invitation string for the shadow session. The data returned is an invitation string in an XML format that can be used with the Windows Desktop Sharing API IRDPSRAPViewer::Connect method to connect to the session running in the target session (specified by TargetSessionId). The caller must allocate a buffer to hold this data and specify the size of the buffer in cchInvitation.</p> <p>Changed to:</p> <p>pszInvitation: The output data containing the invitation string for the shadow session. The data returned is a Unicode string in the XML format specified in [MS-RAI] section 2.2.2 that can be used to connect to a session running in the target session (specified by TargetSessionId). The caller must allocate a buffer to hold this data and specify the size of the buffer in cchInvitation.</p> |

*Date format: YYYY/MM/DD