

[MS-UCODEREF]: Windows Protocols Unicode Reference

Intellectual Property Rights Notice for Open Specifications Documentation

- **Technical Documentation.** Microsoft publishes Open Specifications documentation for protocols, file formats, languages, standards as well as overviews of the interaction among each of these technologies.
- **Copyrights.** This documentation is covered by Microsoft copyrights. Regardless of any other terms that are contained in the terms of use for the Microsoft website that hosts this documentation, you may make copies of it in order to develop implementations of the technologies described in the Open Specifications and may distribute portions of it in your implementations using these technologies or your documentation as necessary to properly document the implementation. You may also distribute in your implementation, with or without modification, any schema, IDL's, or code samples that are included in the documentation. This permission also applies to any documents that are referenced in the Open Specifications.
- **No Trade Secrets.** Microsoft does not claim any trade secret rights in this documentation.
- **Patents.** Microsoft has patents that may cover your implementations of the technologies described in the Open Specifications. Neither this notice nor Microsoft's delivery of the documentation grants any licenses under those or any other Microsoft patents. However, a given Open Specification may be covered by Microsoft [Open Specification Promise](#) or the [Community Promise](#). If you would prefer a written license, or if the technologies described in the Open Specifications are not covered by the Open Specifications Promise or Community Promise, as applicable, patent licenses are available by contacting iplg@microsoft.com.
- **Trademarks.** The names of companies and products contained in this documentation may be covered by trademarks or similar intellectual property rights. This notice does not grant any licenses under those rights. For a list of Microsoft trademarks, visit www.microsoft.com/trademarks.
- **Fictitious Names.** The example companies, organizations, products, domain names, email addresses, logos, people, places, and events depicted in this documentation are fictitious. No association with any real company, organization, product, domain name, email address, logo, person, place, or event is intended or should be inferred.

Reservation of Rights. All other rights are reserved, and this notice does not grant any rights other than specifically described above, whether by implication, estoppel, or otherwise.

Tools. The Open Specifications do not require the use of Microsoft programming tools or programming environments in order for you to develop an implementation. If you have access to Microsoft programming tools and environments you are free to take advantage of them. Certain Open Specifications are intended for use in conjunction with publicly available standard specifications and network programming art, and assumes that the reader either is familiar with the aforementioned material or has immediate access to it.

Revision Summary

| Date | Revision History | Revision Class | Comments |
|------------|------------------|----------------|--|
| 02/14/2008 | 2.0.1 | Editorial | Revised and edited the technical content. |
| 03/14/2008 | 2.0.2 | Editorial | Revised and edited the technical content. |
| 05/16/2008 | 2.0.3 | Editorial | Revised and edited the technical content. |
| 06/20/2008 | 3.0 | Major | Updated and revised the technical content. |
| 07/25/2008 | 3.0.1 | Editorial | Revised and edited the technical content. |
| 08/29/2008 | 3.0.2 | Editorial | Revised and edited the technical content. |
| 10/24/2008 | 3.0.3 | Editorial | Revised and edited the technical content. |
| 12/05/2008 | 3.1 | Minor | Updated the technical content. |
| 01/16/2009 | 3.1.1 | Editorial | Revised and edited the technical content. |
| 02/27/2009 | 3.1.2 | Editorial | Revised and edited the technical content. |
| 04/10/2009 | 3.1.3 | Editorial | Revised and edited the technical content. |
| 05/22/2009 | 3.1.4 | Editorial | Revised and edited the technical content. |
| 07/02/2009 | 4.0 | Major | Updated and revised the technical content. |
| 08/14/2009 | 4.0.1 | Editorial | Revised and edited the technical content. |
| 09/25/2009 | 4.1 | Minor | Updated the technical content. |
| 11/06/2009 | 5.0 | Major | Updated and revised the technical content. |
| 12/18/2009 | 6.0 | Major | Updated and revised the technical content. |
| 01/29/2010 | 7.0 | Major | Updated and revised the technical content. |
| 03/12/2010 | 7.0.1 | Editorial | Revised and edited the technical content. |
| 04/23/2010 | 7.0.2 | Editorial | Revised and edited the technical content. |
| 06/04/2010 | 7.0.3 | Editorial | Revised and edited the technical content. |
| 07/16/2010 | 7.0.3 | No change | No changes to the meaning, language, or formatting of the technical content. |
| 08/27/2010 | 7.0.3 | No change | No changes to the meaning, language, or formatting of the technical content. |
| 10/08/2010 | 7.0.3 | No change | No changes to the meaning, language, or formatting of the technical content. |
| 11/19/2010 | 7.0.3 | No change | No changes to the meaning, language, or formatting of |

| Date | Revision History | Revision Class | Comments |
|-------------|-------------------------|-----------------------|--|
| | | | the technical content. |
| 01/07/2011 | 7.0.3 | No change | No changes to the meaning, language, or formatting of the technical content. |
| 02/11/2011 | 7.0.3 | No change | No changes to the meaning, language, or formatting of the technical content. |
| 03/25/2011 | 7.0.3 | No change | No changes to the meaning, language, or formatting of the technical content. |
| 05/06/2011 | 7.0.3 | No change | No changes to the meaning, language, or formatting of the technical content. |
| 06/17/2011 | 7.1 | Minor | Clarified the meaning of the technical content. |
| 09/23/2011 | 7.1 | No change | No changes to the meaning, language, or formatting of the technical content. |
| 12/16/2011 | 8.0 | Major | Significantly changed the technical content. |
| 03/30/2012 | 9.0 | Major | Significantly changed the technical content. |
| 07/12/2012 | 9.0 | No change | No changes to the meaning, language, or formatting of the technical content. |
| 10/25/2012 | 9.0 | No change | No changes to the meaning, language, or formatting of the technical content. |
| 01/31/2013 | 9.0 | No change | No changes to the meaning, language, or formatting of the technical content. |
| 08/08/2013 | 9.1 | Minor | Clarified the meaning of the technical content. |
| 11/14/2013 | 9.1 | No change | No changes to the meaning, language, or formatting of the technical content. |

Contents

| | |
|--|-----------|
| 1 Introduction | 6 |
| 1.1 Glossary | 6 |
| 1.2 References | 6 |
| 1.2.1 Normative References | 7 |
| 1.2.2 Informative References | 8 |
| 1.3 Overview | 8 |
| 1.4 Applicability Statement | 8 |
| 1.5 Standards Assignments | 9 |
| 2 Messages | 10 |
| 2.1 Transport | 10 |
| 2.2 Message Syntax | 10 |
| 2.2.1 Supported Codepage in Windows | 10 |
| 2.2.2 Supported Codepage Data Files | 18 |
| 2.2.2.1 Codepage Data File Format | 18 |
| 2.2.2.1.1 WCTABLE | 19 |
| 2.2.2.1.2 MBTABLE | 20 |
| 2.2.2.1.3 DBCSRANGE | 21 |
| 3 Protocol Details | 23 |
| 3.1 Client Details | 23 |
| 3.1.1 Abstract Data Model | 23 |
| 3.1.2 Timers | 23 |
| 3.1.3 Initialization | 23 |
| 3.1.4 Higher-Layer Triggered Events | 23 |
| 3.1.5 Message Processing Events and Sequencing Rules | 23 |
| 3.1.5.1 Mapping Between UTF-16 Strings and Legacy Codepages | 23 |
| 3.1.5.1.1 Mapping Between UTF-16 Strings and Legacy Codepages Using CodePage Data File | 23 |
| 3.1.5.1.1.1 Pseudocode for Accessing a Record in the Codepage Data File | 23 |
| 3.1.5.1.1.2 Pseudocode for Mapping a UTF-16 String to a Codepage String | 24 |
| 3.1.5.1.1.3 Pseudocode for Mapping a Codepage String to a UTF-16 String | 27 |
| 3.1.5.1.2 Mapping Between UTF-16 Strings and ISO 2022-Based Codepages | 30 |
| 3.1.5.1.3 Mapping between UTF-16 Strings and GB 18030 Codepage | 30 |
| 3.1.5.1.4 Mapping Between UTF-16 Strings and ISCII Codepage | 30 |
| 3.1.5.1.5 Mapping Between UTF-16 Strings and UTF-7 | 30 |
| 3.1.5.1.6 Mapping Between UTF-16 Strings and UTF-8 | 30 |
| 3.1.5.2 Comparing UTF-16 Strings by Using Sort Keys | 30 |
| 3.1.5.2.1 Pseudocode for Comparing UTF-16 Strings | 30 |
| 3.1.5.2.2 CompareSortKey | 31 |
| 3.1.5.2.3 Accessing the Windows Sorting Weight Table | 32 |
| 3.1.5.2.3.1 Windows Sorting Weight Table | 34 |
| 3.1.5.2.4 GetWindowsSortKey Pseudocode | 34 |
| 3.1.5.2.5 TestHungarianCharacterSequences | 47 |
| 3.1.5.2.6 GetContractionType | 48 |
| 3.1.5.2.7 CorrectUnicodeWeight | 49 |
| 3.1.5.2.8 MakeUnicodeWeight | 50 |
| 3.1.5.2.9 GetCharacterWeights | 50 |
| 3.1.5.2.10 GetExpansionWeights | 51 |
| 3.1.5.2.11 GetExpandedCharacters | 52 |

| | | |
|------------|---|-----------|
| 3.1.5.2.12 | SortkeyContractionHandler | 53 |
| 3.1.5.2.13 | Check3ByteWeightLocale..... | 57 |
| 3.1.5.2.14 | SpecialCaseHandler | 58 |
| 3.1.5.2.15 | GetPositionSpecialWeight | 63 |
| 3.1.5.2.16 | MapOldHangulSortKey | 63 |
| 3.1.5.2.17 | GetJamoComposition | 66 |
| 3.1.5.2.18 | GetJamoStateData..... | 67 |
| 3.1.5.2.19 | FindNewJamoState | 68 |
| 3.1.5.2.20 | UpdateJamoSortInfo | 69 |
| 3.1.5.2.21 | IsJamo..... | 70 |
| 3.1.5.2.22 | IsCombiningJamo | 71 |
| 3.1.5.2.23 | IsJamoLeading | 71 |
| 3.1.5.2.24 | IsJamoVowel..... | 72 |
| 3.1.5.2.25 | IsJamoTrailing | 73 |
| 3.1.5.2.26 | InitKoreanScriptMap | 73 |
| 3.1.5.3 | Mapping UTF-16 Strings to Upper Case | 74 |
| 3.1.5.3.1 | ToUpperCase | 74 |
| 3.1.5.3.2 | UpperCaseMapping..... | 74 |
| 3.1.6 | Timer Events | 75 |
| 3.1.7 | Other Local Events | 75 |
| 4 | Protocol Examples..... | 76 |
| 5 | Security..... | 77 |
| 5.1 | Security Considerations for Implementers..... | 77 |
| 5.2 | Index of Security Parameters | 77 |
| 6 | Appendix A: Product Behavior..... | 78 |
| 7 | Change Tracking..... | 85 |
| 8 | Index | 86 |

1 Introduction

This document is a companion reference to the protocol specifications. It describes how **Unicode** strings are compared in Windows protocols and how Windows supports Unicode conversion to earlier **codepages**. For example:

- **UTF-16** string comparison: Provides linguistic-specific comparisons between two Unicode strings and provides the comparison result based on the language and region for a specific user.
- Mapping of UTF-16 strings to earlier ANSI codepages: Converts Unicode strings to strings in the earlier codepages that are used in older versions of Windows and the applications that are written for these earlier codepages.

Sections 1.8, 2, and 3 of this specification are normative and can contain the terms MAY, SHOULD, MUST, MUST NOT, and SHOULD NOT as defined in RFC 2119. Sections 1.5 and 1.9 are also normative but cannot contain those terms. All other sections and examples in this specification are informative.

1.1 Glossary

The following terms are defined in [\[MS-GLOS\]](#):

Unicode UTF-16

The following terms are specific to this document:

codepage: An ordered set of characters of a specific script in which a numerical index (code-point value) is associated with each character. In this document, the term **codepage** is used in the context of **codepages** defined by Windows; **codepages** can also be called character sets or charsets.

double-byte character set (DBCS): A character encoding in which the codepoints can be either one or two bytes. For example, the **DBCS** is used to encode Chinese, Japanese, and Korean languages.

single-byte character set (SBCS): A character encoding in which each character is represented by one byte. **Single-byte character sets** are limited to 256 characters.

sort keys: Numerical representations of a sort element based on locale-specific sorting rules. A sort key consists of several weighted components that represent a character's script, diacritics, case, and additional treatment based on locale.

MAY, SHOULD, MUST, SHOULD NOT, MUST NOT: These terms (in all caps) are used as described in [\[RFC2119\]](#). All statements of optional behavior use either MAY, SHOULD, or SHOULD NOT.

1.2 References

References to Microsoft Open Specifications documentation do not include a publishing year because links are to the latest version of the documents, which are updated frequently. References to other documents include a publishing year when one is available.

A reference marked "(Archived)" means that the reference document was either retired and is no longer being maintained or was replaced with a new document that provides current implementation details. We archive our documents online [[Windows Protocol](#)].

1.2.1 Normative References

We conduct frequent surveys of the normative references to assure their continued availability. If you have any issue with finding a normative reference, please contact dochelp@microsoft.com. We will assist you in finding the relevant information. Please check the archive site, <http://msdn2.microsoft.com/en-us/library/E4BD6494-06AD-4aed-9823-445E921C9624>, as an additional source.

[CODEPAGEFILES] Microsoft Corporation, "Windows Supported Code Page Data Files.zip", 2009, <http://www.microsoft.com/downloads/details.aspx?FamilyID=5fdc09fb-afec-4c2a-9394-6d046841eace&displaylang=en>

If you have any trouble finding [CODEPAGEFILES], please check [here](#).

[ECMA-035] ECMA International, "Character Code Structure and Extension Techniques", 6th edition, ECMA-035, December 1994, <http://www.ecma-international.org/publications/standards/Ecma-035.htm>

[GB18030] Chinese IT Standardization Technical Committee, "Chinese National Standard GB 18030-2005: Information technology - Chinese coded character set", Published in print by the China Standard Press, http://220.194.5.109/stdlinfo/servlet/com.sac.sacQuery.GjbzcxDetailServlet?std_code=GB

[ISCII] Bureau of Indian Standards, "Indian Script Code for Information Exchange - ISCII", <http://www.bis.org.in/dir/sales.htm>

If you have any trouble finding [ISCII], please check [here](#).

[MSDN-SWT/Vista] Microsoft Corporation, "Windows Vista Sorting Weight Table.txt", <http://www.microsoft.com/downloads/details.aspx?FamilyID=5fdc09fb-afec-4c2a-9394-6d046841eace&displaylang=en>

[MSDN-SWT/W2K3] Microsoft Corporation, "Windows NT 4.0 through Windows Server 2003 Sorting Weight Table.txt", <http://www.microsoft.com/downloads/details.aspx?FamilyID=5fdc09fb-afec-4c2a-9394-6d046841eace&displaylang=en>

[MSDN-SWT/W2K8] Microsoft Corporation, "Windows Server 2008 Sorting Weight Table.txt", <http://www.microsoft.com/downloads/details.aspx?FamilyID=5fdc09fb-afec-4c2a-9394-6d046841eace&displaylang=en>

[MSDN-SWT/Win7] Microsoft Corporation, "Windows 7 through Server 2008 R2 Sorting Weight Table.txt", <http://www.microsoft.com/downloads/details.aspx?FamilyID=5fdc09fb-afec-4c2a-9394-6d046841eace&displaylang=en>

If you have any trouble finding [MSDN-SWT/Win7], please check [here](#).

[MSDN-SWT/Win8] Microsoft Corporation, "Sorting Weight Table", <http://www.microsoft.com/downloads/details.aspx?FamilyID=5fdc09fb-afec-4c2a-9394-6d046841eace&displaylang=en>

If you have any trouble finding [MSDN-SWT/Win8], please check [here](#).

[MSDN-UCMT/Win8] Microsoft Corporation, "Windows 8 Upper Case Mapping Table", <http://www.microsoft.com/download/en/details.aspx?displaylang=en&id=10921>

If you have any trouble finding [MSDN-UCMT/Win8], please check [here](#).

[RFC2119] Bradner, S., "Key words for use in RFCs to Indicate Requirement Levels", BCP 14, RFC 2119, March 1997, <http://www.rfc-editor.org/rfc/rfc2119.txt>

[RFC2152] Goldsmith, D., and David, M., "UTF-7 A Mail-Safe Transformation Format of Unicode", RFC 2152, May 1997, <http://www.ietf.org/rfc/rfc2152.txt>

[UNICODE] The Unicode Consortium, "Unicode Home Page", 2006, <http://www.unicode.org/>

[UNICODE-BESTFIT] The Unicode Consortium, "WindowsBestFit", 2006, <http://www.unicode.org/Public/MAPPINGS/VENDORS/MICSFT/WindowsBestFit/>

[UNICODE-COLLATION] The Unicode Consortium, "Unicode Technical Standard #10 Unicode Collation Algorithm", March 2008, <http://www.unicode.org/reports/tr10/>

[UNICODE-README] The Unicode Consortium, "Readme.txt", 2006, <http://unicode.org/Public/MAPPINGS/VENDORS/MICSFT/WindowsBestFit/readme.txt>

[UNICODE5.0.0/CH3] The Unicode Consortium, "Unicode Encoding Forms", 2006, <http://www.unicode.org/versions/Unicode5.0.0/ch03.pdf#G7404>

1.2.2 Informative References

[MS-GLOS] Microsoft Corporation, "[Windows Protocols Master Glossary](#)".

[MS-LCID] Microsoft Corporation, "[Windows Language Code Identifier \(LCID\) Reference](#)".

1.3 Overview

This document describes the following protocols when dealing with Unicode strings on the Windows platform:

- UTF-16 string comparison: This string comparison is used to provide a linguistic-specific comparison between two Unicode strings. This scenario provides a string comparison result based on the expectations of users from different languages and different regions.
- The mapping of UTF-16 strings to earlier codepages: This scenario is used to convert between Unicode strings and strings in the earlier codepage, which are used by older versions of Windows and applications written for these earlier codepages.

1.4 Applicability Statement

This reference document is applicable as follows:

- To perform UTF-16 character comparisons in the same manner as Windows. This document only specifies a subset of Windows behaviors that are used by other protocols. It does not document those Windows behaviors that are not used by other protocols.
- To provide the capability to map between UTF-16 strings and earlier codepages in the same manner as Windows.

1.5 Standards Assignments

The following standards assignments are used by the Windows Protocols Unicode Reference.

| Parameter | Value | Reference |
|--|---------|-----------------------------------|
| Codepage Data File (section 2.2.2) | Various | [UNICODE-BESTFIT] |

2 Messages

The following sections specify how Windows Protocols Unicode Reference messages are transported and Windows Protocols Unicode Reference message syntax.

2.1 Transport

2.2 Message Syntax

2.2.1 Supported Codepage in Windows

Windows assigns an integer, called code page ID, to every supported codepage.

Based on the usage, the codepage supported in Windows can be categorized in the following:

- ANSI codepage

ANSI codepages are codepages for which non-ASCII values (values greater than 127) represent international characters. [<1>](#)

Windows codepages are also sometimes referred to as active codepages or system active codepages. Windows always has one currently active Windows codepage. All ANSI Windows functions use the currently active codepage.

The usual ANSI codepage ID for US English is codepage 1252.

Windows codepage 1252, the codepage commonly used for English and other Western European languages, was based on an American National Standards Institute (ANSI) draft. That draft eventually became ISO 8859-1, but Windows codepage 1252 was implemented before the standard became final, and is not exactly the same as ISO 8859-1.

- OEM codepage

Original equipment manufacturer (OEM) codepages are codepages for which non-ASCII values represent line drawing and punctuation characters. These codepages are still used for console applications. They are also used for the non-extended file names in the FAT12, FAT16, and FAT32 file systems. The usual OEM codepage ID for US English is codepage 437.

- Extended codepage

These codepages cannot be used as ANSI codepages, or OEM codepages. Windows can support conversions between Unicode and these codepages. These codepages are generally used for information exchange purpose with international/national standard or legacy systems. Examples are UTF-8, UTF-7, EBCDIC, and Macintosh codepages.

The following table shows all the supported codepages by Windows. The Codepage ID lists the integer number assigned to a codepage. ANSI/OEM codepages are in bold face. The Codepage Description column describes the codepage. The Codepage notes column lists the category of a codepage and the relevant protocol section in this document to find protocol information.

| Codepage ID | Codepage descriptions | Codepage notes |
|--------------------|------------------------------|--|
| 37 | IBM EBCDIC US-Canada | Extended codepage; for processing rules, see section 3.1.5.1.1 . |

| Codepage ID | Codepage descriptions | Codepage notes |
|--------------------|--|--|
| 437 | OEM United States | OEM codepage; for processing rules, see section 3.1.5.1.1 . |
| 500 | IBM EBCDIC International | Extended codepage; for processing rules, see section 3.1.5.1.1 . |
| 708 | Arabic (ASMO 708) | Extended codepage; for processing rules, see section 3.1.5.1.1 . |
| 720 | Arabic (Transparent ASMO); Arabic (DOS) | Extended codepage; for processing rules, see section 3.1.5.1.1 . |
| 737 | OEM Greek (formerly 437G); Greek (DOS) | OEM codepage; for processing rules, see section 3.1.5.1.1 . |
| 775 | OEM Baltic; Baltic (DOS) | OEM codepage; for processing rules, see section 3.1.5.1.1 . |
| 850 | OEM Multilingual Latin 1; Western European (DOS) | OEM codepage; for processing rules, see section 3.1.5.1.1 . |
| 852 | OEM Latin 2; Central European (DOS) | OEM codepage; for processing rules, see section 3.1.5.1.1 . |
| 855 | OEM Cyrillic (primarily Russian) | OEM codepage; for processing rules, see section 3.1.5.1.1 . |
| 857 | OEM Turkish; Turkish (DOS) | OEM codepage; for processing rules, see section 3.1.5.1.1 . |
| 858 | OEM Multilingual Latin 1 + Euro symbol | OEM codepage; for processing rules, see section 3.1.5.1.1 . |
| 860 | OEM Portuguese; Portuguese (DOS) | OEM codepage; for processing rules, see section 3.1.5.1.1 . |
| 861 | OEM Icelandic; Icelandic (DOS) | OEM codepage; for processing rules, see section 3.1.5.1.1 . |
| 862 | OEM Hebrew; Hebrew (DOS) | OEM codepage; for processing rules, see section 3.1.5.1.1 . |
| 863 | OEM French Canadian; French Canadian (DOS) | OEM codepage; for processing rules, see section 3.1.5.1.1 . |
| 864 | OEM Arabic; Arabic (864) | OEM codepage; for processing rules, see section 3.1.5.1.1 . |
| 865 | OEM Nordic; Nordic (DOS) | OEM codepage; for processing rules, see section 3.1.5.1.1 . |
| 866 | OEM Russian; Cyrillic (DOS) | OEM codepage; for processing rules, see section 3.1.5.1.1 . |
| 869 | OEM Modern Greek; Greek, Modern (DOS) | OEM codepage; for processing rules, see section 3.1.5.1.1 . |

| Codepage ID | Codepage descriptions | Codepage notes |
|--------------------|---|--|
| 870 | IBM EBCDIC Multilingual/ROECE (Latin 2); IBM EBCDIC Multilingual Latin 2 | Extended codepage; for processing rules, see section 3.1.5.1.1 . |
| 874 | ANSI/OEM Thai (same as 28605, ISO 8859-15); Thai (Windows) | ANSI codepage; for processing rules, see section 3.1.5.1.1 . |
| 875 | IBM EBCDIC Greek Modern | Extended codepage; for processing rules, see section 3.1.5.1.1 . |
| 932 | ANSI/OEM Japanese; Japanese (Shift-JIS) | ANSI/OEM codepage; for processing rules, see section 3.1.5.1.1 . |
| 936 | ANSI/OEM Simplified Chinese (PRC, Singapore); Chinese Simplified (GB2312) | ANSI/OEM codepage; for processing rules, see section 3.1.5.1.1 . |
| 949 | ANSI/OEM Korean (Unified Hangul Code) | ANSI/OEM codepage; for processing rules, see section 3.1.5.1.1 . |
| 950 | ANSI/OEM Traditional Chinese (Taiwan; Hong Kong SAR, PRC); Chinese Traditional (Big5) | ANSI/OEM codepage; for processing rules, see section 3.1.5.1.1 . |
| 1026 | IBM EBCDIC Turkish (Latin 5) | Extended codepage; for processing rules, see section 3.1.5.1.1 . |
| 1047 | IBM EBCDIC Latin 1/Open System | Extended codepage; for processing rules, see section 3.1.5.1.1 . |
| 1140 | IBM EBCDIC US-Canada (037 + Euro symbol); IBM EBCDIC (US-Canada-Euro) | Extended codepage; for processing rules, see section 3.1.5.1.1 . |
| 1141 | IBM EBCDIC Germany (20273 + Euro symbol); IBM EBCDIC (Germany-Euro) | Extended codepage; for processing rules, see section 3.1.5.1.1 . |
| 1142 | IBM EBCDIC Denmark-Norway (20277 + Euro symbol); IBM EBCDIC (Denmark-Norway-Euro) | Extended codepage; for processing rules, see section 3.1.5.1.1 . |
| 1143 | IBM EBCDIC Finland-Sweden (20278 + Euro symbol); IBM EBCDIC (Finland-Sweden-Euro) | Extended codepage; for processing rules, see section 3.1.5.1.1 . |
| 1144 | IBM EBCDIC Italy (20280 + Euro symbol); IBM EBCDIC (Italy-Euro) | Extended codepage; for processing rules, see section 3.1.5.1.1 . |
| 1145 | IBM EBCDIC Latin America-Spain (20284 + Euro symbol); IBM EBCDIC (Spain-Euro) | Extended codepage; for processing rules, see section 3.1.5.1.1 . |
| 1146 | IBM EBCDIC United Kingdom (20285 + Euro symbol); IBM EBCDIC (UK-Euro) | Extended codepage; for processing rules, see section 3.1.5.1.1 . |
| 1147 | IBM EBCDIC France (20297 + Euro symbol); IBM EBCDIC (France-Euro) | Extended codepage; for processing rules, see section 3.1.5.1.1 . |

| Codepage ID | Codepage descriptions | Codepage notes |
|--------------------|---|--|
| 1148 | IBM EBCDIC International (500 + Euro symbol); IBM EBCDIC (International-Euro) | Extended codepage; for processing rules, see section 3.1.5.1.1 . |
| 1149 | IBM EBCDIC Icelandic (20871 + Euro symbol); IBM EBCDIC (Icelandic-Euro) | Extended codepage; for processing rules, see section 3.1.5.1.1 . |
| 1200 | Unicode UTF-16, little-endian byte order (BMP of ISO 10646); available only to managed applications | Not used in Windows. |
| 1201 | Unicode UTF-16, big-endian byte order; available only to managed applications | Not used in Windows. |
| 1250 | ANSI Central European; Central European (Windows) | ANSI codepage; for processing rules, see section 3.1.5.1.1 . |
| 1251 | ANSI Cyrillic; Cyrillic (Windows) | ANSI codepage; for processing rules, see section 3.1.5.1.1 . |
| 1252 | ANSI Latin 1; Western European (Windows) | ANSI codepage; for processing rules, see section 3.1.5.1.1 . |
| 1253 | ANSI Greek; Greek (Windows) | ANSI codepage; for processing rules, see section 3.1.5.1.1 . |
| 1254 | ANSI Turkish; Turkish (Windows) | ANSI codepage; for processing rules, see section 3.1.5.1.1 . |
| 1255 | ANSI Hebrew; Hebrew (Windows) | ANSI codepage; for processing rules, see section 3.1.5.1.1 . |
| 1256 | ANSI Arabic; Arabic (Windows) | ANSI codepage; for processing rules, see section 3.1.5.1.1 . |
| 1257 | ANSI Baltic; Baltic (Windows) | ANSI codepage; for processing rules, see section 3.1.5.1.1 . |
| 1258 | ANSI/OEM Vietnamese; Vietnamese (Windows) | ANSI codepage; for processing rules, see section 3.1.5.1.1 . |
| 1361 | Korean (Johab) | Extended codepage; for processing rules, see section 3.1.5.1.1 . |
| 10000 | MAC Roman; Western European (Mac) | Extended codepage; for processing rules, see section 3.1.5.1.1 . |
| 10001 | Japanese (Mac) | Extended codepage; for processing rules, see section 3.1.5.1.1 . |
| 10002 | MAC Traditional Chinese (Big5); Chinese Traditional (Mac) | Extended codepage; for processing rules, see section 3.1.5.1.1 . |
| 10003 | Korean (Mac) | Extended codepage; for processing rules, see section 3.1.5.1.1 . |
| 10004 | Arabic (Mac) | Extended codepage; for processing rules, see |

| Codepage ID | Codepage descriptions | Codepage notes |
|--------------------|--|--|
| | | section 3.1.5.1.1 . |
| 10005 | Hebrew (Mac) | Extended codepage; for processing rules, see section 3.1.5.1.1 . |
| 10006 | Greek (Mac) | Extended codepage; for processing rules, see section 3.1.5.1.1 . |
| 10007 | Cyrillic (Mac) | Extended codepage; for processing rules, see section 3.1.5.1.1 . |
| 10008 | MAC Simplified Chinese (GB 2312); Chinese Simplified (Mac) | Extended codepage; for processing rules, see section 3.1.5.1.1 . |
| 10010 | Romanian (Mac) | Extended codepage; for processing rules, see section 3.1.5.1.1 . |
| 10017 | Ukrainian (Mac) | Extended codepage; for processing rules, see section 3.1.5.1.1 . |
| 10021 | Thai (Mac) | Extended codepage; for processing rules, see section 3.1.5.1.1 . |
| 10029 | MAC Latin 2; Central European (Mac) | Extended codepage; for processing rules, see section 3.1.5.1.1 . |
| 10079 | Icelandic (Mac) | Extended codepage; for processing rules, see section 3.1.5.1.1 . |
| 10081 | Turkish (Mac) | Extended codepage; for processing rules, see section 3.1.5.1.1 . |
| 10082 | Croatian (Mac) | Extended codepage; for processing rules, see section 3.1.5.1.1 . |
| 12000 | Unicode UTF-32, little-endian byte order; available only to managed applications | Not used in Windows. |
| 12001 | Unicode UTF-32, big-endian byte order; available only to managed applications | Not used in Windows. |
| 20000 | CNS Taiwan; Chinese Traditional (CNS) | Extended codepage; for processing rules, see section 3.1.5.1.1 . |
| 20001 | TCA Taiwan | Extended codepage; for processing rules, see section 3.1.5.1.1 . |
| 20002 | Eten Taiwan; Chinese Traditional (Eten) | Extended codepage; for processing rules, see section 3.1.5.1.1 . |
| 20003 | IBM5550 Taiwan | Extended codepage; for processing rules, see section 3.1.5.1.1 . |
| 20004 | TeleText Taiwan | Extended codepage; for processing rules, see section 3.1.5.1.1 . |

| Codepage ID | Codepage descriptions | Codepage notes |
|--------------------|---|--|
| 20005 | Wang Taiwan | Extended codepage; for processing rules, see section 3.1.5.1.1 . |
| 20105 | IA5 (IRV International Alphabet No. 5, 7-bit); Western European (IA5) | Extended codepage; for processing rules, see section 3.1.5.1.1 . |
| 20106 | IA5 German (7-bit) | Extended codepage; for processing rules, see section 3.1.5.1.1 . |
| 20107 | IA5 Swedish (7-bit) | Extended codepage; for processing rules, see section 3.1.5.1.1 . |
| 20108 | IA5 Norwegian (7-bit) | Extended codepage; for processing rules, see section 3.1.5.1.1 . |
| 20127 | US-ASCII (7-bit) | Extended codepage; for processing rules, see section 3.1.5.1.1 . |
| 20261 | T.61 | Extended codepage; for processing rules, see section 3.1.5.1.1 . |
| 20269 | ISO 6937 Non-Spacing Accent | Extended codepage; for processing rules, see section 3.1.5.1.1 . |
| 20273 | IBM EBCDIC Germany | Extended codepage; for processing rules, see section 3.1.5.1.1 . |
| 20277 | IBM EBCDIC Denmark-Norway | Extended codepage; for processing rules, see section 3.1.5.1.1 . |
| 20278 | IBM EBCDIC Finland-Sweden | Extended codepage; for processing rules, see section 3.1.5.1.1 . |
| 20280 | IBM EBCDIC Italy | Extended codepage; for processing rules, see section 3.1.5.1.1 . |
| 20284 | IBM EBCDIC Latin America-Spain | Extended codepage; for processing rules, see section 3.1.5.1.1 . |
| 20285 | IBM EBCDIC United Kingdom | Extended codepage; for processing rules, see section 3.1.5.1.1 . |
| 20290 | IBM EBCDIC Japanese Katakana Extended | Extended codepage; for processing rules, see section 3.1.5.1.1 . |
| 20297 | IBM EBCDIC France | Extended codepage; for processing rules, see section 3.1.5.1.1 . |
| 20420 | IBM EBCDIC Arabic | Extended codepage; for processing rules, see section 3.1.5.1.1 . |
| 20423 | IBM EBCDIC Greek | Extended codepage; for processing rules, see section 3.1.5.1.1 . |
| 20424 | IBM EBCDIC Hebrew | Extended codepage; for processing rules, see section 3.1.5.1.1 . |

| Codepage ID | Codepage descriptions | Codepage notes |
|--------------------|---|--|
| 20833 | IBM EBCDIC Korean Extended | Extended codepage; for processing rules, see section 3.1.5.1.1 . |
| 20838 | IBM EBCDIC Thai | Extended codepage; for processing rules, see section 3.1.5.1.1 . |
| 20866 | Russian (KOI8-R); Cyrillic (KOI8-R) | Extended codepage; for processing rules, see section 3.1.5.1.1 . |
| 20871 | IBM EBCDIC Icelandic | Extended codepage; for processing rules, see section 3.1.5.1.1 . |
| 20880 | IBM EBCDIC Cyrillic Russian | Extended codepage; for processing rules, see section 3.1.5.1.1 . |
| 20905 | IBM EBCDIC Turkish | Extended codepage; for processing rules, see section 3.1.5.1.1 . |
| 20924 | IBM EBCDIC Latin 1/Open System (1047 + Euro symbol) | Extended codepage; for processing rules, see section 3.1.5.1.1 . |
| 20932 | Japanese (JIS 0208-1990 and 0121-1990) | Extended codepage; for processing rules, see section 3.1.5.1.1 . |
| 20936 | Simplified Chinese (GB2312); Chinese Simplified (GB2312-80) | Extended codepage; for processing rules, see section 3.1.5.1.1 . |
| 20949 | Korean Wansung | Extended codepage; for processing rules, see section 3.1.5.1.1 . |
| 21025 | IBM EBCDIC Cyrillic Serbian-Bulgarian | Extended codepage; for processing rules, see section 3.1.5.1.1 . |
| 21027 | Ext Alpha Lowercase | Extended codepage; for processing rules, see section 3.1.5.1.1 . NOTE: Although this codepage is supported, it has no known use. |
| 21866 | Ukrainian (KOI8-U); Cyrillic (KOI8-U) | Extended codepage; for processing rules, see section 3.1.5.1.1 . |
| 28591 | ISO 8859-1 Latin 1; Western European (ISO) | Extended codepage; for processing rules, see section 3.1.5.1.1 . |
| 28592 | ISO 8859-2 Central European; Central European (ISO) | Extended codepage; for processing rules, see section 3.1.5.1.1 . |
| 28593 | ISO 8859-3 Latin 3 | Extended codepage; for processing rules, see section 3.1.5.1.1 . |
| 28594 | ISO 8859-4 Baltic | Extended codepage; for processing rules, see section 3.1.5.1.1 . |
| 28595 | ISO 8859-5 Cyrillic | Extended codepage; for processing rules, see section 3.1.5.1.1 . |
| 28596 | ISO 8859-6 Arabic | Extended codepage; for processing rules, see section 3.1.5.1.1 . |

| Codepage ID | Codepage descriptions | Codepage notes |
|--------------------|---|---|
| 28597 | ISO 8859-7 Greek | Extended codepage; for processing rules, see section 3.1.5.1.1 . |
| 28598 | ISO 8859-8 Hebrew; Hebrew (ISO-Visual) | Extended codepage; for processing rules, see section 3.1.5.1.1 . |
| 28599 | ISO 8859-9 Turkish | Extended codepage; for processing rules, see section 3.1.5.1.1 . |
| 28603 | ISO 8859-13 Estonian | Extended codepage; for processing rules, see section 3.1.5.1.1 . |
| 28605 | ISO 8859-15 Latin 9 | Extended codepage; for processing rules, see section 3.1.5.1.1 . |
| 38598 | ISO 8859-8 Hebrew; Hebrew (ISO-Logical) | Extended codepage; for processing rules, see section 3.1.5.1.1 . Use [CODEPAGEFILES] 28598.txt. |
| 50220 | ISO 2022 Japanese with no halfwidth Katakana; Japanese (JIS) | Extended codepage; for processing rules, see section 3.1.5.1.1 . |
| 50221 | ISO 2022 Japanese with halfwidth Katakana; Japanese (JIS-Allow 1 byte Kana) | Extended codepage; for processing rules, see section 3.1.5.1.2 . |
| 50222 | ISO 2022 Japanese JIS X 0201-1989; Japanese (JIS-Allow 1 byte Kana - SO/SI) | Extended codepage; for processing rules, see section 3.1.5.1.2 . |
| 50225 | ISO 2022 Korean | Extended codepage; for processing rules, see section 3.1.5.1.2 . |
| 50227 | ISO 2022 Simplified Chinese; Chinese Simplified (ISO 2022) | Extended codepage; for processing rules, see section 3.1.5.1.2 . |
| 50229 | ISO 2022 Traditional Chinese | Extended codepage; for processing rules, see section 3.1.5.1.2 . |
| 51949 | EUC Korean | Extended codepage; for processing rules, see section 3.1.5.1.2 . Use [CODEPAGEFILES] 20949.txt. |
| 52936 | HZ-GB2312 Simplified Chinese; Chinese Simplified (HZ) | Extended codepage; for processing rules, see section 3.1.5.1.2 . |
| 54936 | GB18030 Simplified Chinese (4 byte); Chinese Simplified (GB18030) | Extended codepage; for processing rules, see section 3.1.5.1.3 . |
| 57002 | ISCII Devanagari | Extended codepage; for processing rules, see section 3.1.5.1.4 . |
| 57003 | ISCII Bengali | Extended codepage; for processing rules, see section 3.1.5.1.4 . |
| 57004 | ISCII Tamil | Extended codepage; for processing rules, see section 3.1.5.1.4 . |

| Codepage ID | Codepage descriptions | Codepage notes |
|-------------|------------------------|--|
| 57005 | ISCII Telugu | Extended codepage; for processing rules, see section 3.1.5.1.4 . |
| 57006 | ISCII Assamese | Extended codepage; for processing rules, see section 3.1.5.1.4 . |
| 57007 | ISCII Odia (was Oriya) | Extended codepage; for processing rules, see section 3.1.5.1.4 . |
| 57008 | ISCII Kannada | Extended codepage; for processing rules, see section 3.1.5.1.4 . |
| 57009 | ISCII Malayalam | Extended codepage; for processing rules, see section 3.1.5.1.4 . |
| 57010 | ISCII Gujarati | Extended codepage; for processing rules, see section 3.1.5.1.4 . |
| 57011 | ISCII Punjabi | Extended codepage; for processing rules, see section 3.1.5.1.4 . |
| 65000 | Unicode (UTF-7) | Extended codepage; for processing rules, see section 3.1.5.1.5 . |
| 65001 | Unicode (UTF-8) | Extended codepage; for processing rules, see section 3.1.5.1.6 . |

2.2.2 Supported Codepage Data Files

The mapping of UTF-16 strings to codepages relies on codepage data files to provide conversion data. These codepage data files map Unicode characters to characters in a **single-byte character set (SBCS)** or **double-byte character set (DBCS)**.

The data files of supported system codepages are published as specified in [\[CODEPAGEFILES\]](#), [\[UNICODE\]](#), and [\[UNICODE-BESTFIT\]](#). The location identification uses a simple file-naming convention, which is bestfitxxxx.txt, where xxxx is the codepage number. For example, bestfit950.txt contains the data for codepage 950, and bestfit1252.txt contains the data for codepage 1252.

The pseudocode assumes all these codepage files are available.

2.2.2.1 Codepage Data File Format

The Readme.txt (as specified in [\[UNICODE-README\]](#)) provides details about the codepages files and the file format. This section specifies information about the pseudocode of mapping UTF-16 strings to earlier codepages by taking the content from the Readme.txt.

Each file has sections of keyword tags and records. Any text after ";" is ignored as blank lines. Fields are delimited by one or more space or tab characters. Each section begins with one of the following tags:

- CODEPAGE ([\[UNICODE-README\]](#))
- CPINFO ([\[UNICODE-README\]](#))

- [MBTABLE \(section 2.2.2.1.2\)](#)
- [WCTABLE \(section 2.2.2.1.1\)](#)
- [DBCSRANGE \(section 2.2.2.1.3\)](#) (DBCS codepages only)
- DBCSTABLE (section [2.2.2.1.3](#)) (DBCS codepages only)

2.2.2.1.1 WCTABLE

The WCTABLE tag marks the start of the mapping from Unicode UTF-16 to MultiByte bytes. It has one field.

Field 1: The number of records of Unicode to byte mappings. Note that this field is often more than the number of roundtrip mappings that are supported by the codepage due to Windows best-fit behavior.

An example of the WCTABLE tag is:

```
WCTABLE 698
```

The Unicode UTF-16 mapping records follow the WCTABLE section. These mapping records are in two forms: single-byte or double-byte codepages. Both forms have two fields.

Field 1: The Unicode UTF-16 code point for the character being converted.

Field 2: The single byte that this UTF-16 code point maps to. This can be a best-fit mapping.

The following example shows Unicode to byte-mapping records for SBCSs.

```
0x0000 0x00; Null
0x0001 0x01; Start Of Heading
...
0x0061 0x61; Latin Small Letter A
0x0062 0x62; Latin Small Letter B
0x0063 0x63; Latin Small Letter C
...
0x221e 0x38; Infinity << Best Fit Mapping
...
0xff41 0x61; Fullwidth Latin Small Letter A << Best Fit Mapping
0xff42 0x62; Fullwidth Latin Small Letter B << Best Fit Mapping
0xff43 0x63; Fullwidth Latin Small Letter C << Best Fit Mapping
...
```

Field 1: The Unicode UTF-16 code point for the character being converted.

Field 2: The byte or bytes that this code point maps to as a 16-bit value. The high byte is the lead byte, and the low byte is the trail byte. If the high byte is 0, this is a single-byte code point with the value of the low byte and no lead byte is emitted.

The following example shows Unicode to byte-mapping records for DBCSs.

```
0x0000 0x0000; Null
0x0001 0x0001; Start Of Heading
```

```
...
0x0061 0x0061; a
0x0062 0x0062; b
0x0063 0x0063; c
...
0x221e 0x8187; Infinity
...
0xff41 0x8281; Fullwidth a
0xff42 0x8282; Fullwidth b
0xff43 0x8283; Fullwidth c
...
```

2.2.2.1.2 MBTABLE

The MBTABLE tag marks the start of the mapping from single-byte bytes to Unicode UTF-16. It has one field.

Field 1: The number of records of single-byte to Unicode mappings.

An example of the MBTABLE tag is:

```
MBTABLE 196
```

The Unicode UTF-16 mapping records follow the MBTABLE section. These mapping records have two fields.

Field 1: The single byte character of the codepage.

Field 2: The Unicode UTF-16 code point that the codepage character maps to.

The following example shows mapping records for codepage 932.

```
0x00 0x0000; Null
0x01 0x0001; Start Of Heading
0x02 0x0002; Start Of Text
0x03 0x0003; End Of Text
0x04 0x0004; End Of Transmission
0x05 0x0005; Enquiry
0x06 0x0006; Acknowledge
0x07 0x0007; Bell
0x08 0x0008; Backspace
...
0xa1 0xff61; Halfwidth Ideographic Period
0xa2 0xff62; Halfwidth Opening Corner Bracket
0xa3 0xff63; Halfwidth Closing Corner Bracket
0xa4 0xff64; Halfwidth Ideographic Comma
0xa5 0xff65; Halfwidth Katakana Middle Dot
0xa6 0xff66; Halfwidth Katakana Wo
0xa7 0xff67; Halfwidth Katakana Small A
0xa8 0xff68; Halfwidth Katakana Small I
0xa9 0xff69; Halfwidth Katakana Small U
0xaa 0xff6a; Halfwidth Katakana Small E
0xab 0xff6b; Halfwidth Katakana Small O
0xac 0xff6c; Halfwidth Katakana Small Ya
```

2.2.2.1.3 DBCSRANGE

The DBCSRANGE tag marks the start of the mapping from double-byte bytes to Unicode UTF-16. It has one field.

Field 1: The number of records of lead byte ranges.

An example of the DBCSRANGE tag is:

```
DBCSRANGE 2
```

The Lead Byte Range records follow the DBCSRANGE section. These mapping records have two fields.

Field 1: The start of lead byte range.

Field 2: The end of lead byte range.

The following example shows one of the Lead Byte Range records for codepage 932. In this codepage, it has one range of lead byte, starting from 0x81 (decimal 129) to 0x9f (decimal 159). So there are 31 lead bytes in this example (159 – 129 + 1). Each lead byte will have a corresponding DBCSRANGE.

```
0x81 0x9f; Lead Byte Range
```

A group of DBCSTABLE sections follows the lead-byte range record. Each lead byte will have a corresponding DBCSTABLE section. In each DBCSTABLE section, it has one field.

Field 1: This field is the number of trail byte mappings for the lead byte.

The lead byte of the first DBCSTABLE is the first lead byte of the previous Lead Byte Range record. Each subsequent DBCSTABLE is for the next consecutive lead byte value.

The following example shows the first DBCSTABLE for codepage 932. This is for lead byte 0x81.

```
DBCSTABLE 147; LeadByte = 0x81
```

The DBCSTABLE record describes the mappings available for a particular lead byte. The comment is ignored but descriptive.

Field 1: This field is the trail byte to map from.

Field 2: This field is the Unicode UTF-16 code point that this lead byte/trail byte combination map to.

The following example shows DBCSTABLE records for codepage 932 for lead byte 0x81.

```
0x40 0x3000; Ideographic Space  
0x41 0x3001; Ideographic Comma
```

...

3 Protocol Details

The following sections specify details of the Windows Protocols Unicode Reference, including abstract data models and message processing rules.

3.1 Client Details

3.1.1 Abstract Data Model

This section describes a conceptual model of possible data organization that an implementation maintains to participate in this protocol. The described organization is provided to facilitate the explanation of how the protocol behaves. This document does not mandate that implementations adhere to this model as long as their external behavior is consistent with what is described in this document.

No abstract data model is needed.

3.1.2 Timers

None.

3.1.3 Initialization

None.

3.1.4 Higher-Layer Triggered Events

None.

3.1.5 Message Processing Events and Sequencing Rules

3.1.5.1 Mapping Between UTF-16 Strings and Legacy Codepages

3.1.5.1.1 Mapping Between UTF-16 Strings and Legacy Codepages Using CodePage Data File

This process maps between a Unicode string that is encoded in UTF-16 and a string in a specified codepage by using a codepage data file specified in [2.2.2.1](#).

3.1.5.1.1.1 Pseudocode for Accessing a Record in the Codepage Data File

This section contains the pseudocode that is used to read information from the codepage file. The following example is taken from codepage data file 950.txt.

OPEN SECTION indicates that queries for records in a specific section are made. To open the following section with the WCTABLE label, the following syntax is used. The OPEN SECTION is accessible by using the WideCharMapping name.

```
OPEN SECTION WideCharMapping
    where section name is WCTABLE from bestfit950.txt
```

SELECT RECORD assigns a line from the data file to be referenced by the assigned variable name. For example, the following code selects a record from the WideCharMapping section, and the record is accessible by using the MappingData name.

```
SET UnicodeChar to 0x4e00
SELECT RECORD MappingData from WideCharMapping
    where field 1 matches UnicodeChar
```

The following example selects the line.

```
0x4e00 0xa440
```

Values from selected records are referenced by field number. The following example selects the individual data fields from the selected row.

```
SET MultiByteResult to MappingData.Field2
```

In this example, the value of MultiByteResult is the hexadecimal value 0xa440.

```
CODEPAGE 950                ; Chinese (Taiwan, Hong Kong SAR) - ANSI, OEM
CPINFO 2 0x3f 0x003f       ; DBCS CP, Default Char = Question Mark
...
WCTABLE 20321
0x0000 0x0000;   Null
0x0001 0x0001;   Start Of Heading
0x0002 0x0002;   Start Of Text
0x0003 0x0003;   End Of Text
0x0004 0x0004;   End Of Transmission
0x0005 0x0005;   Enquiry
...
0x4e00 0xa440
0x4e01 0xa442
0x4e03 0xa443
0x4e07 0xc94
```

3.1.5.1.1.2 Pseudocode for Mapping a UTF-16 String to a Codepage String

COMMENT This algorithm maps a Unicode string encoded in UTF-16 to a string in the specified ANSI codepage. The supported ANSI codepages are limited to those that can be set as system codepage.

It requires the following externally specified values:

1) CodePage: An integer value to represent an ANSI codepage value.

If CodePage value is CP_ACP (0), the system default ANSI codepage from the OS should be used.

If CodePage value is CP_OEMCP (1), the system default OEM codepage from the OS should be used.

- 2) `UnicodeString`: A string encoded in UTF-16. Every Unicode code point is an unsigned 16-bit ("WORD") value. A surrogate pair is not supported in this algorithm.
- 3) `UnicodeStringLength`: The string length in 16-bit ("WORD") unit for `UnicodeString`. When `UnicodeStringLength` is 0, the length is decided by counting from the beginning of the string to a NULL character (Unicode value U+0000), including the null character.
- 4) `MultiByteString`: A string encoded in ANSI codepage. Every character can be an 8-bit (byte) unsigned value or two 8-bit unsigned values.
- 5) `MultiByteStringLength`: The length in bytes. This should include the byte for NULL terminator. When `MultiByteStringLength` is 0, the `MultiByteString` value will not be used in this algorithm. Instead, the length of the result string in ANSI codepage will be returned.
- 6) `lpDefaultChar`
Optional. Point to the byte to use if a character cannot be represented in the specified codepage. The application sets this parameter to NULL if the function is to use a system default value. The common default value is 0x3f, which is the ASCII value for the question mark.

PROCEDURE `WideCharToMultiByteFromCodepageDataFile`

```

IF CodePage is CP_ACP THEN
    COMMENT Windows operating system keeps a systemwide value of
        default ANSI system codepage. It is used to provide a default
    COMMENT system codepage to be used by legacy ANSI application.

    SET CodePage to the default ANSI system codepage from the Windows
        operating system.
ELSE IF CodePage is CP_OEMCP THEN
    COMMENT Windows keeps a systemwide value of
        default OEM system codepage. It is used to provide a default
    COMMENT system codepage to be used by legacy console application.

    SET CodePage to the default OEM system codepage from Windows.

ENDIF

IF UnicodeStringLength is 0 THEN
    COMPUTE UnicodeStringLength as the string length in 16-bit units
        of UnicodeString as a NULL-terminated string, including
        NULL terminator.
ENDIF

IF MultiByteStringLength is 0 THEN
    SET IsCountingOnly to True
ELSE
    SET IsCountingOnly to False
ENDIF

SET ResultMultiByteLength to 0

```

```

SET CodePageFileName to the concatenation of strings "Bestfit",
    CodePage as a string, and ".txt"

IF lpDefaultChar is null THEN
    COMMENT No default char is specified by the caller. Read the default
    COMMENT char from CPINFO in the data file

    OPEN SECTION CharacterInfo where section name is CPINFO
    from file with the name of CodePageFileName
    SET lpDefaultChar to CharacterInfo.Field3
ENDIF

OPEN SECTION WideCharMapping where section name is WCTABLE from file
with the name of CodePageFileName

FOR each Unicode codepoint UnicodeChar in UnicodeString
    SELECT MappingData from WideCharMapping
        where field 1 matches UnicodeChar
    IF MappingData is null THEN
        COMMENT There is no mapping for this Unicode character, use
        COMMENT the default character
        IF IsCountingOnly is False THEN
            SET MultiByteString[ResultMultiByteLength]
                to lpDefaultChar
        ENDIF
        INCREMENT ResultMultiByteLength
        CONTINUE FOR loop
    ENDIF

    SET MultiByteResult to MappingData.Field2

    IF MultiByteResult is less than 256 THEN
        COMMENT This is a single byte result
        IF IsCountingOnly is True THEN
            INCREMENT ResultMultiByteLength
        ELSE
            SET MultiByteString[ResultMultiByteLength]
                to MultiByteResult
            INCREMENT ResultMultiByteLength
        ENDIF
    ELSE
        COMMENT This is a double byte result
        IF IsCountingOnly is True THEN
            COMPUTE ResultMultiByteLength as
                ResultMultiByteLength added by 2
        ELSE
            SET MultiByteString[ResultMultiByteLength] to
                MultiByteResult divided by 256
            INCREMENT ResultMultiByteLength
            SET MultiByteString[ResultMultiByteLength] to
                the remainder of MultiByteResult divided by 256
            INCREMENT ResultMultiByteLength
        ENDIF
    ENDIF
END FOR

RETURN ResultMultiByteLength as a 32-bit unsigned integer

```

3.1.5.1.1.3 Pseudocode for Mapping a Codepage String to a UTF-16 String

COMMENT This algorithm maps a Unicode string encoded in the specified codepage to UTF-16.

It requires the following externally specified values:

1) CodePage: An integer value to represent an ANSI codepage value.

If CodePage value is CP_ACP (0), the system default ANSI codepage from the OS should be used.

If CodePage value is CP_OEMCP (1), the system default OEM codepage from the OS should be used

2) MultiByteString: A string encoded in ANSI codepage. Every character can be an 8-bit (byte) unsigned value or two 8-bit unsigned values.

3) MultiByteStringLength: The length in bytes. This should include the byte for terminating null character. When MultiByteStringLength is 0, the length is decided by counting from the beginning of the string to a null character (0x00), including the null character.

4) UnicodeString: A string encoded in UTF-16. Every Unicode code point is an unsigned 16-bit ("WORD") value. Surrogate pair is not supported in this algorithm.

5) UnicodeStringLength: The string length in 16-bit ("WORD") unit for UnicodeString. When UnicodeStringLength is 0, the UnicodeString value will not be used in this algorithm. Instead, the length of the result string in UTF-16 will be returned.

PROCEDURE MultiByteToWideCharFromCodepageDataFile

IF CodePage is CP_ACP THEN

COMMENT Windows keeps a systemwide value of default ANSI system codepage. It is used to provide a default COMMENT system codepage to be used by legacy ANSI application.

SET CodePage to the default ANSI system codepage from Windows.

ELSE IF CodePage is CP_OEMCP THEN

COMMENT Windows keeps a systemwide value of default OEM system codepage. It is used to provide a default COMMENT system codepage to be used by legacy console application.

SET CodePage to the default OEM system codepage from Windows.

ENDIF

IF MultiByteStringLength is 0 THEN

COMPUTE UnicodeStringLength as the string length in 8-bit units of MultiByteString as a null-terminated string, including terminating null character.

ENDIF

```

IF UnicodeStringLength is 0 THEN
    SET IsCountingOnly to True
ELSE
    SET IsCountingOnly to False
ENDIF

SET CodePageFileName to the concatenation of
CodePage as a string, and ".txt"

OPEN SECTION CodePageInfo where section name is CPINFO from file
    with the name of CodePageFileName
COMMENT Read the codepage type.
COMMENT The value for Single Byte Code Page (SBCS) is 1
COMMENT The value for Double Byte Code Page (DBCS) is 2

SET CodePageType to CodePageInfo.Field1
SET DefaultUnicodeChar to CodePageInfo.Field3

OPEN SECTION SingleByteMapping where section name is MBTABLE from file
    with the name of CodePageFileName

SET MultiByteIndex = 0
WHILE MultiByteIndex <= to MultiByteStringLength - 1
    SET MultiByteChar = MultiByteString[MultiByteIndex]
    IF CodePageType is 1 THEN
        COMMENT SBCS codepage
        COMMENT Select a record which contains the mapping data
        SELECT MappingData from SingleByteMapping
            where field 1 matches MultiByteChar
        IF MappingData is null THEN
            COMMENT There is no mapping for this single-byte character, use
            COMMENT the default character
            IF IsCountingOnly is False THEN
                SET MultiByteString[ResultUnicodeLength]
                    to DefaultUnicodeChar
            ENDIF
            INCREMENT ResultMultiByteLength
            INCREMENT MultiByteIndex
            CONTINUE WHILE loop
        ENDIF
        IF IsCountOnly is False THEN
            SET UnicodeString[ResultUnicodeLength]
                to MappingData.Field2
        ENDIF
        INCREMENT ResultUnicodeLength
    ELSE
        COMMENT DBCS codepage
        COMMENT First, try if this is a single-byte mapping
        SELECT MappingData from SingleByteMapping
            where field 1 matches MultiByteChar
        IF MappingData is not null THEN
            COMMENT This byte is a single-byte character
            IF IsCountOnly is False THEN
                SET UnicodeString[ResultUnicodeLength]
                    to MappingData.Field2
            ENDIF
            INCREMENT ResultUnicodeLength
        ELSE
            COMMENT Not a single-byte character

```

```

COMMENT Check if this is a valid lead byte for double byte mapping
OPEN SECTION DBCSRanges
    where section name is DBCSRANGE from file
    with the name of CodePageFileName

COMMENT Read the count of DBCS Range count
SET DBCSRangeCount to DBCSRanges.Field1

SET ValidDBCS to False
COMMENT Enumerate through every DBCSRange record to see if
COMMENT the MultiByteChar is a leading byte

FOR Counter i = 1 to DBCSRangeCount
    COMMENT Select the current record
    SELECT DBCSRangeRecord from DBCSRanges
    SET LeadByteStart to DBCSRangeRecord.Field1
    SET LeadByteEnd to DBCSRangeRecord.Field2
    IF MultiByteChar is larger or equal to LeadByteStart AND
    MultiByteChar is less or equal to LeadByteEnd THEN
        COMMENT This is a valid lead byte
        COMMENT Now check if there is a following valid trailing byte
        SET LeadByteTableCount = MultiByteChar - LeadByteStart

        COMMENT Select the current DBCSTABLE section
        OPEN SECTION DBCSTableSection from DBCSRanges
            where section name is DBCSTABLE
        COMMENT Advance to the right DBCSTABLE section
        FOR LeadByteIndex = 0 to LeadByteTableCount
            ADVANCE SECTION DBCSTableSection
        NEXTFOR
        COMMENT Check if the trailing byte is valid
        IF MultiByteIndex + 1 is less than MultiByteStringLength THEN
            SET TrailByteChar to MultiByteString[MultiByteIndex + 1]
            SELECT MappingData FROM DBCSTABLE
                Where field 1 matches TrailByteChar
            IF MappingData is not null THEN
                COMMENT Valid trailing byte
                SET ValidDBCS to True
                IF IsCountingOnly is FALSE THEN
                    SET UnicodeString[ResultUnicodeLength] to MappingData.Field2
                ENDIF
                INCREMENT ResultUnicodeLength
                COMMENT Increment the MultiByteIndex.
                COMMENT Note that the MultiByteIndex will
                COMMENT be incremented again for the WHILE loop
                INCREMENT MultiByteIndex
                EXIT FOR loop
            ENDIF
        ENDIF
    ENDIF
    COMMENT No valid lead byte is found. Advance to next record
    ADVANCE DBCSRangeRecord
NEXTFOR
IF ValidDBCS is FALSE THEN
    COMMENT There is no valid leading byte/trailing byte sequence
    If IsCountingOnly is FALSE THEN
        SET UnicodeString[ResultUnicodeLength] to DefaultUnicodeChar
    ENDIF
    INCREMENT MultiByteIndex

```

```
        INCREMENT ResultUnicodeLength
    ENDF
ENDIF
    INCREMENT MultiByteIndex
ENDWHILE

RETURN ResultMultiByteLength as a 32-bit unsigned integer
```

3.1.5.1.2 Mapping Between UTF-16 Strings and ISO 2022-Based Codepages

[\[ECMA-035\]](#) defines the standard that is fully identical with International Standard ISO/IEC 2022:1994. EUC (Extended Unix Code) is based on ISO-2022 standard.

For more information, see [\[ECMA-035\]](#).

3.1.5.1.3 Mapping between UTF-16 Strings and GB 18030 Codepage

Windows implements GB-18030 based on [\[GB18030\]](#).

For more information, please see [\[GB18030\]](#).

3.1.5.1.4 Mapping Between UTF-16 Strings and ISCII Codepage

Windows implements ISCII-based codepage based on [\[ISCII\]](#).

For more information, see [\[ISCII\]](#).

3.1.5.1.5 Mapping Between UTF-16 Strings and UTF-7

Windows implements UTF-7 codepage based on [\[RFC2152\]](#).

For more information, see [\[RFC2152\]](#).

3.1.5.1.6 Mapping Between UTF-16 Strings and UTF-8

Windows implements UTF-8 codepage based on [\[UNICODE5.0.0/CH3\]](#).

For more information, see [\[UNICODE5.0.0/CH3\]](#).

3.1.5.2 Comparing UTF-16 Strings by Using Sort Keys

To compare strings, a **sort key** is required for each string. A binary comparison of the sort keys can then be used to arrange the strings in any order.

3.1.5.2.1 Pseudocode for Comparing UTF-16 Strings

This algorithm compares two UTF-16 strings by using linguistically appropriate rules.

```
This algorithm compares two Unicode strings using linguistic
appropriate rules. It requires the following externally specified
values:
```

- 1) StringA: A string encoded in UTF-16

```

2) StringB: A string encoded in UTF-16

CALL GetWindowsSortKey
    WITH StringA
    RETURNING SortKeyA
CALL GetWindowsSortKey
    WITH StringB
    RETURNING SortKeyB

CALL CompareSortKeys
    WITH SortKeyA, SortKeyB
    RETURNING Result

IF Result is "SortKeyA is equal to SortKeyB" THEN
    StringA is considered equal to StringB
ELSE IF Result is "SortKeyA is less than SortKeyB" THEN
    StringA is sorted prior to StringB
ELSE
    StringA is sorted after StringB
ENDIF

```

3.1.5.2.2 CompareSortKey

This algorithm generates sort keys for two strings and uses the sort keys to provide a linguistically appropriate string comparison.

```

COMMENT CompareSortKeys
COMMENT On Entry: SortKeyA - An array of bytes returned from
COMMENT                               GetWindowsSortKey
COMMENT                               SortKeyB - An array of bytes returned from
COMMENT                               GetWindowsSortKey
COMMENT
COMMENT On Exit:  Result - A value indicating if SortKeyA
COMMENT                               is less than, equal to, or greater
COMMENT                               than SortKeyB

PROCEDURE CompareSortKeys

SET index to 0
WHILE index is less than Length(SortKeyA) and
    index is also less than Length(SortKeyB)

    IF SortKeyA[index] is less than SortKeyB[index] THEN
        SET Result to "SortKeyA is less than SortKeyB"
        RETURN
    ENDIF
    IF SortKeyA[index] is greater than SortKeyB[index] THEN
        SET Result to "SortKeyA is greater than SortKeyB"
        RETURN
    ENDIF

INCREMENT index
ENDWHILE

IF Length(SortKeyA) is equal to Length(SortKeyB) THEN
    SET Result to "SortKeyA is equal to SortKeyB"
ELSE IF Length(SortKeyA) is less than Length(SortKeyB) THEN

```

```

    SET Result to "SortKeyA is less than SortKeyB"
ELSE
    assert Length(SortKeyA) must be greater than Length(SortKeyB)
    SET Result to "SortKeyA is greater than SortKeyB"
ENDIF
RETURN

```

Any sorting mechanism can be used to arrange these strings by comparing their sort keys.

3.1.5.2.3 Accessing the Windows Sorting Weight Table

Windows gets its sorting data from a data table (see section [3.1.5.2.3.1](#)). Code points are labeled by using UTF-16 values. The file is arranged in sections of tab-delimited field records. Optional comments begin with a semicolon. Each section contains a label and can have a subsection label. [<2>](#)

```

SORTKEY           - Section label
  DEFAULT 52086   - Subsection label record count

; Comment
0x0001  6  3  2  2; Start Of Heading, U+0001 char record
0x0002  6  4  2  2; Start Of Text
0x0003  6  5  2  2; End Of Text
...
0x00411 4  2  2 18; Latin Capital Letter A, U+0041 char record
0x00421 4  9  2 18; Latin Capital Letter B
0x00431 4 10  2 18; Latin Capital Letter C
...
ENDSORTKEY       - End of section label      |   |   |   |   |
Field 1  2  3  4  5  Comment

```

Note that labels are any field that does not begin with a numerical (0xNNNN) value. Blank lines and characters that follow a ";" are ignored.

This document uses the following notation to specify the processing of the file.

OPEN indicates that queries are made for records in a specific section. To open the preceding section with the SORTKEY label and DEFAULT sublabel, the following syntax is used. The OPEN SECTION is accessible by using the DefaultTable name.

```

OPEN SECTION DefaultTable where name is
  SORTKEY\DEFAULT from unisort.txt

```

SELECT assigns a line from the data file to be referenced by the assigned variable name. To select the highlighted row preceding, this document uses this notation. The selected row is accessible by using the name CharacterRow.

```

SET UnicodeChar to 0x0041
SELECT RECORD CharacterRow FROM DefaultTable
  WHERE field 1 matches UnicodeChar

```


Values from selected records are referenced by field number. The following pseudo code selects the individual data fields from the selected row.

```
SET CharacterWeight.ScriptMember to CharacterRow.Field2
SET CharacterWeight.PrimaryWeight to CharacterRow.Field3
SET CharacterWeight.DiacriticWeight to CharacterRow.Field4
SET CharacterWeight.CaseWeight to CharacterRow.Field5
```

Some sections of the data file are referenced by a locale language code identifier (LCID) or locale name (LOCALENAME).<3> For more information, see [\[MS-LCID\]](#).

For inputs that provide an LCID on versions requiring a LOCALENAME, or inputs providing a LOCALENAME for versions requiring an LCID, mappings between the LCID and LOCALENAME using the tables and rules are specified in [\[MS-LCID\]](#).

```
SORTTABLES
...
    COMPRESSION    19                - 19 Locales have contractions
    LCID 0x0000041a        ; Croatian - Windows 7 uses LCID
    LOCALENAME hr-HR      ; Croatian - Windows 8 uses LOCALENAME    TWO    9
- 9 Records in this subsection
0x0064 0x017e 14 29 4 2 ;d z Hacek
0x0044 0x017e 14 29 4 18;D z Hacek
0x0044 0x017d 14 29 4 26;D Z Hacek
...
    LCID 0x00000405        ; Czech
    LOCALENAME cs-CZ      ; Czech
    TWO    3                - Czech as 3 TWO character contractions
0x0063 0x0068 14 46 2 2 ;ch
0x0043 0x0068 14 46 2 18;Ch
0x0043 0x0048 14 46 2 26;CH
    |      |      |      |      |      |
Field 1  2      3      4      5      6      Comment
```

To select the record for characters 0x0043 and 0x0068 with LCID 0x0405, the following notation is used.<4>

```
SET Character1 to 0x0043
SET Character2 to 0x0068
SET SortLocale to 0x0405

OPEN SECTION ContractionTable where name is
    SORTTABLES\COMPRESSION\LCID[SortLocale]\TWO from unisort.txt
SELECT RECORD ContractionRow FROM ContractionTable WHERE field 1
    matches Character1 and field 2 matches Character2
SET CharacterWeight.ScriptMember to ContractionRow.Field3
SET CharacterWeight.PrimaryWeight to ContractionRow.Field4
SET CharacterWeight.DiacriticWeight to ContractionRow.Field5
SET CharacterWeight.CaseWeight to ContractionRow.Field6
```

To select the record for characters 0x0061 and 0x003a with LOCALENAME moh-CA, the following notation is used.<5>

```
SET Character1 to 0x0061
SET Character2 to 0x003a
SET SortLocale to moh-CA

OPEN SECTION ContractionTable where name is
    SORTTABLES\COMPRESSION\LOCALENAME[SortLocale]\TWO from unisort.txt
SELECT RECORD ContractionRow FROM ContractionTable WHERE field 1
    matches Character1 and field 2 matches Character2
SET CharacterWeight.ScriptMember to ContractionRow.Field3
SET CharacterWeight.PrimaryWeight to ContractionRow.Field4
SET CharacterWeight.DiacriticWeight to ContractionRow.Field5
SET CharacterWeight.CaseWeight to ContractionRow.Field6
```

3.1.5.2.3.1 Windows Sorting Weight Table

This section contains links to detailed character weight specifications that permit consistent sorting and comparison of Unicode strings. The data is not used by itself but is used as one of the inputs to the comparison algorithm. The layout and format of data in this file is also specified there.

- Windows NT 4.0 operating system through Windows Server 2003 operating system [\[MSDN-SWT/W2K3\]](#)
- Windows Vista operating system [\[MSDN-SWT/Vista\]](#)
- Windows Server 2008 operating system [\[MSDN-SWT/W2K8\]](#)
- Windows 7 operating system and Windows Server 2008 R2 operating system [\[MSDN-SWT/Win7\]](#)
- Windows 8 operating system and Windows Server 2012 operating system [\[MSDN-SWT/Win8\]](#)

3.1.5.2.4 GetWindowsSortKey Pseudocode

This algorithm specifies the generation of sort keys for a specific UTF-16 string.

```
STRUCTURE CharacterWeightType
(
    ScriptMember:    8 bit integer
    PrimaryWeight:  8 bit integer
    DiacriticWeight: 8 bit integer
    CaseWeight:     8 bit integer
)

STRUCTURE UnicodeWeightType
(
    ScriptMember:    8 bit integer
    PrimaryWeight:  8 bit integer
    ThirdByteWeight: 8 bit integer
)

STRUCTURE SpecialWeightType
(
    Position:       16 bit integer
    ScriptMember:   8 bit integer
)
```

```

        PrimaryWeight:    8 bit integer
    )

STRUCTURE ExtraWeightType
(
    W6:                8 bit integer
    W7:                8 bit integer
)

SET constant LCID_KOREAN to 0x0412
SET constant LCID_KOREAN_UNICODE_SORT to 0x010412
SET constant LCID_HUNGARIAN to 0x040e

SET constant SORTKEY_SEPARATOR to 0x01
SET constant SORTKEY_TERMINATOR to 0x00

SET global KoreanScriptMap to InitKoreanScriptMap

//
// Script Member Values.
//
SET constant UNSORTABLE        to 0
SET constant NONSPACE_MARK    to 1
SET constant EXPANSION         to 2
SET constant EASTASIA_SPECIAL to 3
SET constant JAMO_SPECIAL     to 4
SET constant EXTENSION_A      to 5
SET constant PUNCTUATION      to 6

SET constant SYMBOL_1         to 7
SET constant SYMBOL_2         to 8
SET constant SYMBOL_3         to 9
SET constant SYMBOL_4         to 10
SET constant SYMBOL_5         to 11
SET constant SYMBOL_6         to 12

SET constant DIGIT            to 13

SET constant LATIN            to 14
SET constant KANA              to 34
SET constant IDEOGRAPH        to 128

IF Windows version is Windows Vista, Windows Server 2008, Windows 7, or
    Windows Server 2008 R2 THEN
SET constant MAX_SPECIAL_CASE to SYMBOL_6

ELSE
SET constant MAX_SPECIAL_CASE to SYMBOL_5
ENDIF
IF Windows version is Windows Server 2008 R2 or Windows 7 or Windows 8 or Windows Server 2012
THEN
    COMMENT Set the constant for the first script member of the Unicode
    COMMENT Private Use Area (PUA) range
    SET constant PUA3BYTESTART to 0xA9
    COMMENT Set the constant for the last script member of the Unicode
    COMMENT Private Use Area (PUA) range
    SET constant PUA3BYTEEND to 0xAF

    COMMENT Set the constant for the first script member of CJK
    COMMENT (Chinese/Japanese/Korean) 3 byte weight range

```

```

SET constant CJK3BYTESTART to 0xC0
COMMENT Set the constant for the last script member of CJK
COMMENT (Chinese/Japanese/Korean) 3 byte weight range
SET constant CJK3BYTEEND to 0xEF
ENDIF

IF Windows version is Windows 8 or Windows Server 2012 THEN
    COMMENT Set the constant for the first code point the Unicode
    COMMENT Ideographic Variant Selector (IVS) range
    SET constant IVS_HIGH_SURROGATE to 0xDB40
    SET constant IVS_LOW_SURROGATE_START to 0xDD00
    SET constant IVS_LOW_SURROGATE_END to 0xDDEF
ENDIF
SET constant FIRST_SCRIPT      to LATIN
SET constant MAX_SCRIPTS      to 256

//
// Values for CJK Unified Ideographs Extension A range.
// 0x3400 thru 0x4dbf
//
SET constant SCRIPT_MEMBER_EXT_A to 254 // SM for Extension A
SET constant PRIMARY_WEIGHT_EXT_A to 255 // AW for Extension A

//
// Lowest weight values.
// Used to remove trailing DW and CW values.
// Also used to keep illegal values out of sort keys.
//

SET constant MIN_DW to 2
SET constant MIN_CW to 2

//
// Bit mask values.
//
// Case Weight (CW) - 8 bits:
// bit 0  => width
// bit 1,2 => small kana, sei-on
// bit 3,4 => upper/lower case
// bit 5  => kana
// bit 6,7 => contraction
//

IF Windows version is Windows Server 2008 R2 or Windows 7 or Windows 8 or Windows Server 2012
THEN
    COMMENT Windows Server 2008 R2 and Windows 7 and
    COMMENT Windows 8 and Windows Server 2012 sorting table
    COMMENT supports up to 8-character
    COMMENT contraction
    COMMENT Set the necessary constants for the support

    SET constant CONTRACTION_8_MASK to 0xc0
    SET constant CONTRACTION_7_MASK to 0xc0
    SET constant CONTRACTION_6_MASK to 0xc0
    SET constant CONTRACTION_5_MASK to 0x80
    SET constant CONTRACTION_4_MASK to 0x80
    SET constant CONTRACTION_3_MASK to 0x40
    SET constant CONTRACTION_2_MASK to 0x40

```

```

SET constant CONTRACTION_MASK to 0xc0

ELSE
COMMENT Otherwise, only 2-character or 3-character contractions are supported.
SET constant CONTRACTION_3_MASK to 0xc0 // Bit-mask to check 2 character contraction or 3
//character contraction
SET constant CONTRACTION_2_MASK to 0x80 // Bit-mask to check 2 character contraction
ENDIF

SET constant CASE_UPPER_MASK to 0xe7 // zero out case bits
SET constant CASE_KANA_MASK to 0xdf // zero out kana bit
SET constant CASE_WIDTH_MASK to 0xfe // zero out width bit

//
// Masks to isolate the various bits in the case weight.
//
// NOTE: Bit 2 must always equal 1 to avoid getting
// a byte value of either 0 or 1.
//

SET constant CASE_EXTRA_WEIGHT_MASK to 0xc4
SET constant ISOLATE_KANA to
(~CASE_KANA_MASK) | CASE_EXTRA_WEIGHT_MASK
SET constant ISOLATE_WIDTH to
(~CASE_WIDTH_MASK) | CASE_EXTRA_WEIGHT_MASK

//
// Values for East Asia special case primary weights.
//
SET constant PW_REPEAT to 0
SET constant PW_CHO_ON to 1
SET constant MAX_SPECIAL_PW to PW_CHO_ON

//
// Values for weight 5 - East Asia Extra Weights.
//
SET constant WT_FIVE_KANA to 3
SET constant WT_FIVE_REPEAT to 4
SET constant WT_FIVE_CHO_ON to 5

//
// PW Mask for Cho-On:
// Leaves bit 7 on in PW, so it becomes Repeat
// if it follows Kana N.
//
SET constant CHO_ON_PW_MASK to 0x87

//
// Special weight values
//
SET constant MAP_INVALID_WEIGHT to 0xff

//
// Some Significant Values for Korean Jamo.
// The L, V & T syllables in the 0x1100 Unicode range
// can be composed to characters in the 0xac00 range.
// See The Unicode Standard for details.
//
SET constant NLS_CHAR_FIRST_JAMO to 0x1100 // Begin Jamo range

```

```

SET constant NLS_CHAR_LAST_JAMO          to 0x11f9 // End Jamo range
SET constant NLS_CHAR_FIRST_VOWEL_JAMO to 0x1160 // First Vowel Jamo
SET constant
NLS_CHAR_FIRST_TRAILING_JAMO to 0x11a8 // First Trailing Jamo
SET constant
NLS_JAMO_VOWEL_COUNT to 21 // Number of vowel Jamo (V)
SET constant
NLS_JAMO_TRAILING_COUNT to 28 // Number of trailing Jamo (L)
SET constant
NLS_HANGUL_FIRST_COMPOSED to 0xac00 // Begin composed range

//
// Values for Unicode Weight extra weights (e.g. Jamo (old Hangul)).
// The following uses SM for extra UW weights.
//
SET constant ScriptMember_Extra_UnicodeWeight to 255
// Leading Weight / Vowel Weight / Trailing Weight
// according to the current Jamo class.
//
STRUCTURE JamoSortInfoType
(
    // true for an old Hangul sequence
    OldHangulFlag : Boolean

    // true if U+1160 (Hangul Jungseong Filler) used
    FillerUsed : Boolean

    // index to the prior modern Hangul syllable (L)
    LeadingIndex : 8 bit integer

    // index to the prior modern Hangul syllable (V)
    VowelIndex : 8 bit integer

    // index to the prior modern Hangul syllable (T)
    TrailingIndex : 8 bit integer

    // Weight to offset from other old hangul (L)
    LeadingWeight : 8 bit integer

    // Weight to offset from other old hangul (V)
    VowelWeight : 8 bit integer

    // Weight to offset from other old hangul (T)
    TrailingWeight : 8 bit integer
)

// This is the raw data record type from the data table
STRUCTURE JamoStateDataType
(
    // true for an old Hangul sequence
    OldHangulFlag : Boolean

    // index to the prior modern Hangul syllable (L)
    LeadingIndex : 8 bit integer

    // index to the prior modern Hangul syllable (V)
    VowelIndex : 8 bit integer

    // index to the prior modern Hangul syllable (T)

```

```

TrailingIndex : 8 bit integer

// weight to distinguish from old Hangul
ExtraWeight : 8 bit integer

// number of additional records in this state
TransitionCount : 8 bit integer

// Current record in unisort.txt Jamo table:
JamoRecord : data record

// SORTTABLES\JAMOSORT\[Character] section
)
COMMENT GetWindowsSortKey
COMMENT
COMMENT On Entry:  SourceString - Unicode String to compute a
COMMENT                               sort key for
COMMENT           SortLocale   - Locale to determine correct
COMMENT                               linguistic sort
COMMENT           Flags        - Bit Flag to control behavior
COMMENT                               of sort key generation.
COMMENT
COMMENT NORM_IGNORENONSPACE   Ignore diacritic weight
COMMENT NORM_IGNORECASE:     Ignore case weight
COMMENT NORM_IGNOREKATYPE:   Ignore Japanese Katakana/Hiraga
COMMENT                               difference
COMMENT NORM_IGNOREWIDTH:    Ignore Chinese/Japanese/Korean
COMMENT                               half-width and full-width difference.
COMMENT
COMMENT On Exit:  SortKey     - Byte array containing the
COMMENT                               computed sort key.
COMMENT

PROCEDURE GetWindowsSortKey(IN SourceString : Unicode String,
                           IN SortLocale : LCID,
                           IN Flags : 32 bit integer,
                           OUT SortKey : BYTE String)

COMMENT Compute flags for sort conditions
COMMENT Based on the case/kana/width flags,
COMMENT turn off bits in case mask when comparing case weight.

SET CaseMask to 0xff

If (NORM_IGNORECASE bit is on in Flags) THEN
    SET CaseMask to CaseMask LOGICAL AND with CASE_UPPER_MASK
ENDIF

If (NORM_IGNOREKATYPE bit is on in Flags) THEN
    SET CaseMask to CaseMask LOGICAL AND with CASE_KANA_MASK
ENDIF

If (NORM_IGNOREWIDTH bit is on in Flags) THEN
    SET CaseMask to CaseMask LOGICAL AND with CASE_WIDTH_MASK
ENDIF

COMMENT Windows 7 and Windows Server 2008 R2 use 3-byte (instead of 2-byte) sequence for
COMMENT Unicode Weights
COMMENT for Private Use Area (PUA) and some Chinese/Japanese/Korean (CJK) script members.

```

```

COMMENT Does this sort have a 3-byte Unicode Weight (CJK sorts)?
IF Windows version is Windows 7 and Windows Server 2008 R2 THEN
    COMMENT Check if the locale can have 3-byte Unicode weight
    SET Is3ByteWeightLocale to CALL Check3ByteWeightLocale(SortLocale)
ENDIF

IF Windows version is Windows Vista, Windows Server 2008, Windows 7, or Windows Server 2008
R2 THEN
    COMMENT For Windows Vista, Windows Server 2008, Windows 7, and Windows Server 2008 R2,
    COMMENT the algorithm
    COMMENT does not remap the script for Korean locale
    SET IsKoreanLocale to false
ELSE

    IF SortLocale is LCID_KOREAN or
    SortLocale is LCID_KOREAN_UNICODE_SORT THEN
        SET IsKoreanLocale to true
        IF KoreanScriptMap is null THEN
            CALL InitKoreanScriptMap
        ELSE
            SET IsKoreanLocale to false
        ENDIF
    ENDIF
ENDIF

//
// Allocate buffer to hold different levels of sort key weights.
// UnicodeWeights/ExtraWeights/SpecialWeights will be eventually
// to be collected together, in that order, into the returned
// Sortkey byte string.
//
// Maximum expansion size is 3 times the input size
//
// Unicode Weight => 4 word (16 bit) length
// (extension A and Jamo need extra words)
SET UnicodeWeights to new empty string of UnicodeWeightType

SET DiacriticWeights to new empty string of BYTE
SET CaseWeights to new empty string of BYTE

// Extra Weight=>4 byte length (4 weights, 1 byte each) FE Special
SET ExtraWeights to new empty string of ExtraWeightType

// Special Weight => dword length (2 words each of 16 bits)
SET SpecialWeights to new empty string of SpecialWeightType

//
// Go through the string, code point by code point,
// testing for contractions and Hungarian special character sequence
//

// loop presumes 0 based index for source string
FOR SourceIndex is 0 to Length(SourceString) -1
    //
    // Get weights
    // CharacterWeight will contain all of the weight information

```



```

// for the character tested.
//

SET CharacterWeight to CALL GetCharacterWeights
    WITH (SortLocale, SourceString[SourceIndex])

SET ScriptMember to CharacterWeight.ScriptMember

// Special case weights have script members less than
// MAX_SPECIAL_CASE (11)
IF ScriptMember is greater than MAX_SPECIAL_CASE THEN

    //
    // No special case on character, but must check for
    // contraction characters and Hungarian special character sequence
    // characters.
    //

    SET HasHungarianSpecialCharacterSequence to CALL
        TestHungarianCharacterSequences
            WITH (SortLocale, SourceString, SourceIndex)

    SET Result to CALL GetContractionType WITH (CharacterWeight)

    CASE Result OF

        "3-character Contraction":
            COMMENT This is only possible for Windows versions that are Windows NT 4.0
            COMMENT through Windows Server 2003
            Set ContractionFound to CALL SortkeyContractionHandler
                WITH (SortLocale, SourceString, SourceIndex,
                    HasHungarianSpecialCharacterSequence, 3,
                    UnicodeWeights, DiacriticWiegths, CaseWeights)
            IF ContractionFound is true THEN
                COMMENT Break out of the case statement
                BREAK
            ENDIF
            IF ContractionFound is true THEN
                COMMENT Break out of the case statement
                BREAK
            ENDIF
            COMMENT If no contraction is found, fall through into the additional cases.
            FALLTHROUGH

        "2-character Contraction":
            COMMENT This is only possible for Windows versions that are Windows NT 4.0
            COMMENT through Windows Server 2003
            Set ContractionFound to CALL SortkeyContractionHandler
                WITH (SortLocale, SourceString, SourceIndex,
                    HasHungarianSpecialCharacterSequence, 2,
                    UnicodeWeights, DiacriticWiegths, CaseWeights)
            IF ContractionFound is true THEN
                COMMENT Break out of the case statement
                BREAK
            ENDIF
            COMMENT If no contraction is found, fall through into the OTHER case.
            COMMENT Since "3-character contraction" or "2-character contraction" are the
            COMMENT only two possible values for
            COMMENT Windows NT 4.0 through Windows Server 2003, all calls to

```

```
COMMENT SortkeyContractionHandler will return false.
COMMENT So, the fallthrough will go directly to the OTHERS section
FALLTHROUGH
```

```
"6-character contraction, 7-character contraction, or 8-character contraction":
```

```
Set ContractionFound to CALL SortkeyContractionHandler
  WITH (SortLocale, SourceString, SourceIndex,
        HasHungarianSpecialCharacterSequence, 8,
        UnicodeWeights, DiacriticWeights, CaseWeights)
IF ContractionFound is true THEN
  COMMENT Break out of the case statement
  BREAK
ELSE
  Set ContractionFound to CALL SortkeyContractionHandler
  WITH (SortLocale, SourceString, SourceIndex,
        HasHungarianSpecialCharacterSequence, 7,
        UnicodeWeights, DiacriticWeights, CaseWeights)
ENDIF
IF ContractionFound is true THEN
  COMMENT Break out of the case statement
  BREAK
ELSE
  Set ContractionFound to CALL SortkeyContractionHandler
  WITH (SortLocale, SourceString, SourceIndex,
        HasHungarianSpecialCharacterSequence, 6,
        UnicodeWeights, DiacriticWeights, CaseWeights)
ENDIF
IF ContractionFound is true THEN
  COMMENT Break out of the case statement
  BREAK
ENDIF
COMMENT If no contraction is found, fall through into additional cases.
FALLTHROUGH
```

```
"4-character contraction or 5-character contraction":
```

```
Set ContractionFound to CALL SortkeyContractionHandler
  WITH (SortLocale, SourceString, SourceIndex,
        HasHungarianSpecialCharacterSequence, 5,
        UnicodeWeights, DiacriticWeights, CaseWeights)
IF ContractionFound is true THEN
  COMMENT Break out of the case statement
  BREAK
ELSE
  Set ContractionFound to CALL SortkeyContractionHandler
  WITH (SortLocale, SourceString, SourceIndex,
        HasHungarianSpecialCharacterSequence, 4,
        UnicodeWeights, DiacriticWeights, CaseWeights)
ENDIF
IF ContractionFound is true THEN
  COMMENT Break out of the case statement
  BREAK
ENDIF
COMMENT If no contraction is found, fall through into additional cases.
FALLTHROUGH
```

```
"2-character contraction or 3-character contraction":
```

```
Set ContractionFound to CALL SortkeyContractionHandler
  WITH (SortLocale, SourceString, SourceIndex,
        HasHungarianSpecialCharacterSequence, 3,
```

```

        UnicodeWeights, DiacriticWeights, CaseWeights)
IF ContractionFound is true THEN
    COMMENT Break out of the case statement
    BREAK
ELSE
    Set ContractionFound to CALL SortkeyContractionHandler
    WITH (SortLocale, SourceString, SourceIndex,
        HasHungarianSpecialCharacterSequence, 2,
        UnicodeWeights, DiacriticWeights, CaseWeights)
ENDIF
IF ContractionFound is true THEN
    COMMENT Break out of the case statement
    BREAK
ENDIF
COMMENT If no contraction is found, fall through into additional cases.
FALLTHROUGH

```

OTHERS :

```

IF Windows version is greater than Windows Server 2008 R2 or Windows 7 THEN
    COMMENT In Windows Server 2008 R2 or Windows 7, Private Use Area (PUA) code
    COMMENT points
    COMMENT and some CJK (Chinese/Japanese/Korean) sorts may need 3 byte
    COMMENT weights
    COMMENT Store normal Unicode weight first. Note that there is no
    COMMENT adjustment of Korean weight anymore.
    SET UnicodeWeight to
        CorrectUnicodeWeight(CharacterWeight, FALSE)
    COMMENT Assume 3-byte Unicode Weight is not used first. The algorithm will
    COMMENT check this later.
    SET UnicodeWeight.ThirdByteWeight to 0

IF (ScriptMember is equal to or greater than PUA3BYTESTART)
    AND
    (ScriptMember is less than or equal to PUA3BYTEEND) THEN
    SET IsScriptMemberPUA3BYTEWeight to true
ELSE
    SET IsScriptMemberPUA3ByteWeight to false
ENDIF

IF (ScriptMember is equal to or greater than CJK3BYTESTART) AND
    (ScriptMember is less than or equal to CJK3BYTEEND) THEN
    SET IsScriptMemberCJK3ByteWeight to true
ELSE
    SET IsScriptMemberCJK3ByteWeight to false
ENDIF
IF (IsScriptMemberPUA3ByteWeight is true) OR
    (Is3ByteWeightLocale AND
    IsScriptMemberCJK3ByteWeight is true) THEN
    COMMENT PUA code points and some CJK sorts need 3 byte weights
    SET UnicodeWeight.ThirdByteWeight to CharacterWeight.DiacriticWeight
ELSE

    COMMENT Normal Diacritic Weight
    APPEND CharacterWeight.DiacriticWeight to DiacriticWeights as a BYTE
ENDIF
APPEND UnicodeWeight to UnicodeWeights

```

```

        SET CaseWeight to GetCaseWeight(CharacterWeight)
        APPEND CharacterWeight.CaseWeight to CaseWeights as a BYTE

    ELSE

        SET UnicodeWeight to
            CorrectUnicodeWeight(CharacterWeight, IsKoreanLocale)
        APPEND UnicodeWeight to UnicodeWeights
        APPEND CharacterWeight.DiacriticWeight to DiacriticWeights
            as a BYTE
        SET CaseWeight to GetCaseWeight(CharacterWeight)
        APPEND CharacterWeight.CaseWeight to CaseWeights as a BYTE
    ENDIF
ENDCASE
ELSE
    CALL SpecialCaseHandler WITH (SourceString, SourceIndex,
        UnicodeWeights, ExtraWeights, SpecialWeights,
        SortLocale, IsKoreanLocale)
ENDIF
ENDFOR

//
// Store the Unicode Weights in the destination buffer.
//
FOR each UnicodeWeight in UnicodeWeights
    //
    // Copy Unicode weight to destination buffer.
    //
    APPEND UnicodeWeight.ScriptMember to SortKey as a BYTE
    APPEND UnicodeWeight.PrimaryWeight to SortKey as a BYTE
    IF Windows version is greater than Windows Server 2008 R2 or Windows 7 THEN
        IF UnicodeWeight.ThirdByteWeight is not 0 THEN
            COMMENT When 3-byte Unicode Weight is used, append the additional BYTE into
            COMMENT SortKey
            APPEND UnicodeWeight.ThirdByteWeight to SortKey as a BYTE
        ENDIF
    ENDIF
ENDIF

ENDFOR

//
// Copy Separator to destination buffer.
//
APPEND SORTKEY_SEPARATOR to SortKey as a BYTE

//
// Store Diacritic Weights in the destination buffer.
//
IF (NORM_IGNORENONSPACE bit is not turned on in Flags) THEN
    IF (IsReverseDW is TRUE) THEN
        //
        // Reverse diacritics:
        // - remove diacritics from left to right.
        // - store diacritics from right to left.
        //
        FOR each DiacriticWeight in
            DiacriticWeights in the "first in first out" order
            IF DiacriticWeight <= MIN_DW THEN
                REMOVE DiacriticWeight from DiacriticWeights
            ENDIF
        ENDFOR
    ENDIF
ENDIF

```

```

        ELSE
            BREAK from the current FOR loop
        ENDIF
    ENDFOR

    FOR each DiacriticWeight in
        DiacriticWeights in the "last in first out" order
        //
        // Copy Unicode weight to destination buffer.
        //
        APPEND DiacriticWeight to SortKey as a BYTE
    ENDFOR
ELSE
    //
    // Regular diacritics:
    // - remove diacritics from right to left.
    // - store diacritics from left to right.
    FOR each DiacriticWeight in
        DiacriticWeights in the "last in first out" order
        IF DiacriticWeight <= MIN_DW THEN
            REMOVE DiacriticWeight from DiacriticWeights
        ELSE
            BREAK from the current FOR loop
        ENDIF
    ENDFOR

    FOR each DiacriticWeight in
        DiacriticWeights in the order of "first in first out"
        //
        // Copy Unicode weight to destination buffer.
        //
        APPEND DiacriticWeight to SortKey as a BYTE
    ENDFOR
ENDIF
ENDIF

//
// Copy Separator to destination buffer.
//
APPEND SORTKEY_SEPARATOR to SortKey as a BYTE

//
// Store case Weights
//
// - Eliminate minimum CW.
// - Copy case weights to destination buffer.
//
IF (NORM_IGNORECASE bit is not turned on in Flags
    OR NORM_IGNOREWIDTH bit is not turned on in Flags) THEN
    FOR each CaseWeight in CaseWeights
        in the "last in first out" order
        IF CaseWeight <= MIN_CW THEN
            REMOVE CaseWeight from CaseWeights
        ELSE
            BREAK from the current FOR loop
        ENDIF
    ENDFOR

    FOR each CaseWeight in CaseWeights

```

```

        //
        // Copy Unicode weight to destination buffer.
        //
        APPEND CaseWeight to SortKey as a BYTE
    ENDFOR
ENDIF

//
// Copy Separator to destination buffer.
//
APPEND SORTKEY_SEPARATOR to SortKey as a BYTE

//
// Store the Extra Weights in the destination buffer for
// EAST ASIA Special.
//
// - Eliminate unnecessary XW.
// - Copy extra weights to destination buffer.
//
IF Length(ExtraWeights) is greater than 0 THEN
    IF (NORM_IGNORENONSPACE bit is turned on in Flag) THEN
        APPEND 0xff to SortKey as a BYTE
        APPEND 0x02 to SortKey as a BYTE
    ENDIF

    // Append W6 group to SortKey
    // Trim unused values from the end of the string
    SET EndExtraWeight to Length(ExtraWeights) - 1

    WHILE EndExtraWeight greater than 0 and
        ExtraWeightSeparator[EndExtraWeight].W6 == 0xe4
        DECREMENT EndExtraWeight
    ENDWHILE

    SET ExtraWeightIndex to 0
    WHILE ExtraWeightIndex is less than or equal to EndExtraWeight
        APPEND ExtraWeightSeparator[ExtraWeightIndex].W6
        to SortKey as a BYTE
        INCREMENT ExtraWeightIndex
    ENDWHILE

    // Append W6 separator
    APPEND 0xff to SortKey as a BYTE

    // Append W7 group to SortKey
    // Trim unused values from the end of the string
    SET EndExtraWeight to Length(ExtraWeights) - 1
    WHILE EndExtraWeight greater than 0 and
        ExtraWeightSeparator[EndExtraWeight].W7 == 0xe4
        DECREMENT EndExtraWeight
    ENDWHILE

    SET ExtraWeightIndex to 0
    WHILE ExtraWeightIndex is less than or equal to EndExtraWeight
        APPEND ExtraWeightSeparator[ExtraWeightIndex].W7 to SortKey
        INCREMENT ExtraWeightIndex
    ENDWHILE

    // Append W7 separator

```

```

        APPEND 0xff to SortKey as a BYTE
    ENDIF

    //
    // Copy Separator to destination buffer.
    //
    APPEND SORTKEY_SEPARATOR to SortKey as a BYTE

    //
    // Store the Special Weights in the destination buffer.
    //
    // - Copy special weights to destination buffer.
    //
    FOR each SpecialWeight in SpecialWeights
        // High byte (most significant)
        SET Byte1 to SpecialWeight.Position >> 8
        // Low byte (least significant)
        SET Byte2 to SpecialWeight.Position & 0xff
        APPEND Byte1 to SortKey as a BYTE
        APPEND Byte2 to SortKey as a BYTE
        APPEND SpecialWeight.Script to SortKey as a BYTE
        APPEND SpecialWeight.Weight to SortKey as a BYTE
    ENDFOR

    //
    // Copy terminator to destination buffer.
    //
    APPEND SORTKEY_TERMINATOR to SortKey

    RETURN SortKey

```

3.1.5.2.5 TestHungarianCharacterSequences

This algorithm checks if the specified UTF-16 string has a Hungarian special-character sequence for the specified locale in the specific string index.

Hungarian contains special character sequences in which the first character of the string designates a string that is equivalent to the last three characters of the string. For example, the string "ddzs" is actually treated as the string "dzsdzs" for the purposes of generating the sort key. This function checks to see if the specified locale is Hungarian, and it also checks to see if the next two characters starting in the specified index are the same. If so, this indicates that it is a likely Hungarian special-character sequence.

```

COMMENT TestHungarianCharacterSequences
COMMENT
COMMENT On Entry:  SortLocale  - Locale to use for linguistic data
COMMENT             SourceString - Unicode String to look for Hungarian
COMMENT                                 special character sequence in
COMMENT             SourceIndex - Index of character in string to
COMMENT                                 look for start of
COMMENT                                 Hungarian special character sequence
COMMENT
COMMENT On Exit:   Result      - Set to true if a Hungarian special
COMMENT                                 character sequence
COMMENT                                 was found
COMMENT

```

```

PROCEDURE TestHungarianCharacterSequences(IN SortLocale : LCID,
                                           IN SourceString : Unicode String,
                                           IN SourceIndex : 32 bit integer,
                                           OUT Result : Boolean)

// Hungarian special character sequence only happen to Hungarian
// Note that this can be found in unisort.txt in the
// SORTTABLES\DOUBLECOMPRESSION section, however since
// there's only 1 locale just hard code it here.
IF SortLocale not equal to LCID_HUNGARIAN) THEN
    SET Result to false
    RETURN
ENDIF

// first test to make sure more data is available
IF SourceIndex + 1 is greater than or equal to
    Length(SourceString) THEN
    SET Result to false
    RETURN
ENDIF

// CMP_MASKOFF_CW (e7) is not necessary
// since it was already masked off
SET FirstWeight to CALL GetCharacterWeights WITH
    (SortLocale, SourceString[SourceIndex])
SET SecondWeight to CALL GetCharacterWeights WITH
    (SortLocale, SourceString[SourceIndex + 1])

IF FirstWeight is equal to SecondWeight THEN
    SET Result to true
ELSE
    SET Result to false
ENDIF

RETURN

```

3.1.5.2.6 GetContractionType

This algorithm specifies the checking of the type of contraction based on the character weight. Contraction is defined by [\[UNICODE-COLLATION\]](#) section 3.2.

For instance, "ll" acts as a single unit in Spanish so that it comes between l and m. This is a two-character contraction. Similarly, "dzs" acts as a single unit in Hungarian, so it is a three-character contraction.

These functions specify if the weights will not be at the beginning of a contraction, the beginning of a two-character contraction, or the beginning of a three-character contraction.

```

COMMENT GetContractionType
COMMENT
COMMENT On Entry:  CharacterWeight - Weights structure to test for
COMMENT                                     a contraction
COMMENT
COMMENT On Exit:   Result           - Type of contraction found:
COMMENT                                     "No contraction"
COMMENT                                     "3-character contraction"
COMMENT                                     "2-character contraction"

```



```

COMMENT          The following results are only possible for
COMMENT          Windows Vista, Windows Server 2008, Windows 7, and
COMMENT          Windows Server 2008 R2
COMMENT          "6-character contraction, 7-character contraction or
COMMENT          8-character contraction"
COMMENT          "4-character contraction or 5-character contraction"
COMMENT          "2-character contraction or 3-character contraction"

```

```

PROCEDURE GetContractionType(IN CharacterWeight : CharacterWeightType,
                             OUT Result)
  IF Windows version is Windows NT 4.0 to Windows 2003 THEN
    CASE CharacterWeight.CaseWeight & CONTRACTION_3_MASK OF
      CONTRACTION_3_MASK : SET Result = "3-character contraction"
      CONTRACTION_2_MASK : SET Result = "2-character contraction"
      OTHERS : SET Result = "No contraction"
    ENDCASE
  ELSE
    COMMENT Windows Vista, Windows Server 2008, Windows 7, and Windows Server 2008 R2
    CASE CharacterWeight.CaseWeight & CONTRACTION_MASK OF
      CONTRACTION_6_MASK : SET Result = "6-character contraction, 7-
      character contraction or 8-character contraction"
      CONTRACTION_4_MASK : SET Result = "4-character contraction or 5-
      character contraction"
      CONTRACTION_2_MASK : SET Result = "2-character contraction or 3-
      character contraction"
      OTHERS : SET Result = "No contraction"
    ENDCASE
  ENDIF
RETURN

```

3.1.5.2.7 CorrectUnicodeWeight

This algorithm specifies the processing of the corrected Unicode weight for the specific character weight, and whether the locale is a Korean locale.

```

COMMENT CorrectUnicodeWeight
COMMENT
COMMENT On Entry:  CharacterWeight - Weights structure to get Unicode
COMMENT          weight of
COMMENT          IsKoreanLocale   - True if this locale needs
COMMENT          adjustment for
COMMENT          Korean mapped scripts behavior.
COMMENT
COMMENT On Exit:  UnicodeWeight   - Corrected Unicode Weight
COMMENT
PROCEDURE
  CorrectUnicodeWeight(IN CharacterWeight : CharacterWeightType,
                      IN IsKoreanLocale : boolean,
                      OUT UnicodeWeight : UnicodeWeightType)
SET UnicodeWeight to CALL MakeUnicodeWeight WITH
  (CharacterWeight.ScriptMember, CharacterWeight.PrimaryWeight,
   IsKoreanLocale)

```

```
RETURN UnicodeWeight
```

3.1.5.2.8 MakeUnicodeWeight

This algorithm specifies the generation of the Unicode weight based on the script member, the primary weight, and whether the locale is a Korean locale.

```
COMMENT MakeUnicodeWeight
COMMENT
COMMENT On Entry:  ScriptMember    - Script member to use for
COMMENT                                     Unicode weight
COMMENT                PrimaryWeight - Primary weight to use for
COMMENT                                     Unicode weight
COMMENT                IsKoreanLocale - True if this locale needs
COMMENT                                     adjustment for Korean mapped
COMMENT                                     scripts behavior.
COMMENT
COMMENT On Exit:   UnicodeWeight    - Corrected Unicode Weight
COMMENT

PROCEDURE MakeUnicodeWeight(IN ScriptMember : 8 bit byte,
                           IN PrimaryWeight : 8 bit byte,
                           IN IsKoreanLocale : boolean,
                           OUT UnicodeWeight : UnicodeWeightType)

IF IsKoreanLocale is true THEN
    SET UnicodeWeight.ScriptMember to
        KoreanScriptMap[ScriptMember]
ELSE
    SET UnicodeWeight.ScriptMember to ScriptMember
ENDIF

SET UnicodeWeight.PrimaryWeight to PrimaryWeight
RETURN UnicodeWeight
```

3.1.5.2.9 GetCharacterWeights

This algorithm specifies the retrieval of the character weight based on the specified locale and the specified UTF-16 code point.

```
COMMENT GetCharacterWeights
COMMENT
COMMENT On Entry:  SortLocale      - Locale to use for linguistic
COMMENT                                     data
COMMENT                SourceCharacter - Unicode Character to return
COMMENT                                     weight for
COMMENT
COMMENT On Exit:   Result          - A structure containing the
COMMENT                                     weights for this character
COMMENT

PROCEDURE GetCharacterWeights(IN SortLocale : LCID,
                             IN SourceCharacter : Unicode Character,
                             OUT Result : CharacterWeightType)
```

```

// Search for the character in the exception table
OPEN SECTION ExceptionTable where name is
    SORTTABLES\EXCEPTION\LCID[SortLocale] from unisort.txt
SELECT RECORD CharacterRow FROM ExceptionTable WHERE field 1
    matches SourceCharacter

IF CharacterRow is null THEN
    // Not found, search for the character in the default table
    OPEN SECTION DefaultTable where name is
        SORTKEY\DEFAULT from unisort.txt
    SELECT RECORD CharacterRow from DefaultTable where field 1
        matches SourceCharacter

    IF CharacterRow is null THEN
        // Not found in default table either, check expansions
        SET Expansion to GetExpandedCharacters(SourceCharacter)

        IF Expansion is not null THEN
            // Has an expansion, set appropriate weights
            SET Result.ScriptMember to EXPANSION
        ELSE
            // No expansion, set appropriate weights
            SET Result.ScriptMember to UNSORTABLE
        ENDIF

        SET Result.PrimaryWeight to 0
        SET Result.DiacriticWeight to 0
        SET Result.CaseWeight to 0

        RETURN Result
    ENDIF
ENDIF

SET Result.ScriptMember to CharacterRow.Field2
SET Result.PrimaryWeight to CharacterRow.Field3
SET Result.DiacriticWeight to CharacterRow.Field4
SET Result.CaseWeight to CharacterRow.Field5

RETURN Result

```

3.1.5.2.10 GetExpansionWeights

This algorithm specifies the generation of a character weight for the specified character that has the expansion behavior, as defined in [\[UNICODE-COLLATION\]](#) section 3.2.

```

COMMENT GetExpansionWeights
COMMENT
COMMENT On Entry:  SourceCharacter - Character to look up
                    expansions for
COMMENT              SortLocale   - Locale to get sort weights for
COMMENT
COMMENT On Exit:   Weights        - String of 2 or 3 weights for
                    this character
COMMENT

PROCEDURE GetExpansionWeights(IN SourceCharacter : Unicode Character,
                              IN SortLocale : LCID,

```

```

        OUT Weights : CharacterWeightType String)

SET Weights to new empty string of CharacterWeightType
SET ExpandedCharacters to CALL GetExpandedCharacters WITH
    (SourceCharacter)

// Append first weight
SET Weight to CALL GetCharacterWeights WITH
    (SortLocale, ExpandedCharacters[0])
APPEND Weight to Weights

// Get second weight, it may expand again
SET Weight to CALL GetCharacterWeights WITH
    (SortLocale, ExpandedCharacters[1])

IF Weight.ScriptMember is EXPANSION THEN
    // second weight expands again, get new expansion
    // note that this can only happen once, as it does
    // with the U=fb03 (ffi ligature)

    SET ExpandedCharacters to CALL
        GetExpandedCharacters (ExpandedCharacters[1])

    // Append second expansion's first weight
    SET Weight to CALL GetCharacterWeights WITH
        (SortLocale, ExpandedCharacters[0])
    APPEND Weight to Weights

    // Get second weight for second expansion, it will not expand again
    SET Weight to CALL GetCharacterWeights WITH
        (SortLocale, ExpandedCharacters[1])
ENDIF

// Finish appending second weight to weights string
APPEND Weight to Weights

RETURN Result

```

3.1.5.2.11 GetExpandedCharacters

This algorithm specifies the generation of the array of expanded characters, if the specified character can be expanded.

```

COMMENT GetExpandedCharacters
COMMENT
COMMENT On Entry:  SourceCharacter - Character to look for in
COMMENT                                     expansion table
COMMENT
COMMENT On Exit:   Result           - Array of two unicode characters
COMMENT                                     for the expansion or null if no
COMMENT                                     expansion found
COMMENT
COMMENT NOTE: Look for default table characters first, some entries
COMMENT       in the expansion table are only used in exception tables
COMMENT       for some locales (ie: 0x00c4 Å)

PROCEDURE

```

```

    GetExpandedCharacters(IN SourceCharacter : Unicode Character,
                        OUT Result : Unicode Character[2])

// Search for the expansion in the expansion table
OPEN SECTION ExpansionTable where name is
    SORTTABLES\EXPANSION from unisort.txt

SELECT RECORD ExpansionRow FROM ExceptionTable WHERE field 1
    matches SourceCharacter

IF ExpansionRow is null THEN
    SET Result to null
    RETURN Result
ENDIF

SET Result[0] to ExpansionRow.Field2
SET Result[1] to ExpansionRow.Field3

RETURN Result

```

3.1.5.2.12 SortkeyContractionHandler

This algorithm checks if the next few characters in the specified string and index have an 8-character, 7-character, 6-character, 5-character, 4-character, 3-character, or 2-character contraction sequence. If true, these characters are given just one character weight. This algorithm also handles the Hangiran special character sequence.

```

COMMENT SortkeyContractionHandler
COMMENT
COMMENT On Entry: SourceString - Source Unicode String
COMMENT SourceIndex - Current index within source string
COMMENT HasHungarianSpecialCharacterSequence: Is the character that the current
COMMENT index points to
COMMENT the starting of the Hungarian special character sequence
COMMENT ContractionType: The contraction type, from 2-character to 8-character
COMMENT contraction, to be checked against
COMMENT UnicodeWeights - String of UnicodeWeightType to
COMMENT append additional weight(s) to
COMMENT DiacriticWeights - String of Diacritic Weight to
COMMENT append extra weight(s) to if
COMMENT needed
COMMENT CaseWeights - String of Case Weight to
COMMENT append special weight(s) to
COMMENT if needed
COMMENT
COMMENT On Exit: Result: a string to indicate the type of contraction from the specified
COMMENT string
COMMENT UnicodeWeights - The UnicodeWeight of the
COMMENT processed character(s) is
COMMENT appended to this string.
COMMENT DiacriticWeights - The Diacritic weight, if any, of
COMMENT the processed character(s) is
COMMENT appended to this string.
COMMENT CaseWeights - The Case Weight, if any,
COMMENT of the processed character(s)
COMMENT is appended to this string.
COMMENT

```

```

PROCEDURE SortkeyContractionHandler (IN SortLocale: LCID,
    IN SourceString: Unicode String,
    IN SourceIndex: 32-bit integer,
    IN HasHungarianSpecialCharacterSequence: boolean
    IN ContractionType: integer number from 2 to 8
    INOUT UnicodeWeights: string of UnicodeWeightType
    INOUT DiacriticWeights: string of BYTE
    INOUT CaseWeights: string of BYTE)

Result: CharacterWeightType

IF HasHungarianSpecialCharacterSequence is true THEN
    COMMENT The beginning of Hungarian special character sequence,
    COMMENT advance one character before starting to check for contraction sequence
    SET SourceIndex to SourceIndex + 1
ENDIF

IF SourceIndex + ContractionType is greater than or equal to SourceString.Length THEN
    SET Result to null
    RETURN false
ENDIF

COMMENT Search for the character in the character contraction table
COMMENT Search for contraction section based on ContractionType

CASE ContractionType
    "8":
    OPEN SECTION ContractionTable where name is
        SORTTABLES\COMPRESSION\LCID[SortLocale]\EIGHT from unisort.txt
    "7":
    OPEN SECTION ContractionTable where name is
        SORTTABLES\COMPRESSION\LCID[SortLocale]\SEVEN from unisort.txt
    "6":
    OPEN SECTION ContractionTable where name is
        SORTTABLES\COMPRESSION\LCID[SortLocale]\SIX from unisort.txt
    "5":
    OPEN SECTION ContractionTable where name is
        SORTTABLES\COMPRESSION\LCID[SortLocale]\FIVE from unisort.txt
    "4":
    OPEN SECTION ContractionTable where name is
        SORTTABLES\COMPRESSION\LCID[SortLocale]\FOUR from unisort.txt
    "3":
    OPEN SECTION ContractionTable where name is
        SORTTABLES\COMPRESSION\LCID[SortLocale]\THREE from unisort.txt
    "2":
    OPEN SECTION ContractionTable where name is
        SORTTABLES\COMPRESSION\LCID[SortLocale]\TWO from unisort.txt
ENDCASE

COMMENT Contraction table may not be found if locale doesn't have them
IF ContractionTable is null THEN
    SET Result to null
    RETURN false
ENDIF

CASE ContractionType
    "8":

```

```

SELECT RECORD ContractionRow FROM ContractionTable
    WHERE field 1 matches SourceString[SourceIndex] and
    WHERE field 2 matches SourceString[SourceIndex + 1] and
    WHERE field 3 matches SourceString[SourceIndex + 2] and
    WHERE field 4 matches SourceString[SourceIndex + 3] and
    WHERE field 5 matches SourceString[SourceIndex + 4] and
    WHERE field 6 matches SourceString[SourceIndex + 5] and
    WHERE field 7 matches SourceString[SourceIndex + 6] and
    WHERE field 8 matches SourceString[SourceIndex + 7]

COMMENT If this sequence isn't a contraction then one will not be found
IF ContractionRow is null THEN
    SET Result to null
RETURN false
ENDIF

COMMENT Found a contraction, get its weights
SET Result.ScriptMember to ContractionRow.Field9
SET Result.PrimaryWeight to ContractionRow.Field10

SET Result.DiacriticWeight to ContractionRow.Field11
SET Result.CaseWeight to ContractionRow.Field12
"7":
SELECT RECORD ContractionRow FROM ContractionTable
    WHERE field 1 matches SourceString[SourceIndex] and
    WHERE field 2 matches SourceString[SourceIndex + 1] and
    WHERE field 3 matches SourceString[SourceIndex + 2] and
    WHERE field 4 matches SourceString[SourceIndex + 3] and
    WHERE field 5 matches SourceString[SourceIndex + 4] and
    WHERE field 6 matches SourceString[SourceIndex + 5] and
    WHERE field 7 matches SourceString[SourceIndex + 6]

COMMENT If this sequence isn't a contraction then one will not be found
IF ContractionRow is null THEN
    SET Result to null
    RETURN false
ENDIF

COMMENT Found a contraction, get its weights
SET Result.ScriptMember to ContractionRow.Field8
SET Result.PrimaryWeight to ContractionRow.Field9

SET Result.DiacriticWeight to ContractionRow.Field10
SET Result.CaseWeight to ContractionRow.Field11
"6":
SELECT RECORD ContractionRow FROM ContractionTable
    WHERE field 1 matches SourceString[SourceIndex] and
    WHERE field 2 matches SourceString[SourceIndex + 1] and
    WHERE field 3 matches SourceString[SourceIndex + 2] and
    WHERE field 4 matches SourceString[SourceIndex + 3] and
    WHERE field 5 matches SourceString[SourceIndex + 4] and
    WHERE field 6 matches SourceString[SourceIndex + 5]

COMMENT If this sequence isn't a contraction then one will not be found
IF ContractionRow is null THEN
    SET Result to null
    RETURN false
ENDIF

```

```

COMMENT Found a contraction, get its weights
SET Result.ScriptMember to ContractionRow.Field7
SET Result.PrimaryWeight to ContractionRow.Field8

SET Result.DiacriticWeight to ContractionRow.Field9
SET Result.CaseWeight to ContractionRow.Field10

"5":
SELECT RECORD ContractionRow FROM ContractionTable
    WHERE field 1 matches SourceString[SourceIndex] and
    WHERE field 2 matches SourceString[SourceIndex + 1] and
    WHERE field 3 matches SourceString[SourceIndex + 2] and
    WHERE field 4 matches SourceString[SourceIndex + 3] and
    WHERE field 5 matches SourceString[SourceIndex + 4]

COMMENT If this sequence isn't a contraction then one will not be found
IF ContractionRow is null THEN
    SET Result to null
    RETURN false
ENDIF

COMMENT Found a contraction, get its weights
SET Result.ScriptMember to ContractionRow.Field6
SET Result.PrimaryWeight to ContractionRow.Field7

SET Result.DiacriticWeight to ContractionRow.Field8
SET Result.CaseWeight to ContractionRow.Field9

"4":
SELECT RECORD ContractionRow FROM ContractionTable
    WHERE field 1 matches SourceString[SourceIndex] and
    WHERE field 2 matches SourceString[SourceIndex + 1] and
    WHERE field 3 matches SourceString[SourceIndex + 2] and
    WHERE field 4 matches SourceString[SourceIndex + 3]

COMMENT If this sequence isn't a contraction then one will not be found
IF ContractionRow is null THEN
    SET Result to null
    RETURN false
ENDIF

COMMENT Found a contraction, get its weights
SET Result.ScriptMember to ContractionRow.Field5
SET Result.PrimaryWeight to ContractionRow.Field6

SET Result.DiacriticWeight to ContractionRow.Field7
SET Result.CaseWeight to ContractionRow.Field8

"3":
SELECT RECORD ContractionRow FROM ContractionTable
    WHERE field 1 matches SourceString[SourceIndex] and
    WHERE field 2 matches SourceString[SourceIndex + 1] and
    WHERE field 3 matches SourceString[SourceIndex + 2]

COMMENT If this sequence isn't a contraction then one will not be found
IF ContractionRow is null THEN
    SET Result to null
    RETURN false

```



```

ENDIF

COMMENT Found a contraction, get its weights
SET Result.ScriptMember to ContractionRow.Field4
SET Result.PrimaryWeight to ContractionRow.Field5

SET Result.DiacriticWeight to ContractionRow.Field6
SET Result.CaseWeight to ContractionRow.Field7

"2":
SELECT RECORD ContractionRow FROM ContractionTable
    WHERE field 1 matches SourceString[SourceIndex] and
    WHERE field 2 matches SourceString[SourceIndex + 1]

COMMENT If this sequence isn't a contraction then one will not be found
IF ContractionRow is null THEN
    SET Result to null
    RETURN false
ENDIF

COMMENT Found a contraction, get its weights
SET Result.ScriptMember to ContractionRow.Field3
SET Result.PrimaryWeight to ContractionRow.Field4

SET Result.DiacriticWeight to ContractionRow.Field5
SET Result.CaseWeight to ContractionRow.Field6

ENDCASE

SET UnicodeWeight to
    CorrectUnicodeWeight(Result, IsKoreanLocale)
APPEND UnicodeWeight to UnicodeWeights
APPEND Result.DiacriticWeight to DiacriticWeights as a BYTE
APPEND Result.CaseWeight to CaseWeights as a BYTE

COMMENT Advance the source index
SET SourceIndex to SourceIndex + ContractionType

RETURN true

```

3.1.5.2.13 Check3ByteWeightLocale

This algorithm checks if the specified locale is a CJK (Chinese/Japanese/Korean) sorting locale that uses third byte in Unicode weight.

```

COMMENT Check3ByteWeightLocale
COMMENT
COMMENT On Entry: SortLocale - Locale to use for linguistic sorting data
COMMENT
COMMENT On Exit: Result: Set to true if the specified locale is a CJK
COMMENT         (Chinese/Japanese/Korean) locale that uses third byte in Unicode weight
COMMENT

SET Result to false

```

```

CASE SortLocale
    "0x0404": // Taiwan (Stroke Count)
    "0x0804": // China (Pronunciation)
    "0x0c04": // Hong Kong (Stroke Count)
    "0x1004": // Singapore (pronunciation)
    "0x1404": // Macau (pronunciation)
    "0x20804": // China (Stroke Count)
    "0x21004": // Singapore (Stroke Count)
    "0x21404": // Macau (Stroke Count)
    "0x30404": // Taiwan (Bopomofo)
    "0x40411": // Japanese (Radical / Stroke)
        SET Result to true
ENDCASE

RETURN Result

```

3.1.5.2.14 SpecialCaseHandler

This algorithm specifies the special processing that is required based on a different script member type.

```

COMMENT SpecialCaseHandler
COMMENT
COMMENT On Entry:  SourceString    - Source Unicode String
COMMENT              SourceIndex    - Current Index within source
COMMENT                               string
COMMENT              UnicodeWeights - String of UnicodeWeightType to
COMMENT                               append additional weight(s) to
COMMENT              ExtraWeights   - String of ExtraWeightType to
COMMENT                               append extra weight(s) to if
COMMENT                               needed
COMMENT              SpecialWeights - String of SpecialWeightType to
COMMENT                               append special weight(s) to
COMMENT                               if needed
COMMENT              SortLocale     - Locale to use for linguistic
COMMENT                               sorting data
COMMENT              IsKoreanLocale - True if this locale needs
COMMENT                               Korean special casing of the
COMMENT                               ScriptMember value
COMMENT On Exit:   SourceIndex    - Index of last character
COMMENT                               processed, caller will need to
COMMENT                               loop increment to continue
COMMENT                               Korean Jamo cases can increment
COMMENT                               this beyond its input value
COMMENT              UnicodeWeights - The UnicodeWeight of the
COMMENT                               processed character(s) is
COMMENT                               appended to this string.
COMMENT              ExtraWeights   - The ExtraWeight, if any, of
COMMENT                               the processed character(s) is
COMMENT                               appended to this string.
COMMENT              SpecialWeights - The Special Weight, if any,
COMMENT                               of the processed character(s)
COMMENT                               is appended to this string.
COMMENT

```

```

PROCEDURE SpecialCaseHandler (IN SourceString : Unicode String
INOUT SourceIndex : 32 bit integer
INOUT UnicodeWeights : UnicodeWeightType String,
INOUT ExtraWeights : ExtraWeightType String,
INOUT SpecialWeights : SpecialWeightType String,
IN SortLocale : LCID,
IN IsKoreanLocale : boolean)

// Get the weight for the current character
SET CharacterWeights to CALL GetCharacterWeights WITH
(SortLocale, SourceString[SourceIndex])
CASE CharacterWeight.ScriptMember OF
UNSORTABLE :
    IF Windows version is Windows 8 or Windows Server 2012 Server THEN
        COMMENT Special case for IVS Sequences
        IF (IVS_HIGH_SURROGATE == SourceString[SourceIndex] AND
SourceIndex < Length(SourceString) - 1) THEN
            SET NextCharacter to SourceString[SourceIndex + 1]
            IF (NextCharacter >= IVS_LOW_SURROGATE_START AND
NextCharacter <= IVS_LOW_SURROGATE_END) THEN
                SourceIndex++;
            ENDIF
        ENDIF
    ENDIF
    // Character is unsortable, so skip it
    RETURN
NONSPACE_MARK :
    // Character is a nonspace mark, so only store the
    // diacritic weight.
    If (Length(DiacriticWeights) is greater than 0) THEN
        SET last DiacriticWeight in DiacriticWeights to
DiacriticWeight + CharacterWeights.DiacriticWeight
    ELSE
        APPEND CharacterWeights.DiacriticWeight to DiacriticWeights as a BYTE
    ENDIF
    RETURN
EXPANSION :
    // Expansion character, each character has 2 weights, store
    // each weight separately
    SET Weights to CALL GetExpansionWeights WITH
(SourceString[SourceIndex], SortLocale)
    // Store the appropriate weights, there should be 2 or 3
    FOR each Weight in Weights
        // Store the weight of the first character of the
        // expansion
        SET UnicodeWeight to CALL CorrectUnicodeWeight WITH
(Weights, IsKoreanLocale)
        APPEND UnicodeWeight to UnicodeWeights
        APPEND Weights.DiacriticWeight to DiacriticWeights as a BYTE
        APPEND Weights.CaseWeight to CaseWeights as a BYTE
    ENDFOR
    RETURN
PUNCTUATION :
    SET Position to Length(UnicodeWeights) as 16 bit integer
    APPEND Position into SpecialWeights as 16 bit integer
    SET SpecialWeight to CALL MakeUnicodeWeight WITH
(CharacterWeight.ScriptMember,
CharacterWeight.PrimaryWeight, False)
    APPEND SpecialWeight to SpecialWeights as 16 bit integer

```

```

RETURN
SYMBOL_1 :
SYMBOL_2 :
SYMBOL_3 :
SYMBOL_4 :
SYMBOL_5 :
SYMBOL_6 :
    // Character is a symbol, store Unicode Weights
    SET UnicodeWeight to CALL CorrectUnicodeWeight WITH
        (Weights[0], IsKoreanLocale)
    APPEND UnicodeWeight to UnicodeWeights
    APPEND CharacterWeights.DiacriticWeight to DiacriticWeights as a BYTE
    APPEND CharacterWeights.CaseWeight to CaseWeights as a BYTE
    RETURN
EASTASIA_SPECIAL :
    // Get the primary and case weight of the current code point
    SET PrimaryWeight to UnicodeWeight.PrimaryWeight
    SET ExtraWeight to UnicodeWeight.CaseWeight
    // Mask off the bits that are not required
    SET ExtraWeight to (ExtraWeight & CaseMask) |
        CASE_EXTRA_WEIGHT_MASK
    // Special case Repeat and Cho-On
    // PrimaryWeight = 0 => Repeat
    // PrimaryWeight = 1 => Cho-On
    // PrimaryWeight = 2+ => Kana
    IF PrimaryWeight is less than or equal to MAX_SPECIAL_PW THEN
        // If the script member of the previous character is
        // invalid, then give the special character
        // invalid weight (highest possible weight) so that it
        // will sort AFTER everything else.
        SET PreviousIndex to SourceIndex - 1
        IF Windows version is Windows 8 or Windows Server 2012 THEN
            // If an IVS sequence was just skipped, then go further back
            IF (PreviousIndex > 0 AND
                SourceString[PreviousIndex-1] == IVS_SURROGATE_HIGH AND
                SourceString[PreviousIndex] >= IVS_SURROGATE_LOW_START AND
                SourceString[PreviousIndex] <= IVS_SURROGATE_LOW_END) THEN
                SET PreviousIndex to SourceIndex -2
            ENDF
        ENDF
        SET UnicodeWeight.ScriptMember to MAP_INVALID_WEIGHT
        SET UnicodeWeight.PrimaryWeight to MAP_INVALID_WEIGHT
        WHILE PreviousIndex is greater than or equal to 0
            SET PreviousWeight to CALL GetCharacterWeights WITH
                (SortLocale, SourceString[PreviousIndex])
            IF PreviousWeight.ScriptMember is less than
                EASTASIA_SPECIAL THEN
                IF PreviousWeight.ScriptMember is not equal to
                    EXPANSION THEN
                    // UNSORTABLE or NONSPACE_MARK
                    // Ignore these to get the
                    // previous ScriptMember/PrimaryWeight
                    DECREMENT PreviousIndex
                IF Windows version is Windows 8 or Windows Server 2012 THEN
                    // If an IVS sequence was just skipped, then go further back
                    IF (PreviousIndex > 0 AND
                        SourceString[PreviousIndex-1] == IVS_SURROGATE_HIGH AND
                        SourceString[PreviousIndex] >= IVS_SURROGATE_LOW_START AND
                        SourceString[PreviousIndex] <= IVS_SURROGATE_LOW_END) THEN

```

```

        DECREMENT PreviousIndex
    ENDIF
ENDIF
CONTINUE WHILE PreviousIndex
ENDIF
ELSE IF PreviousWeight.ScriptMember is equal to
    EASTASIA_SPECIAL THEN
    IF PreviousWeight.PrimaryWeight is less than or equal to
        MAX_SPECIAL_PW THEN
        // Handle case where two special chars follow
        // each other. Keep going back in the string
        DECREMENT PreviousIndex
        CONTINUE WHILE PreviousIndex
    ENDIF
    SET UnicodeWeight to
    CALL MakeUnicodeWeight WITH (KANA,
        PreviousWeight.PrimaryWeight, IsKoreanLocale)
    // Only build weights W6 & W7 if the previous
    // character is KANA.
    // ignores W4 & W5
    // Always:
    // W6 = previous CW & ISOLATE_KANA
    SET PreviousExtraWeight to PreviousWeight.CaseWeight
    // Mask off the bits that aren't required
    SET PreviousExtraWeight to CASE_EXTRA_WEIGHT_MASK |
        (PreviousExtraWeight & CaseMask)
    // Ignore kana and width
    // so these are merely CASE_EXTRA_WEIGHT_MASK
    SET ExtraWeight.W6 to CASE_EXTRA_WEIGHT_MASK
    SET ExtraWeight.W7 to CASE_EXTRA_WEIGHT_MASK
    // Repeat is already done, which is:
    // UW = previous UW (set above)
    // W5 = ignored
    // W7 = previous CW & ISOLATE_WIDTH (done above)
    IF PrimaryWeight is not equal to PW_REPEAT THEN
        // Cho-On:
        // UW = previous UW & CHO_ON_UW_MASK
        // W5 = ignored
        // W7 = current CW & ISOLATE_WIDTH (done above)
        SET UnicodeWeight.PrimaryWeight to
        UnicodeWeight.PrimaryWeight & CHO_ON_PW_MASK
    ENDIF
    // Append the calculated ExtraWeight
    // APPEND ExtraWeight to ExtraWeights
ELSE
    // The previous weight is not EASTASIA_SPECIAL, so just
    // store the previous weight
    SET UnicodeWeight to CorrectUnicodeWeight
        (PreviousWeight, IsKoreanLocale)
    // Append the weight that was found
    APPEND UnicodeWeight to UnicodeWeights
ENDIF
ENDWHILE
ELSE
    // Kana
    // ScriptMember = KANA
    // PrimaryWeight = current PrimaryWeight
    // W4 = current CaseWeight & ISOLATE_SMALL
    // W5 = WT_FIVE_KANA

```

```

        //      W6 = current CaseWeight & ISOLATE_KANA
        //      W7 = current CaseWeight & ISOLATE_WIDTH
        SET UnicodeWeight to CALL MakeUnicodeWeight WITH ( KANA,
            CharacterWeight.PrimaryWeight, IsKoreanLocale)
        APPEND UnicodeWeight to UnicodeWeights
        SET TempExtraWeight.W4 to ExtraWeight & ISOLATE_SMALL
        SET TempExtraWeight.W5 to WT_FIVE_KANA
        SET TempExtraWeight.W6 to ExtraWeight & ISOLATE_KANA
        SET TempExtraWeight.W7 to ExtraWeight & ISOLATE_WIDTH
        APPEND TempExtraWeight to ExtraWeights
    ENDIF
    APPEND CharacterWeight.DiacriticWeight to DiacriticWeights as a BYTE
    APPEND MIN_CW to CaseWeights as a BYTE
    RETURN

JAMO_SPECIAL :
    // See if it's a leading Jamo
    IF (CALL IsJamoLeading(SourceString[SourceIndex])) is true
        THEN
            // If the characters beginning at SourceIndex are a valid
            // old Hangul composition, create the SortKey
            // according to the old Hangul rule
            SET OldHangulCount to
            CALL MapOldHangulSortKey WITH (SourceString,
                SourceIndex, SortLocale, UnicodeWeights, IsKoreanLocale)
            IF OldHangulCount is greater than 0 THEN
                // Decrement OldHangulCount because the caller's loop
                // will increment the SourceIndex as well
                DECREMENT OldHangulCount
                SET SourceIndex to SourceIndex + OldHangulCount
                RETURN
            ENDIF
        ENDIF
        // Otherwise, fall back to the normal behavior
        // No special case on the character, so store the Jamo's
        // weights.
        // Store the real script member in the diacritic weight
        // in the tables since both the diacritic weight and the
        // case weight are not used in Korean
        // For example, from unisort.txt:
        // 0x1101 4 84 83 2 ;   Choseong Ssangkiyeok
        // Field 2 has a value of 4 to trigger the code case for JAMO_SPECIAL.
        // Field 3 (84) is the real primary weight for this Jamo.
        // Field 4 (83) is the real script member for this Jamo.
        SET UnicodeWeight to CALL MakeUnicodeWeight WITH
            (CharacterWeight.DiacriticWeight,
                CharacterWeight.PrimaryWeight, IsKoreanLocale)
        APPEND UnicodeWeight to UnicodeWeights
        APPEND MIN_DW to DiacriticWeights as a BYTE
        APPEND MIN_CW to DiacriticWeights as a BYTE
        RETURN

EXTENSION_A :
    // Extension A gives us two weights
    // UnicodeWeight = SM_EXT_A, AW_EXT_A, AW, DW
    // First Weight
    SET UnicodeWeight to CALL MakeUnicodeWeight WITH
        (SCRIPT_MEMBER_EXT_A, PRIMARY_WEIGHT_EXT_A,
            IsKoreanLocale)
    APPEND UnicodeWeight to UnicodeWeights

```

```

// Since the script member is our flag for this EXTENSION_A special
// case, the real weights are in fields 2 & 3.
// Example:
// From unisort.txt:
// 0x3400 5 16 2 2 ; 𐄀 CJK Unified Ideographs Extension A
// Field 2 is the script member.
// Field 3 is the primary weight.
// Second Weight
SET UnicodeWeight to CALL MakeUnicodeWeight WITH
    (CharacterWeight.PrimaryWeight,
     CharacterWeight.DiacriticWeight, false)
APPEND UnicodeWeight to UnicodeWeights
APPEND MIN_DW to DiacriticWeights as a BYTE
APPEND MIN_CW to DiacriticWeights as a BYTE
RETURN
ENDCASE

```

3.1.5.2.15 GetPositionSpecialWeight

This algorithm specifies the retrieval of special weight based on the source index.

```

COMMENT GetPositionSpecialWeight
COMMENT
COMMENT On Entry:  Position - Position to calculate weight for
COMMENT
COMMENT On Exit:   Weight   - Resulting weight
COMMENT

PROCEDURE GetPositionSpecialWeight(IN Position : 32 bit integer,
                                   OUT Weight  : 16 bit integer)

// Add some bits (0x8003) to adjust the weight and because
// some bits are expected. Since setting 0x3 is required, rotate the source
// index 2 bits so as to not lose the precision.

// Note that if SourceIndex is larger than 0x1FFF, then some bits
// will be lost on the conversion to 16 bits. Presumably if a string
// is over 8191 characters long, they will differ well before this
// point, so the lost information is irrelevant.

SET Weight to (SourceIndex << 2) | 0x8003
RETURN Weight

```

3.1.5.2.16 MapOldHangulSortKey

This algorithm specifies the generation of Unicode weight based on the strings at the specified index that have a special Old Hangul sequence. [<6>](#)

```

COMMENT MapOldHangulSortKey
COMMENT
COMMENT On Entry:  SourceString - Unicode String to test
COMMENT              SourceIndex - Index of leading Jamo to start
COMMENT              from
COMMENT              SortLocale  - Locale to use for linguistic
COMMENT              sort data

```

```

COMMENT          UnicodeWeights - String to store any Unicode
COMMENT          weight found
COMMENT          for this character(s)
COMMENT
COMMENT  On Exit:  CharactersRead - Number of old Hangul found
COMMENT          UnicodeWeights - Any Unicode weights found are
COMMENT          appended
COMMENT

PROCEDURE MapOldHangulSortKey(IN SourceString : Unicode String,
                              IN SourceIndex : 32 bit integer,
                              IN SortLocale : LCID,
                              IN OUTUnicodeWeights : String of UnicodeWeightType,
                              IN IsKoreanLocale : Boolean,
                              OUT CharactersRead : 32 bit integer)

SET CurrentIndex to SourceIndex
SET JamoSortInfo to empty JamoSortInfoType

SET CurrentCharacter to SourceString[CurrentIndex]

IF CALL IsLeadingJamo WITH (CurrentCharacter) is not true
  AND CALL IsVowelJamo WITH (CurrentCharacter) is not true
  AND CALL IsVowelJamo WITH (CurrentCharacter) is not true THEN
  RETURN 0
ENDIF

// Add Leading Jamo weight
IF CALL IsLeadingJamo WITH (CurrentCharacter) is true
  INCREMENT CurrentIndex;
ELSE
  SET CurrentCharacter LEADING JAMO FILLER;
ENDIF

IF CurrentCharacter IS LEADING JAMO FILLER
  SET JamoSortInfo.bFiller to 1;
ENDIF

SET JamoStateData to CALL GetJamoStateData WITH (CurrentCharacter)
SET JamoSortInfo to CALL UpdateJamoSortInfo
  WITH ("Leading Jamo Class", JamoStateData, JamoSortInfo)

// Add Vowel Jamo weight
SET CurrentCharacter to SourceString[CurrentIndex]

IF CALL IsVowelJamo WITH (CurrentCharacter) is true
  INCREMENT CurrentIndex;
ELSE
  SET CurrentCharacter VOWEL JAMO FILLER;
ENDIF

IF CurrentCharacter IS VOWEL JAMO FILLER
  SET JamoSortInfo.bFiller to 1;
ENDIF

SET JamoStateData to CALL GetJamoStateData WITH (CurrentCharacter)
SET JamoSortInfo to CALL UpdateJamoSortInfo
  WITH ("Vowel Jamo Class", JamoStateData, JamoSortInfo)

```



```

// Add Trailing Jamo weight
SET CurrentCharacter to SourceString[CurrentIndex]

IF CALL IsTrailingJamo WITH (CurrentCharacter) is true
INCREMENT CurrentIndex;
SET JamoStateData to CALL GetJamoStateData WITH (CurrentCharacter)
SET JamoSortInfo to CALL UpdateJamoSortInfo
WITH ("Trailing Jamo Class", JamoStateData, JamoSortInfo)
ENDIF

// If this is not Old Hangul
IF JamoSortInfo.OldHangulFlag is not true THEN
SET JamoStateData to CALL GetJamoStateData WITH (SourceString[0])
CLEAR JamoSortInfo
SET JamoSortInfo to CALL UpdateJamoSortInfo
WITH ("Leading Jamo Class", JamoStateData, JamoSortInfo)
SET CurrentIndex to 1;

SET JamoStateData to CALL GetJamoStateData WITH (VOWEL JAMO FILLER)
SET JamoSortInfo to CALL UpdateJamoSortInfo
WITH ("Vowel Jamo Class", JamoStateData, JamoSortInfo)
ENDIF

// Compute the modern hangul syllable prior to this composition
// Users formula from Unicode 3.0 Section 3.11 p54
// "Hangul Syllable Composition"
// This converts a U+11.. sequence to a U+AC00 character

SET ModernHangul to (JamoSortInfo.LeadingIndex *
NLS_JAMO_VOWELCOUNT + JamoSortInfo.VowelIndex) *
NLS_JAMO_TRAILING_COUNT + JamoSortInfo.TrailingIndex +
NLS_HANGUL_FIRST_SYLLABLE

IF JamoSortInfo.bFiller is 1 THEN
DECREMENT ModernHangul
IF ModernHangul is less than first hangul syllable THEN
Set ModernHangul to 0x326e
ENDIF
INCREMENT JamoSortInfo.LeadingWeight by 0x80.
ENDIF

// Store the weights
SET CharacterWeight to CALL GetCharacterWeights WITH (ModernHangul)
SET UnicodeWeight to CALL CorrectUnicodeWeight
WITH (CharacterWeight, IsKoreanLocale)
APPEND UnicodeWeight to UnicodeWeights

// Add additional weights
SET UnicodeWeight to CALL MakeUnicodeWeight WITH
(ScriptMember_Extra_UnicodeWeight,
JamoSortInfo.LeadingWeight, false)
APPEND UnicodeWeight to UnicodeWeights

SET UnicodeWeight to CALL MakeUnicodeWeight WITH
(ScriptMember_Extra_UnicodeWeight,
JamoSortInfo.VowelWeight, false)

APPEND UnicodeWeight to UnicodeWeights

```

```

SET UnicodeWeight to CALL MakeUnicodeWeight WITH
    (ScriptMember_Extra_UnicodeWeight,
     JamoSortInfo.TrailingWeight, false)

APPEND UnicodeWeight to UnicodeWeights

// Return the characters consumed
SET CharactersRead to CurrentIndex - SourceIndex
RETURN CharactersRead

```

3.1.5.2.17 GetJamoComposition

This algorithm specifies the strings at the specified index that form a valid Old Hangul character that is composed of a Jamo character sequence.<7>

```

COMMENT GetJamoComposition
COMMENT
COMMENT On Entry:  SourceString - Unicode String to test
COMMENT             CurrentIndex - Index of leading Jamo to start from
COMMENT             JamoClass    - Class of Jamo to look for
COMMENT             JamoSortInfo - Information about the current
COMMENT                               sequence
COMMENT On Exit:   JamoSortInfo - Updated with information about
COMMENT                               the new sequence
COMMENT             SourceIndex  - Updated to next character if
COMMENT                               Jamo is found
COMMENT             NewJamoClass - New class to look for next
COMMENT
COMMENT NOTE: This function assumes the character at SourceString
COMMENT       [SourceIndex] is a leading Jamo.
COMMENT       Ie: IsJamo() returned true
COMMENT

PROCEDURE GetJamoComposition (IN SourceString : Unicode String,
                              INOUT CurrentIndex : 32 bit integer,
                              IN JamoClass : enumeration,
                              INOUT JamoSortInfo : JamoSortInfoType,
                              OUT NewJamoClass : enumeration)

SET CurrentCharacter to SourceString[CurrentIndex]

// Get the Jamo information for the current character
SET JamoStateData to CALL GetJamoStateData WITH (CurrentCharacter)
SET JamoSortInfo to CALL UpdateJamoSortInfo
    WITH (JamoClass, JamoStateData, JamoSortInfo)

// Move on to the next character
INCREMENT CurrentIndex

WHILE CurrentIndex is less than Length(SourceString)
    SET CurrentCharacter to SourceString[CurrentIndex]

    IF CALL IsJamo WITH (CurrentCharacter) is not true THEN
        // The current character is not a Jamo,
        // Done checking for a Jamo composition
        SET NewJamoClass to "Invalid Jamo Sequence"
        RETURN

```

```

ENDIF

IF CurrentCharacter is equal to 0x1160 THEN
    SET JamoSortInfo.FillerUsed to true
ENDIF

// Get the Jamo class of it
IF CALL IsJamoLeading WITH (CurrentCharacter) is true THEN
    SET NewJamoClass to "Leading Jamo Class"
ELSE IF CALL IsJamoTrailing WITH (CurrentCharacter) is true THEN
    SET NewJamoClass to "Trailing Jamo Class"
ELSE
    SET NewJamoClass to "Vowel Jamo Class"
ENDIF

IF JamoClass is not equal to NewJamoClass THEN
    RETURN NewJamoClass
ENDIF

// Push the current Jamo (SourceString[CurrentIndex])
// into the state machine to check if it is a valid
// old Hangul composition. During the check also
// update the sortkey result in:
JamoSortInfo

// Find the new record
SET JamoStateData to CALL FindNewJamoState
    WITH (CurrentCharacter, JamoStateData)

// A valid old Hangul composition was not found for the current
// character so return the current Jamo class
// (JamoClass and NewJamoClass are identical)
IF JamoStateData is null THEN
    RETURN NewJamoClass
ENDIF

// A match has been found, so update our info.
SET JamoSortInfo to CALL UpdateJamoSortInfo
    WITH (JamoClass, JamoStateData, JamoSortInfo)

// Still in a valid old Hangul composition.
//Go check the next character.
INCREMENT CurrentIndex

ENDWHILE CurrentIndex

SET NewJamoClass to "Invalid Jamo Sequence"
RETURN NewJamoClass

```

3.1.5.2.18 GetJamoStateData

This algorithm specifies the retrieval of state machine information to check if the specified Jamo sequence forms a valid Old Hangul character. [<8>](#)

```

COMMENT GetJamoStateData
COMMENT
COMMENT On Entry: Character - Unicode Character to get Jamo

```

```

COMMENT                                information for
COMMENT
COMMENT On Exit:   JamoStateData - Jamo state information from
COMMENT                                the data file
COMMENT
COMMENT Jamo State information looks like this in the database:
COMMENT
COMMENT SORTTABLES
COMMENT ...
COMMENT JAMOSORT395
COMMENT ...
COMMENT 0x1100      0x00      0x00      0x00      0x00      0x03      ;1100      L
COMMENT 0x1101      0x00      0x01      0x00      0x00      0x04      ;1101      L
COMMENT 0x1102      0x00      0x02      0x00      0x00      0x06      ;1102      L
COMMENT 0x1103      0x00      0x03      0x00      0x00      0x0e      ;1103      L
COMMENT

PROCEDURE GetJamoStateData (IN Character : Unicode Character,
                           OUT JamoStateData : JamoStateDateType)

// Get the Jamo section for this character.
// If Character was 0x1172, this would access the following section:
//   0x1172 0x00 0x00 0x11 0x00 0x38 ; U+1172          record 0
//   |     |     |     |     |     |
// Field 1 2     3     4     5     6           Comment

OPEN SECTION JamoSection
    where name is SORTTABLES\JAMOSORT\[Character] from unisort.txt

// Now open the first record
SELECT RECORD JamoRecord FROM JamoSection WHERE record index is 0

// Now gather the information from that record.
SET JamoStateData.OldHangulFlag to JamoRecord.Field2
SET JamoStateData.LeadingIndex to JamoRecord.Field3
SET JamoStateData.VowelIndex to JamoRecord.Field4
SET JamoStateData.TrailingIndex to JamoRecord.Field5
SET JamoStateData.ExtraWeight to JamoRecord.Field6

// Remember the record
SET JamoStateData.DataRecord to JamoRecord

RETURN JamoStateData

```

3.1.5.2.19 FindNewJamoState

This algorithm specifies retrieval of a new state from the state machine for Jamo processing. [<9>](#)

```

COMMENT FindNewJamoState
COMMENT
COMMENT On Entry:   JamoCharacter - Unicode Character to get Jamo
COMMENT                                information for
COMMENT                JamoStateData - Current Jamo state information
COMMENT
COMMENT On Exit:   JamoStateData - New Jamo state record from the
COMMENT                                data file, null if an
COMMENT                                appropriate state record is

```

```

COMMENT                                not found.
COMMENT

PROCEDURE FindNewJamoState(IN JamoCharacter : Unicode Character,
                           INOUT JamoStateData : JamoStateDataType)

// The current JamoStateData.DataRecord points to the base record.
// There are JamoStateData.TransitionCount following records that may
// match the input JamoCharacter, the search is for the first one
SET DataRecord to JamoStateData.DataRecord

WHILE JamoStateData.TransitionCount is greater than 0
  // advance to the next record in the data and test if
  // it is the correct record for JamoCharacter
  ADVANCE DataRecord to next record in data table
  IF DataRecord.Field1 is equal to JamoCharacter THEN
    // Found a record, get its info and return it
    // Now gather the information from that record.
    SET JamoStateData.OldHangulFlag   to JamoRecord.Field2
    SET JamoStateData.LeadingIndex    to JamoRecord.Field3
    SET JamoStateData.VowelIndex     to JamoRecord.Field4
    SET JamoStateData.TrailingIndex   to JamoRecord.Field5
    SET JamoStateData.ExtraWeight     to JamoRecord.Field6
    SET JamoStateData.TransitionCount to JamoRecord.Field7

    // Remember the record
    SET JamoStateData.DataRecord to JamoRecord

    RETURN JamoStateData
  ENDWHILE

// record not found, return null
SET JamoStateData to null
RETURN JamoStateData

```

3.1.5.2.20 UpdateJamoSortInfo

This algorithm specifies the update of Jamo sorting information based on the current state of the state machine for Jamo processing. [<10>](#)

```

COMMENT UpdateJamoSortInfo
COMMENT
COMMENT On Entry:  JamoClass      - The current Jamo Class
COMMENT              JamoStateData - Information about the new
COMMENT              character state
COMMENT              JamoSortInfo  - Information about the character
COMMENT              state
COMMENT
COMMENT On Exit:   JamoSortInfo - Updated with information about
COMMENT              the new state based on JamoClass
COMMENT              and JamoSortData
COMMENT

PROCEDURE UpdateJamoSortInfo(IN JamoClass : enumeration,
                             IN JamoStateData : JamoStateDataType,
                             INOUT JamoSortInfo : JamoSortInfoType)

```

```

// Record if this is a Jamo unique to old Hangul
SET JamoSortInfo.OldHangulFlag to
    JamoSortInfo.OldHangulFlag | JamoStateData.OldHangulFlag

// Update the indices if the new ones are higher than the current
// ones.
IF JamoStateData.LeadingIndex
    is greater than JamoSortInfo.LeadingIndex THEN
    SET JamoSortInfo.LeadingIndex to JamoStateData.LeadingIndex;
ENDIF

IF JamoStateData.VowelIndex
    is greater than JamoSortInfo.VowelIndex THEN
    SET JamoSortInfo.VowelIndex to JamoStateData.VowelIndex;
ENDIF

IF JamoStateData.TrailingIndex
    is greater than JamoSortInfo.TrailingIndex THEN
    SET JamoSortInfo.TrailingIndex to JamoStateData.TrailingIndex;
ENDIF

// Update the extra weights according to the current Jamo class.
CASE JamoClass OF
    "Leading Jamo Class":
        IF JamoStateData.ExtraWeight
            is greater than JamoSortInfo.LeadingWeight THEN
            SET JamoSortInfo.LeadingWeight to JamoStateData.ExtraWeight
        ENDIF

    "Vowel Jamo Class":
        IF JamoStateData.ExtraWeight
            is greater than JamoSortInfo.VowelWeight THEN
            SET JamoSortInfo.VowelWeight to JamoStateData.ExtraWeight
        ENDIF

    "Trailing Jamo Class":
        IF JamoStateData.ExtraWeight
            is greater than JamoSortInfo.TrailingWeight THEN
            SET JamoSortInfo.TrailingWeight to JamoStateData.ExtraWeight
        ENDIF
ENDCASE

RETURN JamoSortInfo

```

3.1.5.2.21 IsJamo

This algorithm specifies the check for a valid Jamo character. [<11>](#)

```

COMMENT IsJamo
COMMENT
COMMENT On Entry:  SourceCharacter - Unicode Character to test
COMMENT
COMMENT On Exit:   Result           - true if SourceCharacter is in
COMMENT                                     the Jamo range
COMMENT
COMMENT

```

```

PROCEDURE IsJamoLeading(IN SourceCharacter : Unicode Character,
                      OUT Result: boolean)

IF (SourceCharacter is greater than or equal to NLS_CHAR_FIRST_JAMO)
  and
  (SourceCharacter is less than or equal to NLS_CHAR_LAST_JAMO) THEN
  SET Result to true
ELSE
  SET Result to false
ENDIF

RETURN Result

```

3.1.5.2.22 IsCombiningJamo

This algorithm specifies the check for a valid Jamo character. [<12>](#)

```

COMMENT IsCombiningJamo
COMMENT
COMMENT On Entry:  SourceCharacter - Unicode Character to test
COMMENT
COMMENT On Exit:   Result           - true if SourceCharacter is in
COMMENT           the Jamo range
COMMENT

PROCEDURE IsJamoLeading(IN SourceCharacter : Unicode Character,
                      OUT Result: boolean)

IF ((SourceCharacter is greater than or equal to NLS_CHAR_FIRST_JAMO)
  and
  (SourceCharacter is less than or equal to NLS_CHAR_LAST_JAMO))
  Or
  ((SourceCharacter is greater than or equal to NLS_CHAR_FIRST_EXT_A_LEADING_JAMO)
  and
  (SourceCharacter is less than or equal to NLS_CHAR_LAST_EXT_A_LEADING_JAMO))
  Or
  ((SourceCharacter is greater than or equal to NLS_CHAR_FIRST_EXT_B_VOWEL_JAMO)
  and
  (SourceCharacter is less than or equal to NLS_CHAR_LAST_EXT_B_VOWEL_JAMO))
  Or
  ((SourceCharacter is greater than or equal to NLS_CHAR_FIRST_EXT_B_TRAILING_JAMO)
  and
  (SourceCharacter is less than or equal to NLS_CHAR_LAST_EXT_B_TRAILING_JAMO)) THEN
  SET Result to true
ELSE
  SET Result to false
ENDIF

RETURN Result

```

3.1.5.2.23 IsJamoLeading

This algorithm checks if the specified Jamo character is a leading Jamo. [<13>](#)

```

COMMENT IsJamoLeading
COMMENT
COMMENT On Entry: SourceCharacter - Unicode Character to test
COMMENT
COMMENT On Exit: Result - true if SourceCharacter is a
COMMENT leading Jamo
COMMENT

PROCEDURE IsJamoLeading(IN SourceCharacter : Unicode Character,
                      OUT Result: boolean)

IF ((SourceCharacter is greater than or equal to NLS_CHAR_FIRST_JAMO)
    and
    (SourceCharacter is less than or equal to NLS_CHAR_LAST_LEADING_JAMO))
    Or
    ((SourceCharacter is greater than or equal to NLS_CHAR_FIRST_EXT_A_LEADING_JAMO)
    and
    (SourceCharacter is less than or equal to NLS_CHAR_LAST_LEADING_EXT_A_LEADING_JAMO))
    SET Result to true
ELSE
    SET Result to false
ENDIF

RETURN Result

```

3.1.5.2.24 IsJamoVowel

This algorithm checks whether the specified Jamo character is a vowel Jamo. [<14>](#)

```

COMMENT IsJamoVowel
COMMENT
COMMENT On Entry: SourceCharacter - Unicode Character to test
COMMENT
COMMENT On Exit: Result - true if this is a vowel Jamo
COMMENT

PROCEDURE IsJamoTrailing(IN SourceCharacter : Unicode Character,
                        OUT Result: boolean)

IF ((SourceCharacter is greater than or equal to NLS_CHAR_FIRST_VOWEL_JAMO)
    and
    (SourceCharacter is less than or equal to NLS_CHAR_LAST_VOWEL_JAMO))
    Or
    ((SourceCharacter is greater than or equal to NLS_CHAR_FIRST_EXT_B_VOWEL_JAMO)
    and
    (SourceCharacter is less than or equal to NLS_CHAR_LAST_LEADING_EXT_B_VOWEL_JAMO))
    SET Result to true
ELSE
    SET Result to false
ENDIF

RETURN Result

```


3.1.5.2.25 IsJamoTrailing

This algorithm checks if the specified Jamo character is a trailing Jamo. <15>

```
COMMENT IsJamoTrailing
COMMENT
COMMENT On Entry: SourceCharacter - Unicode Character to test
COMMENT
COMMENT On Exit: Result - true if this is a trailing Jamo
COMMENT
COMMENT NOTE: Only call this if the character is known to be a Jamo
COMMENT syllable. This function only helps distinguish between
COMMENT the different types of Jamo, so only call it if
COMMENT IsJamo() has returned true.
COMMENT

PROCEDURE IsJamoTrailing(IN SourceCharacter : Unicode Character,
                        OUT Result: boolean)

IF SourceCharacter is greater than
  or equal to NLS_CHAR_FIRST_VOWEL_JAMO THEN
  SET Result to true
ELSE
  SET Result to false
ENDIF

RETURN Result
```

3.1.5.2.26 InitKoreanScriptMap

This algorithm specifies the initialization of a data structure that is required for the special processing of Korean script members.

```
COMMENT InitKoreanScriptMap
COMMENT
COMMENT On Entry: global KoreanScriptMap - presumed to be null
COMMENT
COMMENT On Exit: global KoreanScriptMap - initialized to map
COMMENT scripts to Korean
COMMENT
COMMENT This procedure initializes the Korean, causing ideographic
COMMENT scripts to sort prior to other scripts for the Korean.
COMMENT

PROCEDURE InitKoreanScriptMap

SET KoreanScriptMap to new array of 256 null bytes

// Initialize the "scripts" prior to first script (Latin, script 14)
FOR counter is 0 to FIRST_SCRIPT - 1
  SET KoreanScriptMap[counter] to counter
ENDFOR counter

// For Korean the Ideographs sort to the first script,
// so start with that index
SET NewScript to FIRST_SCRIPT
```

```

// Test if the IDEOGRAPH script is part of a multiple weights script

// For convenience hard code the information from the
// unisort.txt section SORTTABLES\MULTIPLEWEIGHTS
// IDEOGRAPHS are 128 through 241,
// map them to FIRST_SCRIPT through 127
FOR counter is IDEOGRAPH to 241
    SET KoreanScriptMap[counter] to NewScript
    INCREMENT NewScript
ENDFOR

// Now set the remaining unset scripts the next NewScript value
FOR counter is 0 to MAX_SCRIPTS - 1
    // If the value has not been set yet, set it to the next value
    IF KoreanScriptMap[counter] is null THEN
        SET KoreanScriptMap[counter] to NewScript
        INCREMENT NewScript
    ENDIF
ENDFOR

```

3.1.5.3 Mapping UTF-16 Strings to Upper Case

To map a UTF-16 string to upper case, each UTF-16 code point is looked for in an upper casing table [\[MSDN-UCMT/Win8\]](#). If an entry is found, the input code point is changed to the output code point.

3.1.5.3.1 ToUpperCase

This algorithm converts a UTF-16 string to its upper case form.

```

COMMENT ToUpperCase
COMMENT On Entry: inputString - A string encoded in UTF-16
COMMENT
COMMENT On Exit: Result - A string encoded in UTF-16 with
COMMENT the output in Upper Case form.

PROCEDURE ToUpperCase

SET Result to empty string

SET index to 0
WHILE index is less than Length(inputString)
    SET upperCase to UpperCaseMapping(inputString[index])
    APPEND upperCase to Result
    INCREMENT index
ENDWHILE

RETURN

```

3.1.5.3.2 UpperCaseMapping

This algorithm converts a UTF-16 code point to its upper case form using the UpperCaseTable in [\[MSDN-UCMT/Win8\]](#).

```

COMMENT UpperCaseMapping

```

```
COMMENT On Entry: SourceCharacter - A UTF-16 code point
COMMENT
COMMENT On Exit: Result - Upper case UTF-16 code point

PROCEDURE UpperCaseMapping

SELECT RECORD caseMapping FROM UpperCaseTable WHERE field 1
    matches SourceCharacter
IF EXISTS caseMapping
    SET Result TO caseMapping field 2
ELSE
    SET Result TO SourceCharacter
ENDIF

RETURN
```

3.1.6 Timer Events

None.

3.1.7 Other Local Events

None.

4 Protocol Examples

None.

5 Security

The following sections specify security considerations for implementers of the Windows Protocols Unicode Reference.

5.1 Security Considerations for Implementers

None.

5.2 Index of Security Parameters

None.

6 Appendix A: Product Behavior

The information in this specification is applicable to the following Microsoft products or supplemental software. References to product versions include released service packs:

- Windows NT operating system
- Windows 2000 operating system
- Windows XP operating system
- Windows Server 2003 operating system
- Windows Vista operating system
- Windows Server 2008 operating system
- Windows 7 operating system
- Windows Server 2008 R2 operating system
- Windows 8 operating system
- Windows Server 2012 operating system

Exceptions, if any, are noted below. If a service pack or Quick Fix Engineering (QFE) number appears with the product version, behavior changed in that service pack or QFE. The new behavior also applies to subsequent service packs of the product unless otherwise specified. If a product edition appears with the product version, behavior is different in that product edition.

Unless otherwise specified, any statement of optional behavior in this specification that is prescribed using the terms SHOULD or SHOULD NOT implies product behavior in accordance with the SHOULD or SHOULD NOT prescription. Unless otherwise specified, the term MAY implies that the product does not follow the prescription.

[<1> Section 2.2.1:](#) These codepages are used natively in Windows NT 4.0, Windows 2000, Windows XP, Windows Server 2003, Windows Vista, Windows Server 2008, Windows 7, Windows Server 2008 R2, Windows 8, and Windows Server 2012.

[<2> Section 3.1.5.2.3:](#) Windows 8 and Windows Server 2012 do not use record count for DEFAULT.

[<3> Section 3.1.5.2.3:](#) An LCID is used in Windows NT, Windows 2000, Windows XP, Windows Server 2003, Windows Vista, Windows Server 2008, Windows 7, and Windows Server 2008 R2. A LOCALENAME is used in Windows 8 and Windows Server 2012.

[<4> Section 3.1.5.2.3:](#) An LCID is used in Windows NT, Windows 2000, Windows XP, Windows Server 2003, Windows Vista, Windows Server 2008, Windows 7, and Windows Server 2008 R2.

[<5> Section 3.1.5.2.3:](#) A LOCALENAME is used in Windows 8 and Windows Server 2012.

[<6> Section 3.1.5.2.16:](#) The following MapOldHangulSortKey algorithm is only used in Windows NT, Windows 2000, Windows XP, Windows Server 2003, Windows Vista, Windows Server 2008, Windows 7, and Windows Server 2008 R2.

```
COMMENT MapOldHangulSortKey
COMMENT
COMMENT On Entry:  SourceString  - Unicode String to test
```

```

COMMENT          SourceIndex  - Index of leading Jamo to start
COMMENT          from
COMMENT          SortLocale   - Locale to use for linguistic
COMMENT          sort data
COMMENT          UnicodeWeights - String to store any Unicode
COMMENT          weight found
COMMENT          for this character(s)
COMMENT
COMMENT On Exit:  CharactersRead - Number of old Hangul found
COMMENT          UnicodeWeights - Any Unicode weights found are
COMMENT          appended
COMMENT

PROCEDURE MapOldHangulSortKey(IN SourceString : Unicode String,
                              IN SourceIndex : 32 bit integer,
                              IN SortLocale : LCID,
                              IN OUTUnicodeWeights : String of UnicodeWeightType,
                              IN IsKoreanLocale : Boolean,
                              OUT CharactersRead : 32 bit integer)

SET CurrentIndex to SourceIndex
SET JamoSortInfo to empty JamoSortInfoType

// Get any Old Hangul Leading Jamo composition for our Leading Jamo
SET JamoClass to CALL GetJamoComposition WITH (SourceString,
                                              SourceIndex, "Leading Jamo Class", JamoSortInfo)

IF JamoClass is equal to "Vowel Jamo Class" THEN
    // A Vowel Jamo, try to find an
    // Old Hangul Vowel Jamo composition.
    SET JamoClass to CALL GetJamoComposition WITH (SourceString,
                                                  SourceIndex, "Vowel Jamo Class", JamoSortInfo)
ENDIF

IF JamoClass is equal to "Trailing Jamo Class" THEN
    // A Trailing Jamo, try to find an
    // Old Hangul Trailing Jamo composition.
    SET JamoClass CALL GetJamoComposition WITH (SourceString,
                                              SourceIndex, "Trailing Jamo Class", JamoSortInfo)
ENDIF

// A valid leading and vowel sequence and this is
// old Hangul...
IF JamoSortInfo.OldHangulFlag is true THEN

    // Compute the modern hangul syllable prior to this composition
    // Users formula from Unicode 3.0 Section 3.11 p54
    // "Hangul Syllable Composition"
    // This converts a U+11.. sequence to a U+AC00 character

    SET ModernHangul to (JamoSortInfo.LeadingIndex *
                        NLS_JAMO_VOWELCOUNT + JamoSortInfo.VowelIndex) *
                        NLS_JAMO_TRAILING_COUNT + JamoSortInfo.TrailingIndex +
                        NLS_HANGUL_FIRST_SYLLABLE

    IF JamoSortInfo.FillerUsed is true THEN
        // If the filler is used, sort before the modern Hangul,
        // instead of after
        DECREMENT ModernHangul
    
```

```

// If falling off the modern Hangul syllable block...
IF ModernHangul is less than NLS_HANGUL_FIRST_SYLLABLE THEN
    // Sort after the previous character
    // (Circled Hangul Kiyeok A)
    SET ModernHangul to 0x326e
ENDIF

// Shift the leading weight past any old Hangul
// that sorts after this modern Hangul
SET JamoSortInfo.LeadingWeight to
    JamoSortInfo.LeadingWeight + 0x80
ENDIF

// Store the weights
SET CharacterWeight to CALL GetCharacterWeights WITH (ModernHangul)
SET UnicodeWeight to CALL CorrectUnicodeWeight
    WITH (CharacterWeight, IsKoreanLocale)
APPEND UnicodeWeight to UnicodeWeights

// Add additional weights
SET UnicodeWeight to CALL MakeUnicodeWeight WITH
    (ScriptMember_Extra_UnicodeWeight,
    JamoSortInfo.LeadingWeight, false)
APPEND UnicodeWeight to UnicodeWeights

SET UnicodeWeight to CALL MakeUnicodeWeight WITH
    (ScriptMember_Extra_UnicodeWeight,
    JamoSortInfo.VowelWeight, false)

APPEND UnicodeWeight to UnicodeWeights
SET UnicodeWeight to CALL MakeUnicodeWeight WITH
    (ScriptMember_Extra_UnicodeWeight,
    JamoSortInfo.TrailingWeight, false)

APPEND UnicodeWeight to UnicodeWeights

// Return the characters consumed
SET CharactersRead to CurrentIndex - SourceIndex
RETURN CharactersRead
ENDIF

// Otherwise it isn't a valid old Hangul composition
// and don't do anything with it

SET CharactersRead to 0
RETURN CharactersRead

```

[<7> Section 3.1.5.2.17:](#) The GetJamoComposition algorithm is only used in Windows NT, Windows 2000, Windows XP, Windows Server 2003, Windows Vista, Windows Server 2008, Windows 7, and Windows Server 2008 R2.

[<8> Section 3.1.5.2.18:](#) The following GetJamoStateData algorithm is only used in Windows NT, Windows 2000, Windows XP, Windows Server 2003, Windows Vista, Windows Server 2008, Windows 7, and Windows Server 2008 R2.

```
COMMENT GetJamoStateData
```



```

COMMENT
COMMENT On Entry: Character - Unicode Character to get Jamo
COMMENT information for
COMMENT
COMMENT On Exit: JamoStateData - Jamo state information from
COMMENT the data file
COMMENT
COMMENT Jamo State information looks like this in the database:
COMMENT
COMMENT SORTTABLES
COMMENT ...
COMMENT JAMOSORT395
COMMENT ...
COMMENT 0x11724
COMMENT 0x1172 0x00 0x00 0x11 0x00 0x380x03; U+1172
COMMENT 0x1161 0x01 0x00 0x00 0x00 0x000x01; U+1172,1161
COMMENT 0x1175 0x01 0x00 0x11 0x1b 0x3a0x00; U+1172,1161,1175
COMMENT 0x1169 0x01 0x00 0x11 0x1b 0x3f0x00; U+1172,1169

```

```

PROCEDURE GetJamoStateData (IN Character : Unicode Character,
                           OUT JamoStateData : JamoStateDateType)

```

```

// Get the Jamo section for this character.
// If Character was 0x1172, this would access the following section:
// 0x11724
// 0x1172 0x00 0x00 0x11 0x00 0x38 0x03 ; U+1172 record 0
// 0x1161 0x01 0x00 0x00 0x00 0x00 0x01 ; U+1172,1161 record 1
// 0x1175 0x01 0x00 0x11 0x1b 0x3a 0x00 ; U+1172,1161,1175 record 2
// 0x1169 0x01 0x00 0x11 0x1b 0x3f 0x00 ; U+1172,1169 record 3
// | | | | | | | |
// Field 1 2 3 4 5 6 7 Comment

```

```

OPEN SECTION JamoSection
  where name is SORTTABLES\JAMOSORT\[Character] from unisort.txt

```

```

// Now open the first record
SELECT RECORD JamoRecord FROM JamoSection WHERE record index is 0

```

```

// Now gather the information from that record.
SET JamoStateData.OldHangulFlag to JamoRecord.Field2
SET JamoStateData.LeadingIndex to JamoRecord.Field3
SET JamoStateData.VowelIndex to JamoRecord.Field4
SET JamoStateData.TrailingIndex to JamoRecord.Field5
SET JamoStateData.ExtraWeight to JamoRecord.Field6
SET JamoStateData.TransitionCount to JamoRecord.Field7

```

```

// Remember the record
SET JamoStateData.DataRecord to JamoRecord

```

```

RETURN JamoStateData

```

[<9> Section 3.1.5.2.19:](#) The FindNewJamoState algorithm is only used in Windows NT, Windows 2000, Windows XP, Windows Server 2003, Windows Vista, Windows Server 2008, Windows 7, and Windows Server 2008 R2.

[<10> Section 3.1.5.2.20:](#) The following UpdateJamoSortInfo algorithm is only used in Windows NT, Windows 2000, Windows XP, Windows Server 2003, Windows Vista, Windows Server 2008, Windows 7, and Windows Server 2008 R2.

```

COMMENT UpdateJamoSortInfo
COMMENT
COMMENT On Entry:  JamoClass      - The current Jamo Class
COMMENT              JamoStateData - Information about the new
COMMENT              character state
COMMENT              JamoSortInfo  - Information about the character
COMMENT              state
COMMENT
COMMENT On Exit:   JamoSortInfo  - Updated with information about
COMMENT              the new state based on JamoClass
COMMENT              and JamoSortData
COMMENT

PROCEDURE UpdateJamoSortInfo(IN JamoClass : enumeration,
                             IN JamoStateData : JamoStateDataType,
                             INOUT JamoSortInfo : JamoSortInfoType)

// Record if this is a Jamo unique to old Hangul
SET JamoSortInfo.OldHangulFlag to
    JamoSortInfo.OldHangulFlag | JamoStateData.OldHangulFlag

// Update the indices if the new ones are higher than the current
// ones.
IF JamoStateData.LeadingIndex
    is greater than JamoSortInfo.LeadingIndex THEN
    SET JamoSortInfo.LeadingIndex to JamoStateData.LeadingIndex;
ENDIF

IF JamoStateData.VowelIndex
    is greater than JamoSortInfo.VowelIndex THEN
    SET JamoSortInfo.VowelIndex to JamoStateData.VowelIndex;
ENDIF

IF JamoStateData.TrailingIndex
    is greater than JamoSortInfo.TrailingIndex THEN
    SET JamoSortInfo.TrailingIndex to JamoStateData.TrailingIndex;
ENDIF

// Update the extra weights according to the current Jamo class.
CASE JamoClass OF
    "Leading Jamo Class":
        IF JamoStateData.ExtraWeight
            is greater than JamoSortInfo.LeadingWeight THEN
            SET JamoSortInfo.LeadingWeight to JamoStateData.ExtraWeight
        ENDIF

    "Vowel Jamo Class":
        IF JamoStateData.ExtraWeight
            is greater than JamoSortInfo.VowelWeight THEN
            SET JamoSortInfo.VowelWeight to JamoStateData.ExtraWeight
        ENDIF

    "Trailing Jamo Class":
        IF JamoStateData.ExtraWeight
            is greater than JamoSortInfo.TrailingWeight THEN
            SET JamoSortInfo.TrailingWeight to JamoStateData.ExtraWeight
        ENDIF
ENDCASE

```

RETURN JamoSortInfo

[<11> Section 3.1.5.2.21](#): The IsJamo algorithm is only used in Windows NT, Windows 2000, Windows XP, Windows Server 2003, Windows Vista, Windows Server 2008, Windows 7, and Windows Server 2008 R2.

[<12> Section 3.1.5.2.22](#): The IsCombiningJamo algorithm is only used in Windows 8 and Windows Server 2012.

[<13> Section 3.1.5.2.23](#): The following IsJamoLeading algorithm is only used in Windows NT, Windows 2000, Windows XP, Windows Server 2003, Windows Vista, Windows Server 2008, Windows 7, and Windows Server 2008 R2.

```
COMMENT IsJamoLeading
COMMENT
COMMENT On Entry:  SourceCharacter - Unicode Character to test
COMMENT
COMMENT On Exit:   Result           - true if SourceCharacter is a
COMMENT                                     leading Jamo
COMMENT
COMMENT NOTE: Only call this if the character is known to be a Jamo
COMMENT          syllable. This function only helps distinguish between
COMMENT          the different types of Jamo, so only call it if
COMMENT          IsJamo() has returned true.
COMMENT

PROCEDURE IsJamoLeading(IN SourceCharacter : Unicode Character,
                      OUT Result: boolean)

IF SourceCharacter is less than NLS_CHAR_FIRST_VOWEL_JAMO THEN
    SET Result to true
ELSE
    SET Result to false
ENDIF

RETURN Result
```

[<14> Section 3.1.5.2.24](#): The IsJamoVowel algorithm is only applicable to Windows 8 and Windows Server 2012.

[<15> Section 3.1.5.2.25](#): The following IsJamoTrailing algorithm is only used in Windows NT, Windows 2000, Windows XP, Windows Server 2003, Windows Vista, Windows Server 2008, Windows 7, and Windows Server 2008 R2.

```
COMMENT IsJamoTrailing
COMMENT
COMMENT On Entry:  SourceCharacter - Unicode Character to test
COMMENT
COMMENT On Exit:   Result           - true if this is a trailing Jamo
COMMENT
COMMENT NOTE: Only call this if the character is known to be a Jamo
COMMENT          syllable. This function only helps distinguish between
COMMENT          the different types of Jamo, so only call it if
COMMENT          IsJamo() has returned true.
COMMENT
```

```
PROCEDURE IsJamoTrailing(IN SourceCharacter : Unicode Character,  
                        OUT Result: boolean)  
  
IF SourceCharacter is greater than  
  or equal to NLS_CHAR_FIRST_VOWEL_JAMO THEN  
  SET Result to true  
ELSE  
  SET Result to false  
ENDIF  
  
RETURN Result
```

7 Change Tracking

No table of changes is available. The document is either new or has had no changes since its last release.

8 Index

A

[Abstract data model - client](#) 23
[Applicability](#) 8

C

[Change tracking](#) 85
Client
 [data model](#) 23
 [higher-layer triggered events](#) 23
 [initialization](#) 23
 [local events](#) 75
 [timer events](#) 75
 [timers](#) 23
Codepage
 supported data files
 [format](#) 18
 [overview](#) 18
 [supported in Windows](#) 10

D

[Data model - client](#) 23
[DBCSRANGE](#) 21

E

[Examples - overview](#) 76

G

[Glossary](#) 6

H

[Higher-layer triggered events - client](#) 23

I

[Implementer - security considerations](#) 77
[Index of security parameters](#) 77
[Informative references](#) 8
[Initialization - client](#) 23
[Introduction](#) 6

L

[Local events - client](#) 75

M

Mapping between UTF-16 strings and legacy codepages
 [GB 18031 codepage](#) 30
 [ISCII codepage](#) 30
 [ISO 2022-based codepages](#) 30
 [using codepage data file](#) 23
 [UTF-7 codepage](#) 30

[UTF-8 codepage](#) 30
[MBTABLE](#) 20
Messages
 [overview](#) 10
 [supported codepage data files](#) 18
 [supported codepage in Windows](#) 10
 [transport](#) 10

N

[Normative references](#) 7

O

[Overview](#) 8

P

[Parameter index - security](#) 77
[Product behavior](#) 78
Pseudocode
 [accessing record in codepage data file](#) 23
 [legacy codepage - mapping codepage string to UTF-16 string](#) 27
 [legacy codepage - mapping UTF-16 string to codepage string](#) 24

R

References
 [informative](#) 8
 [normative](#) 7

S

Security
 [implementer considerations](#) 77
 [overview](#) 77
 [parameter index](#) 77
 [Sorting weight table](#) 34
 [Standards assignments](#) 9

T

[Timer events - client](#) 75
[Timers - client](#) 23
[Tracking changes](#) 85
[Transport](#) 10
[Triggered events - higher-layer - client](#) 23

U

UTF-16 string
 [accessing Windows sorting weight table](#) 32
 [Check3ByteWeightLocale](#) 57
 [CompareSortKey](#) 31
 [converting to upper case using UpperCaseTable](#) 74
 [converting with ToUpperCase](#) 74

[CorrectUnicodeWeight](#) 49
[FindNewJamoState](#) 68
[GetCharacterWeights](#) 50
[GetContractionType](#) 48
[GetExpandedCharacters](#) 52
[GetExpansionWeights](#) 51
[GetJamoComposition](#) 66
[GetJamoStateData](#) 67
[GetPositionSpecialWeight](#) 63
[GetWindowsSortKey_pseudocode](#) 34
[InitKoreanScriptMap](#) 73
[IsCombiningJamo](#) 71
[IsJamo](#) 70
[IsJamoLeading](#) 71
[IsJamoTrailing](#) 73
[IsJamoVowel](#) 72
[MakeUnicodeWeight](#) 50
[MapOldHangulSortKey](#) 63
mapping between legacy codepages and
[mapping between UTF-16 strings and GB 18031 codepage](#) 30
[mapping between UTF-16 strings and ISCII codepage](#) 30
[mapping between UTF-16 strings and ISO 2022-based codepages](#) 30
[mapping between UTF-16 strings and UTF-7 codepage](#) 30
[mapping between UTF-16 strings and UTF-8 codepage](#) 30
[using codepage data file](#) 23
mapping to upper case 74
[pseudocode for accessing record in codepage data file](#) 23
[pseudocode for comparing](#) 30
[pseudocode for mapping legacy codepage to](#) 27
[pseudocode for mapping to legacy codepage](#) 24
[sort keys for comparing](#) 30
[SortkeyContractionHandler](#) 53
[SpecialCaseHandler](#) 58
[TestHungarianCharacterSequences](#) 47
[UpdateJamoSortInfo](#) 69

W

[WCTABLE](#) 19
[Windows sorting weight table](#) 34